

<b>Name:</b> De Omampo, Julius Mark A.	<b>Date Performed:</b> 09/27/24
<b>Course/Section:</b> CPE212 – CPE31S2	<b>Date Submitted:</b> 09/27/24
<b>Instructor:</b> Engr. Robin Valenzuela	<b>Semester and SY:</b> 1 <sup>st</sup> (2024 – 2025)
<b>Activity 5: Consolidating Playbook plays</b>	
<b>1. Objectives:</b> 1.1 Use <b>when</b> command in playbook for different OS distributions 1.2 Apply refactoring techniques in cleaning up the playbook codes	
<b>2. Discussion:</b>  <p>We are going to look at a way that we can differentiate a playbook by a host in terms of which distribution the host is running. It's very common in most Linux shops to run multiple distributions, for example, Ubuntu shop or Debian shop and you need a different distribution for a one off-case or perhaps you want to run plays only on certain distributions.</p> <p>It is a best practice in ansible when you are working in a collaborative environment to use the command git pull. git pull is a Git command used to update the local version of a repository from a remote. By default, git pull does two things. Updates the current local working branch (currently checked out branch) and updates the remote-tracking branches for all other branches. git pull essentially pulls down any changes that may have happened since the last time you worked on the repository.</p> <p><b>Requirement:</b>  In this activity, you will need to create a CentOS VM. Likewise, you need to activate the second adapter to a host-only adapter after the installations. Take note of the IP address of the CentOS VM. Make sure to use the command <b>ssh-copy-id</b> to copy the public key to CentOS. Verify if you can successfully SSH to CentOS VM.</p>	
<b>Task 1: Use when command for different distributions</b>  1. In the local machine, make sure you are in the local repository directory ( <b>CPE212_yourname</b> ). Issue the command git pull. When prompted, enter the correct passphrase or password. Describe what happened when you issue this command. Did something happen? Why?	
<pre>julius-de-omampo@workstation: ~\$ cd CPE212_julius/ julius-de-omampo@workstation: ~/CPE212_julius\$ git pull origin main From github.com:jnado-biscoff/CPE212_julius * branch          main          -&gt; FETCH_HEAD Already up to date. julius-de-omampo@workstation: ~/CPE212_julius\$</pre>	

Issuing this code fetches the files from the GitHub Repository.

2. Edit the inventory file and add the IP address of the Centos VM. Issue the command we used to execute the playbook (the one we used in the last activity): *ansible-playbook --ask-become-pass install\_apache.yml*. After executing this command, you may notice that it did not become successful in the Centos VM. You can see that the Centos VM has failed=1. Only the two remote servers have been changed. The reason is that Centos VM does not support "apt" as the package manager. The default package manager for Centos is "yum."

```
GNU nano 7.2                                inventory.yml *
all:
  hosts:
    server1:
      ansible_host: 192.168.56.104
      ansible_user: julius-de-omampo
    server2:
      ansible_host: 192.168.56.106
      ansible_user: julius-de-omampo
    centos:
      ansible_host: 192.168.56.108
      ansible_user: julius-de-omampo

julius-de-omampo@workstation:~/CPE212_julius$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [server1]
ok: [server2]
ok: [centos]

TASK [update repository index] *****
[WARNING]: Updating cache and auto-installing missing dependency: python3-apt
fatal: [centos]: FAILED! => [{"changed": false, "cmd": "apt-get update", "msg": "[Errno 2] No such file or directory: b'a\npt-get'", "rc": 2, "stderr": "", "stderr_lines": [], "stdout": "", "stdout_lines": []}]
changed: [server1]
changed: [server2]

TASK [install apache2 package] *****
ok: [server2]
ok: [server1]

TASK [add PHP support for apache] *****
ok: [server1]
ok: [server2]

PLAY RECAP *****
centos                : ok=1    changed=0    unreachable=0    failed=1    skipped=0    rescued=0    ignored=0
server1               : ok=4    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0
server2               : ok=4    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0

julius-de-omampo@workstation:~/CPE212_julius$ SSSS
```

3. Edit the *install\_apache.yml* file and insert the lines shown below.

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        when: ansible_distribution == "Ubuntu"
```

Make sure to save the file and exit.

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

If you have a mix of Debian and Ubuntu servers, you can change the configuration of your playbook like this.

```
- name: update repository index
  apt:
    update_cache: yes
    when: ansible_distribution in ["Debian", "Ubuntu"]
```

*Note:* This will work also if you try. Notice the changes are highlighted.

GNU nano 7.2

install\_apache.yml \*

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
      when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
      when: ansible_distribution == "Ubuntu"
```

```
julius-de-onampo@workstation:~/CPE212_julius$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:
```

```
PLAY [all] *****

TASK [Gathering Facts] *****
ok: [server2]
ok: [centos]
ok: [server1]

TASK [update repository index] *****
skipping: [centos]
changed: [server1]
changed: [server2]

TASK [install apache2 package] *****
skipping: [centos]
ok: [server1]
ok: [server2]

TASK [add PHP support for apache] *****
skipping: [centos]
ok: [server1]
ok: [server2]

PLAY RECAP *****
centos                : ok=1    changed=0    unreachable=0    failed=0    skipped=3    rescued=0    ignored=0
server1               : ok=4    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0
server2               : ok=4    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0

julius-de-onampo@workstation:~/CPE212_julius$
```

4. Edit the *install\_apache.yml* file and insert the lines shown below

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        state: latest
        when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        state: latest
        when: ansible_distribution == "Ubuntu"

    - name: update repository index
      dnf:
        update_cache: yes
        when: ansible_distribution == "CentOS"

    - name: install apache2 package
      dnf:
        name: httpd
        state: latest
        when: ansible_distribution == "CentOS"

    - name: add PHP support for apache
      dnf:
        name: php
        state: latest
        when: ansible_distribution == "CentOS"
```

Make sure to save and exit.

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

```

- name: update repository index
  dnf:
    update_cache: yes
  when: ansible_distribution == "CentOS"

- name: install apache2 package
  dnf:
    name: httpd
    state: latest
  when: ansible_distribution == "CentOS"

- name: add PHP support for apache
  dnf:
    name: php
    state: latest
  when: ansible_distribution == "CentOS"

```

```

julius-de-onampo@workstation:~/CPE212_julius$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:

```

```

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [server2]
ok: [server1]
ok: [centos]

TASK [update repository index] *****
skipping: [centos]
changed: [server1]
changed: [server2]

TASK [install apache2 package] *****
skipping: [centos]
ok: [server1]
ok: [server2]

TASK [add PHP support for apache] *****
skipping: [centos]
ok: [server1]
ok: [server2]

TASK [update repository index] *****
skipping: [server1]
skipping: [server2]
ok: [centos]

```

```

TASK [install apache2 package] *****
skipping: [server1]
skipping: [server2]
changed: [centos]


TASK [add PHP support for apache] *****
skipping: [server1]
skipping: [server2]
changed: [centos]

PLAY RECAP *****
centos      : ok=4    changed=2    unreachable=0    failed=0    skipped=3    rescued=0    ignored=0
server1    : ok=4    changed=1    unreachable=0    failed=0    skipped=3    rescued=0    ignored=0
server2    : ok=4    changed=1    unreachable=0    failed=0    skipped=3    rescued=0    ignored=0

julius-de-onampo@workstation:~/CPE212_julius$

```

5. To verify the installations, go to CentOS VM and type its IP address on the browser. Was it successful? The answer is no. It's because the httpd service or the Apache HTTP server in the CentOS is not yet active. Thus, you need to activate it first.



5.1 To activate, go to the CentOS VM terminal and enter the following:

*systemctl status httpd*

```
[julius-de-omampo@localhost ~]$ systemctl status httpd
○ httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; preset: d>
   Drop-In: /usr/lib/systemd/system/httpd.service.d
           └─php-fpm.conf
   Active: inactive (dead)
   Docs: man:httpd.service(8)
lines 1-6/6 (END)
```

The result of this command tells you that the service is inactive.

5.2 Issue the following command to start the service:

*sudo systemctl start httpd*

```
[julius-de-omampo@localhost ~]$ sudo systemctl start httpd
[sudo] password for julius-de-omampo:
```

(When prompted, enter the sudo password)


*sudo firewall-cmd --add-port=80/tcp*

(The result should be a success)

```
[julius-de-omampo@localhost ~]$ sudo firewall-cmd --add-port=80/tcp
success
[julius-de-omampo@localhost ~]$
```



5.3 To verify the service is already running, go to CentOS VM and type its IP address on the browser. Was it successful? (Screenshot the browser)



Yes, it was successful.

## Task 2: Refactoring playbook

This time, we want to make sure that our playbook is efficient and that the codes are easier to read. This will also makes run ansible more quickly if it has to execute fewer tasks to do the same thing.

1. Edit the playbook *install\_apache.yml*. Currently, we have three tasks targeting our Ubuntu machines and 3 tasks targeting our CentOS machine. Right now, we try to consolidate some tasks that are typically the same. For example, we can consolidate two plays that install packages. We can do that by creating a list of installation packages as shown below:



```

---
- hosts: all
  become: true
  tasks:

    - name: update repository index Ubuntu
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        when: ansible_distribution == "Ubuntu"

    - name: update repository index for CentOS
      dnf:
        update_cache: yes
        when: ansible_distribution == "CentOS"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        when: ansible_distribution == "CentOS"

```

Make sure to save the file and exit.

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

Refactoring the playbook and running it was a success.

```

---
- hosts: all
  become: true
  tasks:

    - name: update repository index Ubuntu
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        when: ansible_distribution == "Ubuntu"

    - name: update repository index for CentOS
      dnf:
        update_cache: yes
        when: ansible_distribution == "CentOS"

    - name: install apache2 and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        when: ansible_distribution == "CentOS"

```

```

julius-de-onampo@workstation:~/CPE212_julius$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [server2]
ok: [server1]
ok: [centos]

TASK [update repository index Ubuntu] *****
skipping: [centos]
changed: [server1]
changed: [server2]

TASK [install apache2 and php packages for Ubuntu] *****
skipping: [centos]
ok: [server2]
ok: [server1]

TASK [update repository index for CentOS] *****
skipping: [server1]
skipping: [server2]
ok: [centos]

TASK [install apache2 and php packages for CentOS] *****
skipping: [server1]
skipping: [server2]
ok: [centos]

```

```
PLAY RECAP *****
centos                : ok=3    changed=0    unreachable=0    failed=0    skipped=2    rescued=0    ignored=0
server1              : ok=3    changed=1    unreachable=0    failed=0    skipped=2    rescued=0    ignored=0
server2              : ok=3    changed=1    unreachable=0    failed=0    skipped=2    rescued=0    ignored=0

julius-de-omampo@workstation:~/CPE212_julius$
```

2. Edit the playbook *install\_apache.yml* again. In task 2.1, we consolidated the plays into one play. This time we can actually consolidated everything in just 2 plays. This can be done by removing the update repository play and putting the command *update\_cache: yes* below the command *state: latest*. See below for reference:

```
---
- hosts: all
  become: true
  tasks:

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        update_cache: yes
      when: ansible_distribution == "CentOS"
```

Make sure to save the file and exit.

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

Running the consolidated version of the playbook was also a great success.

```

---
- hosts: all
  become: true
  tasks:

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        update_cache: yes
        when: ansible_distribution == "CentOS"

```

```

julius-de-omampo@workstation:~/CPE212_julius$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [server1]
ok: [server2]
ok: [centos]

TASK [install apache2 and php packages for Ubuntu] *****
skipping: [centos]
ok: [server1]
ok: [server2]

TASK [install apache2 and php packages for CentOS] *****
skipping: [server1]
skipping: [server2]
ok: [centos]

PLAY RECAP *****
centos      : ok=2    changed=0    unreachable=0    failed=0    skipped=1    rescued=0    ignored=0
server1    : ok=2    changed=0    unreachable=0    failed=0    skipped=1    rescued=0    ignored=0
server2    : ok=2    changed=0    unreachable=0    failed=0    skipped=1    rescued=0    ignored=0

julius-de-omampo@workstation:~/CPE212_julius$

```

- Finally, we can consolidate these 2 plays in just 1 play. This can be done by declaring variables that will represent the packages that we want to install. Basically, the `apache_package` and `php_package` are variables. The names are arbitrary, which means we can choose different names. We also take out the line `when: ansible_distribution`. Edit the playbook *install\_apache.yml* again and make sure to follow the below image. Make sure to save the file and exit.

```
---
- hosts: all
  become: true
  tasks:

    - name: install apache and php
      apt:
        name:
          - "{{ apache_package }}"
          - "{{ php_package }}"
        state: latest
        update_cache: yes
```

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

Running the refactored consolidated version of the playbook had a little hiccup, as executing it was not successful.

```
---
- hosts: all
  become: true
  tasks:

    - name: install apache2 and php
      apt:
        name:
          - "{{ apache_package }}"
          - "{{ php_package }}"
        state: latest
        update_cache: yes
```

```

julius-de-omampo@workstation:~/CPE212_julius$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [server1]
ok: [server2]
ok: [centos]

TASK [install apache2 and php] *****
fatal: [server1]: FAILED! => {"msg": "The task includes an option with an undefined variable. The error was: 'apache_package' is undefined. 'apache_package' is undefined\n\nThe error appears to be in '/home/julius-de-omampo/CPE212_julius/install_apache.yml': line 6, column 5, but may\nbe elsewhere in the file depending on the exact syntax problem.\n\nThe offending line appears to be:\n\n- name: install apache2 and php\n  ^ here\n"}
fatal: [server2]: FAILED! => {"msg": "The task includes an option with an undefined variable. The error was: 'apache_package' is undefined. 'apache_package' is undefined\n\nThe error appears to be in '/home/julius-de-omampo/CPE212_julius/install_apache.yml': line 6, column 5, but may\nbe elsewhere in the file depending on the exact syntax problem.\n\nThe offending line appears to be:\n\n- name: install apache2 and php\n  ^ here\n"}
fatal: [centos]: FAILED! => {"msg": "The task includes an option with an undefined variable. The error was: 'apache_package' is undefined. 'apache_package' is undefined\n\nThe error appears to be in '/home/julius-de-omampo/CPE212_julius/install_apache.yml': line 6, column 5, but may\nbe elsewhere in the file depending on the exact syntax problem.\n\nThe offending line appears to be:\n\n- name: install apache2 and php\n  ^ here\n"}

PLAY RECAP *****
centos                : ok=1    changed=0    unreachable=0    failed=1    skipped=0    rescued=0    ignored=0
server1               : ok=1    changed=0    unreachable=0    failed=1    skipped=0    rescued=0    ignored=0
server2               : ok=1    changed=0    unreachable=0    failed=1    skipped=0    rescued=0    ignored=0

julius-de-omampo@workstation:~/CPE212_julius$

```

4. Unfortunately, task 2.3 was not successful. It's because we need to change something in the inventory file so that the variables we declared will be in place. Edit the *inventory* file and follow the below configuration:

```

192.168.56.120 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.121 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.122 apache_package=httpd php_package=php

```

Make sure to save the *inventory* file and exit.

**Finally**, we still have one more thing to change in our *install\_apache.yml* file. In task 2.3, you may notice that the package is assign as *apt*, which will not run in CentOS. Replace the *apt* with *package*. Package is a module in ansible that is generic, which is going to use whatever package manager the underlying host or the target server uses. For Ubuntu it will automatically use *apt*, and for CentOS it will automatically use *dnf*. Make sure to save the file and exit. For more details about the ansible package, you may refer to this documentation: [ansible.builtin.package – Generic OS package manager — Ansible Documentation](https://docs.ansible.com/ansible/latest/builtin/package_module.html)

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

The playbook has been consolidated regardless of the OS type, we have managed to shorten the code and make it more efficient.

```
GNU nano 7.2                                inventory.yml *
```

```
all:
  hosts:
    server1:
      ansible_host: 192.168.56.104
      ansible_user: julius-de-omampo
      apache_package: apache2
      php_package: libapache2-mod-php
    server2:
      ansible_host: 192.168.56.106
      ansible_user: julius-de-omampo
      apache_package: apache2
      php_package: libapache2-mod-php
    centos:
      ansible_host: 192.168.56.108
      ansible_user: julius-de-omampo
      apache_package: httpd
      php_package: php
```

```
julius-de-omampo@workstation: ~/CPE212_julius
GNU nano 7.2                                install_apache.yml
```

```
---
- hosts: all
  become: true
  tasks:

  - name: install apache2 and php
    package:
      name:
        - "{{ apache_package }}"
        - "{{ php_package }}"
      state: latest
      update_cache: yes
```

```
julius-de-omampo@workstation:~/CPE212_julius$ ansible-playbook --ask-become-pass install_apache.yml
BECOME password:

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [server1]
ok: [server2]
ok: [centos]

TASK [install apache2 and php] *****
ok: [server2]
ok: [server1]
ok: [centos]

PLAY RECAP *****
centos                : ok=2    changed=0    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0
server1               : ok=2    changed=0    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0
server2               : ok=2    changed=0    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0

julius-de-omampo@workstation:~/CPE212_julius$
```



## Server Installations:

```
julius-de-omampo@server1:~$ php --version
PHP 8.3.6 (cli) (built: Jun 13 2024 15:23:20) (NTS)
Copyright (c) The PHP Group
Zend Engine v4.3.6, Copyright (c) Zend Technologies
    with Zend OPcache v8.3.6, Copyright (c), by Zend Technologies
julius-de-omampo@server1:~$ apache2 -v
Server version: Apache/2.4.58 (Ubuntu)
Server built:   2024-07-17T18:55:23
julius-de-omampo@server1:~$
```

*server1*

```
julius-de-omampo@server2:~$ php --version
PHP 8.3.6 (cli) (built: Jun 13 2024 15:23:20) (NTS)
Copyright (c) The PHP Group
Zend Engine v4.3.6, Copyright (c) Zend Technologies
    with Zend OPcache v8.3.6, Copyright (c), by Zend Technologies
julius-de-omampo@server2:~$ apache2 -v
Server version: Apache/2.4.58 (Ubuntu)
Server built:   2024-07-17T18:55:23
julius-de-omampo@server2:~$
```

*server2*

```
[julius-de-omampo@localhost ~]$ php -version
PHP 8.0.30 (cli) (built: Aug  3 2023 17:13:08) ( NTS gcc x86_64 )
Copyright (c) The PHP Group
Zend Engine v4.0.30, Copyright (c) Zend Technologies
    with Zend OPcache v8.0.30, Copyright (c), by Zend Technologies
[julius-de-omampo@localhost ~]$ httpd -v
Server version: Apache/2.4.62 (CentOS Stream)
Server built:   Aug  3 2024 00:00:00
[julius-de-omampo@localhost ~]$
```

*server3 (centOS)*

## GitHub Repository:

[https://github.com/jmado-biscoff/CPE212\\_julius.git](https://github.com/jmado-biscoff/CPE212_julius.git)

## Supplementary Activity:

1. Create a playbook that could do the previous tasks in Red Hat OS.

## Reflections:

Answer the following:

1. Why do you think refactoring of playbook codes is important?

Refactoring ansible playbook is important for improving readability, reducing redundancy, and promoting modularity. It simplifies maintenance by consolidating tasks and enhancing code reusability across such projects. It also improves performance by eliminating unnecessary executions and prepares your playbooks for scalability as your infrastructure grows. Moreover, it facilitates easier debugging and testing, ensuring your playbooks remain efficient and maintainable over time.

## 2. When do we use the “when” command in playbook?

The when command in playbooks is used to conditionally execute tasks based on the evaluation of expressions, such as variables, facts, or system states. It allows tasks to run only when specific conditions are met, such as checking the operating system type, variable values, or host characteristics. This adds flexibility, enabling you to skip tasks or limit execution to certain hosts or configurations, making your playbooks more efficient and adaptable to different environments.