

1. Semantic Tag

Semantic Tag are HTML element that clearly describe the meaning and purpose of enclosed content to both the browser and the developer.

<header>
<nav>
<main>
<section>
<article>
<footer>

2. Block Level

A Block level element always start on a new line and occupies the full available width.

<h1>
<p>
<div>
<section>

3. Inline Elements

Inline elements do not start on a new line. They occupy only the required width. They stay in the same line used inside text content.

<a>		<table>
	<small>	
	<mark>	
	<sup>	
	<sub>	

4. Anchor Tag

Anchor Tag is an HTML tag used to create hyperlinks that connect one webpage to another webpage, a specific section of the same page, an email address or any external website.

Eg

href - Specifies the destination URL

target - open the link in a new tab or same tab

title - Shows a tooltip when the mouse hovers over the link

Eg: Syntax

```
<a href="https://www.google.com">Google</a>
```

5. Image Tag

Image Tag is used to display image on a webpage. It is empty (Self closing) tag which means it does not require a closing tag.

Eg: Syntax

```

```

src - Specifies the path (location) of the image

alt - Display alternative text if the image cannot be loaded

width - sets width of the image

height - sets height of the image

6. Ordered List

Ordered List is an HTML element used to display a list of items in a numbered or sequential order. Each item in the list is represented using the tag.

Eg:

```
<ol>
```

```
<li> HTML </li>
```

```
<li> Java </li>
```

OP

1. HTML

2. Java

7. Unordered List

Unordered List is an HTML element used to display a list item with bullet points. Each item in the list is represented using the tag.

Eg:

```
<ul>
```

```
<li> HTML </li>
```

```
<li> CSS </li>
```

```
<li> JS </li>
```

OP

• HTML

• CSS

• JS