ALS SDO San Juan Database Tables

This document is a consolidated copy of the table structures defined by the Laravel migrations in this project. It describes the schema only; it does not contain learner, account, or other database row data. Types use Laravel migration names (for example, `string` means a variable-length string and `foreignId` means an unsigned big integer).

Main relationships

- `users` has one `user_profiles` row and can have many enrollments, documents, module progress rows, and game attempts.
- `enrollments` reference a learner (`users`), a community learning center, and optionally an assigned teacher (`users`).
- `learner_documents` reference a learner, optionally an enrollment, and optionally the user who reviewed the document.
- `modules` reference a learning strand and the user who uploaded the module.
- `module_downloads_and_progress` connects a user to a module and stores that learner's progress for that module.
- `module_game_attempts` record individual user attempts associated with a module.
- `personal_access_tokens` use a polymorphic `tokenable_type` / `tokenable_id` relation.

Application tables

`users`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`lrn`	String(12), nullable, unique
`username`	String, unique
`email`	String, nullable, unique
`email_verified_at`	Timestamp, nullable
`password`	String
`role`	Enum: `super_admin`, `admin`, `mobile_teacher`, `learner`; default `learner`
`status`	Enum: `active`, `inactive`; default `active`
`last_login_at`	Timestamp, nullable
`remember_token`	Remember token, nullable
`created_at`, `updated_at`	Timestamps
`deleted_at`	Timestamp, nullable (soft delete)

Additional indexes: (`role`, `status`), `lrn`, and `username`.

`user_profiles`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`user_id`	Foreign key to `users.id`, unique, cascade on delete
`first_name`	String
`middle_name`	String, nullable
`last_name`	String
`name_extension`	String(10), nullable
`birthdate`	Date
`gender`	Enum: `male`, `female`, `other`; default `male`
`civil_status`	Enum: `single`, `married`, `widowed`, `separated`, `solo_parent`, `other`; default `single`
`religion`	String, nullable
`contact_number`	String(25)
`facebook_name`	String, nullable
`street_address`	String
`barangay`	String
`city`	String; default `San Juan City`
`province`	String; default `Metro Manila`
`highest_education_attained`	String
`dropout_reason`	String, nullable
`has_attended_als`	Boolean; default `false`
`previous_als_program`	String, nullable
`previous_als_year`	String(20), nullable
`previous_als_completed`	Boolean, nullable
`previous_als_incomplete_reason`	String, nullable
`mother_tongue`	String; default `Tagalog / Filipino`
`is_ip`	Boolean; default `false`
`ip_community_name`	String, nullable
`is_pwd`	Boolean; default `false`
`pwd_disability_type`	String, nullable
`is_4ps_beneficiary`	Boolean; default `false`
`father_name`	String, nullable
`mother_name`	String, nullable
`guardian_name`	String, nullable
`guardian_relationship`	String, nullable
`emergency_contact_name`	String, nullable
`emergency_contact_number`	String(25), nullable
`profile_photo_path`	String, nullable
`created_at`, `updated_at`	Timestamps
`deleted_at`	Timestamp, nullable (soft delete)

Additional indexes: `barangay` and (`last_name`, `first_name`).

`community_learning_centers`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`clc_name`	String
`clc_code`	String(30), unique
`clc_type`	String; default `Community Center`
`barangay`	String
`physical_location_notes`	Text, nullable
`assigned_teacher_id`	Foreign key to `users.id`, nullable, set null on delete
`status`	Enum: `active`, `inactive`; default `active`
`created_at`, `updated_at`	Timestamps
`deleted_at`	Timestamp, nullable (soft delete)

Additional indexes: `barangay`, `assigned_teacher_id`, and `status`.

`enrollments`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`user_id`	Foreign key to `users.id`, cascade on delete
`calendar_year`	String(10); default `2026`
`program_track`	Enum: `BLP`, `A&E_Elementary`, `A&E_Junior_High`
`clc_id`	Foreign key to `community_learning_centers.id`, cascade on delete
`assigned_teacher_id`	Foreign key to `users.id`, nullable, set null on delete
`enrollment_status`	Enum: `pending`, `under_review`, `enrolled`, `needs_correction`, `rejected`, `withdrawn`, `completed`; default `pending`
`delivery_mode`	Enum: `modular_offline`, `modular_print`, `face_to_face`, `blended`; default `modular_offline`
`schedule_preference`	Enum: `weekend`, `weekday_am`, `weekday_pm`, `flexible`; default `flexible`
`remarks`	Text, nullable
`enrolled_at`	Timestamp, nullable
`completed_at`	Timestamp, nullable
`created_at`, `updated_at`	Timestamps
`deleted_at`	Timestamp, nullable (soft delete)

Additional indexes: (`user_id`, `calendar_year`), (`clc_id`, `enrollment_status`), `enrollment_status`, `calendar_year`, and `program_track`.

`learner_documents`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`user_id`	Foreign key to `users.id`, cascade on delete
`enrollment_id`	Foreign key to `enrollments.id`, nullable, cascade on delete
`document_type`	Enum: `psa_birth_cert`, `barangay_clearance`, `form_137_sf10`, `photo_id`, `portfolio_document`
`file_path`	String
`file_name`	String
`file_size`	Unsigned big integer (bytes)
`mime_type`	String(100)
`verification_status`	Enum: `pending`, `verified`, `rejected`; default `pending`
`verification_notes`	Text, nullable
`reviewed_by`	Foreign key to `users.id`, nullable, set null on delete
`reviewed_at`	Timestamp, nullable
`created_at`, `updated_at`	Timestamps
`deleted_at`	Timestamp, nullable (soft delete)

Additional indexes: (`user_id`, `document_type`), `verification_status`, and `enrollment_id`.

`learning_strands`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`code`	String(20), unique
`name`	String
`description`	Text, nullable
`color_code`	String(30); default `#2563eb`
`icon_name`	String(50); default `book-open`
`order_seq`	Unsigned integer; default `1`
`created_at`, `updated_at`	Timestamps

Additional indexes: `code` and `order_seq`.

`modules`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`strand_id`	Foreign key to `learning_strands.id`, cascade on delete
`level`	Enum: `BLP`, `Elementary`, `Junior_High`
`sub_level`	String(50), nullable
`language`	String(20); default `English`
`module_number`	String(50)
`title`	String
`description`	Text, nullable
`pdf_file_path`	String
`pdf_file_size`	Unsigned big integer; default `0`
`version`	String(20); default `1.0`
`is_published`	Boolean; default `true`
`uploaded_by`	Foreign key to `users.id`, cascade on delete
`created_at`, `updated_at`	Timestamps
`deleted_at`	Timestamp, nullable (soft delete)

Additional indexes: (`strand_id`, `level`), (`level`, `is_published`), `is_published`, (`level`, `sub_level`, `language`), `sub_level`, and `language`.

`module_downloads_and_progress`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`user_id`	Foreign key to `users.id`, cascade on delete
`module_id`	Foreign key to `modules.id`, cascade on delete
`downloaded_at`	Timestamp, nullable
`last_opened_at`	Timestamp, nullable
`completion_status`	Enum: `downloaded`, `in_progress`, `completed`; default `downloaded`
`device_identifier`	String, nullable
`last_page_read`	Unsigned integer; default `1`
`total_pages`	Unsigned integer, nullable
`synced_at`	Timestamp, nullable
`created_at`, `updated_at`	Timestamps

Unique constraint: (`user_id`, `module_id`). Additional indexes: `completion_status` and `synced_at`.

`module_game_attempts`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`attempt_uuid`	UUID
`user_id`	Foreign key to `users.id`, cascade on delete
`module_id`	Foreign key to `modules.id`, cascade on delete
`game_type`	String(50); default `memory_match`
`score`	Unsigned small integer
`max_score`	Unsigned small integer
`moves`	Unsigned small integer
`elapsed_seconds`	Unsigned integer
`device_identifier`	String(150), nullable
`attempted_at`	Timestamp
`created_at`, `updated_at`	Timestamps

Unique constraint: (`user_id`, `attempt_uuid`). Additional indexes: (`user_id`, `attempted_at`) and (`module_id`, `attempted_at`).

`hero_banners`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`title`	String, nullable
`subtitle`	String, nullable
`image_path`	String
`position_x`	Integer; default `50`
`position_y`	Integer; default `50`
`zoom`	Unsigned small integer; default `100`
`button_text`	String, nullable; default `Take A Tour`
`button_url`	String, nullable; default `/register`
`order_seq`	Integer; default `0`
`is_active`	Boolean; default `true`
`created_at`, `updated_at`	Timestamps

Laravel support tables

`password_reset_tokens`

Column	Type / constraints
`email`	String, primary key
`token`	String
`created_at`	Timestamp, nullable

sessions

Column	Type / constraints
id	String, primary key
user_id	Foreign ID, nullable, indexed
ip_address	String(45), nullable
user_agent	Text, nullable
payload	Long text
last_activity	Integer, indexed

cache

Column	Type / constraints
key	String, primary key
value	Medium text
expiration	Integer, indexed

cache_locks

Column	Type / constraints
key	String, primary key
owner	String
expiration	Integer, indexed

jobs

Column	Type / constraints
id	Big integer, primary key, auto-increment
queue	String, indexed
payload	Long text
attempts	Unsigned tiny integer
reserved_at	Unsigned integer, nullable
available_at	Unsigned integer
created_at	Unsigned integer

job_batches

Column	Type / constraints
id	String, primary key
name	String
total_jobs	Integer
pending_jobs	Integer
failed_jobs	Integer
failed_job_ids	Long text
options	Medium text, nullable
cancelled_at	Integer, nullable
created_at	Integer
finished_at	Integer, nullable

`failed_jobs`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`uuid`	String, unique
`connection`	Text
`queue`	Text
`payload`	Long text
`exception`	Long text
`failed_at`	Timestamp; default current timestamp

`personal_access_tokens`

Column	Type / constraints
`id`	Big integer, primary key, auto-increment
`tokenable_type`	String (polymorphic relation)
`tokenable_id`	Unsigned big integer (polymorphic relation)
`name`	Text
`token`	String(64), unique
`abilities`	Text, nullable
`last_used_at`	Timestamp, nullable
`expires_at`	Timestamp, nullable, indexed
`created_at`, `updated_at`	Timestamps