RentaMovil: Vehicle Rental Platform

INSTALLATION MANUAL

Version 2.0

Nicole Dayana Ramirez

Thiago Fabian Rojas

David Santiago Erez

SENA – Servicio Nacional de Aprendizaje

Technologist in Software Analysis and Development Program

Instructor: Karol Daniela Correa

October 2026

Version control

Version	Date	Change description	Responsible
1.0	09/07/2026	Initial creation of the installation manual.	Development team
2.0	07/10/2026	Update to match the current architecture: SQL Server in Docker, Liquibase migrations per schema, RS256 JWT keys, the iam, fleet-maintenance and booking-reservation microservices, API Gateway, web frontend with API mock, mobile app, first Super Admin, verification and common errors.	Development team

Table of contents

1. Introduction..... 5

1.1 Conventions..... 5

2. Objective..... 5

2.1 Scope..... 5

3. Minimum hardware requirements..... 6

4. Required software..... 7

5. Obtaining the project..... 8

5.1 Branches to use..... 8

6. Installing dependencies..... 9

7. Environment variable configuration..... 10

7.1 Passwords that must match..... 10

7.2 Database repositories..... 10

7.3 JWT keys (RS256)..... 10

7.4 Microservices and gateway..... 11

7.5 Web frontend..... 12

7.6 Mobile app..... 12

8. Creating and importing the database..... 13

9. Running the backend..... 14

9.1 With Docker..... 14

9.2 With Maven (without Docker)..... 14

10. Running the frontend....15

10.1 Web frontend in development mode....15

10.2 Web frontend with Docker....15

10.3 Mobile app....15

11. System access....16

12. Test user....17

12.1 Test customer....17

12.2 First Super Admin (once per environment)....17

13. Installation verification....18

14. Common errors and solutions....19

15. Known limitations of the installed version....21

16. Glossary....22

17. Annexes....23

Annex A. Installation order summary....23

Annex B. Operation commands....23

Annex C. Verification screenshots....24

1. Introduction

This manual explains how to prepare a machine, obtain the code, configure and start all RentaMovil components in a local development or testing environment, and how to verify that the installation is correct.

RentaMovil is made up of several repositories that are installed separately and communicate over a Docker network called rentamovil: a SQL Server (Microsoft, n.d.) database, three migration repositories, three Java microservices, an API Gateway, the web frontend with its API mock, and the mobile app. That is why installation order matters, and it is indicated in each step.

1.1 Conventions

- Commands are shown in grey blocks and are typed in a bash terminal. On Windows, Git Bash is recommended (it includes OpenSSL); Docker and Maven commands work the same in PowerShell.
- Passwords and keys are shown as <value> or ********: this manual never publishes real credentials. Each team must define its own.
- When a command must be run inside a folder, the block starts with the corresponding cd.

2. Objective

Enable another person to install and get RentaMovil running by following clear, complete and verifiable instructions, from a blank machine to being able to sign in to the web application with a test user and a Super Admin.

2.1 Scope

It covers local installation (development or testing machine) with Docker. It does not cover deployment on a production server with a domain and HTTPS, nor publishing the mobile app in the stores: this is an academic project with no production server or domain of its own, so that deployment is outside this manual's scope. Using the system is described in the user and administrator manuals, and its internal construction in the technical manual.

3. Minimum hardware requirements

Table 1

Hardware requirements

Resource	Minimum	Recommended
Operating system	64-bit Windows 10/11 with WSL 2, Ubuntu 22.04 or macOS 13	Windows 11 with WSL 2 or Ubuntu 22.04 / 24.04
Processor	64-bit, 4 cores (x86-64)	6 cores or more
RAM memory	8 GB (SQL Server needs at least 2 GB for its container)	16 GB
Disk space	15 GB free (Docker images, Maven and npm dependencies, database)	25 GB free on an SSD
Network	Internet to download images and dependencies	Stable broadband
Browser	An updated Google Chrome, Microsoft Edge or Mozilla Firefox	Google Chrome
Mobile device (optional)	Android 10+ or iOS 16+ with the Expo Go app	On the same Wi-Fi network as the machine

The SQL Server 2022 image is for x86-64 processors. On Mac machines with an Apple Silicon processor it runs through emulation (Rosetta) and is slower.

4. Required software

Table 2

Required software

Tool	Version	Use	Verify with
Git (Git, n.d.)	2.40 or later	Clone the repositories. On Windows it includes Git Bash and OpenSSL.	git --version
Docker Desktop (Docker Inc., n.d.) (or Docker Engine)	24.0 or later, with Docker Compose 2.20+	SQL Server, migrations and the service containers.	docker --version / docker compose version
Java JDK (Oracle Corporation, n.d.)	21 (Eclipse Temurin recommended)	Compile and run the microservices outside Docker.	java -version
Apache Maven (Apache Software Foundation, n.d.)	3.9 or later	Dependencies, tests, running and Liquibase migrations (Liquibase, n.d.).	mvn -version
Node.js (OpenJS Foundation, n.d.) + npm	Node 22 LTS and npm 10 or later	Web frontend, API mock and mobile app.	node -v / npm -v
OpenSSL (OpenSSL Software Foundation, n.d.)	Included in Git Bash, Linux and macOS	Generate the RS256 JWT key pair.	openssl version
Code editor	Visual Studio Code or IntelliJ IDEA	Edit .env files and review the code.	—
Database client (optional)	SQL Server Management Studio or Azure Data Studio	Query the database and create the first Super Admin.	—
Postman (optional)	Current	Test the endpoints.	—
Expo Go (Expo, n.d.) (optional)	Current, on the phone	Run the mobile app.	—

If Docker is going to be used for the entire backend, Java and Maven are not mandatory: the images compile the code inside the container. They are required to run the services and migrations directly on the machine.

5. Obtaining the project

Create a working folder and clone all the repositories into it, side by side:

```
mkdir rentamovil && cd rentamovil
git clone https://github.com/RentaMovil/rtm-iam-db.git
git clone https://github.com/RentaMovil/rtm-fleet-maintenance-db.git
git clone https://github.com/RentaMovil/rtm-booking-db.git
git clone https://github.com/RentaMovil/rtm-iam.git
git clone https://github.com/RentaMovil/rtm-fleet-maintenance.git
git clone https://github.com/RentaMovil/rtm-booking-reservation.git
git clone https://github.com/RentaMovil/rtm-api-gateway.git
git clone https://github.com/RentaMovil/RentaMovil.git
```

Expected folder result:

```
rentamovil/
├── rtm-iam-db/ ← SQL Server + iam schema (installed first)
├── rtm-fleet-maintenance-db/ ← fleet schema
├── rtm-booking-db/ ← booking schema
├── rtm-iam/ ← identity service (:3001)
├── rtm-fleet-maintenance/ ← fleet service (:3002)
├── rtm-booking-reservation/ ← booking service (:3003)
├── rtm-api-gateway/ ← entry point (:8080)
└── RentaMovil/ ← web/Front-end and app_mobile/Frontend
```

5.1 Branches to use

The documented version corresponds to the following branches. Switch to each one with git checkout <branch> inside its folder. Once these changes are merged into develop, it is enough to use develop everywhere.

Table 3

Branch of each repository

Repository	Branch	Reason
rtm-iam-db, rtm-booking-db, rtm-fleet-maintenance-db	develop	Current schemas and reference data (in main, fleet-db is empty).
rtm-iam	feat/ConectBooking	It includes the personId claim needed by booking-reservation.
rtm-fleet-maintenance	develop	The service code is in develop (main only has the initial commit).
rtm-booking-reservation	develop	Version integrated with the frontend.
rtm-api-gateway	feat/booking-routes	It includes the booking-reservation routes.
RentaMovil	develop	Current web frontend and mobile app.

6. Installing dependencies

With Docker, the dependencies of the Java services are downloaded automatically when the images are built (step 9). To run on the machine without Docker, or for the frontend, install them as follows:

Table 4

Dependency installation commands

Component	Folder	Command
Database repositories	rtm-*-db	mvn -q dependency:resolve (optional; Liquibase does it when running)
Microservices and gateway	rtm-iam, rtm-fleet-maintenance, rtm-booking-reservation, rtm-api-gateway	mvn install -DskipTests
Web frontend and API mock	RentaMovil/web/Front-end	npm install
Mobile app	RentaMovil/app_mobile/Frontend	npm install

The first Maven and npm download may take several minutes; later ones use the cache.

7. Environment variable configuration

Each repository includes example files (.env.example and, in the database repositories, liquibase.properties.example). They are copied once and filled in. The .env and liquibase.properties files are never uploaded to the repository.

7.1 Passwords that must match

Define these four passwords first and use them consistently. They must comply with the SQL Server policy: 8 or more characters with uppercase, lowercase, number and symbol.

Table 5

Passwords shared across repositories

Password	Where it is written
SQL Server administrator (sa)	MSSQL_SA_PASSWORD in the .env of rtm-iam-db, rtm-fleet-maintenance-db and rtm-booking-db; password in each liquibase.properties.
iam_app user	IAM_APP_PASSWORD in rtm-iam-db/.env; parameter.iamAppPassword in rtm-iam-db/liquibase.properties; DATABASE_PASSWORD in rtm-iam/.env.
fleet_app user	FLEET_APP_PASSWORD in rtm-fleet-maintenance-db/.env; parameter.fleetAppPassword in its liquibase.properties; DATABASE_PASSWORD in rtm-fleet-maintenance/.env.
booking_app user	BOOKING_APP_PASSWORD in rtm-booking-db/.env; parameter.bookingAppPassword in its liquibase.properties; DATABASE_PASSWORD in rtm-booking-reservation/.env.

7.2 Database repositories

```
cd rtm-iam-db

cp .env.example .env

cp liquibase.properties.example liquibase.properties

# repeat in rtm-fleet-maintenance-db and rtm-booking-db
```

```
# rtm-iam-db/.env
MSSQL_SA_PASSWORD=********
MSSQL_PORT=1433
MSSQL_DATABASE=rentamovil
IAM_APP_PASSWORD=********


# rtm-iam-db/liquibase.properties
url=jdbc:sqlserver://
localhost:1433;databaseName=rentamovil;encrypt=true;trustServerCertificate=true
username=sa
password=********
parameter.iamAppPassword=********
```

7.3 JWT keys (RS256)

The iam service signs the tokens with a private key; the others verify them with the public key. Generate a pair for your environment from Git Bash:

```
openssl genpkey -algorithm RSA -pkeyopt rsa_keygen_bits:2048 -out priv.pem
openssl pkey -in priv.pem -pubout -out pub.pem
sed '/-----/d' priv.pem | tr -d '\r\n' # APP_IAM_JWT_PRIVATE_KEY value
sed '/-----/d' pub.pem | tr -d '\r\n' # APP_IAM_JWT_PUBLIC_KEY value
rm priv.pem pub.pem # do not leave the keys on disk
```

Each value is copied on a single line, without the BEGIN/END lines. The public key is used in rtm-iam (APP_IAM_JWT_PUBLIC_KEY) and in rtm-booking-reservation (APP_BOOKING_RESERVATION_JWT_PUBLIC_KEY). iam does not start if the keys are missing, are shorter than 2048 bits or do not form a pair.

7.4 Microservices and gateway

```
cd rtm-iam && cp .env.example .env
```

```
# repeat in rtm-fleet-maintenance, rtm-booking-reservation and rtm-api-gateway
```

Table 6

Main variables per service

File	Variables to fill in	Local value
rtm-iam/.env	DATABASE_URL, DATABASE_USERNAME, DATABASE_PASSWORD, APP_IAM_PORT, APP_IAM_JWT_PRIVATE_KEY, APP_IAM_JWT_PUBLIC_KEY, APP_IAM_JWT_EXPIRY, APP_IAM_REFRESH_TOKEN_EXPIRY, APP_IAM_BCRYPT_ROUNDS	iam_app user; port 3001; keys from step 7.3; 1800, 604800 and 12 by default.
rtm-fleet-maintenance/.env	DATABASE_URL, DATABASE_USERNAME, DATABASE_PASSWORD, APP_FLEET_MAINTENANCE_PORT, IAM_URL, BOOKING_URL, BOOKING_TIMEOUT	fleet_app user; port 3002; http://localhost:3001 and http://localhost:3003.
rtm-booking-reservation/.env	DATABASE_URL, DATABASE_USERNAME, DATABASE_PASSWORD, APP_BOOKING_RESERVATION_PORT, APP_BOOKING_RESERVATION_JWT_PUBLIC_KEY, APP_BOOKING_RESERVATION_PAYMENT_WINDOW_HOURS	booking_app user; port 3003; iam public key; 24 hours.
rtm-api-gateway/.env	GATEWAY_PORT, IAM_URL, FLEET_URL, BOOKING_URL, PAYMENT_URL, TELEMETRY_URL, CORS_ALLOWED_ORIGINS, RATE_LIMIT_*	Port 8080; the values in .env.example work for local.

The local database URL is jdbc:sqlserver://localhost:1433;databaseName=rentamovil;encrypt=true;trustServerCertificate=true. Inside Docker, each docker-compose.yml changes it automatically to use the container name (sqlserver).

7.5 Web frontend

The RentaMovil/web/Front-end/.env file already contains the local values and has no secrets (everything it holds ends up in the browser):

```
VITE_API_URL=/api # Vite proxy to the gateway (localhost:8080)
VITE_MOCK_API_URL=/mock # Vite proxy to the mock (localhost:3100)
VITE_CLOUDINARY_CLOUD_NAME=<Cloudinary cloud name>
VITE_CLOUDINARY_UPLOAD_PRESET=<Cloudinary unsigned preset>
```

7.6 Mobile app

```
cd RentaMovil/app_mobile/Frontend && cp .env.example .env
# empty EXPO_PUBLIC_API_URL = per-platform value; on a physical phone: http://<machine-IP>:<port>
```

8. Creating and importing the database

The rentamovil database is created in a SQL Server 2022 container. The tables, the reference data (roles, permissions, categories, brands, models and maintenance types) and the users of each service are created with Liquibase migrations, in this mandatory order: rtm-iam-db → rtm-fleet-maintenance-db → rtm-booking-db.

8.1 Create the shared network (once per machine)

```
docker network create rentamovil
```

8.2 SQL Server, rentamovil database and iam schema

```
cd rtm-iam-db
docker compose up -d
docker compose ps -a
```

You should see rentamovil-sqlserver in Up (healthy) status, and the sqlserver-init and migrations containers in Exited (0): the first one created the database and the second one applied the iam migrations.

8.3 fleet schema

```
cd ../rtm-fleet-maintenance-db
docker compose up --build
```

The migrations container ends in Exited (0). Alternative without Docker: mvn liquibase:update.

8.4 booking schema

```
cd ../rtm-booking-db
docker compose up --build
```

Alternative without Docker: mvn liquibase:update.

8.5 Check the migrations

From each database repository:

```
mvn liquibase:status # must report no pending changesets
```

When using parameters, the Maven plugin may print a NoSuchFieldException about parameter.*AppPassword. It is harmless; what matters is the final BUILD SUCCESS.

Each schema stores its history in its own table: dbo.DATABASECHANGELOG_IAM, dbo.DATABASECHANGELOG_FLEET and dbo.DATABASECHANGELOG_BOOKING.

9. Running the backend

Start the services in this order: rtm-iam → rtm-fleet-maintenance → rtm-booking-reservation → rtm-api-gateway. You can do this with Docker (recommended) or directly with Maven; do not use both methods at once for the same service, because they use the same port.

9.1 With Docker

```
cd rtm-iam && docker compose up -d --build
cd ../rtm-fleet-maintenance && docker compose up -d --build
cd ../rtm-booking-reservation && docker compose up -d --build
cd ../rtm-api-gateway && docker compose up -d --build
docker ps # rentamovil-iam, -fleet-maintenance, -booking-reservation, -api-gateway: Up
```

The first build takes several minutes because it downloads the dependencies inside the image; later ones are fast.

9.2 With Maven (without Docker)

Open one terminal per service and, inside each folder, run:

```
mvn spring-boot:run
```

Table 7

Backend services

Service	Port	Container	Check
rtm-iam	3001	rentamovil-iam	curl http://localhost:3001/health
rtm-fleet-maintenance	3002	rentamovil-fleet-maintenance	curl http://localhost:3002/health
rtm-booking-reservation	3003	rentamovil-booking-reservation	curl http://localhost:3003/health

Service	Port	Container	Check
rtm-api-gateway	8080	rentamovil-api-gateway	curl http://localhost:8080/health

Each service responds {"status":"ok","db":"connected",...}. The gateway responds with the status of each service; payment-billing and telemetry-gps appear as down because they do not exist yet, and that is normal.

10. Running the frontend

10.1 Web frontend in development mode

Open two terminals in RentaMovil/web/Front-end:

```
# Terminal 1: API mock (payments, bank accounts and GPS) on port 3100
npm run mock-api


# Terminal 2: web application on port 5173
npm run dev
```

10.2 Web frontend with Docker

With the backend already up on the rentamovil network:

```
cd RentaMovil/web/Front-end
docker compose up -d --build # web at http://localhost:4173 and the mock on the network
```

10.3 Mobile app

```
cd RentaMovil/app_mobile/Frontend
npx expo start
```

Scan the QR code with Expo Go (Android) or with the camera (iOS), or press a for the Android emulator and w for the web version.

Current limitation: the mobile app is not yet connected to the API Gateway. It uses the old mock and local data, so signing in against the new backend does not work from the app (see section 15).

11. System access

Table 8

Access addresses

Component	Address	Note
Web application (development)	http://localhost:5173	Sign-in screen.
Web application (Docker)	http://localhost:4173	Same application served by the rentamovil-web container.
API Gateway	http://localhost:8080	API entry point; /health shows the status of the services.
API mock	http://localhost:3100	Payments, bank accounts and GPS.
SQL Server	localhost,1433	sa user with the password defined in step 7.1 (only for database administration).

12. Test user

The migrations deliberately do not create users: that way there are no passwords or hashes in the repositories. Users are created as follows:

12.1 Test customer

1. Open http://localhost:5173 and click Do you have an account? Register.
2. Register a test user, for example: First name Test, Last name Customer, username test.customer, email test.customer@rentamovil.test and a password that complies with the policy (8 characters, uppercase and number).
3. When you click Create account, the session opens with the Customer role.

It can also be created through the API:

```
curl -X POST http://localhost:8080/auth/register -H "Content-Type: application/json" \
-d '{"firstName":"Prueba","lastName":"Cliente","email":"cliente.prueba@rentamovil.test",
"username":"cliente.prueba","password":"<contraseña>"}'
```

12.2 First Super Admin (once per environment)

Public registration always creates customers, and only a Super Admin can assign roles. In a new database, the first one is assigned directly in the database:

1. Register in the web app the account that will be the administrator (for example, username test.admin).
2. Connect to SQL Server as sa (SQL Server Management Studio, Azure Data Studio or sqlcmd) and run:

```
UPDATE iam.[user]
SET role_id = (SELECT role_id FROM iam.role WHERE name = 'SUPER_ADMIN')
WHERE username = 'admin.prueba';
```

1. Log out and sign back in with that account: the system takes you to the administration panel.
2. From Administration > Super Administration > Users and roles, assign the other roles.

Use test accounts and passwords only in local environments. Never reuse these credentials in production.

13. Installation verification

Table 9

Checklist

Verification	How to check it	Expected result
Network and database	docker ps -a	rentamovil-sqlserver Up (healthy); sqlserver-init and migrations Exited (0).
Migrations	mvn liquibase:status in each *-db repository	No pending changesets.
Services	curl http://localhost:300X/health	status ok and db connected on 3001, 3002 and 3003.
Gateway	curl http://localhost:8080/health	iam, fleet-maintenance and booking-reservation in ok.
JWT keys	curl http://localhost:8080/auth/jwks	Responds with a JSON containing keys and alg RS256.
Frontend	Open http://localhost:5173	You see the sign-in screen.
Registration and sign-in	Create the test customer (12.1)	The customer's Home page opens.
Data in the database	Search vehicles by branch and dates	The search responds (with vehicles if the administrator has already registered any).
Administration	Sign in with the Super Admin (12.2)	Administration appears in the bar and the panel shows all sections.
Persistence	Register a branch or a vehicle and reload the page	The record still appears.
Mock	Open Administration > Bank accounts	The mock accounts are shown.

14. Common errors and solutions

Table 10

Frequent errors

Error	Likely cause	Solution
network rentamovil declared as external, but could not be found	The shared network was not created.	docker network create rentamovil and repeat the command.
rentamovil-sqlserver stops on startup	The sa password does not comply with the SQL Server policy or memory is insufficient.	Use 8+ characters with uppercase, lowercase, number and symbol; assign at least 2 GB of RAM to Docker.
Port is already allocated (1433, 3001, 3002, 3003, 8080, 5173 or 3100)	Another process, or the same service run with Maven and Docker at the same time.	Stop the duplicate process (netstat -ano | findstr :PORT on Windows) or change the port in the .env.
Missing parameter.iamAppPassword (or fleet / booking)	The service user password is missing in liquibase.properties or in the .env.	Fill in the parameter and run the migrations again.
The fleet or booking migrations fail because of iam objects	They were run before rtm-iam-db.	Respect the order: iam-db → fleet-db → booking-db.
A service does not start: schema validation error (Hibernate)	Migrations are missing, or the code and the schema come from different branches.	Run mvn liquibase:update and use the branches from section 5.1.
Login failed for user 'iam_app' (or fleet_app / booking_app)	DATABASE_PASSWORD does not match the parameter used in the migration.	Make the passwords match according to table 7.1.
iam does not start: invalid JWT keys	Empty keys, with line breaks, with the BEGIN/END lines, or that do not form a pair.	Regenerate them with step 7.3 and paste them on a single line.

Error	Likely cause	Solution
401 INVALID_TOKEN on all booking requests	APP_BOOKING_RESERVATION_JWT_PUBLIC_KEY is not iam's public key.	Copy the same APP_IAM_JWT_PUBLIC_KEY.
The gateway responds 503 SERVICE_UNAVAILABLE	The target service is not up.	Start it and check the gateway /health.
Creating a reservation responds 409 FLEET_SERVICE_UNAVAILABLE	Known limitation of booking-reservation (provisional fleet adapter).	Expected behaviour in this version.
Blank screen or network errors on the web	Gateway or mock are down, or the frontend .env was modified.	Check the browser console (F12), bring up the gateway and run npm run mock-api.
The password recovery code does not arrive	In development iam does not send emails: it writes the code in its log.	docker logs rentamovil-iam and look for [EMAIL DE DESARROLLO].
429 when signing in	Limit of 10 attempts every 5 minutes per IP.	Wait or adjust RATE_LIMIT_* in the gateway .env.
java, mvn or npm not recognized	The tool is not installed or is not in the PATH.	Install it and open a new terminal.

15. Known limitations of the installed version

- Creating reservations responds 409 until booking-reservation connects to fleet-maintenance.
- The payment-billing and telemetry-gps services do not exist: payments, bank accounts and GPS are served from the mock (port 3100).
- The mobile app is not connected to the API Gateway.
- The gateway does not yet route /maintenances nor the reference catalogs used by the web app; until they are added, those administration screens do not load data through the gateway.
- iam email sending is development-grade (it writes to the log).

16. Glossary

Term	Definition
Docker / container	Tool that runs each component isolated with everything it needs.
Docker Compose	docker-compose.yml file that defines how one or more containers are brought up.
rentamovil network	Shared Docker network through which containers find each other by name.
Image	Template from which a container is created.
Liquibase	Tool that applies, in order, the versioned changes of the database schema.
Changeset	Each individual database change applied by Liquibase.
Schema	Grouping of tables inside the rentamovil database (iam, fleet, booking, shared).
sa	SQL Server administrator user; only the migrations use it.
.env file	Local file with a component's configuration and secrets; it is not uploaded to the repository.
JWT / RS256	Session token signed with an RSA key pair.
API Gateway	Service that receives all requests and forwards them to the correct microservice.
API mock	Mock server for the functions whose real service does not exist yet.
Health check	/health endpoint that indicates whether a service and its database are working.
Maven / npm	Dependency and build managers for Java and JavaScript.
Expo Go	Phone app used to run the mobile app in development.

17. References

Apache Software Foundation. (n.d.). *Apache Maven* [Software documentation].

https://maven.apache.org/

Docker Inc. (n.d.). *Docker documentation*. https://docs.docker.com/

Expo. (n.d.). *Expo documentation*. https://docs.expo.dev/

Git. (n.d.). *Git documentation*. https://git-scm.com/doc

Liquibase. (n.d.). *Liquibase documentation*. https://docs.liquibase.com/

Microsoft. (n.d.). *SQL Server technical documentation*. https://learn.microsoft.com/en-us/sql/sql-server/

OpenJS Foundation. (n.d.). *Node.js documentation*. https://nodejs.org/en/docs

OpenSSL Software Foundation. (n.d.). *OpenSSL documentation*. https://www.openssl.org/docs/

Oracle Corporation. (n.d.). *Java SE documentation*. https://docs.oracle.com/en/java/javase/

18. Annexes

Annex A. Installation order summary

Step	Action	Main command
1	Create the network	docker network create rentamovil
2	SQL Server + iam schema	cd rtm-iam-db && docker compose up -d
3	fleet schema	cd rtm-fleet-maintenance-db && docker compose up --build
4	booking schema	cd rtm-booking-db && docker compose up --build
5	JWT keys and .env files	openssl genpkey ... / cp .env.example .env
6	iam service	cd rtm-iam && docker compose up -d --build
7	fleet-maintenance service	cd rtm-fleet-maintenance && docker compose up -d --build
8	booking-reservation service	cd rtm-booking-reservation && docker compose up -d --build
9	API Gateway	cd rtm-api-gateway && docker compose up -d --build
10	API mock and web	npm run mock-api and npm run dev
11	First Super Admin	UPDATE iam.[user] ... (section 12.2)

Annex B. Operation commands

Task	Command
View containers and their status	docker ps -a
View the log of a service	docker logs -f rentamovil-iam
Stop a component (data is preserved)	docker compose down
Stop and DELETE the SQL Server data	cd rtm-iam-db && docker compose down -v
Undo the last changeset	mvn liquibase:rollback -Dliquibase.rollbackCount=1

Task	Command
Run a service's tests	mvn test
Lint the web frontend code	npm run lint
Type-check the mobile app	npm run typecheck

Annex C. Verification screenshots

Figure 1. Output of docker ps with the containers running




Figure 2. Response from http://localhost:8080/health



Figure 3. Home screen at http://localhost:5173





Figure 4. Administration panel with the Super Admin menu



References

Ramirez, N. D., Rojas, T. F., & Erez, D. S. (2026a). *Administrator manual: RentaMovil vehicle rental platform* Programa de Tecnólogo en Análisis y Desarrollo de Software, Servicio Nacional de Aprendizaje (SENA).

Ramirez, N. D., Rojas, T. F., & Erez, D. S. (2026c). *Technical manual: RentaMovil vehicle rental platform* Programa de Tecnólogo en Análisis y Desarrollo de Software, Servicio Nacional de Aprendizaje (SENA).

Ramirez, N. D., Rojas, T. F., & Erez, D. S. (2026d). *User manual: RentaMovil vehicle rental platform* Programa de Tecnólogo en Análisis y Desarrollo de Software, Servicio Nacional de Aprendizaje (SENA).

RentaMovil. (2026). *RentaMovil* [Computer software]. GitHub. https://github.com/RentaMovil/RentaMovil

RentaMovil. (2026). *rtm-api-gateway* [Computer software]. GitHub. https://github.com/RentaMovil/rtm-api-gateway

RentaMovil. (2026). *rtm-booking-db* [Computer software]. GitHub. https://github.com/RentaMovil/rtm-booking-db

RentaMovil. (2026). *rtm-booking-reservation* [Computer software]. GitHub. https://github.com/RentaMovil/rtm-booking-reservation

RentaMovil. (2026). *rtm-fleet-maintenance* [Computer software]. GitHub. https://github.com/RentaMovil/rtm-fleet-maintenance

RentaMovil. (2026). *rtm-fleet-maintenance-db* [Computer software]. GitHub. https://github.com/RentaMovil/rtm-fleet-maintenance-db

RentaMovil. (2026). *rtm-iam* [Computer software]. GitHub. https://github.com/RentaMovil/rtm-iam

RentaMovil. (2026). *rtm-iam-db* [Computer software]. GitHub. https://github.com/RentaMovil/rtm-iam-db