The provided code stub will read in a dictionary containing key/value pairs of name:[marks] for a list of students. Print the average of the marks array for the student name provided, showing 2 places after the decimal.

Example

marks key:value pairs are

'alpha': [20, 30, 40]

'beta': [30, 50, 70]

query_name = 'beta'

The **query_name** is 'beta'. beta's average score is $(30 + 50 + 70)/3 = 50.0$.

Input Format

The first line contains the integer n, the number of students' records. The next n lines contain the names and marks obtained by a student, each value separated by a space. The final line contains **query_name**, the name of a student to query.

Constraints

- $2 \leq n \leq 10$
- $0 \leq marks[i] \leq 100$
- **length of marks arrays = 3**

Output Format

Print one line: The average of the marks obtained by the particular student correct to 2 decimal places.

Sample Input 0

```
3
Krishna 67 68 69
Arjun 70 98 63
Malika 52 56 60
Malika
```

Sample Output 0

```
56.00
```

Explanation 0

Marks for Malika are $\{52, 56, 60\}$ whose average is $\frac{52+56+60}{3} \Rightarrow 56$

Sample Input 1

```
2
Harsh 25 26.5 28
Anurag 26 28 30
Harsh
```

Sample Output 1

```
26.50
```

Change Theme Language Pypy 3

```
if __name__ == '__main__':
    n = int(input())
    student_marks = {}
    for _ in range(n):
        name, *line = input().split()
        scores = list(map(float, line))
        student_marks[name] = scores
    query_name = input()
    l1 = list(student_marks[query_name])
    addition = sum(l1)
    result = addition/len(l1)
    print('%.2f'% result)

```

Line: 13 Col: 1

Upload Code as File Run Code Submit Code

Test against custom input