Introduction to SyncTrack and Auto Framing on Reolink Cameras

Reolink SyncTrack and Auto Framing are smart features that improve target tracking and detail visibility on some OMVI Series cameras. This article explains how to achieve this purpose, along with features compatibility and configuration steps.

What is the SyncTrack and Auto Framing Feature on Reolink Cameras

Reolink SyncTrack and Auto Framing are intelligent tracking features available on some OMVI Series cameras, which combine an upper panoramic cam and a lower PT cam. SyncTrack focuses on continuous tracking with full panoramic monitoring without losing the target, while Auto Framing ensures targets remain clearly visible with optimized framing.

1. SyncTrack

SyncTrack is a collaborative tracking feature that allows the upper panoramic cam and the lower PT cam to work together within a multiple-lens architecture. The upper panoramic cam keeps watching the whole scene, while the lower PT cam tracks people, vehicles, or animals in real time. Even if the target moves out of the panoramic view, the PT lens can continue tracking it. In other words, when a person, vehicle, or animal enters the panoramic lens's wide-angle view, the lower PT cam automatically focuses on and tracks the target—even if they leave the wide-angle view. Both views are displayed simultaneously as well on the Reolink App.

2. Auto Framing

Auto Framing is an intelligent zoom-and-track feature. When it is enabled, the lower PT cam'll automatically zoom in and adjust the view when a target object is detected, making people, vehicles, or animals appear larger and clearer. This helps provide more detailed target views without requiring manual zoom adjustment.

3. How They Work Together

Both features work through AI-based detection and real-time coordination between the upper panoramic cam and lower PT cam. The upper panoramic cam continuously monitors the full 180° scene and detects targets, while the AI algorithms calculate their position and motion in real time. The lower PT cam then responds by tracking the target (**SyncTrack**) and adjusting zoom or framing (**Auto Framing**) accordingly.

When **SyncTrack and Auto Framing work together**, they deliver a complete monitoring experience:

- The upper panoramic cam continues to provide a full panoramic view.
- The lower PT cam continuously tracks moving targets.
- Auto Framing enhances target clarity with intelligent zoom and framing.

This combination enables **wide-area coverage, uninterrupted tracking, and detailed close-up viewing simultaneously**, providing a more comprehensive and intelligent surveillance experience.

What Reolink Models are Supported

The following cameras and NVRs support both **SyncTrack and Auto Framing.**

✓ Supported Cameras (Standalone Use with the latest firmware):
Reolink OMVI Series: OMVI 3i PoE, OMVI 3i WiFi, OMVI Series P931, OMVI Series W931

When the above supported camera is added to a compatible NVR, you can still use both features.
✓ Supported NVRs (with the latest firmware Fw. v3.6.4 or later):
RLN8-410 / NVS8 (Hardware version: N7MB01 / NVR_NNT3NA78P)
RLN16-410 / NVS16 (Hardware version: N6MB01 / NVR_NNT4NA716P)
RLN12W / NVS12W
RLN36 / NVS36
RP-PN8 / RP-PN16

Note:
1. Firmware version **v3.6.4** refers to any firmware version that **starts with v3.6.4**, such as v3.6.4.473_26021143.
2. Before setting up both features on the Reolink App, ensure your **Reolink App** is updated to the **latest version(version 4.60 or later).**