

Modulation Waveforms Lab Report

EXPERIMENT CP-SRP EE20017

Jake Stewart
JS3910
Eugene Levinson
EL769



UNIVERSITY OF
BATH

Electrical and Electronic Engineering
University of Bath
United Kingdom
February 24, 2024

Contents

1 Introduction 2

2 Modulation Tests 2

2.1 Results 2

3 Demodulation/detection 2

3.1 AM detection 2

4 Conclusion 2

1 Introduction

Introduce the topic of your report and provide background information.

2 Modulation Tests

A square wave and triangle wave were generated and modulated using an AM modulator. The modulated waveforms were then observed in MATLAB where the [Peak Envelope Power \(PEP\)](#) and [Peak to Average Power Ratio \(PAPR\)](#) were derived with the following code:

```
1 % AM Power
2 R = 50; % Ohms
3 AM_Power = (AM_time.^2) / R; % Power in Watts V^2/R
4 % Peak Envelope Power
5 PEP = max(AM_Power)/2 % Divided by 2 to get the RMS value
6 % Peak to Average Power Ratio
7 PAPR = PEP/mean(AM_Power)
```

2.1 Results

Square Wave

- [PEP](#): 134.5mW
- [PAPR](#): 2.37

Triangular Wave

- [PEP](#): 369.6mW
- [PAPR](#): 4.07

3 Demodulation/detection

3.1 AM detection

Square Wave

- [PEP](#): 575.7mW
- [PAPR](#): 8.22

4 Conclusion

Conclude the report by summarizing the findings and their implications.