

Modulation Waveforms Lab Report

EXPERIMENT CP-SRP EE20017

Jake Stewart
JS3910
Eugene Levinson
EL769



UNIVERSITY OF
BATH

Electrical and Electronic Engineering
University of Bath
United Kingdom
February 23, 2024

Contents

1	Introduction	2
2	Modulation Tests	2
2.1	Results for Square Wave	2
2.2	Results for Triangular Wave	2
3	Conclusion	2

1 Introduction

Introduce the topic of your report and provide background information.

2 Modulation Tests

A square wave and triangle wave were generated and modulated using an AM modulator. The modulated waveforms were then observed in MATLAB where the Peak Envelope Power (PEP) and Peak to Average Power Ratio (PAPR) were derived with the following code:

```
1 % AM Power
2 R = 50; % Ohms
3 AM_Power = (AM_time.^2) / R; % Power in Watts V^2/R
4 % Peak Envelope Power
5 PEP = max(AM_Power)/2 % Divided by 2 to get the RMS value
6 % Peak to Average Power Ratio
7 PAPR = PEP/mean(AM_Power)
```

2.1 Results for Square Wave

- PEP: [insert PEP value for square wave]
- PAPR: [insert PAPR value for square wave]

2.2 Results for Triangular Wave

- PEP: [insert PEP value for triangular wave]
- PAPR: [insert PAPR value for triangular wave]

3 Conclusion

Conclude the report by summarizing the findings and their implications.