

**ISBN:** 9781259643613 **Authors:** Joseph A. De Feo

#### Authors: 303cpm A. De 1 co

#### 4.0. CHAPTER PRELIMINARIES

**High Points of This Chapter** 

**Tackling the First Process of the Trilogy: Designing Innovative Products** 

The Juran Quality by Design Model

The Quality by Design Problem

**Juran Quality by Design Model** 

**Juran Quality by Design Model Substeps** 

**Frequently Used Design Tools** 

**Design for Six Sigma** 

Reference



**ISBN:** 9781259643613 **Authors:** Joseph A. De Feo

# 4.1. High Points of This Chapter

- 1. Designing for quality and innovation is one of the three universal processes of the Juran Trilogy. It is required to achieve breakthroughs, new products, services, and processes.
- 2. An effective design process requires a robust method and structure to create new products (goods, services, information) and ensure that these together with key operational processes—including process controls—are developed prior to the introduction of the products to the marketplace.
- 3. The Juran Quality by Design Model consists of following simple steps, primarily leading to a much better understanding of the customers that will benefit from the new product. It is not a statistical design method as Design for Six Sigma is considered. It is often used to design new services and processes. The steps are as follows:
  - Establish the design targets and goals.
  - Define the market and customers that will be targeted.
  - Discover the market, customers, and societal needs.
  - Develop the features of the new design that will meet the needs.
  - Develop or redevelop the processes to produce the features.
  - Develop process controls to be able to transfer the new designs to operations.
- 4. The Design for Six Sigma model, often called DMADV, consists of a statistical approach to design applicable to manufactured goods. It follows similar steps and incorporates some of the tools in Juran's model:
  - Define the project and the targets.
  - Measure what is critical to customers and quality (CTQs) to establish the required features.
  - Analyze the information and create a high-level design incorporating the CTQs.
  - Design by creating detailed designs, evaluate them, and optimize them before transferring them to operations.
  - Verify the design requirements and execute the final product.



**ISBN:** 9781259643613 **Authors:** Joseph A. De Feo

# 4.2. Tackling the First Process of the Trilogy: Designing Innovative Products

An organization's ability to satisfy its customers depends on the robustness of the design processes because the goods you sell and the services you offer originate there.

The design process is the first of the three elements of the Juran Trilogy. It is one of the three basic functions by which management ensures the survival of the organization. The design process enables innovation to happen by designing products (goods, services, or information) together with the processes—including controls—to produce the final outputs. When design is complete, the other two elements—control and improvement—kick in to continuously improve upon the design as customer needs and technology change.

This handbook addresses two versions of the design process. In this chapter, we will discuss the first version, Juran's universal Quality by Design model. It has been in place since 1986 and provides a structure that can be incorporated into an organization's new product development function, or it can be used independently to be carried out project by project as needed.

The second version, Design for Six Sigma (DFSS), which is referred to by the steps in the process DMADV (define, measure, analyze, design, and verify), is the most recent adaption to Juran's model. It builds upon the Six Sigma Improvement or DMAIC (define, measure, analyze, improve, and control) methodology to improve performance. DMADV was first introduced by GE. It uses elements of the Juran model and incorporates many of the statistical tools common to improvement. DFSS is covered in detail in Chap. 17, Continuous Innovation Using Design for Six Sigma.

The Juran model is especially useful for designing products and redesigning processes simply and economically. The authors have witnessed the design of superb products, processes, and services using this model.

Examples include a prize-winning safety program for a multiple-plant manufacturer; an information system that enables both sales and manufacturing to track the procession of an order throughout the entire order fulfillment process so customers can be informed—on a daily basis—of the exact status of their order; and a redesigned accounts receivable system much faster and more efficient than its predecessor.

The DFSS model is the classic model enhanced by the addition of computers and statistical software packages, which permit the utilization of numerous design tools not easily used without a computer. The Six Sigma model is suitable for designing even complex products and for achieving extraordinary levels of quality. Although it is time consuming and expensive in the short term, when executed properly, it produces a healthy return on investment.



**ISBN:** 9781259643613 **Authors:** Joseph A. De Feo

## 4.3. The Juran Quality by Design Model

Modern, structured quality design is the methodology used to plan both features that respond to customers' needs and the process to be used to make those features. "Quality by Design" refers to the product or service development processes in organizations. Note the dual responsibility of those who plan: to provide the features to meet customer needs and to provide the process to meet operational needs. In times past, the idea that product design stopped at understanding the features that a product should have was the blissful domain of marketers, salespeople, and research and development people. But this new dual responsibility requires that the excitement generated by understanding the features and customer needs be tempered in the fire of operational understanding.

That is, can the processes make the required features without generating waste? To answer this question requires understanding both the current processes' capabilities and customer specifications. If the current processes cannot meet the requirement, modern design must include finding alternative processes that are capable to meet the need.

The Juran Trilogy points out that the word "quality" incorporates two meanings: first, the presence of features that create customer satisfaction; second, freedom from failures regarding those features is also needed. In short, failures in features create dissatisfactions.

- 1. Removing failures is the purpose of quality improvement.
- 2. Creating features is the purpose of Quality by Design.

Kano, Juran, and others have long ago agreed that the absence of failures, that is, no customer dissatisfaction, may not lead us to the belief that satisfaction is thus in hand. We can readily conclude that dissatisfaction goes down as failures are removed. We cannot conclude that satisfaction is therefore going up, because the removal of irritants does not lead to satisfaction—it leads to less dissatisfaction.

It is only the presence of features that creates satisfaction. Satisfaction and dissatisfaction are not co-opposite terms. It is amazing how many organizations fail to grasp this point. Let's take, for example, the typical "bingo card" seen in many hotels. These are replete with "closed-ended" questions. For example, they ask, "How well do you like this on a scale of 1 to 5?" They do not ask, "How well do you like this?" This is the exact opposite of the question "How well don't you like it?" Therefore, any so-called satisfaction rating that does not allow for open-ended questioning such as "What should we do that we are not already doing?" or "Is there someone who provides a service we do not offer?" will always fall into a one-sided dimension of quality understanding. What, then, does a composite score of 3.5 for one branch in a chain of hotels really mean compared to another branch scoring 4.0? It means little. Their so-called satisfaction indices are really dissatisfaction indices.

So we arrive at the basic fundamental of what quality really is. As stated in Chap. 1, Universal Principles of Quality Management, the authors adopted a definition that Juran had postulated long before: "quality" means fitness for use, and we now have extended it to "fitness for purpose." Let's explore this concept.



First, the definition of "fitness for use" takes into account both dimensions of quality—the presence of features and the absence of failures. The sticky points are these: Who gets to decide what "fitness" means? Who decides what "purpose" means? The user decides what "use" means, and the user decides what "fitness" means. Any other answer is bound to lead to argument and misunderstanding. Providers rarely win here. Users, especially society at large, generally always win. For example, take yourself as a consumer. Did you ever use a screwdriver as a pry bar to open a paint can? Of course you did. Did you ever use it to punch holes into a jar lid so your child could catch bugs? Of course you did. Did you ever use it as a chisel to remove some wood, or metal that was in the way of a job you were doing around the house? Of course you did. Now wait just a moment ... a screwdriver's intended use is to drive screws!

So the word "use" has two components, intended use and actual use. When the user utilizes it in the intended way, both the provider and the user are satisfied. Conformance to specification and fitness for purpose match. But what about when the user uses it in the nonintended way, as in the screwdriver example? What, then, regarding specifications and fitness?

To delve even deeper, how does the user actually use the product? What need is it meeting for the user? Here we find another juncture: the user can create artful new uses for a product. For example:

2000 Uses for WD-40.WD-40 was formulated years ago to meet the needs of the U.S. space program. Not many know the origins of the brand name. "WD" refers to water displacement, and 40 is simply the 40th recipe the company came up with. But as the product moved into the consumer market, all kinds of new uses were uncovered by the users. People claimed it was excellent for removing scuff marks from flooring. They claimed it could easily remove price stickers from lamps, inspection stickers from windshields, and bubble gum from children's hair. The company delighted in all this. But the company didn't release all those clever new uses for public consumption. People also claimed that if they sprayed bait or lures with it, they caught more fish. Those with arthritis swore that a quick spray on a stiff elbow gave them relief. Let's not go too far. What about use where the product obviously cannot work? In Latin there is a word for this: ab-use (abuse), where the prefix "ab" simply means "not."

Some examples will help: back to the screwdriver. You could argue that using the screwdriver as a pry bar, chisel, or punch is abuse of its original designed purpose. But clearly many manufacturers have provided a product that can withstand this abuse, and so use then falls back into the "intended" column (whether this came as a result of lawsuits or from some other source). Further, a look at commercial aircraft "black boxes" (which are orange, by the way), show that they clearly survive in circumstances where the aircraft do not survive. Understanding of use in all its forms is what modern design seeks to achieve.

Last, modern design and planning, as we see over and over, seeks to create features in response to understanding customer needs. We are referring to customer-driven features. The sum of all features is the new product, service, or process.

A different type of product planning in which features meeting no stated need are put out for users to explore is beyond the scope of this chapter. 3M's Post-it Notes and the Internet are examples where we collectively did not voice needs, but which we cannot imagine life without them, once we embraced their features.




**ISBN:** 9781259643613 **Authors:** Joseph A. De Feo

### 4.4. The Quality by Design Problem

The Quality by Design model and its associated methods, tools, and techniques have been developed because in the history of modern society, organizations rather universally have demonstrated a consistent failure to produce the goods and services that unerringly delight their customers. As a customer, everyone has been dismayed time and again when flights are delayed, radioactive contamination spreads, medical treatment is not consistent with best practices, a child's toy fails to function, a new piece of software is not as fast or user-friendly as anticipated, government responds with glacial speed (if at all), or a home washing machine with the latest high-tech gadget delivers at higher cost clothes that are no cleaner than before. These frequent, large quality gaps are really the compound result of a number of four smaller gaps, illustrated in Fig. 4.1.

**Figure 4.1** The quality gap. (Inspired by A. Parasuraman, Valarie A. Zeithaml, and Leonard L. Berry, "A Conceptual Model for Service Quality and Its Implications for Further Research," Journal of Marketing, Fall 1985, pp. 41–50.)



The first component of the quality gap is the *understanding gap*, that is, lack of understanding of what the customer needs are. Sometimes this gap is wider because the producer simply fails to consider who the customers are and what they need. More often the gap is there because the supplying organization has erroneous confidence in its ability to understand exactly what the customer really needs. The final perception gap in **Fig. 4.1** also arises from a failure to understand customer needs. Customers do not experience a new suit of clothes or the continuity in service from a local utility simply based on the technical merits of the product. Customers react to how they perceive the good or service provides them with a benefit.

The second constituent of the quality gap is adesign gap. Even if there were perfect knowledge about customer needs and perceptions, many organizations would fail to create designs for their goods and services that are fully consistent with that understanding. Some of this failure arises from the fact that the people who understand customers and the disciplines they use for understanding customer needs are often systematically isolated from those who actually create the designs. In addition, designers—whether they design sophisticated equipment or delicate human services—often lack the simple tools that would enable them to combine their technical expertise with an understanding of the customer needs to create a truly superior product.



The third gap is the *process gap*. Many splendid designs fail because the process by which the physical product is created or the service is delivered is not capable of conforming to the design consistently time after time. This lack of process capability is one of the most persistent and bedeviling failures in the total quality gap.

The fourth gap is the *operations gap*. The means by which the process is operated and controlled may create additional failures in the delivery of the final good or service.

Quality by Design provides the process, methods, tools, and techniques for closing each of these component gaps and thereby ensuring that any final gap is at a minimum. **Figure 4.2** summarizes at a high level the basic steps of Quality by Design. The remainder of this section will provide the details and examples for each of these steps.

**Figure 4.2** Quality by Design steps. (Copyright 1994, Quality by Design, Juran Institute, Inc.)

#### **Quality Planning**

- 1. Establish the project and design goals.
- 2. Identify the customers.
- Discover the customer needs.
- Develop the product or service features.
- 5. Develop the process features.
- Develop the controls and transfer to operations.



ISBN: 9781259643613

Authors: Joseph A. De Feo

# 4.5. Juran Quality by Design Model

We look at each of these as we step through the sequence at a high level.

#### 4.5.1. Step 1: Establish the Project and Design Goals

All design should take place project by project. There is no such thing as design in general; there is only design in specific. In strategic planning, we set out the vision, mission, strategies, objectives, and so on. Each is a specific thing. In product planning, we start with a project, that is, something to plan. We might design a new training room, a new car, a wedding, a customer toll-free hotline, or a new Internet process for bidding on travel booking (such as Priceline.com, Expedia.com). Note that each is a specific thing, and each can be clearly differentiated from anything else. A training room is not a cafeteria, a new car is not a Howitzer, a hotline is not long-distance service, and the travel booking process is not a bookstore online. This is a significant point. Without being able to differentiate what we are designing from anything else, everything collapses into vagueness. So a project is our starting point.

#### 4.5.2. Step 2: Identify the Customers

Going back to the 1980s Total Quality Management (TQM) days, we learned that those who receive the product are customers in some way. If we were designing a training room, the trainees would be an important customer segment. So, too, would the custodians, because they have to clean the room, set it up in different ways, and so on. Customers of the new car include the purchasers, the insurance organizations, the dealers, the carriers, etc. Customers of the hotline include our clients, our service agents, etc. We can include as customers for the travel process the travelers, airlines, and the Web server entity. From all this emerges the basic understanding: A customer is a cast of characters, and each has unique needs that must be met.

#### 4.5.3. Step 3: Discover the Customers' Needs

Wants, needs, perceptions, desires, and other emotions are all involved in our discovery of customer needs. We need to learn how to separate things and prioritize them. But at this point, we need to emphasize that not all high-priority customers (such as the car buyer) are the only ones with high-priority needs. We also stress that just because some customer entity is lower in priority doesn't mean at all that it automatically has lesserpriority needs. We need to understand the "voice of the customer" and the "voice of the market."

Take, for example, the automobile carriers; we simply cannot overlook their needs for the car to be only so high and only so wide. If we ignored their needs, they could stop the product from reaching the cash-paying ultimate customer, our buyer. So, too, could regulators (the various states, the National Highway Transportation Safety Board, the Environmental Protection Agency, etc., impose "needs" that if unmet, could stop the process from going forward at all). So from all this, we reach another point: Customers have to be prioritized in an agreed upon way.



#### 4.5.4. Step 4: Develop the Product or Service Features

The word "feature," as used in product planning, means what the product does, its characteristics, or its functionality. In structured product planning, we adopt a different definition: A feature is the thing that the customer employs to get her or his needs met. For example, in our training room, the trainees need to take notes as they learn. A feature might then be a flip chart, a white board, or a desk. Our custodians might need to move things around quite a bit, so features might include portability, size, weight, and modularity.

As our list of features grows, we soon realize that we cannot possibly have all features at the same priority level. So we need a way to put things in order, once again, and in an agreed upon way. We finalize by optimizing and agreeing on the list of features and the goals for them as well. Note what optimization means: Not all features survive product planning.

#### 4.5.5. Step 5: Develop the Process Features

Because we know that the process is the thing that creates the features, we need to examine current and alternative processes to see which ones will be used to create the features. We need to be sure that the product feature goals can be accomplished via the processes we choose. In other words:

Process capability must reconcile with product requirements. That statement is very important. No process knows its product goals; product goals come from humans. Ideal product goals would naturally reflect the various customers. But the key issue is this: Variation comes from processes; goals come from humans.

In the example of the training room, process goals might be to reset the room in 20 minutes, keep a supply of flip charts in a closet, certify the trainees to a standard, and so on. As before, we need to list all the possible routes to making the product, select the ones we will use based on some rationale, establish goals for the processes, and reach an optimum.

# 4.5.6. Step 6: Develop Process Controls and Transfer to Operations



#### 4.5.6.1. Develop Process Controls

Control is basic to all human activity, from how the body regulates itself as to temperature and metabolism, to financial controls in how we run our organizations or homes. Control consists of three fundamentals:

In product planning, we need to ensure that the processes work as designed within their capabilities. In the training room, for example, controls might take the form of a checklist for resetting the room and a minimum inventory of flip charts. Control makes use of the concept of the feedback loop.

Here's an example you might keep in mind:

Did you ever check the oil in your car? The dipstick is a form of control point. Note that we begin with a control subject (volume of oil), a unit of measure (quarts or liters), a sensor (you and the dipstick), and a goal (keep the oil somewhere between "full" and "add"—inside those hash marks). Then we move on to sample the process (clean the dipstick, put it back in, remove it, and observe the oil level). Next we adjust when adjustment is called for (oil levels below the add demarcation require us to add oil until we bring the oil up to somewhere between add and full, the agreed goal). If the oil is already within the hash marks, the control activity is to replace the dipstick, shut the hood, and drive on until another checkpoint is reached (perhaps next month). Note that the control activity must reflect the agreed upon goal for control. In the engine oil example, the control point was "inside the hash marks," so the control action is to bring the oil to somewhere "inside the hash marks." Many people miss this point; for example, they add oil until the stick reads "full." This is overcontrol. Control actions must reflect control goals.

#### 4.5.6.2. Transfer to Operations

Transfer to operations winds up the whole design process. As used here, "operations" means those who run the process, not "manufacturing." To continue the examples used earlier, operations for the training room is the activity of the trainers, the custodians, and the purchasing department. For the new car, operations include manufacturing, transport, dealer relations, and the legal department. For the hotline, operations means the customer service agents who answer the phone. In the travel bidding process, operations include those who shop the bid or reject it and those who maintain the software that interfaces the prospect with the carriers. From the lessons of the era of productivity, the Industrial Revolution, and into the twentieth century, we have learned that the involvement of the operators is key to any well-running process.

With the development of the Ford Taurus came solid understanding of the value of a "platform" team. Designers, engineers, workers, purchasing agents, salespeople, and managers all sat under one roof to develop the car. The concept of platform teams is well ingrained in many car organizations today. The Chrysler Technical Center in Auburn Hills, Michigan, is a later example of such broad collaboration. Thus, successful transfer to operations must include the operators in the design process as early as possible.

The remainder of this section will provide details, practical guidance, and examples for each of these steps.