

ROVER RESCUE SYSTEM

Manual - Rover

Author:	Student Number:
Christiaan van Arum	500778983
Raphaël Bunck	500774349
Nino van Galen	500790589
Martijn Vegter	500775388

January 13, 2019

Contents

1	Introduction	2
2	Requirements	3
3	Installation	4
4	Usage	5

1 Introduction

TODO

2 Requirements

TODO

3 Installation Guide

This chapter gives a step by step tutorial to get the RSS up and running. After completing the installation, continue reading the usage guide.

3.1 Pre-installation

Before installing the Rover software, make sure you have the following software up and running:

- A RaspberryPi B2 (RPI) with newest version of Raspbian.
- An Active internet connection on the RPI.
- An open SSH, see setup below.

3.2 Headless setup procedure

- Step 1: Create an empty file. You can use Notepad on Windows or TextEdit to do so by creating a new file. Just name the file ssh. Save that empty file and dump it into boot partition (microSD).
- Step 2: Create another file name wpa_supplicant.conf. This time you need to write a few lines of text for this file. For this file, you need to use the FULL VERSION of wpa_supplicant.conf. Meaning you must have the 3 lines of data namely country, ctrl_interface and update_config.

```
country="Your country"
ctrl_interface=DIR=/var/run/wpa_supplicant GROUP=netdev
update_config=1

network={
    ssid="your_real_wifi_ssid"
    scan_ssid=1
    psk="your_real_password"
    key_mgmt=WPA-PSK
}
```

3.3 Installation

To install Rover and its dependencies from your RPI shell prompt, use the following command:

\$ wget -q https://git.io/fx0ko -O /tmp/rover && bash /tmp/rover

3.4 Manual Installation

Update your system package list:

```
$ sudo apt-get -update -y
```

Upgrade all you installed packages to their latest version:

```
$ sudo apt-get dist-upgrade -y
```

To download and install newest version of Node.js, use the following command:

```
$ curl -sL https://deb.nodesource.com/setup_8.x | sudo -E bash -
```

Now install it by running:

```
$ sudo apt-get install nodejs -y
```

To compile and install native addons from npm you also need to install build tools:

```
$ sudo apt-get install build-essential -y
```

To download the Rover code you need to install git:

```
$ sudo apt-get install git -y
```

Clone 'Scriptor' using git:

```
$ git clone https://github.com/RescueOnWheels/Scriptor.git
```

Clone 'Rover' using git:

```
$ git clone https://github.com/RescueOnWheels/Rover.git --recursive
```

Open the 'Scriptor' folder and start using the Rover:

```
$ cd Scriptor && ./start.sh all
```

4 Usage

TODO