

# Alpine: New User Seminar



### CURC Alpine: New User Seminar

Instructor: Ragan Lee, Layla Freeborn Workshop Type: Primer



- Website: www.rc.colorado.edu
- Helpdesk: <u>rc-help@colorado.edu</u>
- Slides: <a href="https://github.com/ResearchComputing/New\_User\_Seminar">https://github.com/ResearchComputing/New\_User\_Seminar</a>





### RMACC Cyber Infrastructure Portal



- https://ask.cyberinfrastructure.org/c/rmacc/65
- This forum provides opportunity for RMACC members to converse amongst themselves and with the larger, global research computing community.
- The "go to" general Q&A platform for the global research computing community researchers, facilitators, research software engineers, CI engineers, sys admins and others.





### Learning Goals

- 1. Understand Basic CURC Resources & the Alpine cluster
- 2. Getting an account & logging in
- 3. Navigate the RC system
- 4. Running a job
- 5. Help!



## Things to take note of:

 Confusing, ambiguous, highly nuanced concepts

 Our goal is to help you avoid common mistakes, pitfalls, and frustrations



**Ask Questions!** 

### Introduction to HPC




#### Resources Include:

 High Performance Computing (HPC) Storage of Research Data High-Speed Data Transfer Data Sharing Cloud Computing Training and Education Secure Research



### Primarily known for: High Performance Computing (HPC)






# High Performance Computing (HPC) vs. Traditional Computing

 Traditional computing generally has access to a single processor (perhaps multiple cores)




### What can I use HPC for?

- Jobs that would take a long time on local machines can instead be distributed over hardware:
  - Parallelized to split up then joined (if software enabled)



Broken up into many serial jobs





### What can / use HPC for?

- Solving large problems that require more:
  - Memory than you have on your PC
  - cores/nodes/power thank you have on your PC
- Jobs that require hardware you may not have:
  - High Performance GPU computing
  - Specific Operating System
- Visualization rendering




# Research Computing Resources



## HPC Cluster: Alpine

#### **Alpine**




- Alpine is the 3rd-generation HPC cluster at CURC, following:
  - Janus
  - RMACC Summit

- Alpine is a heterogeneous cluster with hardware currently provided by CU Boulder, CSU, and Anschutz
- Access available to CU Boulder, CSU, AMC and RMACC users



### HPC Cluster: Alpine

#### **Alpine**




- Hardware on Alpine will continue to be purchased and released in stages:
- Alpine (stage 4):
  - 375 General CPU Nodes
    - AMD Milan, 32-64 Core, 3.74G RAM/Core
  - 12 NVIDIA GPU Nodes
    - 3x NVIDIA A100 (atop General CPU node)
  - 8 AMD GPU Nodes
    - 3x AMD MI100 (atop General CPU node)
  - 22 AMD High-Memory Nodes
    - AMD Milan, 48-64 Core, 21.5G RAM/Core
  - Additional Hardware contributed by CSU, AMC
    - Nodes which boost priority for CSU/AMC users





### HPC Cluster: Alpine

#### **Alpine**



#### Interconnect


- CPU nodes: HDR-100 InfiniBand (200Gb inter-node fabric)
- GPU nodes: 2x25 Gb Ethernet +RoCE
- Scratch Storage: 25Gb Ethernet+RoCE
- Operating System
  - RedHat Enterprise Linux version 8 operating system






# Storage at CURC

#### Core



- Included with RC account
  - /home
  - /projects
  - scratch space

#### **PetaLibrary**



- Paid Service for:
  - Storage
  - Archive
  - Sharing of research data

#### **Local or Cloud**




- You can download your data locally or to a variety of other cloud resources
- Cloud Foundations at Research Computing





# Data Sharing: Within RC

- Sharing workspaces
  Project space
  Scratch Space
  PetaLibrary Space\*



\*If you have purchased PetaLibrary space




### Data Sharing: Outside RC

- Data Transfer Nodes (DTN)
  - Internal CU network needed (VPN)

#### Ways to transfer data:

- Globus (recommended):
  - GUI Web Application
  - Automates large transfers
  - Resumes failed transfers
  - Distributes large transfers across DTNs
  - Endpoints that can shared
- Command line tools
  - scp, sftp, rsync, rclone





# Cloud Computing

- CURC supports AWS, Azure, and GCP
  - For use cases not well-supported by HPC
- Can be used as an alternative to HPC
- CURC also supports Jetstream2
  - NSF-funded cloud provider
- Can be used to enhance HPC
  - · Automatic job submission, high availability, etc.



Request cloud support by contacting the RC helpdesk at <a href="mailto:rc-help@colorado.edu">rc-help@colorado.edu</a>



# Accessing Research Computing



### How to Access RC Resources?

- 1. Get an RC account
- 2. Set up two-factor authentication with Duo
- 3. (Inform us of any specific needs)
- 4. Log in
- 5. Create greatness! (responsibly)





#### Getting an RC Account

- University of Colorado, Boulder users and affiliates:
  - Request an account through the RC Account request portal
  - https://rcamp.rc.colorado.edu/accounts/accountrequest/create/organization
- Colorado State University users:
  - Request an CSU eID if you don't have one
  - Fill out account application form
  - Duo authentication
  - https://it.colostate.edu/research-computing-andcyberinfrastructure/compute/get-started-with-alpine/





#### Getting an RC Account

#### RMACC Users:

- Create an <u>ACCESS-CI</u> Account in the ACCESS user portal
- Email us at <a href="re-help@colorado.edu">rc-help@colorado.edu</a> and request an account. Please include the following information: your ACCESS username, your institutional affiliation, your role, your department, your first and last name, your preferred email address for communication

#### CU Anschutz Users:

- Create an <u>ACCESS-CI</u> Account in the ACCESS user portal
- Reach out to <a href="https://necess.org/hpcsupport@cuanschutz.edu">hpcsupport@cuanschutz.edu</a> to receive and sign the End-User Agreement





### Demo: Getting an Account

- CU Boulder, CSU users and affiliates:
  - Request an account through the RC Account request portal:

https://rcamp.rc.colorado.edu/accounts/accountrequest/create/organization

- AMC, RMACC users and affiliates:
  - Request an account through the ACCESS-CI User Registration Portal:

https://identity.access-ci.org/new-user.html





### Your RC Account

#### Access to:

- 1. Alpine Cluster
- 2. Core Storage
- 3. PetaLibrary Storage\*
- 4. Open OnDemand
- 5. Approximately 2,000 Service Units (SUs) per month

\*If purchased





### Your RC Account

#### How can I use more computational time?:

- Trailhead Allocation (Default)
  - ~2,000 SUs / Month
- Ascent Allocation
  - 350,000 SUs
- Peak Allocation
  - >350,000 SUs

Request an allocation at <a href="https://curc.readthedocs.io/en/latest/clusters/alpine/allocations.html?highlight=alpine%20allocation#comparing-trailhead-auto-allocation-ascent-allocation-and-peak-allocation-tiers">https://curc.readthedocs.io/en/latest/clusters/alpine/allocations.html?highlight=alpine%20allocation#comparing-trailhead-auto-allocation-ascent-allocation-and-peak-allocation-tiers</a>





# Two Factor Authentication (Duo)

- Provides an extra level of authentication
  - We are outside the firewall!
  - Valuable resources
  - Inviting, high-profile target
- Duo
  - You will receive a Duo invitation when your RC account is created





### **Duo Authentication**

- Duo smartphone app (recommended)
- 2. Phone Call/Text is an alternatives







### Linux comfort level check

On a scale from (1-10) how familiar/comfortable are you with

#### Linux?

- The command line
- Basic commands
- Linux filesystem
- Navigating the filesystem

Want more Linux practice? Check out our Super Computing Spin Up!





### **Terminal**

- Mac or Linux
  - Terminal application
- Windows
  - PuTTY
  - Powershell



- Open OnDemand (alternative for CU affiliates)
  - For those less familiar with Linux (ondemand.rc.colorado.edu/)





# Demo: Logging in via Terminal

To login to an RC login node:

\$ ssh <username>@login.rc.colorado.edu

Supply your IdentiKey password and your Duo app will alert you to confirm the login

### Demo: logging in with OnDemand

CURC Open OnDemand is a browser based, integrated, single access point for all of your HPC resources at CU Research Computing.

- CU Boulder: Visit <a href="https://ondemand.rc.colorado.edu">https://ondemand.rc.colorado.edu</a>.
- Other RMACC Institutions: Visit <a href="https://ondemand-rmacc.rc.colorado.edu/">https://ondemand-rmacc.rc.colorado.edu/</a>



# Logging In

- It's important to note that you are NOT logging into any specific resource, Alpine, Blanca, etc.
- When you log in, you land on our login nodes

- From *there*, you can access our other resources:
  - Alpine
  - Blanca
  - Petalibrary



# Navigating Research Computing





#### Node

- One computing server
- Physical hardware
- Work together in parallel

#### **File System**

- The basic tree-like layout
- From most nodes\* you have access to most file systems









#### Node

- One computing server
- Physical hardware
- Work together in parallel

#### **File System**

- The basic tree-like layout
- From most nodes you have access to most file systems







# Node Types

Login	Compile	Compute
Where you log in to	Where you compile code, install packages	Where scheduled jobs run
<ul><li>For editing code, job submission</li><li>No heavy computation</li></ul>	<ul> <li>Explore the Alpine software environment</li> <li>Edit code, submit jobs</li> <li>No heavy computation</li> </ul>	<ul> <li>Intended for heavy computation</li> </ul>
Ex. edit job script	Ex. Install python libs	Ex. Running Matlab





### Alpine Compile Nodes

Alpine's acompile command starts an interactive job which provides the following benefits:

- Users can request specific resources (i.e. more cores to compile with)
- Limits dedicated hardware set aside
- Can't accidentally run full workflows



#### Alpine Compile Nodes

- \$ acompile
  - starts a job with default: 1 core, 3.74GB RAM, for 60 minutes\*
- \$ acompile --help

\*only a single acompile job can be open at a time



### Demo: Exploring Nodes

- Once logged in, type:
  - \$ acompile

To log in to an Alpine compile (or head) node.

- Once on a compile node, type:
  - \$ module avail

To list currently available software





### Filesystem Structure

/home (2GB)

/projects (250GB)

/scratch/alpine (10TB)

Scripts, Code,				
Small, important				
files/directories				

t

Code/files/libraries

Software you are installing

Sharing files

Output from running jobs

Large files/datasets

Sharing files

Cluster specific

Not for sharing files or job output

Not for job output

Not for long term storage

Ex .bashrc

Ex. Shared job scripts

Ex. Data



## Exploring the Filesystem

 Once logged in use the following commands to navigate to your different workspaces

```
$ cd /home/<user>
$ cd /projects/<user>
$ cd /scratch/alpine/<user>
```

#### Using RC Resources

- We have:
  - Logged in
  - Explored nodes
  - Explored filesystem

How do we actually use the computing resources?



# Running a Job



#### Jobs

#### What is a "job"?

- Work for the cluster to perform on
- Has a unique ID

#### 1. Batch jobs

- Submit job script which will be executed when resources are available
  - Create script containing information about the job
  - Submit the job file to a queue

#### 2. Interactive jobs


Work interactively at the command line of a compute node





### Job Scheduling

- CURC Clusters are shared resources, jobs are:
  - Submitted to a queue
  - When the required resources become available, the scheduler determines which set of nodes to use





#### **SLURM**

Simple Linux Utility for Resource Management

- Through SLURM users can:
  - Schedule jobs on specific compute resources
  - Run jobs interactively or hands off
  - Query job statistics



#### Your first job

How to write it?

• Where to write it?

• How to run it?

/home/<user> /projects/<user> Scratch space

### Job Script: 3 main parts

#### 1. Directives

Specify resource requirements

#### 2. Software

- Because jobs run on a different node than from where you submitted...
- ...software that is needed must be loaded via the job script

#### 3. User scripting

 the actual user scripting that will execute when the job runs

```
#!/bin/bash

## Directives
#SBATCH --<resource>=<amount>

## Software
module purge

## User Scripting
hostname # example bash command
```

#### Slurm Options (directives)

#SBATCH <options> sbatch <options>

```
    Allocation:

                              --account=<account no>

    Partition:

                              --partition=<partition name>

    Sending emails:

                                     --mail-type=<type>

    Output file:

                              --output=<file name> (%j gives you job id)

    Number of nodes:

                              --nodes=<nodes>

    Number of tasks:

                              --ntasks=<processes>

    Quality of service:

                              --qos=<qos>

    Reservation:

                              --reservation=<name>

    Wall time:

                              --time=<wall time>

    Job Name:

                              --job-name=<jobname> ...etc...
```

FYI: You do NOT actually type <> above – this designates something specific you as a user must enter about your job





## Slurm Options (directives)

- There are MANY slurm directives, most of which are not required
  - See all options at <a href="http://slurm.schedmd.com/sbatch.html">http://slurm.schedmd.com/sbatch.html</a>

- We will focus on some common options:
  - Partition: Nodes with the same hardware configuration
  - Wall time: Max time your job will run for
  - Node count: # of nodes requested
  - Core count: # of cores requested
  - Output file: name of output file





# Alpine Partitions

Partition	Description	# of nodes	RAM/core (GB)	cores/node	GPUs/node
amilan	General Compute Node: AMD Milan	375	3.74	32-64	0
ami100	GPU Node: 3x AMD MI100	8	3.74	64	3
aa100	GPU Node: 3x Nvidia A100	12	3.74	64	3
amem	High-memory node	22	21.5	48-64	0



### Review: Learning Goals

- 1. Understand Basic Resources (Alpine cluster)
- 2.Getting an account & logging in
- 3. Navigate the RC system
- 4. Running a job
- 5.Help!

## Help! I'm stuck, where do I go?

- Documentation: curc.readthedocs.io/
- Trainings with Center for Research Data and Digital Scholarship (CRDDS):
   <a href="https://www.colorado.edu/crdds/">https://www.colorado.edu/crdds/</a>
  - What should I do next?:
    - Supercomputing Spin Up: Part 1 Working with Linux
    - Supercomputing Spin Up: Part 2 Submitting Jobs
- Helpdesk: rc-help@colorado.edu
- Consult Hours (Tuesday 12:00-1:00 in-person or virtually, Thursday 1:00-2:00 virtually)





#### Helpdesk Tickets

To: rc-help@colorado.edu

Dear Research Computing,

Help! My code won't run! Help!

Help please, Ragan To: rc-help@colorado.edu

Dear Research Computing,

I am running into issues running my Python script. I am using a conda environment called my\_python\_env with the pytorch software, and I am receiving the following error. I am not sure how to troubleshoot. My job ID is 620350. Let me know what I can try!

sbatch: error: Batch job submission failed: Invalid partition name specified.

Thanks, Ragan





#### Questions?

CURC User Policies: <a href="https://curc.readthedocs.io/en/latest/additional-resources/policies.html?highlight=policies#curc-user-policies">https://curc.readthedocs.io/en/latest/additional-resources/policies.html?highlight=policies#curc-user-policies</a>





## Survey and feedback

http://tinyurl.com/curc-survey18

