



Installing software on Alpine with Conda and Mamba



Research Computing
UNIVERSITY OF COLORADO BOULDER

Installing software on Alpine with Conda and Mamba

Date: February 13, 2024

Instructor: Andrew Monaghan

Contributors: Layla Freeborn, Trevor Hall, Brandon Reyes

- Website: www.rc.colorado.edu
- Documentation: <https://curc.readthedocs.io>
- Helpdesk: rc-help@colorado.edu
- Survey: <http://tinyurl.com/curc-survey18>

Slides

https://github.com/ResearchComputing/alpine_conda_mamba_primer



Session Overview

Introduction

- Installing software on CURC systems
- Description of Conda

Setting up Conda on Alpine

- Logging in
- Using conda for the first time: creating the ~/.condarc file
- Starting an interactive session and activating conda

Creating and Modifying Virtual Environments with Conda

- Creating/activating/modifying a python environment
- Useful conda commands and paths

Using Conda Virtual Environments

- In HPC jobs
- In OnDemand Jupyter

Strategies for installing complex Virtual Environments (Discussion only)

- Channels
- Resolving conflicts upon environment creation
- Mamba

Building Software on Alpine

- There are numerous ways to install software on Alpine:
 - grab pre-compiled binaries
 - compile from source
 - **within virtual environments (via Conda, Miniconda, or Mamba)**
 - using containers (Apptainer/Singularity)
 - using a package manager for HPC systems (Spack)

Additional information:

<https://github.com/ResearchComputing/research-software-curc>

Virtual Environments With CONDA

- Conda is a package (software) management system
 - installs, runs, and updates packages and their dependencies
 - creates, saves, loads, and switches between virtual environments
 - created for Python programs, but can package and distribute software for any language

Additional information:

<https://curc.readthedocs.io/en/latest/software/python.html>

Logging into CU Research Computing

login to CURC via your terminal:

```
ssh monaghaa@login.rc.colorado.edu
```

...or login to CURC via your browser:

<https://ondemand-rmacc.rc.colorado.edu>

(once logged in, navigate to **Clusters** -> **Alpine shell**)

Additional information:

<https://curc.readthedocs.io/en/latest/access/logging-in.html>

<https://curc.readthedocs.io/en/latest/gateways/OnDemand.html>

Setting up Conda for the first time

Create a new ~/.condarc configuration file in your editor:

```
[monaghaa@login11 ~]$ nano ~/.condarc
```

Paste the following text in the file:

```
pkgs_dirs:  
- /projects/$USER/.conda_pkgs  
envs_dirs:  
- /projects/$USER/software/anaconda/envs
```

Save and exit the editor by typing **CTRL-o** then **CTRL-x**

Additional information:

<https://curc.readthedocs.io/en/latest/software/python.html#configuring-conda-with-condarc>
<https://conda.io/projects/conda/en/latest/user-guide/configuration/use-condarc.html>

Start a session and activate conda

Start a session on an Alpine compute node with **acompile**:

```
[monaghaa@login11 ~]$ acompile --help
[monaghaa@login11 ~]$ acompile --time=90:00
...
[monaghaa@c3cpu-a5-u28-1 ~]$ module load anaconda
(base) [monaghaa@c3cpu-a5-u28-1 ~]$
```

Note: when you login to CURC you'll be on a **login** node. You'll need to be on a **compute** node to use anaconda. The **acompile** command allows you to quickly start an interactive job on a compute node.

Additional information:

<https://curc.readthedocs.io/en/latest/clusters/alpine/alpine-hardware.html#partitions>

Create your first conda environment!

- Environments are created and programs are installed in a few simple steps

```
(base) [monaghaa@c3cpu-a5-u28-1 ~]$ conda create -n my_first_env python==3.10  
(base) [monaghaa@c3cpu-a5-u28-1 ~]$ conda activate my_first_env  
(my_first_env) [monaghaa@c3cpu-a5-u28-1 ~]$ python
```

Don't install packages in your base environment!

Additional information:

<https://curc.readthedocs.io/en/latest/software/python.html#create-your-own-custom-environment>

Install packages with “conda install”

- Packages are installed within **activated** environments

using **conda install** to install latest version or specific version:

```
(my_first_env) [monaghaa@c3cpu-a5-u28-1 ~]$ conda install pandas
```

```
(my_first_env) [monaghaa@c3cpu-a5-u28-1 ~]$ conda install pandas==0.20.3
```

Additional information:

<https://curc.readthedocs.io/en/latest/software/python.html#using-conda>

Install packages with “pip”

- Packages are installed within **activated** environments

using **pip** to install latest version or specific version:

```
(my_first_env) [monaghaa@c3cpu-a5-u28-1 ~]$ pip install --no-cache-dir pandas
```

--no-cache-dir is crucial on CURC systems!

Useful Conda Commands

```
conda env list                # list all environments
conda list                    # list packages in active env
conda env remove -n <envname> --all # remove an environment
conda config --show channels  # view configured channels
conda deactivate              # deactivate environment
conda create --name <clonedenv> / # clone an environment
    --clone <envtoclone>
```

Additional information:

<https://curc.readthedocs.io/en/latest/software/python.html#basic-conda-commands-to-get-you-started>

Useful conda file paths on Alpine

location of python libraries

/projects/\$USER/software/anaconda/<env>/lib/python3.10/site-packages

location of package executables

/projects/\$USER/software/anaconda/<env>/bin

location of .condarc file

/home/\$USER/.condarc



Running Alpine batch jobs with conda

```
[monaghaa@login11 ~]$ nano runconda.sh #Step 1: open new job script in editor
```

```
#!/bin/bash
# job script name: runconda.sh

#SBATCH --partition=amilan
#SBATCH --nodes=1
#SBATCH --ntasks=1
#SBATCH --time=10:00

module purge
module load anaconda
conda activate my_first_env
python my_python_code.py
```

Step 2: Write job script

<https://curc.readthedocs.io/en/latest/running-jobs/batch-jobs.html>

```
[monaghaa@login11 ~]$ sbatch runconda.sh #Step 3: Schedule job
```

Using your conda environment in Jupyter

Step 1: create a kernel *within* your **activated** environment:

```
(my_first_env) [monaghaa@c3cpu-a5-u28-1 ~]$ conda install -y ipykernel  
(my_first_env) [monaghaa@c3cpu-a5-u28-1 ~]$ python -m ipykernel install --user  
--name my_first_env --display-name my_first_env
```

Step 2: Use the environment in the OnDemand Jupyter app in your browser:

- * <https://ondemand-rmacc.rc.colorado.edu>
- * Navigate to “Interactive Apps” then “Jupyter Session (presets)”
- * Launch a session then open a notebook with “my_first_env”

Additional information:

<https://curc.readthedocs.io/en/latest/gateways/OnDemand.html#jupyter-session>

Strategies for complex environments

- Using channels and channel order
- Resolving conflicts upon environment creation
- Using Mamba to accelerate installation

Additional information:

<https://curc.readthedocs.io/en/latest/software/python.html>

<https://curc.readthedocs.io/en/latest/software/python.html#mamba-package-manager>

Thank you!

Survey and feedback

<http://tinyurl.com/curc-survey18>

