| Status | Finished | |
|-----------|--------------------------------------|--|
| Started | Thursday, 26 December 2024, 10:55 PM | |
| Completed | Thursday, 26 December 2024, 11:28 PM | |
| Durativn | 33 mins 6 secs | |

Correct

Marked out of 1.00

P Flag

questivn

Question 1

Two strings \boldsymbol{A} and $\boldsymbol{\mathcal{B}}$ comprising of lower case English letters are compatible if they are equal or can be made equal by following this step any number of times:

Select a prefix from the string A (possibly empty), and increase the alphabetical value of all the characters in the prefix by the same valid amount. For example, if the string is xyz and we select the prefix xy then we can convert it to yx by increasing the alphabetical value by 1. But if we select the prefix xyz then we cannot increase the alphabetical value.

Your task is to determine if given strings ${\bf A}$ and ${\bf B}$ are compatible.

Input format

First line: String \boldsymbol{A} Next line: String \boldsymbol{B}

Output format

For each test case, print YES if string A can be converted to string B, otherwise print NO.

Constraints

 $1 \le len(A) \le 1000000$ $1 \le len(B) \le 1000000$

SAMPLE INPUT

abaca cdbda

SAMPLE OUTPUT

YES

Explanation

The string **abaca** can be converted to **bcbda** in one move and to **cdbda** in the next move.

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
    #include<string.h>
 3
    int main()
 4 *
    {
         char str1[1000000], str2[1000000];
 5
 6
         int flag=1;
         scanf("%s",str1);
 7
 8
         scanf("%s", str2);
 9
         int a=strlen(str1);
10
         int b=strlen(str2);
         if(a==b)
11
12 1
         {
             for(int i=a-1;i>=0;i--)
13
14 v
                 while(str1[i]!=str2[i])
15
16 +
17
                      for(int j=0;j<=i;j++)
18 *
19
                          if(str1[j]<'z')
                          str1[j]++;
20
                          else
21
22 4
                              flag=0;
23
                              break;
24
25
                          if(flag==0)
26
                          break;
27
28
29
                 }
30
             }
31
         }
32
        else
33
         flag=0;
        if(flag==0)
34
        printf("NO");
35
36
        else
        printf("YES");
37
         return 0;
38
39
   |}
```

| | Input | Expected | GVT | |
|---|----------------|----------|-----|---|
| ~ | abaca cdbda | YES | YES | ~ |

Questivn **2**Correct Marked out of 1.00 Flag questivn

Danny has a possible list of passwords of Manny's facebook account. All passwords length is odd. But Danny knows that Manny is a big fan of palindromes. So, his password and reverse of his password both should be in the list.

You have to print the length of Manny's password and it's widdle character.

Note: The solution will be unique.

INPUT

The first line of input contains the integer N, the number of possible passwords.

Each of the following N lines contains a single word, its length being an odd number greater than 2 and lesser than 14. All characters are lowercase letters of the English alphabet.

OUTPUT

The first and vnly line of output must contain the length of the correct password and its central letter.

CONSTRAINTS

 $1 \le N \le 100$

SAMPLE INPUT

4 abc def feg cba

SAMPLE OUTPUT

35

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
 2
    #include<string.h>
 3
    int main()
 4 *
 5
        int n,flag=0;
 6
        char temp;
        scanf("%d",&n);
 7
 8
        char words[n][14];
 9
         for(int i=0;i<n;i++)
10
        scanf("%s",words[i]);
11
        char reverse[14];
12
         for(int i=0;i<n-1;i++)
13 ,
14
             strcpy(reverse,words[i]);
15
             int size=strlen(reverse);
16
             for(int k=0; k<size/2; k++)</pre>
17 ,
             {
18
                  temp=reverse[k];
19
                 reverse[k]=reverse[size-k-1];
20
                 reverse[size-k-1]=temp;
21
22
             for(int i=i+1 · i < n · i + + )</pre>
```

```
21
             }
             for(int j=i+1;j<n;j++)</pre>
22
23 4
                 if(strcmp(reverse,words[j])==
24
25
26
                      flag=1;
27
                      break;
28
29
30
             if(flag==1)
31
             break;
32
33
         int len=strlen(reverse);
         printf("%d %c ",len,reverse[len/2]);
34
35
         return 0;
36
    }
```

| | Input | Expected | Got | |
|---|-------------------------------|----------|-----|---|
| ~ | 4 abc def feg cba | 3 b | 3 b | ~ |

Questivn 3

Cvrrect

Marked vut vf

1.00

P Flag

questivn

Jvey loves to eat Pizza. But he is worried as the quality of pizza made by most of the restaurants is deteriorating. The last few pizzas ordered by him did not taste good: (. Jvey is feeling extremely hungry and wants to eat pizza. But he is confused about the restaurant from where he should order. As always he asks Chandler for help.

Chandler suggests that Jvey should give each restaurant some points, and then choose the restaurant having **maximum points**. If more than one restaurant has same points, Jvey can choose the one with **lexicographically smallest** name.

Jvey has assigned points to all the restaurants, but can't figure out which restaurant satisfies Chandler's criteria. Can you help him out?

Input:

First line has N, the total number of restaurants.

Next N lines contain Name of Restaurant and Points awarded by Joey, separated by a space. Restaurant name has **no spaces**, all lowercase letters and will not be more than 20 characters.

Output:

Print the name of the restaurant that Joey should choose.

Constraints:

```
1 <= N <= 10^5
1 <= Pvints <= 10^6
```

SAMPLE INPUT

3 Pizzeria 108 Dvminvs 145

Pizzapizza 49

SAMPLE OUTPUT

Dominos

Explanation

Dominos has maximum points.

Answer: (penalty regime: 0 %)

```
1 |#include<stdio.h>
   #include<string.h>
 2
   int main()
 3
 4 * {
 5
        int n;
        scanf("%d",&n);
 6
 7
        char res[n][21];
 8
        int rate[n];
 9
        for(int i=0;i<n;i++)</pre>
10 v
             scanf("%s",res[i]);
11
            scanf("%d",&rate[i]);
12
13
        }
14
        int max=rate[0];
15
        char ans[20];
16
        strcpy(ans,res[0]);
17
        for(int i=1;i<n;i++)</pre>
18 *
19
            if(rate[i]>max)
20 v
             {
21
                 max=rate[i];
22
                strcpy(ans,res[i]);
23
            }
24
            else if(rate[i]==max)
25 *
26
                 if(strcmp(res[i],ans)<0)</pre>
27
                 strcpy(ans,res[i]);
28
29
30
        printf("%s",ans);
31
        return 0;
32 }
```

| | Input | Expected | Gut | |
|---|---------------------------------------------------|----------|---------|---|
| / | 3 Pizzeria 108 Dominos 145 Pizzapizza 49 | Dominos | Dominos | ~ |

Questivn 4
Correct
Marked out of
1.00
Flag
questivn

These days Bechan Chacha is depressed because his crush gave him list of mobile number some of them are valid and some of them are invalid. Bechan Chacha has special power that he can pick his crush number only if he has valid set of mobile numbers. Help him to determine the valid numbers.

You are given a string "S" and you have to determine whether it is Valid mobile number or not. Mobile number is valid only if it is of length 10, consists of numeric values and it shouldn't have prefix zeroes.

Input:

First line of input is T representing total number of test cases.

Next T line each representing "S" as described in in problem statement.

Output:

Print "YES" if it is valid mubile number else print "NO". Nute: Quutes are fur clarity.

Constraints:

$$1 \le T \le 10^3$$

sum of string length $\le 10^5$

SAMPLE INPUT

SAMPLE OUTPUT

```
0123456.87
```

SAMPLE OUTPUT

YES

NO

NO

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
 2
    #include<string.h>
 3
   int main()
 4 * {
 5
        int t;
        scanf("%d",&t);
 6
 7
        while(t--)
 8 *
        {
 9
             int flag=1;
10
             char s[1000000];
             scanf("%s",s);
11
12
             int k=strlen(s);
13
             if(k==10)
14 +
             {
15
                 for(int i=0;i<10;i++)
16 v
                     if(s[0]=='0')
17
18 *
                     {
                         flag=0;
19
20
                         break;
21
                     }
22
                     if(s[i]<'0'||s[i]>'9')
23 *
                     {
                          flag=0;
24
                         break;
25
26
                     }
27
                 }
28
             }
29
             else
30
             flag=0;
             if(flag==1)
31
             printf("YES\n");
32
             else
33
             printf("NO\n");
34
35
        return 0;
36
37
   }
```

| | Input | Expected | Gvt | |
|---|------------|----------|-----|---|
| / | 3 | YES | YES | ~ |
| | 1234567890 | NO | NO | |
| | 0123456789 | NO | NO | |
| | 0123456.87 | | | |

Passed all tests! <