




End of Line Report					Confidentiality Note: This report contains proprietary and confidential information intended solely for the use of authorized personnel. Any unauthorized disclosure, distribution, or reproduction of this document or its contents is strictly prohibited.					 ABHINAVA RIZEL						
Program Name:		Firefly		Motor Code:											ML2A05B-51V	
Tested Date:		30-Apr-26		Serial no:		P49										
Datasheet				Back-EMF				Validation Checklist								
Parameter	Golden Sample	DUT	Deviation	Speed	AVG	DUT	Deviation	Parameter	Compliance							
Model	ML2A05B-51V_P39&P40		P49	-	500	4.44	4.47	0.63%	Back EMF						OK	
Nominal DC Voltage	52		52	-	1000	8.89	8.81	-0.92%	Peak Power						OK	
Peak Power	10.80		11.23	-	1500	13.33	13.18	-1.18%	Peak Torque						OK	
Peak Torque	63.64		65.42	-	2000	17.78	17.55	-1.29%	Characterstics Curves						OK	
Peak Current - AC	356.46		360	-	3000	26.67	26.33	-1.25%	Average Efficiency						OK	
Motor Max Speed	7200		7200	-	4000	35.55	35.14	-1.18%								
Document Ref.	EOL - ML2A05B-51V_P39&P40		5000	44.44	43.92	-1.17%										
			5500	48.89	48.36	-1.08%										
Comparison - Torque Specs				Comparison - Power Specs				Comparison - Group Efficiency Specs								
Speed	Golden Sample	DUT	Deviation	Speed	Golden Sample	DUT	Deviation	Speed	Golden Sample	DUT	Diffrence					
500	64.76	65.42	1.02%	500	3.39	3.44	1.55%	500	54.06	52.23	-3.38%					
1000	64.65	65.24	0.92%	1000	6.77	6.87	1.45%	1000	67.82	66.49	-1.95%					
1500	64.60	65.13	0.82%	1500	10.15	10.28	1.35%	1500	74.27	73.24	-1.38%					
2000	53.39	53.36	-0.06%	2000	11.18	11.23	0.47%	2000	80.78	80.34	-0.54%					
3000	31.24	30.91	-1.04%	3000	9.81	9.76	-0.52%	3000	87.75	87.23	-0.58%					
4000	21.53	21.25	-1.30%	4000	9.02	8.95	-0.78%	4000	89.28	88.72	-0.63%					
4500	17.98	17.73	-1.39%	4500	8.47	8.40	-0.87%	4500	90.00	89.40	-0.67%					
5000	15.49	15.26	-1.48%	5000	8.11	8.03	-0.97%	5000	90.37	89.89	-0.53%					
6000	11.71	11.47	-2.01%	6000	7.35	7.24	-1.49%	6000	90.58	89.96	-0.68%					
7000	8.43	8.25	-2.14%	7000	6.18	6.08	-1.62%	7000	90.51	89.66	-0.93%					
Peak Torque (Golden sample & DUT) 				Peak Power (Golden sample & DUT) 				Motor Efficiency (Golden sample & DUT) 								
Integration Details			sin min	1206	cos min	1194	sin max	2957	cos max	2955	sinP-P	1751	cosP-P	1761	Offset	766.0
Electrical PDI			Leakage current(mA)		1.40		Insulation Resistance(MOhms)		9999		Resistance(mOhms)		8.84			
END OF LINE RESULT									PASS		Tested By					
											HRN - 30 April 2026					