




End of Line Report				Confidentiality Note: This report contains proprietary and confidential information intended solely for the use of authorized personnel. Any unauthorized disclosure, distribution, or reproduction of this document or its contents is strictly prohibited.				ABHINAVA RIZEL									
Program Name:		Firefly Motor										Motor Code:		ML2A05-C01			
Motor Model:		ML2A										Serial no:		A260511A000042			
Datasheet				Back-EMF				Validation Checklist									
Parameter	Golden Sample	DUT	Deviation	Speed	Golden Sample	DUT	Deviation	Parameter	Compliance								
Model	ML2A05A-51V_P05	A260511A000042	-	500	4.80	4.85	0.90%	Back EMF	OK								
Nominal DC Voltage	51	51	-	1000	9.50	9.56	0.62%	Peak Power	OK								
Peak Power	6.58	6.71	-	1500	14.26	14.32	0.43%	Peak Torque	OK								
Peak Torque	45.60	46.58	-	2000	18.99	19.08	0.45%	Characterstics Curves	OK								
Peak Current - AC	240	240	-	3000	28.50	28.60	0.35%	Average Efficiency	OK								
Motor Max Speed	7200	7200	-	4000	38.02	38.13	0.30%										
Document Ref.	AR_Golden Sample Report			5000	47.55	47.66	0.24%										
				5500	52.32	52.47	0.29%										
Comparison - Torque Specs				Comparison - Power Specs				Comparison - Group Efficiency Specs									
Speed	Golden Sample	DUT	Deviation	Speed	Golden Sample	DUT	Deviation	Speed	Golden Sample	DUT	Diffrence						
500	45.57	46.58	2.21%	500	2.39	2.44	2.21%	500	51.50	53.11	3.13%						
1000	45.37	45.59	0.49%	1000	4.75	4.77	0.49%	1000	65.87	66.20	0.50%						
1350	41.29	42.17	2.12%	1350	5.84	5.96	2.12%	1350	73.18	75.30	2.90%						
2000	31.41	32.03	1.98%	2000	6.58	6.71	1.98%	2000	81.82	83.95	2.60%						
3000	20.06	20.45	1.93%	3000	6.30	6.42	1.93%	3000	86.51	87.72	1.40%						
4000	14.60	14.83	1.56%	4000	6.12	6.21	1.56%	4000	86.36	88.27	2.22%						
5000	11.43	11.44	0.05%	5000	5.99	5.99	0.05%	5000	86.56	88.57	2.31%						
6000	8.65	8.90	2.86%	6000	5.44	5.59	2.86%	6000	85.83	89.77	4.58%						
6500	8.13	8.37	2.99%	6500	5.53	5.70	2.99%	6500	85.37	88.94	4.17%						
7000	7.37	7.62	3.37%	7000	5.40	5.59	3.37%	7000	85.67	89.04	3.94%						
Peak Torque (Golden sample & DUT) 				Peak Power (Golden sample & DUT) 				Motor Efficiency (Golden sample & DUT) 									
Integration Details			sin min	1204	cos min	1182	sin max	2847	cos max	2852	sinP-P	1643	cosP-P	1670	Offset	766.00	
Electrical PDI			Leakage current(mA)			1.06		Insulation Resistance(MOhms)			9999		RESISTANCE(mOhms)			16.13	
END OF LINE RESULT						PASS			Tested by		Approval						
									GMN-11.05.2026		This is a system-approved document; signatures are not required.						