

Part No.: ML2A

Motor Model: C01

Serial No: 01 Test

Tested By: GRV

Test Date: 2026-06-24

INSPECTION CHECKLIST

| S.NO | DESCRIPTION                                             | SPECIFICATION                                                             | METHOD OF CHECK                | OBSERVED | STATUS |
|------|---------------------------------------------------------|---------------------------------------------------------------------------|--------------------------------|----------|--------|
| 1    | Spigot Seat                                             | 154.90 (0.00/-0.03) mm                                                    | OD Snap gauge                  | —        | —      |
| 2    | Front Mounting Thread                                   | 3x M6×1 - 6H, depth 18.00 mm                                              | Plug gauge check found OK      | —        | —      |
| 3    | Shaft OD Total Runout Wrt Datum B                       | 0.1 mm                                                                    | Total Indicator Reading        | —        | —      |
| 4    | Shaft Front Face to Front Mount Spigot Seating Distance | 28.20 ± 0.50 mm                                                           | Height Gauge                   | —        | —      |
| 5    | Shaft Spline                                            | As per Drawing                                                            | Master Spline                  | —        | —      |
| 6    | Dry Leak Test                                           | at Min. 0.2 bar                                                           | Pressurised air and foam water | —        | —      |
| 7    | Thermister Fuction                                      | Resistance at room temperature                                            | Resistance meter               | —        | —      |
| 8    | Sensor Cable Color Sequence                             | Pin 1 - Red (Vdd (+5V))                                                   | Visual                         | —        | —      |
| 9    | Sensor Cable Color Sequence                             | Pin 2 - White (PT 1000 +ve)                                               | Visual                         | —        | —      |
| 10   | Sensor Cable Color Sequence                             | Pin 3 - Yellow (Sin output)                                               | Visual                         | —        | —      |
| 11   | Sensor Cable Color Sequence                             | Pin 4 - Blue (Cos output)                                                 | Visual                         | —        | —      |
| 12   | Sensor Cable Color Sequence                             | Pin 5 - Black (Common GND)                                                | Visual                         | —        | —      |
| 13   | Sensor Cable Color Sequence                             | Pin 6 - Green (Shield + Wire)                                             | Visual                         | —        | —      |
| 14   | Motor Length                                            | 177.8 (+/- 1.5)                                                           | Height Gauge                   | —        | —      |
| 15   | Motor Weight                                            | 12.1 (+/- 0.15)                                                           | Weight Scale                   | —        | —      |
| 16   | Phase Cable Grommet                                     | Manual Assembly                                                           | Visual                         | —        | —      |
| 17   | Terminal Cover                                          | Manual Assembly                                                           | Visual                         | —        | —      |
| 18   | Terminal Cover Assembly Bolts                           | Manual Assembly                                                           | Visual                         | —        | —      |
| 19   | Phase Cable Assembly Bolts                              | Manual Assembly                                                           | Visual                         | —        | —      |
| 20   | Visual Defects                                          | Free From Rust, Dust, Physical Damage, Loose fitments, Missing Components | Visual                         | —        | —      |
| 21   | Deviations if any                                       | —                                                                         |                                |          |        |

ⓘ This is a system-approved document; signatures are not required.

INSPECTION RESULT:

FAILED

INSPECTED BY: GRV    INSPECTION DATE: 2026-06-24