

END OF LINE REPORT

Confidentiality Note: This report contains proprietary and confidential information intended solely for the use of authorized personnel. Any unauthorized disclosure, distribution, or reproduction of this document or its contents is strictly prohibited.

Program Name: Firefly Motor	Part No.: ML2A	Motor Model: C01	Serial No: 04Test
-----------------------------	----------------	------------------	-------------------

DATASHEET

PARAMETER	GOLDEN SAMPLE	DUT	DEV (%)
Model	C01	C01	—
Nominal DC Voltage	51.00 V	51.96 V	+1.88%
Peak Power	6.00 kW	6.30 kW	+4.93%
Peak Torque	45.00 Nm	45.94 Nm	+2.09%
Peak Current AC	240.00 A	237.43 A	-1.07%
Motor Max Speed	7200 RPM	7200 RPM	+0.00%

PDI (ELECTRICAL)

TEST	ACCEPTANCE	DUT VALUE	STATUS
Hipot Average	< 3.50 mA	3.00	OK
IR Average	≥ 20.00 MΩ	6999.00	OK
Resistance Average	≈ 15.30 mΩ	15.00	OK

BACK-EMF ANALYSIS


PARAMETER	GOLDEN (V)	DUT (V)	DEV (%)
Avg BEMF @ 3000 RPM	28.50	28.15	-1.23%

POSITION SENSOR PARAMETERS


PARAMETER	GOLDEN SAMPLE	DUT	STATUS
Sine Min	1150	1150	OK
Sine Max	2900	2900	OK
Cos Min	1150	1150	OK
Cos Max	2900	2900	OK
Sine P-P	1750	1750	OK
Cos P-P	1750	1750	OK
Offset	766	766	OK

PERFORMANCE CURVES — GOLDEN SAMPLE VS DUT


TORQUE VS SPEED



POWER VS SPEED



EFFICIENCY PROFILE



TORQUE VS SPEED

SPEED (RPM)	GOLDEN (NM)	DUT (NM)	DEV (%)
500	45.57	45.94	+0.81%
1000	45.37	45.90	+1.17%
3000	20.06	20.04	-0.10%
7000	7.37	7.25	-1.63%

POWER VS SPEED

SPEED (RPM)	GOLDEN (KW)	DUT (KW)	DEV (%)
500	2.39	2.41	+0.64%
1000	4.75	4.81	+1.19%
3000	6.30	6.30	-0.07%
7000	5.40	5.31	-1.58%

EFFICIENCY VS SPEED

SPEED (RPM)	GOLDEN (%)	DUT (%)	DEV (%)
500	51.50	52.22	+1.40%
1000	65.87	66.80	+1.41%
3000	86.51	86.77	+0.30%
7000	85.67	85.31	-0.42%

ⓘ This is a system-approved document; signatures are not required.

END OF LINE RESULT:

PASSED

TESTED BY: GRV

TEST DATE: 2026-06-26