

Part No.: ML2A      Motor Model: C01      Serial No: 05Test      Tested By: GRV      Test Date: 2026-06-26

INSPECTION CHECKLIST

| S.NO | DESCRIPTION                                             | SPECIFICATION                                                                   | METHOD OF CHECK                | OBSERVED | STATUS |
|------|---------------------------------------------------------|---------------------------------------------------------------------------------|--------------------------------|----------|--------|
| 1    | Spigot Seat                                             | 154,90 (0,00/-0,03) mm                                                          | OD Snap gauge                  | —        | —      |
| 2    | Front Mounting Thread                                   | 3x M6×1 - 6H, l 18,00 mm                                                        | Plug gauge check found OK      | —        | —      |
| 3    | Shaft OD Total Runout Wrt Datum B                       | 0,1 mm                                                                          | Total Indicator Reading        | —        | —      |
| 4    | Shaft Front Face to Front Mount Spigot Seating Distance | 28,20 ± 0,50 mm                                                                 | Height Gauge                   | —        | —      |
| 5    | Shaft Spline                                            | As per Drawing                                                                  | Master Spline                  | —        | —      |
| 6    | Dry Leak Test                                           | at Min. 0,2 bar                                                                 | Pressurised air and foam water | —        | —      |
| 7    | Thermister Fuction                                      | Resistance at room temperature                                                  | Resistance meter               | —        | —      |
| 8    | Sensor Cable Color Sequence                             | Pin 1 - Red (Vdd (+5V))                                                         | Visual                         | —        | —      |
| 9    | Sensor Cable Color Sequence                             | Pin 2 - White (PT 1000 +ve)                                                     | Visual                         | —        | —      |
| 10   | Sensor Cable Color Sequence                             | Pin 3 - Yellow (Sin output)                                                     | Visual                         | —        | —      |
| 11   | Sensor Cable Color Sequence                             | Pin 4 - Blue (Cos output)                                                       | Visual                         | —        | —      |
| 12   | Sensor Cable Color Sequence                             | Pin 5 - Black (Common GND)                                                      | Visual                         | —        | —      |
| 13   | Sensor Cable Color Sequence                             | Pin 6 - Green (Shield + Wire)                                                   | Visual                         | —        | —      |
| 14   | Motor Length                                            | 177,8 (+/- 1,5)                                                                 | Height Gauge                   | —        | —      |
| 15   | Motor Weight                                            | 14,7 (+/- 0,15)                                                                 | Weight Scale                   | —        | —      |
| 16   | Phase Cable Grommet                                     | Manual Assembly                                                                 | Visual                         | —        | —      |
| 17   | Terminal Cover                                          | Manual Assembly                                                                 | Visual                         | —        | —      |
| 18   | Terminal Cover Assembly Bolts                           | Manual Assembly                                                                 | Visual                         | —        | —      |
| 19   | Phase Cable Assembly Bolts                              | Manual Assembly                                                                 | Visual                         | —        | —      |
| 20   | Visual Defects                                          | Free From Rust, Dust, Physical Damage                                           | Visual                         | —        | —      |
| 21   | Deviations if any                                       | Connector push mount not provided, push mount cable tie provided as alternative |                                |          |        |

ⓘ This is a system-approved document; signatures are not required.

INSPECTION RESULT: **FAILED**      INSPECTED BY: GRV      INSPECTION DATE: 2026-06-26