



US008301612B2

(12) **United States Patent**  
**Barker et al.**

(10) **Patent No.:** **US 8,301,612 B2**  
(45) **Date of Patent:** **\*Oct. 30, 2012**

(54) **SYSTEM AND METHOD FOR STORING  
DOCUMENTS ACCESSED BY MULTIPLE  
USERS IN AN ON-DEMAND SERVICE**

(75) Inventors: **Timothy J Barker**, San Francisco, CA  
(US); **Ryan Lissack**, San Francisco, CA  
(US); **Daniel L Pletter**, Oakland, CA  
(US)

(73) Assignee: **salesforce.com, inc.**, San Francisco, CA  
(US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **13/165,548**

(22) Filed: **Jun. 21, 2011**

(65) **Prior Publication Data**

US 2011/0252314 A1 Oct. 13, 2011

**Related U.S. Application Data**

(63) Continuation of application No. 11/880,197, filed on  
Jul. 20, 2007, now Pat. No. 7,991,790.

(51) **Int. Cl.**  
**G06F 17/30** (2006.01)

(52) **U.S. Cl.** ..... **707/705; 707/626; 707/785; 707/786**

(58) **Field of Classification Search** ..... **707/737,**  
**707/785, 705, 786, 626**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,959,308 B2 10/2005 Gramsamer et al.  
7,818,298 B2 10/2010 Barker et al.

7,836,019 B2	11/2010	Barker et al.	
2002/0019827 A1 *	2/2002	Shiman et al.	707/200
2003/0154387 A1	8/2003	Evans et al.	
2006/0031308 A1	2/2006	Colson et al.	
2006/0053196 A1	3/2006	Spataro et al.	
2006/0136511 A1 *	6/2006	Ngo et al.	707/203
2006/0143558 A1	6/2006	Albornoz et al.	
2007/0061384 A1	3/2007	Harrington et al.	
2007/0100817 A1 *	5/2007	Acharya et al.	707/5
2007/0150515 A1 *	6/2007	Brave et al.	707/104.1
2007/0220417 A1	9/2007	Mathew et al.	
2007/0226204 A1 *	9/2007	Feldman	707/5
2007/0226807 A1 *	9/2007	Ginter et al.	726/27
2007/0260648 A1	11/2007	Friesenhahn et al.	
2008/0104408 A1 *	5/2008	Mayer	713/178
2008/0127310 A1 *	5/2008	Robbins et al.	726/4
2008/0306883 A1 *	12/2008	Baffier et al.	705/400
2009/0024609 A1	1/2009	Barker et al.	

**OTHER PUBLICATIONS**

Title: "NextPage", Date: Jul. 6, 2006 URL: <http://web.archive.org/web/20060706184011/http://nextpage.com/>, Company Address:  
NextPage Global Headquarters, 13997 South Minuteman Drive,  
Draper, UT 84020 (No. of Pages: 6).

\* cited by examiner

*Primary Examiner* — Phong Nguyen


*Assistant Examiner* — Dennis Myint


(74) *Attorney, Agent, or Firm* — David Lewis

(57) **ABSTRACT**

In accordance with embodiments, there are provided mechanisms and methods for storing documents that are being tracked in an on-demand service. These mechanisms and methods for storing documents in an on-demand service can enable embodiments to provide the sharing of documents and the storing of the documents in association with a tag. The ability of embodiments to provide the sharing of documents and the storing can enable an efficient searching for a shared document. In an embodiment, the shared document is categorized upon being stored.

**37 Claims, 15 Drawing Sheets**





**FIG. 1**





FIG. 3






FIG. 4




FIG. 5





FIG. 6






FIG. 8






FIG. 9






FIG. 10





1002 1004 1006 1008 1010 1300

**Korol**

Settings

My Account

Edit User Details

Notification Settings

Change Password

Domain Administration

User Administration

Profile Administration

Document Type Administration

1302

1304

1306

1308

1310

1312

1314

1316

1318

1320

1322

1324

1326

1328

1330

1332

1334

1336

1338

1340

1342

1344

1346

1348

1350

1352

1354

1356

1358

1360

1362

1364

1366

1368

1370

1372

1374

1376

1378

1380

1382

1384

1386

1388

1390

1392

1394

1396

1398

1400

1402

1404

1406

1408

1410

1412

1414

1416

1418

1420

1422

1424

1426

1428

1430

1432

1434

1436

1438

1440

1442

1444

1446

1448

1450

1452

1454

1456

1458

1460

1462

1464

1466

1468

1470

1472

1474

1476

1478

1480

1482

1484

1486

1488

1490

1492

1494

1496

1498

1500

1502

1504

1506

1508

1510

1512

1514

1516

1518

1520

1522

1524

1526

1528

1530

1532

1534

1536

1538

1540

1542

1544

1546

1548

1550

1552

1554

1556

1558

1560

1562

1564

1566

1568

1570

1572

1574

1576

1578

1580

1582

1584

1586

1588

1590

1592

1594

1596

1598

1600

1602

1604

1606

1608

1610

1612

1614

1616

1618

1620

1622

1624

1626

1628

1630

1632

1634

1636

1638

1640

1642

1644

1646

1648

1650

1652

1654

1656

1658

1660

1662

1664

1666

1668

1670

1672

1674

1676

1678

1680

1682

1684

1686

1688

1690

1692

1694

1696

1698

1700

1702

1704

1706

1708

1710

1712

1714

1716

1718

1720

1722

1724

1726

1728

1730

1732

1734

1736

1738

1740

1742

1744

1746

1748

1750

1752

1754

1756

1758

1760

1762

1764

1766

1768

1770

1772

1774

1776

1778

1780

1782

1784

1786

1788

1790

1792

1794

1796

1798

1800

1802

1804

1806

1808

1810

1812

1814

1816

1818

1820

1822

1824

1826

1828

1830

1832

1834

1836

1838

1840

1842

1844

1846

1848

1850

1852

1854

1856

1858

1860

1862

1864

1866

1868

1870

1872

1874

1876

1878

1880

1882

1884

1886

1888

1890

1892

1894

1896

1898

1900

1902

1904

1906

1908

1910

1912

1914

1916

1918

1920

1922

1924

1926

1928

1930

1932

1934

1936

1938

1940

1942

1944

1946

1948

1950

1952

1954

1956

1958

1960

1962

1964

1966

1968

1970

1972

1974

1976

1978

1980

1982

1984

1986

1988

1990

1992

1994

1996

1998

2000

2002

2004

2006

2008

2010

2012

2014

2016

2018

2020

2022

2024

2026

2028

2030

2032

2034

2036

2038

2040

2042

2044

2046

2048

2050

2052

2054

2056

2058

2060

2062

2064

2066

2068

2070

2072

2074

2076

2078

2080

2082

2084

2086

2088

2090

2092

2094

2096

2098

2100

2102

2104

2106

2108

2110

2112

2114

2116

2118

2120

2122

2124

2126

2128

2130

2132

2134

2136

2138

2140

2142

2144

2146

2148

2150

2152

2154

2156

2158

2160

2162

2164

2166

2168

2170

2172

2174

2176

2178

2180

2182

2184

2186

2188

2190

2192

2194

2196

2198

2200

2202

2204

2206

2208

2210

2212

2214

2216

2218

2220

2222

2224

2226

2228

2230

2232

2234

2236

2238

2240

2242

2244

2246

2248

2250

2252

2254

2256

2258

2260

2262

2264

2266

2268

2270

2272

2274

2276

2278

2280

2282

2284

2286

2288

2290

2292

2294

2296

2298

2300

2302

2304

2306

2308

2310

2312

2314

2316

2318

2320

2322

2324

2326

2328

2330

2332

2334

2336

2338

2340

2342

2344

2346

2348

2350

2352

2354

2356

2358

2360

2362

2364

2366

2368

2370

2372

2374

2376

2378

2380

2382

2384

2386

2388

2390

2392

2394

2396

2398

2400

2402

2404

2406

2408

2410

2412

2414

2416

2418

2420

2422

2424

2426

2428

2430

2432

2434

2436

2438

2440

2442

2444

2446

2448

2450

2452

2454

2456

2458

2460

2462

2464

2466

2468

2470

2472

2474

2476

2478

2480

2482

2484

2486

2488

2490

2492

2494

2496

2498

2500

2502

2504

2506

2508

2510

2512

2514

2516

2518

2520

2522

2524

2526

2528

2530

2532

2534

2536

2538

2540

2542

2544

2546

2548

2550

2552

2554

2556

2558

2560

2562

2564

2566

2568

2570

2572

2574

2576

2578

2580

2582

2584

2586

2588

2590

2592

2594

2596

2598

2600

2602

2604

2606

2608

2610

2612

2614

2616

2618

2620

2622

2624

2626

2628

2630

2632

2634

2636

2638

2640

2642

2644

2646

2648

2650

2652

2654

2656

2658

2660

2662

2664

2666

2668

2670

2672

2674

2676

2678

2680

2682

2684

2686

2688

2690

2692

2694

2696

2698

2700

2702

2704

2706

2708

2710

2712

2714

2716

2718

2720

2722

2724

2726

2728

2730

2732

2734

2736

2738

2740

2742

2744

2746

2748

2750

2752

2754

2756

2758

2760

2762

2764

2766

2768

2770

2772

2774

2776

2778

2780

2782

2784

2786

2788

2790

2792

2794

2796

2798

2800

2802

2804

2806

2808

2810

2812

2814

2816

2818

2820

2822

2824

2826

2828

2830

2832

2834

2836

2838

2840

2842

2844

2846

2848

2850

2852

2854

2856

2858

2860

2862

2864

2866

2868

2870

2872

2874

2876

2878

2880

2882

2884

2886

2888

2890

2892

2894

2896

2898

2900

2902

2904

2906

2908

2910

2912

2914

2916

2918

2920

2922

2924

2926

2928

2930

2932

2934

2936

2938

2940

2942

2944

2946

2948

2950

2952

2954

2956

2958

2960

2962

2964

2966

2968

2970

2972

2974

2976

2978

2980

2982

2984

2986

2988

2990

2992

2994

2996

2998

3000

3002

3004

3006

3008

3010

3012

3014

3016

3018

3020

3022

3024

3026

3028

3030

3032

3034

3036

3038

3040

3042

3044

3046

3048

3050

3052

3054

3056

3058

3060

3062

3064

3066

3068

3070

3072

3074

3076

3078

3080

3082

3084

3086

3088

3090

3092

3094

3096

3098

3100

3102

3104

3106

3108

3110

3112

3114

3116

3118

3120

3122

3124

3126

3128

3130

3132

3134

3136

3138

3140

3142

3144

3146

3148

3150

3152

3154

3156

3158

3160

3162

3164

3166

3168

3170

3172

3174

3176

3178

3180

3182

3184

3186

3188

3190

3192

3194

3196

3198

3200

3202

3204

3206

3208

3210

3212

3214

3216

3218

3220

3222

3224

3226

3228

3230

3232

3234

3236

3238

3240

3242

3244

3246

3248

3250

3252

3254

3256

3258

3260

3262

3264

3266

3268

3270

3272

3274

3276

3278

3280

3282

3284

3286

3288

3290

3292

3294

3296

3298

3300

3302

3304

3306

3308

3310

3312

3314

3316

3318

3320

3322

3324

3326

3328

3330

3332

3334

3336

3338

3340

3342

3344

3346

3348

3350

3352

3354

3356

3358

3360

3362

3364

3366

3368

3370

3372

3374

3376

3378

3380

3382

3384

3386

3388

3390

3392

3394

3396

3398

3400

3402

3404

3406

3408

3410

3412

3414

3416

3418

3420

3422

3424

3426

3428

3430

3432

3434

3436

3438

3440

3442

3444

3446

3448

3450

3452

3454

3456

3458

3460

3462

3464

3466

3468

3470

3472

3474

3476

3478

3480

3482

3484

3486

3488

3490

3492

3494

3496

3498

3500

3502

3504

3506

3508

3510

3512

3514

3516

3518

3520

3522

3524

3526

3528

3530

3532

3534

3536

3538

3540

3542

3544

3546

3548

3550

3552

3554

3556

3558

3560

3562

3564

3566

3568

3570

3572

3574

3576

3578

3580

3582

3584

3586

3588

3590

3592

3594

3596

3598

3600

3602

3604

3606

3608

3610

3612

3614

3616

3618

3620

3622

3624

3626

3628

3630

3632

3634

3636

3638

3640

3642

3644

3646

3648

3650

3652

3654

3656

3658

3660

3662

3664

3666

3668

3670

3672

3674

3676

3678

3680

3682

3684

3686

3688

3690

3692

3694

3696

3698

3700

3702

3704

3706

3708

3710

3712

3714

3716

3718

3720

3722

3724

3726

3728

3730

3732

3734

3736

3738

3740

3742

3744

3746

3748

3750

3752

3754

3756

3758

3760

3762

3764

3766

3768

3770

3772

3774

3776

3778

3780

3782

3784

3786

3788

3790

3792

3794

3796

3798

3800

3802

3804

3806

3808

3810

3812

3814

3816

3818

3820

3822

3824

3826

3828

3830

3832

3834

3836

3838

3840

3842

3844

3846

3848

3850

3852

3854

3856

3858

3860

3862

3864

3866

3868

3870

3872

3874

3876

3878

3880

3882

3884

3886

3888

3890

3892

3894

3896

3898

3900

3902

3904

3906

3908

3910

3912

3914

3916

3918

3920

3922

3924

3926

3928

3930

3932

3934

3936

3938

3940

3942

3944

3946

3948

3950

3952

3954

3956

3958

3960

3962

3964

3966

3968

3970

3972

3974

3976

3978

3980

3982

3984

3986

3988

3

1400





FIG. 14






FIG. 16



1

# SYSTEM AND METHOD FOR STORING DOCUMENTS ACCESSED BY MULTIPLE USERS IN AN ON-DEMAND SERVICE

## CROSS REFERENCE TO RELATED APPLICATIONS

This is a continuation of U.S. patent application Ser. No. 11/880,197 entitled SYSTEM AND METHOD FOR STORING DOCUMENTS ACCESSED BY MULTIPLE USERS IN AN ON-DEMAND SERVICE, by Timothy J. Barker et al., filed Jul. 20, 2007, which is incorporated herein by reference in its entirety.

The following commonly owned, co-pending United States patents and patent applications, including the present application, are related to each other. Each of the other patents/applications are incorporated by reference herein in its entirety:

U.S. patent application Ser. No. 11/825,393 entitled SYSTEM AND METHOD FOR TRACKING DOCUMENTS IN AN ON-DEMAND SERVICE, by Timothy Barker et al., filed Jul. 6, 2007;

U.S. patent application Ser. No. 11/880,197 entitled SYSTEM AND METHOD FOR STORING DOCUMENTS ACCESSED BY MULTIPLE USERS IN AN ON-DEMAND SERVICE, by Timothy Barker et al., filed Jul. 20, 2007; and

U.S. patent application Ser. No. 11/893,617 entitled METHOD AND SYSTEM FOR PUSHING DATA TO SUBSCRIBERS IN AN ON-DEMAND SERVICE, by Timothy Barker et al., filed Aug. 15, 2007; and

U.S. patent application Ser. No. 11/879,535 entitled SYSTEM AND METHOD FOR TRACKING DOCUMENTS IN AN ON-DEMAND SERVICE, by Timothy Barker et al., filed Jul. 17, 2007.

## COPYRIGHT NOTICE

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

## FIELD OF THE INVENTION

The current invention relates generally to storing documents in a database network system.

## BACKGROUND

The subject matter discussed in the background section should not be assumed to be prior art merely as a result of its mention in the background section. Similarly, a problem mentioned in the background section or associated with the subject matter of the background section should not be assumed to have been previously recognized in the prior art. The subject matter in the background section merely represents different approaches, which in and of themselves may also be inventions.

In conventional document management systems, users access their documents stored in one logical storage space. A user of such a conventional system typically retrieves documents from, and stores documents on, the system using the user's own systems. A user system might remotely access one of a plurality of server systems that might in turn access the

2

document management system. Document retrieval from the system might include the issuance of a query from the user system to the document management system. The document management system might process such a request received in the form of a query and might send to the user system information about documents stored in the document management system that are relevant to the request. The ability to share documents among multiple individuals, the ability to provide the retrieval of accurate information relating the shared documents, and the ability to deliver this information to the user system are desirable characteristics of document management systems in general.

Unfortunately, such conventional approaches suffer from the flaw that, searching only the shared documents for particular topics of interest may be cumbersome, because the shared documents may be located in many places and because there may be many shared documents. Additionally, a conventional categorization may be inadequate, because the categories may be inappropriate and the categorization decided upon by the classifier, if the classifier is not as familiar with the document as the users, may be inaccurate.

Accordingly, it is desirable to provide improved techniques enabling the storing and searching of a document that is being shared by multiple users of the document management system.

## BRIEF SUMMARY

In accordance with embodiments, there are provided mechanisms and methods for storing documents accessed in an on-demand system. These mechanisms and methods for storing documents in an on-demand service can enable embodiments to provide the capability to locate documents quickly. The documents that are stored are also shared in a manner such that changes to the document are tracked as a safeguard that allows a user to know whether the document that they have in their possession is the most recent version.

In an embodiment and by way of example, a method for storing documents that are shared by a plurality of users on behalf of a plurality of organizations is provided. One embodiment includes receiving an original document to store on behalf of a first organization and adding a tag to the document. The tag is created by the user, and does not need to be a predefined category. The user (e.g., the document's author) creates the tag. A copy of the original document may be stored to document management storage in association with the tag. When the user saves the document, the user is presented with a choice of categories under which to save the document. The location of the document may then be used by the search engine to prune the search and/or as a search criterion. The document is classified in real time, and any user may find the document by going through the classification schedule.

In an embodiment, during the storage process the document is categorized so that the document can be easily located when a search is performed. The original document and the copy of the original document in the document management storage may be tracked by a unique identifier assigned to the original document and a corresponding unique identifier assigned to the copy of the original document stored in the document management storage. The unique identifier assigned to the copy of the original document stored in the document management storage may be tracked using a portion of a database limited to information of the first organization. Coupling with an on-demand database service enables one embodiment to provide automatically limiting access to the document management storage to the first organization

3

and may facilitate searching for the document. Documents tracked on behalf of other organizations may likewise be stored by the same on-demand database service.

In an embodiment, after the user joins the group, documents may be downloaded from the document management storage into the user's system (e.g., into the user's desktop). In an embodiment, when a user opens one of the documents that was downloaded from the document management storage, a check is performed to determine whether the document opened is the most recent version. This check may be performed in an embodiment by comparing unique identifiers of the two copies of the document (e.g., the copy residing on the user's desktop and the copy stored by the document management system). In an embodiment, if the user's copy of the document is not the most recent version, a message may be sent to the user asking if the user wants to have the user's copy updated. In this specification, the terms "up-to-date," "current," and "most recent version" may be used interchangeably to describe various example embodiments and not as limitations.

In an embodiment, an identifier includes an identification portion, and also includes a hashed version of content of the document with which the identifier is associated. The identification portion may be used to identify that two documents at least originated from the same document, but possibly are different versions of the same document. The hashed content may be used to check whether there has been a change in content.

In an embodiment, initially a version number is checked. As a more thorough check, a hash value, such as a checksum, is checked to see if the two document contents are the same. An embodiment automatically checks version numbers to see if the user has the most recent document (as long as the user has network access or another connection to the server-side system for performing the check) without requiring the user consciously logging onto the site and without necessarily opening any browsers. In an embodiment, the identifier is the version number.

While the present invention is described with reference to an embodiment in which techniques for tracking documents in an on-demand service are implemented in a system having an application server providing a front end for an on-demand database service capable of supporting multiple tenants, the present invention is not limited to multi-tenant databases nor deployment on application servers. Embodiments may be practiced using other database architectures, i.e., ORACLE®, DB2®, by IBM and the like without departing from the scope of the embodiments claimed.

Any of the above embodiments may be used alone or together with one another in any combination. Inventions encompassed within this specification may also include embodiments that are only partially mentioned or alluded to or are not mentioned or alluded to at all in this brief summary or in the abstract. Although various embodiments of the invention may have been motivated by various deficiencies with the prior art, which may be discussed or alluded to in one or more places in the specification, the embodiments of the invention do not necessarily address any of these deficiencies. In other words, different embodiments of the invention may address different deficiencies that may be discussed in the specification. Some embodiments may only partially address some deficiencies or just one deficiency that may be discussed in the specification, and some embodiments may not address any of these deficiencies.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the following drawings like reference numbers are used to refer to like elements. Although the following figures

4

depict various examples of the invention, the invention is not limited to the examples depicted in the figures.

FIG. 1 illustrates a block diagram of an example of an environment in which an on-demand document management system and database service might be used;

FIG. 2 illustrates a block diagram of an embodiment of elements of FIG. 1 and various possible interconnections between these elements;

FIG. 3 shows a block diagram of an embodiment of a system including a document management system;

FIG. 4 shows a block diagram of the content stored in memory system of the memory management system;

FIG. 5 shows a block diagram of an embodiment of an ID;

FIG. 6 shows a flowchart of an embodiment of a client-side method of uploading a document;

FIG. 7 shows a flowchart of an embodiment of a server-side method of uploading a document;

FIG. 8 shows a flowchart of an embodiment of a client-side method of searching for a document;

FIG. 9 shows a flowchart of an embodiment of a server-side method of searching for a document;

FIG. 10 shows a screenshot of a homepage of a website for sharing documents;

FIG. 11 shows a screenshot of an example of a search page of a website for sharing documents;

FIG. 12 shows a screenshot of an example of an upload page of a website for sharing documents;

FIG. 13 shows a screenshot of an example of a settings page of a website for sharing documents;

FIG. 14 shows a screenshot of an example of a document page of a website for sharing documents;

FIG. 15 illustrates a flowchart of an embodiment of a method of using the environment of FIG. 1; and

FIG. 16 illustrates a flowchart of a method of making the environment of FIG. 1.

#### DETAILED DESCRIPTION

Systems and methods are provided for storing documents in an on-demand service. One method embodiment includes receiving an original document to store on behalf of a first organization. The document is stored in document management storage in association with a tag. The tag is created by the user, and does not need to be a predefined category. Consequently, the tag may more accurately categorize the document than a predefined category. The user (e.g., the document's author) creates the tag and categorizes the document. Consequently, there is no need for an administrator that may be less familiar with the contents of the document to categorize the document.

The document management storage may be referred to as a "central depository" in some embodiments. In an embodiment, a single "master copy" of each document is stored in the document management storage. Storing the document with a tag enables searching and locating the document in a manner that is more efficient than were the tag not used. In an embodiment, the document is classified when the document is initially stored, which further facilitates locating the document. When the user saves the document, the user may be presented with a choice of categories under which to save the document. The location, category, and or tag of the document may then be used by the search engine to prune the search and/or as a search criterion. The document is classified in real time, and any user may find the document by going through the classification schedule.

Enforcing the "master copy" paradigm enables embodiments to ensure that document versioning is maintained

5

across many different users accessing the document management storage service using any number of different computers. An identifier (ID) is associated with the document when the document is uploaded to the document management storage. In an embodiment, the identifier is embedded into the document. Alternatively, the identifier may be associated with the name or the file identifier of a document using a look up table or other technique. Yet further, the identifier may be in-part determined from characteristics of the document, such as the name, date of creation, size or the like. In an embodiment, each ID is unique system wide and/or across all tenants. In an embodiment, the identifier may be updated each time the document is edited, so by comparing identifiers a determination may be made as to whether two copies of the same document have differences in their respective contents. In an embodiment, when a member (e.g., a user) is added to a group that has access to the document management storage, an application is downloaded onto the user system for tracking documents downloaded from the document management storage and/or for updating documents downloaded to the user system. A tenant is an entity (a person, organization, group of people or other entity) that has an account on the multi-tenant system. The group is a group of people or other entities that have access to the document management storage. The members of a group may be a subset of the members of a tenant, may include multiple tenants, or may include multiple of subsets of different tenants. The documents that are managed and tracked by the document management system may be stored in the document management storage.

In an embodiment, after a user joins a group, documents may be downloaded from the document management storage into the user's system (e.g., to a storage medium on the user's system). In an embodiment, each time the user opens one of the documents that was downloaded from the document management storage, the application checks whether the document opened is the most recent version. The application may perform the check by comparing the IDs of the two copies of the document. In an embodiment, if the user's copy of the document is not the most recent version, a message may be sent to the user asking if the user wants to have the user's copy updated. Conventional approaches frequently try to address the sharing of documents using a system of locks, so that when a first user obtains control of the document, all other users are blocked from accessing the document until the first user releases the document (and frees up the lock). Unfortunately, such conventional approaches suffer from the flaw that subsequent users cannot work on the document once the first user has obtained control of it. Thus, these conventional approaches cannot be made to scale to a large number of users that desire to access a document. In contrast, in an embodiment of the current system locks are not used.

In an embodiment, the ID includes an identification portion, and a hashed version of content of the document. The identification portion identifies that two documents at least originated from the same document, but possibly are different versions of the same original document. The hashed content may be used to check whether there has been a change in content. An application automatically checks the version numbers to see if the user has the most recent document (as long as the user has network access or another connection to the server-side system for performing the check) without requiring the user consciously logging onto the site and without necessarily opening any browsers.

In an embodiment, initially a version number is checked. In alternative embodiments, a hash value, such as a checksum, may be checked to see if the two document contents are the same.

6

As used herein, the term multi-tenant database system refers to those systems in which various elements of hardware and software of the database system may be shared by one or more customers. For example, a given application server may simultaneously process requests for a great number of customers, and a given database table may store rows for a potentially much greater number of customers. As used herein, the term query plan refers to a set of steps used to access information in a database system.

Next, mechanisms and methods for providing for the searching of documents in an on-demand service will be described with reference to example embodiments.

#### System Overview

FIG. 1 illustrates a block diagram of an environment wherein an on-demand document management system and database service might be used. Environment 10 may include user systems 12, network 14, system 16, processor system 17, application platform 18, network interface 20, tenant data storage 22, system data storage 24, program code 26, process space 28, document management system 301, and document management storage 302. In other embodiments, environment 10 may not have all of the components listed and/or may have other elements instead of, or in addition to, those listed above.

Environment 10 is an environment in which an on-demand database service coupled with a document management system exists. User system 12 may be any machine or system that is used by a user to access a database user system. For example, any of user systems 12 can be a handheld computing device, a mobile phone, a laptop computer, a workstation, and/or a network of computing devices. As illustrated in FIG. 1 (and in more detail in FIGS. 2 and 3) user systems 12 might interact via a network 14 with an on-demand database service, which is system 16, coupled with a document management system 301 and document management storage 302.

An on-demand database service, such as system 16, is a pre-established database system that is made available to outside users that do not need to necessarily be concerned with building and/or maintaining the database system, but instead may be available for their use when the users need the database system (e.g., on the demand of the users). Some on-demand database services may store information from one or more tenants into tables of a common database image to form a multi-tenant database system (MTS). Accordingly, "on-demand database service 16" and "system 16" will be used interchangeably herein. A database image may include one or more database objects. A relational database management system (RDMS) or the equivalent may execute storage and retrieval of information against the database object(s). Application platform 18 may be a framework that allows the applications of system 16 to run, such as the hardware and/or software, e.g., the operating system. In an embodiment, on-demand database service 16 may include an application platform 18 that enables creation, managing and executing one or more applications developed by the provider of the on-demand database service, users accessing the on-demand database service via user systems 12, or third party application developers accessing the on-demand database service via user systems 12.

The users of user systems 12 may differ in their respective capacities, and the capacity of a particular user system 12 might be entirely determined by permissions (permission levels) for the current user. For example, where a salesperson is using a particular user system 12 to interact with system 16, that user system has the capacities allotted to that salesperson. However, while an administrator is using that user system to interact with system 16, that user system has the capacities

allotted to that administrator. In an embodiment, a hierarchical role based model is not used. However, in systems with a hierarchical role model, users at one permission level may have access to applications, data, and database information accessible by a lower permission level user, but may not have access to certain applications, database information, and data accessible by a user at a higher permission level. Thus, different users will have different capabilities with regard to accessing and modifying application and database information, depending on a user's security or permission level.

Network 14 is any network or combination of networks of devices that communicate with one another. For example, network 14 can be any one or any combination of a LAN (local area network), WAN (wide area network), telephone network, wireless network, point-to-point network, star network, token ring network, hub network, or other appropriate configuration. As the most common type of computer network in current use is a TCP/IP (Transfer Control Protocol and Internet Protocol) network, such as the global internet-work of networks often referred to as the "Internet" with a capital "I," that network will be used in many of the examples herein. However, it should be understood that the networks that the present invention might use are not so limited, although TCP/IP is a frequently implemented protocol.

User systems 12 might communicate with system 16 using TCP/IP and, at a higher network level, use other common Internet protocols to communicate, such as HTTP, FTP, AFS, WAP, etc. In an example where HTTP is used, user system 12 might include an HTTP client commonly referred to as a "browser" for sending and receiving HTTP messages to and from an HTTP server at system 16. Such an HTTP server might be implemented as the sole network interface between system 16 and network 14, but other techniques might be used as well or instead. In some implementations, the interface between system 16 and network 14 includes load sharing functionality, such as round-robin HTTP request distributors to balance loads and distribute incoming HTTP requests evenly over a plurality of servers. At least as for the users that are accessing that server, each of the plurality of servers has access to the MTS' data; however, other alternative configurations may be used instead.

In one embodiment, system 16, shown in FIG. 1, implements a web-based customer relationship management (CRM) system. For example, in one embodiment, system 16 includes application servers configured to implement and execute CRM software applications as well as provide related data, code, forms, webpages and other information to and from user systems 12 and to store to, and retrieve from, a database system related data, objects, and Webpage content. With a multi-tenant system, data for multiple tenants may be stored in the same physical database object, however, tenant data typically is arranged so that data of one tenant is kept logically separate from that of other tenants so that one tenant does not have access to another tenant's data, unless such data is expressly shared. In certain embodiments, system 16 implements applications other than, or in addition to, a CRM application. For example, system 16 may provide tenant access to multiple hosted (standard and custom) applications, including a CRM application. User (or third party developer) applications, which may or may not include CRM, may be supported by the application platform 18, which manages creation, storage of the applications into one or more database objects and executing of the applications in a virtual machine in the process space of the system 16.

One arrangement for elements of system 16 is shown in FIG. 1, including a network interface 20, application platform 18, tenant data storage 22 for tenant data 23, system data

storage 24 for system data 25 accessible to system 16 and possibly multiple tenants, program code 26 for implementing various functions of system 16, and a process space 28 for executing MTS system processes and tenant-specific processes, such as running applications as part of an application hosting service. Additional processes that may execute on system 16 include database indexing processes. System 16 may include document management system 301, which may include document management storage 302 supporting storage and retrieval of documents on behalf of tenants whose data is managed and housed by system 16.

Several elements in the system shown in FIG. 1 include conventional, well-known elements that are explained only briefly here. For example, each user system 12 could include a desktop personal computer, workstation, laptop, PDA, cell phone, or any wireless access protocol (WAP) enabled device or any other computing device capable of interfacing directly or indirectly to the Internet or other network connection. User system 12 typically runs an HTTP client, e.g., a browsing program, such as Microsoft's Internet Explorer browser, Netscape's Navigator browser, Opera's browser, or a WAP-enabled browser in the case of a cell phone, PDA or other wireless device, or the like, allowing a user (e.g., subscriber of the multi-tenant database system) of user system 12 to access, process and view information, pages and applications available to it from system 16 over network 14. Each user system 12 also typically includes one or more user interface devices, such as a keyboard, a mouse, trackball, touch pad, touch screen, pen or the like, for interacting with a graphical user interface (GUI) provided by the browser on a display (e.g., a monitor screen, LCD display, etc.) in conjunction with pages, forms, applications and other information provided by system 16 or other systems or servers. For example, the user interface device can be used to access data and applications hosted by system 16, and to perform searches on stored data, and otherwise allow a user to interact with various GUI pages that may be presented to a user. As discussed above, embodiments are suitable for use with the Internet, which refers to a specific global internetwork of networks. However, it should be understood that other networks can be used instead of the Internet, such as an intranet, an extranet, a virtual private network (VPN), a non-TCP/IP based network, any LAN or WAN or the like.

According to one embodiment, each user system 12 and all of its components are operator configurable using applications, such as a browser, including computer code run using a central processing unit such as an Intel Pentium® processor or the like. Similarly, system 16 (and additional instances of an MTS, where more than one is present) and all of their components might be operator configurable using application(s) including computer code to run using a central processing unit such as processor system 17, which may include an Intel Pentium® processor or the like, and/or multiple processor units. A computer program product embodiment includes a machine-readable storage medium (media) having instructions stored thereon/in which can be used to program a computer to perform any of the processes of the embodiments described herein. Computer code for operating and configuring system 16 to intercommunicate and to process webpages, applications and other data and media content as described herein are preferably downloaded and stored on a hard disk, but the entire program code, or portions thereof, may also be stored in any other volatile or non-volatile memory medium or device as is well known, such as a ROM or RAM, or provided on any media capable of storing program code, such as any type of rotating media including floppy disks, optical discs, digital versatile disk (DVD), compact disk (CD),

9

microdrive, and magneto-optical disks, and magnetic or optical cards, nanosystems (including molecular memory ICs), or any type of media or device suitable for storing instructions and/or data. Additionally, the entire program code, or portions thereof, may be transmitted and downloaded from a software source over a transmission medium, e.g., over the Internet, or from another server, as is well known, or transmitted over any other conventional network connection as is well known (e.g., extranet, VPN, LAN, etc.) using any communication medium and protocols (e.g., TCP/IP, HTTP, HTTPS, Ethernet, etc.) as are well known. It will also be appreciated that computer code for implementing embodiments of the present invention can be implemented in any programming language that can be executed on a client system and/or server or server system such as, for example, C, C++, HTML, any other markup language, Java™, JavaScript, ActiveX, any other scripting language, such as VBScript, and many other programming languages as are well known may be used. (Java™ is a trademark of Sun Microsystems, Inc.).

According to one embodiment, each system 16 is configured to provide webpages, forms, applications, data and media content to user (client) systems 12 to support the access by user systems 12 as tenants of system 16. As such, system 16 provides security mechanisms to keep each tenant's data separate unless the data is shared. If more than one MTS is used, they may be located in close proximity to one another (e.g., in a server farm located in a single building or campus), or they may be distributed at locations remote from one another (e.g., one or more servers located in city A and one or more servers located in city B). As used herein, each MTS could include one or more logically and/or physically connected servers distributed locally or across one or more geographic locations. Additionally, the term "server" is meant to include a computer system, including processing hardware and process space(s), and an associated storage system and database application (e.g., OODBMS or RDBMS) as is well known in the art. It should also be understood that "server system" and "server" are often used interchangeably herein. Similarly, the database object described herein can be implemented as single databases, a distributed database, a collection of distributed databases, a database with redundant online or offline backups or other redundancies, etc., and might include a distributed database or storage network and associated processing intelligence.

FIG. 2 and FIG. 3 also illustrate portions of environment 10. However, in FIGS. 2-3 elements of system 16 and various interconnections in an embodiment are further illustrated. FIG. 2 shows that user system 12 may include processor system 12A, memory system 12B, input system 12C, and output system 12D. FIG. 2 shows network 14 and system 16. FIG. 2 also shows that system 16 may include tenant data storage 22, tenant data 23, system data storage 24, system data 25, User Interface (UI) 30, Application Program Interface (API) 32, PL/SOQL 34, save routines 36, application setup mechanism 38, applications servers 100<sub>1</sub>-100<sub>N</sub>, system process space 102, tenant process spaces 104, tenant management process space 110, tenant storage area 112 (which may also be referred to as "tenant storage space"), user storage 114 (which may also be referred to as "user data"), and application metadata 116. In other embodiments, environment 10 may not have the same elements as those listed above and/or may have other elements instead of, or in addition to, those listed above.

User system 12, network 14, system 16, tenant data storage 22, and system data storage 24 were discussed above in FIG. 1. Regarding user system 12, processor system 12A may be any combination of one or more processors. Memory system

10

12B may be any combination of one or more memory devices, short term, and/or long term memory. Input system 12C may be any combination of input devices, such as one or more keyboards, mice, trackballs, scanners, cameras, and/or interfaces to networks. Output system 12D may be any combination of output devices, such as one or more monitors, printers, and/or interfaces to networks. As shown by FIG. 2, system 16 may include a network interface 20 (of FIG. 1) implemented as a set of HTTP application servers 100, an application platform 18, tenant data storage 22, and system data storage 24. Also shown is system process space 102, including individual tenant process spaces 104 and a tenant management process space 110. Each application server 100 may be configured to tenant data storage 22 and the tenant data 23 therein, and system data storage 24 and the system data 25 therein to serve requests of user systems 12. The tenant data 23 might be divided into individual tenant storage areas 112, which can be either a physical arrangement and/or a logical arrangement of data. Within each tenant storage area 112, user storage 114 and application metadata 116 might be similarly allocated for each user. For example, a copy of a user's most recently used (MRU) items might be stored to user storage 114. Similarly, a copy of MRU items for an entire organization that is a tenant might be stored to tenant storage area 112. A UI 30 provides a user interface and an API 32 provides an application programmer interface to system 16 resident processes to users and/or developers at user systems 12. The tenant data and the system data may be stored in various databases, such as one or more Oracle™ databases.

Application platform 18 includes an application setup mechanism 38 that supports application developers' creation and management of applications, which may be saved as metadata into tenant data storage 22 by save routines 36 for execution by subscribers of one or more tenant process spaces 104 managed by tenant management process 110 for example. Invocations to such applications may be coded using PL/SOQL 34 that provides a programming language style interface extension to API 32. A detailed description of some PL/SOQL language embodiments is discussed in commonly owned co-pending U.S. Provisional Patent Application 60/828,192 entitled, PROGRAMMING LANGUAGE SYSTEM AND METHOD FOR EXTENDING APIS TO EXECUTE IN CONJUNCTION WITH DATABASE APIS, by Craig Weissman, filed Oct. 4, 2006, which is incorporated in its entirety herein for all purposes. Invocations to applications may be detected by one or more system processes, which manage retrieving application metadata 116 for the subscriber making the invocation and executing the metadata as an application in a virtual machine.

Each application server 100 may be communicably coupled to database systems, e.g., having access to system data 25 and tenant data 23, via a different network connection. For example, one application server 100<sub>1</sub> might be coupled via the network 14 (e.g., the Internet), another application server 100<sub>N-1</sub> might be coupled via a direct network link, and another application server 100<sub>N</sub> might be coupled by yet a different network connection. Transfer Control Protocol and Internet Protocol (TCP/IP) are typical protocols for communicating between application servers 100 and the database system. However, it will be apparent to one skilled in the art that other transport protocols may be used to optimize the system depending on the network interconnect used.

In certain embodiments, each application server 100 is configured to handle requests for any user associated with any organization that is a tenant. Because it is desirable to be able to add and remove application servers from the server pool at any time for any reason, there is preferably no server affinity

11

for a user and/or organization to a specific application server **100**. In one embodiment, therefore, an interface system implementing a load balancing function (e.g., an F5 Big-IP load balancer) is communicably coupled between the application servers **100** and the user systems **12** to distribute requests to the application servers **100**. In one embodiment, the load balancer uses a least connections algorithm to route user requests to the application servers **100**. Other examples of load balancing algorithms, such as round robin and observed response time, also can be used. For example, in certain embodiments, three consecutive requests from the same user could hit three different application servers **100**, and three requests from different users could hit the same application server **100**. In this manner, system **16** is multi-tenant, wherein system **16** handles storage of, and access to, different objects, data and applications across disparate users and organizations.

As an example of storage, one tenant might be a company that employs a sales force where each salesperson uses system **16** to manage their sales process. Thus, a user might maintain contact data, leads data, customer follow-up data, performance data, goals and progress data, etc., all applicable to that user's personal sales process (e.g., in tenant data storage **22**). In an example of a MTS arrangement, since all of the data and the applications to access, view, modify, report, transmit, calculate, etc., can be maintained and accessed by a user system having nothing more than network access, the user can manage his or her sales efforts and cycles from any of many different user systems. For example, if a salesperson is visiting a customer and the customer has Internet access in their lobby, the salesperson can obtain critical updates as to that customer while waiting for the customer to arrive in the lobby.

While each user's data might be separate from other users' data regardless of the employers of each user, some data might be organization-wide data shared or accessible by a plurality of users or all of the users for a given organization that is a tenant. Thus, there might be some data structures managed by system **16** that are allocated at the tenant level while other data structures might be managed at the user level. Because a MTS might support multiple tenants including possible competitors, the MTS should have security protocols that keep data, applications, and application use separate. Also, because many tenants may opt for access to a MTS rather than maintain their own system, redundancy, up-time, and backup are additional functions that may be implemented in the MTS. In addition to user-specific data and tenant-specific data, system **16** might also maintain system level data usable by multiple tenants or other data. Such system level data might include industry reports, news, postings, and the like that are sharable among tenants.

In certain embodiments, user systems **12** (which may be client systems) communicate with application servers **100** to request and update system-level and tenant-level data from system **16** that may require sending one or more queries to tenant data storage **22** and/or system data storage **24**. System **16** (e.g., an application server **100** in system **16**) automatically generates one or more SQL statements (e.g., one or more SQL queries) that are designed to access the desired information. System data storage **24** may generate query plans to access the requested data from the database.

Each database can generally be viewed as a collection of objects, such as a set of logical tables, containing data fitted into predefined categories. A "table" is one representation of a data object, and may be used herein to simplify the conceptual description of objects and custom objects according to the present invention. It should be understood that "table" and

12

"object" may be used interchangeably herein. Each table generally contains one or more data categories logically arranged as columns or fields in a viewable schema. Each row or record of a table contains an instance of data for each category defined by the fields. For example, a CRM database may include a table that describes a customer with fields for basic contact information such as name, address, phone number, fax number, etc. Another table might describe a purchase order, including fields for information such as customer, product, sale price, date, etc. In some multi-tenant database systems, standard entity tables might be provided for use by all tenants. For CRM database applications, such standard entities might include tables for Account, Contact, Lead, and Opportunity data, each containing pre-defined fields. It should be understood that the word "entity" may also be used interchangeably herein with "object" and "table".

In some multi-tenant database systems, tenants may be allowed to create and store custom objects, or they may be allowed to customize standard entities or objects, for example by creating custom fields for standard objects, including custom index fields. U.S. patent application Ser. No. 10/817,161, filed Apr. 2, 2004, entitled "Custom Entities and Fields in a Multi-Tenant Database System", and which is hereby incorporated herein by reference, teaches systems and methods for creating custom objects as well as customizing standard objects in a multi-tenant database system. In certain embodiments, for example, all custom entity data rows are stored in a single multi-tenant physical table, which may contain multiple logical tables per organization. It is transparent to customers that their multiple "tables" are in fact stored in one large table or that their data may be stored in the same table as the data of other customers.

The following detailed description will first describe the server-side system for tracking documents. Then the client-side system for tracking documents is described. Next an ID associated with the documents will be described. Then a server-side method of tracking documents will be described. Afterwards a client side method of tracking documents will be described.

#### Server-Side Tracker

FIG. 3 shows a block diagram of an embodiment of system **300**. System **300** may include document management system **301**, which may include document management storage **302** having documents **304a-n** with tags **305a-n** and IDs **306a-n**. Document management system **301** may also include server-side tracker **307**, which in turn may include ID manager **308** and server-side updater **310**. Server-side updater **310** may include compare **312**, server-side communications **314**, and database communications **316**. System **300** may also include network **14** and network devices **318a-m**. Documents **304a-n** may also include or be associated with search fields **320a-n** which may include authors **322a-n** and categories **324a-n**. In other embodiments, system **300** may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

Network **14** was discussed in conjunction with FIGS. 1 and 2. System **300** may be an embodiment of environment **10**. Although in this specification, document management system **301** is described as performing various actions, it should be understood that this is a short hand for stating that the action associated with or performed by document management system **301** is performed via system **16**. Document management system **301** may manage and track documents that are shared by a group of users. Document management storage **302** is a location for storing documents to which multiple people need access. Storing the documents in document management storage **302** may facilitate ensuring that

there is only one master version of the latest, published version of a document and that multiple versions of the document with very different content are not created. Also, document management storage **302** may store historical versions of the document, so that the historical versions are available for access if needed. Additionally, storing the documents in document management storage **302** facilitates providing access to those that need access to the document. In an embodiment, document management storage **302** may be tenant data **114** or a location within tenant data **114**.

Documents **304a-n** are the documents stored in document management storage **302**. Documents **304a-n** may be user created documents, such as articles or sales materials.

Tags **305a-n** are tags that are associated with or added to documents **304a-n**, respectively. Tags **305a-n** may be used for limiting the documents that need to be searched. Tags **305a-n** may be keywords or phrases that one interested in finding documents **304a-n** is likely to associate with documents **304a-n**. Tags **305a-n** tag documents **304a-n**, respectively. Tags **305a-n** are added by the user upon uploading and/or publishing documents **304a-n**, respectively, and may be used as search parameters. The values of tags **305a-n** may be used as values of keys in a database. Using tags **305a-n** may reduce the number of documents that need to be searched, because only documents having the tag values of interest need to be searched.

IDs **306a-n** may uniquely identify each of documents **304a-n** and/or each version of each of documents **304a-n**. Optionally, documents **304a-n** may include multiple versions of one or more of documents **304a-n** in addition to the most recent version of the documents. IDs **306a-n** may include a hashed version of the documents **304a-n**, which may be or may include a checksum of all of the contents of the documents **304a-n**, respectively. Including a checksum of each document's contents in the document's ID allows a determination of whether the content of the document has changed. If the checksum of the ID has not changed, it is unlikely that the content of the document has changed. In an embodiment, the checksum is computed using Message Digest algorithm 5 (MD5), which computes a hash value that has a 128 bits. IDs **306a-n** may include a version number, which may be used as a quick check as to whether the content of the document was changed. If the version number has changed, it is likely that content of the document has also changed. IDs **306a-n** may be included within the metadata of, or otherwise embedded within documents **304a-n**. In an embodiment, IDs **306a-n** may be used as pointers to locations in a database where information about the document is stored. Server-Side Tracker **307** may track and update documents **304a-n**. ID manager **308** creates IDs **306a-n** and updates IDs **306a-n** when there is a change to documents **304a-n**.

Server-side updater **310** communicates with an application on one of network devices **318a-m**. Server-side updater **310** receives requests to determine whether the user's version of a document is the most up-to-date version. Server-side updater **310** sends updates of documents to the user.

Compare **312** performs the comparison of an ID received from a user system **12** (FIG. 1) to one of IDs **306a-n** to determine whether the user's copy of the corresponding one of documents **304a-n** is the most recent. In an embodiment, a checksum may be performed to see if the document has changed. So that the value of the checksum embedded into the document does not affect a subsequent checksum of the document, before a checksum of the document is computed for the first time the identifier 000000000000 is embedded into the document, and the checksum is computed with this identifier present. Then this identifier is updated with the actual check-

sum of the document. When it is desired to recalculate the checksum to determine whether this document is the same as another, this document is temporarily updated by setting the checksum to all zeros. The checksum is then calculated with the temporary identifier. After the new checksum is computed, the new checksum is inserted into the document as the identifier. If the checksums are the same, then the two documents are the same. In other words, to prevent the value of the checksum from affecting the value of a new computation of the checksum, the current value of the checksum is temporarily removed, and the checksum is computed while the document contains all zeros for the checksum. The temporary value for the identifier does not need to be all zeros. The temporary value can be any value as long as the same value is used each time the checksum is created.

Server-side communications **314** handles communications with user systems **12**. Server-side communications **314** may be an interface between server-side tracker **307** and network interface **20** and/or application servers **100<sub>1</sub>-100<sub>N</sub>** (FIG. 2). Optionally, server-side communications **314** may also send a client-side tracker and installation software for installing the client-side tracker to the new users (e.g., one of network devices).

Database communications **316** handles communications with tenant storage **22** (FIG. 2). Database communications **316** may be an interface between server-side tracker and a database server for tenant storage **22**.

Network devices **318a-m** may be embodiments of user systems **12** (FIGS. 1 and 2). The icons used for network devices **318a-m** are suggestive of many different types of network devices (e.g., network appliances), such as laptops, PCs, mobile phones, and PDAs.

Search fields **320a-n** are fields that may be included in the document that may be searched separately from the rest of the document (e.g., without searching the rest of the document). Authors **322a-n** are one example of search fields **320a-n** that may be included in the document. Authors **322a-n** are names of people that are listed as the authors of the documents **304a-n**. Categories **324a-n** are another example of search fields **320a-n**. Categories **324a-n** are categories into which documents **304a-n** may be classified. Each of documents **304a-n** may have one or more tags, one or more authors, and one or more categories. Documents **304a-n** may have other search fields in addition to or instead of authors **322a-n** and categories **324a-n**.

#### Client-Side Tracker

FIG. 4 shows a block diagram of the content stored in memory system **400**. Memory system **400** may include operating system **402**, network client **404**, document **406**, ID **408**, and client-side tracker **410** having document tracker **412**, client-side communications **414**, document tracker **416**, and update instructions **418**. In other embodiments, memory **400** may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

Memory system **400** may be an embodiment of memory system **12B** (FIG. 2), which was discussed above. Operating system **402** may include a set of one or more programs that manage the hardware and software resources of the one of network devices **318a-m** within which memory system **400** is incorporated, by (for example) allocating and managing tasks and internal system resources as a service to users and programs of the system based on input from the user or from that network device.

Network client **404** is an interface for communicating with other systems via network **14**. Network client **404** may use



15

any of a variety of different protocols, such as HTTP, FTP, AFS, or WAP. In an embodiment network client 404 is a browser.

Document 406 may be a copy of a version of one of documents 304a-n (FIG. 3) that was downloaded from document management system 301. ID 408 may be a copy of a version of the one of IDs 306a-n (FIG. 3) that corresponds to the one of documents 304a-n of which document 406 is a copy. ID 408 may have a value that is, or corresponds to, the value that the corresponding one of IDs 306a-n had at the time that the user downloaded or last updated document 406.

Client-side tracker 410 is an application that may update (e.g., synchronize) document 406 to agree with the corresponding one of documents 304a-n (FIG. 3) and may track the opening of document 406. Client-side tracker 410 may be downloaded from document management system 301 (FIG. 3) upon the user joining an organization associated with tenant space 112 and/or upon downloading document 406. Client side tracker 410 may participate in downloading document 406 and may store the locations in memory system 400 where document 406 is stored. Optionally, client-side tracker 410 may track changes in where document 406 is stored. Client-side tracker 410 may monitor the user's system (which is one of network devices 318a-m) for when document 406 is opened, and then client side tracker 410 may send communications to document management system 301 to determine whether document 406 is up-to-date and/or whether the user desires updating document 406.

Client-side communications 414 handles communications with server-side communications 314. Client-side communications 414 sends a request to determine whether document 406 is up-to-date by at least sending ID 408 to document management system 301. Document tracker 416 the portion of code of client-side tracker 410 that tracks the location of the document 406 and monitors the user's system to determine whether document 406 was opened. Document tracker 416 may monitor whether documents that were downloaded are open (or are being opened). Document tracker 416 may, at the file-system level, hook into disk level activity to determine when files are opened, by monitoring areas of memory associated with document 406. In another embodiment, a module may be integrated into the authoring application (such as Microsoft Word) that reads files being opened to determine whether the document being opened was downloaded from document management system 301. Update instructions 418 are instructions for updating document 406. Update instructions 418 may cause the overwriting of an old version of document 406 with a new version of document 406.

An ID

FIG. 5 shows a block diagram of an embodiment of ID 500. ID 500 may include identification portion 501, version number 502 and hash value 504. In other embodiments, ID 500 may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

ID 500 is an embodiment of one of IDs 306a-n. Identification portion 501 identifies the document so that two versions of the same document may be associated within one another as two versions of the same document. In an embodiment, identification portion 501 may be used as a key for locating the document in tenant storage 22. Version number 502 is a value assigned to a current version of one of documents 306a-n. Each time one of documents 306a-n is updated version number 502 is changed. Hash value 504 is the output of a hash function applied to one of documents 306a-n. Hash value 504 may be a checksum of the entire document. Each time one of documents 306a-n is updated its hash value is

16

recalculated. Changes in hash value 504 are indicative of changes in the content of the corresponding one of documents 306a-n.

Client-Side Method of Uploading Document

FIG. 6 shows a flowchart of an embodiment of a client-side method 600 of uploading a document. In step 601, user system 12 sends a request to start a process for uploading a document. For example, user system 12 may send a request to view a page that initiates a process for uploading a document. In step 602, user system 12 receives a field for entering a location of a document on user system 12. In step 604, user system 12 uploads an entry for the field to document management system 301. In step 606, document management system 301 sends a request to upload the file identified by steps 602 and 604. In step 608, a field is received by system 12 for entering a tag. In step 610, an entry for the tag is sent to document management system 301. In step 612, a field is received by user system 12 for entering a classification. In step 614, an entry for the classification is sent to document management system 301. In step 616, one or more fields are received by user system 12 for entering data for one or more search fields and/or settings. In step 618, entries for the one or more search fields and/or settings are sent to document management system 301. In an embodiment, each of the steps of method 600 is a distinct step. In another embodiment, although depicted as distinct steps in FIG. 6, steps 602-618 may not be distinct steps. In other embodiments, method 600 may not have all of the above steps and/or may have other steps in addition to or instead of those listed above. The steps of method 600 may be performed in another order. Subsets of the steps listed above as part of method 600 may be used to form their own method.

Server-Side Method of Uploading Document

FIG. 7 shows a flowchart of an embodiment of a server-side method 700 of uploading a document. In step 701, document management system 301 receives a request to start a process for uploading a document. For example, user system 12 may send a request to view a web page that initiates a process for uploading a document. In step 702, document management system 301 sends a field for entering a location of a document on user system 12. In step 704 document management system 301 uploads an entry for the field to document management system 301. In step 706, document management system 301 receives a request to upload the file identified by step 702 and 704. Also, in step 706, in response to the request the file that was requested to be uploaded is uploaded. In step 708, a field is sent by user system 12 for entering a tag. In step 710, an entry for the tag is received at document management system 301. In step 712, a field is sent by user system 12 for entering a classification. In step 714, an entry for the classification is sent to document management system 301. In step 716, one or more other fields are sent by document management system 301 for entering data for one or more other search fields and/or settings. In step 718, entries for the one or more search fields are received at document management system 301. In step 720, the tag, the categories, and the search fields are associated with the document. Step 720 may include adding the tag, the category information, and/or the search field information to the document and/or storing the tag, the categories, and/or the search information in a database as entries for keys that are associated with document. In step 722, the document uploaded is stored within document management system 301. Step 722 may include setting the path of document to include a resource that is shared by a group of users that includes a group of users to which the user associated with user system 12 is a member. Steps 720 and 722 may part of the same step. For example, the storing of the tag, the



17

categories, and/or the search information in a database as entries for keys that are associated with document may be part of the storing process of step 722. In an embodiment, each of the steps of method 700 is a distinct step. In another embodiment, although depicted as distinct steps in FIG. 7, steps 702-722 may not be distinct steps. In other embodiments, method 700 may not have all of the above steps and/or may have other steps in addition to or instead of those listed above. The steps of method 700 may be performed in another order. Subsets of the steps listed above as part of method 700 may be used to form their own method.

#### Client-Side Method of Searching for Document

FIG. 8 shows a flowchart of an embodiment of a client-side method 800 of searching for a document. In step 801, user system 12 sends a request to start a search for a document. For example, user system 12 may send a request to view a webpage with entry fields for a search query for a document. In step 802, user system 12 receives a field for entering a search term, such as a keyword or keyword combination. In step 804, a field is received by user system 12 for entering a tag. In step 806, a field is received by user system 12 for entering a category. In step 808, one or more fields are received by system 12 for entering data for one or more other filters, such as other search fields. Steps 802, 804, 806, and 808 may be performed by receiving one webpage having fields for entering the search term, the tag, the category, and the other filters. In step 810, user system 12 sends an entry for the tag to document management system 301. In step 812, user system 12 sends an entry for the category to document management system 301. In step 814, user system 12 send entries for one or more search terms are sent to document management system 301. In step 816, user system 12 sends entries for the one or more other filters are sent to document management system 301. Some examples of other filters that may be included as part of step 816 are the authors, the workspace, and/or the format. In step 818, search results are received at user system 12 from document management system 301 based on the information sent in the prior steps of method 800. In an embodiment, after every entry and/or update to any field that affects the search results step 818 is performed again, and new search results are presented. In an embodiment, each of the steps of method 800 is a distinct step. In another embodiment, although depicted as distinct steps in FIG. 8, steps 802-818 may not be distinct steps. In other embodiments, method 800 may not have all of the above steps and/or may have other steps in addition to or instead of those listed above. The steps of method 800 may be performed in another order. Subsets of the steps listed above as part of method 800 may be used to form their own method.

#### Server-Side Method of Searching for Document

FIG. 9 shows a flowchart of an embodiment of a server-side method of searching for a document. In step 901, document management system 301 receives a request to start a search for a document. For example, document management system 301 may receive a request to view a webpage that has fields in which data can be entered for a search query for a document. In step 902, document management system 301 sends a field for entering a search term, such as a keyword or keyword combination. In step 904, document management system 301 sends a field to user system 12 for entering a tag. In step 906, document management system 301 sends a field to user system 12 for entering a category. In step 908, one or more fields are sent from document management system 301 (e.g., via system 16 of FIG. 1) to user system 12 for entering data for one or more other filters, such as other search fields. Steps 902, 904, 906, and 908 may be performed by sending one webpage having fields for entering the search term, the tag,

18

the category, and the other filters. In step 910, document management system 301 receives an entry for a tag from user system 12. In step 912, document management system 301 receives at least one entry for the category from user system 12. In step 914, document management system 301 receives at least one an entry for the search terms from user system 12, which may be keywords. In step 916, document management system 301 receives entries for the one or more other filters from user system 12. In step 918, a query is automatically formulated based on the data received at document management system 301. The query may be a database query. In step 920 results of the query are obtained as a result of implementing the machine instructions that implement the query. Step 918 may include determining which documents correspond to the database keys specified by the query. In step 922, search results are sent from document management system 301 to user system 12.

In an embodiment, each of the steps of method 900 is a distinct step. In another embodiment, although depicted as distinct steps in FIG. 9, steps 902-922 may not be distinct steps. In other embodiments, method 900 may not have all of the above steps and/or may have other steps in addition to or instead of those listed above. The steps of method 900 may be performed in another order. Subsets of the steps listed above as part of method 900 may be used to form their own method.

#### Screen Shots

FIG. 10 shows a homepage 1000 of a website for viewing and updating shared documents. Homepage 1000 may include home tab 1002, search tab 1004, upload tab 1006, subscriptions tab 1008, settings tab 1010, search bar 1012 having search term field 1014, filter 1016, and search button 1018. Homepage 1000 also include workspaces box 1020, my published content box 1022, recently viewed box 1024, recent activity box 1026, my subscriptions box 1028, and popular tags box 1030. In other embodiments, homepage 1000 may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

Homepage 1000 displays a variety of types of information that a user may want to monitor and/or interact with. Homepage 1000 may include links to other pages. In an embodiment, homepage 1000 may include a variety of documents that are located in different boxes. Selecting one of the documents in one of the boxes causes a webpage to be presented that shows information about the document. In an embodiment, when the user's cursor hovers over an icon for one of the documents some of the information listed in the document webpage may be displayed, such as the author and the number of votes received for and/or against the document.

Home tab 1002 is a tab that brings a user to homepage 1000 if the user is not already viewing homepage 1000 and/or refreshes homepage 1000. In other words, although if the user selects home tab 1002 while viewing homepage 1000, the page being viewed remains homepage 1000, but may be refreshed. Additionally, home tab 1002 may also be available from other webpages, and if home tab 1002 is selected while on another webpage, the user is brought to homepage 1000. Search tab 1004, when selected, brings the user to a webpage that allows the user to select other options that related to performing a search (the webpage associated with search tab 1004 is discussed in conjunction with FIG. 11). Upload tab 1006, when selected, brings the user to a webpage that includes links and/or instructions for uploading a file to document management storage 302 (the webpage associated with upload tab 1006 is discussed in conjunction with FIG. 12). Subscription tab 1008 brings the user to a webpage that allows the user to initiate and/or modify a subscription to documents updated and/or published within document man-

agement storage **302**. Settings tab **1010** brings a user to a webpage that allows a user to set and/or modify settings related to documents, the user's account, and/or other accounts (the webpage associated with settings tab **1010** is discussed in conjunction with FIG. **13**).

Search bar **1012** includes one or more links and/or fields that allow a user to formulate a search query. As a result of interacting with search bar **1012**, a search may be conducted for documents meeting the search query that are stored within document management storage **302**. For example, search term field **1014** allows a user to enter a combination of keywords, which may be used as part of a search query, and filter **1016** may allow the user to select from a menu of filters that have already been associated with document management system **301**. Some examples of filters that may be included within filter **1016** are discussed in conjunction with FIG. **12**. In an embodiment, if no filter is selected and filter **1016** is left blank, all search fields, categories, tags, and authors are searched for the keywords that were entered into search term field **1014**.

Search button **1018**, when selected, initiates a search based on a search query formulated from the current entries in search term field **1014** and filter **1016**. After the search has been initiated, document management system **301** switches the webpage presented to user system **12** to the search page, and presents results of the search to the user. After the search webpage is presented to the user, the user is allowed to refine the search. The search page is discussed below in conjunction with FIG. **11**.

Workspaces box **1020** lists work spaces that currently exist. Selecting one of the workspaces causes a list of documents stored in that work space to be presented to the user. In an embodiment, upon presenting a list of the documents in the workspace selected, the webpage presented to the user is changed to the search page.

My published content box **1022** lists the documents that the user published. Recently viewed box **1024** lists documents that user has viewed recently. Recent activity box **1026** lists documents containing recent activity of the user. The information displayed may include whether the document was published, how long ago the document was created or added to document management storage **302**, and the date that the document was released to the public, if the document was released, for example. My subscriptions box **1028** lists documents to which the user has a subscription. Popular tags box **1030** lists the more popular tags that were added and/or associated with various documents. In an embodiment, the tags that are more popular (e.g., the tags that appear in more documents) are presented in a larger font. In an embodiment, the more popular the tag the larger the font.

FIG. **11** shows an example of search page **1100**. Search page **1100** may include home tab **1002**, search tab **1004**, upload tab **1006**, subscriptions tab **1008**, and settings tab **1010**, search bar **1012** having search term field **1014**, filter **1016**, and search button **1018**. Search page **1100** may also include search within field **1102** and filters **1104**. Filters **1104** may include file format **1106**, authors **1108**, tags **1110**, workspaces **1112**, and categories **1114**. Search page **1100** may also include results box **1120**. In other embodiments, search page **1100** may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

Home tab **1002**, search tab **1004**, upload tab **1006**, subscriptions tab **1008**, and settings tab **1010**, search bar **1012** having search term field **1014**, filter **1016**, and search button **1018** were explained above in conjunction with FIG. **10**.

Field **1102** allows the user to enter further search terms. In an embodiment, all search fields, categories, tags, and authors

are searched for the keywords that were entered into search term field **1102**. However, the search is limited to the documents that resulted from the search query formed by words entered into search term field **1014** and filter **1016**, and the search is further limited by the tags, categories, authors, workspaces, or other filters selected by the user. In other words, initially, the documents displayed on search page **1100** may be the results of a search using the search terms in search term field **1014** and the filters of filter **1016**, and the search formed search term field **1102** and any other filters, categories, workspaces, authors, or tags the user selects are used to search the results of the search conducted as a result of entering terms into search term field **1014** and selecting one of the filters of filter **1016**. In an embodiment, if search field term **1014** and filter **1016** are blank all of the documents of document management storage **302** are listed on search page **1100**. Upon entering search terms in field **1102** the documents listed on search page **1100** are further limited to those documents that have the search terms in search term fields **1014** and field **1102** that also are not removed by filter **1016**. Similarly filters **1104** further limit the documents listed on the search page **1100** to those that are not removed by filters **1104**. Tags **1110** may be used to select the tags to which the search results will be limited. Workspaces **1112** allows the user to specify the workspaces from which the search results will be taken. Categories **1114** allows the user to list the categories from which the search results will be taken from. A search for the terms entered into search term field **1102** may be conducted only within documents that (1) have the tags specified by tags **1110**, (2) are within the workspaces specified by work spaces **1112**, and/or (3) that are also within the categories specified by categories **1114**. In other embodiments there may be other combinations of types of filters that are used to formulate the search query. Results box **1120** displays the search result from the search associated with (e.g., entered via) search page **1100**.

FIG. **12** shows an example of upload page **1200**. Upload page **1200** may include home tab **1002**, search tab **1004**, upload tab **1006**, subscriptions tab **1008**, and settings tab **1010**. Upload page **1200** may include browse box **1202**, progress box **1204**, and instructions **1206**. In other embodiments, upload page **1200** may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

Upload page **1200** may be used by one of the members of a group having access to the shared documents for uploading a document, which may be added to document management storage **302** for sharing with the group. Home tab **1002**, search tab **1004**, upload tab **1006**, subscriptions tab **1008**, and settings tab **1010** were explained above in conjunction with FIG. **10**. Browse box **1202** allows a user to browse for a file to upload. Browse box **1202** may be used for locating the document that is to be uploaded. Progress box **1204** displays a list of the documents that are being uploaded and an indication of how much of the document has been uploaded. Instructions **1206** lists instruction for uploading a document.

FIG. **13** shows an example of settings page **1300**. Settings page **1300** may include home tab **1002**, search tab **1004**, upload tab **1006**, subscriptions tab **1008**, and settings tab **1010**. Settings page may include user detail **1302**, notification settings **1304**, change password **1306**, user administration **1308**, profile administrations **1310**, role administration **1312**, document type administration **1314**, and edit box **1316**. In other embodiments, settings page **1300** may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

21

Home tab **1002**, search tab **1004**, upload tab **1006**, subscriptions tab **1008**, and settings tab **1010** were explained above in conjunction with FIG. **10**. User details **1302** may allow the users to enter information about themselves, such as their names, e-mail address, company name, job title, time zone, and the language that the user uses on the website. User details **1302** may include information about the user that is used for setting up an account and/or managing the user's account.

Notification settings **1304** include settings that relate to the form in which the user will be automatically notified of changes to documents and the frequency with which the user will be notified of changes to the document. In an embodiment, the notifications that are associated with notifications settings **1304** may occur regardless of whether the user downloaded or opened a version of the document to user system **12**. Notification settings **1304** may include a choice of whether to send the notification via e-mail, and/or a Really Simple Syndication (RSS) feed. Notification settings **1304** may allow a user to choose whether to receive notification nightly as part of a batch of updates that occurred the previous day or as the changes occur in the document. Notification settings **1304** may allow a user to indicate whether to automatically subscribe the user to any document that the user comments upon. Change password **1306** may allow a user to change their password.

User administration **1308** includes options that allow an administrator to add users and/or remove users. For example, user administration **1308** may include a link that causes the sending of an invitation for a potential user to become a new user of document management system **301**. User administration **1308** may include a link that disables a user, enables a user, and/or resets a password of a user. User administration **1308** may allow an administrator to view a list of users, their e-mail addresses, and/or other information about the users. User administration **1308** may include a field for entering a search string for searching for a user.

Profile administrator **1310** may allow the creation of profiles, removal of profiles, and/or the assignment and/or change of privileges associated with a given profile. A profile assigned to a user may determine the workspaces that the user can access and a combination of one or more roles in which the user can access that workspace. For example, one profile may allow access to workspace A only as a viewer and to workspace B as a commentator. A profile may have a set of actions that are allowed. For example one profile may allow the creation of roles, while another profile may allow the viewing of roles, but not the creation of roles. Each profile may have a set of webpages that are viewable by a user having that profile. For example, one profile may not allow a user to view the settings tab, or may render a settings webpage with fewer options available for modification. A profile may be used for defining a group of users that have access to a particular set of shared documents.

Role administration **1312** allows the administrator to setup and/or edit the roles that are available to be assigned to a user. Role administrator **1312** may allow an administrator to change, add and/or remove the privileges that are associated with each role. Role administrator **1312** may be capable of adding new roles. Some examples of some roles may be viewer, commentator, administrator, and/or application exchange user. A given user may be assigned multiple roles. For example, if a user is assigned only the roles of commentator and viewer, then the user may be allowed to add comments about documents and view documents, but may not have the privileges associated with an administrator or application exchange user.

22

Document type administration **1314** allows the user to edit, add and/or remove the document types that are available for assigning to any given document. A document type is a description of a type of document. A document that is assigned a document type has one or more characteristics that are described by the document type. Some examples of document types may be competitive information, competitive alert, business operations, industry briefing, marketing campaign, research publication, and sales aid. Each document type may have properties associated with that document type. A property is a description of one or more characteristics that are associated with a document type. Examples of the properties associated with a type may be competitor, approved for client use, and industry. Each property may have a list of possible values and the administrator may be able to select whether that list is available to choose in a pick list (or other property values menu), whether the value is a required property of the type, and/or whether the property is available to use as a filter while searching. For example, the document type business operations may have a property titled business operations, which in turn may be capable of assuming the values of attrition, procurement, credit collections, general, and/or order management.

FIG. **14** is a screenshot of an embodiment of a document webpage **1400** for viewing details about a document. Document webpage **1400** includes preview **1402**, author **1404**, creation date **1406**, revision data **1408**, vote **1410**, description **1411**, tags **1412**, workspace **1414**, page link **1416**, subscription indication **1418**, favorites indication **1420**, download button **1422**, revise button **1424**, delete button **1426**, publish to workspace button **1428**, comments tab **1430**, version tab **1432**, subscribers tab **1434** and downloads tab **1436**. In other embodiments, document webpage **1400** may not have all of the elements listed and/or may have other elements instead of or in addition to those listed.

Document webpage **1400** includes information about a document stored in document management storage **302**. Selecting one of the documents in one of the boxes of homepage **1000** or search page **1100** causes a document webpage **1400** to be rendered and thereby presented. Preview **1402** shows an excerpt of the document. Author **1404** includes the name or an identifier of the author of the document. Creation date **1406** is the date at which the document was created or first uploaded to document management system **301**. Revision data **1408** may include the name of the last person to revise the document and/or the date of the most recent revision. Vote **1410** is an indication of how many people voted for and/or against the document. There may also be a link for placing a vote for and/or against the document. Description **1411** may include a brief description of the document. Tags **1412** are a list of tags that are associated with the document. Workspace **1414** is a list of workspaces where the document was stored. Page link **1416** is a link to the location where the document is stored. Subscription indication **1418** indicates whether the current user is subscribed to the document. Subscription indication **1418** may include a button that initiates and/or terminates a subscription to a document. Favorites indication **1420** indicates whether the current user has the document included within the user's list of favorite documents to view, each listing in the favorites list being associated with a link (e.g., a shortcut) to that document. Favorites indication **1420** may include a button that adds and/or removes the document from being on a list of favorite documents to view. Download button **1422** initiates a download of the document from document management system **301** to user system **12**. Revise button **1424** initiates a process that allows the user to revise the document. Delete button **1426**

23

causes the document to be deleted. Publish to workspace **1428** causes the document to be published to a workspace where other members of the group may view and/or edit the document. In step **1428**, a document revised via revise button **1424** may be placed into transitional storage pending approval for publication to the workspace. Comments tab **1430** brings the user to a webpage that allows the user to view comments added by other users and/or add comments about the document. Version tab **1432** brings the user to a webpage that allows the user to view other versions (e.g., older versions) of the document. Subscribers tab **1434** brings the user to a page that allows the user to view a list of subscribers. Method for Using the Environment (FIGS. 1 and 2)

FIG. 15 shows a flowchart of an example of a method **1500** of using environment **10**. In step **1510**, user system **12** (FIGS. 1 and 2) establishes an account. In step **1512**, one or more tenant process space **104** (FIG. 2) are initiated on behalf of user system **12**, which may also involve setting aside space in tenant space **112** (FIG. 2) and tenant data **114** (FIG. 2) for user system **12**. Step **1512** may also involve modifying application metadata to accommodate user system **12**. In step **1514**, user system **12** uploads data. In step **1516**, one or more data objects are added to tenant data **114** where the uploaded data is stored. In step **1518**, methods associated with FIGS. 6-14 may be implemented. The user of method **1500** may represent an organization that is a tenant of system **16** (FIG. 1), and the users of methods associated with FIGS. 6-14 may only be associated with the tenant. In an embodiment, each of the steps of method **1500** is a distinct step. In another embodiment, although depicted as distinct steps in FIG. 15, steps **1502-1518** may not be distinct steps. In other embodiments, method **1500** may not have all of the above steps and/or may have other steps in addition to or instead of those listed above. The steps of method **1500** may be performed in another order. Subsets of the steps listed above as part of method **1500** may be used to form their own method.

Method for Creating the Environment (FIGS. 1 and 2)

FIG. 16 is a method of making environment **10**, in step **1602**, user system **12** (FIGS. 1 and 2) is assembled, which may include communicatively coupling one or more processors, one or more memory devices, one or more input devices (e.g., one or more mice, keyboards, and/or scanners), one or more output devices (e.g., one or more printers, one or more interfaces to networks, and/or one or more monitors) to one another.

In step **1604**, system **16** (FIGS. 1 and 2) is assembled, which may include communicatively coupling one or more processors, one or more memory devices, one or more input devices (e.g., one or more mice, keyboards, and/or scanners), one or more output devices (e.g., one or more printers, one or more interfaces to networks, and/or one or more monitors) to one another. Additionally assembling system **16** may include installing application platform **18**, network interface **20**, tenant data storage **22**, system data storage **24**, system data **25**, program code **26**, process space **28**, UI **30**, API **32**, PL/SOQL **34**, save routine **36**, application setup mechanism **38**, applications servers **100<sub>1</sub>-100<sub>N</sub>**, system process space **102**, tenant process spaces **104**, tenant management process space **110**, tenant space **112**, tenant data **114**, and application metadata **116** (FIG. 2).

In step **1606**, user system **12** is communicatively coupled to network **14**. In step **1608**, system **16** is communicatively coupled to network **14** allowing user system **12** and system **16** to communicate with one another (FIG. 2). In step **1610**, one or more instructions may be installed in system **16** (e.g., the instructions may be installed on one or more machine readable media, such as computer readable media, therein) and/or

24

system **16** is otherwise configured for performing the steps of methods associated with FIGS. 6-14. For example, as part of step **1610**, one or more instructions may be entered into the memory of system **16** for creating document management storage **302**, transferring documents to the document management storage, implementing server-side tracker **307**, generating and updating IDs **306a-n**, uploading documents, storing documents, searching for documents, and/or inviting users to join a group that is authorized to access the document management storage **302** (FIG. 3). In an embodiment, each of the steps of method **1600** is a distinct step. In another embodiment, although depicted as distinct steps in FIG. 16, steps **1602-1608** may not be distinct steps. In other embodiments, method **1600** may not have all of the above steps and/or may have other steps in addition to or instead of those listed above. The steps of method **1600** may be performed in another order. Subsets of the steps listed above as part of method **1600** may be used to form their own method.

Extensions and Alternatives

In an embodiment, a timestamp of the last time that the document was altered may be included in ID **500** instead of, or in addition to, version number **502** and/or hash value **504** (FIG. 5). In an embodiment, only one of version number **502** and hash value **504** is included in ID **500**. In an embodiment, version number **502** is a value that is incremented every time that that document is altered. In an embodiment, version number **502** is a value that is decremented every time that a document is altered.

In an embodiment only the latest approved version of a document is available for viewing by users. For example, a first user downloads a document to their user system. Then a second user updates the document in the system. System **16** may be configured to route document changes entered by the second user to a workflow, so that document changes can be approved before being published. While the document is undergoing an approval workflow (in other words, prior to the changes being approved), if the first user opens the document the first user will not be notified of any of the changes made by the second user, because the first user is still viewing the latest approved document. When the document is approved, the first user would be notified if the document is opened on the first user's desktop.

In an embodiment, the downloading of a document from document management storage **302** (FIG. 3) to the user's system may entail the following steps on the client side. In one of the steps the user sends a request for a copy of one of documents **304a-n** (FIG. 3). In one of the steps, the user's system receives a copy of the document (document **406** of FIG. 4). In one of steps the document is stored in a location in memory **400** (FIG. 4). In one of the steps client-side tracker **410** (FIG. 4) records the location of where document **400** is located, so that client-side tracker **410** only needs to monitor the locations to where the documents were downloaded in order to determine whether one of the documents downloaded from document management system **301** (FIG. 3) was opened. In another embodiment, upon installation or at another time, the user designates a particular location where all documents that were downloaded from document management system **301** will be stored, and when downloading a document from document management system **301**, client-side tracker **410** ensures that the document is stored in the designated location. Alternatively, client-side tracker **410** tracks the entire user system or is triggered to launch by the opening of document **406** (FIG. 4). In an embodiment, the client-side tracker **410** may include a file browser for browsing documents in document management storage **302**.

25

Each embodiment disclosed herein may be used or otherwise combined with any of the other embodiments disclosed. Any element of any embodiment may be used in any embodiment.

While the invention has been described by way of example and in terms of the specific embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. To the contrary, it is intended to cover various modifications and similar arrangements as would be apparent to those skilled in the art. Therefore, the scope of the appended claims should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements.

The invention claimed is:

1. A method for storing documents tracked on behalf of a plurality of organizations, comprising:
  - receiving at a host system, a document to store on behalf of a first organization of the plurality of organizations from a client machine;
  - receiving a tag from the client machine for storing in association with the document;
  - storing in a storage accessible to the host system, the document in association with the tag, the document being stored to document management storage; and
  - associating by the host system, the document in the document management storage with a unique identifier;
  - allowing a level of access to the document to be granted to multiple users that are members of the first organization, the level of access allowing a plurality of users to at least edit the document, and
  - store the document that was edited on the host system as a master copy of the document;
  - wherein the document stored in the document management storage and a location of copies of the document are tracked using a portion of a database limited to information of the first organization;
  - the document has a name; the name, the unique identifier and the tag are different from one another.
2. The method of claim 1, further comprising:
  - applying by the host system, a hash function to the document, therein generating a hash value, and
  - including the hash value within the unique identifier, regardless of the document's author.
3. The method of claim 2, the applying of the hash function and the including of the hash value in the unique identifier are performed in association with the storing of the document in the document management storage.
4. The method of claim 2, the document being a document of a user that is a member of the first organization, the method further comprising:
  - determining whether the document has changed by at least determining whether the hash value of the document has changed.
5. The method of claim 2, further comprising each time the document is updated the hash value of the document is recalculated.
6. The method of claim 2, the document has a name; the name, the unique identifier and the tag are independent of one another.
7. The method of claim 2, further comprising automatically computing the hash value for each document uploaded to the document management storage.
8. The method of claim 1, further comprising: receiving a category and storing the document in association with the category.
9. The method of claim 1, further comprising: sending a request for a value for the tag.

26

10. The method of claim 1, further comprising: entering values for one or more search fields, the one or more search fields being different from the tag.

11. The method of claim 10, the one or more search fields include a field for an author of the document.

12. The method of claim 10, the one or more fields include a name of a workspace.

13. The method of claim 10, the one or more fields including a document format.

14. The system of claim 10, the one or more search fields include a search field for a document format.

15. The method of claim 1, further comprising: associating the document with one or more of a plurality of document types chosen from a list of document types, each document type describing one or more characteristics associated with the document.

16. The method of claim 15, each of the document types including one or more properties associated with a list of properties, each property describing one or more characteristics associated with the document type that is associated with the document.

17. The method of claim 15, wherein the document types can be created and defined by the user.

18. The method of claim 15, wherein the document types include at least competitive information, competitive alert, business operations, industry briefing, marketing campaign, research publication, and sales aid.

19. The method of claim 15, wherein a list of properties is stored in association with a document type, each property of the list of properties being a description of one or more characteristics associated with a particular document type.

20. The method of claim 19, wherein the properties include at least competitor, approved for client use, and industry.

21. The method of claim 1, further comprising:
 

- receiving at a host system, a search query for a document, the search query not including the unique identifier;
- receiving the tag as part of the search query;
- performing a search based on the search query by at least limiting the search to documents that have the tag; and
- returning results of the search.

22. The method of claim 21, the document being associated with one or more of a plurality of document types chosen from a list of document types, each document type describing one or more characteristics associated with the document, the method further comprising:

- receiving a category as part of the search query;

- receiving a property as part of the search query;

- receiving values for one or more search fields, the one or more search fields being different from the tag, the property, and the category;

- identifying database records having the tag as a value of a database key and the category as a value of another database key; and

- searching for the document based on the database records identified and the search query.

23. The method of claim 1, wherein

- the database is a multi-tenant on-demand relational database in which use of the relational database is provided to the tenant as a service,

- the organization exists independently of the database, the organization existed prior to becoming a tenant, and the organization is allowed to store within the portion of the document management storage, multiple documents that are each tracked and that may each be edited by multiple members of the organization; and

- the organization is one of multiple tenants of the multi-tenant database; the portion of the database that is lim-

27

ited to information of the first organization, is one of a plurality of portions of the database, each of the plurality of portions of the database being limited to storing information for a different one of the plurality of organizations.

24. The method claim 1,

the portion of the database that is limited to the first organization includes one or more workspaces;

the storing of the of document in the document management storage includes publishing the document in a workspace selected from the one or more workspaces; and

a given user must be have access to the workspace in which the document is published to have access to the document.

25. The method of claim 1, further comprising allowing the user to freely choose a name of the document, the name of the file not requiring segmentation.

26. The method of claim 1, wherein the unique identifier is associated with a name of the document using a look up table.

27. The method of claim 1, wherein the user of the client machine is presented with a popular tags box that lists one or more tags that have been previously associated with various prior documents stored in the document management storage; the font size for each of the one or more tags listed in the popular tags box is proportional to a prior frequency of use of the one or more tags.

28. The method of claim 1,

the tag is not required to be part of the name and is not required to be part of the unique identifier;

the unique identifier is not required to be part of the name and is required to be part of the tag; and

the name is not required to be part of the tag and is not required to be part of the unique identifier.

29. The method of claim 1, the unique identifier is not required to be segmented.

30. The method of claim 1, the unique identifier of each document is only a hash value.

31. The method of claim 1, further comprising uploading the document and publishing the document to a work prior to assigning a tag.

32. The method of claim 1, further comprising associating a second tag with the document, each tag not being required to have a particular format of content.

33. The method of claim 1, further comprising associating a second tag with the document, each tag a database key for locating the document.

34. A method for storing documents tracked on behalf of a plurality of organizations, comprising:

receiving at a host system, a document to store on behalf of a first organization from a client machine;

sending to the user an interface for creating a tag, the tag is not required to be a particular format;

receiving the tag from the client machine for storing in association with the document;

storing in a storage accessible to the host system, the document in association with the tag, the document being stored to document management storage;

associating by the host system, the document in the document management storage with a unique identifier; and

storing the tag as a value for a database key in a table of the database, the database key being associated via the database with a location of the document;

28

wherein the document stored in the document management storage and copies of the document are tracked using a portion of a database limited to information of the first organization; the document has a name; the name, the unique identifier and the tag are independent of one another.

35. A method for storing documents tracked on behalf of a plurality of organizations, comprising:

receiving at a host system, a document to store on behalf of a first organization of the plurality of organizations from a client machine;

receiving a tag from the client machine for storing in association with the document;

storing in a storage accessible to the host system, the document in association with the tag, the document being stored to document management storage; and

associating by the host system, the document in the document management storage with a unique identifier; and

allowing a group of users access to the document, multiple users from the group being allowed to edit the document, each user being associated with a profile and allowing each profile to specify more than one role, each role being associated with a set of one or more access privileges;

the document has a name; the name, the unique identifier and the tag are independent of one another;

wherein the document stored in the document management storage and a location of copies of the document are tracked using a portion of a database limited to information of the first organization; the document has a name; the name, the unique identifier and the tag are different from one another.

36. A method for storing documents tracked on behalf of a plurality of organizations, comprising:

receiving at a host system, a document to store on behalf of a first organization from a client machine;

receiving a tag from the client machine for storing in association with the document;

storing in a storage accessible to the host system, the document in association with the tag, the document being stored to document management storage; and

associating by the host system, the document in the document management storage with a unique identifier;

wherein the document stored in the document management storage and copies of the document are tracked using a portion of a database limited to information of the first organization;

associating by the host system, the document with one or more of a plurality of document types chosen from a list of document types, each of the document types including one or more properties associated with a list of properties, each property describing one or more characteristics associated with the document type that is associated with the document; and

receiving values for one or more search fields, the one or more search fields being different from the tag, the document types, and the properties; and

the one or more search fields including at least a field for an author of the original document,

a name of a workspace, and

a document format.

37. The method of claim 36, the workspace being one of a plurality of workspaces, each document has only one master document, which is stored in one workspace.

\* \* \* \* \*