



US009286484B2

(12) **United States Patent**  
**Nath**

(10) **Patent No.:** **US 9,286,484 B2**  
(45) **Date of Patent:** **Mar. 15, 2016**

(54) **METHOD AND SYSTEM FOR PROVIDING  
DOCUMENT RETENTION USING  
CRYPTOGRAPHY**

4,757,533 A 7/1988 Allen et al.  
4,796,220 A 1/1989 Wolfe  
4,799,258 A 1/1989 Davies  
4,827,508 A 5/1989 Shear  
4,888,800 A 12/1989 Marshall et al.

(71) Applicant: **INTELLECTUAL VENTURES I  
LLC**, Wilmington, DE (US)

(Continued)

(72) Inventor: **Satyajit Nath**, Cupertino, CA (US)

#### FOREIGN PATENT DOCUMENTS

(73) Assignee: **Intellectual Ventures I LLC**,  
Wilmington, DE (US)

EP 0 672 991 A2 9/1995  
EP 0 674 253 A1 9/1995

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

#### OTHER PUBLICATIONS

(21) Appl. No.: **14/106,223**

"Affect," The American Heritage Dictionary of the English Lan-  
guage, Fourth Edition, Houghton Mifflin Company, 2002. Retrieved  
May 4, 2006 from <http://dictionary.reference.com/search?q=affect>.

(Continued)

(22) Filed: **Dec. 13, 2013**

(65) **Prior Publication Data**

US 2014/0101457 A1 Apr. 10, 2014

*Primary Examiner* — Kaveh Abrishamkar

(74) *Attorney, Agent, or Firm* — Sterne, Kessler, Goldstein  
& Fox P.L.L.C.

#### Related U.S. Application Data

(62) Division of application No. 10/815,251, filed on Mar.  
30, 2004, now Pat. No. 8,613,102.

(51) **Int. Cl.**  
**G06F 21/62** (2013.01)

(52) **U.S. Cl.**  
CPC .... **G06F 21/6209** (2013.01); **G06F 2221/2137**  
(2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**


#### U.S. PATENT DOCUMENTS

4,203,166 A 5/1980 Ehram et al.  
4,734,568 A 3/1988 Watanabe

(57) **ABSTRACT**

Techniques for utilizing security criteria to implement docu-  
ment retention for electronic documents are disclosed. The  
security criteria can also limit when, how and where access to  
the electronic documents is permitted. The security criteria  
can pertain to keys (or ciphers) used to secure (e.g., encrypt)  
electronic files (namely, electronic documents), or to unse-  
cure (e.g., decrypt) electronic files already secured. At least a  
portion of the security criteria can be used to implement  
document retention, namely, a document retention policy.  
After a secured electronic document has been retained for the  
duration of the document retention policy, the associated  
security criteria becomes no longer available, thus preventing  
subsequent access to the secured electronic document. In  
other words, access restrictions on electronic documents can  
be used to prevent access to electronic documents which are  
no longer to be retained.

**15 Claims, 12 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

4,972,472 A	11/1990	Brown et al.	6,044,155 A	3/2000	Thomlinson et al.
5,032,979 A	7/1991	Hecht et al.	6,055,314 A	4/2000	Spies et al.
5,052,040 A	9/1991	Preston et al.	6,058,424 A	5/2000	Dixon et al.
5,058,164 A	10/1991	Elmer et al.	6,061,790 A	5/2000	Bodnar
5,144,660 A	9/1992	Rose	6,069,957 A	5/2000	Richards
5,204,897 A	4/1993	Wyman	6,085,323 A	7/2000	Shimizu et al.
5,220,657 A	6/1993	Bly et al.	6,088,717 A	7/2000	Reed et al.
5,247,575 A	9/1993	Sprague et al.	6,088,805 A	7/2000	Davis et al.
5,276,735 A	1/1994	Boebert et al.	6,098,056 A	8/2000	Rusnak et al.
5,301,247 A	4/1994	Rasmussen et al.	6,101,507 A	8/2000	Cane et al.
5,319,705 A	6/1994	Halter et al.	6,105,131 A	8/2000	Carroll
5,369,702 A	11/1994	Shanton	6,134,327 A	10/2000	Van Oorschot
5,375,169 A	12/1994	Scheidt et al.	6,134,658 A	10/2000	Multerer et al.
5,404,404 A	4/1995	Novorita	6,134,660 A	10/2000	Boneh et al.
5,406,628 A	4/1995	Beller et al.	6,134,664 A	10/2000	Walker
5,414,852 A	5/1995	Kramer et al.	6,141,754 A	10/2000	Choy
5,495,533 A	2/1996	Linehan et al.	6,145,084 A	11/2000	Zuili
5,499,297 A	3/1996	Boebert	6,158,010 A	12/2000	Moriconi et al.
5,502,766 A	3/1996	Boebert et al.	6,161,139 A	12/2000	Win et al.
5,535,375 A	7/1996	Eshel et al.	6,182,142 B1	1/2001	Win et al.
5,557,765 A	9/1996	Lipner et al.	6,185,612 B1	2/2001	Jensen et al.
5,570,108 A	10/1996	McLaughlin et al.	6,185,684 B1	2/2001	Pravetz et al.
5,584,023 A	12/1996	Hsu	6,205,549 B1	3/2001	Pravetz et al.
5,600,722 A	2/1997	Yamaguchi et al.	6,212,561 B1	4/2001	Sitaraman et al.
5,606,663 A	2/1997	Kadooka	6,223,285 B1	4/2001	Komuro et al.
5,655,119 A	8/1997	Davy	6,226,618 B1	5/2001	Downs et al.
5,671,412 A	9/1997	Christiano	6,226,745 B1	5/2001	Wiederhold et al.
5,673,316 A	9/1997	Auerbach et al.	6,240,188 B1	5/2001	Dondeti et al.
5,677,953 A	10/1997	Dolphin	6,249,873 B1	6/2001	Richard et al.
5,680,452 A	10/1997	Shanton	6,253,193 B1	6/2001	Ginter et al.
5,684,987 A	11/1997	Mamiya et al.	6,260,141 B1	7/2001	Park
5,689,718 A	11/1997	Sakurai et al.	6,263,348 B1	7/2001	Kathrow et al.
5,699,428 A	12/1997	McDonnal et al.	6,272,631 B1	8/2001	Thomlinson et al.
5,708,709 A	1/1998	Rose	6,272,632 B1	8/2001	Carmen et al.
5,715,403 A	2/1998	Stefik	6,282,649 B1	8/2001	Lambert et al.
5,717,755 A	2/1998	Shanton	6,289,450 B1 *	9/2001	Pensak et al. .... 713/167
5,720,033 A	2/1998	Deo	6,292,895 B1	9/2001	Baltzley
5,729,734 A	3/1998	Parker et al.	6,292,899 B1	9/2001	McBride
5,745,573 A	4/1998	Lipner et al.	6,295,361 B1	9/2001	Kadansky et al.
5,748,736 A	5/1998	Mittra	6,301,614 B1	10/2001	Najork et al.
5,751,287 A	5/1998	Hahn et al.	6,308,256 B1	10/2001	Folmsbee
5,757,920 A	5/1998	Misra et al.	6,314,409 B2	11/2001	Schnek et al.
5,765,152 A	6/1998	Ericson	6,317,777 B1	11/2001	Skarbo et al.
5,778,065 A	7/1998	Hauser et al.	6,336,114 B1	1/2002	Garrison
5,787,169 A	7/1998	Eldridge et al.	6,339,423 B1	1/2002	Sampson et al.
5,787,173 A	7/1998	Seheidt et al.	6,339,825 B2	1/2002	Pensak et al.
5,787,175 A	7/1998	Carter	6,341,164 B1	1/2002	Dilkie et al.
5,790,789 A	8/1998	Suarez	6,343,316 B1	1/2002	Sakata
5,790,790 A	8/1998	Smith et al.	6,347,374 B1	2/2002	Drake et al.
5,813,009 A	9/1998	Johnson et al.	6,349,337 B1	2/2002	Parsons, Jr. et al.
5,821,933 A	10/1998	Keller et al.	6,351,813 B1	2/2002	Mooney et al.
5,825,876 A	10/1998	Peterson, Jr.	6,353,859 B1	3/2002	McKeehan et al.
5,835,592 A	11/1998	Chang et al.	6,356,903 B1	3/2002	Baxter et al.
5,835,601 A	11/1998	Shimbo et al.	6,356,941 B1	3/2002	Cohen
5,857,189 A	1/1999	Riddle	6,357,010 B1	3/2002	Viets et al.
5,862,325 A	1/1999	Reed et al.	6,363,480 B1	3/2002	Perlman
5,870,468 A	2/1999	Harrison	6,370,249 B1	4/2002	Van Oorschot
5,870,477 A	2/1999	Sasaki et al.	6,381,698 B1	4/2002	Devanbu et al.
5,881,287 A	3/1999	Mast	6,389,433 B1	5/2002	Bolosky et al.
5,892,900 A	4/1999	Ginter et al.	6,389,538 B1	5/2002	Gruse et al.
5,893,084 A	4/1999	Morgan et al.	6,393,420 B1	5/2002	Peters
5,898,781 A	4/1999	Shanton	6,405,315 B1	6/2002	Burns et al.
5,922,073 A	7/1999	Shimada	6,421,714 B1	7/2002	Rai et al.
5,923,754 A	7/1999	Angelo et al.	6,442,688 B1	8/2002	Moses et al.
5,933,498 A	8/1999	Schnek et al.	6,442,695 B1	8/2002	Dutcher et al.
5,944,794 A	8/1999	Okamoto et al.	6,449,721 B1	9/2002	Pensak et al.
5,953,419 A	9/1999	Lohstroh et al.	6,453,353 B1	9/2002	Win et al.
5,968,177 A	10/1999	Batten-Carew et al.	6,466,932 B1	10/2002	Dennis et al.
5,987,440 A	11/1999	O'Neil et al.	6,477,544 B1	11/2002	Bolosky et al.
5,991,879 A	11/1999	Still	6,490,680 B1	12/2002	Scheidt et al.
5,999,907 A	12/1999	Donner	6,505,300 B2	1/2003	Chan et al.
6,014,730 A	1/2000	Ohtsu	6,510,349 B1	1/2003	Schnek et al.
6,023,506 A	2/2000	Ote et al.	6,529,956 B1	3/2003	Smith et al.
6,032,216 A	2/2000	Schmuck et al.	6,530,020 B1	3/2003	Aoki
6,038,322 A	3/2000	Harkins	6,530,024 B1	3/2003	Proctor
			6,542,608 B2	4/2003	Scheidt et al.
			6,549,623 B1	4/2003	Scheidt et al.
			6,550,011 B1	4/2003	Sims
			6,557,039 B1	4/2003	Leong et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,567,914	B1	5/2003	Just et al.	7,003,560	B1	2/2006	Mullen et al.
6,571,291	B1	5/2003	Chow	7,013,332	B2	3/2006	Friedel et al.
6,584,466	B1	6/2003	Serbinis et al.	7,013,485	B2	3/2006	Brown et al.
6,587,946	B1	7/2003	Jakobsson	7,020,645	B2	3/2006	Bisbee et al.
6,588,673	B1	7/2003	Chan et al.	7,024,427	B2	4/2006	Bobbitt et al.
6,594,662	B1	7/2003	Sieffert et al.	7,035,854	B2	4/2006	Hsiao et al.
6,598,161	B1	7/2003	Kluttz et al.	7,035,910	B1	4/2006	Dutta et al.
6,603,857	B1	8/2003	Batten-Carew et al.	7,046,807	B2	5/2006	Hirano et al.
6,608,636	B1	8/2003	Roseman	7,051,213	B1	5/2006	Kobayashi et al.
6,611,599	B2	8/2003	Natarajan	7,058,978	B2	6/2006	Feuerstein et al.
6,615,349	B1	9/2003	Hair	7,073,063	B2	7/2006	Peinado
6,615,350	B1	9/2003	Schell et al.	7,073,073	B1	7/2006	Nonaka et al.
6,625,650	B2	9/2003	Stelliga	7,076,067	B2	7/2006	Raike et al.
6,629,243	B1	9/2003	Kleinman et al.	7,076,312	B2	7/2006	Law et al.
6,633,311	B1	10/2003	Douvikas et al.	7,076,469	B2	7/2006	Schreiber et al.
6,640,307	B2	10/2003	Viets et al.	7,076,633	B2	7/2006	Tormasov et al.
6,646,515	B2	11/2003	Jun et al.	7,080,077	B2	7/2006	Ramamurthy et al.
6,647,388	B2	11/2003	Numao et al.	7,095,853	B2	8/2006	Morishita
6,678,835	B1	1/2004	Shah et al.	7,096,266	B2	8/2006	Lewin et al.
6,687,822	B1	2/2004	Jakobsson	7,099,926	B1	8/2006	Ims et al.
6,711,683	B1	3/2004	Laczko, Sr. et al.	7,107,269	B2	9/2006	Arlein et al.
6,718,361	B1	4/2004	Basani et al.	7,120,635	B2	10/2006	Bhide et al.
6,735,701	B1	5/2004	Jacobson	7,120,757	B2	10/2006	Tsuge
6,738,908	B1	5/2004	Bonn et al.	7,124,164	B1	10/2006	Chemtob
6,775,779	B1	8/2004	England et al.	7,130,964	B2	10/2006	Ims et al.
6,782,403	B1	8/2004	Kino et al.	7,131,071	B2	10/2006	Gune et al.
6,801,999	B1	10/2004	Venkatesan et al.	7,134,041	B2	11/2006	Murray et al.
6,807,534	B1	10/2004	Erickson	7,136,903	B1	11/2006	Phillips et al.
6,807,636	B2	10/2004	Hartman et al.	7,145,898	B1	12/2006	Elliott
6,810,389	B1	10/2004	Meyer	7,146,498	B1	12/2006	Takechi et al.
6,810,479	B1	10/2004	Barlow et al.	7,159,036	B2	1/2007	Hinchliffe et al.
6,816,871	B2	11/2004	Lee	7,171,557	B2	1/2007	Kallahalla et al.
6,826,698	B1	11/2004	Minkin et al.	7,174,563	B1	2/2007	Brownlie et al.
6,834,333	B2	12/2004	Yoshino et al.	7,178,033	B1	2/2007	Garcia
6,834,341	B1	12/2004	Bahl et al.	7,181,017	B1	2/2007	Nagel et al.
6,845,452	B1	1/2005	Roddy et al.	7,185,364	B2	2/2007	Knouse et al.
6,851,050	B2	2/2005	Singhal et al.	7,187,033	B2	3/2007	Pendharkar
6,865,555	B2	3/2005	Novak	7,188,181	B1	3/2007	Squier et al.
6,874,139	B2	3/2005	Krueger et al.	7,194,764	B2	3/2007	Martherus et al.
6,877,136	B2	4/2005	Bess et al.	7,200,747	B2	4/2007	Riedel et al.
6,889,210	B1	5/2005	Vainstein	7,203,317	B2	4/2007	Kallahalla et al.
6,891,953	B1	5/2005	DeMello et al.	7,203,968	B2	4/2007	Asano et al.
6,892,201	B2	5/2005	Brown et al.	7,219,230	B2	5/2007	Riedel et al.
6,892,306	B1	5/2005	En-Seung et al.	7,224,795	B2	5/2007	Takada et al.
6,907,034	B1	6/2005	Begis	7,225,256	B2	5/2007	Villavicencio
6,909,708	B1	6/2005	Krishnaswamy et al.	7,227,953	B2	6/2007	Shida
6,915,434	B1	7/2005	Kuroda et al.	7,233,948	B1	6/2007	Shamoon et al.
6,915,435	B1*	7/2005	Merriam ..... 726/5	7,237,002	B1	6/2007	Estrada et al.
6,920,558	B2	7/2005	Sames et al.	7,249,044	B2	7/2007	Kumar et al.
6,931,450	B2	8/2005	Howard et al.	7,249,251	B2	7/2007	Todd et al.
6,931,530	B2	8/2005	Pham et al.	7,260,555	B2	8/2007	Rossmann et al.
6,931,597	B1	8/2005	Prakash	7,265,764	B2	9/2007	Alben et al.
6,938,042	B2	8/2005	Aboulhosn et al.	7,266,684	B2	9/2007	Jancula
6,941,355	B1	9/2005	Donaghey et al.	7,280,658	B2	10/2007	Amini et al.
6,941,456	B2	9/2005	Wilson	7,287,055	B2	10/2007	Cannata et al.
6,941,472	B2	9/2005	Moriconi et al.	7,287,620	B2	10/2007	Thomas et al.
6,944,183	B1	9/2005	Iyer et al.	7,290,148	B2	10/2007	Tozawa et al.
6,947,556	B1	9/2005	Matyas, Jr. et al.	7,308,702	B1	12/2007	Thomsen et al.
6,950,818	B2	9/2005	Dennis et al.	7,313,824	B1	12/2007	Bala et al.
6,950,936	B2	9/2005	Subramaniam et al.	7,319,752	B2	1/2008	Asano et al.
6,950,941	B1	9/2005	Lee et al.	7,380,120	B1	5/2008	Garcia
6,950,943	B1	9/2005	Bacha et al.	7,383,586	B2	6/2008	Cross et al.
6,952,780	B2	10/2005	Olsen et al.	7,386,529	B2	6/2008	Kiessig et al.
6,957,261	B2	10/2005	Lortz	7,512,810	B1	3/2009	Ryan
6,959,308	B2	10/2005	Gramsamer et al.	7,555,558	B1	6/2009	Kenrich et al.
6,961,849	B1	11/2005	Davis et al.	7,565,683	B1	7/2009	Huang et al.
6,968,060	B1	11/2005	Pinkas	7,681,034	B1	3/2010	Lee et al.
6,971,018	B1	11/2005	Witt et al.	7,729,995	B1	6/2010	Alain et al.
6,978,376	B2	12/2005	Giroux et al.	7,730,543	B1	6/2010	Nath
6,978,377	B1	12/2005	Asano et al.	RE41,546	E	8/2010	Vainstein
6,988,133	B1	1/2006	Zavalkovsky et al.	7,836,310	B1	11/2010	Gutnik
6,988,199	B2	1/2006	Toh et al.	7,890,990	B1	2/2011	Vainstein et al.
6,993,135	B2	1/2006	Ishibashi	7,913,311	B2	3/2011	Alain et al.
6,996,718	B1	2/2006	Henry et al.	7,921,288	B1	4/2011	Hildebrand
7,003,117	B2	2/2006	Kacker et al.	7,921,450	B1	4/2011	Vainstein et al.
				7,950,066	B1	5/2011	Zuili
				8,006,280	B1	8/2011	Hildebrand et al.
				8,065,713	B1	11/2011	Vainstein et al.
				2001/0011254	A1	8/2001	Clark

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2001/0021926 A1 9/2001 Schnek et al.  
 2001/0032181 A1 10/2001 Jakstadt et al.  
 2001/0034839 A1 10/2001 Karjoth et al.  
 2001/0044903 A1 11/2001 Yamamoto et al.  
 2001/0056541 A1\* 12/2001 Matsuzaki et al. .... 713/193  
 2001/0056550 A1 12/2001 Lee  
 2002/0010679 A1 1/2002 Felsher  
 2002/0016922 A1 2/2002 Richards et al.  
 2002/0031230 A1 3/2002 Sweet et al.  
 2002/0035624 A1 3/2002 Kim  
 2002/0046350 A1 4/2002 Lordemann et al.  
 2002/0050098 A1 5/2002 Chan  
 2002/0056042 A1 5/2002 Van Der Kaay et al.  
 2002/0062240 A1 5/2002 Morinville  
 2002/0062245 A1 5/2002 Niu et al.  
 2002/0069077 A1 6/2002 Brophy et al.  
 2002/0069272 A1 6/2002 Kim et al.  
 2002/0069363 A1 6/2002 Winburn  
 2002/0073320 A1 6/2002 Rinkevich et al.  
 2002/0077986 A1 6/2002 Kobata et al.  
 2002/0077988 A1 6/2002 Sasaki et al.  
 2002/0087479 A1 7/2002 Malcolm  
 2002/0099947 A1 7/2002 Evans  
 2002/0124180 A1 9/2002 Hagman  
 2002/0129235 A1 9/2002 Okamoto et al.  
 2002/0133699 A1 9/2002 Pueschel  
 2002/0138762 A1 9/2002 Horne  
 2002/0143710 A1 10/2002 Liu  
 2002/0143906 A1 10/2002 Tormasov et al.  
 2002/0156726 A1 10/2002 Kleckner et al.  
 2002/0157016 A1 10/2002 Russell et al.  
 2002/0169963 A1 11/2002 Seder et al.  
 2002/0169965 A1 11/2002 Hale et al.  
 2002/0172367 A1 11/2002 Mulder et al.  
 2002/0174109 A1 11/2002 Chandy et al.  
 2002/0176572 A1 11/2002 Ananth  
 2002/0178271 A1 11/2002 Graham et al.  
 2002/0194484 A1 12/2002 Bolosky et al.  
 2002/0198798 A1 12/2002 Ludwig et al.  
 2003/0009685 A1 1/2003 Choo et al.  
 2003/0014391 A1 1/2003 Evans et al.  
 2003/0023559 A1 1/2003 Choi et al.  
 2003/0028610 A1 2/2003 Pearson  
 2003/0033528 A1 2/2003 Ozog et al.  
 2003/0037133 A1 2/2003 Owens  
 2003/0037237 A1 2/2003 Abgrall et al.  
 2003/0037253 A1 2/2003 Blank et al.  
 2003/0046238 A1 3/2003 Nonaka et al.  
 2003/0051039 A1 3/2003 Brown et al.  
 2003/0056139 A1 3/2003 Murray et al.  
 2003/0074580 A1 4/2003 Knouse et al.  
 2003/0078959 A1 4/2003 Yeung et al.  
 2003/0079175 A1 4/2003 Limantsev  
 2003/0081784 A1 5/2003 Kallahalla et al.  
 2003/0081787 A1 5/2003 Kallahalla et al.  
 2003/0088517 A1 5/2003 Medoff  
 2003/0088783 A1 5/2003 DiPierro  
 2003/0108883 A1 6/2003 Rondinone et al.  
 2003/0110169 A1 6/2003 Zuili  
 2003/0110266 A1 6/2003 Rollins et al.  
 2003/0110397 A1 6/2003 Supramaniam  
 2003/0115146 A1 6/2003 Lee et al.  
 2003/0115570 A1 6/2003 Bisceglia  
 2003/0120601 A1 6/2003 Ouye  
 2003/0120684 A1 6/2003 Zuili et al.  
 2003/0154381 A1 8/2003 Ouye  
 2003/0159066 A1 8/2003 Staw et al.  
 2003/0177070 A1 9/2003 Viswanath et al.  
 2003/0177378 A1 9/2003 Wittkotter  
 2003/0182579 A1 9/2003 Leporini et al.  
 2003/0196096 A1 10/2003 Sutton  
 2003/0197729 A1 10/2003 Denoue et al.  
 2003/0200202 A1 10/2003 Hsiao et al.  
 2003/0217264 A1 11/2003 Martin et al.  
 2003/0217281 A1 11/2003 Ryan

2003/0217333 A1 11/2003 Smith et al.  
 2003/0226013 A1 12/2003 Dutertre  
 2003/0233650 A1 12/2003 Zaner et al.  
 2004/0022390 A1 2/2004 McDonald et al.  
 2004/0025037 A1 2/2004 Hair  
 2004/0039781 A1 2/2004 LaVallee et al.  
 2004/0064710 A1 4/2004 Vainstein  
 2004/0068524 A1 4/2004 Aboulhosn et al.  
 2004/0068664 A1 4/2004 Nachenberg et al.  
 2004/0073718 A1 4/2004 Johannessen et al.  
 2004/0088548 A1 5/2004 Smetters et al.  
 2004/0098580 A1 5/2004 DeTreville  
 2004/0103202 A1 5/2004 Hildebrand et al.  
 2004/0103280 A1 5/2004 Balfanz et al.  
 2004/0158586 A1 8/2004 Tsai  
 2004/0193602 A1 9/2004 Liu et al.  
 2004/0193905 A1 9/2004 Lirov et al.  
 2004/0193912 A1 9/2004 Li et al.  
 2004/0199514 A1 10/2004 Rosenblatt et al.  
 2004/0215956 A1 10/2004 Venkatachary et al.  
 2004/0215962 A1 10/2004 Douceur et al.  
 2004/0243853 A1 12/2004 Swander et al.  
 2005/0021467 A1 1/2005 Franzdonk  
 2005/0021629 A1 1/2005 Cannata et al.  
 2005/0028006 A1 2/2005 Leser et al.  
 2005/0039034 A1 2/2005 Doyle et al.  
 2005/0071275 A1 3/2005 Vainstein et al.  
 2005/0071657 A1 3/2005 Ryan  
 2005/0071658 A1 3/2005 Nath et al.  
 2005/0081029 A1 4/2005 Thornton et al.  
 2005/0086531 A1 4/2005 Kenrich  
 2005/0091484 A1 4/2005 Thornton et al.  
 2005/0120199 A1 6/2005 Carter  
 2005/0138371 A1 6/2005 Supramaniam  
 2005/0138383 A1 6/2005 Vainstein  
 2005/0177716 A1 8/2005 Ginter et al.  
 2005/0198326 A1 9/2005 Schlimmer et al.  
 2005/0223242 A1 10/2005 Nath  
 2005/0223414 A1 10/2005 Kenrich et al.  
 2005/0256909 A1 11/2005 Aboulhosn et al.  
 2005/0273600 A1 12/2005 Seeman  
 2005/0283610 A1 12/2005 Serret-Avila et al.  
 2005/0288961 A1 12/2005 Tabrizi  
 2006/0005021 A1 1/2006 Torrubia-Saez  
 2006/0075465 A1 4/2006 Ramanathan et al.  
 2006/0093150 A1 5/2006 Reddy et al.  
 2006/0168147 A1 7/2006 Inoue et al.  
 2006/0230437 A1 10/2006 Alexander Boyer et al.  
 2007/0006214 A1 1/2007 Dubal et al.

## FOREIGN PATENT DOCUMENTS

EP 0 809 170 A1 11/1997  
 EP 0 913 966 A2 5/1999  
 EP 0 913 967 A2 5/1999  
 EP 0 950 941 A2 10/1999  
 EP 0 950 941 A3 10/1999  
 EP 1 107 504 B1 6/2001  
 EP 1 107 504 A2 6/2001  
 EP 1 130 492 A2 9/2001  
 EP 1 154 348 A2 11/2001  
 EP 1324565 A1 7/2003  
 GB 2 328 047 A 2/1999  
 JP 2001-036517 2/2001  
 WO WO 96/41288 A1 12/1996  
 WO WO 00/56028 A2 9/2000  
 WO WO 01/61438 A2 8/2001  
 WO WO 01/63387 A2 8/2001  
 WO WO 01/63387 A3 8/2001  
 WO WO 01/77783 A2 10/2001  
 WO WO 01/78285 A1 10/2001  
 WO WO 01/84271 A2 11/2001

## OTHER PUBLICATIONS

"Encrypting File System," from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.  
 "Features of EFS" from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

(56)

**References Cited**

## OTHER PUBLICATIONS

"How EFS work," from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Inside Encrypting file system," Part 1, from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Inside Encrypting file system," Part 2, from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Security Options", Dec. 20, 2001. DC & Co. pp. 1-2.

"Security with Encrypting File System," from MSDN Oct. 2001 version, exact publication date is unknown but believed prior to Dec. 12, 2001.

"Windows 2000 EFS" in the Apr. 1999 issue of Windows NT magazine.

A Real-Time Push-Pull Communications Model for Distributed Real-Time and Multimedia Systems, Jan. 1999, School of Computer Sciences Carnegie Mellon University, Kanaka Juvva, Raj Rajkumar. Adobe Acrobat 5.0 Classroom in a Book, Adobe Press, Jun. 26, 2001, pp. 1-4.

Adobe Acrobat Security Settings, Acrobat 7.0, Nov. 15, 2004 pp. 1-4.

Boneh et al., "Hierarchical Identity Based Encryption with Constant Size Ciphertext," Advances in Cryptology—EUROCRYPT 2005, vol. 3493, Jun. 20, 2005, pp. 440-456.

Boneh et al., "IBE Secure E-mail," Stanford University, Apr. 8, 2002, <http://crypto.stanford.edu/ibe/>.

Crocker, Steven Toye, "Effectuating access policy changes to designated places for secured files," U.S. Appl. No. 10/259,075, filed Sep. 27, 2002.

Crocker, Steven Toye, "Multi-level cryptographic transformations for securing digital assets," U.S. Appl. No. 10/404,566, filed Mar. 31, 2003.

Examination Report, completion date Jun. 18, 2008, for European Patent Application No. EP 02 258 532.7-1244, 6 pgs.

Expiration Mechanism for Chipcards, IBM Technical Disclosure Bulletin, Oct. 1, 2001, UK.

Kenrich, Michael Frederick, "Multi-Level File Digest", U.S. Appl. No. 10/894,493, filed Jul. 19, 2004.

Kinghorn, Gary Mark, "Method and system for protecting electronic data in enterprise environment," U.S. Appl. No. 10/159,220, filed May 31, 2002.

McDaniel et al. "Antigone: A Flexible Framework for Secure Group Communication," Proceedings of the 8th USENIX Security Symposium, Aug. 23, 1999.

Microsoft Press Computer Dictionary, 1997, Microsoft Press, Third Edition, p. 426.

Microsoft Windows 200 server. Windows 2000 Group Policy White Paper, 2000.

Nath, Satyajit, "Method and system for securing digital assets using content type designations," U.S. Appl. No. 10/405,587, filed Apr. 1, 2003.

Prakash, Nalini J., "Method and apparatus for securing/unsecuring files by file crawling," U.S. Appl. No. 10/325,102, filed Dec. 20, 2002.

Rossmann, Alain, "Hybrid systems for securing digital assets," U.S. Appl. No. 10/325,013, filed Dec. 20, 2002.

Search Report, completion date Apr. 14, 2005, for European Patent Application No. EP 02 25 8533, 2 pages.

Search Report, completion date Jul. 6, 2005, for European Patent Application No. EP 02 25 8529, 4 pages.

Search Report, completion date Mar. 16, 2005, for European Patent Application No. EP 02 25 8534, 2 pages.

Search Report, completion date Mar. 2, 2005, for European Patent Application No. EP 02 25 8535, 2 pages.

Search Report, completion date Mar. 3, 2005, for European Patent Application No. EP 02 25 8537, 2 pages.

Search Report, completion date May 12, 2005, for European Patent Application No. EP 02 25 8539, 2 pages.

Search Report, completion date May 8, 2003, for European Patent Application No. EP 02 25 8530, 2 pages.

Search Report, completion date May 8, 2003, for European Patent Application No. EP 02 25 8540, 2 pages.

Search Report, completion date Oct. 2, 2003, for European Patent Application No. EP 02 25 8531, 2 pages.

Search Report, completion date Oct. 8, 2003, for European Patent Application No. EP 02 25 8536, 2 pages.

Stallings, William, "Cryptography and Network Security: Principles and Practice," 1999, pp. 333-337, Second Edition, Prentice Hall, Upper Saddle River, New Jersey.

Symantec. Norton Antivirus Corporate Edition Implementation Guide, 1999.

Wikipedia, "Remote procedure call," web page indexed by archive.org on Feb. 16, 2004; downloaded from [http://web.archive.org/web/20040216160749/http://en.wikipedia.org/wiki/Remote\\_procedure\\_call](http://web.archive.org/web/20040216160749/http://en.wikipedia.org/wiki/Remote_procedure_call) on Nov. 19, 2010.

U.S. Appl. No. 10/074,825, entitled "Method and Apparatus for Accessing Secured Electronic Data Off-line," inventor Lee et al., Feb. 12, 2002, 108 pgs.

U.S. Appl. No. 10/206,737, entitled "Method and System for Updating Keys in a Distributed Security System," inventor Hildebrand, Jul. 26, 2002, 60 pgs.

U.S. Appl. No. 10/259,075, entitled "Effectuating Access Policy Changes to Designated Places for Secured Files," inventor Crocker, Sep. 27, 2002, 60 pgs.

U.S. Appl. No. 10/286,575, entitled "Method and Architecture for Providing Access to Secured Data from Non-Secured Clients," inventor Vainstein, Nov. 1, 2002, 46 pgs.

U.S. Appl. No. 10/368,277, entitled "Method and apparatus for uniquely identifying files," inventor Ouye, Feb. 18, 2003, 25 pgs.

U.S. Appl. No. 10/448,806, entitled "Method and System for Using Remote Headers to Secure Electronic Files" inventor Ryan, May 30, 2003, 35 pgs.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3






FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9




FIG. 10






FIG. 11

# METHOD AND SYSTEM FOR PROVIDING DOCUMENT RETENTION USING CRYPTOGRAPHY

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 10/815,251, filed Mar. 30, 2004, which is incorporated herein by reference.

This application is related to: (i) U.S. patent application Ser. No. 10/815,229, filed Mar. 30, 2004, and entitled "METHOD AND SYSTEM FOR PROVIDING CRYPTOGRAPHIC DOCUMENT RETENTION WITH OFF-LINE ACCESS," which is hereby incorporated herein by reference; (ii) U.S. patent application Ser. No. 10/206,737, filed Jul. 26, 2002, and entitled "METHOD AND SYSTEM FOR UPDATING KEYS IN A DISTRIBUTED SECURITY SYSTEM," which is hereby incorporated herein by reference; (iii) U.S. patent application Ser. No. 10/676,850, filed Sep. 30, 2003, and entitled "METHOD AND SYSTEM FOR SECURING DIGITAL ASSETS USING TIME-BASED SECURITY CRITERIA," which is hereby incorporated herein by reference; (iv) U.S. patent application Ser. No. 10/405,587, filed Apr. 1, 2003, and entitled "METHOD AND SYSTEM FOR SECURING DIGITAL ASSETS USING CONTENT TYPE DESIGNATIONS," which is hereby incorporated herein by reference; (v) U.S. patent application Ser. No. 10/246,079, filed Sep. 17, 2002, and entitled "METHOD AND APPARATUS FOR GENERATING KEYS FROM ACCESS RULES IN A DECENTRALIZED MANNER AND METHODS THEREFOR," which is hereby incorporated herein by reference; (vi) U.S. patent application Ser. No. 10/186,203, filed Jun. 26, 2002, and entitled "METHOD AND SYSTEM FOR IMPLEMENTING CHANGES TO SECURITY POLICIES IN A DISTRIBUTED SECURITY SYSTEM," which is hereby incorporated herein by reference; (vii) U.S. patent application Ser. No. 10/159,537, filed May 5, 2002, and entitled "METHOD AND APPARATUS FOR SECURING DIGITAL ASSETS," which is hereby incorporated herein by reference; and (viii) U.S. patent application Ser. No. 10/127,109, filed Apr. 22, 2002, and entitled "EVALUATION OF ACCESS RIGHTS TO SECURED DIGITAL ASSETS," which is hereby incorporated herein by reference.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to security systems for data and, more particularly, to security systems that protect electronic files in an inter/intra enterprise environment.

### 2. Description of Related Art

The Internet is the fastest growing telecommunications medium in history. This growth and the easy access it affords have significantly enhanced the opportunity to use advanced information technology for both the public and private sectors. It provides unprecedented opportunities for interaction and data sharing among businesses and individuals. However, the advantages provided by the Internet come with a significantly greater element of risk to the confidentiality and integrity of information. The Internet is an open, public and international network of interconnected computers and electronic devices. Without proper security means, an unauthorized person or machine may intercept information traveling across the Internet and even gain access to proprietary information stored in computers that interconnect to the Internet.

There are many efforts in progress aimed at protecting proprietary information traveling across the Internet and controlling access to computers carrying the proprietary information. Cryptography allows people to carry over the confidence found in the physical world to the electronic world, thus allowing people to do business electronically without worries of deceit and deception. Every day millions of people interact electronically, whether it is through e-mail, e-commerce (business conducted over the Internet), ATM machines, or cellular phones. The perpetual increase of information transmitted electronically has led to an increased reliance on cryptography.

One of the ongoing efforts in protecting the proprietary information traveling across the Internet is to use one or more cryptographic techniques to secure a private communication session between two communicating computers on the Internet. The cryptographic techniques provide a way to transmit information across an unsecure communication channel without disclosing the contents of the information to anyone eavesdropping on the communication channel. Using an encryption process in a cryptographic technique, one party can protect the contents of the data in transit from access by an unauthorized third party, yet the intended party can read the encrypted data after using a corresponding decryption process.

A firewall is another security measure that protects the resources of a private network from users of other networks. However, it has been reported that many unauthorized accesses to proprietary information occur from the inside, as opposed to from the outside. An example of someone gaining unauthorized access from the inside is when restricted or proprietary information is accessed by someone within an organization who is not supposed to do so. Due to the open nature of networks, contractual information, customer data, executive communications, product specifications, and a host of other confidential and proprietary intellectual property remain available and vulnerable to improper access and usage by unauthorized users within or outside a supposedly protected perimeter.

Many businesses and organizations have been looking for effective ways to protect their proprietary information. Typically, businesses and organizations have deployed firewalls, Virtual Private Networks (VPNs) and Intrusion Detection Systems (IDS) to provide protection. Unfortunately, these various security means have been proven insufficient to reliably protect proprietary information residing on private networks. For example, depending on passwords to access sensitive documents from within often causes security breaches when the password of a few characters long is leaked or detected. Consequently, various cryptographic means are deployed to provide restricted access to electronic data (namely, electronic documents) in security systems.

Besides restricting access to electronic documents, businesses and organizations also face the difficulty of implementing document retention for electronic documents. In today's heavily regulated business environment, various electronic documents need to be retained for a certain period of time and thereafter may be disposed of. Although conventional approaches are able to retain documents for a period of time and then dispose of them, these conventional approaches require that the retention duration be known and specified. With file security systems that oversee the creation and securing of electronic documents, often the electronic documents have retention periods that depend on future events that are unscheduled. Unfortunately, however, conventional approaches are unable to adequately handle document retention when unscheduled future events are involved.

Therefore, there is a need to provide more effective ways to impose document retention restrictions on electronic resources even when unscheduled future events are involved.

### SUMMARY OF THE INVENTION

The invention relates to techniques for utilizing security criteria to implement document retention for electronic documents. The security criteria can also limit when, how and where access to the electronic documents is permitted. The security criteria can pertain to keys (or ciphers) used to secure (e.g., encrypt) electronic files (namely, electronic documents), or to unsecure (e.g., decrypt) electronic files already secured. At least a portion of the security criteria can be used to implement document retention, namely, a document retention policy. After a secured electronic document has been retained for the duration of the document retention policy, the associated security criteria becomes no longer available, thus preventing subsequent access to the secured electronic document. In other words, access restrictions on electronic documents can be used to prevent access to electronic documents which are no longer to be retained.

In one embodiment, the security criteria can be managed by a document retention system. In another embodiment, the security criteria can be managed more generally by a file security system.

The invention can be implemented in numerous ways, including as a method, system, device, and computer readable medium. Several embodiments of the invention are discussed below.

As a method of providing automated document retention for electronic documents, one embodiment of the invention includes the acts of: obtaining an electronic document; assigning a document retention policy to the electronic document, the document retention policy being based on a future event that is unscheduled; and cryptographically imposing the document retention policy on the electronic document.

As a method for restricting access to an electronic document, one embodiment of the invention includes the acts of: identifying an electronic document to be secured, the electronic document having at least a data portion that contains data; obtaining a document key; encrypting the data portion of the electronic document using the document key to produce an encrypted data portion; obtaining a retention access key, the retention access key being used to enforce a document retention policy on the electronic document; encrypting the document key using the retention access key to produce an encrypted document key; forming a secured electronic document from at least the encrypted data portion and the encrypted document key; and storing the secured electronic document.

As a method for accessing a secured electronic document by a requestor, the secured electronic document having at least a header portion and a data portion, one embodiment of the invention includes the acts of: obtaining a retention access key, the retention access key being used to enforce a document retention policy on the electronic document; obtaining an encrypted document key from the header portion of the secured electronic document; decrypting the encrypted document key using the retention access key to produce a document key; decrypting an encrypted data portion of the secured electronic document using the document key to produce a data portion; and supplying the data portion to the requestor.

As a method for distributing cryptographic keys used in a file security system, one embodiment of the invention includes the acts of: receiving a request for a document retention key that is necessary to gain access to a cryptographically

secured electronic document; identifying a document retention period associated with the document retention key, the document retention period being dependent on a future event that was unscheduled when the document retention period was associated with the electronic document; determining whether the document retention period associated with the document retention key has been exceeded; and refusing to distribute the document retention key in response to the request when it is determined that the document retention period for the electronic document has been exceeded.

As a file security system for restricting access to electronic files, one embodiment of the invention includes at least a key store and an access manager operatively connected to the key store. The key store stores a plurality of cryptographic key pairs. Each of the cryptographic key pairs includes a public key and a private key, and at least one of the cryptographic key pairs pertains to a retention policy that is dependent on a future event. The access manager determines whether the private key of the at least one of the cryptographic key pairs pertaining to the retention policy is permitted to be provided to a requestor based on whether the future event has occurred. The requestor requires the private key of the at least one of the cryptographic key pairs pertaining to the retention policy to access a secured electronic file. The secured electronic file was previously secured using the public key of the at least one of the cryptographic key pairs pertaining to the retention policy, and the future event was unscheduled at the time the electronic file was so secured.

As a computer readable medium including at least computer program code for providing automated data retention for electronic data, one embodiment of the invention includes at least: computer program code for obtaining electronic data; computer program code for assigning a data retention policy to the electronic data, the data retention policy being based on a future event that is unscheduled; and computer program code for cryptographically imposing the data retention policy to the electronic data.

Other objects, features, and advantages of the present invention will become apparent upon examining the following detailed description of an embodiment thereof, taken in conjunction with the attached drawings.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements, and in which:

FIG. 1 is a block diagram of a file security system according to one embodiment of the invention.

FIG. 2 is a flow diagram of a retention policy assignment process according to one embodiment of the invention.

FIG. 3 is a flow diagram of a future event evaluation process according to one embodiment of the invention.

FIG. 4 is a flow diagram of an expiration process according to one embodiment of the invention.

FIG. 5 is a flow diagram of an access request process according to one embodiment of the invention.

FIG. 6 is a flow diagram of a file securing process according to one embodiment of the invention.

FIGS. 7A and 7B are flow diagrams of a document securing process according to one embodiment of the invention.

FIG. 8 is a flow diagram of a document unsecuring process according to one embodiment of the invention.

FIG. 9 is a flow diagram of an access key retrieval process according to one embodiment of the invention.

FIG. 10 shows a basic security system in which the invention may be practiced in accordance with one embodiment thereof.

FIG. 11 shows an exemplary data structure of a secured file that may be used in one embodiment of the invention.

#### DETAILED DESCRIPTION OF THE INVENTION

The invention relates to techniques for utilizing security criteria to implement document retention for electronic documents. The security criteria can also limit when, how and where access to the electronic documents is permitted. The security criteria can pertain to keys (or ciphers) used to secure (e.g., encrypt) electronic files (namely, electronic documents), or to unsecure (e.g., decrypt) electronic files already secured. At least a portion of the security criteria can be used to implement document retention, namely, a document retention policy. After a secured electronic document has been retained for the duration of the document retention policy, the associated security criteria becomes no longer available, thus preventing subsequent access to the secured electronic document. In other words, access restrictions on electronic documents can be used to prevent access to electronic documents which are no longer to be retained.

In one embodiment, the security criteria can be managed by a document retention system. In another embodiment, the security criteria can be managed more generally by a file security system.

Secured files are files that require one or more keys, passwords, access privileges, etc. to gain access to their content. The security is often provided through encryption and access rules. The files, for example, can pertain to documents, multimedia files, data, executable code, images and text. In general, a secured file can only be accessed by authenticated users with appropriate access rights or privileges. In one embodiment, each secured file is provided with a header portion and a data portion, where the header portion contains, or points to, security information. The security information is used to determine whether access to associated data portions of secured files is permitted.

As used herein, a user may mean a human user, a software agent, a group of users, a member of the group, a device and/or application. Besides a human user who needs to access a secured document, a software application or agent sometimes needs to access secured files in order to proceed. Accordingly, unless specifically stated, the "user" as used herein does not necessarily pertain to a human being.

The invention is related to processes, systems, architectures and software products for providing automated retention of digital assets (e.g., electronic documents). The invention is particularly suitable in an enterprise environment. The invention can also be implemented by a security system that additionally secures digital assets (i.e., secured data) so that only authenticated users with appropriate access rights or privileges can gain access thereto. Digital assets may include, but not be limited to, various types of documents, multimedia files, data, executable code, images and text.

In the following description, numerous specific details are set forth in order to provide a thorough understanding of the invention. However, it will become obvious to those skilled in the art that the invention may be practiced without these specific details. The description and representation herein are the common meanings used by those experienced or skilled in the art to most effectively convey the substance of their work to others skilled in the art. In other instances, well-known

methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the invention.

Reference herein to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the invention. The appearances of the phrase "in one embodiment" in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Further, the order of blocks in process flowcharts or diagrams representing one or more embodiments of the invention do not inherently indicate any particular order, nor imply any limitations in the invention.

Embodiments of the invention are discussed herein with reference to FIGS. 1-11. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these figures is for explanatory purposes as the invention extends beyond these limited embodiments.

FIG. 1 is a block diagram of a file security system 100 according to one embodiment of the invention. The file security system 100 includes an access server 102 that provides central management for the file security system 100. The access server 102 can store or retrieve files from a server file store 104. The access server 102 can control the distribution of cryptographic keys from a key store 106. In addition, the access server 102 can generate cryptographic keys that are stored to the key store 106. Alternatively, the access server 102 can store cryptographic keys in the key store 106 that have been received by the access server 102.

The file security system 100 also includes user machines 108 and user file stores 112. The user machines 108 couple to the access server 102 via a network 110. The network 110 can be a private network or a public network. The user machine 108 also has a user file store 112 coupled thereto. The user file store 112 can store electronic files locally for the user of the corresponding user machine 108. On the other hand, the server file store 104 can provide centralized, remote storage of electronic files for any of the users of the user machines 108.

According to the invention, the file security system 100 enables a user at the user machine 108 to secure an electronic file (document) such that access to the secured electronic file is restricted. In one embodiment of the invention, the access restriction is or includes a document retention restriction. As an example, the document retention restriction could permit subsequent access to the secured electronic file only during the retention period. After the retention period, the secured electronic file would be unable to be unsecured and thus subsequent access would be cryptographically prevented. In one embodiment, the retention period is initially based on a future event that is unscheduled. Here, the file security system 100 can interact with an event evaluator 114 to determine (e.g., periodically) whether the future event has now been scheduled. Once the future event is scheduled, the retention period is determinable. The event evaluator 114 can be referred to as a remote resource that is used to evaluate future events. The event evaluator 114 can be a web server or a document management system (e.g., a contract management system).

Once an electronic file has been secured, a user at a user machine can attempt to access the secured electronic file. In doing so, the user machine for the user would need to access the access server 102 and retrieve the appropriate one or more cryptographic keys from the key store 106 that are needed to unsecure the secured electronic file. However, after expira-

tion of the retention period for the secured electronic document, the access server **102** does not permit the delivery of at least certain cryptographic keys from the key store **106** (private keys) that are needed to unsecure secured electronic files. The access server **102** normally also requires the user to be authorized to access the electronic file prior to delivery of at least certain cryptographic keys from the key store **106**. Typically, the cryptographic keys needed to unsecure a secured electronic file are private keys.

Nevertheless, once the restrictions and/or authorizations have been satisfied and the private keys have been supplied, the private keys are usable to unsecure the secured electronic files. Typically, the private keys will expire after a relatively short period of time (e.g., 1-30 days) so that users are forced to again retrieve the necessary cryptographic keys.

FIG. **2** is a flow diagram of a retention policy assignment process **200** according to one embodiment of the invention. The retention policy assignment process **200** operates to cryptographically secure an electronic document to implement document retention. The retention policy assignment process **200** is, for example, performed by a computing device, such as the access server **102** or the user machines **108** illustrated in FIG. **1**.

The retention policy assignment process **200** initially opens or creates **200** an electronic document. A user of a computing device may assist with the opening or creation of the electronic document. Next, a decision **202** determines whether document retention is requested. Here, according to the invention, document retention policies can be imposed on the electronic document. Hence, the decision **202** determines whether document retention is to be imposed on the electronic document. When the decision **202** determines that document retention is not to be imposed, then the retention policy assignment process **200** is complete and ends with no document retention policy being imposed.

On the other hand, when the decision **202** determines that document retention is requested, then a document retention policy is specified **204** based on a future event that is presently unscheduled. Typically, the document retention policy specifies that the electronic document is to be maintained until some future point in time. However, when the document retention policy is based on a future event which is presently unscheduled, the future point in time is not known and cannot be determined. Once the future event becomes scheduled, then the period of time for document retention can be determined. In other words, the document retention policy becomes determinable because the future event is no longer unscheduled. Next, the document retention policy is cryptographically imposed **206** on the electronic document. Recall, however, that the document retention policy at this point is based on a future event which is presently unscheduled. In one implementation, a cryptographic key is utilized to encrypt the electronic document so that access to the electronic document can be restricted after the document retention policy has been exceeded. In other words, after the period of time for document retention specified by the document retention policy has been exceeded, the cryptographic key that is needed to gain access to the electronic document is no longer made available to users. As a result, because the electronic document was previously cryptographically secured using a cryptographic key, if the corresponding or counterpart cryptographic key is no longer available, then the electronic document remains encrypted and thus unusable. In any case, following the operation **206**, the retention policy assignment process **200** is complete and ends.

Once a document retention policy has been assigned to an electronic document, the document retention system or file

security system **100** as shown in FIG. **1** needs to periodically evaluate whether future events associated with the document retention policies are now scheduled. In one embodiment, the access server **102** shown in FIG. **1** can be utilized to periodically evaluate whether future events have become scheduled.

FIG. **3** is a flow diagram of a future event evaluation process **300** according to one embodiment of the invention. The future event evaluation process **300** can, for example, be performed by the access server **102** illustrated in FIG. **1**.

The future event evaluation process **300** initially identifies **302** a future event. Here, the future event is a future event that is being monitored by a document retention system (or file security system) because it is utilized by one or more document retention policies assigned to one or more electronic documents managed by the system. After the future event has been identified **302**, a remote resource can be queried **304** for status of the future event. The remote resource can, for example, be a file, a web server or an external system. An example of an external system would be a document management system or a contract management system. In any case, the event evaluator **114** shown in FIG. **1** can represent the remote resource that is being queried **304**.

Next, a decision **306** determines whether a status response has been received from the remote resource. When the decision **306** determines that a status response has not been received, then the future event evaluation process **300** awaits a status response. However, after a period of time in which no response is received, the status response can be deemed or default to indicate that the future event remains unscheduled. On the other hand, when the decision **306** determines that the status response has been received, a decision **308** determines whether the future event is now scheduled by examination of the status response. When the decision **308** determines that the future event is now scheduled, then schedule information pertaining to the future event can be stored **310**. For example, the access server **102** shown in FIG. **1** can store schedule information for the future event. At a minimum, the schedule information can contain an indication that the future event is now scheduled. Typically, the schedule information would specify a date representing the occurrence (past or future) of the future event. Alternatively, when the decision **308** determines that the future event still remains unscheduled, then the operation **310** is bypassed.

Following the operation **310** or its being bypassed, a decision **312** determines whether there are other future events to be evaluated. When the decision **312** determines that there are other future events to be evaluated, the future event evaluation process **300** returns to repeat the operation **302** and subsequent operations, thereby allowing other future events to be similarly evaluated. On the other hand, when the decision **312** determines that there are no other future events to be evaluated, then the future event evaluation process **300** is complete and ends. Typically, the future event evaluation process **300** would be periodically invoked to evaluate whether any future events have become scheduled.

In one embodiment, the remote resource can be addressed for requests (queries) by a Universal Resource Locator (URL). The URL could point to a file, a web-server or some other web-based application. In case where the URL points to a file, the file stores and can provide the status response as to whether the associated future event is unscheduled or not. The URL specifies the correct file and can do so by identifying the descriptions of future events, an event type and an event identifier.

In another embodiment, when the remote resource is a web server or an external system, the request (query) to the web server or external system can use a URL to access the web

server. The URL can specify the web server or external system and describe the future event of interest. Alternatively, the query or request to the web server or external system can be a markup language (e.g., XML) document. Such a status request would also at least describe the future event of interest. The status response from the web server or external system can return an indication as to whether the associated future event is unscheduled or not. As an example, the status response can be a markup language (e.g., XML) document. It should be noted that the status response can also be signed with an electronic signature that can be used to authenticate its origin.

In still another embodiment, the remote resource is network accessible (e.g., web server or external system). Here, the remote resource can be accessed using networking techniques, such as TCP/IP networks, to get future event information from the remote resource.

FIG. 4 is a flow diagram of an expiration process 400 according to one embodiment of the invention. The expiration process 400 represents other processing that determines whether document retention periods associated with electronic documents have been exceeded, and if so, renders the associated electronic documents inaccessible. The expiration process 400 would typically be periodically invoked. The expiration process 400 can, for example, be performed by the access server 102 illustrated in FIG. 1.

The expiration process 400 initially identifies 402 a future event. Here, the future event is a future event associated with a document retention policy that is being utilized to retain one or more electronic documents by a document retention system (or file security system).

Next, a decision 404 determines whether the future event has been scheduled. As an example, the decision 404 can examine schedule information that is stored by the future event evaluation process 300 illustrated in FIG. 3. In any case, the decision 404 determines whether the future event has now been scheduled. When the decision 404 determines that the future event has been scheduled, then a decision 406 determines whether a document retention period associated with the now scheduled future event has expired. For example, a document retention period might typically be represented as a predetermined period of time following a future event. Hence, once the future event is scheduled and thus has a date certain, the document retention period is determinable.

When the decision 406 determines that the document retention period has expired, then the cryptographic key associated with the document retention policy is identified 408. The document retention policy may be associated with one or a plurality of cryptographic keys that are utilized to secure one or a plurality of different electronic documents. In any event, once the cryptographic key is identified 408, the cryptographic key is deactivated 410. In other words, the cryptographic key utilized to implement the document retention policy for the electronic document is destroyed, deleted or disabled. Consequently, the cryptographic key is no longer useable to gain access to the electronic document that has been encrypted therewith, thereby implementing the document retention policy. In other words, the associated electronic document is thereafter inaccessible by those persons or machines that were previously able to access the electronic document. In effect, the electronic document has been effectively destroyed. The operations 408 and 410 are bypassed when the decision 404 determines that the future event has not yet been scheduled or when the decision 406 determines that the document retention period has not yet expired.

In any case, following the operation 410 or its being bypassed, a decision 412 determines whether there are other

future events to be similarly processed so as to determine whether the associated document retention period or periods have expired. Hence, when the decision 412 determines that other future events are to be processed, the expiration process 400 returns to repeat the operation 402 and subsequent operations to process another future event.

FIG. 5 is a flow diagram of an access request process 500 according to one embodiment of the invention. The access request process 500 is, for example, performed by a computing device, such as the user machines 108 illustrated in FIG. 1.

The access request process 500 begins with a decision 502 that determines whether an electronic document access request has been received. A user of a computing device can initiate an electronic document access request. When the decision 502 determines that an electronic document access request has not been received, then the access request process 500 awaits such a request. Once the decision 502 determines that a document access request has been received, then a decision 504 can determine whether document retention is imposed on the electronic document that is to be accessed. When the decision 504 determines that document retention is not imposed on the electronic document to be accessed, access to the electronic document is permitted 506.

On the other hand, when the decision 504 determines that document retention is imposed on the electronic document to be accessed, a cryptographic key associated with the document retention policy that is imposed on the electronic document is requested 508. A decision 510 then determines whether the requested key has been received. Here, the requested key is the cryptographic key that has been requested 508. In one implementation, such as shown in FIG. 1, the user machine 108 requests the key from the access server 102, and the key is provided (if at all) to the user machine 108 via the network 110.

When the decision 510 determines that the requested key has not been received, then access to the electronic document is denied 512. In this case, the document retention policy causes the cryptographic key to be no longer available to the requestor. In such case, although the requestor may have access to the electronic document, since the cryptographic key is not available, the requestor is not able to gain access to the electronic document. In other words, the electronic document remains in its encrypted format and thus unusable by the requestor. In such case, the document retention policy imposed on the electronic document caused the electronic document to expire.

On the other hand, when the decision 510 determines that the requested key has been received, then access to the electronic document is permitted 514 through use of the cryptographic key. In other words, the cryptographic key can be used to decrypt the encrypted electronic document, thereby allowing the requestor to gain access to the electronic document.

Following the operations 506, 512 and 514, the access request process 500 is complete and ends. However, it should be noted that additional layers of encryption could be imposed on the electronic document besides the level of encryption utilized to implement a document retention policy. Hence, other keys or requirements can be imposed by a file security system in order to further restrict access to the electronic documents. For example, co-pending U.S. patent application Ser. No. 10/405,587, filed Apr. 1, 2003 and entitled "METHOD AND SYSTEM FOR SECURING DIGITAL ASSETS USING CONTENT TYPE DESIGNATIONS," describes representative other document security measures and is hereby incorporated herein by reference.

11

As previously noted, document retention can be provided by a file security system. In which case, an electronic file can be cryptographically secured using a key that is associated with file retention. The key can then automatically be made unavailable after the retention period for the electronic document has been exceeded. Accordingly, the electronic file is no longer accessible after the retention period is exceeded. Typically, such inaccessibility is permanent and irreversible. However, in special situations, the automatic nature of the non-retention can be suspended so as to permit extended access. For example, a system administrator can cause the retention period to be extended so that the electronic file remains accessible even after the original extension period has been scheduled. This override capability can be important when, for example, legal issues arise concerning the electronic file. In such cases, the electronic file should be retained and not automatically expired. In one embodiment, the system administrator can either override an assigned retention period or set a new retention period (which may also be based on a future event).

FIG. 6 is a flow diagram of a file securing process 600 according to one embodiment of the invention. The file securing process 600 is, for example, performed by a computing device, such as the access server 102 or the user machines 108 illustrated in FIG. 1.

The file securing process 600 initially identifies 602 an electronic file to be secured. Here, the electronic file is identified to the computing device carrying out the file securing process 600. A user of the computing device may assist in the identification of the electronic file. After the electronic file to be secured has been identified 602, a document retention access key is obtained 604. Typically, the document retention access key is obtained 604 from an access server. For example, if the file securing process 600 is performed by the user machine 108, the document retention access key can be retrieved remotely from the access server 102, which can retrieve the document retention access key from the key store 106. Here, the document retention access key is a public key and is normally readily available.

Next, after the time-based access key has been obtained 604, the electronic file is secured 606 through use of the document retention access key. The result of the securing of the electronic file is to produce a secured electronic file. Typically, the electronic file is cryptographically secured through encryption (directly or indirectly) using the document retention access key. In one embodiment, one or more other keys are used to further control access to the electronic file. Thereafter, the secured electronic file is stored 608. After the secured electronic file is stored 608, the file securing process 600 ends. Following the securing process 600, the secured electronic file can be distributed to one or more user machines 108 having interested users.

FIGS. 7A and 7B are flow diagrams of a document securing process 700 according to one embodiment of the invention. The document securing process 700 is, for example, performed by a computing device, such as the access server 102 or the user machines 108 illustrated in FIG. 1.

The document securing process 700 opens or creates 702 an electronic document. At this point, the electronic document is unsecured, which is often referred to as being in the "clear." Next, a decision 704 determines whether the electronic document is to be secured. Here, the user or creator of the electronic document has the option of securing the document, if so desired. When the decision 704 determines that the electronic document is not to be secured, then the electronic document is saved 706. Here, the electronic document being saved is not secured. Following the block 706, the document

12

securing process 700 ends with the electronic document being saved in an unsecured fashion.

On the other hand, when the decision 704 determines that the electronic document is to be secured, then a data portion of the electronic document is encrypted 708 using a document key. The document key can be a cryptographic key that is generated or obtained. Typically, each document managed and secured by the file (document) security system would be encrypted 708 using a different document key. After the data portion of the electronic document has been encrypted 708, a decision 710 determines whether a document retention restriction should be imposed on the electronic document. The user or creator of the electronic document can have the option of securing the document with a document retention access restriction, if so desired.

When the decision 710 determines that a document retention restriction should be imposed on the electronic document, a public document retention access key is requested 712. In one embodiment, the public document retention access key can be requested from the access server 102 by the user machine 108. The access server 102 can then retrieve or generate the public document retention access key and supply it to the user machine 108. In an alternative implementation, the user machine may have already received the public document retention access key (e.g., such as in a key cache) and thus would not need to request such.

Next, a decision 714 determines whether the public document retention access key has been received. Once the decision 714 determines that the public document retention access key has been received (or already available), the document key is encrypted 716 using the public document retention access key. Here, the document key is being encrypted using the public document retention access key. In other words, the public document retention access key is indirectly used to encrypt the electronic document by encryption of the document key. Next, a secured electronic document is formed 718 from the encrypted data portion and the encrypted document key. Thereafter, the secured electronic document is saved 720. In this case, following the block 720, the document securing process 700 ends with the electronic document being saved in a secured fashion with at least a document retention access restriction.

Alternatively, when the decision 710 determines that a document retention access restriction is not to be imposed on the electronic document, then the blocks 712-716 are bypassed. In such case, the secured electronic document is formed 718 from the encrypted data portion and the document key. Here, the document key is not encrypted using a public document retention access key. The resulting secured electronic document is then saved 720. In this case, following the block 720, the document securing process 700 ends with the electronic document being saved in a secured fashion without any time-based access restrictions.

FIG. 8 is a flow diagram of a document unsecuring process 800 according to one embodiment of the invention. The document unsecuring process 800 can be performed at a client machine or a server machine, such as the user machine 108 or the access server 102 illustrated in FIG. 1.

The document unsecuring process 800 begins with a decision 802 that determines whether a request to access a secured electronic document has been received. When the decision 802 determines that a request to access a secured electronic document has not yet been received, the document unsecuring process 800 awaits such a request. In other words, the document unsecuring process 800 can be considered to be invoked once access to a secured electronic document is requested.

13

Once the decision **802** determines that a request to access a secured electronic document has been received, a decision **804** determines whether a document retention restriction is present. In one implementation, the decision **804** can evaluate a header portion of the secured electronic document to determine whether a document retention restriction is present. In another implementation, the decision **804** can evaluate a system policy to determine whether a document retention restriction is present. As an example, the header can include an indicator of a document retention restriction.

When the decision **804** determines that a document retention restriction is present, then a private document retention access key is requested **806**. In one embodiment, the private document retention access key is requested **806** from a file security system, such as a server machine thereof (e.g., access server **102**). Then, a decision **808** determines whether the requested key has been received. When the decision **808** determines that the requested key has not yet been received, a decision **810** determines whether access to the requested key has been denied. Typically, the private document retention access key is only available so long as a retention period for the secured electronic document has not been exceeded. In one embodiment, the access server **102** controls access to the private document retention access key which is stored in the key store **106**. Hence, in such an embodiment, the access server **102** would deny any request for the document retention access key after the retention period has been exceeded. In any case, when the decision **810** determines that access to the requested key has been denied, then access to the secured electronic document is denied and notice that access has been denied is returned **812**. In one embodiment, the notice can more specifically indicate that access is denied because the document has expired. Following the block **812**, the document unsecuring process **800** ends with access to the secured electronic document being denied.

On the other hand, when the decision **810** determines that access to the requested key has not been denied, then the document unsecuring process **800** returns to repeat the decision **808** so as to wait for the requested key to be received. Once the decision **808** determines that the requested key (the private document retention access key) has been received, the encrypted document key from the secured electronic document is decrypted **814** using the private document retention access key to yield the document key (unencrypted). Here, in one embodiment, a header portion of the secured electronic document includes at least the encrypted document key (as well as the indicator for the private document retention access key). Next, an encrypted data portion of the secured electronic document is decrypted **816** using the document key. Finally, the data portion of the electronic document is then returned **818** to the requestor. Additionally, it should be noted that when the decision **804** determines that a document retention access restriction is not present, then the document unsecuring process **800** skips blocks **806-814** and proceeds to block **816**. Following block **818**, the document unsecuring process **800** ends with access to the secured electronic document being successful.

In one embodiment, the document retention access keys (e.g., the public and private key pair) can be unique (i.e., different) for each electronic document. Alternatively, to manage the number of key pairs, the document retention access keys can be shared by electronic documents being retained for a like duration.

FIG. 9 is a flow diagram of an access key retrieval process **900** according to one embodiment of the invention. The

14

access key retrieval process **900** is, for example, performed by a server machine, such as the access server **102** illustrated in FIG. 1.

The access key retrieval process **900** begins with a decision **902** that determines whether a request for a document retention access key has been received. When the decision **902** determines that a request for a document retention access key has not yet been received, the access key retrieval process **900** awaits such a request. Once the decision **902** determines that a document retention access key has been received, the access key retrieval process **900** continues. In other words, the access key retrieval process **900** can be deemed invoked when a request for a document retention access key is received.

In any case, once the access key retrieval process **900** continues, a decision **904** determines whether the requested access key is a private key. When the decision **904** determines that the requested key is not a private key (i.e., is a public key), then a public document retention access key (which was requested) is sent **906**. Typically, the public document retention access key would be sent to a requestor (such as a user machine). In one embodiment, the public document retention access key is retrieved from a remote key store by a server and sent by the server to the requestor.

On the other hand, when the decision **904** determines that the requested key is a private key (i.e., a private document retention access key), a decision **912** determines whether the private document retention access key is available. When the decision **912** determines that the private document retention access key is not available, then the key request is denied **914**. In such case, the requestor would not be able to utilize the electronic documents that have been secured with the associated document retention policy. In effect, the electronic documents would be deemed expired (i.e., no longer retained).

Alternatively, when the decision **912** determines that the private document retention access key is available, then the private document retention access key is sent **916** to the requestor. In this case, the requestor is able to use the requested key to gain access to the electronic documents. Following the blocks **906**, **914** and **916**, the access key retrieval process **900** ends.

FIG. 10 shows a basic security system **1000** in which the invention may be practiced in accordance with one embodiment thereof. The security system **1000** may be employed in an enterprise or inter-enterprise environment. It includes a first server **1006** (also referred to as a central server) providing centralized access management for the enterprise. The first server **1006** can control restrictive access to files secured by the security system **1000** as well as file (e.g., document) retention. To provide dependability, reliability and scalability of the system, one or more second servers **1004** (also referred to as local servers, of which one is shown) may be employed to provide backup or distributed access management for users or client machines serviced locally. The server **1004** is coupled to a network **1008** and a network **1010**. For illustration purposes, there are two client machines **1001** and **1002** being serviced by the local server **1004**. Alternatively, one of the client machines **1001** and **1002** may be considered as a networked storage device.

Secured files may be stored in any one of the devices **1001**, **1002**, **1004** and **1006**. When a user of the client machine **1001** attempts to exchange a secured file with a remote destination **1012** being used by an external user, the processes discussed above can be utilized to ensure that the requested secure file is delivered without compromising the security imposed on the secured file.

According to one embodiment, a created document is caused to go through an encryption process that is preferably



15

transparent to a user. In other words, the created document is encrypted or decrypted under the authoring application so that the user is not aware of the process. One or more keys, such as a user key and a document retention access key, can be used to retrieve a file key to decrypt an encrypted document. Typically, the user key is associated with an access privilege for the user or a group of users, and the document retention access key is associated with a retention period imposed on the created document. For a given secured document, only a user with proper access privileges can access the secured document and then only after a time restriction, if present, is satisfied.

In one setting, a secured document may be uploaded via the network **1010** from the client computer **1001** to a computing or storage device **1002** that may serve as a central repository. Although not necessary, the network **1010** can provide a private link between the computer **1001** and the computing or storage device **1002**. Such link may be provided by an internal network in an enterprise or a secured communication protocol (e.g., VPN and HTTPS) over a public network (e.g., the Internet). Alternatively, such link may simply be provided by a TCP/IP link. As such, secured documents on the computing or storage device **1002** may be remotely accessed.

In another setting, the computer **1001** and the computing or storage device **1002** are inseparable, in which case the computing or storage device **1002** may be a local store to retain secured documents or receive secured network resources (e.g., dynamic Web contents, results of a database query, or a live multimedia feed). Regardless of where the secured documents or secured resources are actually located, a user, with proper access privileges and within retention periods, can access the secured documents or resources from the client computer **1001** or the computing or storage device **1002** using an application (e.g., Microsoft Internet Explorer, Microsoft Word or Adobe Acrobat Reader).

Accordingly, respective local modules in local servers, in coordination with the central server, form a distributed mechanism to provide not only distributed access control enforcement but also file (e.g., document) retention. Such distributed access control enforcement ensures the dependability, reliability and scalability of centralized access control management undertaken by the central server for an entire enterprise or a business location.

FIG. **11** shows an exemplary data structure **1120** of a secured file that maybe used in one embodiment of the invention. The data structure **1120** includes two portions: a header (or header portion) **1122** and encrypted data (or an encrypted data portion) **1124**. The header **1122** can be generated in accordance with a security template associated with a data store and thus provides restrictive access to the data portion **1124** which, for example, is an encrypted version of a plain file. Optionally, the data structure **1120** may also include an error-checking portion **1125** that stores one or more error-checking codes, for example, a separate error-checking code for each block of encrypted data **1124**. These error-checking codes may also be associated with a Cyclical Redundancy Check (CRC) for the header **1122** and/or the encrypted data **1124**. The header **1122** includes a flag bit or signature **1127** and security information **1126** that is in accordance with the security template for the data store. According to one embodiment, the security information **1126** is encrypted and can be decrypted with a user key associated with an authenticated user (or requestor).

The security information **1126** can vary depending upon implementation. However, as shown in FIG. **11**, the security information **1126** includes a user identifier (ID) **1128**, access policy (access rules) **1129**, keys (cryptographic keys) **1130**,

16

and other information **1131**. Although multiple user identifiers may be used, a user identifier **1128** is used to identify a user or a group that is permitted to access the secured file. The access rules **1129** provide restrictive access to the encrypted data portion **1124**. The keys **1130** are cipher keys (and/or pointers or identifiers therefor) that, once obtained, can be used to decrypt the encrypted data portion **1124** and thus, in general, are protected. In one implementation of the data structure **1120**, at least one of the keys **1130** is encrypted in conjunction with the access rules **1129**. In another implementation of the data structure **1120**, at least one of the keys **1130** is a file retention access key or is a key encrypted with a file retention access key, either of which can possibly be further protected by the access rules **1129**. The other information **1131** is an additional space for other information to be stored within the security information **1126**. For example, the other information **1131** may be used to include other information facilitating secure access to the secured file, such as version number or author identifier.

The invention is preferably implemented by software or a combination of hardware and software, but can also be implemented in hardware. The invention can also be embodied as computer readable code on a computer readable medium. The computer readable medium is any data storage device that can store data which can thereafter be read by a computer system. Examples of the computer readable medium include read-only memory, random-access memory, CD-ROMs, DVDs, magnetic tape, optical data storage devices, and carrier waves. The computer readable medium can also be distributed over network-coupled computer systems so that the computer readable code is stored and executed in a distributed fashion.

The various embodiments, implementations and features of the invention noted above can be combined in various ways or used separately. Those skilled in the art will understand from the description that the invention can be equally applied to or used in various other settings with respect to different combinations, embodiments, implementations or features as provided in the description herein.

The advantages of the invention are numerous. Different embodiments or implementations may yield one or more of the following advantages. One advantage of the invention is that retention of electronic data (e.g., electronic documents) is provided in a robust, cryptographically secure manner. Another advantage of the invention is that retention policies can be based on future events that are unscheduled when assigned to electronic data. Still another advantage of the invention is that the needed cryptographic keys to unsecure secured electronic data are no longer released by a server to a client once a retention policy has expired, thereby effectively and properly disposing of the electronic data.

The foregoing description of embodiments is illustrative of various aspects/embodiments of the present invention. Various modifications to the invention can be made to the preferred embodiments by those skilled in the art without departing from the true spirit and scope of the invention as defined by the appended claims. Accordingly, the scope of the present invention is defined by the appended claims rather than the foregoing description of embodiments.

What is claimed is:

1. A method for restricting access to an electronic document, comprising:
  - identifying an electronic document to be secured, the electronic document having at least a data portion that contains data;

17

encrypting the data portion of the electronic document using a document key to produce an encrypted data portion;  
 encrypting the document key using a retention access key to produce an encrypted document key, the retention access key being used to enforce a document retention policy on the electronic document; and  
 forming a secured electronic document based on at least the encrypted data portion and the encrypted document key,  
 wherein the document retention policy is dependent on a future event that is presently unscheduled, wherein the document retention policy expires at a determined time after the future event occurs, and wherein the future event is scheduled after the document retention policy is associated with the electronic document.

2. The method of claim 1, wherein the retention access key is a public retention access key.

3. The method of claim 1, further comprising:  
 maintaining accessibility to the retention access key from a remote key store while a document retention period of the document retention policy has not been exceeded.

4. The method of claim 3, further comprising:  
 receiving, by a client machine, the retention access key from the remote key store over a network.

5. The method of claim 3, further comprising:  
 receiving, by a server, the retention access key from the remote key store over a network.

6. The method of claim 1, further comprising:  
 extending the determined time of expiration after the future event has occurred.

7. A method for accessing a secured electronic document by a requestor, the secured electronic document having at least a header portion and an encrypted data portion, comprising:  
 obtaining a retention access key, the retention access key being used to enforce a document retention policy on the secured electronic document;  
 obtaining an encrypted document key from the header portion of the secured electronic document;  
 decrypting the encrypted document key using the retention access key to produce a document key; and  
 decrypting the encrypted data portion of the secured electronic document using the document key to produce a data portion,  
 wherein the document retention policy is dependent on a future event that is presently unscheduled, wherein the document retention policy expires at a determined time after the future event occurs, and wherein the future event is scheduled after the document retention policy is associated with the electronic document.

18

8. The method of claim 7, further comprising:  
 supplying the data portion to the requestor, wherein the retention access key is identified by an indicator within a header portion of the secured electronic document.

9. The method of claim 7, wherein the retention access key is a private retention access key.

10. The method of claim 7, wherein the obtaining a retention access key comprises obtaining the retention access key from a server, wherein the server determines whether the retention access key is permitted to be provided to the requestor based on the document retention policy.

11. The method of claim 7, wherein the retention access key is available from a remote key store only so long as a document retention period of the document retention policy has not been exceeded.

12. The method of claim 7, wherein:  
 the retention access key is available only so long as a document retention period of the document retention policy has not been exceeded, and  
 the document retention period can be extended to permit extended access to the electronic document.

13. The method of claim 7, wherein the retention access key is available while a document retention period of the document retention policy has not been exceeded.

14. A non-transitory computer-readable storage medium having control logic recorded thereon that, in response to execution by a processor in a computing system, causes the processor to perform operations to restrict access to an electronic document, the operations comprising:  
 identifying an electronic document to be secured, the electronic document having at least a data portion that contains data;  
 encrypting the data portion of the electronic document using a document key to produce an encrypted data portion;  
 encrypting the document key using a retention access key to produce an encrypted document key, the retention access key being used to enforce a document retention policy on the electronic document; and  
 forming a secured electronic document based on at least the encrypted data portion and the encrypted document key,  
 wherein the document retention policy is dependent on a future event that is presently unscheduled, wherein the document retention policy expires at a determined time after the future event occurs, and wherein the future event is scheduled after the document retention policy is associated with the electronic document.

15. The non-transitory computer-readable storage medium of claim 14, the operations further comprising:  
 providing the retention access key to a requesting device if the document retention policy has not expired; and  
 denying, access to the retention access key if the document retention policy has expired.

\* \* \* \* \*