Monitoring

Table of Contents

View SMSC Statistics

Using CLI

You can view the current state of SMSC using the command `smsc stat get` with appropriate parameters as described below:

```
Name
    smsc stat get

SYNOPSIS
    smsc stat get

DESCRIPTION
    This command is used to view the details of the current state of the SMSC and
    monitor the SMSC. The output prints the following parameters:

    Time            - Current time. By obtaining this statistic twice, this
                      value can be used to calculate the time interval between
                      statistic time.

    MessageInProcess    - Number of messages currently being processed for
                      delivery in GSM (MT messages) and SMPP (messages that
                      are routed to ESME) and SIP (messages that are routed to
                      ESME).

    MessageId       - This is the last assigned Message Id. This indicates
                      the number of messages that have come into the SMSC
                      from GSM (Mobile Originated messages), from ESMEs or from SIP
                      and stored in the Cassandra database. The MessageId
                      counter is initiated from the time of the installation
                      of the SMSC.

    MessageScheduledTotal   - The number of messages put into the delivering
                      process in both GSM, SMPP or SIP since the SMSC was started.

    DueSlotProcessingLag    - The time (in seconds) between "in time" due_slot
                      and "in process" due_slot. "In time" means the current actual
                      time, "in process" means that SMSC GW is processing messages
                      that was scheduled for that time (in the past).

                      If this value is equal to 0 or 1 or 2, it means that the
                      SMSC is not highly loaded and all the messages are
                      being processed on time.

                      If this value is high, say for example 300, then it
                      means the SMSC is overloaded and is now processing
                      messages, that are scheduled for processing 300 seconds
                      before the current time.
```

```
                If this value is progressively increasing, then the SMSC
                is heavily overloaded and the incoming messages count at
                SMPP (and MO) are more than what the SMSC can deliver.

                If the incoming messages are not many, this value will
                decrease and will reach 0 when there are no messages.

                Normally this value will return to 0 except for few
                peaks. If it does not, then you must reduce the load for
                SMSC.

    DueSlotProcessingTime - This field shows the time for which SMSC GW is
                processing / fetching stored in cassandra database messages
                ("in process" due_slot). If this time is far before the
                current actual time, then this means:
                - either SMSC GW is overloaded and can not send messages
                  in time
                - or SMSC GW was turned off for much time and now is
                  checking for messages for the time when it was off
                If you want to skip unsent messages that was scheduled for
                the time in the past (and then shift DueSlotProcessingTime
                to to current time) - you can use the command [the reference
                to CLI / GUI command "smsc skip-unsent-messages" - see the
                Chapter "Skipping of scheduled for the past and not yet
                sent messages ("In process" due_slot shifting)."

    Param1          - Ignore.

    Param2          - Ignore.

    SmscStartTime       - The time when the SMSC was started.
EXAMPLES
    smsc stat get
    Stat: Time: Mon Jan 13 18:40:42 CET 2014, MessageInProcess: 515, MessageId: 10212,
    MessageScheduledTotal: 8992, DueSlotProcessingLag: 0, Param1: 0, Param2: 0,
    SmscStartTime: Mon Jan 13 18:39:30 CET 2014
```

Using GUI

Procedure: View SMSC Statistics using the GUI

1. In the GUI Management Console for SMSC Gateway, click on 'Stats' in the left panel.

2. The main panel will display the current statistics of the SMSC and display the details of the parameters 'START TIME', 'CURRENT TIME', 'TOTAL MESSAGES SCHEDULED', 'MESSAGES IN PROCESS', 'CURRENT MESSAGE ID' and 'DUE SLOT PROCESSING LAG'. For more details of these parameters please refer to the description of the CLI command in the preceding section.

   This page gets auto-refreshed every 2.5 seconds and therefore the statistics get refreshed automatically.

CDR Log

Restcomm SMSC is configured to generate CDR in a plain text file located at *restcomm-smscgateway-<version>/jboss-5.1.0.GA/server/<profile>/log/cdr.log*. The CDR generated in the text file is of the below format:

```
SIMBIT_DATE,ADDR_SRC_DIGITS,ADDR_SRC_TON,ADDR_SRC_NPI,ADDR_DST_DIGITS,ADDR_DST_TON,ADDR_DST_NPI,Message_Delivery_Status,ORIG_SYSTEM_ID,MESSAGE_ID,NNN_DIGITS,IMSI,CORR_ID,First 20 characters of SMS, Reason_For_Failure
```

where ADDR_SRC_DIGITS, ADDR_SRC_TON, ADDR_SRC_NPI, ADDR_DST_DIGITS, ADDR_DST_TON, ADDR_DST_NPI, ORIG_SYSTEM_ID, MESSAGE_ID, NNN_DIGITS, IMSI and CORR_ID are as explained in [_slot_messages_table_yyyy_mm_dd]; SIMBIT_DATE, Message_Delivery_Status and Reason_For_Failure are described below in this section.

> NNN_DIGITS and IMSI fields are present only in the case of SS7 terminated messages when there is a SRI positive response. CORR_ID is present only if a message has come to the SMSC Gateway via "home-routing" procedure.

SIMBIT_DATE

Time when the message reached the SMSC Gateway.

Message_Delivery_Status

The CDR text file contains a special field, Message_Delivery_Status, that specifies the message delivery status. The possible values are described below:

Message_Delivery_Status if delivering to GSM network:

partial

Delivered a part of a multi-part message but not the last part.

success

Delivered the last part of a multi-part message or a single message.

temp_failed

Failed delivering a part of a multi-part message or a single message. It does not indicate if a resend will be attempted or not.

failed

Failed delivering a message and the SMSC will now attempt to resend the message or part of the message.

failed_imsi

Delivery process was broken by a mproc rule applying at the step when a successful SRI response has been received from HLR.

Message_Delivery_Status if delivering to ESME:

partial_esme

Delivered a part of a multi-part message but not the last part.

success_esme

Delivered the last part of a multi-part message or a single message.

temp_failed_esme

Failed delivering a part of a multi-part message or a single message.

failed_esme

Failed delivering a message and the SMSC will now attempt to resend the message or part of the message.

Message_Delivery_Status if delivering to SIP:

partial_sip

Delivered a part of a multi-part message but not the last part.

success_sip

Delivered the last part of a multi-part message or a single message.

temp_failed_sip

Failed delivering a part of a multi-part message or a single message.

failed_sip

Failed delivering a message and the SMSC will now attempt to resend the message or part of the message.

Message_Delivery_Status if the message has been rejected by the OCS Server (Diameter Server):

ocs_rejected

OCS Server rejected an incoming message.

Message_Delivery_Status if the message has been rejected by a mproc rule applying at the step when a message has been arrived to SMSC GW:

mproc_rejected

A mproc rule rejected an incoming message (and reject response was sent to a message originator).

mproc_dropped

A mproc rule dropped an incoming message (and accept response was sent to a message originator).

. The last field in the CDR generated is `Reason_For_Failure`, which records the reason for delivery failure and is empty if the delivery is successful. The possible delivery failure cases are explained below.

Reasons_For_Failure

XXX response from HLR

A MAP error message is received from HLR after SRI request; XXX: `AbsentSubscriber`, `AbsentSubscriberSM`, `CallBarred`, `FacilityNotSuppored`, `SystemFailure`, `UnknownSubscriber`, `DataMissing`, `UnexpectedDataValue`, `TeleserviceNotProvisioned`.

Error response from HLR: xxx

Another MAP error message is received from HLR after SRI request.

Error XXX after `MtForwardSM` Request

A MAP error message is received from MSC/VLR after `MtForwardSM` request; XXX: `subscriberBusyForMtSms`, `absentSubscriber`, `absentSubscriberSM`, `smDeliveryFailure`, `systemFailure`, `facilityNotSup`, `dataMissing`, `unexpectedDataValue`, `facilityNotSupported`, `unidentifiedSubscriber`, `illegalSubscriber`.

Error after `MtForwardSM` Request: xxx

Another MAP error message is received from MSC/VLR after `MtForwardSM` request.

DialogClose after `MtRequest`

No `MtForwardSM` response and no error message received after `MtForwardSM` request.

`onDialogProviderAbort` after `MtForwardSM` Request

MAP `DialogProviderAbort` is received after `MtForwardSM` request.

`onDialogProviderAbort` after SRI Request

MAP `DialogProviderAbort` is received after SRI request.

Error condition when invoking `sendMtSms()` from `onDialogReject()`

After a `MtForwardSM` request MAP version conflict, MAP message negotiation was processed but this process failed, or other fundamental MAP error occurred.

`onDialogReject` after SRI Request

After a SRI request MAP version conflict, MAP message negotiation was processed but this process failed, or other fundamental MAP error occurred.

`onDialogTimeout` after `MtForwardSM` Request

Dialog timeout occurred after `MtForwardSM` Request. The reason may be GSM network connection failure or SMSC overload.

`onDialogTimeout` after SRI Request

Dialog timeout occurred after SRI Request. The reason may be GSM network connection failure or SMSC overload.

`onDialogUserAbort` after `MtForwardSM` Request

`DialogUserAbort` message is received from a peer or sent to a peer. The reason may be GSM fundamental failure or SMSC overload.

`onDialogUserAbort` after SRI Request

`DialogUserAbort` message is received from a peer or sent to a peer. The reason may be GSM fundamental failure or SMSC overload.

onRejectComponent *after* `MtForwardSM` *Request*

Reject component was received from a peer or sent to a peer. This is an abnormal case and implies MAP incompatibility.

onRejectComponent *after SRI Request*

Reject component was received from a peer or sent to a peer. This is an abnormal case and implies MAP incompatibility.

Other

Any other message that usually indicates some internal failure.