

SIP Servlets Application Security

Table of Contents

Application security varies depending on the server type used. The following procedures describe how to configure the JBoss AS7 and Tomcat servers to enable Security.

Procedure: Enable SIP Application Security in JBoss AS7

1. Add Security Policy to Server Configuration

- a. Open the configuration file located in `$JBOSS_HOME/standalone/configuration/standalone-sip.xml`
- b. Append a security domain to the under the `<security-domains>`:

```
<security-domain name="sip-servlets">
  <authentication>
    <login-module code="UsersRoles" flag="required">
      <module-option name="usersProperties"
value="${jboss.server.config.dir}/sip-servlets-users.properties"/>
      <module-option name="rolesProperties"
value="${jboss.server.config.dir}/sip-servlets-roles.properties"/>
      <module-option name="hashAlgorithm" value="MD5"/>
      <module-option name="hashEncoding" value="RFC2617"/>
      <module-option name="hashUserPassword" value="false"/>
      <module-option name="hashStorePassword" value="true"/>
      <module-option name="passwordIsA1Hash" value="true"/>
      <module-option name="storeDigestCallback"
value="org.jboss.security.auth.callback.RFC2617Digest"/>
    </login-module>
  </authentication>
</security-domain>
```

2. Create SIP Server User Properties File

- a. Open a terminal and navigate to the `$JBOSS_HOME/standalone/configuration` directory:

```
home]$ cd standalone/configuration
```

- b. Create and open a `sip-servlets-users.properties` file and append the user lines to the file:

```
# A sample users.properties file, this line creates user "admin" with
# password "admin" for "sip-servlets-realm"
admin=<A1_cryptographic_string>
```

- c. To create `<A1_cryptographic_string>`, execute the following command in a terminal:

```
home]$ java -cp ../../modules/system/layers/base/org/picketbox/main/picketbox-
4.0.15.Final.jar org.jboss.security.auth.callback.RFC2617Digest admin sip-
servlets <password>
```

- d. Copy the A1 hash, and paste it into the admin parameter in the previous step.
- e. Save and close `sip-servlets-users.properties`.

3. Create the SIP Server Roles File

- a. Create and open `sip-servlets-roles.properties` (using your preferred editor) and append the following information to the file:

```
# A sample roles.properties file for use with some roles
# Each line in this file assigns roles to the users defined in
# sip-servlets-users.properties
admin=caller,role1,role2,..
```

4. Add the Security Domain to the SIP Application

- a. Open the `jboss-web.xml` file for the SIP application to which security is required.
- b. Add the `<security-domain>` element as a child of the `<jboss-web>` element:

```
<jboss-web>
  <security-domain>sip-servlets</security-domain>
</jboss-web>
```

5. Add Security Constraints to the SIP Application

- a. Open the `sip.xml` file for the SIP application.
- b. Add the `<security-constraint>` element as a child of the `<web-app>` element:

```
<security-constraint>
  <display-name>REGISTER Method Security Constraint</display-name>
  <resource-collection>
    <resource-name>SimpleSipServlet</resource-name>
    <description>Require authenticated REGISTER requests</description>
    <servlet-name>SimpleSipServlet</servlet-name>
    <sip-method>REGISTER</sip-method>
  </resource-collection>
  <auth-constraint>
    <role-name>caller</role-name>
  </auth-constraint>
</security-constraint>

<login-config>
  <auth-method>DIGEST</auth-method>
  <realm-name>sip-servlets</realm-name>
</login-config>
```

1. Activate the Memory Realm in Catalina:

- a. Open a terminal and navigate to the `/conf` directory:

```
home]$ cd server/default/<tomcat_home>/conf/
```

- b. Open `server.xml` and uncomment the following line:

```
<!--<Realm className="org.apache.catalina.realm.MemoryRealm"/>-->
```

2. Update SIP Server User Properties File

- a. In the `/conf` directory, open `tomcat-users.xml` (using your preferred editor) and append the following child element:

```
<user name="user" password="password" roles="caller"/>
```

3. Add Security Constraints to the SIP Application

- a. Open the `sip.xml` file for the SIP application to which security is required.
- b. Add the child element to the element:

```
<security-constraint>
  <display-name>REGISTER Method Security Constraint</display-name>
  <resource-collection>
    <resource-name>SimpleSipServlet</resource-name>
    <description>Require authenticated REGISTER requests</description>
    <servlet-name>SimpleSipServlet</servlet-name>
    <sip-method>REGISTER</sip-method>
  </resource-collection>
  <auth-constraint>
    <role-name>caller</role-name>
  </auth-constraint>
</security-constraint>
<login-config>
  <auth-method>DIGEST</auth-method>
  <realm-name>sip-servlets-realm</realm-name>
</login-config>
```