# **Linux Lab Midterm Project**

# **Linux Lab Midterm Project**

# **Daily User Log Archiver**

Student Name: Hrithvik Bhardwaj
Course: B.Tech CSE — Linux Lab
Project Type: Shell Scripting

Date: October 2025

#### Goal

Create a **shell script** that:

- Logs current system information (user, date, processes, disk usage)
- · Rotates and archives old logs weekly
- Runs automatically every day using a cron job

# **Implementation Details**

#### 1. Identify User

The script identifies the user executing it using:

whoami

Example:

```
echo "User: $(whoami)"
```

#### 2. File Management

Logs are stored in:

```
~/daily_logs/log_YYYY-MM-DD.txt
```

A new file is created every day, containing:

- · Current date and time
- · Logged-in user
- · System uptime

- Top 5 CPU-consuming processes
- Disk usage summary
- Kernel/system messages (via dmesg)

### 3. Archiving

- Logs older than 7 days are moved to ~/daily\_logs/archive
- Every **Sunday**, the archive directory is compressed into:

```
weekly_logs_YYYY-WW.tar.gz
```

#### 4. Loop and Conditions

The script uses a loop to check each log's age and move it if older than 7 days:

```
for file in log_*.txt; do
  if [ condition-to-check-age ]; then
    mv "$file" archive/
  fi
done
```

Optimized version uses:

```
find "${LOG_DIR}" -maxdepth 1 -type f -name 'log_*.txt' -mtime +7 -print0 | while

IFS= read -r -d $'�' file; do
    mv "$file" "${ARCHIVE_DIR}/"

done
```

## **Full Shell Script**

```
#!/usr/bin/env bash
# daily_log.sh - Daily User Log Archiver

set -u

BASE_DIR="${HOME}/daily_logs"
LOG_DIR="${BASE_DIR}/logs"
ARCHIVE_DIR="${BASE_DIR}/archive"
LOCKDIR="${BASE_DIR}/.lock"
WEEKLY_DIR="${BASE_DIR}"
TODAY="$(date +%Y-%m-%d)"
LOGFILE="log_${TODAY}.txt"
LOGPATH="${LOG_DIR}/${LOGFILE}"
WEEK_TAG="$(date +%Y-%V)"
```

```
mkdir -p "${LOG_DIR}" "${ARCHIVE_DIR}" || { echo "Failed to create log dirs"; exit
1; }
acquire_lock() {
  if mkdir "${LOCKDIR}" 2>/dev/null; then
  else
    echo "Another instance is running."
   exit 1
 fi
}
release_lock() {
  rm -rf "${LOCKDIR}"
}
write log() {
 {
    echo "=== Daily User Log ==="
    echo "Date: $(date --iso-8601=seconds)"
    echo "User: $(whoami)"
    echo
    echo "--- Uptime ---"
    uptime
    echo
    echo "--- Top 5 CPU processes ---"
    ps -eo pid, comm, %cpu, %mem --sort=-%cpu | head -n 6
    echo
    echo "--- Disk Usage ---"
    df -h
    echo
    echo "--- Log Directory Size ---"
    du -sh "${LOG_DIR}" 2>/dev/null
    echo
    echo "--- Recent Kernel Messages ---"
    if command -v dmesg >/dev/null 2>&1; then
     dmesg | tail -n 50
    else
      echo "(dmesg not available)"
    fi
    echo "=== End of Log ==="
  } > "${LOGPATH}"
  echo "Log written: ${LOGPATH}"
```

```
}
rotate old logs() {
  find "${LOG_DIR}" -maxdepth 1 -type f -name 'log_*.txt' -mtime +7 -print0 | while
IFS= read -r -d $'♠' file; do
    mv -v "$file" "${ARCHIVE_DIR}/"
 done
}
weekly archive if sunday() {
  if [ "$(date +%u)" -eq 7 ]; then
    if [ "$(find "${ARCHIVE_DIR}" -type f | wc -1)" -gt 0 ]; then
      TARNAME="${WEEKLY_DIR}/weekly_logs_${WEEK_TAG}.tar.gz"
      tar -czf "${TARNAME}" -C "${ARCHIVE_DIR}" .
      echo "Created weekly archive: ${TARNAME}"
      find "${ARCHIVE_DIR}" -type f -delete
      echo "Cleared archive directory."
    else
      echo "No files to archive."
    fi
 fi
}
show menu() {
 cat <<MENU
Daily Log Archiver Menu:
1) Create today's log
2) Rotate old logs
3) Create weekly archive
4) View latest log
0) Exit
MENU
  read -r choice
  case "${choice}" in
    1) main ;;
    2) rotate old logs ;;
    3) weekly_archive_if_sunday ;;
    4) ls -1t "${LOG_DIR}" | head -n1 | xargs -I{} cat "${LOG_DIR}/{}" ;;
    0) release_lock; exit 0 ;;
    *) echo "Invalid choice." ;;
  esac
}
```

```
main() {
    acquire_lock
    write_log
    rotate_old_logs
    weekly_archive_if_sunday
    release_lock
}

if [ "${1:-}" = "menu" ]; then
    acquire_lock
    show_menu
    release_lock
    exit 0

fi

main
exit 0
```

### **Cron Job Setup**

To schedule the script to run daily at 8 PM:

```
crontab -e

Add the line:
0 20 * * * /home/user/daily_log.sh >/dev/null 2>&1

Confirm with:
```

# **Directory Structure**

crontab -1

```
~/daily_logs/

├─ logs/

├─ log_2025-10-01.txt

├─ log_2025-10-02.txt

├─ archive/

├─ log_2025-09-25.txt
```

### **Optional Enhancements**

### 1. Email Logs Automatically

```
echo "Log attached" | mail -s "Daily Log" -a "$LOGPATH" user@example.com
```

#### 2. Error Handling

- o Script checks if directories exist before writing.
- Uses a lock (.lock) to avoid concurrent runs.

#### 3. Interactive Menu

Case-based menu allows manual logging, archiving, and viewing.

#### **Commands Used**

Feature	Command	Purpose
Identify User	whoami	Get current username
Date Format	date +%Y-%m-%d	Create timestamped filenames
Disk Usage	df -h	Human-readable disk usage
Process List	`ps -eo pid,comm,%cpu,%memsort=-%cpu	head -n 6`
File Search	<pre>findname "log_*.txt" -mtime +7</pre>	Find logs older than 7 days
Archiving	tar -czf	Compress weekly logs
Scheduling	crontab -e	Automate daily execution

# **Learning Outcomes**

- Practical experience with shell scripting, loops, and conditions
- Understanding of **cron jobs** for automation
- Use of system commands (ps, df, find, tar)
- Managing file I/O and directory structures
- Basic error handling and process synchronization

#### Conclusion

The Daily User Log Archiver efficiently:

- Automates daily system monitoring
- Reduces manual log management
- Demonstrates file handling, archiving, scheduling, and automation concepts

This project encapsulates key Linux administration skills through scripting.