

Low-Code API Orchestration Platform

Sample Requests and Responses

Name: Revanth Kumar Dompaka

Roll No: S20230010073

B.Tech in CSE

Indian Institute of Information Technology, Sri City

Base URL: `http://localhost:5000`

1 Health Check

Request

```
GET /health
```

Response

```
{
  "status": "ok",
  "message": "server is running"
}
```

2 Vendor Management

2.1 Create a Vendor

Request

```
POST /api/v1/vendors
Content-Type: application/json

{
  "name": "VendorG",
  "description": "Voter ID verification vendor - expects
    voterId and name",
```

```

    "baseUrl": "http://localhost:5000",
    "endpoint": "/vendors/vendorG/verify-voter-id",
    "method": "POST",
    "authentication": { "type": "NONE", "value": "" },
    "timeout": 5000,
    "retry": { "count": 3, "delay": 1000 },
    "responseSchema": {
        "voterStatus": "string - VALID or INVALID",
        "constituency": "string",
        "verifiedAt": "string - ISO date"
    }
}

```

Response

```

{
    "success": true,
    "status": "SUCCESS",
    "message": "vendor created successfully",
    "data": {
        "_id": "6a490dc898ada03a6cdc370b",
        "name": "VendorG",
        "description": "Voter ID verification vendor - expects voterId and name",
        "baseUrl": "http://localhost:5000",
        "endpoint": "/vendors/vendorG/verify-voter-id",
        "method": "POST",
        "timeout": 5000,
        "retry": { "count": 3, "delay": 1000 },
        "isActive": true,
        "createdAt": "2026-07-04T13:42:32.030Z"
    },
    "timestamp": "2026-07-04T13:42:32.381Z"
}

```

2.2 Get All Vendors

Request

```
GET /api/v1/vendors
```

Response

```
{
  "success": true,
  "status": "SUCCESS",
  "message": "vendors fetched successfully",
  "data": [
    {
      "_id": "6a48fdf07429c3e57021853f",
      "name": "VendorA",
      "description": "PAN verification vendor - expects
        panNumber and fullName",
      "baseUrl": "http://localhost:5000",
      "endpoint": "/vendors/vendorA/verify-pan",
      "method": "POST",
      "timeout": 5000,
      "retry": { "count": 3, "delay": 1000 },
      "isActive": true
    }
  ],
  "timestamp": "2026-07-04T11:20:47.678Z"
}
```

3 API Config Management

3.1 Create an API Config

Request

```
POST /api/v1/configs
Content-Type: application/json

{
  "name": "Verify Aadhaar and Voter ID",
  "description": "verifies Aadhaar using VendorC and if
    verified checks Voter ID",
  "endpoint": "/verify-aadhaar-voter",
  "method": "POST",
  "version": "v1",
  "validation": [
    {
```

```

        "field": "aadhaar",
        "required": true,
        "type": "string",
        "regex": "^[0-9]{12}$",
        "message": "aadhaar must be a 12 digit number"
    },
    {
        "field": "name",
        "required": true,
        "type": "string",
        "message": "name is required"
    },
    {
        "field": "voterId",
        "required": true,
        "type": "string",
        "regex": "^[A-Z]{3}[0-9]{7}$",
        "message": "voterId must be in valid format eg.
            ABC1234567"
    }
],
"workflow": [
    {
        "step": 1,
        "vendor": "6a48fdf07429c3e570218541",
        "requestMapping": { "aadhaar": "aadhaarNumber", "name": "name" },
        "responseMapping": { "status": "aadhaarStatus", "verifiedAt": "aadhaarVerifiedAt" },
        "condition": { "field": null, "operator": null, "value": null },
        "parallel": false,
        "onFailure": "STOP"
    },
    {
        "step": 2,
        "vendor": "6a490dc898ada03a6cdc370b",
        "requestMapping": { "voterId": "voterId", "name": "name" },
        "responseMapping": { "voterStatus": "voterStatus", "constituency": "constituency" },
    }
]

```

```

        "condition": { "field": "aadhaarStatus", "operator":
            "eq", "value": "VERIFIED" },
        "parallel": false,
        "onFailure": "STOP"
    }
]
}

```

Response

```

{
  "success": true,
  "status": "SUCCESS",
  "message": "api config created successfully",
  "data": {
    "_id": "6a490e9698ada03a6cdc370c",
    "name": "Verify Aadhaar and Voter ID",
    "endpoint": "/verify-aadhaar-voter",
    "method": "POST",
    "version": "v1",
    "isActive": true,
    "createdAt": "2026-07-04T13:45:58.113Z"
  },
  "timestamp": "2026-07-04T13:45:58.181Z"
}

```

4 Orchestrated Endpoints

4.1 Verify PAN — Success

Request

```

POST /api/v1/verify-pan
Content-Type: application/json

{
  "pan": "ABCDE1234F",
  "name": "Revanth Kumar"
}

```

Response

```
{
  "success": true,
  "status": "SUCCESS",
  "message": "workflow executed successfully",
  "data": {
    "status": "VALID",
    "confidence": 98
  },
  "timestamp": "2026-07-04T11:22:06.744Z"
}
```

4.2 Verify PAN — Validation Error (invalid format)

Request

```
POST /api/v1/verify-pan
Content-Type: application/json
```

```
{
  "pan": "INVALID123",
  "name": "Revanth Kumar"
}
```

Response

```
{
  "success": false,
  "status": "VALIDATION_FAILED",
  "message": "validation failed",
  "errors": [
    {
      "field": "pan",
      "message": "pan must be in valid format eg.
        ABCDE1234F"
    }
  ],
  "timestamp": "2026-07-04T11:23:08.560Z"
}
```

4.3 Verify PAN — Validation Error (empty body)

Request

```
POST /api/v1/verify-pan
Content-Type: application/json

{}
```

Response

```
{
  "success": false,
  "status": "VALIDATION_FAILED",
  "message": "validation failed",
  "errors": [
    {
      "field": "pan",
      "message": "pan must be in valid format eg.
        ABCDE1234F"
    },
    {
      "field": "name",
      "message": "name is required"
    }
  ],
  "timestamp": "2026-07-04T12:57:26.222Z"
}
```

4.4 Verify Aadhaar — Success

Request

```
POST /api/v1/verify-aadhaar
Content-Type: application/json

{
  "aadhaar": "327017735022",
  "name": "Revanth Kumar"
}
```

Response

```
{
  "success": true,
  "status": "SUCCESS",
  "message": "workflow executed successfully",
  "data": {
    "verificationStatus": "VERIFIED",
    "verifiedAt": "2026-07-04T13:06:08.547Z"
  },
  "timestamp": "2026-07-04T13:06:08.613Z"
}
```

4.5 Verify Document — 3-Step Pipeline (OCR → Fraud Detection → Face Match)

Request

```
POST /api/v1/verify-document
Content-Type: application/json

{
  "documentBase64": "dGVzdGRvY3VtZW50",
  "selfieBase64": "dGVzdHNIbGZpZQ=="
}
```

Response — all three step results merged into one

```
{
  "success": true,
  "status": "SUCCESS",
  "message": "workflow executed successfully",
  "data": {
    "name": "Sample User",
    "documentNumber": "ABCDE1234F",
    "documentType": "PAN",
    "ocrConfidence": 92,
    "ocrStatus": "EXTRACTED",
    "fraudScore": 12,
    "riskLevel": "LOW",
    "isFlagged": false,
  }
}
```



```
        "faceMatched": true,
        "similarity": 94.5,
        "faceMatchStatus": "MATCH"
    },
    "timestamp": "2026-07-04T13:06:57.733Z"
}
```

4.6 Verify Aadhaar and Voter ID — Multi-Step (manually configured)

Request

```
POST /api/v1/verify-aadhaar-voter
Content-Type: application/json

{
  "aadhaar": "327017735022",
  "name": "Revanth Kumar",
  "voterId": "ABC1234567"
}
```

Response

```
{
  "success": true,
  "status": "SUCCESS",
  "message": "workflow executed successfully",
  "data": {
    "aadhaarStatus": "VERIFIED",
    "aadhaarVerifiedAt": "2026-07-04T13:46:51.032Z",
    "voterStatus": "VALID",
    "constituency": "Sample Constituency",
    "voterVerifiedAt": "2026-07-04T13:46:52.647Z"
  },
  "timestamp": "2026-07-04T13:46:52.708Z"
}
```

5 AI Agent

5.1 Generate Config from Natural Language

Request

```
POST /api/v1/agent/generate-config
Content-Type: application/json

{
  "prompt": "Create an API that verifies PAN using VendorA and
    if successful runs fraud detection using VendorE"
}
```

Response

```
{
  "success": true,
  "status": "SUCCESS",
  "message": "Workflow generated successfully",
  "data": {
    "name": "Verify PAN and Detect Fraud",
    "description": "validates a PAN using VendorA and runs
      fraud detection using VendorE if successful",
    "endpoint": "/verify-pan-fraud",
    "method": "POST",
    "version": "v1",
    "validation": [
      {
        "field": "pan",
        "required": true,
        "type": "string",
        "regex": "^[A-Z]{5}[0-9]{4}[A-Z]{1}$",
        "message": "pan must be in valid format"
      },
      {
        "field": "name",
        "required": true,
        "type": "string",
        "message": "name is required"
      }
    ]
  },
}
```

```

    "workflow": [
      {
        "step": 1,
        "vendor": { "name": "VendorA" },
        "requestMapping": { "pan": "panNumber", "name": "
          fullName" },
        "responseMapping": {
          "verificationStatus": "panVerificationStatus
            ",
          "score": "panConfidenceScore"
        },
        "condition": { "field": null, "operator": null, "
          value": null },
        "onFailure": "STOP"
      },
      {
        "step": 2,
        "vendor": { "name": "VendorE" },
        "requestMapping": { "name": "name", "pan": "
          documentNumber" },
        "responseMapping": {
          "fraudScore": "fraudScore",
          "riskLevel": "riskLevel",
          "flagged": "isFlaggedForFraud"
        },
        "condition": {
          "field": "panVerificationStatus",
          "operator": "eq",
          "value": "VALID"
        },
        "onFailure": "CONTINUE"
      }
    ],
    "isActive": true,
    "_id": "6a4906e39f7bcd1e09a75944",
    "createdAt": "2026-07-04T13:13:07.439Z"
  },
  "timestamp": "2026-07-04T13:13:07.553Z"
}

```

5.2 Execute AI-Generated Endpoint

Request

```
POST /api/v1/verify-pan-fraud
Content-Type: application/json

{
  "pan": "ABCDE1234F",
  "name": "Revanth Kumar"
}
```

Response

```
{
  "success": true,
  "status": "SUCCESS",
  "message": "workflow executed successfully",
  "data": {
    "panVerificationStatus": "VALID",
    "panConfidenceScore": 98,
    "fraudScore": 12,
    "riskLevel": "LOW",
    "isFlaggedForFraud": false
  },
  "timestamp": "2026-07-04T13:14:11.739Z"
}
```

6 Edge Cases

6.1 Unknown Endpoint

Request

```
POST /api/v1/verify-something-random
Content-Type: application/json

{ "pan": "ABCDE1234F" }
```

Response

```
{
  "success": false,
  "status": "FAILED",
  "message": "no configuration found for POST /verify-something-random",
  "timestamp": "2026-07-04T12:58:34.994Z"
}
```

6.2 Wrong HTTP Method

Request

```
GET /api/v1/verify-pan
```

Response

```
{
  "success": false,
  "status": "FAILED",
  "message": "no configuration found for GET /verify-pan",
  "timestamp": "2026-07-04T13:01:09.763Z"
}
```

6.3 Aadhaar with Letters

Request

```
POST /api/v1/verify-aadhaar
Content-Type: application/json

{
  "aadhaar": "ABCDEFGHijkl",
  "name": "Revanth Kumar"
}
```

Response

```
{
  "success": false,
  "status": "VALIDATION_FAILED",
  "message": "validation failed",
  "errors": [
    {
      "field": "aadhaar",
      "message": "aadhaar must be a 12 digit number"
    }
  ],
  "timestamp": "2026-07-04T12:59:49.352Z"
}
```

6.4 Duplicate Endpoint via AI Agent

Request

```
POST /api/v1/agent/generate-config
Content-Type: application/json

{
  "prompt": "Create an API that verifies Aadhaar using VendorC
            and if verified runs face match using VendorF"
}
```

Response — when endpoint already exists

```
{
  "success": false,
  "status": "FAILED",
  "message": "endpoint already exists",
  "timestamp": "2026-07-04T13:09:46.996Z"
}
```

6.5 Missing Required Field — Document Pipeline

Request

```
POST /api/v1/verify-document
Content-Type: application/json
```

```
{
  "documentBase64": "dGVzdGRvY3VtZW50"
}
```

Response

```
{
  "success": false,
  "status": "VALIDATION_FAILED",
  "message": "validation failed",
  "errors": [
    {
      "field": "selfieBase64",
      "message": "selfieBase64 is required"
    }
  ],
  "timestamp": "2026-07-04T13:00:19.307Z"
}
```