Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;

for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;
}
```

Declare and initialization

Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;


for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;
}
```

Execute initializer
cnt is now 0

Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;

for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;
}
```

(cnt < 10) is true
since cnt is 0

Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;

for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;
}
```

Read x value, assuming input x is 0.001

Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;

for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;

}
```

This is true as x is 0.001

Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;


for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;

}
```

Continue: goes to the end of loop body

Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;

for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;
}
```

cnt is increased by 1

Trace for Loop with Continue

```
int cnt;
float x=0, sum=0;

for (cnt = 0; cnt < 10; cnt++)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        sum += x;
}
```

Compare cnt with 10…..

Trace while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

while (cnt < 10)
{

        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        ++cnt;

        sum += x;

}
```

Trace while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

while (cnt < 10)
{

        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        ++cnt;


        sum += x;


}
```

cnt<10 is true

Trace while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

while (cnt < 10)
{
        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        ++cnt;

        sum += x;

}
```

Read x, assuming x is 0.001

Trace while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

while (cnt < 10)
{

        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
    ++cnt;


    sum += x;

}
```

This is true as x is 0.001

Trace while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

while (cnt < 10)
{

        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        ++cnt;


        sum += x;


}
```

Continue: goes to the end of loop body

Trace while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

while (cnt < 10)
{

        cin >> x;
        if (x > -0.01 && x < 0.01)
                continue;
        ++cnt;


        sum += x;


}
```

Cnt is still 0, and we compare cnt with 10 again, which is true...

Trace do while Loop with continue

```cpp
int cnt = 0;
float x = 0, sum = 0;

do
{
    cin >> x;
    if (x > -0.01 && x < 0.01)
        continue;
    ++cnt;
    sum += x;
} while (cnt < 10);
```

Trace do while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

do
{
    cin >> x;
    if (x > -0.01 && x < 0.01)
        continue;
    ++cnt;
    sum += x;
} while (cnt < 10);
```

Read x, assuming x is 0.001

Trace do while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

do
{
    cin >> x;
    if (x > -0.01 && x < 0.01)
        continue;
    ++cnt;
    sum += x;
} while (cnt < 10);
```

This is true as x is 0.001

Trace do while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

do
{
    cin >> x;
    if (x > -0.01 && x < 0.01)
        continue;
    ++cnt;
    sum += x;
} while (cnt < 10);
```

Continue: goes to the end of loop body

Trace do while Loop with continue

```
int cnt = 0;
float x = 0, sum = 0;

do
{
    cin >> x;
    if (x > -0.01 && x < 0.01)
        continue;
    ++cnt;
    sum += x;
} while (cnt < 10);
```

cnt is still 0, and we compare cnt with 10 again, which is true…