SAMPLE REQUEST



Same body as HD01. FTD wordmark on the chest, NEVER ENOUGH death-metal logo across the back. Plain sleeves.

KEY FEATURES

- Cropped, boxy body with dropped shoulders and a blouson hem (body gathered into rib)
- Full balloon sleeves gathered into ribbed cuffs
- Two-piece hood with centre seam, self-lined
- Full-length front zip, single slider
- Split kangaroo pouch pocket, divided by the zip
- Ribbed cuffs and hem
- Screen prints applied by FTD in house (see artwork pages)

STYLE CODE	FTD-D01-HD02
STYLE NAME	Never Enough Zip Hoodie
COLLECTION	Drop 01
COLOUR	Black
SAMPLE TYPE	First (proto / fit) sample
SAMPLE SIZE	M
SIZE RANGE	XS · S · M · L · XL · XXL
QUANTITY	1 sample, plus 1 spare set of the printable panels for test prints
BRAND CONTACT	—
VERSION / DATE	v0.1 · 21 Oct 2026

IMPORTANT: PRINTED IN HOUSE

FTD screen prints this style itself. Please supply the panels listed on the "Cut panels" page **cut but not sewn**, send them to FTD for printing, then sew the sample when they return. Same pattern as FTD-D01-HD01 / HD02 (one hoodie block, two print versions).

Value status: CONFIRMED decided PROPOSED starting point, please advise

TBC answer needed

FLATS & FEATURES



FRONT




BACK

CALLOUTS

1. Two-piece hood, self-lined, centre seam
2. Zip top stop at neck
3. Full-length zip, metal, single slider
4. Dropped shoulder, topstitched
5. Split pouch pocket, bar-tacked ends
6. Balloon sleeve, gathered into cuff
7. Rib cuff
8. Rib hem, body gathered in (blouson)
9. Chest print P1 (FTD wordmark)
10. Hood centre seam
11. Back print area (see artwork page)

POINTS OF MEASURE



FRONT



BACK

Blue lines show the main points of measure; every point, with how to measure it, is in the measurement chart. Garment laid flat, unstretched unless noted.

A Body length
B Chest width
C Shoulder width (dropped)
D Body width above hem rib
E Hem rib width, relaxed
F Hem rib height
G Armhole, straight
H Sleeve length
I Bicep width
J Sleeve width at balloon
K Cuff width, relaxed
L Cuff height
M Neck width
N Front neck drop
O Hood height
P Hood width
Q Zip length
R Pouch pocket opening

MEASUREMENT CHART

CODE	POINT OF MEASURE	HOW TO MEASURE	XS	S	M	L	XL	XXL	TOL.	GRADE
A	Body length	HPS to bottom edge of hem rib	56	58	**60**	62	64	66	±1	2
B	Chest width	2.5 cm below armhole, edge to edge	60	63	**66**	69	72	75	±1	3
C	Shoulder width (dropped)	Shoulder seam point to point, across back	58	61	**64**	67	70	73	±1	3
D	Body width above hem rib	Edge to edge at the rib seam	46	49	**52**	55	58	61	±1	3
E	Hem rib width, relaxed	Bottom edge, edge to edge	34	37	**40**	43	46	49	±1	3
F	Hem rib height	Rib seam to bottom edge	7	7	**7**	7	7	7	±0.5	0
G	Armhole, straight	Shoulder point to underarm, straight	28	29	**30**	31	32	33	±0.5	1
H	Sleeve length	Shoulder seam to cuff edge, along top of sleeve	58	59	**60**	61	62	63	±1	1
I	Bicep width	2.5 cm below armhole, perpendicular to sleeve	27	28	**29**	30	31	32	±0.5	1
J	Sleeve width at balloon	Widest point of lower sleeve, approx. 20 cm above cuff	29	30	**31**	32	33	34	±0.5	1
K	Cuff width, relaxed	Cuff edge, edge to edge	8.5	9	**9.5**	10	10.5	11	±0.5	0.5
L	Cuff height	Cuff seam to edge	7	7	**7**	7	7	7	±0.5	0
M	Neck width	Seam to seam at shoulder	20	20.5	**21**	21.5	22	22.5	±0.5	0.5
N	Front neck drop	HPS to top of zip, vertical	8	8.5	**9**	9.5	10	10.5	±0.5	0.5
O	Hood height	Neck seam at side to top of hood	35	35.5	**36**	36.5	37	37.5	±1	0.5
P	Hood width	Widest point, laid flat	26	26.5	**27**	27.5	28	28.5	±0.5	0.5
Q	Zip length	Top stop to bottom of hem rib (to fit)	49	50.5	**52**	53.5	55	56.5	±0.5	1.5
R	Pouch pocket opening	Each side, along the opening edge	15	15.5	**16**	16.5	17	17.5	±0.5	0.5

All values PROPOSED

Centimetres, laid flat. Sample size M highlighted. Proportions follow the flats; please check the pattern against them and advise on any points that won't work.

MATERIALS & TRIMS

COMPONENT	SPECIFICATION	PLACEMENT	COLOUR	STATUS
Main fabric	100% cotton heavyweight fleece, brushed back, 450–500 gsm. Pre-shrunk; shrinkage ≤3% length and width. Cotton face required for screen printing (no polyester: ink dye migration).	Body, sleeves, hood, pocket	Black	PROPOSED
Hood lining	Self fabric (double-layer hood)	Hood	Black	PROPOSED
Rib	2×2 rib, 95% cotton / 5% elastane, approx. 400 gsm	Cuffs, hem	Black, matched to main	PROPOSED
Zip (sample)	Metal, open-end (separating), no. 5 or 8 teeth, single auto-lock slider. Best available stock zip in this finish.	Centre front	Gunmetal / black nickel	PROPOSED
Zip (production)	As above with custom FTD puller. Quote separately: mould cost and minimum order.	Centre front	TBC	TBC
Thread	Polyester core-spun, Tex 40	All seams	Black	PROPOSED
Neck tape	Woven or printed tape covering back neck seam (as drawn in flat)	Inside back neck	Black	TBC
Main label	Woven FTD label, artwork by FTD	Inside centre back neck	TBC	TBC
Size label	Woven or printed, size only	Under main label	TBC	TBC
Care / composition label	Printed satin; fibre composition, care symbols, brand	Left side seam, 8 cm above hem	White on black	PROPOSED

Please send fabric and rib swatches with your quote if possible, so FTD can test print on them before sampling.

AREA	DETAILS PROPOSED
Seams	Overlock (4-thread) all body and sleeve seams; twin-needle topstitch 6 mm at armhole seams as drawn.
Shoulders	Dropped shoulder; armhole seam topstitched on body side.
Sleeves	Balloon shape: extra volume in the lower sleeve, gathered evenly into the cuff. Cuff joined with overlock, topstitched.
Hem	Body gathered evenly into rib hem (blouson). Rib joined with overlock, cover-stitched.
Zip	Inserted between front panels, ending at hem rib bottom and at neck. Topstitched both sides 3 mm. Zip teeth exposed as drawn.
Hood	Two-piece, centre seam. Self-lined, joined at face opening and neck; no drawcord (per flat, confirm).
Pouch pocket	Split pouch, one each side of zip; opening edges bound or topstitched 6 mm; bar-tack at opening ends.
Neck	Back neck seam covered with neck tape; main label sewn into tape at centre back.
Finishing	Trim all threads; press; no fusing. Fold and bag individually.

Stitch details follow the dashed topstitch lines on the flats. Where a different method is standard in your factory for the same look, please suggest it.

ARTWORK & PRINT PLACEMENT



FRONT



BACK

PRINT	APPROX. SIZE CM (W × H)	PLACEMENT	PANELS PRINTED
P1 FTD wordmark	44.7 × 23.3	Centred on CF, across the zip. Top edge approx. 8 cm below HPS. Matched across the zip within 3 mm.	Front L, Front R
P2 NEVER ENOUGH logo	50.5 × 43.3	Centred on CB. Top edge approx. 2 cm below the hood seam.	Back

Method: Screen print by FTD in house. Ink: white plastisol or water-based discharge (TBC after test prints on the sample fabric). No printing by the manufacturer.

Sizes are taken from the flats and are approximate for the first sample. FTD will make 1:1 placement guides on the pattern pieces once the pattern is shared, so prints that cross seams line up.

CUT PANELS: PRINT BEFORE SEWING

WHY

The FTD wordmark crosses the zip, so the two front panels are printed before the zip goes in. The back is printed flat at the same time so all prints are cured together. FTD prints the flat panels, then the manufacturer sews the garment.

PANELS TO SEND TO FTD, CUT AND UNSEWN

- Front L
- Front R
- Back

PANELS THE FACTORY KEEPS

- Sleeves (×2)
- Hood (×2 outer, ×2 lining)
- Pouch pocket pieces
- Cuff rib (×2)
- Hem rib

STEPS

1. Manufacturer shares the pattern (PDF or DXF) for the sample size. FTD makes placement guides.
2. Manufacturer cuts the sample and sends the printable panels to FTD, plus **1 spare set** for test prints.
3. Each panel marked on the reverse with style code, size and panel name; all notches cut.
4. FTD prints and cures the panels, then returns them with the spare set marked as used.
5. Manufacturer sews the sample to this pack and sends it to FTD for fit approval.

Allow for print shrinkage: panels should be cut from pre-shrunk fabric. If the manufacturer can't supply unsewn panels, please tell us before quoting.

LABELS, QUESTIONS & APPROVAL

QUESTIONS FOR THE MANUFACTURER

1. Sample cost per style, lead time, and how many fit rounds are included.
2. Can you supply the printable panels cut but unsewn, then sew them after we return them printed? Cost and turnaround?
3. Production minimum order per style and colour, and how it can be split across sizes.
4. Fleece options at 450–500 gsm, 100% cotton: shrinkage figures and colourfastness.
5. Zip options for the sample (brand, finish), and for production: cost and minimum for a custom puller, including mould fee.
6. Can you grade the pattern XS–XXL and share the pattern pieces (PDF or DXF) so we can make print placement guides?
7. Can you source the woven main and size labels, and the care labels?
8. Shipping method, cost and duties to the UK.

LABELS

- UK law requires a fibre composition label on clothing sold in the UK (e.g. "100% cotton"). Care symbols are standard practice.
- Include the brand name and a contact address on the label or packaging so the product can be traced.
- Main label artwork, size label format and care wording will be supplied by FTD before production.

REVISION LOG

VERSION	DATE	CHANGE
v0.1	21 Oct 2026	First issue for sample quote

SAMPLE APPROVAL

STAGE	DATE	COMMENTS	APPROVED BY
Fit sample			
Print test			
Pre-production			