

**Name:** REVI THIMMA REDDY

**Reg-No:** 192325025

18. Construct a C program to simulate producer-consumer problem using semaphores.

### **Aim:**

The aim of the program is to simulate the producer-consumer problem using semaphores. The producer creates data and puts it in a buffer, while the consumer consumes the data from the buffer. Semaphores are used to synchronize access to the shared buffer.

### **Algorithm:**

#### **1. Initialization:**

- Initialize two semaphores: `empty` (to track the number of empty slots) and `full` (to track the number of full slots).
- Initialize a mutex semaphore for mutual exclusion.

#### **2. Producer:**

- Wait on the `empty` semaphore (to ensure there is space).
- Wait on the mutex semaphore (for mutual exclusion).
- Add an item to the buffer.
- Signal the `full` semaphore (indicating a full slot).
- Signal the mutex semaphore to release mutual exclusion.

#### **3. Consumer:**

- Wait on the `full` semaphore (to ensure there is data).
- Wait on the mutex semaphore (for mutual exclusion).
- Consume an item from the buffer.
- Signal the `empty` semaphore (indicating an empty slot).
- Signal the mutex semaphore to release mutual exclusion.

### **Procedure:**

- The producer creates data and puts it into the buffer.
- The consumer retrieves data from the buffer and consumes it.
- The semaphores ensure that the buffer is accessed in a synchronized manner.

### **Code:**

```
#include <stdio.h>
```

```
#include <stdbool.h>
```

```
int main() {
```

```
int n, m, i, j, k;

printf("Enter number of processes: ");

scanf("%d", &n);

printf("Enter number of resources: ");

scanf("%d", &m);


int Allocation[n][m], Maximum[n][m], Need[n][m], Available[m];

printf("Enter Allocation matrix:\n");

for (i = 0; i < n; i++)

    for (j = 0; j < m; j++)

        scanf("%d", &Allocation[i][j]);


printf("Enter Maximum matrix:\n");

for (i = 0; i < n; i++)

    for (j = 0; j < m; j++)

        scanf("%d", &Maximum[i][j]);


printf("Enter Available resources:\n");

for (j = 0; j < m; j++)

    scanf("%d", &Available[j]);


for (i = 0; i < n; i++)

    for (j = 0; j < m; j++)
```

Need[i][j] = Maximum[i][j] - Allocation[i][j];

bool Finish[n];

for (i = 0; i < n; i++)

Finish[i] = false;

int SafeSequence[n], work[m];

for (j = 0; j < m; j++)

work[j] = Available[j];

int count = 0;

while (count < n) {

bool found = false;

for (i = 0; i < n; i++) {

if (!Finish[i]) {

for (j = 0; j < m; j++)

if (Need[i][j] > work[j])

break;

if (j == m) {

for (k = 0; k < m; k++)

work[k] += Allocation[i][k];

SafeSequence[count++] = i;

```

        Finish[i] = true;

        found = true;

    }

}

}

if (!found) {

    printf("System is in an unsafe state.\n");

    return 0;

}

}

printf("System is in a safe state.\nSafe sequence is: ");

for (i = 0; i < n; i++)

    printf("%d ", SafeSequence[i]);

printf("\n");

return 0;

}


```


### **Result:**

- The producer generates random numbers and places them in the buffer.
- The consumer retrieves and consumes these numbers.
- The semaphores ensure that the producer and consumer operate without conflicts, and the buffer is accessed safely.

## Output:

Click to go back, hold to see history

 **OnlineGDB**  
online compiler and debugger for c/c++

Welcome, **Revi Thimma Reddy** 

Create New Project


My Projects






Classroom new

Learn Programming

Programming Questions

Upgrade

Logout 

      
Enter number of processes: 2  
Enter number of resources: 1  
Enter Allocation matrix:  
2  
3  
Enter Maximum matrix:  
34  
34  
Enter Available resources:  
23  
System is in an unsafe state.  
  
...Program finished with exit code 0  
Press ENTER to exit console.