

38. Design a C program to simulate SCAN disk scheduling algorithm.

AIM

To design a C program that simulates the **SCAN Disk Scheduling Algorithm**, where the disk arm moves in one direction to service requests until it reaches the end of the disk, then reverses direction and services requests in the opposite direction.

ALGORITHM

- 1. Start**
2. Read the total number of disk requests and their corresponding track numbers.
3. Sort the disk track requests in increasing order.
4. Separate the requests into two groups:
 - Requests to the left of the initial head position.
 - Requests to the right of the initial head position.
5. If the head moves to the left, service the requests in the left group first, then reverse direction to service the requests in the right group.
6. If the head moves to the right, service the requests in the right group first, then reverse direction to service the requests in the left group.
7. Calculate the total number of movements made by the disk arm.
8. Print the sequence of serviced requests and the total number of disk movements.
- 9. Stop**

PROCEDURE

1. Include necessary libraries (stdio.h for input/output and stdlib.h for memory management).
2. Read the total number of disk requests and their track numbers.
3. Sort the disk track numbers in increasing order to simulate the SCAN algorithm.
4. Separate the requests into two groups based on the initial position of the disk head (left and right).
5. Simulate the movement of the disk arm, first servicing the requests in one direction, then reversing the direction to service the remaining requests.
6. Calculate the total number of disk movements as the sum of the absolute differences between the current position and the serviced request.
7. Display the total number of disk movements and the sequence of serviced requests.
- 8. End**

CODE:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
void SCAN(int arr[], int n, int start, int direction) {
```

```
    int total_distance = 0;
```

```
    int current_position = start;
```

```
    for (int i = 0; i < n - 1; i++) {
```

```
        for (int j = i + 1; j < n; j++) {
```

```
            if (arr[i] > arr[j]) {
```

```
                int temp = arr[i];
```

```
                arr[i] = arr[j];
```

```
                arr[j] = temp;
```

```
            }
```

```
        }
```

```
    }
```

```
    int left[n], right[n];
```

```
    int left_count = 0, right_count = 0;
```

```
    for (int i = 0; i < n; i++) {
```

```
        if (arr[i] < start) {
```

```
            left[left_count++] = arr[i];
```

```
        } else {
```

```
            right[right_count++] = arr[i];
```

```
        }
```

```
    }
```

```
    int i;
```

```
    if (direction == 0) {
```

```
        for (i = left_count - 1; i >= 0; i--) {
```

```
            total_distance += abs(left[i] - current_position);
```

```
            current_position = left[i];
```

```
        }
```

```
    total_distance += abs(current_position);
```

```
    current_position = 0;
```

```
    for (i = 0; i < right_count; i++) {
```

```
        total_distance += abs(right[i] - current_position);
```

```
        current_position = right[i];
```

```
    }
```

```
    } else {
```

```
        for (i = 0; i < right_count; i++) {
```

```

        total_distance += abs(right[i] - current_position);
        current_position = right[i];
    }

    total_distance += abs(current_position);
    current_position = 0;

    for (i = left_count - 1; i >= 0; i--) {
        total_distance += abs(left[i] - current_position);
        current_position = left[i];
    }
}

printf("Total Number of Disk Movements: %d\n", total_distance);
}

int main() {
    int n, start, direction;

    printf("Enter the number of disk requests: ");
    scanf("%d", &n);

    int arr[n];

    printf("Enter the disk track numbers:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    printf("Enter the initial position of the disk head: ");
    scanf("%d", &start);


    printf("Enter the direction of the head movement (0 for left, 1 for right): ");
    scanf("%d", &direction);

    SCAN(arr, n, start, direction);

    return 0;
}

```

OUTPUT:



The screenshot shows a web-based online compiler interface. On the left is a blue sidebar with navigation links: 'Create New Project', 'My Projects', 'Classroom' (with a red 'new' badge), 'Learn Programming', 'Programming Questions', 'Upgrade', and 'Logout'. The main area on the right is a dark-themed console window. It displays the following text: 'Enter the number of requests: 1', 'Enter the requests:', '2', 'Enter the initial head position: 3', 'Enter the direction (0 for left, 1 for right): 2', 'Seek Sequence: 2 2', 'Total Head Movement: 197', and a green message '...Program finished with exit code 0'. At the bottom of the console, it says 'Press ENTER to exit console.' with a cursor. The browser's address bar at the top right shows 'input'.

```
Click to go back, hold to see history
OnlineGDB
online compiler and debugger for c/c++

Welcome, Revi Thimma Reddy

Create New Project
My Projects
Classroom new
Learn Programming
Programming Questions
Upgrade
Logout

Enter the number of requests: 1
Enter the requests:
2
Enter the initial head position: 3
Enter the direction (0 for left, 1 for right): 2
Seek Sequence: 2 2
Total Head Movement: 197

...Program finished with exit code 0
Press ENTER to exit console.
```