



SETU Code Lab Design Document

Diarmuid O'Neill

South East Technological University

12/02/2026

Table of Contents

Introduction	4
Hosting	4
Architecture Diagram	5
Sequence Diagrams	6
Solve a Problem	6
Login	7
Sign Up	7
View Problems	8
Create Problem / Test Cases.....	8
Update Problem / Test Cases.....	9
Create / Update Course	9
View Results	10
View Profile	10
View Leaderboard.....	11
Algorithms.....	12
Test Harness for Running Submitted Code.....	12
Approach to the use of Artificial Intelligence	13
Database.....	14
Entity Relationship Diagram	14
SQL Statements	15
Table Creation.....	15
Login/SignUp	17
View Problems.....	17
Solve Problem.....	17
CRUD Problem	18
CRUD Test Case.....	18
CRUD Course	19
View Results	20
View Profile	21
User Interface	22
Logo	22

High-Level UI Flow	22
Login	23
Sign Up	23
View Problems	24
View Problem > Solve Problem	24
View Problem > Solve Problem > Submission Alert.....	25
View Problem > Manage Problems	25
View Problem > Manage Problems > Create/Update Problem	26
View Problem > Manage Courses	26
View Problem > Manage Courses > Create/Update Course	27
View Problem > Manage Courses > View Course	27
View Problem > Manage Course > View Course > View Result	28
View Problem > Profile	28
Automated Deployment Script.....	29

Introduction


The purpose of this document is to outline the proposed design for SETU Code Lab. It will explore how each part of the project is intended to be implemented. It includes sections on hosting, sequence diagrams, important algorithms, database design and the user interface.

Hosting

The system will be hosted using DigitalOcean's Droplet service. This is a virtual private server (VPS). The \$12 per month regular option provides 2GBs of RAM, 1 CPU, 50GB of SSD storage and 1TB of bandwidth which should be enough for SETU Code Lab with some optimization. The chosen operating system for this server is Ubuntu 24.04 as it is very stable, provides excellent Docker support and is familiar to the developer.

For security purposes an SSH key will be generated and used to access the server console. This is faster and more secure than the password option that is offered by DigitalOcean. The Github repository containing the project will be cloned onto the server and the needed dependencies will be installed such as Node.js, Node Package Manager (NPM) and Nginx for serving the frontend.


Architecture Diagram




SETU Code Lab uses a three-tier architecture. Tier one (T1) is the client and is built using React, Typescript and SCSS. This is where the user interface resides. Tier two (T2) is the web server and is implemented using Node.js (this is a JavaScript runtime which allows TypeScript to run on a web server) and Express.js which is a Node.js framework used to simplify the routing process. This is where the application logic resides. Tier three (T3) is the services layer and consists of a PostgreSQL database which stores all the application data and the Docker service which is used to create temporary containers in which user submitted code runs in isolation.

Sequence Diagrams


Solve a Problem




Login




Sign Up




View Problems




Create Problem / Test Cases




Update Problem / Test Cases




Create / Update Course



View Results



View Profile



[View Leaderboard](#)

Algorithms

Test Harness for Running Submitted Code

To run student submitted functions they must be injected into a static string harness which contains a main class and the needed dependency imports to map sample inputs to function parameters. This allows any inputted java function to run in isolation in a docker container with sample inputs from associated test cases. This harness is mostly the same for all submissions; however, some parts need to be dynamic to allow functions with parameters of different primitive and complex types and functions with different numbers of parameters to run. The harness looks like this:

```
import com.fasterxml.jackson.databind.ObjectMapper;
import java.util.*;

public class Main {
    static final ObjectMapper mapper = new ObjectMapper();
    ${code}
    static class Input {
        ${inputFields}
    }
    public static void main(String[] args) {
        try {
            Input input = mapper.readValue(args[0], Input.class);
            ${functionCallLine}
            System.out.println(result);
        } catch (Exception e) {
            System.out.println("ERROR:" + e.getMessage());
        }
    }
}
```

`${code}` is the student's submitted code, `${inputFields}` are all the input parameter types and names, and `${functionCallLine}` contains the final return type, the function itself and the input parameters. "Input input = mapper.readValue(args[0], Input.class);" maps sample inputs from problem test cases, these are passed as arguments when the main function is called. Below are the commands that run inside the docker container which allow the java code to execute with test case inputs (`${processedInput}` is the test case inputs).

```
"sh", "-c", `
cat << 'EOF' > Main.java
${preprocessedCode}
EOF
javac Main.java
java -cp " ./app/*" Main '${processedInput}'
`
```


Approach to the use of Artificial Intelligence

It is likely that some students using SETU Code Lab will attempt to use generative AI to assist them with completing problems. This is not how the platform is intended to be used as it hinders students' ability to learn coding concepts effectively. While it is impossible to prevent the use of generative AI entirely, the platform aims to increase the work factor to discourage most users from using it. A file called `antiCheat.ts` has been created which disables copy/paste functionality and can detect when a user switches tabs. This is only active on the "solve a problem" screen and can be bypassed in certain situations. This only acts as a deterrent to the use of AI assistance.

```
export const useAntiCheat = () => {
  const [shouldAutoSubmit, setShouldAutoSubmit] = useState(false);
  useEffect(() => {
    const prevent = (e: Event) => e.preventDefault();
    const preventContext = (e: MouseEvent) =>
e.preventDefault();
    const handleKeyDown = (e: KeyboardEvent) => {
      if ((e.ctrlKey || e.metaKey) && ["c", "v", "x",
"a"].includes(e.key.toLowerCase())) {
        e.preventDefault()
        alert("Warning: Copy/Paste is disabled");
      }
    };
    const handleVisibility = () => {
      if (document.hidden) {
        setShouldAutoSubmit(true);
        alert("You left the tab. Your work has been
automatically submitted.");
      }
    }
    document.addEventListener("visibilitychange",
handleVisibility);
    document.addEventListener("copy", prevent);
    document.addEventListener("paste", prevent);
    document.addEventListener("cut", prevent);
    document.addEventListener("contextmenu", preventContext);
    document.addEventListener("keydown", handleKeyDown);
    return () => {
      document.removeEventListener("visibilitychange",
handleVisibility);
      document.removeEventListener("copy", prevent);
      document.removeEventListener("paste", prevent);
      document.removeEventListener("cut", prevent);
      ...
    }
  });
}
```

Database

Entity Relationship Diagram



SQL Statements

Table Creation

Problem Table

```
CREATE TABLE problem (  
    problem_id          SERIAL PRIMARY KEY,  
    user_id             INTEGER REFERENCES users(user_id),  
    problem_title       VARCHAR(255),  
    problem_description TEXT,  
    difficulty          INTEGER CHECK (difficulty BETWEEN 1 AND 5),  
    placeholder_code    TEXT  
);
```

Test_case Table

```
CREATE TABLE test_case (  
    test_case_id        SERIAL PRIMARY KEY,  
    problem_id          INT REFERENCES problem(problem_id) ON DELETE  
CASCADE,  
    input_value         JSONB NOT NULL,  
    expected_value      JSONB NOT NULL  
);
```

User Table

```
CREATE TABLE users (  
    user_id            SERIAL PRIMARY KEY,  
    user_name          TEXT NOT NULL,  
    email              VARCHAR(255) UNIQUE NOT NULL,  
    password           VARCHAR(255) NOT NULL,  
    role               VARCHAR(50) NOT NULL CHECK (role IN  
( 'student', 'lecturer' ))  
);
```

Submission Table

```
CREATE TABLE submission (  
    submission_id      SERIAL PRIMARY KEY,  
    user_id            INT REFERENCES users(user_id),  
    problem_id         INT REFERENCES problem(problem_id) ON DELETE  
CASCADE,  
    submitted_code     TEXT,  
    submitted_at       TIMESTAMP DEFAULT now(),  
    overall_status     BOOLEAN,  
    time_taken         INT,  
    percentage         INT  
);
```

Test_case_result Table

```
CREATE TABLE test_case_result (  
    test_case_result_id SERIAL PRIMARY KEY,  
    submission_id INT REFERENCES submission(submission_id) ON  
DELETE CASCADE,  
    test_case_id INT REFERENCES test_case(test_case_id) ON  
DELETE CASCADE,  
    passed BOOLEAN,  
    actual_output TEXT,  
    runtime_ms INTEGER  
);
```

Course Table

```
CREATE TABLE course (  
    course_id SERIAL PRIMARY KEY,  
    owner_id INT REFERENCES users(user_id) ON DELETE  
CASCADE,  
    course_title VARCHAR(255),  
    course_description TEXT,  
    created_at TIMESTAMP DEFAULT now()  
);
```

Enrollment Table

```
CREATE TABLE enrollment (  
    course_id INT REFERENCES course(course_id) ON DELETE  
CASCADE,  
    user_id INT REFERENCES users(user_id) ON DELETE  
CASCADE,  
    PRIMARY KEY (course_id, user_id)  
);
```

Course_problem Table

```
CREATE TABLE course_problem (  
    course_id INT REFERENCES course(course_id) ON DELETE  
CASCADE,  
    problem_id INT REFERENCES problem(problem_id) ON  
DELETE CASCADE,  
    PRIMARY KEY (course_id, problem_id)  
);
```


Login/SignUp

createUser SQL Statement

```
INSERT INTO users (user_name, role, email, password)
VALUES ($1, $2, $3, $4)
RETURNING *
```

getUserByEmail SQL Statement

```
SELECT user_id
AS id, user_name
AS name, email, password, role
FROM users
WHERE email = $1
```

View Problems

fetchProblems SQL Statement

```
SELECT problem.*, users.user_name
FROM problem
AS problem
JOIN users AS users
ON problem.user_id = users.user_id
```

Solve Problem

fetchTestCases SQL Statement

```
SELECT *
FROM test_case
WHERE problem_id=$1
```

createSubmission SQL Statement

```
INSERT INTO submission (user_id, problem_id, submitted_code,
overall_status, time_taken)
VALUES ($1, $2, $3, $4, $5)
RETURNING *
```

createTestCaseResult SQL Statement

```
INSERT INTO test_case_result (submission_id, test_case_id, passed,
actual_output, runtime_ms)
VALUES ($1, $2, $3, $4, $5)
```

CRUD Problem

insertProblem SQL Statement

```
INSERT INTO problem (user_Id, problem_title, problem_description,
difficulty, placeholder_code)
VALUES ($1, $2, $3, $4, $5)
RETURNING *
```

fetchProblemsByUserId SQL Statement

```
SELECT problem.*, users.user_name
FROM problem AS problem
JOIN users AS users
ON problem.user_id = users.user_id
WHERE problem.user_id = $1
```

getAllAvailableProblems SQL Statement

```
SELECT * FROM problem
WHERE user_id = $1 OR user_id = 1
```

updateProblem SQL Statement

```
UPDATE problem
SET problem_title=$1, problem_description=$2, difficulty=$3,
placeholder_code=$4
WHERE problem_id=$5 RETURNING *
```

deleteProblem SQL Statement

```
DELETE FROM problem WHERE problem_id=$1
RETURNING *
```

CRUD Test Case

createTestCase SQL Statement

```
INSERT INTO test_case (problem_id, input_value, expected_value)
VALUES ($1, $2::json, $3::json)
RETURNING *
```

updateTestCase SQL Statement

```
UPDATE test_case
SET input_value=$1, expected_value=$2
WHERE test_case_id=$3
RETURNING *
```

deleteTestCase SQL Statement

```
DELETE FROM test_case
  WHERE test_case_id=$1
RETURNING *
```

CRUD Course

fetchAllStudents SQL Statement

```
SELECT user_id AS student_id, user_name AS student_name
  FROM users
  WHERE role='student'
```

AddUserToCourse SQL Statement

```
INSERT INTO enrollment (course_id, user_id)
  VALUES (1, $1)
RETURNING *
```

fetchCourseByUserId SQL Statement

```
SELECT c.*
  FROM course c
  JOIN enrollment e ON c.course_id = e.course_id
  WHERE e.user_id = $1
```

fetchCreatedCourseByUserId

```
SELECT * FROM course WHERE owner_id=$1
```

insertCourse SQL Statement

```
INSERT INTO course (owner_id, course_title, course_description)
  VALUES ($1, $2, $3)
RETURNING *
```

insertCourseProblem SQL Statement

```
INSERT INTO course_problem (course_id, problem_id)
  VALUES ($1, $2) RETURNING *
```

insertEnrollment SQL Statement

```
INSERT INTO enrollment (course_id, user_id)
  VALUES ($1, $2) RETURNING *
```

updateCourseDetails SQL Statement

```
UPDATE course SET course_title=$1, course_description=$2
WHERE course_id=$3 RETURNING *
```

deleteCourseProblems SQL Statement

```
DELETE FROM course_problem WHERE course_id=$1
```

deleteEnrollmentsByCourseId SQL Statement

```
DELETE FROM enrollment WHERE course_id=$1
```

fetchProblemIdsFromCourse SQL Statement

```
SELECT problem_id FROM course_problem WHERE course_id = $1
```

fetchStudentIdsFromCourse SQL Statement

```
SELECT user_id FROM enrollment WHERE course_id = $1
```

View Results

fetchStudentsOnCourse SQL Statement

```
SELECT u.user_id, u.user_name FROM users u
JOIN enrollment e ON u.user_id = e.user_id
WHERE e.course_id = $1
```

getSubmissionsForCourse SQL Statement

```
SELECT DISTINCT ON (s.user_id, s.problem_id)
    s.submission_id,
    s.user_id,
    s.problem_id,
    s.submitted_code,
    s.submitted_at,
    s.overall_status,
    s.time_taken,
    s.percentage
FROM submission s
WHERE s.user_id = ANY($1)
AND s.problem_id = ANY($2)
AND s.submitted_at > $3::timestamp
ORDER BY
    s.user_id,
    s.problem_id,
    s.submitted_at DESC
```

fetchTestCaseResults SQL Statement

```
SELECT * FROM test_case_result WHERE submission_id=$1
```

View Profile

fetchUserData SQL Statement

```
SELECT user_id, user_name, email, role FROM users
      WHERE user_id = $1
```

deleteAccount SQL Statement

```
DELETE FROM users WHERE user_id = $1
```

getSubmissionsForUser SQL Statement

```
SELECT * FROM submission
      WHERE user_id = $1
      ORDER BY submitted_at DESC
```

getProblemsByIds SQL Statement

```
SELECT * FROM problem WHERE problem_id=ANY($1::int[])
```

User Interface


Logo

This is the logo and favicon for SETU Code Lab. It has been designed in the shape of the letter C and is intended to be simple and recognizable. The light grey and bright red colours have been chosen as they contrast well with the dark background chosen for the rest of the platform.




High-Level UI Flow

The diagram below shows how to navigate to each screen on the platform. Additional UI elements such as pop-ups and drop-down menus are not shown here, just the main screens. Items in the lecturer only box are only accessible to users with the lecturer role.




Login



The login form is centered on a dark gray background. It features the SETU Code Lab logo at the top left, which consists of a stylized 'C' with a red and white arrow. To the right of the logo is the text 'SETU Code Lab'. Below the logo and text are two input fields: one for 'email' with an envelope icon and one for 'password' with a lock icon. A red 'Log in' button is positioned below these fields. At the bottom of the form, there is a link that says 'Sign up if you don't have an account already'.

Sign Up



The sign up form is centered on a dark gray background. It features the SETU Code Lab logo at the top left, which consists of a stylized 'C' with a red and white arrow. To the right of the logo is the text 'SETU Code Lab'. Below the logo and text are four input fields: one for 'name' with a person icon, one for 'email' with an envelope icon, one for 'password' with a lock icon, and one for 'confirm password' with a lock icon. Below these fields are two radio buttons: 'Student' (selected) and 'Lecturer'. A red 'Sign up' button is positioned below the radio buttons. At the bottom of the form, there is a link that says 'Log in if you already have an account'.

View Problems

SETU Code Lab

Leaderboard | Problems | Profile

Log Out

Good Morning Diarmuid O'Neill

Search Questions...

- 1. Two Sum | Dr. John Doe ★☆☆☆☆
- ✓ 2. Wildcard Matching | Dr. Jane Doe ★★★★★
- ✓ 3. Add Two Numbers | Dr. Jane Doe ★★★★★
- 4. Median of Two Sorted Arrays | Dr. Jane Doe ★★★★★
- 5. Remove Element | Dr. Jane Doe ★★★★★
- 6. Two Sum | Dr. John Doe ★☆☆☆☆
- 7. Two Sum | Dr. John Doe ★☆☆☆☆
- 8. Two Sum | Dr. John Doe ★☆☆☆☆
- 9. Two Sum | Dr. John Doe ★☆☆☆☆
- 10. Two Sum | Dr. John Doe ★☆☆☆☆
- 11. Two Sum | Dr. John Doe ★☆☆☆☆

View Problem > Solve Problem

SETU Code Lab

1. Two Sum | Dr. John Doe ★☆☆☆☆

Given an array of integers `nums` and an integer `target`, return indices of the two numbers such that they add up to `target`.

You may assume that each input would have exactly one solution, and you may not use the same element twice.

You can return the answer in any order.

Example 1:
Input: `nums = [2,7,11,15]`, `target = 9`
Output: `[0,1]`
Explanation: Because `nums[0] + nums[1] == 9`, we return `[0, 1]`.

Example 2:
Input: `nums = [3,2,4]`, `target = 6`
Output: `[1,2]`

Example 3:
Input: `nums = [3,3]`, `target = 6`
Output: `[0,1]`

Constraints:

- `2 <= nums.length <= 104`
- `-109 <= nums[i] <= 109`
- `-109 <= target <= 109`
- Only one valid answer exists.

Follow-up: Can you come up with an algorithm that is less than $O(n^2)$ time complexity?

Code editor


```
1 class Solution {
2     public int[] twoSum(int[] nums, int target) {
3
4     }
5 }
```

Submit


Test cases

```
1 [2,7,11,15]
2 9
3 [3,2,4]
4 6
5 [3,3]
6 6
```


View Problem > Solve Problem > Submission Alert



View Problem > Manage Problems



View Problem > Manage Problems > Create/Update Problem

The screenshot shows the 'Create New Problem' form in the SETU Code Lab interface. The form is divided into two main sections: 'Create New Problem' on the left and 'Placeholder Code' on the right. The 'Create New Problem' section contains fields for 'Title' (with a placeholder 'eg. Palindrome Number...'), 'Difficulty' (with a placeholder 'eg. 0-5...'), and a 'Description' text area. The 'Description' area contains a sample markdown text for a palindrome problem. The 'Placeholder Code' section contains a code editor with a placeholder for Java code. Below the code editor are fields for 'Sample input' (placeholder 'eg. (*x*: 313)') and 'Expected output' (placeholder 'eg. true'). A '+ Add Test Case' button is located below these fields. A 'Next' button is at the bottom right of the form.

SETU Code Lab

Leaderboard | Problems | Profile

Courses ▾

Lecturer Menu ▾

Create New Problem

Title :

Difficulty :

Description :

eg. (markdown formatting is supported)

```
## Palindrome Number

Given an integer 'x', return 'true' if 'x' is a **palindrome**, and 'false' otherwise.

---

### Example 1

**Input:**

x = 121

**Output:**

true

**Explanation:**
```

Placeholder Code

```
eg.
public static boolean isPalindrome(int x) {
    *student code goes here*
}
```

Sample input :

Expected output :

+ Add Test Case

Next

View Problem > Manage Courses



The screenshot shows the 'Manage Courses' interface in the SETU Code Lab. It features a list of courses with their names and icons for editing and deleting. The courses are: 1. Y3 Software Development, 2. Y2 Games Development, 3. Y1 Common, and 4. All Students. A '+ Create New Class' button is at the bottom.



SETU Code Lab



Leaderboard | Problems | Profile

Courses ▾

Lecturer Menu ▾

1. Y3 Software Development  


2. Y2 Games Development  

3. Y1 Common  

4. All Students

+ Create New Class

View Problem > Manage Courses > Create/Update Course

SETU Code LabLeaderboard | Problems | Profile

Courses ▾

Lecturer Menu ▾

Create New Class

Title :

▾ Add Problem

▾ Add Student

1. Two Sum

2. Palindrome Number

3. Remove Element

4. Median of Two Sorted Arrays

1. Stuart Rossiter


2. Diarmuid O'Neill

3. Conor Hendley

4. Isaiah Andres

Next

View Problem > Manage Courses > View Course

SETU Code LabLeaderboard | Problems | Profile

Courses ▾


Lecturer Menu ▾

SWD Y3 - Student Results

	1. Two Sum	2. Palindrome Number	3. Remove element	4. Median of Two Sorted Arrays	Total
1. Stuart Rossiter	100%	-	100%	-	-
2. Diarmuid O'Neill	40%	80%	39%	33%	48%
3. Conor Hendley	100%	100%	99%	100%	100%
4. Isaiah Andres	100%	100%	100%	100%	100%

Download Results.csv

View Problem > Manage Course > View Course > View Result



The screenshot shows the SETU Code Lab interface. The top navigation bar includes the SETU Code Lab logo, the text 'Leaderboard | Problems | Profile', and a user profile icon. The left sidebar contains 'Courses' and 'Lecturer Menu' dropdowns. The main content area is divided into three sections:


- Submission Header:**
 - Title: Isalah Andres - Palindrome Number Submission
 - Submitted: Feb 15th, 2026 18:56
 - Overall Status: **Pass**
 - Time Taken: 01:01:21
- Submitted Code:**

```
public static boolean isPalindrome(int x) {
    if(x<0) {
        return false;
    }
    int forwards = x;
    int temp = 0;
    while(forwards != 0) {
        temp = temp * 10;
        temp += forwards % 10;
        forwards = (forwards / 10);
    }
    return temp == x
}
```
- Test Case Results:**

4/4 Test cases passed

Input:	Expected Output:	Actual Output :	Result:	Runtime:
{"x":121}	true	true	Pass	52ms
{"x":121}	true	true	Pass	52ms
{"x":121}	true	true	Pass	52ms
{"x":121}	true	true	Pass	52ms

View Problem > Profile



The screenshot shows the SETU Code Lab interface. The top navigation bar includes the SETU Code Lab logo, the text 'Leaderboard | Problems | Profile', and a user profile icon. The left sidebar contains 'Courses' and 'Lecturer Menu' dropdowns. The main content area is divided into two sections:

- User Profile:**
 - Avatar: Diarmuid O'Neill
 - Student
 - Problems completed: 24
 - Longest Streak: 3
 - Rank: **GOLD**
 - [Delete Account](#)
- Submission History:**

Problem:	Overall Status:	Submitted at:
1. Two Sum	Pass	Feb 15th, 2026 18:56
2. Palindrome Number	Pass	Feb 14th, 2026 19:23
3. Remove element	Fail	Feb 14th, 2026 18:03
4. Median of Two Sorted Arrays	Fail	Feb 10th, 2026 17:52
5. Two Sum	Pass	Feb 9th, 2026 18:56
6. Palindrome Number	Pass	Feb 7th, 2026 19:23
7. Remove element	Fail	Feb 2th, 2026 18:03
8. Median of Two Sorted Arrays	Fail	Jan 21th, 2026 17:52
9. Palindrome Number	Pass	Jan 14th, 2026 19:23
10. Remove element	Fail	Jan 12th, 2026 18:03
11. Median of Two Sorted Arrays	Fail	Jan 1th, 2026 17:52

Automated Deployment Script

The following script automates the deployment process. It works by pulling any code changes from the remote GitHub repository, running the frontend build step, running the backend build step and finally restarting the backend application.

```
#!/usr/bin/env bash

# Exit immediately if a command exits with a non-zero status
set -e

cd /var/www/SETU_Code_Lab || exit 1

git pull

cd /var/www/SETU_Code_Lab/SETU_Code_Lab_Code/client || exit 1

npm run build

cd /var/www/SETU_Code_Lab/SETU_Code_Lab_Code/server || exit 1

npm run build

pm2 restart setucl-backend

echo "Deployment Successful"
```