



iCrash :
A Crisis Management Case Study
MESSIR Analysis Document
- v 1.4 -
(Report type: Specification)

Wednesday 5th April, 2017 - 20:33

Contents

1	Introduction	15
1.1	Overview	15
1.2	Purpose and recipients of the document	15
1.3	Application Domain	15
1.4	Definitions, acronyms and abbreviations	15
1.5	Document structure	16
2	General Description	17
2.1	Domain Stakeholders	17
2.1.1	Communication Company	17
2.1.2	Humans	18
2.1.3	Coordinators	18
2.1.4	Administrator	18
2.1.5	Creator	19
2.1.6	Activator	19
2.2	System's Actors	20
2.3	Use Cases Model	20
2.3.1	Use Cases	20
2.3.2	Use Case Instance(s)	48
3	Environment Model	61
3.1	Local view 01	61
3.2	Local view 02	62
3.3	Local view 03	62
3.4	Local view 04	62
3.5	Local view 05	62
3.6	Local view 10	62
3.7	Local view 12	65
3.8	Global view 01	65
3.9	Actors and Interfaces Descriptions	66
3.9.1	actActivator Actor	66
3.9.2	actAdministrator Actor	66
3.9.3	actAuthenticated Actor	67
3.9.4	actCaptchaService Actor	67
3.9.5	actComCompany Actor	68
3.9.6	actCoordinator Actor	68
3.9.7	actDatabase Actor	69
3.9.8	actMailingService Actor	69
3.9.9	actMsrCreator Actor	70
3.9.10	actSystem Actor	70

4 Concept Model	71
4.1 PrimaryTypes-Classes	71
4.1.1 Local view 01	71
4.1.2 Local view 02	71
4.1.3 Local view 03	71
4.1.4 Local view 04	73
4.1.5 Global view 01	73
4.2 PrimaryTypes-Datatypes	73
4.2.1 Local view 06	73
4.2.2 Global view 01	73
4.3 SecondaryTypes-Datatypes	73
4.3.1 Local view 01	73
4.4 Concept Model Types Descriptions	76
4.4.1 Primary types - Class types descriptions	76
4.4.2 Primary types - Datatypes types descriptions	79
4.4.3 Primary types - Association types descriptions	81
4.4.4 Primary types - Aggregation types descriptions	82
4.4.5 Secondary types - Class types descriptions	82
4.4.6 Secondary types - Datatypes types descriptions	82
4.4.7 Secondary types - Association types descriptions	82
4.4.8 Secondary types - Aggregation types descriptions	82
4.4.9 Secondary types - Composition types descriptions	83
5 Operation Model	85
5.1 Environment - Out Interface Operation Scheme for actActivator	85
5.1.1 Operation Model for oeSetClock	85
5.1.2 Operation Model for oeSollicitateCrisisHandling	86
5.2 Environment - Out Interface Operation Scheme for actAdministrator	87
5.2.1 Operation Model for oeAddCoordinator	87
5.2.2 Operation Model for oeDeleteCoordinator	89
5.3 Environment - Out Interface Operation Scheme for actAuthenticated	91
5.3.1 Operation Model for oeSubmitCaptcha	91
5.3.2 Operation Model for oeLogin	92
5.3.3 Operation Model for oeLogout	94
5.4 Environment - Out Interface Operation Scheme for actCaptchaService	95
5.4.1 Operation Model for oeSendCaptcha	95
5.4.2 Operation Model for oeCaptchaInvalid	96
5.4.3 Operation Model for oeCaptchaValid	97
5.5 Environment - Out Interface Operation Scheme for actComCompany	98
5.5.1 Operation Model for oeAlert	98
5.6 Environment - Out Interface Operation Scheme for actCoordinator	101
5.6.1 Operation Model for oeCloseCrisis	101
5.6.2 Operation Model for oeGetAlertsSet	102
5.6.3 Operation Model for oeGetCrisisSet	102
5.6.4 Operation Model for oeInvalidateAlert	103
5.6.5 Operation Model for oeReportOnCrisis	105
5.6.6 Operation Model for oeSetCrisisHandler	105
5.6.7 Operation Model for oeSetCrisisStatus	106
5.6.8 Operation Model for oeSetCrisisType	106

5.6.9	Operation Model for oeValidateAlert	107
5.7	Environment - Out Interface Operation Scheme for actMsrCreator	108
5.7.1	Operation Model for oeCreateSystemAndEnvironment	108
5.8	Environment - Actor Operation Scheme for actMsrCreator	111
5.8.1	Operation Model for init	111
5.9	Primary Types - Operation Schemes for Class ctAdministrator	111
5.9.1	Operation Model for init	111
5.10	Primary Types - Operation Schemes for Class ctAlert	112
5.10.1	Operation Model for init	112
5.10.2	Operation Model for isSentToCoordinator	113
5.11	Primary Types - Operation Schemes for Class ctAuthenticated	113
5.11.1	Operation Model for init	113
5.12	Primary Types - Operation Schemes for Class ctCoordinator	114
5.12.1	Operation Model for init	114
5.13	Primary Types - Operation Schemes for Class ctCrisis	115
5.13.1	Operation Model for init	115
5.13.2	Operation Model for handlingDelayPassed	116
5.13.3	Operation Model for maxHandlingDelayPassed	116
5.13.4	Operation Model for isSentToCoordinator	117
5.13.5	Operation Model for isAllocatedIfPossible	117
5.14	Primary Types - Operation Schemes for Class ctHuman	118
5.14.1	Operation Model for init	118
5.14.2	Operation Model for isAcknowledged	119
5.15	Primary Types - Operation Schemes for Class ctState	120
5.15.1	Operation Model for init	120
5.16	Primary Types - Operation Schemes for Datatype dtAlertID	121
5.16.1	Operation Model for is	121
5.17	Primary Types - Operation Schemes for Datatype dtComment	121
5.17.1	Operation Model for is	121
5.18	Primary Types - Operation Schemes for Datatype dtCoordinatorID	122
5.18.1	Operation Model for is	122
5.19	Primary Types - Operation Schemes for Datatype dtCrisisID	123
5.19.1	Operation Model for is	123
5.20	Primary Types - Operation Schemes for Datatype dtGPSLocation	123
5.20.1	Operation Model for is	123
5.20.2	Operation Model for isNearTo	124
5.21	Primary Types - Operation Schemes for Datatype dtLatitude	125
5.21.1	Operation Model for is	125
5.22	Primary Types - Operation Schemes for Datatype dtLogin	125
5.22.1	Operation Model for is	125
5.23	Primary Types - Operation Schemes for Datatype dtLongitude	126
5.23.1	Operation Model for is	126
5.24	Primary Types - Operation Schemes for Datatype dtPassword	127
5.24.1	Operation Model for is	127
5.25	Primary Types - Operation Schemes for Datatype dtPhoneNumber	127
5.25.1	Operation Model for is	127
5.26	Primary Types - Operation Schemes for Enumeration etAlertStatus	128
5.26.1	Operation Model for is	128
5.27	Primary Types - Operation Schemes for Enumeration etCrisisStatus	129

5.27.1	Operation Model for is	129
5.28	Primary Types - Operation Schemes for Enumeration etCrisisType	129
5.28.1	Operation Model for is	129
5.29	Primary Types - Operation Schemes for Enumeration etHumanKind	130
5.29.1	Operation Model for is	130
5.30	Secondary Types - Operation Schemes for Classes	131
5.31	Secondary Types - Operation Schemes for Datatype dtSMS	131
5.31.1	Operation Model for is	131
5.32	Secondary Types - Operation Schemes for Enumerations	131
6	Test Model(s)	133
6.1	Test Model for testcase01	133
6.1.1	Test Steps Specification	133
6.1.2	Test Case Instance - instance01	154
6.1.3	Test Case Instance - instance01Part01	154
6.1.4	Test Case Instance - instance01Part02	156
7	Additional Constraints	159
7.1	Quality Constraints	159
7.1.1	Functional suitability	159
7.1.2	Performance efficiency	159
7.1.3	Compatibility	160
7.1.4	Usability	160
7.1.5	Reliability	161
7.1.6	Security	162
7.1.7	Maintainability	162
7.1.8	Portability	163
7.2	Other Constraints	164
A	Undocumented Messir Specification Elements	165
A.1	Undocumented Use Cases	165
A.1.1	Undocumented Use Cases - User-Goal Level	165
A.1.2	Undocumented Use Cases - Subfunction Level	165
A.1.3	Undocumented Use Case Views	165
A.2	Undocumented Use Case Instances	165
A.2.1	Undocumented Use Case Instances - User-Goal Level	165
A.2.2	Undocumented Use Case Instance Views	165
A.3	Undocumented Actors	166
A.4	Undocumented Environment Model Views	166
A.5	Undocumented Primary Types	166
A.5.1	Undocumented Primary Classe Types	166
A.5.2	Undocumented Primary Datatype Types	166
A.6	Undocumented Concept Model Views	166
A.7	Undocumented Operation Specifications	166
A.8	Undocumented Test-Case Instance Specifications	167
B	Specification project lu.uni.lassy.excalibur.examples.icrash	169
B.1	Use Cases Model	170
B.1.1	Use Cases	170

C Messir Specification Files Listing	171
C.1 File /src-gen/messir-spec/.views.msr	171
C.2 File /src-gen/messir-spec/operations/concepts/secondarytypes-datatypes/dtSMS.msr	171
C.3 File /src-gen/messir-spec/operations.../environment-actActivator-oeSetClock.msr	172
C.4 File /src-gen.../environment-actActivator-oeSollicitateCrisisHandling.msr	172
C.5 File /src-gen/messir-spec.../environment-actAdministrator-oeAddCoordinator.msr	173
C.6 File /src-gen.../environment-actAdministrator-oeDeleteCoordinator.msr	174
C.7 File /src-gen/messir-spec.../environment-actAuthenticated-oeSubmitCaptcha.msr	175
C.8 File /src-gen/messir-spec/operations.../environment-actAuthenticated.msr	176
C.9 File /src-gen/messir-spec.../environment-actCaptchaGenerator-oeSendCaptcha.msr	178
C.10 File /src-gen.../environment-actCaptchaValidator-oeCaptchaInvalid.msr	179
C.11 File /src-gen/messir-spec.../environment-actCaptchaValidator-oeCaptchaValid.msr	180
C.12 File /src-gen/messir-spec/operations/environment/environment-actComCompany.msr	181
C.13 File /src-gen/messir-spec.../environment-actCoordinator-oeCloseCrisis.msr	183
C.14 File /src-gen/messir-spec.../environment-actCoordinator-oeGetAlertsSet.msr	183
C.15 File /src-gen/messir-spec.../environment-actCoordinator-oeGetCrisisSet.msr	184
C.16 File /src-gen/messir-spec.../environment-actCoordinator-oeInvalidateAlert.msr	184
C.17 File /src-gen/messir-spec.../environment-actCoordinator-oeReportOnCrisis.msr	184
C.18 File /src-gen/messir-spec.../environment-actCoordinator-oeSetCrisisHandler.msr	185
C.19 File /src-gen/messir-spec.../environment-actCoordinator-oeSetCrisisStatus.msr	185
C.20 File /src-gen/messir-spec.../environment-actCoordinator-oeSetCrisisType.msr	185
C.21 File /src-gen/messir-spec.../environment-actCoordinator-oeValidateAlert.msr	186
C.22 File /src-gen/messir-spec/operations.../environment-actMsrCreator-init.msr	186
C.23 File /src-gen.../environment-actMsrCreator-oeCreateSystemAndEnvironment.msr	186
C.24 File /src-gen/messir-spec/concepts/environment-authentication.msr	188
C.25 File /src-gen/messir-spec/environment/environment.msr	188
C.26 File /src-gen/messir-spec/concepts/primarytypes-associations.msr	191
C.27 File /src-gen/messir-spec/concepts/primarytypes-authentication-datatypes.msr	192
C.28 File /src-gen/messir-spec.../primarytypes-classes-ctAdministrator.msr	193
C.29 File /src-gen/messir-spec/operations.../primarytypes-classes-ctAlert.msr	193
C.30 File /src-gen/messir-spec.../primarytypes-classes-ctAuthenticated.msr	194
C.31 File /src-gen/messir-spec/operations.../primarytypes-classes-ctCoordinator.msr	194
C.32 File /src-gen/messir-spec/operations.../primarytypes-classes-ctCrisis.msr	195
C.33 File /src-gen/messir-spec/operations.../primarytypes-classes-ctHuman.msr	197
C.34 File /src-gen/messir-spec/operations.../primarytypes-classes-ctState.msr	198
C.35 File /src-gen/messir-spec/concepts/primarytypes-classes.msr	198
C.36 File /src-gen/messir-spec/operations.../primarytypes-datatypes-dtAlertID.msr	200
C.37 File /src-gen/messir-spec/operations.../primarytypes-datatypes-dtComment.msr	201
C.38 File /src-gen/messir-spec.../primarytypes-datatypes-dtCoordinatorID.msr	201
C.39 File /src-gen/messir-spec/operations.../primarytypes-datatypes-dtCrisisID.msr	202
C.40 File /src-gen/messir-spec.../primarytypes-datatypes-dtGPSLocation.msr	202
C.41 File /src-gen/messir-spec/operations.../primarytypes-datatypes-dtLogin.msr	204
C.42 File /src-gen/messir-spec/operations.../primarytypes-datatypes-dtPassword.msr	204
C.43 File /src-gen/messir-spec.../primarytypes-datatypes-dtPhoneNumber.msr	204
C.44 File /src-gen/messir-spec.../primarytypes-datatypes-etAlertStatus.msr	205
C.45 File /src-gen/messir-spec.../primarytypes-datatypes-etCrisisStatus.msr	205
C.46 File /src-gen/messir-spec/operations.../primarytypes-datatypes-etCrisisType.msr	206
C.47 File /src-gen/messir-spec/operations.../primarytypes-datatypes-etHumanKind.msr	206
C.48 File /src-gen/messir-spec/concepts/primarytypes-datatypes.msr	207

C.49	File /src-gen/messir-spec/concepts/secondarytypes-associations.msr	208
C.50	File /src-gen/messir-spec/concepts/secondarytypes-classes.msr	208
C.51	File /src-gen/messir-spec/concepts/secondarytypes-datatypes.msr	208
C.52	File /src-gen/messir-spec/usecases/subfunctions-usecases.msr	209
C.53	File /src-gen/messir-spec/test/tc-testcase01.msr	212
C.54	File /src-gen/messir-spec/test/tci-testcase01-instance01.msr	221
C.55	File /src-gen/messir-spec/usecases/usecase-suDeployAndRun.msr	230
C.56	File /src-gen/messir-spec/usecases/usecase-suGlobalCrisisHandling.msr	235
C.57	File /src-gen/messir-spec/usecases/usecase-ugAdministrateTheSystem.msr	235
C.58	File /src-gen/messir-spec/usecases/usecase-ugAverageTypeofCrisis.msr	236
C.59	File /src-gen/messir-spec/usecases/usecase-ugCrisisInTime.msr	237
C.60	File /src-gen/messir-spec/usecases/usecase-ugLogin.msr	237
C.61	File /src-gen/messir-spec/usecases/usecase-ugManageCrisis.msr	238
C.62	File /src-gen/messir-spec/usecases/usecase-ugMonitor.msr	239
C.63	File /src-gen/messir-spec/usecases/usecase-ugSecurelyUseSystem.msr	239
C.64	File /src-gen/messir-spec/usecases/usecase-ugUserActivity.msr	239
C.65	File /src-gen/messir-spec/usecases/usecase-ugVictimSendFamilyNotification.msr . .	240
C.66	File /src-gen/messir-spec/usecases/usecase-ugWitnessSendFamilyNotification.msr . .	241
C.67	File /src-gen/messir-spec/usecases/usecaseinstance-uciugLogin.msr	242
C.68	File /.../usecaseinstance-ugAverageTypeofCrisis-uciugStatisticAvergeTypeofCrisis.msr	243
C.69	File /src-gen.../usecaseinstance-ugCrisisInTime-uciugStatisticCrisisInTime.msr . .	244
C.70	File /src-gen.../usecaseinstance-ugSecurelyUseSystem-uciugSecurelyUseSystem.msr .	244
C.71	File /src-gen.../usecaseinstance-ugUserActivity-uciugUserActivity.msr	245
C.72	File /.../usecaseinstance-ugVictimSendFamilyNotification-uciugVictimSendFamilyNotification.msr	245
C.73	File /.../usecaseinstance-ugWitnessSendFamilyNotification-uciugWitnessSendFamilyNotification.msr	246

D Listing of the Prolog Files Referenced in the Operation Model Specification . 249

D.1	File /src-gen/prolog-ref-spec/Operations.../outactActivator-oeSetClock.pl	249
D.2	File /src-gen/prolog-ref-spec.../outactActivator-oeSollicitateCrisisHandling.pl	250
D.3	File /src-gen/prolog-ref-spec.../outactAdministrator-oeAddCoordinator.pl	252
D.4	File /src-gen/prolog-ref-spec.../outactAdministrator-oeDeleteCoordinator.pl	253
D.5	File /src-gen/prolog-ref-spec/Operations.../outactAuthenticated-oeLogin.pl	254
D.6	File /src-gen/prolog-ref-spec/Operations.../outactAuthenticated-oeLogout.pl	256
D.7	File /src-gen/prolog-ref-spec/Operations.../outactComCompany-oeAlert.pl	257
D.8	File /src-gen/prolog-ref-spec/Operations.../outactCoordinator-oeCloseCrisis.pl	261
D.9	File /src-gen/prolog-ref-spec/Operations.../outactCoordinator-oeGetAlertsSet.pl . .	262
D.10	File /src-gen/prolog-ref-spec/Operations.../outactCoordinator-oeGetCrisisSet.pl . .	263
D.11	File /src-gen/prolog-ref-spec.../outactCoordinator-oeInvalidateAlert.pl	264
D.12	File /src-gen/prolog-ref-spec.../outactCoordinator-oeReportOnCrisis.pl	266
D.13	File /src-gen/prolog-ref-spec.../outactCoordinator-oeSetCrisisHandler.pl	267
D.14	File /src-gen/prolog-ref-spec.../outactCoordinator-oeSetCrisisStatus.pl	269
D.15	File /src-gen/prolog-ref-spec.../outactCoordinator-oeSetCrisisType.pl	271
D.16	File /src-gen/prolog-ref-spec.../outactCoordinator-oeValidateAlert.pl	272
D.17	File /src-gen.../outactMsrCreator-oeCreateSystemAndEnvironment.pl	274
D.18	File /src-gen/prolog-ref-spec.../PrimaryTypesClasses-ctAdministrator-init.pl	276
D.19	File /src-gen/prolog-ref-spec/Operations.../PrimaryTypesClasses-ctAlert-init.pl . . .	276
D.20	File /src-gen.../PrimaryTypesClasses-ctAlert-isSentToCoordinator.pl	277
D.21	File /src-gen/prolog-ref-spec.../PrimaryTypesClasses-ctAuthenticated-init.pl	277
D.22	File /src-gen/prolog-ref-spec.../PrimaryTypesClasses-ctCoordinator-init.pl	278

D.23	File /src-gen.../PrimaryTypesClasses-ctCrisis-handlingDelayPassed.pl	278
D.24	File /src-gen/prolog-ref-spec.../PrimaryTypesClasses-ctCrisis-init.pl	279
D.25	File /src-gen.../PrimaryTypesClasses-ctCrisis-isAllocatedIfPossible.pl	279
D.26	File /src-gen.../PrimaryTypesClasses-ctCrisis-isSentToCoordinator.pl	280
D.27	File /src-gen.../PrimaryTypesClasses-ctCrisis-maxHandlingDelayPassed.pl	281
D.28	File /src-gen/prolog-ref-spec/Operations.../PrimaryTypesClasses-ctHuman-init.pl .	282
D.29	File /src-gen/prolog-ref-spec.../PrimaryTypesClasses-ctHuman-isAcknowledged.pl .	282
D.30	File /src-gen/prolog-ref-spec/Operations.../PrimaryTypesClasses-ctState-init.pl .	282
D.31	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtAlertID-is.pl	283
D.32	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtComment-is.pl	284
D.33	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtCoordinatorID-is.pl .	284
D.34	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtCrisisID-is.pl	285
D.35	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtGPSLocation-is.pl . . .	285
D.36	File /src-gen.../PrimaryTypesDatatypes-dtGPSLocation-isNearTo.pl	286
D.37	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtLatitude-is.pl	287
D.38	File /src-gen/prolog-ref-spec/Operations.../PrimaryTypesDatatypes-dtLogin-is.pl .	287
D.39	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtLongitude-is.pl	288
D.40	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtPassword-is.pl	288
D.41	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-dtPhoneNumber-is.pl . .	289
D.42	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-etAlertStatus-is.pl	289
D.43	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-etCrisisStatus-is.pl	290
D.44	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-etCrisisType-is.pl	290
D.45	File /src-gen/prolog-ref-spec.../PrimaryTypesDatatypes-etHumanKind-is.pl	291
D.46	File /src-gen/prolog-ref-spec/Operations.../SecondaryTypesDatatypes-dtSMS-is.pl .	291
Glossary	293

List of Figures

2.1	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-suDeployAndRun	22
2.2	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-suGlobalCrisisHandling . .	30
2.3	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugAdministrateTheSystem	30
2.4	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugAverageTypeofCrisis . . .	31
2.5	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugCrisisInTime	31
2.6	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugLogin	32
2.7	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugManageCrisis	35
2.8	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugMonitor	35
2.9	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugSecurelyUseSystem . . .	36
2.10	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugUserActivity	36
2.11	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugVictimSendFamilyNotification	36
2.12	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-ugWitnessSendFamilyNotification	37
2.13	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-oeSetCrisisHandler	42
2.14	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-oeSollicitateCrisisHandling	43
2.15	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-suDeployAndRun-uciSimpleAndComplete-Part0	
2.16	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-suDeployAndRun-uciSimpleAndComplete-Part0	
2.17	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugStatisticAverageTypeofCrisis	51
2.18	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugStatisticCrisisInTime	52
2.19	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugLoginCaptchaFailure	52
2.20	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugLoginCaptchaSuccess	53
2.21	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugLoginCaptchaToleranceExceeded	53
2.22	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugLoginFailure	54
2.23	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugLoginRejected	54
2.24	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugLoginSuccess	57
2.25	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugSecurelyUseSystem .	57
2.26	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugUserActivity	58
2.27	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugVictimSendFamilyNotification	58
2.28	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: uci-uciugWitnessSendFamilyNotification	59
3.1	Environment Model - Local View 01 - environment model local view - Part	61
3.2	Environment Model - Local View 02 - environment model local view - Part	62
3.3	Environment Model - Local View 03 - administrator actor environment mode	63
3.4	Environment Model - Local View 04 - coordinator actor environment model	63
3.5	Environment Model - Local View 05 - authenticated actor environment mode	64
3.6	Environment Model - Local View 10 -	64
3.7	Environment Model - Local View 12 -	65
3.8	Environment Model - Global View 01 - em-gv-01 environment model global v	66
4.1	Concept Model - PrimaryTypes-Classes local view 01 - Local view of all the primary types	71
4.2	Concept Model - PrimaryTypes-Classes local view 02 - local view of the ctState primary ty	72
4.3	Concept Model - PrimaryTypes-Classes local view 03 - local view of the ctAlert primary ty	72

4.4	Concept Model - PrimaryTypes-Classes local view 04 - local view of the ctCrisis primary t	73
4.5	Concept Model - PrimaryTypes-Classes global view 01 - Primary types class types global vi	74
4.6	Concept Model - PrimaryTypes-Datatypes local view 06 -	74
4.7	Concept Model - PrimaryTypes-Datatypes global view 01 - global view of primary types dataty	75
4.8	Concept Model - SecondaryTypes-Datatypes local view 01 - Local view of the secondary types da	76
5.1	lu.uni.lassy.excalibur.examples.icrash Operation Scope: operation-scope-outactActivator-oeSollicitateCri	
5.2	lu.uni.lassy.excalibur.examples.icrash Operation Scope: operation-scope-outactComCompany-oeAlertv2	
5.3	lu.uni.lassy.excalibur.examples.icrash Operation Scope: operation-scope-outactComCompany-oeAlertv3	
5.4	lu.uni.lassy.excalibur.examples.icrash Operation Scope: operation-scope-outactMsrCreator-oeCreateSyst	
6.1	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: tci-testcase01-instance01-Part01	155
6.2	lu.uni.lassy.excalibur.examples.icrash Sequence Diagram: tci-testcase01-instance01-Part02	157
B.1	lu.uni.lassy.excalibur.examples.icrash Use Case Diagram: uc-oeCloseCrisis	170

Listings

5.1	Messir (MCL-oriented) specification of the operation <i>oeSetClock</i>	85
5.2	Messir (MCL-oriented) specification of the operation <i>oeSollicitateCrisisHandling</i>	86
5.3	Messir (MCL-oriented) specification of the operation <i>oeAddCoordinator</i>	89
5.4	Messir (MCL-oriented) specification of the operation <i>oeDeleteCoordinator</i>	90
5.5	Messir (MCL-oriented) specification of the operation <i>oeSubmitCaptcha</i>	91
5.6	Messir (MCL-oriented) specification of the operation <i>oeLogin</i>	93
5.7	Messir (MCL-oriented) specification of the operation <i>oeLogout</i>	94
5.8	Messir (MCL-oriented) specification of the operation <i>oeSendCaptcha</i>	95
5.9	Messir (MCL-oriented) specification of the operation <i>oeCaptchaInvalid</i>	97
5.10	Messir (MCL-oriented) specification of the operation <i>oeCaptchaValid</i>	98
5.11	Messir (MCL-oriented) specification of the operation <i>oeAlert</i>	100
5.12	Messir (MCL-oriented) specification of the operation <i>oeCreateSystemAndEnvironment</i>	108
5.13	Messir (MCL-oriented) specification of the operation <i>init</i>	111
5.14	Messir (MCL-oriented) specification of the operation <i>init</i>	112
5.15	Messir (MCL-oriented) specification of the operation <i>isSentToCoordinator</i>	113
5.16	Messir (MCL-oriented) specification of the operation <i>init</i>	114
5.17	Messir (MCL-oriented) specification of the operation <i>init</i>	115
5.18	Messir (MCL-oriented) specification of the operation <i>handlingDelayPassed</i>	116
5.19	Messir (MCL-oriented) specification of the operation <i>maxHandlingDelayPassed</i>	117
5.20	Messir (MCL-oriented) specification of the operation <i>isSentToCoordinator</i>	117
5.21	Messir (MCL-oriented) specification of the operation <i>isAllocatedIfPossible</i>	118
5.22	Messir (MCL-oriented) specification of the operation <i>init</i>	119
5.23	Messir (MCL-oriented) specification of the operation <i>init</i>	120
5.24	Messir (MCL-oriented) specification of the operation <i>is</i>	121
5.25	Messir (MCL-oriented) specification of the operation <i>is</i>	122
5.26	Messir (MCL-oriented) specification of the operation <i>is</i>	122
5.27	Messir (MCL-oriented) specification of the operation <i>is</i>	123
5.28	Messir (MCL-oriented) specification of the operation <i>is</i>	124
5.29	Messir (MCL-oriented) specification of the operation <i>isNearTo</i>	124
5.30	Messir (MCL-oriented) specification of the operation <i>is</i>	125
5.31	Messir (MCL-oriented) specification of the operation <i>is</i>	126
5.32	Messir (MCL-oriented) specification of the operation <i>is</i>	126
5.33	Messir (MCL-oriented) specification of the operation <i>is</i>	127
5.34	Messir (MCL-oriented) specification of the operation <i>is</i>	128
5.35	Messir (MCL-oriented) specification of the operation <i>is</i>	128
5.36	Messir (MCL-oriented) specification of the operation <i>is</i>	129
5.37	Messir (MCL-oriented) specification of the operation <i>is</i>	130
5.38	Messir (MCL-oriented) specification of the operation <i>is</i>	130
5.39	Messir (MCL-oriented) specification of the operation <i>is</i>	131

6.1	Messir (MCL-oriented) specification of the test step <i>testcase01-ts01oeCreateSystemAndEnvironment</i>	
6.2	Messir (MCL-oriented) specification of the test step <i>testcase01-ts02oeSetClock</i>	134
6.3	Messir (MCL-oriented) specification of the test step <i>testcase01-ts03oeLogin</i>	136
6.4	Messir (MCL-oriented) specification of the test step <i>testcase01-ts04oeAddCoordinator</i>	137
6.5	Messir (MCL-oriented) specification of the test step <i>testcase01-ts05oeLogout</i>	138
6.6	Messir (MCL-oriented) specification of the test step <i>testcase01-ts06oeSetClock02</i>	138
6.7	Messir (MCL-oriented) specification of the test step <i>testcase01-ts07oeAlert1</i>	140
6.8	Messir (MCL-oriented) specification of the test step <i>testcase01-ts08oeSetClock03</i>	141
6.9	Messir (MCL-oriented) specification of the test step <i>testcase01-ts09oeSollicitateCrisisHandling</i>	142
6.10	Messir (MCL-oriented) specification of the test step <i>testcase01-ts10oeLogin02</i>	143
6.11	Messir (MCL-oriented) specification of the test step <i>testcase01-ts11oeGetCrisisSet</i>	144
6.12	Messir (MCL-oriented) specification of the test step <i>testcase01-ts12oeSetCrisisHandler</i>	146
6.13	Messir (MCL-oriented) specification of the test step <i>testcase01-ts13oeSetClock04</i>	147
6.14	Messir (MCL-oriented) specification of the test step <i>testcase01-ts14oeValidateAlert</i>	148
6.15	Messir (MCL-oriented) specification of the test step <i>testcase01-ts15oeAlert2</i>	149
6.16	Messir (MCL-oriented) specification of the test step <i>testcase01-ts16oeSetClock05</i>	151
6.17	Messir (MCL-oriented) specification of the test step <i>testcase01-ts17oeSetCrisisStatus</i>	152
6.18	Messir (MCL-oriented) specification of the test step <i>testcase01-ts18oeReportOnCrisis</i>	153
6.19	Messir (MCL-oriented) specification of the test step <i>testcase01-ts19oeCloseCrisis</i>	154
C.1	Messir Spec. file .views.msr	171
C.2	Messir Spec. file dtSMS.msr	171
C.3	Messir Spec. file environment-actActivator-oeSetClock.msr	172
C.4	Messir Spec. file environment-actActivator-oeSollicitateCrisisHandling.msr	172
C.5	Messir Spec. file environment-actAdministrator-oeAddCoordinator.msr	173
C.6	Messir Spec. file environment-actAdministrator-oeDeleteCoordinator.msr	174
C.7	Messir Spec. file environment-actAuthenticated-oeSubmitCaptcha.msr	175
C.8	Messir Spec. file environment-actAuthenticated.msr	176
C.9	Messir Spec. file environment-actCaptchaGenerator-oeSendCaptcha.msr	178
C.10	Messir Spec. file environment-actCaptchaValidator-oeCaptchaInvalid.msr	179
C.11	Messir Spec. file environment-actCaptchaValidator-oeCaptchaValid.msr	180
C.12	Messir Spec. file environment-actComCompany.msr	181
C.13	Messir Spec. file environment-actCoordinator-oeCloseCrisis.msr	183
C.14	Messir Spec. file environment-actCoordinator-oeGetAlertsSet.msr	183
C.15	Messir Spec. file environment-actCoordinator-oeGetCrisisSet.msr	184
C.16	Messir Spec. file environment-actCoordinator-oeInvalidateAlert.msr	184
C.17	Messir Spec. file environment-actCoordinator-oeReportOnCrisis.msr	184
C.18	Messir Spec. file environment-actCoordinator-oeSetCrisisHandler.msr	185
C.19	Messir Spec. file environment-actCoordinator-oeSetCrisisStatus.msr	185
C.20	Messir Spec. file environment-actCoordinator-oeSetCrisisType.msr	185
C.21	Messir Spec. file environment-actCoordinator-oeValidateAlert.msr	186
C.22	Messir Spec. file environment-actMsrCreator-init.msr	186
C.23	Messir Spec. file environment-actMsrCreator-oeCreateSystemAndEnvironment.msr	186
C.24	Messir Spec. file environment-authentication.msr	188
C.25	Messir Spec. file environment.msr	188
C.26	Messir Spec. file primarytypes-associations.msr	191
C.27	Messir Spec. file primarytypes-authentication-datatypes.msr	192
C.28	Messir Spec. file primarytypes-classes-ctAdministrator.msr	193
C.29	Messir Spec. file primarytypes-classes-ctAlert.msr	193
C.30	Messir Spec. file primarytypes-classes-ctAuthenticated.msr	194

C.31	Messir Spec. file primarytypes-classes-ctCoordinator.msr.	194
C.32	Messir Spec. file primarytypes-classes-ctCrisis.msr.	195
C.33	Messir Spec. file primarytypes-classes-ctHuman.msr.	197
C.34	Messir Spec. file primarytypes-classes-ctState.msr.	198
C.35	Messir Spec. file primarytypes-classes.msr.	198
C.36	Messir Spec. file primarytypes-datatypes-dtAlertID.msr.	200
C.37	Messir Spec. file primarytypes-datatypes-dtComment.msr.	201
C.38	Messir Spec. file primarytypes-datatypes-dtCoordinatorID.msr.	201
C.39	Messir Spec. file primarytypes-datatypes-dtCrisisID.msr.	202
C.40	Messir Spec. file primarytypes-datatypes-dtGPSLocation.msr.	202
C.41	Messir Spec. file primarytypes-datatypes-dtLogin.msr.	204
C.42	Messir Spec. file primarytypes-datatypes-dtPassword.msr.	204
C.43	Messir Spec. file primarytypes-datatypes-dtPhoneNumber.msr.	204
C.44	Messir Spec. file primarytypes-datatypes-etAlertStatus.msr.	205
C.45	Messir Spec. file primarytypes-datatypes-etCrisisStatus.msr.	205
C.46	Messir Spec. file primarytypes-datatypes-etCrisisType.msr.	206
C.47	Messir Spec. file primarytypes-datatypes-etHumanKind.msr.	206
C.48	Messir Spec. file primarytypes-datatypes.msr.	207
C.49	Messir Spec. file secondarytypes-associations.msr.	208
C.50	Messir Spec. file secondarytypes-classes.msr.	208
C.51	Messir Spec. file secondarytypes-datatypes.msr.	209
C.52	Messir Spec. file subfunctions-usecases.msr.	209
C.53	Messir Spec. file tc-testcase01.msr.	212
C.54	Messir Spec. file tci-testcase01-instance01.msr.	221
C.55	Messir Spec. file usecase-suDeployAndRun.msr.	230
C.56	Messir Spec. file usecase-suGlobalCrisisHandling.msr.	235
C.57	Messir Spec. file usecase-ugAdministrateTheSystem.msr.	235
C.58	Messir Spec. file usecase-ugAverageTypeofCrisis.msr.	236
C.59	Messir Spec. file usecase-ugCrisisInTime.msr.	237
C.60	Messir Spec. file usecase-ugLogin.msr.	237
C.61	Messir Spec. file usecase-ugManageCrisis.msr.	238
C.62	Messir Spec. file usecase-ugMonitor.msr.	239
C.63	Messir Spec. file usecase-ugSecurelyUseSystem.msr.	239
C.64	Messir Spec. file usecase-ugUserActivity.msr.	239
C.65	Messir Spec. file usecase-ugVictimSendFamilyNotification.msr.	240
C.66	Messir Spec. file usecase-ugWitnessSendFamilyNotification.msr.	241
C.67	Messir Spec. file usecaseinstance-uciugLogin.msr.	242
C.68	Messir Spec. file usecaseinstance-ugAverageTypeofCrisis-uciugStatisticAvergeTypeofCrisis.msr.	243
C.69	Messir Spec. file usecaseinstance-ugCrisisInTime-uciugStatisticCrisisInTime.msr.	244
C.70	Messir Spec. file usecaseinstance-ugSecurelyUseSystem-uciugSecurelyUseSystem.msr.	244
C.71	Messir Spec. file usecaseinstance-ugUserActivity-uciugUserActivity.msr.	245
C.72	Messir Spec. file usecaseinstance-ugVictimSendFamilyNotification-uciugVictimSendFamilyNotification.msr.	246
C.73	Messir Spec. file usecaseinstance-ugWitnessSendFamilyNotification-uciugWitnessSendFamilyNotification.msr.	247
D.1	Prolog file outactActivator-oeSetClock.pl.	249
D.2	Prolog file outactActivator-oeSollicitateCrisisHandling.pl.	250
D.3	Prolog file outactAdministrator-oeAddCoordinator.pl.	252
D.4	Prolog file outactAdministrator-oeDeleteCoordinator.pl.	253
D.5	Prolog file outactAuthenticated-oeLogin.pl.	254
D.6	Prolog file outactAuthenticated-oeLogout.pl.	256

D.7 Prolog file outactComCompany-oeAlert.pl	257
D.8 Prolog file outactCoordinator-oeCloseCrisis.pl	261
D.9 Prolog file outactCoordinator-oeGetAlertsSet.pl	262
D.10 Prolog file outactCoordinator-oeGetCrisisSet.pl	263
D.11 Prolog file outactCoordinator-oeInvalidateAlert.pl	264
D.12 Prolog file outactCoordinator-oeReportOnCrisis.pl	266
D.13 Prolog file outactCoordinator-oeSetCrisisHandler.pl	267
D.14 Prolog file outactCoordinator-oeSetCrisisStatus.pl	269
D.15 Prolog file outactCoordinator-oeSetCrisisType.pl	271
D.16 Prolog file outactCoordinator-oeValidateAlert.pl	272
D.17 Prolog file outactMsrCreator-oeCreateSystemAndEnvironment.pl	274
D.18 Prolog file PrimaryTypesClasses-ctAdministrator-init.pl	276
D.19 Prolog file PrimaryTypesClasses-ctAlert-init.pl	276
D.20 Prolog file PrimaryTypesClasses-ctAlert-isSentToCoordinator.pl	277
D.21 Prolog file PrimaryTypesClasses-ctAuthenticated-init.pl	277
D.22 Prolog file PrimaryTypesClasses-ctCoordinator-init.pl	278
D.23 Prolog file PrimaryTypesClasses-ctCrisis-handlingDelayPassed.pl	278
D.24 Prolog file PrimaryTypesClasses-ctCrisis-init.pl	279
D.25 Prolog file PrimaryTypesClasses-ctCrisis-isAllocatedIfPossible.pl	279
D.26 Prolog file PrimaryTypesClasses-ctCrisis-isSentToCoordinator.pl	280
D.27 Prolog file PrimaryTypesClasses-ctCrisis-maxHandlingDelayPassed.pl	281
D.28 Prolog file PrimaryTypesClasses-ctHuman-init.pl	282
D.29 Prolog file PrimaryTypesClasses-ctHuman-isAcknowledged.pl	282
D.30 Prolog file PrimaryTypesClasses-ctState-init.pl	282
D.31 Prolog file PrimaryTypesDatatypes-dtAlertID-is.pl	283
D.32 Prolog file PrimaryTypesDatatypes-dtComment-is.pl	284
D.33 Prolog file PrimaryTypesDatatypes-dtCoordinatorID-is.pl	284
D.34 Prolog file PrimaryTypesDatatypes-dtCrisisID-is.pl	285
D.35 Prolog file PrimaryTypesDatatypes-dtGPSLocation-is.pl	285
D.36 Prolog file PrimaryTypesDatatypes-dtGPSLocation-isNearTo.pl	286
D.37 Prolog file PrimaryTypesDatatypes-dtLatitude-is.pl	287
D.38 Prolog file PrimaryTypesDatatypes-dtLogin-is.pl	287
D.39 Prolog file PrimaryTypesDatatypes-dtLongitude-is.pl	288
D.40 Prolog file PrimaryTypesDatatypes-dtPassword-is.pl	288
D.41 Prolog file PrimaryTypesDatatypes-dtPhoneNumber-is.pl	289
D.42 Prolog file PrimaryTypesDatatypes-etAlertStatus-is.pl	289
D.43 Prolog file PrimaryTypesDatatypes-etCrisisStatus-is.pl	290
D.44 Prolog file PrimaryTypesDatatypes-etCrisisType-is.pl	290
D.45 Prolog file PrimaryTypesDatatypes-etHumanKind-is.pl	291
D.46 Prolog file SecondaryTypesDatatypes-dtSMS-is.pl	291

Chapter 1

Introduction

1.1 Overview

iCrash is a simple system dedicated to any person who wants to inform of a car crash crisis situation in order to allow for crisis handling. At anytime and anywhere, anyone can be the witness or victim of a car crash and might be in a situation allowing for alerting this crisis. The *iCrash* system has for objectives to support crisis declaration and secure administration and crisis handling by the *iCrash* professional users.

1.2 Purpose and recipients of the document

This document is an analysis document complying with the **Messip** methodology [?]. Its intent is to provide an example of a precise specification of the functional properties of the *iCrash* system.

The recipients of this document are:

- the *iCrash* system's buyer company (ABC): this document is used as a contractual document jointly with any other document considered as useful (as requirement elicitation document, ...) in order to have a higher degree of precision in requirement description. It is also used as a basis document for the *iCrash* system validation using specification based testing.
- the *iCrash* system development company (ADC) is expected to use this document as the basis for development (mainly design, implementation, maintenance). It is also used for verification and validation using test plans defined using the analysis models described in this document and according to the **Messip** methodology.

1.3 Application Domain

The *iCrash* system belongs to the Crisis Management Systems Domain. It is a system dedicated to crisis professional and non professional end users. It has to be considered as an autonomous and external service for the society. It is not an institutional system certified and guaranteed by any governmental entity and thus, must be used with caution.

1.4 Definitions, acronyms and abbreviations

N.A.

1.5 Document structure

The document structure is designed to be coherent with the **Messip** methodology [?]. Section 2 provides a general description of the system purpose, its users, its environment and some general non functional requirements. A more detailed description of the non functional requirements, if any, are provided in section ?. The **system operation** triggered by events sent by the external **actors** belonging to the environment are described in Section 3. The *iCrash* concepts used to represent the any persistent or transient information is given in Section 4. The precise specification of the system operations in term of system's state changes, events sent together with the constraints on the allowed sequences of system operations are described in Section 5.

Chapter 2

General Description

In the context of the **Messip** method, the information provided in this section is intended to present the system for which the **Messip** analysis is provided. The content of this section is made accordingly to the requirements elicitation document that might have been done during the project but also adapted coherently in order to be an abstract introduction to the **Messip** analysis.

2.1 Domain Stakeholders

All stakeholders of the system are detailed in this section. After a brief description of a stakeholder, its objectives are first stated. Thereafter, the responsibilities of the stakeholder are detailed which help to achieve the stakeholder objectives to a certain degree. While the objectives characterize the general problems addressed by the *iCrash* system, the responsibilities describe concrete actions that are expected from a stakeholder. Some of these responsibilities can be traced looking at the use case described in Section B.1, and hence must be supported by the *iCrash* system. All stakeholders listed in this section have an interest in the system or are affected by the system in some way, but only a subset of the stakeholders are directly involved in the use cases described. Let us remind that use case diagrams or descriptions are not **Messip** analysis phase mandatory outputs. They are proposed as informal means to help understanding the semantics of the system specification made of the mandatory analysis models, which provide a complete executable specification.

2.1.1 Communication Company

A Communication Company is a company that has the capacity to ensure communication of information between its customers and the *iCrash* system. The objectives of a Communication Company are:

- to be able to deliver any SMS sent by any human to the *iCrash* 's phone number.
- to be able to transmit SMS messages from the ABC company that owns the *iCrash* system to any human having an SMS compatible device accessible using a phone number.

In order to achieve these objectives, the responsibilities of a Communication Company are:

- ensure confidentiality and integrity of the information sent by a human to the *iCrash* system or from the system to a human.
- to be always available and reliable.

2.1.2 Humans

A human is any person who considers himself related to a car crash either as a witness, a victim or an anonymous person. The objectives of a human are:

- inform the *iCrash* system about the crisis situation he detected.
- be sure that the ABC company has been informed about the situation.
- to be informed about the situation of the crisis he is related to as a victim or witness.

In order to achieve these objectives, the responsibilities of a human are:

- to provide as much details as possible concerning the crisis to the ABC company.
- to declare a crisis only if the crisis is real.
- to have access to the SMS compatible communication device he used to communicate with the *iCrash* system.

2.1.3 Coordinators

A coordinator is an employee of the ABC company being responsible of handling one or several crises. The objectives of a coordinator are:

- to securely monitor the existing alerts and crisis.
- to securely manage alerts and crisis until their termination.

In order to achieve these objectives, the responsibilities of a coordinator are:

- to be capable to determine how an alert received should be considered.
- to be available to react to requests to handle alerts and crisis.
- to be autonomous in handling crisis and to report on its handling.
- to be able to decide when a crisis or an alert can be closed.
- to know its system identification information for secure usage of the system.

2.1.4 Administrator

An administrator is an employee of the ABC company being responsible of administrating the *iCrash* system. The objectives of an administrator are:

- to add or delete coordinator actors from the system and its environment.

In order to achieve these objectives, the responsibilities of a coordinator are:

- know the company employees that can be coordinators and that have access to the system.
- to know its system identification information for secure usage of the system.
- to know the security policy of the ABC company.
- to communicate the coordinators their identification information for secure system usage.

2.1.5 Creator

Any system has a `Creator` stakeholder which is a technician who is installing the *iCrash* system on the targeted deployment infrastructure.

The objectives of a `Creator` are:

- to install the *iCrash* system
- to define the values for the initial system's state
- to define the values for the initial system's environment
- to ensure the integration of the *iCrash* system with its initial environment

In order to achieve these objectives, the responsibilities of a `Creator` are:

- provide the necessary data to the *iCrash* system for its initialization.

2.1.6 Activator

An `activator` is a logical representation of the active part the *iCrash* system. It represents an implicit stakeholder belonging to the system's environment that interacts with the *iCrash* system autonomously without the need of a external entity. It is usually used for representing time triggered functionalities.

The objectives of a `activator` are:

- to communicate the current time to the system
- to notify the administrator that some crisis are still pending for a too long time.

In order to achieve these objectives, the responsibilities of a `activator` are:

- to know the current universal time
- to send the messages to the system according to the time constraints specifically defined for it.

2.2 System's Actors

The objective of this section is not to provide the full requirement elicitation document in this section but to reuse a part of this document to provide a informal introduction to the **Messir** specification of the system under development. The use case model is made of a use case diagrams modelling abstractly and informally the actors and their use cases together with a set of use cases descriptions. In addition, those diagrams and description tables are adapted to the **Messir** specification since actor and messages names together with parameters are partly adapted to be consistent with the specification identifiers (see [?] for more details).

Among all the stakeholders presented in the previous section, we can determine five types of direct actors¹:

- `actComCompany`: for the Communication Company stakeholder.
- `actAdministrator`: for the Administrator stakeholder.
- `actCoordinator`: for the Coordinators stakeholders.
- `actActivator`: for the Activator stakeholder.
- `actMsrCreator`: for the Creator stakeholder.

In addition to those system actors, we can add five other types of actors related to the system's ones. Those five actors are grouped into two categories:

- *Indirect actors*
 - *Witness*: for any human that is a witness of a car crash
 - *Victim*: for any human that is a victim of a car crash
 - *Anonymous*: for any human that want to inform about a car crash while staying anonymous.
- *Abstract actors*
 - `actHuman`: represent abstractly any kind of human being actor wanting to communicate with the ABC system in the context of a car crash.
 - `actAuthenticated`: for the logical Activator stakeholder.

2.3 Use Cases Model

This section contains the use cases elicited during the requirements elicitation phase. The use cases are textually described as suggested by the **Messir** method and inspired by the standard Cokburn template [?].

2.3.1 Use Cases

2.3.1.1 summary-suDeployAndRun

The goal is to install the iCrash system on its infrastructure and to exploit its capacities related to the secure administration and efficient handling of car crash situations depending on alerts received.

¹The naming conventions in **Messir** propose to start each type name by lowercase letters indicating the meta model type used (i.e. act for actors, ct for class type,). In addition to ease the reading it makes the translational semantics into Prolog code more straightforward.

USE-CASE DESCRIPTION	
<i>Name</i>	suDeployAndRun
<i>Scope</i>	system
<i>Level</i>	summary
Primary actor(s)	
1	actAdministrator [active]
Secondary actor(s)	
1	actMsrCreator [active]
2	actCoordinator [active, multiple]
3	actActivator [proactive]
4	actComCompany [active]
Goal(s) description	
The goal is to install the iCrash system on its infrastructure and to exploit its capacities related to the secure administration and efficient handling of car crash situations depending on alerts received.	
Reuse	
1	<u>oeCreateSystemAndEnvironment [1..1]</u>
2	<u>ugAdministrateTheSystem [1..*]</u>
3	<u>suGlobalCrisisHandling [1..*]</u>
4	<u>oeSetClock [1..*]</u>
5	<u>oeSollicitateCrisisHandling [0..*]</u>
6	<u>oeAlert [1..*]</u>
Protocol condition(s)	
1	the iCrash system has never been deployed and used
Pre-condition(s)	
1	none
Main post-condition(s)	
1	the iCrash system has been created and has handled the crisis situations for which it received alerts through the communication company.
Main Steps	
a	the actor actMsrCreator executes the <u>oeCreateSystemAndEnvironment</u> use case
b	the actor actAdministrator executes the <u>ugAdministrateTheSystem</u> use case
c	the actor actComCompany executes the <u>oeAlert</u> use case
d	the actor actActivator executes the <u>oeSetClock</u> use case
e	the actor actActivator executes the <u>oeSollicitateCrisisHandling</u> use case
f	the actor actCoordinator executes the <u>suGlobalCrisisHandling</u> use case
Steps Ordering Constraints	
1	step (a) must be always the first step.
2	step (f) can be executed by different actCoordinator actors.
3	if (e) then previously (d).

Figure 2.1 shows the use case diagram for the suDeployAndRun summary use case

2.3.1.2 summary-suGlobalCrisisHandling

the actCoordinator's goal is to monitor the alerts received and the corresponding crisis in order to act as necessary to handle the crisis.




Figure 2.1: suDeployAndRun summary use case

USE-CASE DESCRIPTION	
<i>Name</i>	suGlobalCrisisHandling
<i>Scope</i>	system
<i>Level</i>	summary
Primary actor(s)	
1	actCoordinator [active]
Goal(s) description	
the actCoordinator's goal is to monitor the alerts received and the corresponding crisis in order to act as necessary to handle the crisis.	
Reuse	
1	ugSecurelyUseSystem [1..*]
2	ugMonitor [1..*]
3	ugManageCrisis [1..*]
Protocol condition(s)	
1	the iCrash system has been deployed
2	the coordinator actor involved in the use case has been declared by the actor actAdministrator
Pre-condition(s)	
1	none
Main post-condition(s)	
1	modifications have been made by the coordinator on existing alerts or crisis OR the coordinator requested an updated status on existing alerts or crisis.
Main Steps	
a	the actor actCoordinator executes the ugSecurelyUseSystem use case
b	the actor actCoordinator executes the ugMonitor use case
c	the actor actCoordinator executes the ugManageCrisis use case
Steps Ordering Constraints	
1	steps (a) (b) and (c) executions are interleaved (steps (b) and (c) have their protocol constrained by steps of (a)).
2	steps (a) (b) and (c) can be executed multiple times.

Figure 2.2 shows the use case diagram for the suGlobalCrisisHandling user goal use case

2.3.1.3 usergoal-ugAdministateTheSystem

the actAdministrator's goal is to follow an identification procedure to be allowed to add or delete the necessary crisis coordinators that will be granted the responsibility to handle alerts and crisis.

USE-CASE DESCRIPTION	
<i>Name</i>	ugAdministateTheSystem
<i>Scope</i>	system
<i>Level</i>	usergoal
Primary actor(s)	
1	actAdministrator [active]
Goal(s) description	
the actAdministrator's goal is to follow an identification procedure to be allowed to add or delete the necessary crisis coordinators that will be granted the responsibility to handle alerts and crisis.	

continues in next page ...

... Use-Case Description table continuation

Reuse
1 <u>ugSecurelyUseSystem [1..*]</u>
2 <u>oeAddCoordinator [1..*]</u>
3 <u>oeDeleteCoordinator [0..*]</u>
Protocol condition(s)
1 the iCrash system has been deployed
Pre-condition(s)
1 none
Main post-condition(s)
1 modifications have been made to the system and its environment concerning existing or new coordinators.
Main Steps
a the actor <code>actAdministrator</code> executes the <u>ugSecurelyUseSystem</u> use case
b the actor <code>actAdministrator</code> executes the <u>oeAddCoordinator</u> use case
c the actor <code>actAdministrator</code> executes the <u>oeDeleteCoordinator</u> use case
Steps Ordering Constraints
1 steps (a) (b) and (c) executions are interleaved (steps (b) and (c) have their protocol constrained by steps of (a)).
2 steps (a) (b) and (c) can be executed multiple times.

Figure 2.3 shows the use case diagram for the ugAdministrateTheSystem user goal use case

2.3.1.4 usergoal-ugAverageTypeofCrisis

An actor has been login as a Administrator to use the statistic function. So he can see the average time for the different types of a crises

USE-CASE DESCRIPTION
Name ugAverageTypeofCrisis
Scope system
Level usergoal
Primary actor(s)
1 <code>actAdministrator</code> [active]
2 <code>actDatabase</code> [proactive]
Secondary actor(s)
1 <code>actSystem</code> [active]
Goal(s) description
An actor has been login as a Administrator to use the statistic function. So he can see the average time for the different types of a crises
Reuse
1 <u>oeStatistic [1..*]</u>
2 <u>ugSercurelyUserSystem [0..*]</u>
3 <u>oeTimeOfTypeOfCrisis [0..*]</u>
4 <u>ugAdministrateTheSystem [1..*]</u>
Protocol condition(s)

continues in next page ...

... Use-Case Description table continuation

1	The actor has been login as a administrator and he has to click on the button static.
2	The actor must be able to access the system (connected to the internet)
Pre-condition(s)	
1	The actor is not login as a administrator, so he can click the button statistic.
Main post-condition(s)	
1	if the login was successful, the actor is now identified and thus able to access the AdministateTheSystem
2	The actor can click the button statistic and so he see the statistic
Main Steps	
a	the actor actSystem executes the <u>ugSercurelyUserSystem</u> use case
b	the actor actSystem executes the <u>oeStatistic</u> use case
c	the actor actAdministrator executes the <u>oeTimeOfTypeOfCrisis</u> use case
d	the actor actAdministrator executes the <u>ugAdministateTheSystem</u> use case
e	the actor actDatabase executes the <u>oeTimeOfTypeOfCrisis</u> use case
Steps Ordering Constraints	
1	at least a
2	if b then previously a
3	if c then previously b
4	if d then previously c
Additional Information	
none	

Figure 2.4 The actor administrator will open the statics the average time for each type of crises, there the administrator can find out how long the different types of crisis needs. The tree types of a crises are small, medium and huge . Also the abstract user System give the information

2.3.1.5 usergoal-ugCrisisInTime

An actor has been login as a Administrator to use the statistic function. So he can see the number of crises compared with the time

USE-CASE DESCRIPTION	
Name	ugCrisisInTime
Scope	system
Level	usergoal
Primary actor(s)	
1	actAdministrator [active]
2	actDatabase [proactive]
Secondary actor(s)	
1	actSystem [active]
Goal(s) description	
An actor has been login as a Administrator to use the statistic function. So he can see the number of crises compared with the time	
Reuse	
1	<u>oeStatistic</u> [1..*]
2	<u>ugSercurelyUserSystem</u> [0..*]

continues in next page ...

... Use-Case Description table continuation

3	<u>oeNumberOfCrisis [0..*]</u>
4	<u>ugAdministateTheSystem [1..*]</u>
Protocol condition(s)	
1	The actor has been login as a administrator and he has to click on the button static.
2	The actor must be able to access the system (connected to the internet)
Pre-condition(s)	
1	The actor is not login as a administrator, so he can click the button statistic.
Main post-condition(s)	
1	if the login was successful, the actor is now identified and thus able to access the AdministateTheSystem
2	The actor can click the button statistic and so he see the statistic
Main Steps	
a	the actor actSystem executes the <u>ugSercurelyUserSystem</u> use case
b	the actor actSystem executes the <u>oeStatistic</u> use case
c	the actor actAdministrator executes the <u>oeNumberOfCrisis</u> use case
d	the actor actAdministrator executes the <u>ugAdministateTheSystem</u> use case
e	the actor actDatabase executes the <u>oeNumberOfCrisis</u> use case
Steps Ordering Constraints	
1	at least a
2	if b then previously a
3	if c then previously b
4	if d then previously c
Additional Information	
none	

Figure 2.5 The actor administrator will open the statics The number of crisis at the time, there he can find out how many crisis are send at the different time. Also the abstract user System give the information

2.3.1.6 usergoal-ugLogin

An actor wants to identify himself in order to gain access to the systems functionalities

USE-CASE DESCRIPTION	
Name	ugLogin
Scope	system
Level	usergoal
Primary actor(s)	
1	actAuthenticated[active]
Secondary actor(s)	
1	actCaptchaService[active]
2	actMailingService[active]
Goal(s) description	
An actor wants to identify himself in order to gain access to the systems functionalities	
Reuse	

continues in next page ...

... Use-Case Description table continuation

1	<u>oeLogin [1..1]</u>
2	<u>oeSendCaptcha [1..1]</u>
3	<u>oeSubmitCaptcha [1..1]</u>
4	<u>oeCaptchaInvalid [1..1]</u>
5	<u>oeCaptchaValid [1..1]</u>
<i>Protocol condition(s)</i>	
1	the system has to be started
2	the actor (client) must be able to access the system (connected to the internet)
<i>Pre-condition(s)</i>	
1	the actor is not identified (logged in) and thus not able to access the systems functionalities
<i>Main post-condition(s)</i>	
1	if the login was successful, the actor is now identified and thus able to access the systems functionalities
2	if an attempt to log in failed, the authentication is refused and the actor has to try again
3	if the actor failed three times to log in, each further attempt to log in is accompanied by a captcha verification test
4	if the actor failed three times to log in without and five times with captcha verification, the requested user name will be blocked from further log in attempts
<i>Main Steps</i>	
a	the actor actAuthenticated executes the <u>oeLogin</u> use case
b	the actor actCaptchaService executes the <u>oeSendCaptcha</u> use case
c	the actor actAuthenticated executes the <u>oeSubmitCaptcha</u> use case
d	the actor actCaptchaService executes the <u>oeCaptchaInvalid</u> use case
e	the actor actCaptchaService executes the <u>oeCaptchaValid</u> use case
<i>Steps Ordering Constraints</i>	
1	at least a
2	if b then previously a
3	if c then previously b
4	if d then previously c
5	if e then previously c
<i>Additional Information</i>	
none	

Figure 2.6 An actor tries to log in to the system using his credentials

2.3.1.7 usergoal-ugManageCrisis

The goal is to do an action that makes the handling of a crisis or an alert progress.

USE-CASE DESCRIPTION	
Name	ugManageCrisis
Scope	system
Level	usergoal
<i>Primary actor(s)</i>	
1	actCoordinator[active]
<i>Goal(s) description</i>	

continues in next page ...

... Use-Case Description table continuation

The goal is to do an action that makes the handling of a crisis or an alert progress.

Reuse	
1	<u>oeValidateAlert [0..*]</u>
2	<u>oeSetCrisisStatus [0..*]</u>
3	<u>oeSetCrisisHandler [0..*]</u>
4	<u>oeReportOnCrisis [0..*]</u>
5	<u>oeCloseCrisis [0..*]</u>
6	<u>oeInvalidateAlert [0..*]</u>
Protocol condition(s)	
1	the iCrash system has been deployed
Pre-condition(s)	
1	none
Main post-condition(s)	
1	there exist one alert or one crisis whose related information has been changed.
Main Steps	
a	the actor actCoordinator executes the <u>oeValidateAlert</u> use case
b	the actor actCoordinator executes the <u>oeSetCrisisStatus</u> use case
c	the actor actCoordinator executes the <u>oeSetCrisisHandler</u> use case
d	the actor actCoordinator executes the <u>oeReportOnCrisis</u> use case
e	the actor actCoordinator executes the <u>oeCloseCrisis</u> use case
f	the actor actCoordinator executes the <u>oeInvalidateAlert</u> use case
Steps Ordering Constraints	
1	managing a crisis is doing one of the indicated use cases.

Figure 2.7 shows the use case diagram for the ugManageCrisis user goal use case

2.3.1.8 usergoal-ugMonitor

the actCoordinator's goal is to get the detailed list of existing crisis or alerts to decide on next actions to undertake.

USE-CASE DESCRIPTION	
Name	ugMonitor
Scope	system
Level	usergoal
Primary actor(s)	
1	actCoordinator[active]
Goal(s) description	
the actCoordinator's goal is to get the detailed list of existing crisis or alerts to decide on next actions to undertake.	
Reuse	
1	<u>oeGetCrisisSet [0..*]</u>
2	<u>oeGetAlertsSet [0..*]</u>
Protocol condition(s)	
1	the iCrash system has been deployed
Pre-condition(s)	

continues in next page ...

... Use-Case Description table continuation

1	none
<i>Main post-condition(s)</i>	
1	none
<i>Main Steps</i>	
a	the actor <code>actCoordinator</code> executes the <code>oeGetAlertsSet</code> use case
b	the actor <code>actCoordinator</code> executes the <code>oeGetCrisisSet</code> use case

Figure 2.8 shows the use case diagram for the ugMonitor user goal use case

2.3.1.9 usergoal-ugSecurelyUseSystem

the actAdministrator's goal is to follow an identification procedure to be allowed to add or delete the necessary crisis coordinators that will be granted the responsibility to handle alerts and crisis.

USE-CASE DESCRIPTION	
<i>Name</i>	ugSecurelyUseSystem
<i>Scope</i>	system
<i>Level</i>	usergoal
<i>Primary actor(s)</i>	
1	<code>actAuthenticated</code> [active]
<i>Goal(s) description</i>	
the actAdministrator's goal is to follow an identification procedure to be allowed to add or delete the necessary crisis coordinators that will be granted the responsibility to handle alerts and crisis.	
<i>Reuse</i>	
1	<code>oeLogin</code> [1..1]
2	<code>oeLogout</code> [1..1]
<i>Protocol condition(s)</i>	
1	the iCrash system has been deployed
<i>Pre-condition(s)</i>	
1	none
<i>Main post-condition(s)</i>	
1	the <code>actAuthenticated</code> is known by the system not to be logged.
<i>Main Steps</i>	
a	the actor <code>actAuthenticated</code> executes the <code>oeLogin</code> use case
b	the actor <code>actAuthenticated</code> executes the <code>oeLogout</code> use case
<i>Steps Ordering Constraints</i>	
1	step (a) must always precede step (b).

Figure 2.9 shows the use case diagram for the ugSecurelyUseSystem user goal use case

2.3.1.10 usergoal-ugUserActivity

An actor has been login as a Administrator to use the statistic function. So he can see the number of user compared with the time




Figure 2.2: suGlobalCrisisHandling user goal use case




Figure 2.3: ugAdministateTheSystem user goal use case




Figure 2.4: The average time for each type of crises




Figure 2.5: The number of crisis at the time




Figure 2.6: User goal: log in to the system

USE-CASE DESCRIPTION	
Name	ugUserActivity
Scope	system
Level	usergoal
<i>Primary actor(s)</i>	
1	actAdministrator[active]
2	actDatabase[proactive]
<i>Secondary actor(s)</i>	
1	actSystem[active]
<i>Goal(s) description</i>	
An actor has been login as a Administrator to use the statistic function. So he can see the number of user compared with the time	
<i>Reuse</i>	
1	<u>oeStatistic</u> [1...*]
2	<u>ugSercurelyUserSystem</u> [0...*]
3	<u>oeUserActivityStatistic</u> [0...*]
4	<u>ugAdministateTheSystem</u> [1...*]
<i>Protocol condition(s)</i>	
1	The actor has been login as a administrator and he has to click on the button static.
2	The actor must be able to access the system (connected to the internet)
<i>Pre-condition(s)</i>	
1	The actor is not login as a administrator, so he can click the button statistic.
<i>Main post-condition(s)</i>	
1	if the login was successful, the actor is now identified and thus able to access the AdministateTheSystem
2	The actor can click the button statistic and so he see the statistic

continues in next page ...

... Use-Case Description table continuation

Main Steps	
a	the actor actSystem executes the <u>ugSecurelyUserSystem</u> use case
b	the actor actSystem executes the <u>oeStatistic</u> use case
c	the actor actAdministrator executes the <u>oeUserActivityStatistic</u> use case
d	the actor actAdministrator executes the <u>ugAdministrateTheSystem</u> use case
e	the actor actDatabase executes the <u>oeUserActivityStatistic</u> use case
Steps Ordering Constraints	
1	at least a
2	if b then previously a
3	if c then previously b
4	if d then previously c
Additional Information	
none	

Figure 2.10 The actor administrator will open the statics the activity of the users, there he can find out how many users are active at any time. Also the abstract user System give the information

2.3.1.11 usergoal-ugVictimSendFamilyNotification

USE-CASE DESCRIPTION	
Name	ugVictimSendFamilyNotification
Scope	system
Level	usergoal
Primary actor(s)	
1	actSystem[active]
Secondary actor(s)	
1	actAuthenticated[active]
2	actCoordinator[proactive]
Goal(s) description	
Reuse	
1	<u>oeCreateAlert</u> [1..*]
2	<u>oeCreateCrisis</u> [1..1]
3	<u>oeUpdateCrisis</u> [0..*]
Protocol condition(s)	
1	
Pre-condition(s)	
1	
Main post-condition(s)	
1	
Main Steps	
a	the actor actAuthenticated executes the <u>oeCreateAlert</u> use case
b	the actor actCoordinator executes the <u>oeCreateAlert</u> use case
c	the actor actCoordinator executes the <u>oeCreateCrisis</u> use case
d	the actor actSystem executes the <u>oeChooseInformation</u> use case

continues in next page ...

... Use-Case Description table continuation

e	the actor actCoordinator executes the <u>oeUpdateCrisis</u> use case
Steps Ordering Constraints	
1	if c then previously a or b
2	if d then previously a or b
3	if e then previously a or b
Additional Information	
none	

Figure 2.11

2.3.1.12 usergoal-ugWitnessSendFamilyNotification

USE-CASE DESCRIPTION	
Name	ugWitnessSendFamilyNotification
Scope	system
Level	usergoal
Primary actor(s)	
1	actSystem[active]
Secondary actor(s)	
1	actAuthenticated[active]
2	actCoordinator[proactive]
Goal(s) description	
Reuse	
1	<u>oeCreateAlert</u> [1...*]
2	<u>oeCreateCrisis</u> [1..1]
3	<u>oeUpdateCrisis</u> [0...*]
Protocol condition(s)	
1	
Pre-condition(s)	
1	
Main post-condition(s)	
1	
Main Steps	
a	the actor actAuthenticated executes the <u>oeCreateAlert</u> use case
b	the actor actCoordinator executes the <u>oeCreateAlert</u> use case
c	the actor actCoordinator executes the <u>oeCreateCrisis</u> use case
d	the actor actSystem executes the <u>oeChooseInformation</u> use case
e	the actor actCoordinator executes the <u>oeUpdateCrisis</u> use case
Steps Ordering Constraints	
1	if c then previously a or b
2	if d then previously a or b
3	if e then previously a or b
Additional Information	
none	




Figure 2.7: ugManageCrisis user goal use case




Figure 2.8: ugMonitor user goal use case




Figure 2.9: ugSecurelyUseSystem user goal use case




Figure 2.10: The activity of the users




Figure 2.11:

Figure 2.12 The authenticated Witness creates an alert in which he can identify the victim by name and surname. The system sends the notification. The coordinator creates a crisis for the alert and a new notification is sent with every update of the crisis.




Figure 2.12: Witness family notification

2.3.1.13 subfunction-oeCaptchaInvalid

Notifies the system that the supplied captcha answer is invalid

USE-CASE DESCRIPTION	
Name	oeCaptchaInvalid
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actCaptchaService[active]
<i>Secondary actor(s)</i>	
1	actMailingService[]
2	actAuthenticated[]
<i>Goal(s) description</i>	
Notifies the system that the supplied captcha answer is invalid	
<i>Protocol condition(s)</i>	
1	The system must have requested the generation of a captcha test from the generation actor first and should have received a captcha test
2	The system must have submitted or forwarded an answer to the captcha test to the validation actor
<i>Pre-condition(s)</i>	
1	The submitted answer to the captcha test is incorrect
<i>Main post-condition(s)</i>	
1	The system is notified about the failure state of the submitted answer to the captcha test
2	If the requested user name failed five times in a row to log in, the user name will be blocked and a mail with instructions to unblock the user name will be send to the affected user
<i>Additional Information</i>	
none	

2.3.1.14 subfunction-oeCaptchaValid

Notifies the system that the supplied captcha answer is valid

USE-CASE DESCRIPTION	
<i>Name</i>	oeCaptchaValid
<i>Scope</i>	system
<i>Level</i>	subfunction
<i>Primary actor(s)</i>	
1	actCaptchaService[active]
<i>Secondary actor(s)</i>	
1	actAuthenticated[]
<i>Goal(s) description</i>	
Notifies the system that the supplied captcha answer is valid	
<i>Protocol condition(s)</i>	
1	The system must have requested the generation of a captcha test from the generation actor first and should have received a captcha test
2	The system must have submitted or forwarded an answer to the captcha test to the validation actor
<i>Pre-condition(s)</i>	
1	The submitted answer to the captcha test is correct
<i>Main post-condition(s)</i>	
1	The system is notified about the success state of the submitted answer to the captcha test
<i>Additional Information</i>	
none	

2.3.1.15 subfunction-oeChooseInformation

USE-CASE DESCRIPTION	
<i>Name</i>	oeChooseInformation
<i>Scope</i>	system
<i>Level</i>	subfunction
<i>Primary actor(s)</i>	
1	actSystem[active]
<i>Secondary actor(s)</i>	
1	actAuthenticated[]
<i>Goal(s) description</i>	
<i>Protocol condition(s)</i>	
1	
<i>Pre-condition(s)</i>	
1	
<i>Main post-condition(s)</i>	
1	
<i>Additional Information</i>	
none	

2.3.1.16 subfunction-oeCreateAlert

USE-CASE DESCRIPTION	
<i>Name</i>	oeCreateAlert
<i>Scope</i>	system
<i>Level</i>	subfunction
<i>Primary actor(s)</i>	
1	actAuthenticated[active]
<i>Secondary actor(s)</i>	
1	actCoordinator[]
<i>Goal(s) description</i>	
<i>Protocol condition(s)</i>	
1	
<i>Pre-condition(s)</i>	
1	
<i>Main post-condition(s)</i>	
1	
<i>Additional Information</i>	
none	

2.3.1.17 subfunction-oeCreateCrisis

USE-CASE DESCRIPTION	
<i>Name</i>	oeCreateCrisis
<i>Scope</i>	system
<i>Level</i>	subfunction
<i>Primary actor(s)</i>	
1	actCoordinator[active]
<i>Goal(s) description</i>	
<i>Protocol condition(s)</i>	
1	
<i>Pre-condition(s)</i>	
1	
<i>Main post-condition(s)</i>	
1	
<i>Additional Information</i>	
none	

2.3.1.18 subfunction-oeNumberOfCrisis

An actor has been login as a Administrator to use the statistic function. So he can see the number of crises compared with the time

USE-CASE DESCRIPTION	
<i>Name</i>	oeNumberOfCrisis
<i>Scope</i>	system
<i>Level</i>	subfunction

continues in next page ...

... Use-Case Description table continuation

Primary actor(s)
1 actAdministrator [active]
Secondary actor(s)
1 actDatabase [passive]
Goal(s) description
An actor has been login as a Administrator to use the statistic function. So he can see the number of crises compared with the time
Protocol condition(s)
1 The actor has been login as a administrator and he has to click on the button static. 2 The actor must be able to access the system (connected to the internet)
Pre-condition(s)
1 The actor is not login as a administrator, so he can click the button statistic.
Main post-condition(s)
1 if the login was successful, the actor is now identified and thus able to access the AdministateTheSystem 2 The actor can click the button statistic and so he see the statistic
Additional Information
none

2.3.1.19 subfunction-oeSendCaptcha

The actor responsible for captcha generation sends a captcha test and its answer to the system

USE-CASE DESCRIPTION
<i>Name</i> oeSendCaptcha
<i>Scope</i> system
<i>Level</i> subfunction
Primary actor(s)
1 actCaptchaService [active]
Secondary actor(s)
1 actAuthenticated []
Goal(s) description
The actor responsible for captcha generation sends a captcha test and its answer to the system
Protocol condition(s)
1 the system has to be started 2 the captcha generator has to be available
Pre-condition(s)
1 the system must have notified the actor first in order that he can generate the captcha
Main post-condition(s)
1 due to the request of the system, the captcha test and its answer has been generated and sent back to the system
Additional Information
none

2.3.1.20 subfunction-oeSendNotification

USE-CASE DESCRIPTION	
Name	oeSendNotification
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actSystem[active]
<i>Goal(s) description</i>	
<i>Protocol condition(s)</i>	
1	
<i>Pre-condition(s)</i>	
1	
<i>Main post-condition(s)</i>	
1	
<i>Additional Information</i>	
none	

2.3.1.21 subfunction-oeSendStatistic

Send the statistic to the system that the system send it to the administrator

USE-CASE DESCRIPTION	
Name	oeSendStatistic
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actSystem[active]
<i>Secondary actor(s)</i>	
1	actAdministrator[passive]
2	actDatabase[passive]
<i>Goal(s) description</i>	
Send the statistic to the system that the system send it to the administrator	
<i>Protocol condition(s)</i>	
1	The actor has been login as a administrator to call the statistic so the subfunction can send the data to the system
<i>Pre-condition(s)</i>	
1	The administrator has call the statistic, so the function will send the information
<i>Main post-condition(s)</i>	
1	if the administrator click to the button statistic so the system will find the information.
2	the Database has send back the information to the system and after to the actor.
<i>Additional Information</i>	
none	

2.3.1.22 subfunction-oeSetCrisisHandler

goal is to declare himself as been the handler of a crisis having the specified id.

USE-CASE DESCRIPTION	
Name	oeSetCrisisHandler
Scope	system
Level	subfunction
<i>Parameters</i>	
AdtCrisisID:	dtCrisisID 1
<i>Primary actor(s)</i>	
1	actCoordinator[active]
<i>Secondary actor(s)</i>	
1	actCoordinator[passive]
2	actComCompany[passive, multiple]
<i>Goal(s) description</i>	
goal is to declare himself as been the handler of a crisis having the specified id.	
<i>Protocol condition(s)</i>	
1	
<i>Pre-condition(s)</i>	
1	
<i>Main post-condition(s)</i>	
1	
<i>Additional Information</i>	
none	

Figure 2.13 shows the use case diagram for the oeSetCrisisHandler subfunction use case




Figure 2.13: oeSetCrisisHandler subfunction use case

2.3.1.23 subfunction-oeSollicitateCrisisHandling

the actActivator's goal is to decrease the number of unhandled crisis.

USE-CASE DESCRIPTION	
Name	oeSollicitateCrisisHandling
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actActivator [proactive]
<i>Secondary actor(s)</i>	
1	actCoordinator [passive, multiple]
2	actAdministrator [passive]
<i>Goal(s) description</i>	the actActivator's goal is to decrease the number of unhandled crisis.
<i>Protocol condition(s)</i>	
1	the iCrash system has been deployed.
2	there exist some crisis still pending and for which no solicitation has been sent to the administrator and the coordinators for more than a predefined maximum delay.
<i>Pre-condition(s)</i>	
1	none
<i>Main post-condition(s)</i>	
1	a simple text message ieMessage('There are alerts not treated since more than the defined delay. Please REACT !') is sent to the system administrator and to all the coordinators of the environment for each crisis that is known to be not handled and for which no solicitation has been sent to the administrator and the coordinators for more than a predefined maximum delay.'
2	the reminder period for the concerned crisis is initialized.

Figure 2.14 shows the use case diagram for the oeSollicitateCrisisHandling subfunction use case




Figure 2.14: oeSollicitateCrisisHandling subfunction use case

2.3.1.24 subfunction-oeStatistic

Is a new button for the administrator so he can look the different statistic

USE-CASE DESCRIPTION	
Name	oeStatistic
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actAdministrator [active]
<i>Secondary actor(s)</i>	
1	actSystem [passive]
<i>Goal(s) description</i>	
Is a new button for the administrator so he can look the different statistic	
<i>Protocol condition(s)</i>	
1	The actor has been login as a administrator and he has to click on the button static.
2	The actor must be able to access the system (connected to the internet)
<i>Pre-condition(s)</i>	
1	The actor is not login as a administrator, so he can click the button statistic.
<i>Main post-condition(s)</i>	
1	if the login was successful, the actor is now identified and thus able to access the AdministateTheSystem
2	The actor can click the button statistic and so he see the statistic
<i>Additional Information</i>	
none	

2.3.1.25 subfunction-oeSubmitCaptcha

The actor submits his answer to a captcha test to the system for validation

USE-CASE DESCRIPTION	
Name	oeSubmitCaptcha
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actAuthenticated [active]
<i>Secondary actor(s)</i>	
1	actCaptchaService []
<i>Goal(s) description</i>	
The actor submits his answer to a captcha test to the system for validation	
<i>Protocol condition(s)</i>	
1	the system has to be started
2	the actor has to be connected but not yet identified to the system
3	the system must have received first the captcha test and its answer from the actor responsible for captcha generation
<i>Pre-condition(s)</i>	
1	the actor receives the captcha test from the system
<i>Main post-condition(s)</i>	

continues in next page ...

... Use-Case Description table continuation

1	the actor submitted an answer to the given captcha test back to the system
Additional Information	
none	

2.3.1.26 subfunction-oeTimeOfTypeOfCrisis

An actor has been login as a Administrator to use the statistic function. So he can see the average time for the different types of a crises

USE-CASE DESCRIPTION	
Name	oeTimeOfTypeOfCrisis
Scope	system
Level	subfunction
Primary actor(s)	
1	actAdministrator [active]
Secondary actor(s)	
1	actDatabase [passive]
2	actSystem [passive]
Goal(s) description	
An actor has been login as a Administrator to use the statistic function. So he can see the average time for the different types of a crises	
Protocol condition(s)	
1	The actor has been login as a administrator and he has to click on the button static.
2	The actor must be able to access the system (connected to the internet)
Pre-condition(s)	
1	The actor is not login as a administrator, so he can click the button statistic.
Main post-condition(s)	
1	if the login was successful, the actor is now identified and thus able to access the AdministateTheSystem
2	The actor can click the button statistic and so he see the statistic
Additional Information	
none	

2.3.1.27 subfunction-oeUpdateCrisis

USE-CASE DESCRIPTION	
Name	oeUpdateCrisis
Scope	system
Level	subfunction
Primary actor(s)	
1	actCoordinator [proactive]
Goal(s) description	
Protocol condition(s)	
1	
Pre-condition(s)	

continues in next page ...

... Use-Case Description table continuation

1
<i>Main post-condition(s)</i>
1
<i>Additional Information</i>
none

2.3.1.28 subfunction-oeUserActivityStatistic

An actor has been login as a Administrator to use the statistic function. So he can see the number of user compared with the time

USE-CASE DESCRIPTION	
Name	oeUserActivityStatistic
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actAdministrator [active]
<i>Secondary actor(s)</i>	
1	actDatabase [passive]
<i>Goal(s) description</i>	
An actor has been login as a Administrator to use the statistic function. So he can see the number of user compared with the time	
<i>Protocol condition(s)</i>	
1	The actor has been login as a administrator and he has to click on the button static.
2	The actor must be able to access the system (connected to the internet)
<i>Pre-condition(s)</i>	
1	The actor is not login as a administrator, so he can click the button statistic.
<i>Main post-condition(s)</i>	
1	if the login was successful, the actor is now identified and thus able to access the AdministateTheSystem
2	The actor can click the button statistic and so he see the statistic
<i>Additional Information</i>	
none	

2.3.1.29 subfunction-ugSercurelyUserSystem

USE-CASE DESCRIPTION	
Name	ugSercurelyUserSystem
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actSystem [active]
<i>Goal(s) description</i>	
<i>Protocol condition(s)</i>	
1	

continues in next page ...

... Use-Case Description table continuation

<i>Pre-condition(s)</i>
1
<i>Main post-condition(s)</i>
1
<i>Additional Information</i>
none

2.3.2 Use Case Instance(s)

2.3.2.1 Use-Case Instance - uciSimpleAndCompletePart01:suDeployAndRun

First part of a use case instance for the summary use case suDeployAndRun illustrating a simple and complete interaction scenario primarily handled by an administrator in a concrete situation.

SUMMARY USE-CASE INSTANCE	
<i>Instantiated Use Case</i>	
suDeployAndRun	
<i>Instance ID</i>	
uciSimpleAndCompletePart01	
<i>Remarks</i>	
a	shows the system initialization and the first administrative tasks by the administrator.
b	The unique and always existing actMsrCreator actor instance (named here theCreator) requests the initialization of the system and its environment (made of one administrator identified here by bill), one activator actor (identified by theClock) and indicating that the number of communication company actor instances for the system's environment is 4 (one of them is identified here by tango)
c	the administrator logs in to initialize a coordinator
d	an alert is received. Time is going on without having the coordinator handling the alert which let's the proactive actor trigger the automatic solicitation of crisis handling.
e	this first part stops before the coordinator logs in the system.

Figure 2.15 shows the sequence diagram representing the first part of a simple and complete use case instance for the summary use case suDeployAndRun.

2.3.2.2 Use-Case Instance - uciSimpleAndCompletePart02:suDeployAndRun

Second part of a simple and complete use case instance for the summary use case suDeployAndRun illustrating a simple and complete interaction scenario primarily handled by an administrator in a concrete situation.

SUMMARY USE-CASE INSTANCE	
<i>Instantiated Use Case</i>	
suDeployAndRun	
<i>Instance ID</i>	
uciSimpleAndCompletePart02	
<i>Remarks</i>	
a	starts when the coordinator logs in the system until the full handling of all the existing crisis.
b	shows an instantiated case of handling of a crisis by a coordinator until its closure after reporting.

Figure 2.16 shows the sequence diagram representing the second part of a simple and complete use case instance for the summary use case suDeployAndRun.




Figure 2.15: uci-suDeployAndRun-uciSimpleAndComplete-Part01




Figure 2.16: uci-suDeployAndRun-uciSimpleAndComplete-Part02 use case instance sequence diagram

2.3.2.3 Use-Case Instance - uciugStatisticAverageTypeofCrisis:ugAverageTypeofCrisis

The Administrator click the button to open the statics so the system has to call the information for the average time of the different types and send it back to the Administrator so he can see it.

USERGOAL USE-CASE INSTANCE	
<i>Instantiated Use Case</i>	ugAverageTypeofCrisis
<i>Instance ID</i>	uciugStatisticAverageTypeofCrisis

Figure 2.17 The Administrator click the button to open the statics so the system has to call the information for the average time of the different types and send it back to the Administrator so he can see it.




Figure 2.17: The average time of the different types

2.3.2.4 Use-Case Instance - uciugStatisticCrisisInTime:ugCrisisInTime

The administrator click the button to open the statics so the system has to call the information for the number of the crises compared with the time and send it back to the Administrator so he can see it.

USERGOAL USE-CASE INSTANCE	
<i>Instantiated Use Case</i>	ugCrisisInTime
<i>Instance ID</i>	uciugStatisticCrisisInTime

Figure 2.18 The administrator click the button to open the statics so the system has to call the information for the number of the crises compared with the time and send it back to the Administrator so he can see it.




Figure 2.18: The number of the crises compared with the time

2.3.2.5 Use-Case Instance - uciugLoginCaptchaFailure:ugLogin

A failed captcha response submission after at least three failed login attempts

USERGOAL USE-CASE INSTANCE
<i>Instantiated Use Case</i>
ugLogin
<i>Instance ID</i>
uciugLoginCaptchaFailure

Figure 2.19 The actor tries to log in with captcha verification and incorrect credentials. The log in process will be aborted.




Figure 2.19: A failed login with captcha verification

Figure 2.20 The actor tries to log in with captcha verification and correct credentials. The log in will be allowed.




Figure 2.20: A successful login with captcha verification

2.3.2.7 Use-Case Instance - uciugLoginCaptchaToleranceExceeded:ugLogin

After three failed login attempts without and five login attempts with captcha verification, the requested login user name will be blocked for further login attempts

USERGOAL USE-CASE INSTANCE
<i>Instantiated Use Case</i> ugLogin
<i>Instance ID</i> uciugLoginCaptchaToleranceExceeded

Figure 2.21 The actor failed to log in three times without and five times with captcha verification. The login availability for the requested user name will be blocked.




Figure 2.21: The tolerance of login attempts is exceeded

2.3.2.8 Use-Case Instance - uciugLoginFailure:ugLogin

A user submitted a wrong combination of user name and password during the login process. The authentication is refused.

USERGOAL USE-CASE INSTANCE	
<i>Instantiated Use Case</i>	ugLogin
<i>Instance ID</i>	uciugLoginFailure

Figure 2.22 A user has submitted an incorrect combination of user name and password during the login process




Figure 2.22: A failed login attempt

2.3.2.9 Use-Case Instance - uciugLoginRejected:ugLogin



Figure 2.23: A rejected login attempt

USERGOAL USE-CASE INSTANCE
<i>Instantiated Use Case</i> ugLogin
<i>Instance ID</i> uciugLoginSuccess

Figure 2.24 A user has submitted a correct combination of user name and password during the login process




Figure 2.24: A successful login attempt

2.3.2.11 Use-Case Instance - uciugSecurelyUseSystem:ugSecurelyUseSystem

USERGOAL USE-CASE INSTANCE
<i>Instantiated Use Case</i> ugSecurelyUseSystem
<i>Instance ID</i> uciugSecurelyUseSystem

Figure 2.25

2.3.2.12 Use-Case Instance - uciugUserActivity:ugUserActivity

The user administration will manage the creation, the modification and the deletion of the user accounts.



Figure 2.25:

Figure 2.26 The administrator click the button to open the statics so the system has to call the information for the number of the user compared with the time and send it back to the Administrator so he can see it.

2.3.2.13 Use-Case Instance - uciugVictimSendFamilyNotification:ugVictimSendFamilyNotification

The authenticated Victim creates an alert in which he can choose to sent a notification to his family with a personal commentary. The system sends the notification. The coordinator creates a crisis for the alert and a new notification is sent with every update of the crisis.

USERGOAL USE-CASE INSTANCE
<i>Instantiated Use Case</i>
ugVictimSendFamilyNotification
<i>Instance ID</i>
uciugVictimSendFamilyNotification

Figure 2.27 The authenticated Victim creates an alert in which he can choose to sent a notification to his family with a personal commentary. The system sends the notification. The coordinator creates a crisis for the alert and a new notification is sent with every update of the crisis.

2.3.2.14 Use-Case Instance - uciugWitnessSendFamilyNotification:ugWitnessSendFamilyNotification

The authenticated Witness creates an alert in which he can identify the victim by name and surname. The system sends the notification. The coordinator creates a crisis for the alert and a new notification is sent with every update of the crisis.

USERGOAL USE-CASE INSTANCE
<i>Instantiated Use Case</i>
WtngSendFamilyNotification




Figure 2.26: The number of the user compared with the time




Figure 2.27: Use case instance of ugVictimSendFamilyNotification




Figure 2.28: Use case instance of `ugWitnessSendFamilyNotification`

Chapter 3

Environment Model

We provide below the view(s) defined for the **Messip** environment model (cf. [?]) of the system.

3.1 Local view 01

Figure 3.1 shows the local view giving the second part of the environment model of the system in term of its state class, actors with their input and output interfaces and all related associations.




Figure 3.1: Environment Model - Local View 01. environment model local view - Part 1.

3.2 Local view 02

Figure 3.2 shows the local view giving the second part the environment model of the system in term of its state class, actors with their input and output interfaces and all related associations.




Figure 3.2: Environment Model - Local View 02. environment model local view - Part 2.

3.3 Local view 03

Figure 3.3 shows the local view for the administrator actor and interfaces

3.4 Local view 04

Figure 3.4 shows the local view for the coordinator actor and interfaces

3.5 Local view 05

Figure 3.5 shows the local view for the authenticated actor and interfaces

3.6 Local view 10

Figure 3.6




Figure 3.3: Environment Model - Local View 03. administrator actor environment model view.




Figure 3.4: Environment Model - Local View 04. coordinator actor environment model view.




Figure 3.5: Environment Model - Local View 05. authenticated actor environment model local view.



Figure 3.6: Environment Model - Local View 10. .

3.7 Local view 12

Figure 3.7



Figure 3.7: Environment Model - Local View 12. .

3.8 Global view 01

Figure 3.8 shows a global view for all actors with their relationships with ctState




Figure 3.8: Environment Model - Global View 01. em-gv-01 environment model global view.

3.9 Actors and Interfaces Descriptions

We provide for the given views the description of the actors together with their associated input and output interface descriptions.

3.9.1 actActivator Actor

ACTOR	
<i>actActivator</i>	
represents a logical actor for time automatic message sending based on system's or environment status.	
<i>OutputInterfaces</i>	
OUT 1	[proactive] oeSolicitCrisisHandling() :ptBoolean used to avoid crisis to stay too long in an not handled status.
OUT 2	[proactive] oeSetClock(AcurrentClock:dtDateAndTime) :ptBoolean used to update the system's time

3.9.2 actAdministrator Actor

ACTOR	
<i>actAdministrator</i>	
represents an actor responsible of administration tasks for the <i>iCrash</i> system.	

continues in next page ...

...Actor table continuation

<i>Extends</i>	icrash.environment.actAuthenticated
<i>OutputInterfaces</i>	
OUT 1	oeAddCoordinator (AdtCoordinatorID:dtCoordinatorID, AdtLogin:dtLogin, AdtPassword:dtPassword) :ptBoolean sent to add a new coordinator in the system's post state and environment's post state.
OUT 2	oeDeleteCoordinator (AdtCoordinatorID:dtCoordinatorID) :ptBoolean sent to delete an existing coordinator in the system's post state and environment's post state.
<i>InputInterfaces</i>	
IN 1	ieCoordinatorAdded () :ptBoolean its reception confirms the creation of the requested coordinator.
IN 2	ieCoordinatorDeleted () :ptBoolean its reception confirms the deletion of the requested coordinator.
IN 3	ieClickStatistic () :ptBoolean
IN 4	ieStatistic () :ptBoolean
IN 5	ieCallTimeAndCrisisNumber () :ptBoolean

3.9.3 **actAuthenticated Actor**

ACTOR	
<i>actAuthenticated</i>	
abstract actor providing reusable input and output interfaces for actors that need to authenticate themselves.	
<i>OutputInterfaces</i>	
OUT 1	oeLogin (AdtLogin:dtLogin, AdtPassword:dtPassword) :ptBoolean sent to request authorization to request access secured system operations.
OUT 2	oeLogout () :ptBoolean sent to end the secured access to specific system operations.
OUT 3	oeSubmitCaptcha (AdtResponse:dtCaptchaResponse) :ptBoolean sent to submit an answer to a previously given captcha test
OUT 4	oeCreateAlert () :ptBoolean sent to create a new alert
<i>InputInterfaces</i>	
IN 1	ieMessage (AMessage:ptString) :ptBoolean allows for receiving general textual messages.
IN 2	ieConfirmCaptcha (ACaptcha:dtCaptcha) :ptBoolean The request of the system to the user to field a captcha test

3.9.4 **actCaptchaService Actor**

ACTOR	
<i>actCaptchaService</i>	<i>continues in next page ...</i>

... Actor table continuation

Actor providing a randomly generated captcha test to hedge a users login process. It also keeps track of the related correct answers and he is responsible for verifying a user's answer to a given captcha test.

<i>OutputInterfaces</i>	
OUT 1	oeSendCaptcha (AdtCaptcha:dtCaptcha, AdtResponse:dtCaptchaResponse) :ptBoolean The response by the actor which provides a captcha test to the system
OUT 2	oeCaptchaInvalid(AdtCaptchaId:ptInteger) :ptBoolean Returns an answer to the system to notify that the supplied captcha was invalid
OUT 3	oeCaptchaValid(AdtCaptchaId:ptInteger) :ptBoolean Returns an answer to the system to notify that the supplied captcha was valid
<i>InputInterfaces</i>	
IN 1	ieGenerateCaptcha () :ptBoolean The request to the actor to generate and provide a captcha test
IN 2	ieVerifyCaptcha (AdtCaptchaResponse:dtCaptchaResponse) :ptBoolean Submits a captcha answer to the actor to be verified

3.9.5 actComCompany Actor

ACTOR
<i>actComCompany</i>
represents the communication company stakeholder ensuring the input/ouput of textual messages with humans having communicaiton devices.
<i>OutputInterfaces</i>
OUT 1 oeAlert (AetHumanKind:etHumanKind, AdtDate:dtDate, AdtTime:dtTime, AdtPhoneNumber:dtPhoneNumber, AdtGPSLocation:dtGPSLocation, AdtComment:dtComment) :ptBoolean sent to alert of a potential crisis situation.
<i>InputInterfaces</i>
IN 1 ieSmsSend (AdtPhoneNumber:dtPhoneNumber, AdtSMS:dtSMS) :ptBoolean allows for receiving textual messages to be dispatched to the communication company customers having the provided phone number.

3.9.6 actCoordinator Actor

ACTOR
<i>actCoordinator</i>
represents actor responsible of handling one or several crisis for the <i>iCrash</i> system.
<i>Extends</i>
icrash.environment.actAuthenticated
<i>OutputInterfaces</i>
OUT 1 oeInvalidateAlert (AdtAlertID:dtAlertID) :ptBoolean sent to indicate that an alert should be considered as closed.
OUT 2 oeCloseCrisis (AdtCrisisID:dtCrisisID) :ptBoolean sent to indicate that a crisis should be considered as closed.
OUT 3 oeGetAlertsSet (AetAlertStatus:etAlertStatus) :ptBoolean sent to request all the ctAlert instances having a specific status.

continues in next page ...

...Actor table continuation

OUT 4	oeGetCrisisSet (AetCrisisStatus:etCrisisStatus) :ptBoolean sent to request all the ctCrisis instances having a specific status.
OUT 5	oeSetCrisisHandler (AdtCrisisID:dtCrisisID) :ptBoolean sent to declare himself as been the handler of a crisis having the specified id.
OUT 6	oeReportOnCrisis (AdtCrisisID:dtCrisisID, AdtComment:dtComment) :ptBoolean sent to update the textual information available for a specific handled crisis.
OUT 7	oeSetCrisisStatus (AdtCrisisID:dtCrisisID, AetCrisisStatus:etCrisisStatus) :ptBoolean sent to define the handling status of a specific crisis.
OUT 8	oeSetCrisisType (AdtCrisisID:dtCrisisID, AetCrisisType:etCrisisType) :ptBoolean sent to define the gravity type of a specific crisis.
OUT 9	oeValidateAlert (AdtAlertID:dtAlertID) :ptBoolean sent to indicate that a specific alert is not a fake.
OUT 10	oeCreateAlert () :ptBoolean
OUT 11	oeCreateCrisis () :ptBoolean
OUT 12	oeUpdateCrisis () :ptBoolean

InputInterfaces

IN 1	ieSendAnAlert (ActAlert:ctAlert) :ptBoolean allows for receiving a requested ctAlert instance.
IN 2	ieSendACrisis (ActCrisis:ctCrisis) :ptBoolean allows for receiving a requested ctCrisis instance.

3.9.7 actDatabase Actor

ACTOR	
<i>actDatabase</i>	
<i>InputInterfaces</i>	
IN 1 ieCallTimeAndCrisisNumber () :ptBoolean	
IN 2 ieCallUserActivity () :ptBoolean	
IN 3 ieCallTypeWithTimeAverage () :ptBoolean	
IN 4 oeSendStatistic () :ptBoolean	
IN 5 oeStatistic () :ptBoolean	

3.9.8 actMailingService Actor

ACTOR	
<i>actMailingService</i>	
An actor who is responsible for sending mails to actors who are registered in the system with an e-mail address	

continues in next page ...

...Actor table continuation

<i>InputInterfaces</i>	
IN 1	ieSendMail (AAddress:ptString, ATtitle:ptString, AContent:ptString) :ptBoolean Sends an e-mail to a given e-mail address

3.9.9 actMsrCreator Actor

ACTOR
<i>actMsrCreator</i>
Represents the creator stakeholder in charge of state and environment initialization.
<i>OutputInterfaces</i>
OUT 1 oeCreateSystemAndEnvironment (AqtyComCompanies:ptInteger) :ptBoolean sent to request the initialization of the system's class instances and the environment actors instances.

3.9.10 actSystem Actor

ACTOR
<i>actSystem</i>
<i>OutputInterfaces</i>
OUT 1 ugSercurelyUserSystem () :ptBoolean
OUT 2 ugVictimSendFamilyNotification () :ptBoolean
OUT 3 ugWitnessSendFamilyNotification () :ptBoolean
OUT 4 oeChooseInformation () :ptBoolean
OUT 5 oeSendNotification () :ptBoolean
OUT 6 oeSendStatistic () :ptBoolean
<i>InputInterfaces</i>
IN 1 ieCallTimeAndCrisisNumber () :ptBoolean
IN 2 ieCallUserActivity () :ptBoolean
IN 3 ieCallTypeWithTimeAverage () :ptBoolean

Chapter 4

Concept Model

4.1 PrimaryTypes-Classes

4.1.1 Local view 01

Figure 4.1 shows the local view on all the primary types class types.




Figure 4.1: Concept Model - PrimaryTypes-Classes local view 01. Local view of all the primary types class types .

4.1.2 Local view 02

Figure 4.2 shows the local view of the **ctState** primary type class type.

4.1.3 Local view 03

Figure 4.3 shows the local view of the **ctAlert** primary type class type.

ctState	
@	nextValueForAlertID : dtInteger
@	nextValueForCrisisID : dtInteger
@	clock : dtDateAndTime
@	crisisReminderPeriod : dtSecond
@	maxCrisisReminderPeriod : dtSecond
@	vpLastReminder : dtDateAndTime
@	vpStarted : ptBoolean
	init(AnextValueForAlertID: dtInteger, AnextValueForCrisisID: dtInteger, Aclock: • dtDateAndTime, AcrisisReminderPeriod: dtSecond, AmaxCrisisReminderPeriod: dtSecond, AvpLastReminder: dtDateAndTime, AvpStarted: ptBoolean): ptBoolean

Figure 4.2: Concept Model - PrimaryTypes-Classes local view 02. local view of the ctState primary type.

ctAlert	
@	id : dtAlertID
@	status : etAlertStatus
@	location : dtGPSLocation
@	instant : dtDateAndTime
@	comment : dtComment
	init(Aid: dtAlertID, Astatus: etAlertStatus, Alocation: dtGPSLocation, Ainstant: dtDateAndTime, • Acomment: dtComment): ptBoolean
	• isSentToCoordinator(AactCoordinator: actCoordinator): ptBoolean

Figure 4.3: Concept Model - PrimaryTypes-Classes local view 03. local view of the ctAlert primary type.

4.1.4 Local view 04

Figure 4.4 shows the local view of the ctCrisis primary type class type.




Figure 4.4: Concept Model - PrimaryTypes-Classes local view 04. local view of the ctCrisis primary type.

4.1.5 Global view 01

Figure 4.5 shows the global view on primary types class types showing the association(s) types with the actor classes of the environment model.

4.2 PrimaryTypes-Datatypes

4.2.1 Local view 06

Figure 4.6

4.2.2 Global view 01

Figure 4.7 shows a global view on the *iCrash* primary types datatype types.

4.3 SecondaryTypes-Datatypes

4.3.1 Local view 01

Figure 4.8 shows the local view of the secondary types datatype types.




Figure 4.5: Concept Model - PrimaryTypes-Classes global view 01. Primary types class types global view - cm-pt-ct-gv-01 .




Figure 4.6: Concept Model - PrimaryTypes-Datatypes local view 06. .




Figure 4.7: Concept Model - PrimaryTypes-Datatypes global view 01. global view of primary types datatype types - cm-pt-dt-gv-01 .




Figure 4.8: Concept Model - SecondaryTypes-Datatypes local view 01. Local view of the secondary types datatype types.

4.4 Concept Model Types Descriptions

This section provides the textual descriptions of all the types defined in the concept model and that can be part of the graphical views provided.

4.4.1 Primary types - Class types descriptions

The table below is providing comments on the graphical views given for the class types of the primary types. Type logical operations are precisely specified in the operation model.

CLASSES	
<i>ctAdministrator</i>	
used to characterize internally the entity that is responsible of administrating the <i>iCrash</i> system.	
<i>extends</i>	icrash.concepts.primarytypes.classes.ctAuthenticated
operation	init (Alogin:dtLogin, Apwd:dtPassword) :ptBoolean used to initialize the current object as a new instance of the ctAdministrator type.
<i>ctAlert</i>	
Used to model crisis alerts sent by any human having communication capability using communication companies belonging to the system's environment	
attribute	comment: dtComment a textual description providing unstructured information on the alert.
attribute	id: dtAlertID the alert unique identification information.
attribute	instant: dtDateAndTime the date and time at which the alert notification has been sent.
attribute	location: dtGPSLocation the position of the alert provided by the space-based satellite navigation system used by the human using the communication company to inform the <i>iCrash</i> system of a crisis.
attribute	status: etAlertStatus the alert validation status
operation	init (Aid:dtAlertID, Astatus:etAlertStatus, Alocation:dtGPSLocation, Ainstant:dtDateAndTime, Acomment:dtComment) :ptBoolean used to initialize the current object as a new instance of the ctAlert type.
operation	isSentToCoordinator (AactCoordinator:actCoordinator) :ptBoolean used to provide a given coordinator with current alert information.

continues in next page ...

... Classes table continuation

<i>... Classes table continuation</i>	
<i>ctAuthenticated</i>	
	used to model system's representation about actors that need to authenticate to access some specific functionalities.
attribute	login: <code>dtLogin</code> an identifier for authentication.
attribute	pwd: <code>dtPassword</code> a key for authentication.
attribute	vpIsLogged: <code>ptBoolean</code> used to determine the access status.
operation	init (Alogin:dtLogin, Apwd:dtPassword) :ptBoolean used to initialize the current object as a new instance of the ctAuthenticated type.
<i>ctCaptchaService</i>	
attribute	map: <code>dtCaptchaResponseMap</code>
operation	init () :ptBoolean
<i>ctCoordinator</i>	
	used to model system's representation about the actors that have the responsibility to handle alerts and crisis.
extends	icrash.concepts.primarytypes.classes.ctAuthenticated
attribute	id: <code>dtCoordinatorID</code> a unique identification information.
operation	init (Aid:dtCoordinatorID, Alogin:dtLogin, Apwd:dtPassword) :ptBoolean used to initialize the current object as a new instance of the ctCoordinator type.
<i>ctCrisis</i>	
	Used to model crisis that are inferred from the reception of at least one alert message. Crisis are entities that are handled by the <i>iCrash</i> system.
attribute	comment: <code>dtComment</code> a textual description providing unstructured information on the crisis handling.
attribute	id: <code>dtCrisisID</code> the crisis unique identification information.
attribute	instant: <code>dtDateAndTime</code> the date and time at which the first related alert notification has been sent.
attribute	location: <code>dtGPSLocation</code> the position of the crisis equal by the one of the first alert received and associated to the crisis.
attribute	status: <code>etCrisisStatus</code> the crisis handling status.
attribute	type: <code>etCrisisType</code> an indication of the gravity of the crisis.
operation	handlingDelayPassed () :ptBoolean used to determine if the crisis stood too long in a pending status since last reminder.
operation	init (Aid:dtCrisisID, Atype:etCrisisType, Astatus:etCrisisStatus, Alocation:dtGPSLocation, Ainstant:dtDateAndTime, Acomment:dtComment) :ptBoolean used to initialize the current object as a new instance of the ctAlert type.

continues in next page ...

... Classes table continuation

operation	isAllocatedIfPossible() :ptBoolean used to allocate a crisis to a coordinator if any or to alert the administrator of crisis waiting to be handled.
operation	isSentToCoordinator(AactCoordinator:actCoordinator) :ptBoolean used to provide a given coordinator with current crisis information.
operation	maxHandlingDelayPassed() :ptBoolean used to determine if the crisis stood too longly in a pending status since its creation.
<i>ctHuman</i>	
	used to model system's representation about the indirect actors that has alerted of potential crisis.
attribute	id: dtPhoneNumber the number of the communication device used to send an alert to <i>iCrash</i> system.
attribute	kind: etHumanKind role with respect to the alert notified.
operation	init (Aid:dtPhoneNumber, Akind:etHumanKind) :ptBoolean init: used to initialize the current object as a new instance of the ctHuman type.
<i>ctMailingService</i>	
operation	init () :ptBoolean
<i>ctState</i>	
	used to model the system. Each system specified using Messip must include a ctState class for which there is only one instance at any state of the abstract machine after creation.
attribute	clock: dtDateAndTime used to represent the system local time.
attribute	crisisReminderPeriod: dtSecond used to define the delay between two reminders after which a reminder must be sent to the administrator and to the known coordinators to encourage them to handle the crisis.
attribute	maxCrisisReminderPeriod: dtSecond used to define the maximum delay after which the crisis is randomly allocated to a coordinator if any or an alert message is sent to the administrator in order to encourage him to add coordinators.
attribute	nextValueForAlertID: dtInteger nextValueForAlertID: dtInteger: used to associate each alert declared with a unique identification value.
attribute	nextValueForCrisisID: dtInteger used to associate each crisis declared with a unique identification value.
attribute	vpLastReminder: dtDateAndTime date and time of the last reminder.
attribute	vpStarted: ptBoolean used to avoid reacting to an actor message if the system is not started (i.e. oeCreateSystemAndEnvironment not executed).
operation	init (AnextValueForAlertID:dtInteger, AnextValueForCrisisID:dtInteger, Aclock:dtDateAndTime, AcrisisReminderPeriod:dtSecond, AmaxCrisisReminderPeriod:dtSecond, AvpLastReminder:dtDateAndTime, AvpStarted:ptBoolean) :ptBoolean used to initialize the current object as a new instance of the ctState type.

4.4.2 Primary types - Datatypes types descriptions

The table below is providing comments on the graphical views given for the datatype types of the primary types.

DATATYPES	
<i>dtAlertID</i>	
A string used to identify alerts.	
<i>extends</i> dtString <i>operation</i> is () :ptBoolean used to determine which strings are considered as valid alert identifiers.	
<i>dtCaptcha</i>	
Contains the actual representation of an image based captcha test	
<i>attribute</i> id: dtCaptchaId The internal id of this captcha test. This is used for the actCaptchaGenerator to identify the captcha test in case of a response. <i>attribute</i> question: ptString The human readable question related to this captcha test, needed by a human to be able to solve the captcha test	
<i>dtCaptchaId</i>	
<i>extends</i> dtInteger	
<i>dtCaptchaImage</i>	
The actual representation of an image related to a captcha test. The inheritance from dtString allows to store the binary data of the image as bytes in string format.	
<i>extends</i> dtString <i>attribute</i> height: dtInteger Represents the height of the image in pixels <i>attribute</i> width: dtInteger Represents the width of the image in pixels	
<i>dtCaptchaResponse</i>	
Contains the users response to a given captcha test	
<i>attribute</i> id: dtCaptchaId The internal id which qualifies the related captcha test <i>attribute</i> response: ptString The response data given by the user	
<i>dtCaptchaResponseMap</i>	
A data structure which hold references to correct answers, each one related to one captcha test. This data structure maps an id number to at last one answer.	
<i>operation</i> get (AId:dtCaptchaId) :dtCaptchaResponse Gets the answer of the mapping from the given id <i>operation</i> is () :ptBoolean Verifies if this map is a valid data structure <i>operation</i> register(AdtResponse:dtCaptchaResponse) :ptBoolean Saves an answer to a captcha test to this data structure <i>operation</i> remove (AId:dtCaptchaId) :ptBoolean Removes the reference to an answer from this data structure by the given id number	
<i>dtComment</i>	

continues in next page ...

... Datatypes table continuation

a datatype made of a string value used to receive, store and send textual information about crisis and alerts.	
extends operation	dtString is() :ptBoolean used to determine which strings are considered as valid comments.
dtCoordinatorID	
A string used to identify coordinators.	
extends operation	dtString is() :ptBoolean used to determine which strings are considered as valid coordinators identifiers.
dtCrisisID	
A string used to identify crisis.	
extends operation	dtString is() :ptBoolean used to determine which strings are considered as valid crisis identifiers.
dtGPSLocation	
used to define coordinates of geographical positions on earth. It is defined a couple made of a latitude and a longitude.	
attribute attribute operation operation	latitude: dtLatitude for the latitude part of the coordinate. longitude: dtLongitude for the longitude part of the coordinate. is() :ptBoolean used to determine which couples are considered as valid dtGPSLocation values. isNearTo(AGPSLocation:dtGPSLocation) :ptBoolean used to determine if locations are considered enough close to be treated as equivalent in the application domain context.
dtLatitude	
used to define a latitude value of a geographical positions on earth.	
extends operation	dtReal is() :ptBoolean used to determine which strings are considered as valid dtLatitude.
dtLogin	
a login string used to authentify an <i>iCrash</i> user	
extends operation	dtString is() :ptBoolean used to determine which strings are considered as valid dtLogin.
dtLongitude	
used to define a longitude value of a geographical positions on earth.	
extends operation	dtReal is() :ptBoolean used to determine which strings are considered as valid dtLongitude.
dtPassword	
a password string used to authentify an <i>iCrash</i> user	
extends operation	dtString is() :ptBoolean used to determine which strings are considered as valid dtPassword.

continues in next page ...

... Datatypes table continuation

dtPhoneNumber	a string used to store the phone number from the human declaring the crisis or the alert.
extends	dtString
operation	is () :ptBoolean used to determine which strings are considered as valid dtPhoneNumber.
dtStatisticCrisisInTime	Statistic representing a number of crises compared with a specific timespan
attribute	number: ptInteger The amount of crises
attribute	time: dtTime The related timestamp
dtStatisticTypeCrisis	Show what the attribute for the static the average time of the different crises
attribute	time: dtTime The related timestamp representing the date
attribute	typeC: ptString The type of the crisis
dtStatisticUserActivity	Represents a statistic of a number of users in relation to a specific timespan
attribute	number: ptInteger The amount of involved users
attribute	time: dtTime The related timestamp

ENUMERATIONS	
etAlertStatus	
	this type is used to indicate the different validation status of an alert.
operation	is () :ptBoolean used to determine which litteral belongs to the enumeration.
etCrisisStatus	
	this type is used to indicate the different handling status of a crisis.
operation	is () :ptBoolean used to determine which litteral belongs to the enumeration.
etCrisisType	
	this type is used to indicate the different types of a crisis.
operation	is () :ptBoolean used to determine which litteral belongs to the enumeration.
etHumanKind	
	this type is used to indicate the kind of human that informs about a car crash crisis.
operation	is () :ptBoolean used to determine which litteral belongs to the enumeration.

4.4.3 Primary types - Association types descriptions

The table below is providing comments on the association types of the primary types.

UNDIRECTED ASSOCIATIONS	
<i>assctAlertctCrisis</i>	a crisis is related to one or more alerts as the alerts judged to concern all the same crisis due to their location. An alert alerts exactly one crisis.
<i>assctAlertctHuman</i>	alerts are notified by human through the communication company. We need to keep an internal representation of those human to allow for communication of alert handling.
<i>assctAuthenticatedactAuthenticated</i>	mainly used to determine if the login request of an authenticated actor can be granted based on the given credentials and the registered ones.
<i>assctCoordinatoractCoordinator</i>	frequent messages must be sent to coordinator especially in relation to crisis they handle.
<i>assctCrisisctCoordinator</i>	at any point in time we need to know if a coordinator is handling existing crisis or not.
<i>assctHumanactComCompany</i>	in order to communicate with humans who informed about potential crisis, we need to record the communication company to use to send them messages.

4.4.4 Primary types - Aggregation types descriptions

There are no aggregation types for the primary types.

4.4.4.1 Primary types - Composition types descriptions

There are no composition types for the primary types.

4.4.5 Secondary types - Class types descriptions

There are no elements in this category in the system analysed.

4.4.6 Secondary types - Datatypes types descriptions

The table below is providing comments on the graphical views given for the datatype types of the secondary types.

DATATYPES	
<i>dtSMS</i>	a datatype made of a string value used to send textual information to human mobile devices.
attribute	<i>value: ptString</i> the textual information.
operation	<i>is() :ptBoolean</i> used to determine which strings are considered as valid comments.

4.4.7 Secondary types - Association types descriptions

There are no association types for the secondary types.

4.4.8 Secondary types - Aggregation types descriptions

There are no aggregation types for the secondary types.

4.4.9 Secondary types - Composition types descriptions

There are no composition types for the secondary types.

Chapter 5

Operation Model

This section contains the operation schemes of each operation defined in either an actor, its output interface, in a primary or secondary type (class, datatype or enumeration types). The **Messip** OCL code listing is joined to the comment table.

5.1 Environment - Out Interface Operation Scheme for actActivator

5.1.1 Operation Model for oeSetClock

The oeSetClock operation has the following properties:

OPERATION	
<i>oeSetClock[proactive]</i>	
An active message used to statically set the date and time information in the system's state.	
<i>Parameters</i>	
1	AcurrentClock: dtDateAndTime the date and time to be considered as the actual one.
<i>Return type</i>	
ptBoolean	
<i>Pre-Condition (protocol)</i>	
PreP 1	the system is supposed to be created and initialized and the provided date and time value is greater than the one known by the system.
<i>Pre-Condition (functional)</i>	
PreF 1	none
<i>Post-Condition (functional)</i>	
PostF 1	the ctState instance post-state is updated to have its clock attribute equal to the given date and time.
<i>Post-Condition (protocol)</i>	
PostP 1	none

The listing 5.1 provides the **Messip** (MCL-oriented) specification of the operation.

```
1
2 /* Pre Protocol:*/
3 preP{let TheSystem: ctState in
```

```

4  let AvpStarted: ptBoolean in
5
6  /* PreP01 */
7  self.rnActor.bnSystem = TheSystem
8  and self.rnActor.bnSystem.vpStarted = AvpStarted
9  and AvpStarted = true
10 and TheSystem.clock.lt(AcurrentClock)
11
12 /* Pre Functional:*/
13 preF{true}
14
15 /* Post Functional:*/
16 postF{let TheSystem: ctState in
17   self.rnActor.bnSystem = TheSystem
18
19 /* PostF01 */
20 and TheSystem@post.clock = AcurrentClock}
21
22 /* Post Protocol:*/
23 postP{ true}

```

Listing 5.1: **Messir** (MCL-oriented) specification of the operation *oeSetClock*.

5.1.2 Operation Model for *oeSollicitateCrisisHandling*

The *oeSollicitateCrisisHandling* operation has the following properties:

OPERATION	
<i>oeSollicitateCrisisHandling[proactive]</i>	
A proactive message (message of a pro-active actor with no parameter triggered automatically if the pre protocol condition is true) used to avoid crisis to stay too long in an not handled status.	
<i>Return type</i>	
ptBoolean	
<i>Pre-Condition (protocol)</i>	
PreP 1	the system is started
PreP 2	there exist some crisis that are in pending status and for which the duration between the current ctState clock information and the last reminder is greater than the crisis reminder period duration.
<i>Pre-Condition (functional)</i>	
PreF 1	none
<i>Post-Condition (functional)</i>	
PostF 1	if there exist coordinators and crisis who stood in a not handled status more than the maximum allowed time then those crisis are randomly allocated to the existing coordinators.
PostF 2	for all other crisis who stood too longly in a not handled status but not more than the maximum delay allowed then a reminder message is sent to the administrator and all coordinator actors of the environment to sollicitate handling of those crisis.
<i>Post-Condition (protocol)</i>	
PostP 1	the value of the last reminder known by the system at post state is the system's clock value.

The listing 5.2 provides the **Messir** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol:*/
2

```

```

3 preP{let TheSystem: ctState in
4   let AvpStarted: ptBoolean in
5   let ColctCrisisToHandle:
6     Bag(ctCrisis) in
7
8   self.rnActor.rnSystem = TheSystem
9
10 /* PreP01 */
11 and TheSystem.vpStarted
12
13 /* PreP02 */
14 and TheSystem.rnctCrisis->select(handlingDelayPassed())
15   = ColctCrisisToHandle
16 and ColctCrisisToHandle->size().geq(1)
17
18 /* Pre Functional:*/
19 preF{true}
20
21 /* Post Functional:*/
22 postF{let TheSystem: ctState in
23   let AMessageForCrisisHandlers: dtComment in
24   let ColctCrisisToAllocateIfPossible:Bag(ctCrisis) in
25
26   self.rnActor.rnSystem = TheSystem
27 /* PostF01 */
28 and TheSystem.rnctCrisis->select(maxHandlingDelayPassed())
29   = ColctCrisisToAllocateIfPossible
30 and ColctCrisisToAllocateIfPossible->forAll(isAllocatedIfPossible())
31
32 /* PostF02 */
33 and TheSystem.rnctCrisis->select(handlingDelayPassed())
34   = ColctCrisisToHandle
35
36 and ColctCrisisToHandle->msrColSubtract(ColctCrisisToAllocateIfPossible)
37   = ColctCrisisToRemind
38
39 and if (ColctCrisisToRemind->size().geq(1))
40   then (AMessageForCrisisHandlers.value
41     ='There are alerts pending since more than the defined delay. Please REACT !'
42   and TheSystem.rnactAdministrator.
43     rnInterfaceIN^ieMessage(AMessageForCrisisHandlers)
44   and TheSystem.rnactCoordinator
45     ->forAll(rnInterfaceIN^ieMessage(AMessageForCrisisHandlers))
46   )
47 else true
48 endif}
49
50 /* Post Protocol:*/
51 postP{ let TheSystem: ctState in
52   let TheClock: dtDateAndTime in
53
54   self.rnActor.rnSystem = TheSystem
55   and TheSystem.clock = TheClock
56   and TheSystem@post.vpLastReminder = TheClock}

```

Listing 5.2: **Messir** (MCL-oriented) specification of the operation *oeSollicitateCrisisHandling*.

Figure 5.1 shows concept model elements in the scope of the *oeSollicitateCrisisHandling* operation

5.2 Environment - Out Interface Operation Scheme for actAdministrator

5.2.1 Operation Model for *oeAddCoordinator*

The *oeAddCoordinator* operation has the following properties:




Figure 5.1: oeSollicitateCrisisHandling operation scope

OPERATION	
<i>oeAddCoordinator</i>	
sent to add a new coordinator in the system's post state and environment's post state.	
Parameters	
1	AdtCoordinatorID: dtCoordinatorID used to initialize the id field
2	AdtLogin: dtLogin used to initialize the login field
3	AdtPassword: dtPassword used to initialize the password field
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctAdministrator instance is considered logged)
Pre-Condition (functional)	
PreF 1	it is supposed that there cannot exist a ctCoordinator instance with the same id attribute as the one the administrator wants to delete.
Post-Condition (functional)	
PostF 1	the environment has a new instance of coordinator actor allowing for input/output message communication with the system.
PostF 2	the system's state has a new instance of ctCoordinator initialized with the given values.
PostF 3	the new actor instance and ctCoordinator instance are related.
PostF 4	the new actor instance and ctCoordinator instance are related according to the authenticated association.
PostF 5	the administrator actor is informed about the satisfaction of its request.

continues in next page ...

...Operation table continuation

<i>Post-Condition (protocol)</i>	
PostP 1	none

The listing 5.3 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol*/
2  preP{let TheSystem: ctState in
3    let TheActor:actAdministrator in
4
5
6    self.rnActor.rnSystem = TheSystem
7    and self.rnActor = TheActor
8
9  /* PreP01 */
10   and TheSystem.vpStarted = true
11  /* PreP02 */
12  and TheActor.rnctAuthenticated.vpIsLogged = true}
13
14 /* Pre Functional*/
15 preF{let TheSystem: ctState in
16  let TheActor:actAdministrator in
17  let ColctCoordinators:Bag(ctCoordinator) in
18
19  self.rnActor.rnSystem = TheSystem
20  and self.rnActor = TheActor
21 /* PreF01 */
22  and TheSystem.rnctCoordinator->select(id.eq(AdtCoordinatorID))
23  = ColctCoordinators
24  and ColctCoordinators->isEmpty() = true}
25
26 /* Post Functional*/
27 postF{let TheSystem: ctState in
28  let TheactCoordinator:actCoordinator in
29  let ThectCoordinator:ctCoordinator in
30  self.rnActor.rnSystem = TheSystem
31  and self.rnActor = TheActor
32 /* PostF01 */
33  TheactCoordinator.init()
34 /* PostF02 */
35  and ThectCoordinator.init(AdtCoordinatorID,AdtLogin,AdtPassword)
36
37 /* PostF03 */
38  and TheactCoordinator@post.rnctCoordinator = ThectCoordinator
39
40 /* PostF04 */
41  and ThectCoordinator@post.rnactAuthenticated = TheactCoordinator
42
43 /* PostF05 */
44  and TheActor.rnInterfaceIN^ieCoordinatorAdded()}
45
46 /* Post Protocol*/
47 postP{ true}

```

Listing 5.3: **Messip** (MCL-oriented) specification of the operation *oeAddCoordinator*.

5.2.2 Operation Model for oeDeleteCoordinator

The *oeDeleteCoordinator* operation has the following properties:

OPERATION	
<i>oeDeleteCoordinator</i>	
sent to delete an existing coordinator in the system's post state and environment's post state.	
<i>Parameters</i>	
1	AdtCoordinatorID: dtCoordinatorID used for ctCoordinator instance retrieval
<i>Return type</i>	
ptBoolean	
<i>Pre-Condition (protocol)</i>	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctAdministrator instance is considered logged)
<i>Pre-Condition (functional)</i>	
PreF 1	it is supposed that there exist one ctCoordinator instance with the same id attribute than the one the administrator wants to create.
<i>Post-Condition (functional)</i>	
PostF 1	the ctCoordinator class instance having the required id do not belong anymore to the post state as well as is related actCoordinator actor instance.
PostF 2	the administrator actor is informed about the satisfaction of its request.
<i>Post-Condition (protocol)</i>	
PostP 1	none

The listing 5.4 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol*/
2  preP{let TheSystem: ctState in
3    let TheActor:actAdministrator in
4
5
6    self.rnActor.rnSystem = TheSystem
7    and self.rnActor = TheActor
8
9    /* PreP01 */
10   and TheSystem.vpStarted = true
11   /* PreP02 */
12   and TheActor.rnctAuthenticated.vpIsLogged = true}
13
14 /* Pre Functional*/
15 preF{let TheSystem: ctState in
16   let TheActor:actAdministrator in
17
18   self.rnActor.rnSystem = TheSystem
19   and self.rnActor = TheActor
20   /* PreF01 */
21   TheSystem.rnctCoordinator->select(id.eq(AdtCoordinatorID))
22   = ColctCoordinators
23   and ColctCoordinators->size().eq(1)}
24
25 /* Post Functional*/
26 postF{let TheSystem: ctState in
27   let TheActor:actAdministrator in
28   let ThectCoordinator:ctCoordinator in
29   self.rnActor.rnSystem = TheSystem
30   and self.rnActor = TheActor
31   /* PostF01 */
```

```

32 TheSystem.rnctCoordinator->select(id.eq(AdtCoordinatorID))
33 = ThectCoordinator
34 and ThectCoordinator.rnactCoordinator->forAll(msrIsKilled)
35 and ThectCoordinator.msrIsKilled
36
37 /* PostF02 */
38 and TheActor.rnInterfaceIN^ieCoordinatorDeleted()
39
40 /* Post Protocol:*/
41 /* PostP01 */
42 and true}
43
44 /* Post Protocol:*/
45 postP{ true}

```

Listing 5.4: **Messip** (MCL-oriented) specification of the operation *oeDeleteCoordinator*.

5.3 Environment - Out Interface Operation Scheme for actAuthenticated

5.3.1 Operation Model for oeSubmitCaptcha

The *oeSubmitCaptcha* operation has the following properties:

OPERATION
<i>oeSubmitCaptcha</i>
Submits a response to a captcha test to the system
Parameters
1 AdtResponse: dtCaptchaResponse The response given by the user of the captcha test
Return type
ptBoolean
Pre-Condition (protocol)
PreP 1 the system must be started PreP 2 the actor must not be logged in yet PreP 3 the system must have send a captcha test to the actor first
Pre-Condition (functional)
PreF 1 none
Post-Condition (functional)
PostF 1 the actors answer to the captcha test will be forwarded to the captcha validator
Post-Condition (protocol)
PostP 1 the system is no longer expecting the user to answer a captcha test

The listing 5.5 provides the **Messip** (MCL-oriented) specification of the operation.

```

1
2 /* Pre Protocol:*/
3 preP{let TheSystem: ctState in
4   let TheActor:actAuthenticated in
5     self.rnActor.rnSystem = TheSystem
6     and self.rnActor = TheActor
7

```

```

8  /* PreP01 */
9  and TheSystem.vpStarted = true
10 /* PreP02 */
11 and TheActor.rnctAuthenticated.vpIsLogged = false
12 /* PreP03 */
13 and TheActor.rnctAuthenticated.awaitedCaptchaId.is() = true}
14
15 /* Post Functional:*/
16 postF{true}
17
18 /* Post Functional:*/
19 postF{let TheSystem: ctState in
20   let TheactAuthenticated:actAuthenticated in
21   let TheactValidator:actCaptchaService in
22
23   self.rnActor.rnSystem = TheSystem
24   and self.rnActor = TheactAuthenticated
25
26   /* PostF01 */
27   and TheactValidator.bnInterfaceIN^ieVerifyCaptcha(AdtResponse) }
28
29 /* Post Protocol:*/
30 postP{ let TheSystem: ctState in
31   let TheactAuthenticated:actAuthenticated in
32
33   self.rnActor.rnSystem = TheSystem
34   and self.rnActor = TheactAuthenticated
35
36   /* PostF01 */
37   and TheactAuthenticated.rnctAuthenticated.awaitedCaptchaId.is() = false}

```

Listing 5.5: **Messip** (MCL-oriented) specification of the operation *oeSubmitCaptcha*.

5.3.2 Operation Model for oeLogin

The *oeLogin* operation has the following properties:

OPERATION	
<i>oeLogin</i>	
sent to request authorization to request access secured system operations.	
<i>Parameters</i>	
1	AdtLogin: dtLogin first information used to determine accessibility rights for the actual actor.
2	AdtPassword: dtPassword second information used to determine accessibility rights for the actual actor.
<i>Return type</i>	
ptBoolean	
<i>Pre-Condition (protocol)</i>	
PreP 1	the system is started
PreP 2	the actor is not already logged in ! (i.e. the associated ctAuthenticated instance is not considered logged)
<i>Pre-Condition (functional)</i>	
PreF 1	none
<i>Post-Condition (functional)</i>	

continues in next page ...

...Operation table continuation

PostF 1	if the login and password provided by the actor correspond to the ones that belong to the ctAuthenticated instance he is related to then a welcome message is sent to the actor (n.b. the logged status is changed as a post-protocol condition); else the actor is notified that he gave incorrect data and all the administrator actors existing in the environment are notified of an intrusion attempt.
<i>Post-Condition (protocol)</i>	
PostP 1	if the authentication information is correct then the actor is known to be logged in ! (i.e. the associated ctAuthenticated instance with given login and password is considered logged)

The listing 5.6 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol:*/
2  preP{let TheSystem: ctState in
3    let TheActor:actAuthenticated in
4    self.rnActor.rnSystem = TheSystem
5    and self.rnActor = TheActor
6
7
8  /* PreP01 */
9  and TheSystem.vpStarted = true
10 /* Prep02 */
11 and TheActor.rnctAuthenticated.vpIsLogged = false}
12
13 /* Pre Functional:*/
14 preF{/* PreF01 */
15 true}
16
17 /* Post Functional:*/
18 postF{let TheSystem: ctState in
19   let TheactAuthenticated:actAuthenticated in
20
21   let AptStringMessageForTheactAuthenticated: ptString in
22   let AptStringMessageForTheactAdministrator:ptString in
23
24   self.rnActor.rnSystem = TheSystem
25   and self.rnActor = TheactAuthenticated
26
27   and /* PostF01 */
28   if (TheactAuthenticated.rnctAuthenticated.pwd
29     = AdtPassword
30     and TheactAuthenticated.rnctAuthenticated.login
31     = AdtLogin
32   )
33   then (AptStringMessageForTheactAuthenticated.eq('You are logged ! Welcome ...')
34     and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactAuthenticated)
35   )
36   else (AptStringMessageForTheactAuthenticated
37     .eq('Wrong identification information ! Please try again ...')
38     and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactAuthenticated)
39     and AptStringMessageForTheactAdministrator.eq('Intrusion tentative !')
40     and TheSystem.rnactAdministrator
41       .rnInterfaceIN^ieMessage(AptStringMessageForTheactAdministrator)
42   )
43   endif}
44
45 /* Post Protocol:*/
46 postP{ let TheSystem: ctState in
47   let TheactAuthenticated:actAuthenticated in
48
49   self.rnActor.rnSystem = TheSystem
50   and self.rnActor = TheactAuthenticated

```

```

51  /* PostP01 */
52  if (TheactAuthenticated.rnctAuthenticated.pwd = AdtPassword
53    and TheactAuthenticated.rnctAuthenticated.login = AdtLogin
54  )
55  then (TheactAuthenticated.rnctAuthenticated@post.vpIsLogged = true)
56 else true
57 endif}

```

Listing 5.6: **Messip** (MCL-oriented) specification of the operation *oeLogin*.

5.3.3 Operation Model for *oeLogout*

The *oeLogout* operation has the following properties:

OPERATION
<i>oeLogout</i>
sent to end the secured access to specific system operations.
<i>Return type</i>
ptBoolean
<i>Pre-Condition (protocol)</i>
PreP 1 the system is started
PreP 2 the actor is currently logged in ! (i.e. the associated ctAuthenticated instance is considered logged)
<i>Pre-Condition (functional)</i>
PreF 1
<i>Post-Condition (functional)</i>
PostF 1 a logout confirmation message is sent to the actor (n.b. the logged status is changed as a post-protocol condition)
<i>Post-Condition (protocol)</i>
PostP 1 the actor is known to be logged out ! (i.e. the associated ctAuthenticated instance with given login and password is considered logged out)

The listing 5.7 provides the **Messip** (MCL-oriented) specification of the operation.

```

1
2  /* Pre Protocol:*/
3  preP{let TheSystem: ctState in
4    let TheActor:actAdministrator in
5    self.rnActor.rnSystem = TheSystem
6    and self.rnActor = TheActor
7
8  /* PreP01 */
9  and TheSystem.vpStarted = true
10 /* PreP02 */
11 and TheActor.rnctAuthenticated.vpIsLogged = true}
12
13 /* Pre Functional:*/
14 preF{/* PreF01 */
15 true}
16
17 /* Post Functional:*/
18 postF{let TheSystem: ctState in
19 let TheactAuthenticated:actAuthenticated in
20 let AptStringMessageForTheactAuthenticated: ptString in

```

```

21
22 self.rnActor.rnSystem = TheSystem
23 and self.rnActor = TheactAuthenticated
24
25 /* PostF01 */
26 AptStringMessageForTheactAuthenticated.eq('You are logged out ! Good Bye ...')
27 and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactAuthenticated)
28
29 /* Post Protocol:*/
30 postP{ let TheSystem: ctState in
31 let TheactAuthenticated:actAuthenticated in
32
33 self.rnActor.rnSystem = TheSystem
34 and self.rnActor = TheactAuthenticated.asset
35 /* PostP01 */
36 TheactAuthenticated.rnctAuthenticated@post.vpIsLogged = false}

```

Listing 5.7: **Messir** (MCL-oriented) specification of the operation *oeLogout*.

5.4 Environment - Out Interface Operation Scheme for actCaptchaService

5.4.1 Operation Model for oeSendCaptcha

The *oeSendCaptcha* operation has the following properties:

OPERATION	
<i>oeSendCaptcha</i>	
Sends a generated captcha test to the system	
Parameters	
1	AdtCaptcha: dtCaptcha The generated captcha test
2	AdtResponse: dtCaptchaResponse The correct answer to the generated captcha test
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system must be started
PreP 2	the system must be in the state for awaiting a captcha test
Pre-Condition (functional)	
PreF 1	the generated captcha test is supposed to be a valid captcha test
PreF 2	the generated captcha answer should be valid and should be related to the captcha test over it's id number
Post-Condition (functional)	
PostF 1	the system is no longer in the state of waiting for a captcha test
Post-Condition (protocol)	
PostP 1	none

The listing 5.8 provides the **Messir** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol:*/
2  preP{let TheSystem: ctState in
3    self.rnActor.rnSystem = TheSystem
4
5
6  /* PreP01 */
7  and TheSystem.vpStarted = true}
8
9  /* Pre Functional:*/
10 preF{true}
11
12 /* Post Functional:*/
13 postF{let TheSystem: ctState in
14   let TheactGenerator:actCaptchaService in
15   let TheactAuthenticated:actAuthenticated in
16
17   self.rnActor.rnSystem = TheSystem
18   and self.rnActor = TheactGenerator
19
20  /* PostF01 */
21  and TheactValidator.rnInterfaceIN^ieRegisterAnswer(AdtResponse)
22  /* PostF02 */
23  and TheactAuthenticated.rnInterfaceIN^ieConfirmCaptcha(AdtCaptcha) }
24
25 /* Post Protocol:*/
26 postP{ true}

```

Listing 5.8: **Mess1p** (MCL-oriented) specification of the operation *oeSendCaptcha*.

5.4.2 Operation Model for oeCaptchaInvalid

The *oeCaptchaInvalid* operation has the following properties:

OPERATION	
oeCaptchaInvalid	
Returns an answer to the system to notify that the supplied captcha was invalid	
Parameters	
1	AdtCaptchaId: ptInteger The id of the supplied captcha test
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	The system must be started
PreP 2	The actor for generating captcha tests must have first generated a captcha test and must have send it to the validating actor to store it locally
Pre-Condition (functional)	
PreF 1	none
Post-Condition (functional)	
PostF 1	The user is notified by the system about the invalid answer to the given captcha test by a message
Post-Condition (protocol)	
PostP 1	The actor does no longer hold reference to the correct answer to the given captcha test

The listing 5.9 provides the **Mess1p** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol*/
2  preP{let TheSystem: ctState in
3    let TheactValidator:actCaptchaService in
4    self.rnActor.rnSystem = TheSystem
5
6
7  /* PreP01 */
8  and TheSystem.vpStarted = true
9  /* PreP02 */
10 and TheactValidator.rnactCaptchaValidator.map.get(AdtCaptchaId).is() = true}
11
12 /* Pre Functional*/
13 preF{true}
14
15 /* Post Functional*/
16 postF{let TheSystem: ctState in
17   let TheactValidator:actCaptchaService in
18   let TheactAuthenticated:actAuthenticated in
19
20   let AptStringMessageForTheactValidator: ptString in
21
22   self.rnActor.rnSystem = TheSystem
23   and self.rnActor = TheactValidator
24
25  /* PostF01 */
26  and AptStringMessageForTheactValidator.eq('Your submitted captcha response is invalid. Try
     again.')
27  and TheactAuthenticated.bnInterfaceIN^ieMessage(AptStringMessageForTheactValidator) }
28
29 /* Post Protocol*/
30 postP{ let TheSystem: ctState in
31   let TheactValidator:actCaptchaService in
32
33   self.rnActor.rnSystem = TheSystem
34   and self.rnActor = TheactValidator
35
36  /* PostP01 */
37  and TheactValidator.rnactCaptchaValidator.map.remove(AdtCaptchaId) }

```

Listing 5.9: **Messip** (MCL-oriented) specification of the operation *oeCaptchaInvalid*.

5.4.3 Operation Model for oeCaptchaValid

The *oeCaptchaValid* operation has the following properties:

OPERATION	
oeCaptchaValid	
Returns an answer to the system to notify that the supplied captcha was valid	
Parameters	
1	AdtCaptchaId: ptInteger The id of the supplied captcha test
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	The system must be started
PreP 2	The actor for generating captcha tests must have first generated a captcha test and must have send it to the validating actor to store it locally
Pre-Condition (functional)	
PreF 1	none
Post-Condition (functional)	

continues in next page ...

... Operation table continuation

PostF 1	The user is notified by the system about the valid answer to the given captcha test by a message
Post-Condition (protocol)	
PostP 1	The actor does no longer hold reference to the correct answer to the given captcha test

The listing 5.10 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol:*/
2  preP{let TheSystem: ctState in
3      let TheactValidator:actCaptchaService in
4      self.rnActor.rnSystem = TheSystem
5
6      /* PreP01 */
7      and TheSystem.vpStarted = true
8      /* PreP02 */
9      and TheactValidator.rnactCaptchaValidator.map.get(AdtCaptchaId).is() = true}
10
11
12 /* Pre Functional:*/
13 preF{true}
14
15 /* Post Functional:*/
16 postF{let TheSystem: ctState in
17     let TheactValidator:actCaptchaService in
18     let TheactAuthenticated:actAuthenticated in
19
20     let AptStringMessageForTheactValidator: ptString in
21
22     self.rnActor.rnSystem = TheSystem
23     and self.rnActor = TheactValidator
24
25     /* PostF01 */
26     and AptStringMessageForTheactValidator.eq('You are now logged in!')
27     and TheactAuthenticated.bnInterfaceIN^ieMessage(AptStringMessageForTheactValidator)}
28
29 /* Post Protocol:*/
30 postP{ let TheSystem: ctState in
31     let TheactValidator:actCaptchaService in
32
33     self.rnActor.rnSystem = TheSystem
34     and self.rnActor = TheactValidator
35
36     /* PostP01 */
37     and TheactValidator.rnactCaptchaValidator.map.remove(AdtCaptchaId) }
```

Listing 5.10: **Messip** (MCL-oriented) specification of the operation *oeCaptchaValid*.

5.5 Environment - Out Interface Operation Scheme for actComCompany

5.5.1 Operation Model for oeAlert

The *oeAlert* operation has the following properties:

OPERATION

continues in next page ...

...Operation table continuation

<i>oeAlert</i>	<p>Any human having a phone able to connect to the communication companies using the <i>iCrash</i> system can send his company an sms message with structured information in order to declare an alert.</p>
<i>Parameters</i>	
1	AetHumanKind: etHumanKind the kind of human informing of an alert.
2	AdtDate: dtDate the date of the alert
3	AdtTime: dtTime the time of the alert
4	AdtPhoneNumber: dtPhoneNumber the phone number of the human sending the alert SMS message
5	AdtGPSLocation: dtGPSLocation the GPS position of the phone at the date and time the message was sent.
6	AdtComment: dtComment a free text message sent by the human providing information on the alert that he wants to declare
<i>Return type</i>	
ptBoolean	
<i>Pre-Condition (protocol)</i>	
PreP 1	the system is supposed to be created and initialized.
<i>Pre-Condition (functional)</i>	
PreF 1	the date and time the alert is declared is supposed to be in the past with respect to the current time known by the system.
<i>Post-Condition (functional)</i>	
PostF 1	the ctState attribute for the next value for alert IDs is incremented by one at post.
PostF 2	a new alert instance exists in the post state with status pending, instant information (resp. GPS location and comment) based on date and time provided (resp. position and comment); and with alert ID being a string conversion of the dtInteger value available in the pre state in the ctState instance.
PostF 3	if there exist no already registered alert near to the alert currently declared then a new crisis is added in the post state and initialized with: its ID being the one provided by the ctState instance (which is incremented by one in the post state), its type considered as small, its status being pending, its declared time being the same than the alert and a default comment indicating that a report will come later on. else the crisis to which the new alert must be related to is the one related to any alert nearby in the pre-state.
PostF 4	the post state relates the new alert to the previously characterized crisis.
PostF 5	if there is no ctHuman instance having same phone number and same kind in the pre-state then a new one is added in the post-state with given phone number and kind and is associated to the communication company actor used to declare the alert. else the pre-state one is chosen
PostF 6	and this specified ctHuman is related to the new alert thus indicating he has signed the alert.
<i>Post-Condition (protocol)</i>	
PostP 1	none

The listing 5.11 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Pre Protocol:*/
2  preP{let TheSystem: ctState in
3    self.rnActor.rnSystem = TheSystem
4
5  /* PreP01 */
6  and TheSystem.vpStarted = true}
7
8
9  /* Pre Functional:*/
10 preF{let TheSystem: ctState in
11   self.rnActor.rnSystem = TheSystem
12
13 /* PreF01 */
14 and (TheSystem.clock.date.gt(AdtDate)
15       or (TheSystem.clock.date.eq(AdtDate)
16             and TheSystem.clock.time.gt(AdtTime)
17               )
18           ) }
19
20 /* Post Functional:*/
21 postF{let TheSystem: ctState in
22
23   let ActHuman:ctHuman in
24   let TheactComCompany:actComCompany in
25   let ActAlert:ctAlert in
26   let AAlertInstant:dtDateAndTime in
27   let AetAlertStatus:etAlertStatus in
28   let ActAlertNearBy:ctAlert in
29   let ActCrisis:ctCrisis in
30   let AdtCrisisID:dtCrisisID in
31   let AetCrisisType:etCrisisType in
32   let AetCrisisStatus:etCrisisStatus in
33   let ACrisisInstant:dtDateAndTime in
34   let ACrisisdtComment:dtComment in
35   let AptStringMessage:ptString in
36   let AdtSMS:dtSMS in
37   let AdtAlertID:dtAlertID in
38
39   self.rnActor.rnSystem = TheSystem
40   and self.rnActor = TheactComCompany
41 /* PostF01 */
42 TheSystem.nextValueForAlertID=PrenextValueForAlertID
43 and PrenextValueForAlertID.add(1) = PostnextValueForAlertID
44 and TheSystem@post.nextValueForAlertID = PostnextValueForAlertID
45
46 /* PostF02 */
47 and AAlertInstant.date=AdtDate
48 and AAlertInstant.time=AdtTime
49
50 and AetAlertStatus=pending
51
52 and TheSystem.nextValueForAlertID.todtString().eq(AdtAlertID)
53
54 and ActAlert.init(AdtAlertID,
55                   AetAlertStatus,
56                   AdtGPSLocation,
57                   AAlertInstant,
58                   AdtComment)
59
60 /* PostF03 */
61 and TheSystem.rnctAlert.select(location.isNearTo(AdtGPSLocation)) = ColctAlertsNearBy
62 and if (ColctAlertsNearBy->size()=0)
63   then (TheSystem.nextValueForCrisisID = PrenextValueForCrisisID
64         and PrenextValueForCrisisID.add(1) = PostnextValueForCrisisID
65         and TheSystem@post.nextValueForCrisisID = PostnextValueForCrisisID
66         and TheSystem.nextValueForCrisisID.todtString().eq(AdtCrisisID)
67         and AdtCrisisType = small

```

```

68     and AetCrisisStatus = pending
69     and ACrisisInstant= AAlertInstant
70     and ACrisisdtComment = 'no reporting yet defined'
71     and ActCrisis.init( AdtCrisisID,
72         AdtCrisisType,
73         AetCrisisStatus,
74         AdtGPSLocation,
75         ACrisisInstant,
76         ACrisisdtComment)
77     )
78 else (ColctAlertsNearBy.rnTheCrisis->msrAny(true) = ActCrisis)
79 endif
80
81 /* PostF04 */
82 and ActAlert@post.rnTheCrisis = ActCrisis
83
84 /* PostF05 */
85 and TheSystem.rnctHuman->select(id.eq(AdtPhoneNumber)) = HumanColl
86
87 and HumanColl->select(kind.etEq(AetHumanKind)) = HumanCol2
88 and if (HumanCol2->msrIsEmpty)
89     then (ActHuman.init(AdtPhoneNumber,AetHumanKind)
90         and ActHuman@post.rnactComCompany = TheactComCompany
91     )
92 else (HumanCol2->any(true) = ActHuman)
93 endif
94
95 and ActHuman.rnSignaled->msrIncluding(ActAlert) = ColAlerts
96
97 and ActHuman@post.rnSignaled = ColAlerts
98
99 /* PostF06 */
100 AdtSMS.value = 'Your alert has been registered. We will handle it and keep you informed'
101 and TheactComCompany.rnInterfaceIN^ieSmsSend(AdtPhoneNumber,AdtSMS) }
102
103 /* Post Protocol:*/
104 postP{ true}

```

Listing 5.11: **Messir** (MCL-oriented) specification of the operation *oeAlert*.

Figure 5.2 shows concept model elements in the scope of the oeAlert operation

Figure 5.3 shows concept model elements in the scope of the oeAlert operation

5.6 Environment - Out Interface Operation Scheme for actCoordinator

5.6.1 Operation Model for oeCloseCrisis

The oeCloseCrisis operation has the following properties:

OPERATION
<i>oeCloseCrisis</i>
sent to indicate that a crisis should be considered as closed.
<i>Parameters</i>
1 AdtCrisisID: dtCrisisID the identification information used to determine the crisis to close
<i>Return type</i>
ptBoolean

continues in next page ...

... Operation table continuation

<i>Pre-Condition (protocol)</i>	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
<i>Pre-Condition (functional)</i>	
PreF 1	it is supposed that there exist one ctCrisis instance with the same id attribute value as the one provided by the coordinator actor who wants to close.
<i>Post-Condition (functional)</i>	
PostF 1	the ctCrisis class instance having the provided id is considered closed in the post state.
PostF 2	There is no handler declared in the system as associated to the crisis.
PostF 3	all the alert instances associated to this crisis do not belong any more to the system's post state.
PostF 4	the coordinator actor is informed about the satisfaction of its request.
<i>Post-Condition (protocol)</i>	
PostP 1	none

5.6.2 Operation Model for oeGetAlertsSet

The oeGetAlertsSet operation has the following properties:

OPERATION	
<i>oeGetAlertsSet</i>	
sent to request all the ctAlert instances having a specific status.	
Parameters	
1	AetAlertStatus: etAlertStatus the criteria used to select the alerts to send back to the actor
Return type	
ptBoolean	
<i>Pre-Condition (protocol)</i>	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
<i>Pre-Condition (functional)</i>	
PreF 1	none
<i>Post-Condition (functional)</i>	
PostF 1	the post state is the one obtained by satisfying the isSentToCoordinator predicate for each alert having the provided status and for the actor sending the message. (cf. specification of isSentToCoordinator predicate given for the ctAlert type).
<i>Post-Condition (protocol)</i>	
PostP 1	none

5.6.3 Operation Model for oeGetCrisisSet

The oeGetCrisisSet operation has the following properties:

OPERATION
<i>continues in next page ...</i>

... Operation table continuation

<i>oeGetCrisisSet</i>	sent to request all the ctCrisis instances having a specific status.
Parameters	
1 AetCrisisStatus: etCrisisStatus	the status information used to determine the crisis to send back to the actor
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
Pre-Condition (functional)	
PreF 1	none
Post-Condition (functional)	
PostF 1	the post state is the one obtained by satisfying the <code>isSentToCoordinator</code> predicate for each crisis having the provided status and for the actor sending the message <code>ieSendACrisis</code> . (cf. specification of <code>isSentToCoordinator</code> predicate given for the <code>ctCrisis</code> type.)
Post-Condition (protocol)	
PostP 1	none

5.6.4 Operation Model for oeInvalidateAlert

The `oeInvalidateAlert` operation has the following properties:

OPERATION	
<i>oeInvalidateAlert</i>	
sent to indicate that an alert should be considered as closed.	
Parameters	
1 AdtAlertID: dtAlertID	
the identification information used to determine the alert to close	
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
Pre-Condition (functional)	
PreF 1	it is supposed that there exist one <code>ctAlert</code> instance with the same <code>id</code> attribute value as the one provided by the coordinator actor who wants to close.
Post-Condition (functional)	
PostF 1	the <code>ctAlert</code> class instance having the provided id is considered closed in the post state.
PostF 2	the coordinator actor is informed about the satisfaction of its request.
Post-Condition (protocol)	
PostP 1	none




Figure 5.2: oeAlert operation scope




Figure 5.3: oeAlert operation scope

5.6.5 Operation Model for oeReportOnCrisis

The `oeReportOnCrisis` operation has the following properties:

OPERATION	
<i>oeReportOnCrisis</i>	
sent to update the textual information available for a specific handled crisis.	
Parameters	
1	AdtCrisisID: dtCrisisID the identification information used to determine the crisis to report on
2	AdtComment: dtComment the textual information commenting the crisis
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
Pre-Condition (functional)	
PreF 1	it is supposed that there exist one crisis in the pre state having the given id.
Post-Condition (functional)	
PostF 1	the comment attribute of the crisis instance having the given id is replaced by the given one and the requesting actor is notified of this update.
Post-Condition (protocol)	
PostP 1	none

5.6.6 Operation Model for oeSetCrisisHandler

The `oeSetCrisisHandler` operation has the following properties:

OPERATION	
<i>oeSetCrisisHandler</i>	
sent to declare himself as been the handler of a crisis having the specified id.	
Parameters	
1	AdtCrisisID: dtCrisisID the identification information used to determine the crisis
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
Pre-Condition (functional)	
PreF 1	there exist one crisis having the given id in the pre-state.
Post-Condition (functional)	
PostF 1	the ctCrisis instance having the provided id is in handled status at poststate and is associated to the actor that sends the message (which himself is notified with a textual message as confirmation).

continues in next page ...

... Operation table continuation

PostF 2	All the alerts related to this crisis are sent to the actor such that he can decide how to handle them.
PostF 3	if the crisis was already handled at pre-state then the associated handler actor is notified about the change of handler for one of his crisis (n.b. it might be the same even if not relevant).
PostF 4	a message is sent to the communication company for any human related to an alert associated to the crisis. A human will receive as many messages as alerts he sent despite the fact that they might relate to the same crisis (i.e. one alert, one acknowledgement).
Post-Condition (protocol)	
PostP 1	none

5.6.7 Operation Model for oeSetCrisisStatus

The `oeSetCrisisStatus` operation has the following properties:

OPERATION	
<i>oeSetCrisisStatus</i>	
sent to define the handling status of a specific crisis.	
Parameters	
1	AdtCrisisID: dtCrisisID the identification information used to determine the crisis
2	AetCrisisStatus: etCrisisStatus the new status value
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
Pre-Condition (functional)	
PreF 1	it is supposed that there exist one crisis in the pre state having the given id.
Post-Condition (functional)	
PostF 1	the crisis status attribute of the crisis instance having the given id is replaced by the given one and the requesting actor is notified of this update.
Post-Condition (protocol)	
PostP 1	none

5.6.8 Operation Model for oeSetCrisisType

The `oeSetCrisisType` operation has the following properties:

OPERATION	
<i>oeSetCrisisType</i>	
sent to define the gravity type of a specific crisis.	
Parameters	
1	AdtCrisisID: dtCrisisID the identification information used to determine the crisis

continues in next page ...

... Operation table continuation

2	AetCrisisType: etCrisisType the new type value
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
Pre-Condition (functional)	
PreF 1	it is supposed that there exist one crisis in the pre state having the given id.
Post-Condition (functional)	
PostF 1	the crisis type attribute of the crisis instance having the given id is replaced by the given one and the requesting actor is notified of this update.
Post-Condition (protocol)	
PostP 1	none

5.6.9 Operation Model for oeValidateAlert

The `oeValidateAlert` operation has the following properties:

OPERATION	
<i>oe ValidateAlert</i>	
sent to indicate that a specific alert is not a fake.	
Parameters	
1	AdtAlertID: dtAlertID the identification information used to determine the alert instance
Return type	
ptBoolean	
Pre-Condition (protocol)	
PreP 1	the system is started
PreP 2	the actor logged previously and did not log out ! (i.e. the associated ctCoordinator instance is considered logged)
Pre-Condition (functional)	
PreF 1	it is supposed that there exist one ctAlert instance with the same <code>id</code> attribute value as the one provided by the coordinator actor who wants to validate.
Post-Condition (functional)	
PostF 1	the ctAlert class instance having the provided id is considered as valid in the post state and the coordinator actor is informed about the satisfaction of its request.
Post-Condition (protocol)	
PostP 1	none

5.7 Environment - Out Interface Operation Scheme for actMsrCreator

5.7.1 Operation Model for oeCreateSystemAndEnvironment

The oeCreateSystemAndEnvironment operation has the following properties:

OPERATION	
<i>oeCreateSystemAndEnvironment</i>	
sent to request the initialization of the system's class instances and the environment actors instances.	
<i>Parameters</i>	
1	AqtyComCompanies: ptInteger the quantity of communication companies to create in the environment
<i>Return type</i>	
ptBoolean	
<i>Pre-Condition (protocol)</i>	
PreP 1	none
<i>Pre-Condition (functional)</i>	
Pref 1	none
<i>Post-Condition (functional)</i>	
PostF 1	the ctState instance is initialized with the integer 1 for the crisis and alert counters used for their identifications, a value for the clock corresponding to a default initial time (i.e. January 1st, 1970) the crisis reminder period is set to 300 seconds, the maximum crisis reminder period is fixed to 1200 seconds (i.e. 20 minutes), an initial value for the automatic reminder period equal to the current date and time and the system is considered in a started state. Those predicates must be satisfied first since all the other depend on the existence of a ctState instance !
PostF 2	the actMsrCreator actor instance is initiated (remember that since the oeCreateSystemAndEnvironment is a special event its role is to make consistent the post state thus creating the actor and its interfaces is required even though the sending of this message logically would need the actor and its interfaces to already exist ...).
PostF 3	the environment for communication company actors, in the post state, is made of AqtyComCompanies instances allowing for receiving and sending messages to humans.
PostF 4	the environment for administrator actors, in the post state, is made of one instance.
PostF 5	the environment for activator actors, in the post state, is made of one instance allowing for automatic message sending based on current system's and environment state'.
PostF 6	the set of ctAdministrator instances at post is made of one instance initialized with 'icrashadmin' (resp. '7WXC1359') for login (resp. password) values.
PostF 7	the association between ctAdministrator and actAdministrator is made of one couple made of the conjointly specified instances.
<i>Post-Condition (protocol)</i>	
PostP 1	none is given since the only protocol variable to be modified in the post state is the one initialized with the ctState instance (i.e. vpStarted).

The listing 5.12 provides the **Messip** (MCL-oriented) specification of the operation.


```

1
2 /* Pre Protocol:*/
3 preP{true}
4
5 /* Pre Functional:*/
6 preF{true}
7
8 /* Post Functional:*/
9 postF{let TheSystem: ctState in
10    let AactMsrCreator: actMsrCreator in
11    let AactAdministrator: actAdministrator in
12    let AnextValueForAlertID: dtInteger in
13    let AnextValueForCrisisID: dtInteger in
14    let Aclock: dtDateAndTime in
15    let AcrisisReminderPeriod: dtSecond in
16    let AmaxCrisisReminderPeriod: dtSecond in
17    let AvpStarted: ptBoolean in
18
19 /* PostF01 -- MUST ALWAYS BE MADE FIRST -- */
20    AnextValueForAlertID.value.eq(1)
21    and AnextValueForCrisisID.value.eq(1)
22    and Aclock.date.year.value = 1970
23    and Aclock.date.month.value = 01
24    and Aclock.date.day.value = 01
25    and Aclock.time.hour.value = 00
26    and Aclock.time.minute.value = 00
27    and Aclock.time.second.value = 00
28
29    and AcrisisReminderPeriod.value.eq(300)
30    and AmaxCrisisReminderPeriod.value.eq(1200)
31    and AvpStarted = true
32    and TheSystem.init(AnextValueForAlertID,
33        AnextValueForCrisisID,
34        Aclock,
35        AcrisisReminderPeriod,
36        AmaxCrisisReminderPeriod,
37        Aclock,
38        AvpStarted
39    )
40 /* PostF02*/
41 and AactMsrCreator.init()
42 /* PostF03 */
43 and let AactComCompanyCol: Bag(actComCompany) in
44 AactComCompanyCol->size() = AqtyComCompanies
45 AactComCompanyCol-> forAll(init())
46 /* PostF04*/
47 and AactAdministrator.init()
48 /* PostF05*/
49 and let AactActivator:actActivator in
50 AactActivator.init()
51 /* PostF06 */
52 and let ActAdministrator:ctAdministrator in
53    let AdtLogin:dtLogin in
54    let AdtPassword:dtPassword in
55    AdtLogin.value.eq('icrashadmin')
56    and AdtPassword.value.eq('7WXC1359')
57    and ActAdministrator.init(AdtLogin,AdtPassword)
58 /* PostF07*/
59 and ActAdministrator@post.rnactAuthenticated = AactAdministrator}
60
61 /* Post Protocol:*/
62 postP{ true}

```

Listing 5.12: **Messir** (MCL-oriented) specification of the operation *oeCreateSystemAndEnvironment*.

Figure 5.4 shows all the concept model elements in the scope of the *oeCreateSystemAndEnvironment* operation

Figure 5.4: `oeCreateSystemAndEnvironment` operation scope

5.8 Environment - Actor Operation Scheme for actMsrCreator

5.8.1 Operation Model for init

The `init` operation has the following properties:

OPERATION
<i>init</i>
used to create an instance of the actor together with its interface instances and update the associations with the <code>ctState</code> instance.
<i>Return type</i>
<code>ptBoolean</code>

5.9 Primary Types - Operation Schemes for Class ctAdministrator

5.9.1 Operation Model for init

The `init` operation has the following properties:

OPERATION
<i>init</i>
used to initialize the current object as a new instance of the <code>ctAdministrator</code> type.
<i>Parameters</i>
1 Alogin: dtLogin used to initialize the login field 2 Apwd: dtPassword used to initialize the password field
<i>Return type</i>
<code>ptBoolean</code>
<i>Post-Condition (functional)</i>
PostF 1 true iff the system poststate includes the current object as a new <code>ctAdministrator</code> instance having its login and password attributes equal to the one provided as parameters and its <code>vpIsLogged</code> attribute equal to false.

The listing 5.13 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{if
3  (
4  let Self:ctAdministrator in
5  /* Post F01 */
6  Self.login(Alogin)
7  and Self.pwd = Apwd
8  and Self.vpIsLogged = false
9
10 /* Post F02 */
11 and (Self.oclIsNew and self = Self)
12 )
13
14 then (result = true)
15 else (result = false)

```

```
16 endif}
```

Listing 5.13: **Messip** (MCL-oriented) specification of the operation *init*.

5.10 Primary Types - Operation Schemes for Class ctAlert

5.10.1 Operation Model for init

The *init* operation has the following properties:

OPERATION	
<i>init</i>	
used to initialize the current object as a new instance of the ctAlert type.	
<i>Parameters</i>	
1	Aid: dtAlertID used to initialize the id field
2	Astatus: etAlertStatus used to initialize the status field
3	Alocation: dtGPSLocation used to initialize the location field
4	Ainstant: dtDateAndTime used to initialize the instant field
5	Acomment: dtComment used to initialize the comment field
<i>Return type</i>	
ptBoolean	
<i>Post-Condition (functional)</i>	
PostF 1	true iff the system poststate includes the current object as a new ctAlert instance having its attributes equal to the ones provided as parameters.

The listing 5.14 provides the **Messip** (MCL-oriented) specification of the operation.

```

1
2 /* Post Functional:*/
3 postF{if
4 (
5 /* Post F01 */
6 let Self:ctAlert in
7 Self.id = Aid
8 and Self.status = Astatus
9 and Self.location = Alocation
10 and Self.instant = Ainstant
11 and Self.comment = Acomment
12 /* Post F02 */
13 and (Self.oclIsNew and self = Self)
14 )
15 then (result = true)
16 else (result = false)
17 endif}

```

Listing 5.14: **Messip** (MCL-oriented) specification of the operation *init*.

5.10.2 Operation Model for *isSentToCoordinator*

The *isSentToCoordinator* operation has the following properties:

OPERATION	
<i>isSentToCoordinator</i>	
used to provide a given coordinator with current alert information.	
<i>Parameters</i>	
1	AactCoordinator: actCoordinator the message destination
<i>Return type</i>	
ptBoolean	
<i>Post-Condition (functional)</i>	
PostF 1	true iff the message <i>ieSendAnAlert</i> is sent to the input interface of the given coordinator actor with the current alert as parameter value.

The listing 5.15 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{if
3  (
4  /* Post F01 */
5  AactCoordinator.rnInterfaceIN.ieSendAnAlert (self)
6  )
7  then (result = true)
8  else (result = false)
9  endif}
10

```

Listing 5.15: **Messip** (MCL-oriented) specification of the operation *isSentToCoordinator*.

5.11 Primary Types - Operation Schemes for Class *ctAuthenticated*

5.11.1 Operation Model for *init*

The *init* operation has the following properties:

OPERATION	
<i>init</i>	
used to initialize the current object as a new instance of the <i>ctAuthenticated</i> type.	
<i>Parameters</i>	
1	Alogin: dtLogin used to initialize the login field
2	Apwd: dtPassword used to initialize the password field
<i>Return type</i>	
ptBoolean	
<i>Post-Condition (functional)</i>	

continues in next page ...

... Operation table continuation

PostF 1	true iff the system poststate includes the current object as a new ctAuthenticated instance having its attributes equal to the ones provided as parameters.
---------	---

5.12 Primary Types - Operation Schemes for Class ctCoordinator

5.12.1 Operation Model for init

The `init` operation has the following properties:

OPERATION	
<i>init</i>	
used to initialize the current object as a new instance of the ctCoordinator type.	
<i>Parameters</i>	
1	Aid: dtCoordinatorID used to initialize the id field
2	Alogin: dtLogin used to initialize the login field
3	Apwd: dtPassword used to initialize the password field
<i>Return type</i>	
ptBoolean	
<i>Post-Condition (functional)</i>	
PostF 1	true iff the system poststate includes the current object as a new ctCoordinator instance having its attributes equal to the ones provided as parameters.

The listing 5.16 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{if
3  (
4  /* Post F01 */
5  let Self:ctCoordinator in
6  Self.id = Aid
7  and Self.login = Alogin
8  and Self.pwd = Apwd
9  and Self.vpIsLogged = false
10 /* Post F02 */
11 and (Self.oclIsNew and self = Self)
12 )
13 then (result = true)
14 else (result = false)
15 endif}

```

Listing 5.16: **Messip** (MCL-oriented) specification of the operation *init*.

5.13 Primary Types - Operation Schemes for Class ctCrisis

5.13.1 Operation Model for init

The `init` operation has the following properties:

OPERATION	
<i>init</i>	
used to initialize the current object as a new instance of the <code>ctCrisis</code> type.	
Parameters	
1	Aid: dtCrisisID used to initialize the id field
2	Atype: etCrisisType used to initialize the type field
3	Astatus: etCrisisStatus used to initialize the status field
4	Alocation: dtGPSLocation used to initialize the location field
5	Ainstant: dtDateAndTime used to initialize the instant field
6	Acomment: dtComment used to initialize the comment field
Return type	
ptBoolean	
Post-Condition (functional)	
PostF 1	true iff the system poststate includes the current object as a new <code>ctCrisis</code> instance having its attributes equal to the ones provided as parameters.

The listing 5.17 provides the **Messip** (MCL-oriented) specification of the operation.

```

1
2 /* Post Functional:*/
3 postF{if
4 (
5 /* Post F01 */
6 let Self:ctCrisis in
7 Self.id = Aid
8 and Self.type = Atype
9 and Self.status = Astatus
10 and Self.location = Alocation
11 and Self.instant = Ainstant
12 and Self.comment = Acomment
13 /* Post F02 */
14 and (Self.oclIsNew and self = Self)
15 )
16 then (result = true)
17 else (result = false)
18 endif}

```

Listing 5.17: **Messip** (MCL-oriented) specification of the operation `init`.

5.13.2 Operation Model for handlingDelayPassed

The handlingDelayPassed operation has the following properties:

OPERATION
<i>handlingDelayPassed</i>
used to determine if the crisis stood too longly in a pending status since last reminder.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the crisis is in pending status and if the duration between the current ctState clock information and the last reminder is greater than the crisis reminder period duration.

The listing 5.18 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheSystem:ctState in
3  let CurrentClockSecondsQty:dtInteger in
4  let vpLastReminderSecondsQty:dtInteger in
5  let CrisisReminderPeriod:dtSecond in
6  if
7    ( /* Post F01 */
8      self.rnSystem = TheSystem
9      and self.status = pending
10     and TheSystem.clock.toSecondsQty() = CurrentClockSecondsQty
11     and TheSystem.vpLastReminder.toSecondsQty() = vpLastReminderSecondsQty
12     and TheSystem.crisisReminderPeriod = CrisisReminderPeriod
13     and CurrentClockSecondsQty.sub(vpLastReminderSecondsQty).gt(CrisisReminderPeriod) = true
14   )
15 }
16 then (result = true)
17 else (result = false)
18 endif}

```

Listing 5.18: **Messip** (MCL-oriented) specification of the operation *handlingDelayPassed*.

5.13.3 Operation Model for maxHandlingDelayPassed

The maxHandlingDelayPassed operation has the following properties:

OPERATION
<i>maxHandlingDelayPassed</i>
used to determine if the crisis stood too longly in a pending status since its creation.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the crisis is in pending status and if the duration between the current ctState clock information and the crisis instant is greater than the maximum reminder period duration.

The listing 5.19 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheSystem:ctState in
3  let CurrentClockSecondsQty:dtInteger in
4  let CrisisInstantSecondsQty:dtInteger in
5  let MaxCrisisReminderPeriod:dtSecond in
6  if
7  ( /* Post F01 */
8  self.rnSystem = TheSystem
9  and self.status = pending
10 and TheSystem.clock.toSecondsQty() = CurrentClockSecondsQty
11 and Self.instant.toSecondsQty() = CrisisInstantSecondsQty
12 and TheSystem.maxCrisisReminderPeriod = MaxCrisisReminderPeriod
13 and CurrentClockSecondsQty.sub(CrisisInstantSecondsQty)
14 .gt (MaxCrisisReminderPeriod)
15 )
16 )
17 then (result = true)
18 else (result = false)
19 endif}

```

Listing 5.19: **Messip** (MCL-oriented) specification of the operation *maxHandlingDelayPassed*.

5.13.4 Operation Model for *isSentToCoordinator*

The *isSentToCoordinator* operation has the following properties:

OPERATION
<i>isSentToCoordinator</i>
used to provide a given coordinator with current crisis information.
<i>Parameters</i>
1 AactCoordinator: actCoordinator the message destination actor
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the message ieSendACrisis is sent by the simulator to the input interface of the given coordinator actor with the current crisis as parameter value.

The listing 5.20 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{if
3  (
4  /* Post F01 */
5  AactCoordinator.rnInterfaceIN.ieSendACrisis(self)
6  )
7  then (result = true)
8  else (result = false)
9  endif}

```

Listing 5.20: **Messip** (MCL-oriented) specification of the operation *isSentToCoordinator*.

5.13.5 Operation Model for *isAllocatedIfPossible*

The *isAllocatedIfPossible* operation has the following properties:

OPERATION	
<i>isAllocatedIfPossible</i>	
used to allocate a crisis to a coordinator if any or to alert the administrator of crisis waiting to be handled.	
<i>Return type</i>	
ptBoolean	
<i>Post-Condition (functional)</i>	
PostF 1	true iff the duration between the crisis creation and the system's clock is greater than the maximum delay defined and
PostF 2	if there exist at least one coordinator then (a) the post state associates to the crisis any of the existing coordinators and (b) the coordinator is informed that he is now the handlers of the crisis whose ID is communicated
PostF 3	else a message is sent to all known administrators to request creation of new coordinators.

The listing 5.21 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{if (
3    /* Post F01 */
4    self.maxHandlingDelayPassed()
5    and
6    if (TheSystem.rnactCoordinator->msrIsEmpty = false)
7    then (
8      /* Post F02 */
9      TheSystem.rnactCoordinator->msrAny(true) = TheCoordinatorActor
10     and TheCoordinatorActor.rnctCoordinator = TheCoordinator
11     and self@post.rnHandler = TheCoordinator
12     and self@post.status = handled
13     and self.id.value = TheCrisisIDptString
14     and 'You are now considered as handling the crisis having ID: '
15     .ptStringConcat(TheCrisisIDptString) = TheMessage
16     and TheCoordinatorActor.rnInterfaceIN^ieMessage(TheMessage)
17   )
18 } else ( /* Post F03 */
19   TheSystem.rnactAdministrator
20   ->forAll(rnInterfaceIN.ieMessage('Please add new coordinators to handle pending crisis !'))
21   )
22 endif
23 )
24 )
25 then (result = true)
26 else (result = false)
27 endif}
```

Listing 5.21: **Messip** (MCL-oriented) specification of the operation *isAllocatedIfPossible*.

5.14 Primary Types - Operation Schemes for Class ctHuman

5.14.1 Operation Model for init

The *init* operation has the following properties:

OPERATION	
<i>continues in next page ...</i>	

...Operation table continuation

init	used to initialize the current object as a new instance of the ctHuman type.
Parameters	
1 Aid: dtPhoneNumber	used to initialize the id field
2 Akind: etHumanKind	used to initialize the kind field
Return type	
ptBoolean	
Post-Condition (functional)	
PostF 1	true iff the system poststate includes the current object as a new ctHuman instance having its attributes equal to the ones provided as parameters.

The listing 5.22 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{if
3  (
4  /* Post F01 */
5  let Self:ctHuman in
6
7
8  Self.id = Aid
9  and Self.kind = Akind
10
11 /* Post F02 */
12 and (Self.oclIsNew and self = Self)
13 )
14 then (result = true)
15 else (result = false)
16 endif}

```

Listing 5.22: **Messip** (MCL-oriented) specification of the operation *init*.

5.14.2 Operation Model for isAcknowledged

The *isAcknowledged* operation has the following properties:

OPERATION
isAcknowledged
used to specify the property of having sent an alert acknowledge message to the human having declared the alert through its own communication company.
Return type
ptBoolean
Post-Condition (functional)
PostF 1 true iff the message ieSmsSend is sent to the related input interface of the related communication company actor with the human phone number and the generic message 'The handling of your alert by our services is in progress !'

5.15 Primary Types - Operation Schemes for Class ctState

5.15.1 Operation Model for init

The `init` operation has the following properties:

OPERATION	
<i>init</i>	
used to initialize the current object as a new instance of the <code>ctState</code> type.	
<i>Parameters</i>	
1	AnextValueForAlertID: dtInteger used to initialize the <code>nextValueForAlertID</code> field
2	AnextValueForCrisisID: dtInteger used to initialize the <code>nextValueForCrisisID</code> field
3	Aclock: dtDateAndTime used to initialize the <code>clock</code> field
4	AcrisisReminderPeriod: dtSecond used to initialize the <code>crisisReminderPeriod</code> field
5	AmaxCrisisReminderPeriod: dtSecond used to initialize the <code>maxCrisisReminderPeriod</code> field
6	AvpLastReminder: dtDateAndTime used to initialize the <code>vpLastReminder</code> field
7	AvpStarted: ptBoolean used to initialize the <code>vpStarted</code> field
<i>Return type</i>	
<code>ptBoolean</code>	
<i>Post-Condition (functional)</i>	
PostF 1	true iff the system poststate includes the current object as a new <code>ctState</code> instance having its attributes equal to the ones provided as parameters.

The listing 5.23 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{if
3  (
4  /* Post F01 */
5  let Self:ctState in
6
7
8  Self.nextValueForAlertID = AnextValueForAlertID
9  and Self.nextValueForCrisisID = AnextValueForCrisisID
10 and Self.clock = Aclock
11 and Self.crisisReminderPeriod = AcrisisReminderPeriod
12 and Self.maxCrisisReminderPeriod = AmaxCrisisReminderPeriod
13 and Self.vpLastReminder = AvpLastReminder
14 and Self.vpStarted = AvpStarted
15
16 and (Self.oclIsNew and self = Self)
17 )
18 then (result = true)
19 else (result = false)

```

```
20 endif}
```

Listing 5.23: **Messip** (MCL-oriented) specification of the operation *init*.

5.16 Primary Types - Operation Schemes for Datatype dtAlertID

5.16.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid alert identifiers.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 if the length of the value attribute of a dtAlertID is a ptInteger greater than zero and lower or equal to 20 then the operation returns the ptBoolean true, else the ptBoolean false.

The listing 5.24 provides the **Messip** (MCL-oriented) specification of the operation.

```
1
2 /* Post Functional:*/
3 postF{let TheResult: ptBoolean in
4   ( if
5     ( self.value.length().gt(0)
6       and self.value.length().leq(20)
7     )
8     then (TheResult = true)
9     else (TheResult = false)
10  endif
11  result = TheResult
12 )}
```

Listing 5.24: **Messip** (MCL-oriented) specification of the operation *is*.

5.17 Primary Types - Operation Schemes for Datatype dtComment

5.17.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid comments.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the length of the string value is not more than 160 characters.

The listing 5.25 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3      ( if
4          ( MaxLength = 160
5              and self.value.length().leq(MaxLength)
7      )
8      then (TheResult = true)
9      else (TheResult = false)
10     endif
11     result = TheResult
12 )}
```

Listing 5.25: **Messip** (MCL-oriented) specification of the operation *is*.

5.18 Primary Types - Operation Schemes for Datatype dtCoordinatorID

5.18.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which string are considered as valid alert identifiers.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 if the length of the value attribute of a dtCoordinatorID is a ptInteger greater than zero and lower or equal to 5 than the operation returns the ptBoolean true, else the ptBoolean false.

The listing 5.26 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3      ( if
4          ( self.value.length().gt(0)
5              and self.value.length().leq(5)
7      )
8      then (TheResult = true)
9      else (TheResult = false)
10     endif
11     result = TheResult
12 )}
```

Listing 5.26: **Messip** (MCL-oriented) specification of the operation *is*.

5.19 Primary Types - Operation Schemes for Datatype dtCrisisID

5.19.1 Operation Model for is

The `is` operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid crisis identifiers.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 if the length of the value attribute of a <code>dtCrisisID</code> is a <code>ptInteger</code> greater than zero and lower or equal to 10 than the operation returns the <code>ptBoolean</code> true, else the <code>ptBoolean</code> false.

The listing 5.27 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3    if
4      ( self.value.length().gt(0)
5        and self.value.length().leq(10)
6      )
7    then (TheResult = true)
8    else (TheResult = false)
9  endif
10  result = TheResult
11 }
12 }
```

Listing 5.27: **Messip** (MCL-oriented) specification of the operation `is`.

5.20 Primary Types - Operation Schemes for Datatype dtGPSLocation

5.20.1 Operation Model for is

The `is` operation has the following properties:

OPERATION
<i>is</i>
used to determine which couples are considered as valid <code>dtGPSLocation</code> values.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true if both latitude and longitude are valid values according to their <code>is</code> operation.

The listing 5.28 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3    ( if
4      ( self.latitude.is()
5        and self.longitude.is
6      )
7      then (TheResult = true)
8      else (TheResult = false)
9    endif
10   result = TheResult
11 }
12 }
```

Listing 5.28: **Messip** (MCL-oriented) specification of the operation *is*.

5.20.2 Operation Model for *isNearTo*

The *isNearTo* operation has the following properties:

OPERATION
<i>isNearTo</i>
used to determine if locations are considered enough close to be treated as equivalent in the application domain context. In the context of the iCrash system, we compute the distance between two GPS locations using the following Haversine formula. (more details can be found at: http://www.movable-type.co.uk/scripts/latlong.html and http://www.gpsvisualizer.com/calculators#distance)
<i>Parameters</i>
1 AGPSLocation: dtGPSLocation the GPS location to be compared to.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 if the Haversine formula ($\text{ACOS}(\text{SIN}(\text{lat1}) * \text{SIN}(\text{lat2}) + \text{COS}(\text{lat1}) * \text{COS}(\text{lat2}) * \text{COS}(\text{lon2-lon1})) * 6371$, in which latitudes and longitudes are in radians applied to the two dtGPS coordinates is lower to 100 meters) then the predicate is true and false otherwise.

The listing 5.29 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in true
3    let EarthRadius: dtReal in
4    let MaxDistance: dtReal in
5    let ComparedLatitude: dtLatitude in
6    let ComparedLongitude: dtLongitude in
7    let R1: dtReal in let R1a: dtReal in
8    let R2: dtReal in let R2a: dtReal in
9
10   ( if
11     ( EarthRadius.value = 6371
12       and MaxDistance.value = 100
13
14       and self.latitude = ComparedLatitude
15       and self.longitude = ComparedLongitude
16       and self.latitude.sin() = R1a
17       and self.latitude.sin().mul(R1a) = R1
18       and self.latitude.cos() = R2a
19     )}
```

```

20     and self.latitude.cos().mul(R2a) = R2
21
22     and self.longitude = ComparedLongitude
23     and self.longitude.sub(ComparedLongitude).cos().mul(R2)
24         .add(R1).acos().mul(EarthRadius).sub(MaxDistance)
25         .value.leq(0)
26     )
27     then (TheResult = true)
28     else (TheResult = false)
29     endif
30     result = TheResult
31 }

```

Listing 5.29: **Messip** (MCL-oriented) specification of the operation *isNearTo*.

5.21 Primary Types - Operation Schemes for Datatype dtLatitude

5.21.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid dtLatitude.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 <i>is</i> true if the value is a real in the interval [-90.0 , +90.0].

The listing 5.30 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3      if
4          ( AdtValue.value.geq(-90.0)
5              and AdtValue.value.leq(+90.0)
6          )
7      then (TheResult = true)
8      else (TheResult = false)
9      endif
10     result = TheResult
11 }
12 }

```

Listing 5.30: **Messip** (MCL-oriented) specification of the operation *is*.

5.22 Primary Types - Operation Schemes for Datatype dtLogin

5.22.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid dtLogin.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 is true if the length of the string value is not more than 20 characters.

The listing 5.31 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3      let MaxLength: ptInteger in
4          ( if
5              ( MaxLength = 20
6                  and self.value.length().leq(MaxLength)
7              )
8          then (TheResult = true)
9          else (TheResult = false)
10     endif
11     result = TheResult
12 ) }
```

Listing 5.31: **Messip** (MCL-oriented) specification of the operation *is*.

5.23 Primary Types - Operation Schemes for Datatype dtLongitude

5.23.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid dtLongitude.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 is true if the value is a real in the interval [-180.0 , +180.0].

The listing 5.32 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3      ( if
4          ( AdtValue.value.geq(-180.0)
5              and AdtValue.value.leq(+180.0)
6          )
7      ) }
```

```

8   then (TheResult = true)
9   else (TheResult = false)
10  endif
11  result = TheResult
12 }

```

Listing 5.32: **Messip** (MCL-oriented) specification of the operation *is*.

5.24 Primary Types - Operation Schemes for Datatype dtPassword

5.24.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid dtPassword.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 is true of the length of the string value is at least 6 characters long.

The listing 5.33 provides the **Messip** (MCL-oriented) specification of the operation.

```

1
2 /* Post Functional:*/
3 postF{let TheResult: ptBoolean in
4   let MinLength: ptInteger in
5   ( if
6     ( MinLength = 6
7     and self.value.length().geq(MinLength)
8   )
9   then (TheResult = true)
10  else (TheResult = false)
11  endif
12  result = TheResult
13 )

```

Listing 5.33: **Messip** (MCL-oriented) specification of the operation *is*.

5.25 Primary Types - Operation Schemes for Datatype dtPhoneNumber

5.25.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid dtPhoneNumber.
<i>Return type</i>

continues in next page ...

... Operation table continuation

ptBoolean
Post-Condition (functional)
PostF 1 is true of the length of the string value is from 4 to 30 characters. No standard is applied !

The listing 5.34 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3    ( if
4      ( self.value.length().gt(4)
5        and self.value.length().leq(30)
6      )
7      then (TheResult = true)
8      else (TheResult = false)
9    endif
10   result = TheResult
11 }
12 }
```

Listing 5.34: **Messip** (MCL-oriented) specification of the operation *is*.

5.26 Primary Types - Operation Schemes for Enumeration etAlertStatus

5.26.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which litteral belongs to the enumeration.
Return type
ptBoolean
Post-Condition (functional)
PostF 1 true iff the value is equal to one of the following values: pending, valid, invalid

The listing 5.35 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3    ( if
4      ( self = pending
5        or self = valid
6        or self = invalid
7      )
8      then (TheResult = true)
9      else (TheResult = false)
10     endif
11 }
```

```

12     result = TheResult
13 )

```

Listing 5.35: **Messip** (MCL-oriented) specification of the operation *is*.

5.27 Primary Types - Operation Schemes for Enumeration etCrisisStatus

5.27.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which litteral belongs to the enumeration.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the value is equal to one of the following values: pending, handled, solved, closed.

The listing 5.36 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3    if
4      ( self = pending
5       or self = handled
6       or self = solved
7       or self = closed
8     )
9    then (TheResult = true)
10   else (TheResult = false)
11   endif
12   result = TheResult
13 }
14 )

```

Listing 5.36: **Messip** (MCL-oriented) specification of the operation *is*.

5.28 Primary Types - Operation Schemes for Enumeration etCrisisType

5.28.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which litteral belongs to the enumeration.

continues in next page ...

... Operation table continuation

<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the value is equal to one of the following values: small, medium, huge

The listing 5.37 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2 postF{let TheResult: ptBoolean in
3   if
4     ( self = small
5      or self = medium
6      or self = huge
7    )
8   then (TheResult = true)
9   else (TheResult = false)
10  endif
11  result = TheResult
12 }
13 }
```

Listing 5.37: **Messip** (MCL-oriented) specification of the operation *is*.

5.29 Primary Types - Operation Schemes for Enumeration etHumanKind

5.29.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which litteral belongs to the enumeration.
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the value is equal to one of the following values: witness, victim, anonym

The listing 5.38 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2 postF{let TheResult: ptBoolean in
3   if
4     ( self = witness
5      or self = victim
6      or self = anonymous
7    )
8   then (TheResult = true)
```

```

10    else (TheResult = false)
11  endif
12  result = TheResult
13 }

```

Listing 5.38: **Messip** (MCL-oriented) specification of the operation *is*.

5.30 Secondary Types - Operation Schemes for Classes

There are no elements in this category in the system analysed.

5.31 Secondary Types - Operation Schemes for Datatype dtSMS

5.31.1 Operation Model for *is*

The *is* operation has the following properties:

OPERATION
<i>is</i>
used to determine which strings are considered as valid comments
<i>Return type</i>
ptBoolean
<i>Post-Condition (functional)</i>
PostF 1 true iff the length of the string value is not more than 160 characters.

The listing 5.39 provides the **Messip** (MCL-oriented) specification of the operation.

```

1  /* Post Functional:*/
2  postF{let TheResult: ptBoolean in
3    let MaxLength: ptInteger in
4    ( if
5      ( MaxLength = 160
6        and self.value.length().leq(MaxLength)
7      )
8      then (TheResult = true)
9      else (TheResult = false)
10     endif
11     result = TheResult
12   )
13 }

```

Listing 5.39: **Messip** (MCL-oriented) specification of the operation *is*.

5.32 Secondary Types - Operation Schemes for Enumerations

There are no elements in this category in the system analysed.

Chapter 6

Test Model(s)

6.1 Test Model for testcase01

this positive test case intends to verify the correctness of the execution of a simple instance of the suDeployAndRun use case.

6.1.1 Test Steps Specification

6.1.1.1 testcase01-ts01oeCreateSystemAndEnvironment-actMsrCreator.outactMsrCreator.oeCreateSy

The testcase01-ts01oeCreateSystemAndEnvironment-actMsrCreator.outactMsrCreator.oeCreateSy has the following properties:

TEST STEP	
<i>ts01oeCreateSystemAndEnvironment</i>	
This test step initializes the system state and environment.	
<i>Test Sent Message</i>	
TSM 1	<p>out:Creator</p> <p>sends to system</p> <p>actMsrCreator.outactMsrCreator.oeCreateSystemAndEnvironment (AqtyComCompanies)</p>
<i>Variables</i>	
V 1	Creator:icrash.environment.actMsrCreator only actMsrCreator actors can trigger the system and environment creation and initialization.
<i>Constraints</i>	
C 1	the number of communication company actor instances present in the environment is equal to four to represent all the communication companies available in Luxembourg.
<i>Oracle Constraints</i>	
OC 1	true for testing only the executability (is available and can be triggered) of the operation.

The listing 6.1 provides the **Messip** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   Creator:actMsrCreator
4   AqtyComCompanies: ptInteger
5 }
6
7 constraints{
8   AqtyComCompanies = 4
9 }
10
11 oracle{
12   constraints{
13     true
14   }
15 }
```

Listing 6.1: **Messip** (MCL-oriented) specification of the test step *testcase01-ts01oeCreateSystemAndEnvironment*.

6.1.1.2 testcase01-ts02oeSetClock-actActivator.outactActivator.oeSetClock

The *testcase01-ts02oeSetClock-actActivator.outactActivator.oeSetClock* has the following properties:

TEST STEP	
<i>ts02oeSetClock</i>	
test the update of the current time.	
<i>Test Sent Message</i>	
TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p style="color: blue;">actActivator.outactActivator.oeSetClock (ACurrentClock)</p>
<i>Variables</i>	
V 1	<p>TheActor:actActivator</p> <p>proactive actor responsible of requesting the update of the system's clock.</p>
<i>Constraints</i>	
C 1	TheActor is any instance existing in the current environment status.
C 2	ACurrentClock is a fixed date equal to the 24th November 2017 at 15:20:00 using a 24-hours notation ¹ .
<i>Oracle Constraints</i>	
OC 1	true for testing only the executability (is available and can be triggered) of the operation.

The listing 6.2 provides the **Messip** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor:actActivator
4   ACurrentClock:dtDateAndTime
```

¹for more details see the ISO 8601 Data elements and interchange formats - Information interchange - Representation of dates and times - <http://www.iso.org/iso/home/standards/iso8601.htm>

```

5 }
6
7 constraints{
8   TheActor=TheSystem.rnactActivator->any2(true)
9   ACurrentClock.date.year.value = 2017
10  ACurrentClock.date.month.value = 11
11  ACurrentClock.date.day.value = 24
12  ACurrentClock.time.hour.value = 15
13  ACurrentClock.time.minute.value = 20
14  ACurrentClock.time.second.value = 00
15 }
16
17 oracle{
18   constraints{
19     true
20   }
21 }

```

Listing 6.2: **Messip** (MCL-oriented) specification of the test step *testcase01-ts02oeSetClock*.

6.1.1.3 testcase01-ts03oeLogin-actAdministrator.outactAdministrator.oeLogin

The `testcase01-ts03oeLogin-actAdministrator.outactAdministrator.oeLogin` has the following properties:

TEST STEP	
<i>ts03oeLogin</i>	
test the authentified access of the administrator	
<i>Test Sent Message</i>	<p>TSM 1</p> <p>out:TheActor</p> <p>sends to system</p> <p>actAdministrator.outactAdministrator.oeLogin (AdtLogin, AdtPassword)</p>
<i>Variables</i>	
V 1	<p>TheActor:actAdministrator</p> <p>an actAdministrator actor as subtype of actAuthenticated can send oeLogin messages to the system.</p>
<i>Constraints</i>	
C 1	TheActor is any <code>actAdministrator</code> instance existing in the environment. It is thus expected that there exist at least one.
C 2	AdtLogin has its value attribute equal to the primitive string 'icrashadmin' (which is the correct administrator login known by the system after the step one.)
C 3	AdtPassword has its value attribute equal to the primitive string '7WXC1359' (which is the correct administrator password known by the system after the step one.)
<i>Oracle Constraints</i>	
OC 1	the <code>AMessage</code> value is expected to be equal to the primitive string 'You are logged ! Welcome ...'
OC 2	TheActor receives from system <code>ieMessage(AMessage)</code>

The listing 6.3 provides the **Messip** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actAdministrator
4   AdtLogin:dtLogin
5   AdtPassword:dtPassword
6 }
7
8 constraints{
9   TheActor=TheSystem.rnactAdministrator->any2(true)
10  AdtLogin.value.eq('icrashadmin')
11  AdtPassword.value.eq('7WXC1359')
12 }
13
14 oracle{
15   variables{
16     AMessage:ptString
17   }
18   constraints{
19     AMessage = 'You are logged ! Welcome ...'
20     TheActor.inactAdministrator.ieMessage(AMessage)
21   }
22 }
```

Listing 6.3: **Messir** (MCL-oriented) specification of the test step *testcase01-ts03oeLogin*.

6.1.1.4 testcase01-ts04oeAddCoordinator-actAdministrator.outactAdministrator.oeAddCoordinator

The *testcase01-ts04oeAddCoordinator-actAdministrator.outactAdministrator.oeAddCoordinator* has the following properties:

TEST STEP	
<i>ts04oeAddCoordinator</i>	
to test the add of a new coordinator by an administrator.	
<i>Test Sent Message</i>	
TSM 1	out:TheActor sends to system actAdministrator.outactAdministrator.oeAddCoordinator (AdtCoordinatorID, AdtLogin, AdtPassword)
<i>Variables</i>	
V 1	TheActor:actAdministrator actAdministor actors as being the only one allowed to add coordinators.
<i>Constraints</i>	
C 1	TheActor is any <code>actAdministrator</code> instance existing in the environment. It is expected that there exists at least one which is the same during all the test case.
C 2	AdtCoordinatorID is equal to 1 to set the new coordinator ID
C 3	AdtLogin has its value attribute equal to the primitive string 'steve' which is the ID defined for the new coordinator.
C 4	AdtPassword has its value attribute equal to the primitive string 'pwdMessirExcalibur2017' which is the password to be set for steve.
<i>Oracle Constraints</i>	
OC 1	the administrator should have been acknowledged for the adding of the new coordinator.

The listing 6.4 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actAdministrator
4   AdtCoordinatorID : dtCoordinatorID
5   AdtLogin:dtLogin
6   AdtPassword:dtPassword
7 }
8
9 constraints{
10  TheActor = TheSystem.rnactAdministrator->any2(true)
11  AdtCoordinatorID.value.eq('1')
12  AdtLogin.value.eq('steve')
13  AdtPassword.value.eq('pwdMessirExcalibur2017')
14 }
15
16 oracle{
17  constraints{
18    TheActor.inactAdministrator.ieCoordinatorAdded()
19  }
20 }
```

Listing 6.4: **Messir** (MCL-oriented) specification of the test step *testcase01-ts04oeAddCoordinator*.

6.1.1.5 testcase01-ts05oeLogout-actAdministrator.outactAdministrator.oeLogout

The *testcase01-ts05oeLogout-actAdministrator.outactAdministrator.oeLogout* has the following properties:

TEST STEP	
<i>ts05oeLogout</i>	
to test the logout of a connected administrator.	
<i>Test Sent Message</i>	<p>TSM 1</p> <p>out:TheActor</p> <p>sends to system</p> <p>actAdministrator.outactAdministrator.oeLogout ()</p>
<i>Variables</i>	
V 1	TheActor:actAdministrator an actAdministrator actor as subtype of actAuthenticated can send oeLogout messages to the system.
<i>Constraints</i>	
C 1	TheActor is any actAdministrator instance existing in the environment. It is expected that there exists at least one which is the same during all the test case.
<i>Oracle Constraints</i>	
OC 1	the AMessage value is expected to be equal to the primitive string 'You are logged out ! Good Bye ...'
OC 2	the administrator should have received the message AMessae.

The listing 6.5 provides the **Messip** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actAdministrator
4 }
5
6 constraints{
7   TheActor = TheSystem.rnactAdministrator->any2(true)
8 }
9
10 oracle{
11   variables{
12     AMessage:ptString
13   }
14   constraints{
15     AMessage = 'You are logged out ! Good Bye ...'
16     TheActor.inactAdministrator.ieMessage(AMessage)
17   }
18 }
```

Listing 6.5: **Messip** (MCL-oriented) specification of the test step *testcase01-ts05oeLogout*.

6.1.1.6 testcase01-ts06oeSetClock02-actActivator.outactActivator.oeSetClock

The `testcase01-ts06oeSetClock02-actActivator.outactActivator.oeSetClock` has the following properties:

TEST STEP	
<i>ts06oeSetClock02</i>	
test the update of the current time.	
<i>Test Sent Message</i>	
TSM 1	out:TheActor sends to system actActivator.outactActivator.oeSetClock (ACurrentClock)
<i>Variables</i>	
V 1	TheActor:icrash.environment.actActivator proactive actors responsible of requesting the update of the system's clock.
<i>Constraints</i>	
C 1	TheActor is any instance existing in the current environment status.
C 2	ACurrentClock is a fixed date equal to the 26th November 2017 at 10:15:00 using a 24-hours notation.
<i>Oracle Constraints</i>	
OC 1	true for testing only the executability (is available and can be triggered) of the operation.

The listing 6.6 provides the **Messip** (MCL-oriented) specification of the test step.

```

1
2 variables{
```

```

3 TheActor:actActivator
4 ACurrentClock:dtDateAndTime
5 }
6
7 constraints{
8 TheActor=TheSystem.rnactActivator->any2(true)
9 ACurrentClock.date.year.value = 2017
10 ACurrentClock.date.month.value = 11
11 ACurrentClock.date.day.value = 26
12 ACurrentClock.time.hour.value = 10
13 ACurrentClock.time.minute.value = 15
14 ACurrentClock.time.second.value = 00
15 }
16
17 oracle{
18 constraints{
19 true
20 }
21 }

```

Listing 6.6: **Messir** (MCL-oriented) specification of the test step *testcase01-ts06oeSetClock02*.

6.1.1.7 testcase01-ts07oeAlert1-actComCompany.outactComCompany.oeAlert

The `testcase01-ts07oeAlert1-actComCompany.outactComCompany.oeAlert` has the following properties:

TEST STEP	
ts07oeAlert1	
tests the declaration of a new alert functionality.	
<i>Test Sent Message</i>	
TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actComCompany.outactComCompany.oeAlert (AetHumanKind, AdtDate, AdtTime, AdtPhoneNumber, AdtGPSLocation, AdtComment)</p>
<i>Variables</i>	
V 1	<p>TheActor:actComCompany</p> <p>actComCompany actors transfer alert declaration messages.</p>
<i>Constraints</i>	
C 1	TheActor is any instance existing in the current environment status. It is expected to exist at least one.
C 2	AetHumanKind is equal to witness
C 3	AdtDate is equal to the 26th of November 2017
C 4	AdtTime is equal to 10:10:16 using a 24-hours.
C 5	AdtPhoneNumber is equal to the ptString value '+3524666445252'.
C 6	AdtGPSLocation is equal to (49.627675 , 6.159590).
C 7	AdtComment is equal to '3 cars involved in an accident.'
<i>Oracle Constraints</i>	
OC 1	AdtSMS is equal to the ptString 'Your alert has been registered. We will handle it and keep you informed'.

continues in next page ...

... Test Step table continuation

OC 2	AdtSMS is sent to the phone number AdtPhoneNumber using the communication company having sent the alert using its ieSmsSend input message.
------	--

The listing 6.7 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actComCompany
4   AetHumanKind:etHumanKind
5   AdtDate:dtDate
6   AdtTime:dtTime
7   AdtPhoneNumber:dtPhoneNumber
8   AdtGPSLocation:dtGPSLocation
9   AdtComment:dtComment
10 }
11
12 constraints{
13   TheActor = TheSystem.rnactComCompany->any2(true)
14   AetHumanKind = witness
15   AdtDate.year.value = 2017
16   AdtDate.month.value = 11
17   AdtDate.day.value = 26
18   AdtTime.hour.value = 10
19   AdtTime.minute.value = 10
20   AdtTime.second.value = 16
21   AdtPhoneNumber.value = '+3524666445252'
22   AdtGPSLocation.latitude.value = 49.627675
23   AdtGPSLocation.longitude.value = 6.159590
24   AdtComment.value = '3 cars involved in an accident.'
25 }
26
27 oracle{
28   variables{
29     AdtSMS:dtSMS
30   }
31   constraints{
32     AdtSMS.value = 'Your alert has been registered. We will handle it and keep you informed'
33     TheActor.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
34   }
35 }
```

Listing 6.7: **Messir** (MCL-oriented) specification of the test step *testcase01-ts07oeAlert1*.

6.1.1.8 testcase01-ts08oeSetClock03-actActivator.outactActivator.oeSetClock

The `testcase01-ts08oeSetClock03-actActivator.outactActivator.oeSetClock` has the following properties:

TEST STEP
<i>ts08oeSetClock03</i>
test the update of the current time.
<i>Test Sent Message</i>

continues in next page ...

... Test Step table continuation

TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actActivator.outactActivator.oeSetClock (ACurrentClock)</p>
Variables	
V 1	TheActor:actActivator proactive actor responsible of requesting the update of the system's clock.
Constraints	
C 1	TheActor is any instance existing in the current environment status.
C 2	ACurrentClock is a fixed date equal to the 26th November 2017 at 10:30:00 using a 24-hours notation.
Oracle Constraints	
OC 1	true for testing only the executability (is available and can be triggered) of the operation.

The listing 6.8 provides the **Messip** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor:actActivator
4   ACurrentClock:dtDateAndTime
5 }
6
7 constraints{
8   TheActor=TheSystem.rnactActivator->any2(true)
9   ACurrentClock.date.year.value = 2017
10  ACurrentClock.date.month.value = 11
11  ACurrentClock.date.day.value = 26
12  ACurrentClock.time.hour.value = 10
13  ACurrentClock.time.minute.value = 30
14  ACurrentClock.time.second.value = 00
15 }
16
17 oracle{
18   constraints{
19     true
20   }
21 }
```

Listing 6.8: **Messip** (MCL-oriented) specification of the test step *testcase01-ts08oeSetClock03*.

6.1.1.9 testcase01-ts09oeSollicitateCrisisHandling-actActivator.outactActivator.oeSollicitateCrisisHand

The testcase01-ts09oeSollicitateCrisisHandling-actActivator.outactActivator.oeSollicit has the following properties:

TEST STEP
<i>ts09oeSollicitateCrisisHandling</i>
test the proactive sollication to handle an alert.

Test Sent Message

continues in next page ...

... Test Step table continuation

TSM 1	out:TheActor sends to system actActivator.outactActivator.oeSollicitateCrisisHandling ()
Variables	
V 1	TheActor:icrash.environment.actActivator proactive actor responsible of triggering sollicitation functionality.
Constraints	
C 1	TheActor is any instance existing in the current environment status. It is expected to exist at least one.
Oracle Variables	
OV 1	TheAdministrator:actAdministrator actAdministrator actors can be sollicitated to handle alerts.
OV 2	TheCoordinator:actCoordinator actCoordinator actors can be sollicitated to handle alerts.
OV 3	AMessageForCrisisHandlers:ptString messages sent to sollicitated actors are of type ptString.
Oracle Constraints	
OC 1	TheAdministrator is any instance existing in the current environment status. It is expected to exist at least one.
OC 2	TheCoordinator is any instance existing in the current environment status. It is expected to exist at least one.
OC 3	AMessageForCrisisHandlers is equal to the ptString 'There are alerts pending since more than the defined delay. Please REACT !'
OC 4	TheCoordinator and TheAdministrator have received the message AMessageForCrisisHandlers.

The listing 6.9 provides the **Mess1P** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actActivator
4 }
5
6 constraints{
7   TheActor = TheSystem.rnactActivator->any2(true)
8 }
9
10 oracle{
11   variables{
12     TheAdministrator:actAdministrator
13     TheCoordinator:actCoordinator
14     AMessageForCrisisHandlers:ptString
15   }
16   constraints{
17     TheAdministrator = TheSystem.rnactAdministrator->any2(true)
18     TheCoordinator = TheSystem.rnactCoordinator->any2(true)
19     AMessageForCrisisHandlers = 'There are alerts pending since more than the defined delay. Please
                                  REACT !'
20     TheAdministrator.inactAdministrator.ieMessage(AMessageForCrisisHandlers)

```

```

21     TheCoordinator.inactAdministrator.ieMessage(AMessageForCrisisHandlers)
22 }
23 }
```

Listing 6.9: **Messir** (MCL-oriented) specification of the test step *testcase01-ts09oeSollicitateCrisisHandling*.

6.1.1.10 testcase01-ts10oeLogin02-actAuthenticated.outactAuthenticated.oeLogin

The *testcase01-ts10oeLogin02-actAuthenticated.outactAuthenticated.oeLogin* has the following properties:

TEST STEP	
<i>ts10oeLogin02</i>	
test the authentified access of the coordinator	
<i>Test Sent Message</i>	
TSM 1	out:TheActor sends to system actAuthenticated.outactAuthenticated.oeLogin (AdtLogin, AdtPassword)
<i>Variables</i>	
V 1	TheActor:actCoordinator an actCoordinator actor as subtype of actAuthenticated can send oeLogin messages to the system.
<i>Constraints</i>	
C 1	TheActor is any actAdministrator instance existing in the environment. It is thus expected that there exist at least one.
C 2	AdtLogin has its value attribute equal to the primitive string 'icrashadmin' (which is the correct administrator login known by the system after the step one.)
C 3	AdtPassword has its value attribute equal to the primitive string '7WXC1359' (which is the correct administrator password known by the system after the step one.)
<i>Oracle Constraints</i>	
OC 1	the AMessage value is expected to be equal to the primitive string 'You are logged ! Welcome ...'

The listing 6.10 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actCoordinator
4   AdtLogin:dtLogin
5   AdtPassword:dtPassword
6 }
7
8 constraints{
9   TheActor = TheSystem.rnactCoordinator->select(a | a.rnctCoordinator.login.value.eq('steve'))->any2
10  (true)
11  AdtLogin.value.eq('steve')
11  AdtPassword.value.eq('pwdMessirExcalibur2017')
```

```

12 }
13
14 oracle{
15   variables{
16     AMessage:ptString
17   }
18 constraints{
19   AMessage = 'You are logged ! Welcome ...'
20   TheActor.inactAuthenticated.ieMessage(AMessage)
21 }
22 }
```

Listing 6.10: **Messip** (MCL-oriented) specification of the test step *testcase01-ts10oeLogin02*.

6.1.1.11 testcase01-ts11oeGetCrisisSet-actCoordinator.outactCoordinator.oeGetCrisisSet

The *testcase01-ts11oeGetCrisisSet-actCoordinator.outactCoordinator.oeGetCrisisSet* has the following properties:

TEST STEP	
<i>ts11oeGetCrisisSet</i>	
cf. actor documentation	
<i>Test Sent Message</i>	
TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actCoordinator.outactCoordinator.oeGetCrisisSet (AetCrisisStatus)</p>
<i>Variables</i>	
V 1	TheActor:icrash.environment.actCoordinator cf. actor documentation
V 2	AetCrisisStatus:icrash.concepts.primarytypes.datatypes.etCrisisStatus cf. actor documentation
V 3	ActCrisis:icrash.concepts.primarytypes.classes.ctCrisis cf. actor documentation
<i>Constraints</i>	
C 1	TheActor is the coordinator actor related to a coordinator in the system's state having steve as login value
C 2	AetCrisisStatus value is pending
<i>Oracle Constraints</i>	
OC 1	ActCrisis is any ctCrisis instance that has been sent to TheActor.

The listing 6.11 provides the **Messip** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actCoordinator
4   AetCrisisStatus : etCrisisStatus
5 }
6
7 constraints{
```

```

8   TheActor=TheSystem.rnactCoordinator
9     ->select(a | a.bnctCoordinator.login.value.eq('steve'))
10    ->any2(true)
11  AetCrisisStatus = pending
12 }
13
14 oracle{
15   variables{
16     ActCrisis:ctCrisis
17   }
18   constraints{
19     TheActor.bnactCoordinator.ieSendACrisis(ActCrisis)
20   }
21 }
```

Listing 6.11: **Messir** (MCL-oriented) specification of the test step *testcase01-ts11oeGetCrisisSet*.

6.1.1.12 testcase01-ts12oeSetCrisisHandler-actCoordinator.outactCoordinator.oeSetCrisisHandler

The *testcase01-ts12oeSetCrisisHandler-actCoordinator.outactCoordinator.oeSetCrisisHandler* has the following properties:

TEST STEP	
<i>ts12oeSetCrisisHandler</i> cf. actor documentation	
Test Sent Message	
TSM 1	out:TheActor sends to system actCoordinator.outactCoordinator.oeSetCrisisHandler (AdtCrisisID)
Variables	
V 1	TheActor:icrash.environment.actCoordinator cf. actor documentation
V 2	TheComCompany:icrash.environment.actComCompany cf. actor documentation
V 3	TheCoordinator:icrash.environment.actCoordinator cf. actor documentation
V 4	AdtCrisisID:icrash.concepts.primarytypes.datatypes.dtCrisisID cf. actor documentation
V 5	AMessage:lu.uni.lassy.messir.libraries.primitives.ptString cf. actor documentation
V 6	AdtPhoneNumber:icrash.concepts.primarytypes.datatypes.dtPhoneNumber cf. actor documentation
V 7	AdtSMS:icrash.concepts.secondarytypes.datatypes.dtSMS cf. actor documentation
V 8	ActAlert:icrash.concepts.primarytypes.classes.ctAlert cf. actor documentation
Constraints	
C 1	TheActor is the coordinator actor related to a coordinator in the system's state having steve as login value
C 2	AdtCrisisID as a value of 1

continues in next page ...

... Test Step table continuation

C 3	AMessage is the string 'You are now considered as handling the crisis !'
C 4	AdtPhoneNumber
C 5	AdtSMS has for value the string 'The handling of your alert by our services is in progress !'
Oracle Constraints	
OC 1	there is a communication company actor that received the message ieSmsSend(AdtPhoneNumber,AdtSMS)
OC 2	there is a coordinator actor that received an alert using the message ieSendAnAlert(ActAlert)

The listing 6.12 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actCoordinator
4   AdtCrisisID : dtCrisisID
5 }
6
7 constraints{
8   TheActor=TheSystem.rnactCoordinator
9     ->select(a | a.rnctCoordinator.login.value.eq('steve'))
10    ->any2(true)
11 }
12
13 oracle{
14   variables{
15     AMessage:ptString
16     AdtPhoneNumber:dtPhoneNumber
17     AdtSMS:dtSMS
18     ActAlert:ctAlert
19     TheComCompany: actComCompany
20     TheCoordinator:actCoordinator
21   }
22   constraints{
23     AMessage = 'You are now considered as handling the crisis !'
24     AdtSMS.value = 'The handling of your alert by our services is in progress !'
25     TheComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
26     TheCoordinator.inactCoordinator.ieSendAnAlert(ActAlert)
27     TheActor.inactAuthenticated.ieMessage(AMessage)
28   }
29 }
```

Listing 6.12: **Messir** (MCL-oriented) specification of the test step *testcase01-ts12oeSetCrisisHandler*.

6.1.1.13 testcase01-ts13oeSetClock04-actActivator.outactActivator.oeSetClock

The *testcase01-ts13oeSetClock04-actActivator.outactActivator.oeSetClock* has the following properties:

TEST STEP
<i>ts13oeSetClock04</i>
cf. actor documentation
<i>Test Sent Message</i>

continues in next page ...

... Test Step table continuation

TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actActivator.outactActivator.oeSetClock (ACurrentClock)</p>
<i>Variables</i>	
V 1	TheActor:icrash.environment.actActivator cf. actor documentation
V 2	ACurrentClock:lu.uni.lassy.messir.libraries.calendar.dtDateAndTime cf. actor documentation
<i>Constraints</i>	
C 1	TheActor
C 2	ACurrentClock

The listing 6.13 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor:actActivator
4   ACurrentClock:dtDateAndTime
5 }
6
7 constraints{
8   TheActor=TheSystem.rnactActivator->any2(true)
9   ACurrentClock.date.year.value = 2017
10  ACurrentClock.date.month.value = 11
11  ACurrentClock.date.day.value = 26
12  ACurrentClock.time.hour.value = 10
13  ACurrentClock.time.minute.value = 45
14  ACurrentClock.time.second.value = 00
15 }
16
17 oracle{
18   constraints{
19     true
20   }
21 }
```

Listing 6.13: **Messir** (MCL-oriented) specification of the test step *testcase01-ts13oeSetClock04*.

6.1.1.14 testcase01-ts14oeValidateAlert-actCoordinator.outactCoordinator.oeValidateAlert

The *testcase01-ts14oeValidateAlert-actCoordinator.outactCoordinator.oeValidateAlert* has the following properties:

TEST STEP
<i>ts14oeValidateAlert</i> cf. actor documentation
<i>Test Sent Message</i>

continues in next page ...

... Test Step table continuation

TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actCoordinator.outactCoordinator.oeValidateAlert (AdtAlertID)</p>
Variables	
V 1	TheActor:icrash.environment.actCoordinator cf. actor documentation
V 2	AdtAlertID:icrash.concepts.primarytypes.datatypes.dtAlertID cf. actor documentation
V 3	AMessage:lu.uni.lassy.messir.libraries.primitives.ptString cf. actor documentation
Constraints	
C 1	TheActor is the coordinator actor related to a coordinator in the system's state having steve as login value
C 2	AdtAlertID
C 3	AMessage
Oracle Constraints	
OC 1	

The listing 6.14 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actCoordinator
4   AdtAlertID : dtAlertID
5 }
6
7 constraints{
8   TheActor=TheSystem.rnactCoordinator
9     ->select(a | a.rnctCoordinator.login.value.eq('steve'))
10    ->any2(true)
11 }
12
13 oracle{
14   variables{
15     AMessage:ptString
16   }
17   constraints{
18     AMessage = 'The Alert is now declared as valid !'
19     TheActor.actAuthenticated.inactAuthenticated.ieMessage(AMessage)
20   }
21 }
```

Listing 6.14: **Messir** (MCL-oriented) specification of the test step *testcase01-ts14oeValidateAlert*.

6.1.1.15 testcase01-ts15oeAlert2-actComCompany.outactComCompany.oeAlert

The `testcase01-ts15oeAlert2-actComCompany.outactComCompany.oeAlert` has the following properties:

TEST STEP	
<i>ts15oeAlert2</i> cf. actor documentation	
Test Sent Message	
TSM 1	<p>out:TheActor sends to system</p> <p>actComCompany.outactComCompany.oeAlert (AetHumanKind, AdtDate, AdtTime, AdtPhoneNumber, AdtGPSLocation, AdtComment)</p>
Variables	
V 1	TheActor:icrash.environment.actComCompany cf. actor documentation
V 2	AetHumanKind:icrash.concepts.primarytypes.datatypes.etHumanKind cf. actor documentation
V 3	AdtDate:lu.uni.lassy.messir.libraries.calendar.dtDate cf. actor documentation
V 4	AdtTime:lu.uni.lassy.messir.libraries.calendar.dtTime cf. actor documentation
V 5	AdtPhoneNumber:icrash.concepts.primarytypes.datatypes.dtPhoneNumber cf. actor documentation
V 6	AdtGPSLocation:icrash.concepts.primarytypes.datatypes.dtGPSLocation cf. actor documentation
V 7	AdtComment:icrash.concepts.primarytypes.datatypes.dtComment cf. actor documentation
V 8	AdtSMS:icrash.concepts.secondarytypes.datatypes.dtSMS cf. actor documentation
Constraints	
C 1	TheActor
C 2	AetHumanKind
C 3	AdtDate
C 4	AdtTime
C 5	AdtPhoneNumber
C 6	AdtGPSLocation
C 7	AdtComment
C 8	AdtSMS
Oracle Constraints	
OC 1	

The listing 6.15 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actComCompany
4   AetHumanKind:etHumanKind
5   AdtDate:dtDate
6   AdtTime:dtTime

```

```

7  AdtPhoneNumber:dtPhoneNumber
8  AdtGPSLocation:dtGPSLocation
9  AdtComment:dtComment
10 }
11
12 constraints{
13  TheActor = TheSystem.rnactComCompany->any2(true)
14  AetHumanKind = witness
15  AdtDate.year.value = 2017
16  AdtDate.month.value = 11
17  AdtDate.day.value = 26
18  AdtTime.hour.value = 10
19  AdtTime.minute.value = 20
20  AdtTime.second.value = 00
21  AdtPhoneNumber.value = '+3524666445000'
22  AdtGPSLocation.latitude.value = 49.627095
23  AdtGPSLocation.longitude.value = 6.160251
24  AdtComment.value = 'A car crash just happened.'
25 }
26
27 oracle{
28  variables{
29   AdtSMS:dtSMS
30  }
31  constraints{
32   AdtSMS.value = 'Your alert has been registered. We will handle it and keep you informed'
33   TheActor.actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber, AdtSMS)
34  }
35 }

```

Listing 6.15: **Messir** (MCL-oriented) specification of the test step *testcase01-ts15oeAlert2*.

6.1.1.16 testcase01-ts16oeSetClock05-actActivator.outactActivator.oeSetClock

The *testcase01-ts16oeSetClock05-actActivator.outactActivator.oeSetClock* has the following properties:

TEST STEP	
<i>ts16oeSetClock05</i>	
cf. actor documentation	
<i>Test Sent Message</i>	
TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actActivator.outactActivator.oeSetClock (ACurrentClock)</p>
<i>Variables</i>	
V 1	TheActor:icrash.environment.actActivator cf. actor documentation
V 2	ACurrentClock:lu.uni.lassy.messir.libraries.calendar.dtDateAndTime cf. actor documentation
<i>Constraints</i>	
C 1	TheActor
C 2	ACurrentClock

The listing 6.16 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor:actActivator
4   ACurrentClock:dtDateAndTime
5 }
6
7 constraints{
8   TheActor=TheSystem.rnactActivator->any2(true)
9   ACurrentClock.date.year.value = 2017
10  ACurrentClock.date.month.value = 11
11  ACurrentClock.date.day.value = 26
12  ACurrentClock.time.hour.value = 12
13  ACurrentClock.time.minute.value = 45
14  ACurrentClock.time.second.value = 00
15 }
16
17 oracle{
18   constraints{
19     true
20   }
21 }
```

Listing 6.16: **Messir** (MCL-oriented) specification of the test step *testcase01-ts16oeSetClock05*.

6.1.1.17 testcase01-ts17oeSetCrisisStatus-actCoordinator.outactCoordinator.oeSetCrisisStatus

The *testcase01-ts17oeSetCrisisStatus-actCoordinator.outactCoordinator.oeSetCrisisStatus* has the following properties:

TEST STEP	
<i>ts17oeSetCrisisStatus</i>	
cf. actor documentation	
<i>Test Sent Message</i>	
TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actCoordinator.outactCoordinator.oeSetCrisisStatus (AdtCrisisID, AetCrisisStatus)</p>
<i>Variables</i>	
V 1	TheActor:icrash.environment.actCoordinator cf. actor documentation
V 2	AdtCrisisID:icrash.concepts.primarytypes.datatypes.dtCrisisID cf. actor documentation
V 3	AetCrisisStatus:icrash.concepts.primarytypes.datatypes.etCrisisStatus cf. actor documentation
V 4	AMessage:lu.uni.lassy.messir.libraries.primitives.ptString cf. actor documentation
<i>Constraints</i>	
C 1	TheActor is the coordinator actor related to a coordinator in the system's state having steve as login value
C 2	AdtCrisisID

continues in next page ...

... Test Step table continuation

C 3	AetCrisisStatus
C 4	AMessage
Oracle Constraints	
OC 1	

The listing 6.17 provides the **Messip** (MCL-oriented) specification of the test step.

```

1  variables{
2    TheActor : actCoordinator
3    AdtCrisisID : dtCrisisID
4    AetCrisisStatus : etCrisisStatus
5  }
6
7
8  constraints{
9    TheActor=TheSystem.rnactCoordinator
10   ->select(a | a.rnctCoordinator.login.value.eq('steve'))
11   ->any2(true)
12 }
13
14 oracle{
15   variables{
16     AMessage:ptString
17   }
18   constraints{
19     AMessage = 'The crisis status has been updated !'
20     TheActor.inactAuthenticated.ieMessage(AMessage)
21   }
22 }
```

Listing 6.17: **Messip** (MCL-oriented) specification of the test step *testcase01-ts17oeSetCrisisStatus*.

6.1.1.18 testcase01-ts18oeReportOnCrisis-actCoordinator.outactCoordinator.oeReportOnCrisis

The *testcase01-ts18oeReportOnCrisis-actCoordinator.outactCoordinator.oeReportOnCrisis* has the following properties:

TEST STEP	
<i>ts18oeReportOnCrisis</i>	
cf. actor documentation	
<i>Test Sent Message</i>	
TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actCoordinator.outactCoordinator.oeReportOnCrisis (AdtCrisisID, AdtComment)</p>
<i>Variables</i>	
V 1	TheActor:icrash.environment.actCoordinator cf. actor documentation
V 2	AdtCrisisID:icrash.concepts.primarytypes.datatypes.dtCrisisID <i>continues in next page ...</i>

... Test Step table continuation

V 3	cf. actor documentation AdtComment:icrash.concepts.primarytypes.datatypes.dtComment
V 4	cf. actor documentation AMessage:lu.uni.lassy.messir.libraries.primitives.ptString cf. actor documentation
Constraints	
C 1	TheActor is the coordinator actor related to a coordinator in the system's state having steve as login value
C 2	AdtCrisisID
C 3	AdtComment
C 4	AMessage
Oracle Constraints	
OC 1	

The listing 6.18 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actCoordinator
4   AdtCrisisID : dtCrisisID
5   AdtComment : dtComment
6 }
7
8 constraints{
9   TheActor=TheSystem.rnactCoordinator
10   ->select(a | a.rnctCoordinator.login.value.eq('steve'))
11   ->any2(true)
12 }
13
14 oracle{
15   variables{
16     AMessage:ptString
17   }
18   constraints{
19     AMessage = 'The crisis comment has been updated !'
20     TheActor.inactAuthenticated.ieMessage(AMessage)
21   }
22 }
```

Listing 6.18: **Messir** (MCL-oriented) specification of the test step *testcase01-ts18oeReportOnCrisis*.

6.1.1.19 testcase01-ts19oeCloseCrisis-actCoordinator.outactCoordinator.oeCloseCrisis

The *testcase01-ts19oeCloseCrisis-actCoordinator.outactCoordinator.oeCloseCrisis* has the following properties:

TEST STEP
<i>ts19oeCloseCrisis</i>
cf. actor documentation
<i>Test Sent Message</i>

continues in next page ...

... Test Step table continuation

TSM 1	<p>out:TheActor</p> <p>sends to system</p> <p>actCoordinator.outactCoordinator.oeCloseCrisis (AdtCrisisID)</p>
Variables	
V 1	TheActor: icrash.environment.actCoordinator cf. actor documentation
V 2	AdtCrisisID: icrash.concepts.primarytypes.datatypes.dtCrisisID cf. actor documentation
V 3	AMessage: lu.uni.lassy.messir.libraries.primitives.ptString cf. actor documentation
Constraints	
C 1	TheActor is the coordinator actor related to a coordinator in the system's state having steve as login value
C 2	AdtCrisisID
C 3	AMessage
Oracle Constraints	
OC 1	

The listing 6.19 provides the **Messir** (MCL-oriented) specification of the test step.

```

1
2 variables{
3   TheActor : actCoordinator
4   AdtCrisisID : dtCrisisID
5 }
6
7 constraints{
8   TheActor=TheSystem.rnactCoordinator
9     ->select(a | a.rnctCoordinator.login.value.eq('steve'))
10    ->any2(true)
11 }
12
13 oracle{
14   variables{
15     AMessage:ptString
16   }
17   constraints{
18     AMessage = 'The crisis is now closed !'
19     TheActor.inactAuthenticated.ieMessage(AMessage)
20   }
21 }
```

Listing 6.19: **Messir** (MCL-oriented) specification of the test step *testcase01-ts19oeCloseCrisis*.

6.1.2 Test Case Instance - instance01

6.1.3 Test Case Instance - instance01Part01

Figure 6.1 Sequence diagram representing the first part of a simple and complete testcase instance for *iCrash*.




Figure 6.1: tci-testcase01-instance01-Part01 testcase instance sequence diagram

6.1.4 Test Case Instance - instance01Part02

Figure 6.2 Sequence diagram representing the second part of a simple and complete testcase instance for *iCrash*.



Figure 6.2: tci-testcase01-instance01-Part02 testcase instance sequence diagram

Chapter 7

Additional Constraints

7.1 Quality Constraints

Description of all the constraints that concern the required quality criteria according to their ISO definition [?].

7.1.1 Functional suitability

Constraints on the degree to which the product provides functions that meet stated and implied needs when the product is used under specified conditions.

7.1.1.1 Functional completeness

List of requirements on the degree to which the set of functions covers all the specified tasks and user objectives.

1. (to be filled)

7.1.1.2 Functional correctness

List of requirements on the degree to which the set of functions covers all the specified tasks and user objectives.

1. (to be filled)

7.1.1.3 Functional appropriateness

List of requirements on the degree to which the functions facilitate the accomplishment of specified tasks and objectives.

1. (to be filled)

7.1.2 Performance efficiency

Constraints on the performance relative to the amount of resources used under stated conditions

7.1.2.1 Time behaviour

List of requirements on the degree to which the response and processing times and throughput rates of a product or system, when performing its functions, meet requirements.

1. (to be filled)

7.1.2.2 Resource utilization

List of requirements on the degree to which the amounts and types of resources used by a product or system, when performing its functions, meet requirements.

1. (to be filled)

7.1.2.3 Capacity

List of requirements on the degree to which the maximum limits of a product or system parameter meet requirements.

1. (to be filled)

7.1.3 Compatibility

Constraints on the degree to which a product, system or component can exchange information with other products, systems or components, and/or perform its required functions, while sharing the same hardware or software environment.

7.1.3.1 Co-existence

List of requirements on the degree to which a product can perform its required functions efficiently while sharing a common environment and resources with other products, without detrimental impact on any other product.

1. (to be filled)

7.1.3.2 Interoperability

List of requirements on the degree to which two or more systems, products or components can exchange information and use the information that has been exchanged.

1. (to be filled)

7.1.4 Usability

Constraints on the usability degree to which a product or system can be used by specified users to achieve specified goals with effectiveness, efficiency and satisfaction in a specified context of use.

7.1.4.1 Appropriateness recognizability

List of requirements on the degree to which users can recognize whether a product or system is appropriate for their needs.

1. (to be filled)

7.1.4.2 Learnability

List of requirements on the degree to which a product or system can be used by specified users to achieve specified goals of learning to use the product or system with effectiveness, efficiency, freedom from risk and satisfaction in a specified context of use.

1. (to be filled)

7.1.4.3 Operability

List of requirements on the degree to which a product or system has attributes that make it easy to operate and control.

1. (to be filled)

7.1.4.4 User error protection

List of requirements on the degree to which a system protects users against making errors.

1. (to be filled)

7.1.4.5 User interface aesthetics

List of requirements on the degree to which a user interface enables pleasing and satisfying interaction for the user.

1. (to be filled)

7.1.4.6 Accessibility

List of requirements on the degree to which a product or system can be used by people with the widest range of characteristics and capabilities to achieve a specified goal in a specified context of use.

1. (to be filled)

7.1.5 Reliability

Constraints on the degree to which a system, product or component performs specified functions under specified conditions for a specified period of time.

7.1.5.1 Maturity

List of requirements on the degree to which a system, product or component meets needs for reliability under normal operation.

1. (to be filled)

7.1.5.2 Availability

List of requirements on the degree to which a system, product or component is operational and accessible when required for use.

1. (to be filled)

7.1.5.3 Fault tolerance

List of requirements on the degree to which a system, product or component operates as intended despite the presence of hardware or software faults.

1. (to be filled)

7.1.5.4 Recoverability

List of requirements on the degree to which, in the event of an interruption or a failure, a product or system can recover the data directly affected and re-establish the desired state of the system.

1. (to be filled)

7.1.6 Security

Constraints on the degree to which a product or system protects information and data so that persons or other products or systems have the degree of data access appropriate to their types and levels of authorization.

7.1.6.1 Confidentiality

List of requirements on the degree to which a product or system ensures that data are accessible only to those authorized to have access.

1. (to be filled)

7.1.6.2 Integrity

List of requirements on the degree to which a system, product or component prevents unauthorized access to, or modification of, computer programs or data.

1. (to be filled)

7.1.6.3 Non-repudiation

List of requirements on the degree to which actions or events can be proven to have taken place, so that the events or actions cannot be repudiated later.

1. (to be filled)

7.1.6.4 Accountability

List of requirements on the degree to which the actions of an entity can be traced uniquely to the entity.

1. (to be filled)

7.1.6.5 Authenticity

List of requirements on the degree to which the identity of a subject or resource can be proved to be the one claimed.

1. (to be filled)

7.1.7 Maintainability

Constraints on the degree of effectiveness and efficiency with which a product or system can be modified by the intended maintainers.

7.1.7.1 Modularity

List of requirements on the degree to which a system or computer program is composed of discrete components such that a change to one component has minimal impact on other components.

1. (to be filled)

7.1.7.2 Reusability

List of requirements on the degree to which an asset can be used in more than one system, or in building other assets.

1. (to be filled)

7.1.7.3 Analysability

List of requirements on the degree of effectiveness and efficiency with which it is possible to assess the impact on a product or system of an intended change to one or more of its parts, or to diagnose a product for deficiencies or causes of failures, or to identify parts to be modified.

1. (to be filled)

7.1.7.4 Modifiability

List of requirements on the degree to which a product or system can be effectively and efficiently modified without introducing defects or degrading existing product quality.

1. (to be filled)

7.1.7.5 Testability

List of requirements on the degree of effectiveness and efficiency with which test criteria can be established for a system, product or component and tests can be performed to determine whether those criteria have been met.

1. (to be filled)

7.1.8 Portability

Constraints on the degree of effectiveness and efficiency with which a system, product or component can be transferred from one hardware, software or other operational or usage environment to another.

7.1.8.1 Adaptability

List of requirements on the degree to which a product or system can effectively and efficiently be adapted for different or evolving hardware, software or other operational or usage environments.

1. (to be filled)

7.1.8.2 Installability

List of requirements on the degree of effectiveness and efficiency with which a product or system can be successfully installed and/or uninstalled in a specified environment.

1. (to be filled)

7.1.8.3 Replaceability

List of requirements on the degree to which a product can replace another specified software product for the same purpose in the same environment.

1. (to be filled)

7.2 Other Constraints

Any other unclassified constraints judged as required for the product under development.

Appendix A

Undocumented Messir Specification Elements

A.1 Undocumented Use Cases

A.1.1 Undocumented User-Goal Level Use Cases

- icrash.usecases.ugVictimSendFamilyNotification.ugVictimSendFamilyNotification
- icrash.usecases.ugWitnessSendFamilyNotification.ugWitnessSendFamilyNotification

A.1.2 Undocumented Subfunction Level Use Cases

- icrash.usecases.subfunctions.oeChooseInformation
- icrash.usecases.subfunctions.oeCreateAlert
- icrash.usecases.subfunctions.oeCreateCrisis
- icrash.usecases.subfunctions.oeSendNotification
- icrash.usecases.subfunctions.oeUpdateCrisis
- icrash.usecases.subfunctions.ugSercurelyUserSystem

A.1.3 Undocumented Use Case Views

- uc-ugVictimSendFamilyNotification

A.2 Undocumented Use Case Instances

A.2.1 Undocumented User-Goal Level Use Case Instances

- usecases.uciugSecurelyUseSystem.uciugSecurelyUseSystem

A.2.2 Undocumented Use Case Instance Views

- uci-uciugSecurelyUseSystem

A.3 Undocumented Actors

- icrash.environment.actDatabase
- icrash.environment.actSystem

A.4 Undocumented Environment Model Views

- em-view10
- em-view12

A.5 Undocumented Primary Types

A.5.1 Undocumented Primary Classe Types

- icrash.concepts.primarytypes.classes.ctCaptchaService
- icrash.concepts.primarytypes.classes.ctMailingService

A.5.2 Undocumented Primary Datatype Types

- icrash.concepts.primarytypes.authentication.datatypes.dtCaptchaId

A.6 Undocumented Concept Model Views

- cm-pt-dt-lv-02-dtGPSLocation

A.7 Undocumented Operation Specifications

- icrash.concepts.primarytypes.authentication.datatypes.dtCaptcha.is
- icrash.concepts.primarytypes.authentication.datatypes.dtCaptchaImage.is
- icrash.concepts.primarytypes.authentication.datatypes.dtCaptchaResponse.is
- icrash.concepts.primarytypes.authentication.datatypes.dtCaptchaResponseMap.is
- icrash.concepts.primarytypes.authentication.datatypes.dtCaptchaResponseMap.register
- icrash.concepts.primarytypes.authentication.datatypes.dtCaptchaResponseMap.remove
- icrash.environment.actAdministrator.outactAdministrator.ugAdministrateTheSystem
- icrash.environment.actAuthenticated.outactAuthenticated.oeCreateAlert
- icrash.environment.actCoordinator.outactCoordinator.oeCreateAlert
- icrash.environment.actCoordinator.outactCoordinator.oeCreateCrisis
- icrash.environment.actCoordinator.outactCoordinator.oeUpdateCrisis
- icrash.environment.actSystem.outactSystem.oeChooseInformation

- icrash.environment.actSystem.outactSystem.oeSendNotification
- icrash.environment.actSystem.outactSystem.oeSendStatistic
- icrash.environment.actSystem.outactSystem.ugSercurelyUserSystem
- icrash.environment.actSystem.outactSystem.ugVictimSendFamilyNotification
- icrash.environment.actSystem.outactSystem.ugWitnessSendFamilyNotification

A.8 Undocumented Test-Case Instance Specifications

- lu.uni.lassy.excalibur.examples.icrash.tests.testcase01.instance01.instance01
- lu.uni.lassy.excalibur.examples.icrash.tests.testcase01.instance01.instance01Part01
- lu.uni.lassy.excalibur.examples.icrash.tests.testcase01.instance01.instance01Part02

Appendix B

Specification project
`lu.uni.lassy.excalibur.examples.icrash`

B.1 Use Cases Model

This section contains the use cases elicited during the requirements elicitation phase. The use cases are textually described as suggested by the **Messir** method and inspired by the standard Cokburn template [?].

B.1.1 Use Cases

B.1.1.1 subfunction-oeCloseCrisis

the actCoordinator's goal is to declare a crisis as closed.

USE-CASE DESCRIPTION	
Name	oeCloseCrisis
Scope	system
Level	subfunction
<i>Primary actor(s)</i>	
1	actCoordinator[active]
<i>Goal(s) description</i>	
the actCoordinator's goal is to declare a crisis as closed.	
<i>Protocol condition(s)</i>	
1	the iCrash system has been deployed.
<i>Pre-condition(s)</i>	
1	none
<i>Main post-condition(s)</i>	
1	the crisis is known by the system to be closed.
2	a message ieMessage(AMessage) is sent to the actCoordinator to inform him that his crisis is now considered as closed.

Figure B.1 shows the use case diagram for the oeCloseCrisis subfunction use case




Figure B.1: oeCloseCrisis subfunction use case

Appendix C

Messir Specification Files Listing

C.1 File ./src-gen/messir-spec/.views.msr

```
1 //  
2 //DON'T TOUCH THIS FILE !!!  
3 //  
4 package uuid7e0d382938204f3c9036c123484468fb {  
5   Concept Model {}  
6 }
```

Listing C.1: Messir Spec. file .views.msr.

C.2 File ./src-gen/messir-spec/operations/concepts/secondarytypes-datatatypes/dtSMS.msr

```
1 package icrash.operations.concepts.secondarytypes.datatypes.dtSMS{  
2  
3 import lu.uni.lassy.messir.libraries.primitives  
4 import lu.uni.lassy.messir.libraries.calendar  
5 import lu.uni.lassy.messir.libraries.math  
6  
7 import icrash.concepts.primarytypes.datatypes  
8 import icrash.concepts.primarytypes.classes  
9 import icrash.concepts.secondarytypes.datatypes  
10 import icrash.concepts.secondarytypes.classes  
11  
12 Operation Model {  
13 operation: icrash.concepts.secondarytypes.datatypes.dtSMS.is():ptBoolean{  
14   postF{  
15     let TheResult: ptBoolean in  
16     let MaxLength: ptInteger in  
17     ( if  
18       ( MaxLength = 160  
19         and self.value.length().leq(MaxLength)  
20       )  
21     then (TheResult = true)  
22     else (TheResult = false)  
23     endif  
24     result = TheResult  
25   })  
26 prolog{ "src/Operations/Concepts/SecondaryTypesDatatypes/SecondaryTypesDatatypes-dtSMS-is.pl"}  
27 }  
28 }  
29 }
```

Listing C.2: Messir Spec. file dtSMS.msr.

C.3 File ./src-gen/messir-spec/operations/environment/environment-actActivator-oeSetClock.msr

```

1 package icrash.operations.environment.actActivator.oeSetClock {
2
3 import icrash.environment
4
5 import lu.uni.lassy.messir.libraries.primitives
6 import lu.uni.lassy.messir.libraries.calendar
7 import lu.uni.lassy.messir.libraries.math
8
9 import icrash.concepts.primarytypes.datatypes
10 import icrash.concepts.primarytypes.classes
11
12 Operation Model {
13
14 operation: actActivator.outactActivator.oeSetClock(AcurrentClock:dtDateAndTime) :ptBoolean
15 {
16 preP{
17 let TheSystem: ctState in
18 let AvpStarted: ptBoolean in
19
20 /* PreP01 */
21 self.rnActor.rnSystem = TheSystem
22 and self.rnActor.rnSystem.vpStarted = AvpStarted
23 and AvpStarted = true
24 and TheSystem.clock.lt(AcurrentClock)
25 }
26 preF{true}
27
28 postF{
29 let TheSystem: ctState in
30 self.rnActor.rnSystem = TheSystem
31
32 /* PostF01 */
33 and TheSystem@post.clock = AcurrentClock
34 }
35 postP{true}
36
37 prolog{"src/Operations/Environment/OUT/outactActivator-oeSetClock.pl"}
38
39 }
40 }
41 }
```

Listing C.3: Messir Spec. file environment-actActivator-oeSetClock.msr.

C.4 File ./src-gen/messir-spec/operations/environment/environment-actActivator-oeSollicitateCrisisHandling.msr

```

1 package icrash.operations.environment.actActivator.oeSollicitateCrisisHandling {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.concepts.primarytypes.datatypes
9 import icrash.concepts.primarytypes.classes
10 import icrash.environment
11
12 Operation Model {
13
14 operation: actActivator.outactActivator.oeSollicitateCrisisHandling():ptBoolean
15 {
16 preP{
17 let TheSystem: ctState in
```

```

18 let AvpStarted: ptBoolean in
19 let ColctCrisisToHandle:
20     Bag(ctCrisis) in
21
22 self.rnActor.rnSystem = TheSystem
23
24 /* PreP01 */
25 and TheSystem.vpStarted
26
27 /* PreP02 */
28 and TheSystem.rnctCrisis->select(handlingDelayPassed())
29     = ColctCrisisToHandle
30 and ColctCrisisToHandle->size().geq(1)
31 }
32 preF{true}
33
34 postF{
35 let TheSystem: ctState in
36 let AMessageForCrisisHandlers: dtComment in
37 let ColctCrisisToAllocateIfPossible:Bag(ctCrisis) in
38
39 self.rnActor.rnSystem = TheSystem
40 /* PostF01 */
41 and TheSystem.rnctCrisis->select(maxHandlingDelayPassed())
42     = ColctCrisisToAllocateIfPossible
43 and ColctCrisisToAllocateIfPossible->forAll(isAllocatedIfPossible())
44
45 /* PostF02 */
46 and TheSystem.rnctCrisis->select(handlingDelayPassed())
47     = ColctCrisisToHandle
48
49 and ColctCrisisToHandle->msrColSubtract(ColctCrisisToAllocateIfPossible)
50     = ColctCrisisToRemind
51
52 and if (ColctCrisisToRemind->size().geq(1))
53     then (AMessageForCrisisHandlers.value
54         ='There are alerts pending since more than the defined delay. Please REACT !'
55         and TheSystem.rnactAdministrator.
56             rnInterfaceIN^ieMessage(AMessageForCrisisHandlers)
57         and TheSystem.rnactCoordinator
58             ->forAll(rnInterfaceIN^ieMessage(AMessageForCrisisHandlers))
59     )
60 else true
61 endif
62 }
63 postP{
64 let TheSystem: ctState in
65 let TheClock: dtDateAndTime in
66
67 self.rnActor.rnSystem = TheSystem
68 and TheSystem.clock = TheClock
69 and TheSystem@post.vpLastReminder = TheClock
70 }
71
72 prolog{"src/Operations/Environment/OUT/outactActivator-oeSollicitateCrisisHandling.pl"}
73 }
74 }
75 }

```

Listing C.4: Messir Spec. file environment-actActivator-oeSollicitateCrisisHandling.msr.

C.5 File ./src-gen/messir-spec/operations/environment/environment-actAdministrator-oeAddCoordinator.msr

```

1 package icrash.operations.environment.actAdministrator.oeAddCoordinator {
2
3 import lu.uni.lassy.messir.libraries.primitives
4

```

```

5 import icrash.concepts.primarytypes.datatypes
6 import icrash.concepts.primarytypes.classes
7 import icrash.environment
8
9 Operation Model {
10
11 operation: actAdministrator.outactAdministrator.oeAddCoordinator(AdtCoordinatorID:dtCoordinatorID,
12 AdtLogin:dtLogin, AdtPassword:dtPassword):ptBoolean
12 {
13 prep{
14 let TheSystem: ctState in
15 let TheActor:actAdministrator in
16
17 self.rnActor.rnSystem = TheSystem
18 and self.rnActor = TheActor
19
20 /* PreP01 */
21 and TheSystem.vpStarted = true
22 /* PreP02 */
23 and TheActor.rnctAuthenticated.vpIsLogged = true
24 }
25 preF{
26 let TheSystem: ctState in
27 let TheActor:actAdministrator in
28 let ColctCoordinators:Bag(ctCoordinator) in
29
30 self.rnActor.rnSystem = TheSystem
31 and self.rnActor = TheActor
32 /* PreF01 */
33 and TheSystem.rnctCoordinator->select(id.eq(AdtCoordinatorID))
34 = ColctCoordinators
35 and ColctCoordinators->isEmpty() = true
36 }
37 postF{
38 let TheSystem: ctState in
39 let TheactCoordinator:actCoordinator in
40 let ThectCoordinator:ctCoordinator in
41 self.rnActor.rnSystem = TheSystem
42 and self.rnActor = TheActor
43 /* PostF01 */
44 TheactCoordinator.init()
45 /* PostF02 */
46 and ThectCoordinator.init(AdtCoordinatorID,AdtLogin,AdtPassword)
47
48 /* PostF03 */
49 and TheactCoordinator@post.rnctCoordinator = ThectCoordinator
50
51 /* PostF04 */
52 and ThectCoordinator@post.rnactAuthenticated = TheactCoordinator
53
54 /* PostF05 */
55 and TheActor.rnInterfaceIN^ieCoordinatorAdded()
56 }
57 postP{true}
58
59 prolog{"src/Operations/Environment/OUT/outactAdministrator-oeAddCoordinator.pl"}
60 }
61 }
62 }

```

Listing C.5: Messir Spec. file environment-actAdministrator-oeAddCoordinator.msr.

C.6 File ./src-gen/messir-spec/operations/environment/environment-actAdministrator-oeDeleteCoordinator.msr

```

1 package icrash.operations.environment.actAdministrator.oeDeleteCoordinator {
2
3 import lu.uni.lassy.messir.libraries.primitives

```

```

4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.calendar
6
7 import icrash.environment
8
9 import icrash.concepts.primarytypes.datatypes
10 import icrash.concepts.primarytypes.classes
11
12 Operation Model {
13
14 operation: actAdministrator.outactAdministrator.oeDeleteCoordinator(AdtCoordinatorID:dtCoordinatorID
15 ) :ptBoolean
16 {
17 let TheSystem: ctState in
18 let TheActor:actAdministrator in
19
20 self.rnActor.rnSystem = TheSystem
21 and self.rnActor = TheActor
22
23 /* PreP01 */
24 and TheSystem.vpStarted = true
25 /* PreP02 */
26 and TheActor.rnctAuthenticated.vpIsLogged = true
27 }
28 preF{
29 let TheSystem: ctState in
30 let TheActor:actAdministrator in
31
32 self.rnActor.rnSystem = TheSystem
33 and self.rnActor = TheActor
34 /* PreF01 */
35 TheSystem.rnctCoordinator->select(id.eq(AdtCoordinatorID))
36 = ColctCoordinators
37 and ColctCoordinators->size().eq(1)
38 }
39 postF{
40 let TheSystem: ctState in
41 let TheActor:actAdministrator in
42 let ThetcCoordinator:ctCoordinator in
43 self.rnActor.rnSystem = TheSystem
44 and self.rnActor = TheActor
45 /* PostF01 */
46 TheSystem.rnctCoordinator->select(id.eq(AdtCoordinatorID))
47 = ThetcCoordinator
48 and ThetcCoordinator.rnactCoordinator->forAll(msrIsKilled)
49 and ThetcCoordinator.msrIsKilled
50
51 /* PostF02 */
52 and TheActor.rnInterfaceIN^ieCoordinatorDeleted()
53
54 /* Post Protocol:*/
55 /* PostP01 */
56 and true
57 }
58 postP{true}
59
60 prolog{"src/Operations/Environment/OUT/outactAdministrator-oeDeleteCoordinator.pl"}
61 }
62 }
63 }

```

Listing C.6: Messir Spec. file environment-actAdministrator-oeDeleteCoordinator.msr.

C.7 File ./src-gen/messir-spec/operations/environment/environment-actAuthenticated-oeSubmitCaptcha.msr

```

1 package icrash.environment.operations.actAuthenticated.outactAuthenticated.oeSubmitCaptcha {

```

```

2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.environment
9 import icrash.concepts.primarytypes.datatypes
10 import icrash.concepts.primarytypes.classes
11 import icrash.concepts.primarytypes.authentication.datatypes
12 import icrash.environment.authentication
13
14 Operation Model {
15
16   operation: icrash.environment.actAuthenticated.outactAuthenticated.oeSubmitCaptcha(AdtResponse:
17     dtCaptchaResponse):ptBoolean{
18     preP{
19       let TheSystem: ctState in
20       let TheActor:actAuthenticated in
21       self.rnActor.rnSystem = TheSystem
22       and self.rnActor = TheActor
23
24       /* PreP01 */
25       and TheSystem.vpStarted = true
26       /* Prep02 */
27       and TheActor.rnctAuthenticated.vpIsLogged = false
28       /* Prep03 */
29       and TheActor.rnctAuthenticated.awaitedCaptchaId.is() = true
30     }
31     preF{
32       true
33     }
34     postF{
35       let TheSystem: ctState in
36       let TheactAuthenticated:actAuthenticated in
37       let TheactValidator:actCaptchaService in
38
39       self.rnActor.rnSystem = TheSystem
40       and self.rnActor = TheactAuthenticated
41
42       /* PostF01 */
43       and TheactValidator.rnInterfaceIN^ieVerifyCaptcha(AdtResponse)
44     }
45     postP{
46       let TheSystem: ctState in
47       let TheactAuthenticated:actAuthenticated in
48
49       self.rnActor.rnSystem = TheSystem
50       and self.rnActor = TheactAuthenticated
51
52       /* PostF01 */
53       and TheactAuthenticated.rnctAuthenticated.awaitedCaptchaId.is() = false
54     }
55     /*prolog{
56       "src/Operations/Environment/OUT/outactAuthenticated-oeSubmitCaptcha.pl"
57     }*/
58   }
59 }
60 }
```

Listing C.7: Messir Spec. file environment-actAuthenticated-oeSubmitCaptcha.msr.

C.8 File ./src-gen/messir-spec/operations/environment/environment-actAuthenticated.msr

```

1 package icrash.operations.environment.actAuthenticated{
2
```

```

3 import lu.uni.lassy.messir.libraries.primitives
4
5 import icrash.concepts.primarytypes.datatypes
6 import icrash.concepts.primarytypes.classes
7 import icrash.concepts.secondarytypes.datatypes
8 import icrash.concepts.secondarytypes.classes
9 import icrash.environment
10
11 Operation Model {
12
13 operation: actAuthenticated.outactAuthenticated.oeLogin(AdtLogin:dtLogin, AdtPassword:dtPassword) :
14   ptBoolean
15 {
16   let TheSystem: ctState in
17   let TheActor:actAuthenticated in
18   self.rnActor.rnSystem = TheSystem
19   and self.rnActor = TheActor
20
21 /* PreP01 */
22 and TheSystem.vpStarted = true
23 /* PreP02 */
24 and TheActor.rnctAuthenticated.vpIsLogged = false
25 }
26 preF{
27 /* PreF01 */
28 true
29 }
30 postF{
31 let TheSystem: ctState in
32 let TheactAuthenticated:actAuthenticated in
33
34 let AptStringMessageForTheactAuthenticated: ptString in
35 let AptStringMessageForTheactAdministrator:ptString in
36
37 self.rnActor.rnSystem = TheSystem
38 and self.rnActor = TheactAuthenticated
39
40 and /* PostF01 */
41 if (TheactAuthenticated.rnctAuthenticated.pwd
42     = AdtPassword
43     and TheactAuthenticated.rnctAuthenticated.login
44     = AdtLogin
45     )
46 then (AptStringMessageForTheactAuthenticated.eq('You are logged ! Welcome ...')
47       and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactAuthenticated)
48     )
49 else (AptStringMessageForTheactAuthenticated
50       .eq('Wrong identification information ! Please try again ...')
51       and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactAuthenticated)
52       and AptStringMessageForTheactAdministrator.eq('Intrusion tentative !')
53       and TheSystem.rnactAdministrator
54       .rnInterfaceIN^ieMessage(AptStringMessageForTheactAdministrator)
55     )
56 endif
57 }
58 postP{
59 let TheSystem: ctState in
60 let TheactAuthenticated:actAuthenticated in
61
62 self.rnActor.rnSystem = TheSystem
63 and self.rnActor = TheactAuthenticated
64 /* PostP01 */
65 if (TheactAuthenticated.rnctAuthenticated.pwd = AdtPassword
66     and TheactAuthenticated.rnctAuthenticated.login = AdtLogin
67     )
68 then (TheactAuthenticated.rnctAuthenticated@post.vpIsLogged = true)
69 else true
70 endif
71 }

```

```

72 prolog{"src/Operations/Environment/OUT/outactAuthenticated-oeLogin.pl"}
73 }
74 /*-----*/
75
76 operation: actAuthenticated.outactAuthenticated.oeLogout():ptBoolean{
77
78 preP{
79   let TheSystem: ctState in
80   let TheActor:actAdministrator in
81   self.rnActor.rnSystem = TheSystem
82   and self.rnActor = TheActor
83
84 /* PreP01 */
85 and TheSystem.vpStarted = true
86 /* PreP02 */
87 and TheActor.rnctAuthenticated.vpIsLogged = true
88 }
89 preF{
90 /* PreF01 */
91 true
92 }
93 postF{
94   let TheSystem: ctState in
95   let TheactAuthenticated:actAuthenticated in
96   let AptStringMessageForTheactAuthenticated: ptString in
97
98   self.rnActor.rnSystem = TheSystem
99   and self.rnActor = TheactAuthenticated
100
101 /* PostF01 */
102 AptStringMessageForTheactAuthenticated.eq('You are logged out ! Good Bye ...')
103 and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactAuthenticated)
104 }
105 postP{
106   let TheSystem: ctState in
107   let TheactAuthenticated:actAuthenticated in
108
109   self.rnActor.rnSystem = TheSystem
110   and self.rnActor = TheactAuthenticated.asSet
111 /* PostP01 */
112 TheactAuthenticated.rnctAuthenticated@post.vpIsLogged = false
113 }
114 prolog{"src/Operations/Environment/OUT/outactAuthenticated-oeLogout.pl"}
115 }
116 }
117 }
```

Listing C.8: Messir Spec. file environment-actAuthenticated.msr.

C.9 File ./src-gen/messir-spec/operations/environment/environment-actCaptchaGenerator-oeSendCaptcha.msr

```

1 package icrash.environment.operations.actCaptchaGenerator.outactCaptchaGenerator.oeSendCaptcha {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.environment
9 import icrash.concepts.primarytypes.datatypes
10 import icrash.concepts.primarytypes.classes
11 import icrash.concepts.primarytypes.authentication.datatypes
12 import icrash.environment.authentication
13
14 Operation Model {
15
16   operation: icrash.environment.authentication.actCaptchaService.outactCaptchaService.oeSendCaptcha(
      AdtCaptcha:dtCaptcha, AdtResponse:dtCaptchaResponse):ptBoolean{
```

```

17 preP{
18   let TheSystem: ctState in
19   self.rnActor.rnSystem = TheSystem
20
21   /* PreP01 */
22   and TheSystem.vpStarted = true
23 }
24 preF{
25   true
26 }
27 postF{
28   let TheSystem: ctState in
29   let TheactGenerator:actCaptchaService in
30   let TheactAuthenticated:actAuthenticated in
31
32   self.rnActor.rnSystem = TheSystem
33   and self.rnActor = TheactGenerator
34
35   /* PostF01 */
36   and TheactValidator.bnInterfaceIN^ieRegisterAnswer(AdtResponse)
37   /* PostF02 */
38   and TheactAuthenticated.bnInterfaceIN^ieConfirmCaptcha(AdtCaptcha)
39 }
40 postP{
41   true//TODO: Is this correct?
42 }
43 }
44 }
45 }
```

Listing C.9: Messir Spec. file environment-actCaptchaGenerator-oeSendCaptcha.msr.

C.10 File ./src-gen/messir-spec/operations/environment/environment-actCaptchaValidator-oeCaptchaInvalid.msr

```

1 package icrash.environment.operations.actCaptchaValidator.outactCaptchaValidator.oeCaptchaInvalid {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.environment
9 import icrash.concepts.primarytypes.datatypes
10 import icrash.concepts.primarytypes.classes
11 import icrash.environment.authentication
12
13 Operation Model {
14
15   operation: icrash.environment.authentication.actCaptchaService.outactCaptchaService.
16     oeCaptchaInvalid(AdtCaptchaId:ptInteger):ptBoolean{
17   preP{
18     let TheSystem: ctState in
19     let TheactValidator:actCaptchaService in
20     self.rnActor.rnSystem = TheSystem
21
22     /* PreP01 */
23     and TheSystem.vpStarted = true
24     /* PreP02 */
25     and TheactValidator.bnactCaptchaValidator.map.get(AdtCaptchaId).is() = true
26   }
27   preF{
28     true
29 }
30   postF{
31     let TheSystem: ctState in
32     let TheactValidator:actCaptchaService in
33     let TheactAuthenticated:actAuthenticated in
```

```

33
34     let AptStringMessageForTheactValidator: ptString in
35
36     self.rnActor.rnSystem = TheSystem
37     and self.rnActor = TheactValidator
38
39     /* PostF01 */
40     and AptStringMessageForTheactValidator.eq('Your submitted captcha response is invalid. Try again
        .')
41     and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactValidator)
42   }
43 postP{
44     let TheSystem: ctState in
45     let TheactValidator:actCaptchaService in
46
47     self.rnActor.rnSystem = TheSystem
48     and self.rnActor = TheactValidator
49
50     /* PostP01 */
51     and TheactValidator.rnactCaptchaValidator.map.remove(AdtCaptchaId)
52   }
53 }
54 }
55 }
```

Listing C.10: Messir Spec. file environment-actCaptchaValidator-oeCaptchaInvalid.msr.

C.11 File ./src-gen/messir-spec/operations/environment/environment-actCaptchaValidator-oeCaptchaValid.msr

```

1 package icrash.environment.operations.actCaptchaValidator.outactCaptchaValidator.oeCaptchaValid {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.environment
9 import icrash.concepts.primarytypes.datatypes
10 import icrash.concepts.primarytypes.classes
11 import icrash.environment.authentication
12
13 Operation Model {
14
15   operation: icrash.environment.authentication.actCaptchaService.outactCaptchaService.oeCaptchaValid
        (AdtCaptchaId:ptInteger):ptBoolean{
16     prep{
17       let TheSystem: ctState in
18       let TheactValidator:actCaptchaService in
19       self.rnActor.rnSystem = TheSystem
20
21       /* Prep01 */
22       and TheSystem.vpStarted = true
23       /* Prep02 */
24       and TheactValidator.rnactCaptchaValidator.map.get(AdtCaptchaId).is() = true
25     }
26     preF{
27       true
28     }
29   postF{
30     let TheSystem: ctState in
31     let TheactValidator:actCaptchaService in
32     let TheactAuthenticated:actAuthenticated in
33
34     let AptStringMessageForTheactValidator: ptString in
35
36     self.rnActor.rnSystem = TheSystem
37     and self.rnActor = TheactValidator
38   }
```

```

38
39     /* PostF01 */
40     and AptStringMessageForTheactValidator.eq('You are now logged in!')
41     and TheactAuthenticated.rnInterfaceIN^ieMessage(AptStringMessageForTheactValidator)
42 }
43 postP{
44     let TheSystem: ctState in
45     let TheactValidator:actCaptchaService in
46
47     self.rnActor.rnSystem = TheSystem
48     and self.rnActor = TheactValidator
49
50     /* PostP01 */
51     and TheactValidator.rnactCaptchaValidator.map.remove(AdtCaptchaId)
52 }
53 }
54 }
55 }
```

Listing C.11: Messir Spec. file environment-actCaptchaValidator-oeCaptchaValid.msr.

C.12 File ./src-gen/messir-spec/operations/environment/environment-actComCompany.msr

```

1 // Do not add/remove lines because code is inserted in slides
2
3 package icrash.operations.environment.actComCompany{
4
5 import lu.uni.lassy.messir.libraries.primitives
6 import lu.uni.lassy.messir.libraries.calendar
7 import lu.uni.lassy.messir.libraries.math
8
9 import icrash.concepts.primarytypes.datatypes
10 import icrash.concepts.primarytypes.classes
11 import icrash.concepts.secondarytypes.datatypes
12
13 import icrash.environment
14
15 Operation Model {
16
17 operation: actComCompany.outactComCompany.oeAlert(
18     AetKind:etHumanKind,
19     AdtMyDate:dtDate,
20     AdtTime:dtTime,
21     AdtPhoneNumber:dtPhoneNumber,
22     AdtGPSLocation:dtGPSLocation,
23     AdtComment:dtComment
24 ) :ptBoolean{
25
26 preP{
27     let TheSystem: ctState in
28     self.rnActor.rnSystem = TheSystem
29
30     /* PreP01 */
31     and TheSystem.vpStarted = true
32 }
33 preF{
34     let TheSystem: ctState in
35     self.rnActor.rnSystem = TheSystem
36
37     /* PreF01 */
38     and (TheSystem.clock.date.gt(AdtDate)
39         or (TheSystem.clock.date.eq(AdtDate)
40             and TheSystem.clock.time.gt(AdtTime)
41             )
42         )
43 }
44 postF{
```

```

45 let TheSystem: ctState in
46
47 let ActHuman:ctHuman in
48 let TheactComCompany:actComCompany in
49 let ActAlert:ctAlert in
50 let AAAlertInstant:dtDateAndTime in
51 let AetAlertStatus:etAlertStatus in
52 let ActAlertNearBy:ctAlert in
53 let ActCrisis:ctCrisis in
54 let AdtCrisisID:dtCrisisID in
55 let AetCrisisType:etCrisisType in
56 let AetCrisisStatus:etCrisisStatus in
57 let ACrisisInstant:dtDateAndTime in
58 let ACrisisdtComment:dtComment in
59 let AptStringMessage:ptString in
60 let AdtSMS:dtSMS in
61 let AdtAlertID:dtAlertID in
62
63 self.rnActor.rnSystem = TheSystem
64 and self.rnActor = TheactComCompany
65 /* PostF01 */
66 TheSystem.nextValueForAlertID=PrenextValueForAlertID
67 and PrenextValueForAlertID.add(1) = PostnextValueForAlertID
68 and TheSystem@post.nextValueForAlertID = PostnextValueForAlertID
69
70 /* PostF02 */
71 and AAAlertInstant.date=AdtDate
72 and AAAlertInstant.time=AdtTime
73
74 and AetAlertStatus=pending
75
76 and TheSystem.nextValueForAlertID.todtString().eq(AdtAlertID)
77
78 and ActAlert.init(AdtAlertID,
79             AetAlertStatus,
80             AdtGPSLocation,
81             AAAlertInstant,
82             AdtComment)
83
84 /* PostF03 */
85 and TheSystem.rnctAlert.select(location.isNearTo(AdtGPSLocation)) = ColctAlertsNearBy
86 and if (ColctAlertsNearBy->size()=0)
87 then (TheSystem.nextValueForCrisisID = PrenextValueForCrisisID
88 and PrenextValueForCrisisID.add(1) = PostnextValueForCrisisID
89 and TheSystem@post.nextValueForCrisisID = PostnextValueForCrisisID
90 and TheSystem.nextValueForCrisisID.todtString().eq(AdtCrisisID)
91 and AdtCrisisType = small
92 and AetCrisisStatus = pending
93 and ACrisisInstant= AAAlertInstant
94 and ACrisisdtComment = 'no reporting yet defined'
95 and ActCrisis.init( AdtCrisisID,
96             AdtCrisisType,
97             AetCrisisStatus,
98             AdtGPSLocation,
99             ACrisisInstant,
100            ACrisisdtComment)
101 )
102 else (ColctAlertsNearBy.rnTheCrisis->msrAny(true) = ActCrisis)
103 endif
104
105 /* PostF04 */
106 and ActAlert@post.rnTheCrisis = ActCrisis
107
108 /* PostF05 */
109 and TheSystem.rnctHuman->select(id.eq(AdtPhoneNumber)) = HumanColl
110
111 and HumanColl->select(kind.etEq(AetHumanKind)) = HumanCol2
112 and if (HumanCol2->msrIsEmpty)
113 then (ActHuman.init(AdtPhoneNumber,AetHumanKind)
114 and ActHuman@post.rnactComCompany = TheactComCompany

```

```

115      )
116  else (HumanCol2->any(true) = ActHuman)
117  endif
118
119 and ActHuman.rnSignaled->msrIncluding(ActAlert) = ColAlerts
120
121 and ActHuman@post.rnSignaled = ColAlerts
122
123 /* PostF06 */
124 AdtSMS.value = 'Your alert has been registered. We will handle it and keep you informed'
125 and TheactComCompany.rnInterfaceIN^ieSmsSend(AdtPhoneNumber,AdtSMS)
126 }
127 /* Post Protocol:*/
128 /* PostP01 */
129 postP{true}
130
131 prolog{"src/Operations/Environment/OUT/outactComCompany-oeAlert.pl"}
132 }
133 }
134 }
```

Listing C.12: Messir Spec. file environment-actComCompany.msr.

C.13 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeCloseCrisis.msr

```

1 package icrash.operations.environment.actCoordinator.oeCloseCrisis {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7 import icrash.concepts.primarytypes.datatypes
8 import icrash.environment
9
10 Operation Model {
11
12 operation: actCoordinator.outactCoordinator.oeCloseCrisis(AdtCrisisID:dtCrisisID):ptBoolean{
13 prolog {"src/Operations/Environment/OUT/outactCoordinator-oeCloseCrisis.pl"}
14 }
15 }
16 }
```

Listing C.13: Messir Spec. file environment-actCoordinator-oeCloseCrisis.msr.

C.14 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeGetAlertsSet.msr

```

1 package icrash.operations.environment.actCoordinator.oeGetAlertsSet {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.concepts.primarytypes.datatypes
9 import icrash.environment
10
11 Operation Model {
12
13 operation: actCoordinator.outactCoordinator.oeGetAlertsSet(AetAlertStatus:etAlertStatus):ptBoolean{
14 prolog {"src/Operations/Environment/OUT/outactCoordinator-oeGetAlertsSet.pl"}
15 }
16 }
17 }
```

Listing C.14: Messir Spec. file environment-actCoordinator-oeGetAlertsSet.msr.

C.15 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeGetCrisisSet.msr

```

1 package icrash.operations.environment.actCoordinator.oeGetCrisisSet {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7 import icrash.concepts.primarytypes.datatypes
8 import icrash.environment
9
10 Operation Model {
11
12 operation: actCoordinator.outactCoordinator.oeGetCrisisSet(AetCrisisStatus:etCrisisStatus) :ptBoolean
13   {
14     prolog{"src/Operations/Environment/OUT/outactCoordinator-oeGetCrisisSet.pl"}
15   }
16 }
```

Listing C.15: Messir Spec. file environment-actCoordinator-oeGetCrisisSet.msr.

C.16 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeInvalidateAlert.msr

```

1 package icrash.operations.environment.actCoordinator.oeInvalidateAlert {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7 import icrash.concepts.primarytypes.datatypes
8 import icrash.environment
9
10 Operation Model {
11
12 operation: actCoordinator.outactCoordinator.oeInvalidateAlert(AdtAlertID:dtAlertID) :ptBoolean{
13   prolog{"src/Operations/Environment/OUT/outactCoordinator-oeInvalidateAlert.pl"}
14 }
15 }
16 }
```

Listing C.16: Messir Spec. file environment-actCoordinator-oeInvalidateAlert.msr.

C.17 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeReportOnCrisis.msr

```

1 package icrash.operations.environment.actCoordinator.oeReportOnCrisis {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7 import icrash.concepts.primarytypes.datatypes
8 import icrash.environment
9
10 Operation Model {
11
12 operation: actCoordinator.outactCoordinator.oeReportOnCrisis(AdtCrisisID:dtCrisisID, AdtComment:
13   dtComment) :ptBoolean{
14   prolog{"src/Operations/Environment/OUT/outactCoordinator-oeReportOnCrisis.pl"}
15 }
16 }
```

17 }

Listing C.17: Messir Spec. file environment-actCoordinator-oeReportOnCrisis.msr.

C.18 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeSetCrisisHandler.msr

```

1 package icrash.operations.environment.actCoordinator.oeSetCrisisHandler {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.concepts.primarytypes.datatypes
9 import icrash.concepts.primarytypes.classes
10 import icrash.concepts.secondarytypes.datatypes
11 import icrash.environment
12
13 Operation Model {
14
15 operation: actCoordinator.outactCoordinator.oeSetCrisisHandler(AdtCrisisID:dtCrisisID):ptBoolean{
16 prolog{"src/Operations/Environment/OUT/outactCoordinator-oeSetCrisisHandler.pl"}
17 }
18
19 }
20 }
```

Listing C.18: Messir Spec. file environment-actCoordinator-oeSetCrisisHandler.msr.

C.19 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeSetCrisisStatus.msr

```

1 package icrash.operations.environment.actCoordinator.oeSetCrisisStatus {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7 import icrash.concepts.primarytypes.datatypes
8 import icrash.environment
9
10 Operation Model {
11
12 operation: actCoordinator.outactCoordinator.oeSetCrisisStatus(AdtCrisisID:dtCrisisID,
AetCrisisStatus:etCrisisStatus):ptBoolean{
13 prolog{"src/Operations/Environment/OUT/outactCoordinator-oeSetCrisisStatus.pl"}
14 }
15
16 }
17 }
```

Listing C.19: Messir Spec. file environment-actCoordinator-oeSetCrisisStatus.msr.

C.20 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeSetCrisisType.msr

```

1 package icrash.operations.environment.actCoordinator.oeSetCrisisType {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7 import icrash.concepts.primarytypes.datatypes
```

```

8 import icrash.environment
9
10 Operation Model {
11
12 operation: actCoordinator.outactCoordinator.oeSetCrisisType(AdtCrisisID:dtCrisisID, AetCrisisType:
    etCrisisType):ptBoolean{
13 prolog{"src/Operations/Environment/OUT/outactCoordinator-oeSetCrisisType.pl"}
14 }
15
16 }
17 }
```

Listing C.20: Messir Spec. file environment-actCoordinator-oeSetCrisisType.msr.

C.21 File ./src-gen/messir-spec/operations/environment/environment-actCoordinator-oeValidateAlert.msr

```

1 package icrash.operations.environment.actCoordinator.oeValidateAlert {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.string
6 import lu.uni.lassy.messir.libraries.calendar
7 import icrash.concepts.primarytypes.datatypes
8 import icrash.environment
9
10 Operation Model {
11
12 operation: actCoordinator.outactCoordinator.oeValidateAlert(AdtAlertID:dtAlertID):ptBoolean{
13 prolog{"src/Operations/Environment/OUT/outactCoordinator-oeValidateAlert.pl"}
14 }
15
16 }
17 }
```

Listing C.21: Messir Spec. file environment-actCoordinator-oeValidateAlert.msr.

C.22 File ./src-gen/messir-spec/operations/environment/environment-actMsrCreator-init.msr

```

1 package icrash.operations.icrash.environment.actMsrCreator.init {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import icrash.environment
5
6 Operation Model {
7
8 operation: actMsrCreator.init():ptBoolean{
9 // generic operation provided by the simulator
10 }
11 }
```

Listing C.22: Messir Spec. file environment-actMsrCreator-init.msr.

C.23 File ./src-gen/messir-spec/operations/environment/environment-actMsrCreator-oeCreateSystemAndEnvironment.msr

```

1 package icrash.operations.environment.actMsrCreator.oeCreateSystemAndEnvironment{
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.calendar
6
7 import icrash.concepts.primarytypes.datatypes
```

```

8 import icrash.concepts.primarytypes.classes
9 import icrash.concepts.secondarytypes.datatypes
10 import icrash.concepts.secondarytypes.classes
11 import icrash.environment
12
13 Operation Model {
14
15 operation: actMsrCreator.outactMsrCreator.oeCreateSystemAndEnvironment (AqtyComCompanies:ptInteger):
16     ptBoolean
17 {preP{true}
18 preF{true}
19 postF{
20     let TheSystem: ctState in
21     let AactMsrCreator: actMsrCreator in
22     let AactAdministrator: actAdministrator in
23     let AnextValueForAlertID: dtInteger in
24     let AnextValueForCrisisID: dtInteger in
25     let Aclock: dtDateAndTime in
26     let AcrisisReminderPeriod: dtSecond in
27     let AmaxCrisisReminderPeriod: dtSecond in
28     let AvpStarted: ptBoolean in
29
30     /* PostF01 -- MUST ALWAYS BE MADE FIRST -- */
31     AnextValueForAlertID.value.eq(1)
32     and AnextValueForCrisisID.value.eq(1)
33     and Aclock.date.year.value = 1970
34     and Aclock.date.month.value = 01
35     and Aclock.date.day.value = 01
36     and Aclock.time.hour.value = 00
37     and Aclock.time.minute.value = 00
38     and Aclock.time.second.value = 00
39
40     and AcrisisReminderPeriod.value.eq(300)
41     and AmaxCrisisReminderPeriod.value.eq(1200)
42     and AvpStarted = true
43     and TheSystem.init(AnextValueForAlertID,
44         AnextValueForCrisisID,
45         Aclock,
46         AcrisisReminderPeriod,
47         AmaxCrisisReminderPeriod,
48         Aclock,
49         AvpStarted
50     )
51     /* PostF02*/
52     and AactMsrCreator.init()
53     /* PostF03 */
54     and let AactComCompanyCol: Bag(actComCompany) in
55     AactComCompanyCol->size() = AqtyComCompanies
56     AactComCompanyCol-> forAll(init())
57     /* PostF04*/
58     and AactAdministrator.init()
59     /* PostF05*/
60     and let AactActivator:actActivator in
61     AactActivator.init()
62     /* PostF06 */
63     and let ActAdministrator:ctAdministrator in
64     let AdtLogin:dtLogin in
65     let AdtPassword:dtPassword in
66     AdtLogin.value.eq('icrashadmin')
67     and AdtPassword.value.eq('7WXC1359')
68     and ActAdministrator.init(AdtLogin,AdtPassword)
69     /* PostF07*/
70     and ActAdministrator@post.rnactAuthenticated = AactAdministrator
71 postP{true}
72 prolog{ "src/Operations/Environment/OUT/outactMsrCreator-oeCreateSystemAndEnvironment.pl"}
73
74 }
75 }
76

```

77 }

Listing C.23: Messir Spec. file environment-actMsrCreator-oeCreateSystemAndEnvironment.msr.

C.24 File [./src-gen/messir-spec/concepts/environment-authentication.msr](#)

```

1 package icrash.environment.authentication {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import icrash.concepts.primarytypes.authentication.datatypes
5
6 /*
7 This file is dedicated for actors in relation with the authentication feature. Please use your own
8 file dedicated for your feature
9 if you want to add new actors.
9 */
10 Environment Model {
11
12 actor actMailingService role rnactMailingService cardinality[1 .. 1] {
13   operation init():ptBoolean
14   input interface inactMailingService {
15     operation ieSendMail(AAddress:ptString, ATitle:ptString, AContent:ptString):ptBoolean
16   }
17   output interface outactMailingService {
18   }
19 }
20
21 actor actCaptchaService role rnactCaptchaService cardinality[1 .. 1]{
22   operation init():ptBoolean
23   input interface inactCaptchaService {
24     operation ieGenerateCaptcha():ptBoolean//Documented
25     operation ieVerifyCaptcha(AdtCaptchaResponse:dtCaptchaResponse):ptBoolean
26   }
27   output interface outactCaptchaService {
28     operation oeSendCaptcha(AdtCaptcha:dtCaptcha, AdtResponse:dtCaptchaResponse):ptBoolean//Partly
29       Documented
30     operation oeCaptchaInvalid(AdtCaptchaId:ptInteger):ptBoolean
31     operation oeCaptchaValid(AdtCaptchaId:ptInteger):ptBoolean
32   }
33 }
34
35 }
```

Listing C.24: Messir Spec. file environment-authentication.msr.

C.25 File [./src-gen/messir-spec/environment/environment.msr](#)

```

1 package icrash.environment{
2
3 import icrash.concepts.primarytypes.datatypes
4 import icrash.concepts.primarytypes.classes
5 import icrash.concepts.secondarytypes.datatypes
6 import lu.uni.lassy.messir.libraries.primitives
7 import lu.uni.lassy.messir.libraries.math
8 import lu.uni.lassy.messir.libraries.calendar
9 import icrash.concepts.primarytypes.authentication.datatypes
10
11 Environment Model {
12
13 actor actMsrCreator role rnactMsrCreator cardinality [1..1] {
14   operation init():ptBoolean
15   input interface inactMsrCreator {
16   }
17 }
```

```

19  output interface outactMsrCreator {
20    operation oeCreateSystemAndEnvironment(AqtyComCompanies:ptInteger ):ptBoolean
21  }
22 }
23
24 actor actAdministrator
25   role rnactAdministrator
26   cardinality [1..1]
27   extends actAuthenticated {
28
29   operation init():ptBoolean
30
31   output interface outactAdministrator{
32
33     operation oeAddCoordinator(
34       AdtCoordinatorID:dtCoordinatorID ,
35       AdtLogin:dtLogin ,
36       AdtPassword:dtPassword ):ptBoolean
37
38     operation oeDeleteCoordinator(
39       AdtCoordinatorID:dtCoordinatorID ):ptBoolean
40
41   //Sam:
42   operation oeUserActivityStatistic() : ptBoolean
43   operation oeNumberOfCrisis() : ptBoolean
44   operation oeTimeOfTypeOfCrisis() : ptBoolean
45   operation ugAdministrateTheSystem() : ptBoolean
46   operation oeStatistic() : ptBoolean
47 }
48
49   input interface inactAdministrator{
50
51   operation ieCoordinatorAdded():ptBoolean
52   operation ieCoordinatorDeleted():ptBoolean
53
54   //Sam:
55   operation ieClickStatistic() : ptBoolean
56   operation ieStatistic() : ptBoolean
57   operation ieCallTimeAndCrisisNumber() : ptBoolean
58 }
59 }
60
61 actor actCoordinator
62   role rnactCoordinator
63   cardinality [0..*]
64   extends actAuthenticated{
65
66   operation init():ptBoolean
67
68   output interface outactCoordinator{
69     operation oeInvalidateAlert(AdtAlertID:dtAlertID ):ptBoolean
70     operation oeCloseCrisis(AdtCrisisID:dtCrisisID ):ptBoolean
71     operation oeGetAlertsSet(AetAlertStatus:etAlertStatus ):ptBoolean
72     operation oeGetCrisisSet(AetCrisisStatus:etCrisisStatus ):ptBoolean
73     operation oeSetCrisisHandler(AdtCrisisID:dtCrisisID ):ptBoolean
74     operation oeReportOnCrisis(
75       AdtCrisisID:dtCrisisID ,
76       AdtComment:dtComment
77       ):ptBoolean
78     operation oeSetCrisisStatus(
79       AdtCrisisID:dtCrisisID ,
80       AetCrisisStatus:etCrisisStatus
81       ):ptBoolean
82     operation oeSetCrisisType(
83       AdtCrisisID:dtCrisisID ,
84       AetCrisisType:etCrisisType
85       ):ptBoolean
86     operation oeValidateAlert(AdtAlertID:dtAlertID ):ptBoolean
87
88   //Vlad:

```

```

89   operation oeCreateAlert() : ptBoolean
90   operation oeCreateCrisis() : ptBoolean
91   operation oeUpdateCrisis() : ptBoolean
92 }
93
94 input interface inactCoordinator{
95   operation ieSendAnAlert(ActAlert:ctAlert ):ptBoolean
96   operation ieSendACrisis(ActCrisis:ctCrisis ):ptBoolean
97 }
98 }
99
100 actor actComCompany role rnactComCompany cardinality [0...*]{
101
102   operation init():ptBoolean
103
104   output interface outactComCompany{
105     operation oeAlert(
106       AdtHumanKind:etHumanKind ,
107       AdtDate:dtDate ,
108       AdtTime:dtTime ,
109       AdtPhoneNumber:dtPhoneNumber ,
110       AdtGPSLocation:dtGPSLocation ,
111       AdtComment:dtComment
112     ):ptBoolean
113   }
114
115   input interface inactComCompany{
116     operation ieSmsSend(AdtPhoneNumber:dtPhoneNumber ,
117       AdtSMS:dtSMS
118     ):ptBoolean
119   }
120 }
121
122 actor actAuthenticated role rnactAuthenticated cardinality [0...*]{
123
124   operation init():ptBoolean
125
126   output interface outactAuthenticated{
127     operation oeLogin(AdtLogin:dtLogin , AdtPassword:dtPassword ):ptBoolean
128     operation oeLogout():ptBoolean
129
130   //Michel:
131   operation oeSubmitCaptcha(AdtResponse:dtCaptchaResponse ):ptBoolean
132
133   //Vlad:
134   operation oeCreateAlert() : ptBoolean
135 }
136
137   input interface inactAuthenticated{
138     operation ieMessage(AMessage:ptString):ptBoolean
139
140   //Michel:
141   operation ieConfirmCaptcha(ACaptcha:dtCaptcha ):ptBoolean
142 }
143 }
144
145 actor actActivator[proactive] role rnactActivator cardinality [1..1]{
146
147   operation init():ptBoolean
148
149   output interface outactActivator{
150     proactive operation oeSollicitateCrisisHandling():ptBoolean
151     proactive operation oeSetClock(AcurrentClock:dtDateAndTime ):ptBoolean
152   }
153
154   input interface inactActivator{
155   }
156 }
157
158 //Sam:

```

```

159 actor actSystem role rnactSystem cardinality[1 .. 1] {
160   input interface inactSystem {
161     operation ieCallTimeAndCrisisNumber() : ptBoolean
162     operation ieCallUserActivity() : ptBoolean
163     operation ieCallTypeWithTimeAverage() : ptBoolean
164   }
165   output interface outactSystem {
166     operation ugSecurelyUserSystem() : ptBoolean
167     operation ugVictimSendFamilyNotification() : ptBoolean
168     operation ugWitnessSendFamilyNotification() : ptBoolean
169     operation oeChooseInformation() : ptBoolean
170     operation oeSendNotification() : ptBoolean
171     operation oeSendStatistic() : ptBoolean
172   }
173 }
174
175 actor actDatabase role rnactDatabase cardinality[1 .. 1] {
176   input interface inactDatabase {
177     operation ieCallTimeAndCrisisNumber() : ptBoolean
178     operation ieCallUserActivity() : ptBoolean
179     operation ieCallTypeWithTimeAverage() : ptBoolean
180     operation oeSendStatistic() : ptBoolean
181     operation oeStatistic() : ptBoolean
182   }
183   output interface outactDatabase {
184   }
185 }
186
187 }
188 }
```

Listing C.25: Messir Spec. file environment.msr.

C.26 File [./src-gen/messir-spec/concepts/primarytypes-associations.msr](#)

```

1 package icrash.concepts.primarytypes.associations {
2
3 import icrash.concepts.primarytypes.datatypes
4 import icrash.concepts.primarytypes.classes
5 import icrash.environment
6 import lu.uni.lassy.messir.libraries.primitives
7
8 Concept Model {
9
10   Primary Types{
11
12   // Internal
13
14   association assctAlertctCrisis
15     ctAlert(rnAlerts)[1..*]
16     ctCrisis (rnTheCrisis)[1..1]
17
18   association assctAlertctHuman
19     ctAlert(rnSignaled)[1..*]
20     ctHuman (rnSignaler)[1..1]
21
22   association assctCrisisctCoordinator
23     ctCrisis(rnHandled)[0..*]
24     ctCoordinator(rnHandler)[0..1]
25
26   // With Actors
27
28   association assctHumanactComCompany
29     ctHuman(rnctHuman)[0..*]
30     actComCompany(rnactComCompany)[1..1]
31
32   association assctCoordinatoractCoordinator
```

```

33     ctCoordinator(rnctCoordinator) [1..1]
34     actCoordinator(rnactCoordinator) [1..1]
35
36     association assctAuthenticatedactAuthenticated
37         ctAuthenticated(rnctAuthenticated) [1..1]
38         actAuthenticated(rnactAuthenticated) [1..1]
39
40     }
41 }
42 }
```

Listing C.26: Messir Spec. file primarytypes-associations.msr.

C.27 File [./src-gen/messir-spec/concepts/primarytypes-authentication-datatatypes.msr](#)

```

1 package icrash.concepts.primarytypes.authentication.datatypes {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.string
5 import lu.uni.lassy.messir.libraries.math
6 import lu.uni.lassy.messir.libraries.calendar
7
8 /*
9 This file is dedicated for datatypes in relation with the authentication feature. Please use your
10 own file dedicated for your feature
11 if you want to add new datatypes.
12 */
13
14 Concept Model {
15
16     Primary Types {
17         datatype dtCaptchaId extends dtInteger{//TODO: View
18
19         }
20         datatype dtCaptcha {//TODO: link to images
21             attribute id: dtCaptchaId
22             attribute question: ptString
23             operation is():ptBoolean
24         }
25         datatype dtCaptchaResponse {
26             attribute id: dtCaptchaId
27             attribute response: ptString//TODO: Type?
28             operation is():ptBoolean
29         }
30         datatype dtCaptchaImage extends dtString{
31             attribute width : dtInteger
32             attribute height : dtInteger
33             operation is():ptBoolean
34
35             datatype dtCaptchaResponseMap{//TODO: Is this sufficient?
36             operation is():ptBoolean//TODO: View
37
38             operation register(AdtResponse:dtCaptchaResponse):ptBoolean
39             operation get(AId:dtCaptchaId):dtCaptchaResponse
40             operation remove(AId:dtCaptchaId):ptBoolean
41         }
42     }
43
44     Secondary Types {
45
46     }
47 }
```

Listing C.27: Messir Spec. file primarytypes-authentication-datatypes.msr.

C.28 File ./src-gen/messir-spec/operations/concepts/primarytypes-classes/primarytypes-classes-ctAdministrator.msr

```

1 package icrash.operations.concepts.primarytypes.classes.ctAdministrator{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 import icrash.concepts.primarytypes.datatypes
6 import icrash.concepts.primarytypes.classes
7
8 Operation Model {
9
10 operation: icrash.concepts.primarytypes.classes.ctAdministrator.init(
11   Alogin:dtLogin ,
12   Apwd:dtPassword
13   ):ptBoolean{
14 postF{
15 if
16 (
17 let Self:ctAdministrator in
18 /* Post F01 */
19 Self.login(Alogin)
20 and Self.pwd = Apwd
21 and Self.vpIsLogged = false
22
23 /* Post F02 */
24 and (Self.oclIsNew and self = Self)
25 )
26 then (result = true)
27 else (result = false)
28 endif
29 }
30 prolog{ "src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctAdministrator-init.pl"}
31 }
32 }
33 }
```

Listing C.28: Messir Spec. file primarytypes-classes-ctAdministrator.msr.

C.29 File ./src-gen/messir-spec/operations/concepts/primarytypes-classes/primarytypes-classes-ctAlert.msr

```

1 package icrash.operations.concepts.primarytypes.classes.ctAlert{
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.calendar
5
6 import icrash.concepts.primarytypes.datatypes
7 import icrash.concepts.primarytypes.classes
8
9 import icrash.environment
10
11 Operation Model {
12
13 operation: icrash.concepts.primarytypes.classes.ctAlert.init(Aid:dtAlertID , Astatus:etAlertStatus ,
14   Alocation:dtGPSLocation , Ainstant:dtDateAndTime , Acomment:dtComment
15   ):ptBoolean{
16 postF{
17 if
18 (
19 /* Post F01 */
20 let Self:ctAlert in
21 Self.id = Aid
22 and Self.status = Astatus
23 and Self.location = Alocation
23 and Self.instant = Ainstant
```

```

24 and Self.comment = Acomment
25 /* Post F02 */
26 and (Self.oclIsNew and self = Self)
27 )
28 then (result = true)
29 else (result = false)
30 endif
31 }
32 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctAlert-init.pl"}
33 }
34
35 operation: icrash.concepts.primarytypes.classes.ctAlert.isSentToCoordinator(AactCoordinator:
            actCoordinator ):ptBoolean
36 {
37 postF{
38 if
39 (
40 /* Post F01 */
41 AactCoordinator.rnInterfaceIN.ieSendAnAlert(self)
42 )
43 then (result = true)
44 else (result = false)
45 endif
46 }
47 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctAlert-isSentToCoordinator.
        pl"}
48
49 }
50 }
51 }

```

Listing C.29: Messir Spec. file primarytypes-classes-ctAlert.msr.

C.30 File ./src-gen/messir-spec/operations/concepts/primarytypes-classes/primarytypes-classes-ctAuthenticated.msr

```

1 package icrash.operations.concepts.primarytypes.classes.ctAuthenticated {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import icrash.concepts.primarytypes.datatypes
5 import icrash.concepts.primarytypes.classes
6
7 Operation Model {
8
9 operation: icrash.concepts.primarytypes.classes.ctAuthenticated.init(Alogin:dtLogin, Apwd:dtPassword
    ):ptBoolean
10 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctAuthenticated-init.pl"}
11 }
12 }
13
14 }

```

Listing C.30: Messir Spec. file primarytypes-classes-ctAuthenticated.msr.

C.31 File ./src-gen/messir-spec/operations/concepts/primarytypes-classes/primarytypes-classes-ctCoordinator.msr

```

1 package icrash.operations.concepts.primarytypes.classes.ctCoordinator.init {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import icrash.concepts.primarytypes.datatypes
5 import icrash.concepts.primarytypes.classes
6
7 Operation Model {
8

```

```

9 operation: icrash.concepts.primarytypes.classes.ctCoordinator.init(Aid:dtCoordinatorID, Alogin:
10   dtLogin, Apwd:dtPassword):ptBoolean
11 postF{
12 if
13 (
14 /* Post F01 */
15 let Self:ctCoordinator in
16 Self.id = Aid
17 and Self.login = Alogin
18 and Self.pwd = Apwd
19 and Self.vpIsLogged = false
20 /* Post F02 */
21 and (Self.oclIsNew and self = Self)
22 )
23 then (result = true)
24 else (result = false)
25 endif
26 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctCoordinator-init.pl"}
27 }
28 }
29 }

```

Listing C.31: Messir Spec. file primarytypes-classes-ctCoordinator.msr.

C.32 File ./src-gen/messir-spec/operations/concepts/primarytypes-classes/primarytypes-classes-ctCrisis.msr

```

1 package icrash.operations.concepts.primarytypes.classes.ctCrisis {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5 import lu.uni.lassy.messir.libraries.calendar
6
7 import icrash.concepts.primarytypes.datatypes
8 import icrash.concepts.primarytypes.classes
9 import icrash.concepts.secondarytypes.datatypes
10 import icrash.concepts.secondarytypes.classes
11 import lu.uni.lassy.messir.libraries.primitives
12
13 import icrash.environment
14
15 Operation Model {
16 /**
17 operation: icrash.concepts.primarytypes.classes.ctCrisis.init(
18   Aid:dtCrisisID,
19   Atype:etCrisisType,
20   Astatus:etCrisisStatus,
21   Alocation:dtGPSLocation,
22   Ainstant:dtDateAndTime,
23   Acomment:dtComment
24   ):ptBoolean{
25 postF{
26 if
27 (
28 /* Post F01 */
29 let Self:ctCrisis in
30 Self.id = Aid
31 and Self.type = Atype
32 and Self.status = Astatus
33 and Self.location = Alocation
34 and Self.instant = Ainstant
35 and Self.comment = Acomment
36 /* Post F02 */
37 and (Self.oclIsNew and self = Self)
38 )
39 then (result = true)
40 else (result = false)

```

```

41 endif}
42 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctCrisis-init.pl"}
43 //-----
44 operation: icrash.concepts.primarytypes.classes.ctCrisis.handlingDelayPassed():ptBoolean
45 {
46 postF{
47 let TheSystem:ctState in
48 let CurrentClockSecondsQty:dtInteger in
49 let vpLastReminderSecondsQty:dtInteger in
50 let CrisisReminderPeriod:dtSecond in
51 if
52 ( /* Post F01 */
53 self.rnSystem = TheSystem
54 and self.status = pending
55 and TheSystem.clock.toSecondsQty() = CurrentClockSecondsQty
56 and TheSystem.vpLastReminder.toSecondsQty() = vpLastReminderSecondsQty
57 and TheSystem.crisisReminderPeriod = CrisisReminderPeriod
58 and CurrentClockSecondsQty.sub(vpLastReminderSecondsQty).gt(CrisisReminderPeriod) = true
59 )
60 then (result = true)
61 else (result = false)
62 endif
63 }
64 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctCrisis-handlingDelayPassed
    .pl"}}
65 //-----
66 operation: icrash.concepts.primarytypes.classes.ctCrisis.maxHandlingDelayPassed():ptBoolean
67 {
68 postF{
69 let TheSystem:ctState in
70 let CurrentClockSecondsQty:dtInteger in
71 let CrisisInstantSecondsQty:dtInteger in
72 let MaxCrisisReminderPeriod:dtSecond in
73 if
74 ( /* Post F01 */
75 self.rnSystem = TheSystem
76 and self.status = pending
77 and TheSystem.clock.toSecondsQty() = CurrentClockSecondsQty
78 and Self.instant.toSecondsQty() = CrisisInstantSecondsQty
79 and TheSystem.maxCrisisReminderPeriod = MaxCrisisReminderPeriod
80 and CurrentClockSecondsQty.sub(CrisisInstantSecondsQty)
81         .gt(MaxCrisisReminderPeriod)
82 )
83 then (result = true)
84 else (result = false)
85 endif
86 }
87 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctCrisis-
    maxHandlingDelayPassed.pl"}}
88 //-----
89 operation: icrash.concepts.primarytypes.classes.ctCrisis.isSentToCoordinator(AactCoordinator:
    actCoordinator):ptBoolean
90 {
91 postF{
92 if
93 (
94 /* Post F01 */
95 AactCoordinator.bnInterfaceIN.ieSendACrisis(self)
96 )
97 then (result = true)
98 else (result = false)
99 endif}
100 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctCrisis-isSentToCoordinator
    .pl" }
101 //-----
102 operation: icrash.concepts.primarytypes.classes.ctCrisis.isAllocatedIfPossible():ptBoolean
103 {
104 postF{
105 if (
106 /* Post F01 */

```

```

107 self.maxHandlingDelayPassed()
108 and
109 if (TheSystem.rnactCoordinator->msrIsEmpty = false)
110 then (
111 /* Post F02 */
112 TheSystem.rnactCoordinator->msrAny(true) = TheCoordinatorActor
113 and TheCoordinatorActor.rnctCoordinator = TheCoordinator
114 and self@post.rnHandler = TheCoordinator
115 and self@post.status = handled
116 and self.id.value = TheCrisisIDptString
117 and 'You are now considered as handling the crisis having ID: '
118 .ptStringConcat(TheCrisisIDptString) = TheMessage
119 and TheCoordinatorActor.rnInterfaceIN^ieMessage(TheMessage)
120 )
121 else ( /* Post F03 */
122 TheSystem.rnactAdministrator
123 ->forAll(rnInterfaceIN.ieMessage('Please add new coordinators to handle pending crisis !'))
124 )
125 endif
126 )
127 then (result = true)
128 else (result = false)
129 endif
130 }
131 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctCrisis-
    isAllocatedIfPossible.pl"}
132 }
133 }
134 }

```

Listing C.32: Messir Spec. file primarytypes-classes-ctCrisis.msr.

C.33 File ./src-gen/messir-spec/operations/concepts/primarytypes-classes/primarytypes-classes-ctHuman.msr

```

1 package icrash.operations.concepts.primarytypes.classes.ctHuman.init {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import icrash.concepts.primarytypes.datatypes
5
6 import icrash.concepts.primarytypes.classes
7
8 Operation Model {
9
10 operation: icrash.concepts.primarytypes.classes.ctHuman.init(Aid:dtPhoneNumber, Akind:etHumanKind):
    ptBoolean
11 {
12 postF{
13 if
14 (
15 /* Post F01 */
16 let Self:ctHuman in
17
18 Self.id = Aid
19 and Self.kind = Akind
20
21 /* Post F02 */
22 and (Self.oclIsNew and self = Self)
23 )
24 then (result = true)
25 else (result = false)
26 endif
27 }
28 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctHuman-init.pl"}
29 }
30 operation: icrash.concepts.primarytypes.classes.ctHuman.isAcknowledged():ptBoolean{
31 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctHuman-isAcknowledged.pl"}
32 }

```

```
33 }
34 }
```

Listing C.33: Messir Spec. file primarytypes-classes-ctHuman.msr.

C.34 File ./src-gen/messir-spec/operations/concepts/primarytypes-classes/primarytypes-classes-ctState.msr

```
1 package icrash.operations.concepts.primarytypes.classes.ctState{
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.calendar
5 import lu.uni.lassy.messir.libraries.math
6
7 import icrash.concepts.primarytypes.classes
8
9 Operation Model {
10
11 operation: icrash.concepts.primarytypes.classes.ctState.init(
12 AnextValueForAlertID: dtInteger,
13 AnextValueForCrisisID: dtInteger ,
14 dtAclock:dtDateAndTime,
15 AcrisisReminderPeriod: dtSecond,
16 AmaxCrisisReminderPeriod: dtSecond ,
17 AvpLastReminder: dtDateAndTime ,
18 AvpStarted:ptBoolean ):ptBoolean{
19 postF{
20 if
21 (
22 /* Post F01 */
23 let Self:ctState in
24
25 Self.nextValueForAlertID = AnextValueForAlertID
26 and Self.nextValueForCrisisID = AnextValueForCrisisID
27 and Self.clock = Aclock
28 and Self.crisisReminderPeriod = AcrisisReminderPeriod
29 and Self.maxCrisisReminderPeriod = AmaxCrisisReminderPeriod
30 and Self.vpLastReminder = AvpLastReminder
31 and Self.vpStarted = AvpStarted
32
33 and (Self.oclIsNew and self = Self)
34 )
35 then (result = true)
36 else (result = false)
37 endif
38 }
39 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesClasses-ctState-init.pl" }
40 }
41 }
42 }
```

Listing C.34: Messir Spec. file primarytypes-classes-ctState.msr.

C.35 File ./src-gen/messir-spec/concepts/primarytypes-classes.msr

```
1 package icrash.concepts.primarytypes.classes {
2
3 import icrash.concepts.primarytypes.datatypes
4 import icrash.environment
5 import lu.uni.lassy.messir.libraries.primitives
6 import lu.uni.lassy.messir.libraries.math
7 import lu.uni.lassy.messir.libraries.calendar
8 import icrash.concepts.primarytypes.authentication.datatypes
9
10 Concept Model {
11
12 Primary Types{
```

```

13
14 state class ctState {
15   attribute nextValueForAlertID:dtInteger
16   attribute nextValueForCrisisID:dtInteger
17   attribute clock:dtDateAndTime
18   attribute crisisReminderPeriod:dtSecond
19   attribute maxCrisisReminderPeriod:dtSecond
20   attribute vpLastReminder:dtDateAndTime
21   attribute vpStarted:ptBoolean
22
23   operation init( AnextValueForAlertID:dtInteger,
24     AnextValueForCrisisID:dtInteger,
25     Aclock:dtDateAndTime,
26     AcrisisReminderPeriod:dtSecond ,
27     AmaxCrisisReminderPeriod:dtSecond ,
28     AvpLastReminder:dtDateAndTime ,
29     AvpStarted:ptBoolean ): ptBoolean
30 }
31
32 class ctAlert role rnctAlert cardinality [0..*]{
33   attribute id:dtAlertID
34   attribute status: etAlertStatus
35   attribute location:dtGPSLocation
36   attribute instant:dtDateAndTime
37   attribute comment:dtComment
38
39   operation init( Aid:dtAlertID ,
40     Astatus:etAlertStatus ,
41     Alocation:dtGPSLocation ,
42     Ainstant:dtDateAndTime ,
43     Acomment:dtComment ):ptBoolean
44   operation isSentToCoordinator(AactCoordinator:actCoordinator ):ptBoolean
45
46 }
47
48 class ctCrisis role rnctCrisis cardinality [0..*]{
49   attribute id:dtCrisisID
50   attribute type:etCrisisType
51   attribute status: etCrisisStatus
52   attribute location:dtGPSLocation
53   attribute instant:dtDateAndTime
54   attribute comment:dtComment
55
56   operation init(
57     Aid:dtCrisisID ,
58     Atype:etCrisisType ,
59     Astatus:etCrisisStatus ,
60     Alocation:dtGPSLocation ,
61     Ainstant:dtDateAndTime ,
62     Acomment:dtComment ):ptBoolean
63
64   operation handlingDelayPassed():ptBoolean
65   operation maxHandlingDelayPassed():ptBoolean
66   operation isSentToCoordinator(AactCoordinator:actCoordinator ):ptBoolean
67   operation isAllocatedIfPossible():ptBoolean
68 }
69
70 class ctHuman role rnctHuman cardinality [0..*]{
71   attribute id:dtPhoneNumber
72   attribute kind:etHumanKind
73
74   operation init(
75     Aid:dtPhoneNumber ,
76     Akind:etHumanKind ):ptBoolean
77   operation isAcknowledged():ptBoolean
78 }
79
80 class ctAuthenticated
81   role rnctAuthenticated
82   cardinality [0..*]{
```

```

83     attribute login:dtLogin
84     attribute pwd: dtPassword
85     attribute vpIsLogged:ptBoolean
86
87     attribute awaitedCaptchaId:ptInteger //Michel
88
89
90     operation init(
91         Alogin:dtLogin ,
92         Apwd:dtPassword ):ptBoolean
93    }
94
95     class ctCoordinator
96         role rnctCoordinator
97         cardinality [0..*]
98         extends ctAuthenticated{
99
100    attribute id:dtCoordinatorID
101
102    operation init(
103        Aid:dtCoordinatorID ,
104        Alogin:dtLogin ,
105        Apwd:dtPassword ):ptBoolean
106    }
107
108    class ctAdministrator
109        role rnctAdministrator
110        cardinality [1..1]
111        extends ctAuthenticated{
112
113        operation init(
114            Alogin:dtLogin ,
115            Apwd:dtPassword ):ptBoolean
116        }
117
118    //Michel:
119    class ctCaptchaService role rnctCaptchaService cardinality [1..1]{//TODO: View
120        attribute map:dtCaptchaResponseMap
121
122        operation init():ptBoolean//TODO: Improve
123    }
124    class ctMailingService role rnctMailingService cardinality [1..1]{//TODO: View
125        operation init():ptBoolean//TODO: Improve
126    }
127    }
128 }
129 }
```

Listing C.35: Messir Spec. file primarytypes-classes.msr.

C.36 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatatypes/primarytypes-datatypes-dtAlertID.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.dtAlertID{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7     operation: icrash.concepts.primarytypes.datatypes.dtAlertID.is():ptBoolean{
8
9     postF{
10        let TheResult: ptBoolean in
11        ( if
12            ( self.value.length().gt(0)
13            and self.value.length().leq(20)
14            )
15        then (TheResult = true)
```

```

16  else (TheResult = false)
17  endif
18  result = TheResult
19  )
20  prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtAlertID-is.pl"}
21  }
22 }
23 }
```

Listing C.36: Messir Spec. file primarytypes-datatypes-dtAlertID.msr.

C.37 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-dtComment.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.dtComment{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.dtComment.is():ptBoolean{
8
9     postF{
10       let TheResult: ptBoolean in
11       (
12         if
13           ( MaxLength = 160
14             and self.value.length().leq(MaxLength)
15           )
16         then (TheResult = true)
17         else (TheResult = false)
18       endif
19       result = TheResult
20     )
21   prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtComment-is.pl"}
22 }
23 }
24 }
```

Listing C.37: Messir Spec. file primarytypes-datatypes-dtComment.msr.

C.38 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-dtCoordinatorID.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.dtCoordinatorID{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6   operation: icrash.concepts.primarytypes.datatypes.dtCoordinatorID.is():ptBoolean{
7
8     postF{
9       let TheResult: ptBoolean in
10      (
11        if
12          ( self.value.length().gt(0)
13            and self.value.length().leq(5)
14          )
15        then (TheResult = true)
16        else (TheResult = false)
17      endif
18      result = TheResult
19    )
20   prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtCoordinatorID-is.pl"
21 }
```

```
22 }
23 }
```

Listing C.38: Messir Spec. file primarytypes-datatatypes-dtCoordinatorID.msr.

C.39 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatatypes-dtCrisisID.msr

```
1 package icrash.operations.concepts.primarytypes.datatypes.dtCrisisID{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.dtCrisisID.is():ptBoolean{
8
9     postF{
10       let TheResult: ptBoolean in
11       ( if
12         ( self.value.length().gt(0)
13           and self.value.length().leq(10)
14         )
15         then (TheResult = true)
16         else (TheResult = false)
17       endif
18       result = TheResult
19     )
20   }
21   prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtCrisisID-is.pl"}
22 }
23 }
24 }
```

Listing C.39: Messir Spec. file primarytypes-datatatypes-dtCrisisID.msr.

C.40 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatatypes-dtGPSLocation.msr

```
1 package icrash.operations.concepts.primarytypes.datatypes.dtGPSLocation{
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.math
5
6 import icrash.concepts.primarytypes.datatypes
7 import icrash.concepts.primarytypes.classes
8 import icrash.concepts.secondarytypes.datatypes
9 import icrash.concepts.secondarytypes.classes
10
11 Operation Model {
12
13   operation: icrash.concepts.primarytypes.datatypes.dtGPSLocation.is():ptBoolean{
14     postF{
15       let TheResult: ptBoolean in
16       ( if
17         ( self.latitude.is()
18           and self.longitude.is()
19         )
20         then (TheResult = true)
21         else (TheResult = false)
22       endif
23       result = TheResult
24     )
25   }
26   prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtGPSLocation-is.pl"}
27 }
```

```

28 operation: icrash.concepts.primarytypes.datatypes.dtGPSLocation.isNearTo(aGPSLocation:
29   dtGPSLocation):ptBoolean{
30   postF{
31     let TheResult: ptBoolean in true
32     let EarthRadius: dtReal in
33     let MaxDistance: dtReal in
34     let ComparedLatitude: dtLatitude in
35     let ComparedLongitude: dtLongitude in
36     let R1: dtReal in let R1a: dtReal in
37     let R2: dtReal in let R2a: dtReal in
38
39     (if
40       (EarthRadius.value = 6371
41         and MaxDistance.value = 100
42
43         and self.latitude = ComparedLatitude
44         and self.longitude = ComparedLongitude
45         and self.latitude.sin() = R1a
46         and self.latitude.sin().mul(R1a) = R1
47         and self.latitude.cos() = R2a
48         and self.latitude.cos().mul(R2a) = R2
49
50         and self.longitude = ComparedLongitude
51         and self.longitude.sub(ComparedLongitude).cos().mul(R2)
52           .add(R1).acos().mul(EarthRadius).sub(MaxDistance)
53           .value.leg(0)
54     )
55     then (TheResult = true)
56     else (TheResult = false)
57   endif
58   result = TheResult
59 }
60 prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtGPSLocation-isNearTo
61   .pl"}
62 operation: icrash.concepts.primarytypes.datatypes.dtLatitude.is():ptBoolean{
63   postF{
64     let TheResult: ptBoolean in
65     (if
66       (AdtValue.value.geq(-90.0)
67         and AdtValue.value.leg(+90.0)
68     )
69     then (TheResult = true)
70     else (TheResult = false)
71   endif
72   result = TheResult
73 }
74 prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtLatitude-is.pl"}
75 }
76 operation: icrash.concepts.primarytypes.datatypes.dtLongitude.is():ptBoolean{
77   postF{
78     let TheResult: ptBoolean in
79     (if
80       (AdtValue.value.geq(-180.0)
81         and AdtValue.value.leg(+180.0)
82     )
83     then (TheResult = true)
84     else (TheResult = false)
85   endif
86   result = TheResult
87 }
88 prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtLongitude-is.pl"}
89 }
90 }
91 }
```

Listing C.40: Messir Spec. file primarytypes-datatatypes-dtGPSLocation.msr.

C.41 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-dtLogin.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.dtLogin{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.dtLogin.is():ptBoolean{
8     postF{
9       let TheResult: ptBoolean in
10      let MaxLength: ptInteger in
11      ( if
12        ( MaxLength = 20
13          and self.value.length().leq(MaxLength)
14        )
15        then (TheResult = true)
16        else (TheResult = false)
17      endif
18      result = TheResult
19    )
20  }
21  prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtLogin-is.pl"}
22 }
23 }
24 }
```

Listing C.41: Messir Spec. file primarytypes-datatypes-dtLogin.msr.

C.42 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-dtPassword.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.dtPassword{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.dtPassword.is():ptBoolean{
8     postF{
9       let TheResult: ptBoolean in
10      let MinLength: ptInteger in
11      ( if
12        ( MinLength = 6
13          and self.value.length().geq(MinLength)
14        )
15        then (TheResult = true)
16        else (TheResult = false)
17      endif
18      result = TheResult
19    )
20  }
21  prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtPassword-is.pl"}
22 }
23 }
24 }
```

Listing C.42: Messir Spec. file primarytypes-datatypes-dtPassword.msr.

C.43 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-dtPhoneNumber.msr

```
1 package icrash.operations.concepts.primarytypes.datatypes.dtPhoneNumber{
```

```

1
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.dtPhoneNumber.is():ptBoolean{
8
9     postF{
10      let TheResult: ptBoolean in
11      ( if
12        ( self.value.length().gt(4)
13          and self.value.length().leq(30)
14        )
15        then (TheResult = true)
16        else (TheResult = false)
17      endif
18      result = TheResult
19    )
20  }
21  prolog{"src/Operations/Concepts/PrimaryTypesDatatypes/PrimaryTypesDatatypes-dtPhoneNumber-is.pl"}
22 }
23 }
24 }
```

Listing C.43: Messir Spec. file primarytypes-datatypes-dtPhoneNumber.msr.

C.44 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-etAlertStatus.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.etAlertStatus{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.etAlertStatus.is():ptBoolean{
8     postF{
9       let TheResult: ptBoolean in
10      ( if
11        ( self = pending
12          or self = valid
13          or self = invalid
14        )
15        then (TheResult = true)
16        else (TheResult = false)
17      endif
18      result = TheResult
19    )
20  }
21 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesDatatypes-etAlertStatus-is.pl"}
22 }
23 }
24 }
```

Listing C.44: Messir Spec. file primarytypes-datatypes-etAlertStatus.msr.

C.45 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-etCrisisStatus.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.etCrisisStatus{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.etCrisisStatus.is():ptBoolean{
```

```

8  postF{
9    let TheResult: ptBoolean in
10   ( if
11     ( self = pending
12     or self = handled
13     or self = solved
14     or self = closed
15   )
16   then (TheResult = true)
17   else (TheResult = false)
18   endif
19   result = TheResult
20 )
21 }
22 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesDatatypes-etCrisisStatus-is.pl"}
23 }
24 }
25 }

```

Listing C.45: Messir Spec. file primarytypes-datatatypes-etCrisisStatus.msr.

C.46 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatatypes-etCrisisType.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.etCrisisType{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.etCrisisType.is():ptBoolean{
8     postF{
9       let TheResult: ptBoolean in
10      ( if
11        ( self = small
12        or self = medium
13        or self = huge
14      )
15      then (TheResult = true)
16      else (TheResult = false)
17      endif
18      result = TheResult
19    )
20  }
21 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesDatatypes-etCrisisType-is.pl"}
22 }
23 }
24 }

```

Listing C.46: Messir Spec. file primarytypes-datatatypes-etCrisisType.msr.

C.47 File ./src-gen/messir-spec/operations/concepts/primarytypes-datatypes/primarytypes-datatypes-etHumanKind.msr

```

1 package icrash.operations.concepts.primarytypes.datatypes.etHumanKind{
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 Operation Model {
6
7   operation: icrash.concepts.primarytypes.datatypes.etHumanKind.is():ptBoolean{
8     postF{
9       let TheResult: ptBoolean in
10      ( if
11        ( self = witness
12        or self = victim
13      )
14      then (TheResult = true)
15      else (TheResult = false)
16      endif
17      result = TheResult
18    )
19  }
20 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesDatatypes-etHumanKind-is.pl"}
21 }
22 }
23 }

```

```

13     or self = anonymous
14   )
15   then (TheResult = true)
16   else (TheResult = false)
17   endif
18   result = TheResult
19 }
20 prolog{"src/Operations/Concepts/PrimaryTypesClasses/PrimaryTypesDatatypes-etHumanKind-is.pl"}
21 }
22 }
23 }
```

Listing C.47: Messir Spec. file primarytypes-datatypes-etHumanKind.msr.

C.48 File ./src-gen/messir-spec/concepts/primarytypes-datatypes.msr

```

1 package icrash.concepts.primarytypes.datatypes {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.string
5 import lu.uni.lassy.messir.libraries.math
6 import lu.uni.lassy.messir.libraries.calendar
7
8 Concept Model {
9
10 Primary Types {
11
12   datatype dtAlertID extends dtString {
13     operation is():ptBoolean
14   }
15   datatype dtCrisisID extends dtString {
16     operation is():ptBoolean
17   }
18   datatype dtLogin extends dtString {
19     operation is():ptBoolean
20   }
21   datatype dtPassword extends dtString {
22     operation is():ptBoolean
23   }
24   datatype dtCoordinatorID extends dtString {
25     operation is():ptBoolean
26   }
27   datatype dtPhoneNumber extends dtString {
28     operation is():ptBoolean
29   }
30   datatype dtComment extends dtString {
31     operation is():ptBoolean
32   }
33   datatype dtLatitude extends dtReal {
34     operation is():ptBoolean
35   }
36   datatype dtLongitude extends dtReal {
37     operation is():ptBoolean
38   }
39   datatype dtGPSLocation {
40     attribute latitude: dtLatitude
41     attribute longitude: dtLongitude
42     operation is():ptBoolean
43     operation isNearTo(AGPSLocation:dtGPSLocation ):ptBoolean
44   }
45
46   enum etCrisisStatus {
47     constants["pending", "handled", "solved", "closed"]
48     operation is():ptBoolean
49   }
50   enum etAlertStatus {
51     constants["pending", "valid", "invalid"]
```

```

52     operation is():ptBoolean
53   }
54   enum etCrisisType {
55     constants["small", "medium", "huge"]
56     operation is():ptBoolean
57   }
58   enum etHumanKind {
59     constants["witness", "victim", "anonymous"]
60     operation is():ptBoolean
61   }
62
63 //Sam
64 datatype dtStatisticUserActivity{
65   attribute number: ptInteger
66   attribute time : dtTime
67 }
68 datatype dtStatisticCrisisInTime{
69   attribute number : ptInteger
70   attribute time : dtTime
71 }
72 datatype dtStatisticTypeCrisis{
73   attribute typeC : ptString
74   attribute time : dtTime
75 }
76 }
77 }
78 }
```

Listing C.48: Messir Spec. file primarytypes-datatypes.msr.

C.49 File ./src-gen/messir-spec/concepts/secondarytypes- associations.msr

```

1 package icrash.concepts.secondarytypes.associations {
2
3 Concept Model {
4
5   Secondary Types{
6
7   }
8 }
9 }
```

Listing C.49: Messir Spec. file secondarytypes-associations.msr.

C.50 File ./src-gen/messir-spec/concepts/secondarytypes- classes.msr

```

1 package icrash.concepts.secondarytypes.classes {
2
3 Concept Model {
4
5   Secondary Types{
6
7   }
8 }
9 }
```

Listing C.50: Messir Spec. file secondarytypes-classes.msr.

C.51 File ./src-gen/messir-spec/concepts/secondarytypes- datatypes.msr

```

1 package icrash.concepts.secondarytypes.datatypes {
2
3 import lu.uni.lassy.messir.libraries.primitives
4 import lu.uni.lassy.messir.libraries.string
5
6 import icrash.concepts.primarytypes.datatypes
7
8 Concept Model {
9
10 Secondary Types {
11
12 datatype dtSMS {
13     attribute value: ptString
14     operation is():ptBoolean
15 }
16 }
17 }
18 }
```

Listing C.51: Messir Spec. file secondarytypes-datatatypes.msr.

C.52 File ./src-gen/messir-spec/usecases/subfunctions-usecases.msr

```

1 package icrash.usecases.subfunctions {
2
3 import lu.uni.lassy.messir.libraries.primitives
4
5 import icrash.concepts.primarytypes.datatypes
6 import icrash.concepts.primarytypes.classes
7 import icrash.concepts.secondarytypes.datatypes
8 import lu.uni.lassy.messir.libraries.primitives
9 import lu.uni.lassy.messir.libraries.math
10 import lu.uni.lassy.messir.libraries.calendar
11 import icrash.environment.authentication
12
13 import icrash.environment
14
15 Use Case Model {
16
17 /**
18 use case system subfunction oeAddCoordinator(AdtCoordinatorID:dtCoordinatorID, AdtLogin:dtLogin,
19     AdtPassword:dtPassword) {
20     actor actAdministrator[primary,active]
21     returned messages {
22         ieCoordinatorAdded() returned to actAdministrator
23     }
24 /**
25 use case system subfunction oeAlert(
26     AetKind:etHumanKind,
27     AdtMyDate:dtDate,
28     AdtTime:dtTime,
29     AdtPhoneNumber:dtPhoneNumber,
30     AdtGPSLocation:dtGPSLocation,
31     AdtComment:dtComment) {
32     actor actComCompany[primary,active]
33     returned messages {
34         ieSmsSend(AdtPhoneNumber,AdtSMS) returned to actComCompany
35     }
36 }
37 /**
38 use case system subfunction oeInvalidateAlert(AdtAlertID:dtAlertID) {
39     actor actCoordinator[primary,active]
40     actor actComCompany[secondary,passive]
41     returned messages {
42         ieMessage(AMessage) returned to actCoordinator
43     }
44 }
45 /**
```

```

46 use case system subfunction oeCloseCrisis(AdtCrisisID:dtCrisisID) {
47   actor actCoordinator[primary,active]
48   returned messages {
49     ieMessage(AMessage) returned to actCoordinator
50   }
51 //-----
52 use case system subfunction oeCreateSystemAndEnvironment(AqtyComCompanies:ptInteger) {
53   actor actMsrCreator[primary,active]
54 }
55 //-----
56 use case system subfunction oeDeleteCoordinator(AdtCoordinatorID:dtCoordinatorID) {
57   actor actAdministrator[primary,active]
58   returned messages {
59     ieCoordinatorDeleted() returned to actAdministrator
60   }
61 }
62 //-----
63 use case system subfunction oeGetAlertsSet(AetAlertStatus:etAlertStatus) {
64   actor actCoordinator[primary,active]
65   returned messages {
66     ieSendAnAlert(ActAlert) returned to actCoordinator
67   }
68 }
69 //-----
70 use case system subfunction oeGetCrisisSet(AetCrisisStatus:etCrisisStatus) {
71   actor actCoordinator[primary,active]
72   returned messages {
73     ieSendACrisis(ActCrisis) returned to actCoordinator
74   }
75 }
76 //-----
77 use case system subfunction oeSetCrisisHandler(AdtCrisisID:dtCrisisID) {
78   actor actCoordinator[primary,active]
79   actor actCoordinator[secondary,passive]
80   actor actComCompany[secondary,passive,multiple]
81   returned messages {
82     ieMessage(AMessage)
83       returned to actCoordinator
84     ieSendAnAlert(ActAlert)
85       returned to actCoordinator
86     ieSmsSend(AdtPhoneNumber,AdtSMS)
87       returned to actComCompany
88   }
89 }
90 //-----
91 use case system subfunction oeLogin(AdtLogin:dtLogin , AdtPassword:dtPassword) {
92   actor actAuthenticated[primary,active]
93   returned messages {
94     ieConfirmCaptcha(ACaptcha) returned to actAuthenticated
95     ieGenerateCaptcha returned to actCaptchaService//Modified by Michel
96     ieMessage(AMessage) returned to actAuthenticated
97   }
98 }
99 //-----
100 use case system subfunction oeLogout() {
101   actor actAuthenticated[primary,active]
102   returned messages {
103     ieMessage(AMessage) returned to actAuthenticated
104   }
105 }
106 //-----
107 use case system subfunction oeReportOnCrisis(AdtCrisisID:dtCrisisID,AdtComment:dtComment) {
108   actor actCoordinator[primary,active]
109   returned messages {
110     ieMessage(AMessage) returned to actCoordinator
111   }
112 }
113 //-----
114 use case system subfunction oeSetClock(AcurrentClock:dtDateAndTime) {
115   actor actActivator[primary,proactive]

```

```

116 }
117 //-----
118 use case system subfunction oeSetCrisisStatus(AdtCrisisID:dtCrisisID ,AetCrisisStatus:
119   etCrisisStatus) {
120   actor actCoordinator[primary,active]
121   returned messages {
122     ieMessage(AMessage) returned to actCoordinator
123   }
124 //-----
125 use case system subfunction oeSollicitateCrisisHandling() {
126   actor actActivator[primary,proactive]
127   actor actCoordinator[secondary,passive,multiple]
128   actor actAdministrator[secondary,passive]
129   returned messages {
130     ieMessage(AMessage) returned to actCoordinator
131     //ieMessage(AMessage) returned to actAdministrator
132   }
133 }
134 //-----
135 use case system subfunction oeValidateAlert(AdtAlertID:dtAlertID) {
136   actor actCoordinator[primary,active]
137   returned messages {
138     ieMessage(AMessage) returned to actCoordinator
139   }
140 }
141
142 //Michel:
143 use case system subfunction oeSendCaptcha() {
144   actor actCaptchaService[primary, active]
145   actor actAuthenticated[secondary]
146   returned messages{
147     ieConfirmCaptcha() returned to actAuthenticated
148   }
149 }
150 use case system subfunction oeSubmitCaptcha() {
151   actor actAuthenticated[primary, active]
152   actor actCaptchaService[secondary]
153   returned messages{
154     ieMessage returned to actAuthenticated
155     ieVerifyCaptcha returned to actCaptchaService
156   }
157 }
158
159 use case system subfunction oeCaptchaInvalid() {
160   actor actCaptchaService[primary, active]
161   actor actMailingService[secondary]
162   actor actAuthenticated[secondary]
163   returned messages{
164     ieSendMail() returned to actMailingService
165     ieMessage() returned to actAuthenticated
166   }
167 }
168 use case system subfunction oeCaptchaValid() {
169   actor actCaptchaService[primary, active]
170   actor actAuthenticated[secondary]
171   returned messages{
172     ieMessage() returned to actAuthenticated
173   }
174 }
175
176 //Sam:
177 use case system subfunction oeStatistic(){
178   actor actAdministrator[primary, active]
179   actor actSystem[secondary,passive]
180   returned messages{
181     ieCallTimeAndCrisisNumber returned to actSystem
182     ieCallUserActivity returned to actSystem
183     ieCallTypeWithTimeAverage returned to actSystem
184   }

```

```

185  }
186  use case system subfunction oeUserActivityStatistic() {
187    actor actAdministrator[primary, active]
188    actor actDatabase[secondary, passive]
189
190  returned messages{
191
192  }
193 }
194 use case system subfunction oeNumberOfCrisis() {
195  actor actAdministrator[primary, active]
196  actor actDatabase[secondary, passive]
197  returned messages{
198
199  }
200 }
201 use case system subfunction oeTimeOfTypeOfCrisis() {
202  actor actAdministrator[primary, active]
203  actor actDatabase[secondary, passive]
204  actor actSystem[secondary, passive]
205  returned messages{
206    ieCallTimeAndCrisisNumber returned to actSystem
207  }
208 }
209 use case system subfunction ugSercurelyUserSystem() {
210  actor actSystem[primary, active]
211
212 }
213 use case system subfunction oeSendStatistic() {
214  actor actSystem[primary, active]
215  actor actAdministrator[secondary, passive]
216  actor actDatabase[secondary, passive]
217  returned messages{
218    ieShowStaticTimeAverage returned to actAdministrator
219    ieShowStaticUser returned to actAdministrator
220    ieShowStaticCrisis returned to actAdministrator
221  }
222 }
223
224 //Vlad:
225 use case system subfunction oeCreateAlert() {
226  actor actAuthenticated[primary, active]
227  actor actCoordinator[secondary]
228 }
229 use case system subfunction oeCreateCrisis() {
230  actor actCoordinator[primary, active]
231 }
232 use case system subfunction oeUpdateCrisis() {
233  actor actCoordinator[primary, proactive]
234 }
235 use case system subfunction oeSendNotification() {
236  actor actSystem[primary, active]
237 }
238
239 //Unidentifiable:
240 use case system subfunction oeChooseInformation() {
241  actor actSystem[primary, active]
242  actor actAuthenticated[secondary]
243 }
244
245 }
246 }
```

Listing C.52: Messir Spec. file subfunctions-usecases.msr.

C.53 File ./src-gen/messir-spec/test/tc-testcase01.msr

```

1 package lu.uni.lassy.excalibur.examples.icrash.tests.testcase01 {
2
```

```

3 import lu.uni.lassy.messir.libraries.string
4 import lu.uni.lassy.messir.libraries.primitives
5 import lu.uni.lassy.messir.libraries.math
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.concepts.primarytypes.associations
9 import icrash.concepts.primarytypes.classes
10 import icrash.concepts.primarytypes.datatypes
11 import icrash.concepts.secondarytypes.datatypes
12 import icrash.environment
13
14 Test Model{
15   test case testcase01 order 01 {
16   //-----
17     test step ts01oeCreateSystemAndEnvironment order 01 {
18       variables{
19         Creator:actMsrCreator
20         AqtyComCompanies: ptInteger
21       }
22       constraints{
23         AqtyComCompanies = 4
24       }
25       test message{
26         out:Creator sends to system actMsrCreator.outactMsrCreator.oeCreateSystemAndEnvironment(
27           AqtyComCompanies)
28       }
29       oracle{
30         constraints{
31           true
32         }
33         prolog{"src/Tests/system/01/system-sim-01-01-oeCreateSystemAndEnvironment.pl"}
34       }
35     //-----
36     test step ts02oeSetClock order 02{
37       variables{
38         TheActor:actActivator
39         ACurrentClock:dtDateAndTime
40       }
41       constraints{
42         TheActor=TheSystem.rnactActivator->any2(true)
43
44         ACurrentClock.date.year.value = 2017
45         ACurrentClock.date.month.value = 11
46         ACurrentClock.date.day.value = 24
47         ACurrentClock.time.hour.value = 15
48         ACurrentClock.time.minute.value = 20
49         ACurrentClock.time.second.value = 00
50       }
51       test message{
52         out:TheActor sends to system actActivator.outactActivator.oeSetClock(ACurrentClock)
53       }
54       oracle{
55         constraints{
56           true
57         }
58       }
59     }
60   //-----
61
62 test step ts03oeLogin order 03{
63   variables{
64     TheActor : actAdministrator
65     AdtLogin:dtLogin
66     AdtPassword:dtPassword
67   }
68   constraints{
69     TheActor=TheSystem.rnactAdministrator->any2(true)
70     AdtLogin.value.eq('icrashadmin')
71     AdtPassword.value.eq('7WXC1359')

```

```

72      }
73  test message{
74      out:TheActor sends to system actAdministrator.outactAdministrator.oeLogin(AdtLogin,AdtPassword)
75  }
76  oracle{
77      variables{
78          AMesssage:ptString
79      }
80      constraints{
81          AMesssage = 'You are logged ! Welcome ...'
82          TheActor.inactAdministrator.ieMessage(AMesssage)
83      }
84  }
85  }
86 //-----
87 test step ts04oeAddCoordinator order 04{
88      variables{
89          TheActor : actAdministrator
90          AdtCoordinatorID : dtCoordinatorID
91          AdtLogin:dtLogin
92          AdtPassword:dtPassword
93      }
94      constraints{
95          TheActor = TheSystem.rnactAdministrator->any2(true)
96          AdtCoordinatorID.value.eq('1')
97          AdtLogin.value.eq('steve')
98          AdtPassword.value.eq('pwdMessirExcalibur2017')
99      }
100     test message{
101         out:TheActor
102         sends to system actAdministrator.outactAdministrator.oeAddCoordinator
103             (AdtCoordinatorID,
104              AdtLogin,
105              AdtPassword)
106     }
107     oracle{
108         constraints{
109             TheActor.inactAdministrator.ieCoordinatorAdded()
110         }
111     }
112 }
113 //-----
114 test step ts05oeLogout order 05{
115     variables{
116         TheActor : actAdministrator
117     }
118     constraints{
119         TheActor = TheSystem.rnactAdministrator->any2(true)
120     }
121     test message{
122         out:TheActor sends to system actAdministrator.outactAdministrator.oeLogout()
123     }
124     oracle{
125         variables{
126             AMesssage:ptString
127         }
128         constraints{
129             AMesssage = 'You are logged out ! Good Bye ...'
130             TheActor.inactAdministrator.ieMessage(AMesssage)
131         }
132     }
133 }
134 //-----
135 test step ts06oeSetClock02 order 06{
136     variables{
137         TheActor:actActivator
138         ACurrentClock:dtDateAndTime
139     }
140     constraints{
141         TheActor=TheSystem.rnactActivator->any2(true)

```

```

142     ACurrentClock.date.year.value = 2017
143     ACurrentClock.date.month.value = 11
144     ACurrentClock.date.day.value = 26
145     ACurrentClock.time.hour.value = 10
146     ACurrentClock.time.minute.value = 15
147     ACurrentClock.time.second.value = 00
148 }
149 test message{
150     out:TheActor sends to system actActivator.outactActivator.oeSetClock(ACurrentClock)
151 }
152 oracle{
153     constraints{
154         true
155     }
156 }
157 }
158 //-----
159 test step ts07oeAlert1 order 07{
160     variables{
161         TheActor : actComCompany
162         AetHumanKind:etHumanKind
163         AdtDate:dtDate
164         AdtTime:dtTime
165         AdtPhoneNumber:dtPhoneNumber
166         AdtGPSLocation:dtGPSLocation
167         AdtComment:dtComment
168     }
169     constraints{
170         TheActor = TheSystem.rnactComCompany->any2(true)
171         AetHumanKind = witness
172         AdtDate.year.value = 2017
173         AdtDate.month.value = 11
174         AdtDate.day.value = 26
175         AdtTime.hour.value = 10
176         AdtTime.minute.value = 10
177         AdtTime.second.value = 16
178         AdtPhoneNumber.value = '+3524666445252'
179         AdtGPSLocation.latitude.value = 49.627675
180         AdtGPSLocation.longitude.value = 6.159590
181         AdtComment.value = '3 cars involved in an accident.'
182     }
183     test message{
184         out:TheActor
185         sends to system actComCompany.outactComCompany.oeAlert( AetHumanKind,
186                         AdtDate,
187                         AdtTime,
188                         AdtPhoneNumber,
189                         AdtGPSLocation,
190                         AdtComment)
191     }
192     oracle{
193         variables{
194             AdtSMS:dtSMS
195         }
196         constraints{
197             AdtSMS.value = 'Your alert has been registered. We will handle it and keep you informed'
198             TheActor.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
199         }
200     }
201 }
202 //-----
203 test step ts08oeSetClock03 order 08{
204     variables{
205         TheActor:actActivator
206         ACurrentClock:dtDateAndTime
207     }
208     constraints{
209         TheActor=TheSystem.rnactActivator->any2(true)
210         ACurrentClock.date.year.value = 2017
211         ACurrentClock.date.month.value = 11

```

```

212     ACurrentClock.date.day.value = 26
213     ACurrentClock.time.hour.value = 10
214     ACurrentClock.time.minute.value = 30
215     ACurrentClock.time.second.value = 00
216   }
217   test message{
218     out:TheActor sends to system actActivator.outactActivator.oeSetClock(ACurrentClock)
219   }
220   oracle{
221     constraints{
222       true
223     }
224   }
225 }
226 //-----
227 test step ts09oeSollicitateCrisisHandling order 09{
228   variables{
229     TheActor : actActivator
230   }
231   constraints{
232     TheActor = TheSystem.rnactActivator->any2(true)
233   }
234   test message{
235     out:TheActor sends to system actActivator.outactActivator.oeSollicitateCrisisHandling()
236   }
237   oracle{
238     variables{
239       TheAdministrator:actAdministrator
240       TheCoordinator:actCoordinator
241       AMesssageForCrisisHandlers:ptString
242     }
243     constraints{
244       TheAdministrator = TheSystem.rnactAdministrator->any2(true)
245       TheCoordinator = TheSystem.rnactCoordinator->any2(true)
246       AMesssageForCrisisHandlers = 'There are alerts pending since more than the defined delay. Please
REACT !'
247
248       TheAdministrator.inactAdministrator.ieMessage(AMesssageForCrisisHandlers)
249       TheCoordinator.inactAdministrator.ieMessage(AMesssageForCrisisHandlers)
250
251 /* this oracle should be written like this (not currently possible due to grammar limitations:
252
253   oracle{
254     variables{
255       TheAdministrator:actAdministrator
256       AMesssageForCrisisHandlers:ptString
257     }
258     constraints{
259       AMesssageForCrisisHandlers = 'There are alerts pending since more than the defined delay. Please
REACT !'
260       TheAdministrator = TheSystem.rnactAdministrator->any2(true)
261
262       TheSystem.rnactCoordinator->forAll(TheCoordinator:actCoordinator | TheCoordinator.
actAuthenticated.inactAuthenticated.ieMessage(AMessage))
263
264 */
265   }
266 }
267 }
268 //-----
269 test step ts10oeLogin02 order 10{
270   variables{
271     TheActor : actCoordinator
272     AdtLogin:dtLogin
273     AdtPassword:dtPassword
274   }
275   constraints{
276     TheActor = TheSystem.rnactCoordinator->select(a | a.rnctCoordinator.login.value.eq('steve'))->
any2(true)
277     AdtLogin.value.eq('steve')

```

```

278     AdtPassword.value.eq('pwdMessirExcalibur2017')
279   }
280   test message{
281     out:TheActor sends to system actAuthenticated.outactAuthenticated.oeLogin(AdtLogin,AdtPassword)
282   }
283   oracle{
284     variables{
285       AMessage:ptString
286     }
287     constraints{
288       AMessage = 'You are logged ! Welcome ...'
289       TheActor.inactAuthenticated.ieMessage(AMessage)
290     }
291   }
292 }
293 //-----
294 test step ts11oeGetCrisisSet order 11{
295   variables{
296     TheActor : actCoordinator
297     AetCrisisStatus : etCrisisStatus
298   }
299   constraints{
300     TheActor=TheSystem.rnactCoordinator
301     ->select(a | a.rnctCoordinator.login.value.eq('steve'))
302     ->any2(true)
303     AetCrisisStatus = pending
304   }
305   test message{
306     out:TheActor sends to system actCoordinator.outactCoordinator.oeGetCrisisSet(AetCrisisStatus)
307   }
308   oracle{
309 //TODO - make consistent with test step implementation by adding Prolog code for input messages
310   variables{
311     ActCrisis:ctCrisis
312   }
313   constraints{
314     TheActor.inactCoordinator.ieSendACrisis(ActCrisis)
315   }
316 }
317 }
318 //-----
319 test step ts12oeSetCrisisHandler order 12{
320   variables{
321     TheActor : actCoordinator
322     AdtCrisisID : dtCrisisID
323   }
324   constraints{
325     TheActor=TheSystem.rnactCoordinator
326     ->select(a | a.rnctCoordinator.login.value.eq('steve'))
327     ->any2(true)
328     //and AdtCrisisID.value= '1'
329   }
330   test message{
331     out:TheActor sends to system actCoordinator.outactCoordinator.oeSetCrisisHandler(AdtCrisisID)
332   }
333   oracle{
334     variables{
335       AMessage:ptString
336       AdtPhoneNumber:dtPhoneNumber
337       AdtSMS:dtSMS
338       ActAlert:ctAlert
339     }
340     TheComCompany: actComCompany
341     TheCoordinator:actCoordinator
342   }
343   constraints{
344     AMessage = 'You are now considered as handling the crisis !'
345     AdtSMS.value = 'The handling of your alert by our services is in progress !'
346     TheComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
347     TheCoordinator.inactCoordinator.ieSendAnAlert(ActAlert)

```

```

348     TheActor.inactAuthenticated.ieMessage(AMessage)
349   }
350 }
351 }
352 //-----
353 test step ts13oeSetClock04 order 13{
354   variables{
355     TheActor:actActivator
356     ACurrentClock:dtDateAndTime
357   }
358   constraints{
359     TheActor=TheSystem.rnactActivator->any2(true)
360     ACurrentClock.date.year.value = 2017
361     ACurrentClock.date.month.value = 11
362     ACurrentClock.date.day.value = 26
363     ACurrentClock.time.hour.value = 10
364     ACurrentClock.time.minute.value = 45
365     ACurrentClock.time.second.value = 00
366   }
367   test message{
368     out:TheActor sends to system actActivator.outactActivator.oeSetClock(ACurrentClock)
369   }
370   oracle{
371     constraints{
372       true
373     }
374   }
375 }
376 //-----
377 test step ts14oeValidateAlert order 14{
378   variables{
379     TheActor : actCoordinator
380     AdtAlertID : dtAlertID
381   }
382   constraints{
383     TheActor=TheSystem.rnactCoordinator
384     ->select(a | a.rnctCoordinator.login.value.eq('steve'))
385     ->any2(true)
386     //and AdtAlertID.value= '1'
387   }
388   test message{
389     out:TheActor sends to system actCoordinator.outactCoordinator.oeValidateAlert(AdtAlertID)
390   }
391   oracle{
392     variables{
393       AMessage:ptString
394     }
395     constraints{
396       AMessage = 'The Alert is now declared as valid !'
397       TheActor.actAuthenticated.inactAuthenticated.ieMessage(AMessage)
398     }
399   }
400 }
401 //-----
402 test step ts15oeAlert2 order 15{
403   variables{
404     TheActor : actComCompany
405     AetHumanKind:etHumanKind
406     AdtDate:dtDate
407     AdtTime:dtTime
408     AdtPhoneNumber:dtPhoneNumber
409     AdtGPSLocation:dtGPSLocation
410     AdtComment:dtComment
411   }
412   constraints{
413     TheActor = TheSystem.rnactComCompany->any2(true)
414     AetHumanKind = witness
415     AdtDate.year.value = 2017
416     AdtDate.month.value = 11
417     AdtDate.day.value = 26

```

```

418     AdtTime.hour.value = 10
419     AdtTime.minute.value = 20
420     AdtTime.second.value = 00
421     AdtPhoneNumber.value = '+3524666445000'
422     AdtGPSLocation.latitude.value = 49.627095
423     AdtGPSLocation.longitude.value = 6.160251
424     AdtComment.value = 'A car crash just happened.'
425   }
426   test message{
427     out:TheActor
428     sends to system actComCompany.outactComCompany.oeAlert( AetHumanKind,
429                   AdtDate,
430                   AdtTime,
431                   AdtPhoneNumber,
432                   AdtGPSLocation,
433                   AdtComment)
434   }
435   oracle{
436     variables{
437       AdtSMS:dtSMS
438     }
439     constraints{
440       AdtSMS.value = 'Your alert has been registered. We will handle it and keep you informed'
441       TheActor.actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
442     }
443   }
444 }
445 /**
446 test step ts16oeSetClock05 order 16{
447   variables{
448     TheActor:actActivator
449     ACurrentClock:dtDateAndTime
450   }
451   constraints{
452     TheActor=TheSystem.rnactActivator->any2(true)
453     ACurrentClock.date.year.value = 2017
454     ACurrentClock.date.month.value = 11
455     ACurrentClock.date.day.value = 26
456     ACurrentClock.time.hour.value = 12
457     ACurrentClock.time.minute.value = 45
458     ACurrentClock.time.second.value = 00
459   }
460   test message{
461     out:TheActor sends to system actActivator.outactActivator.oeSetClock(ACurrentClock)
462   }
463   oracle{
464     constraints{
465       true
466     }
467   }
468 }
469 /**
470 test step ts17oeSetCrisisStatus order 17{
471   variables{
472     TheActor : actCoordinator
473     AdtCrisisID : dtCrisisID
474     AetCrisisStatus : etCrisisStatus
475   }
476   constraints{
477     TheActor=TheSystem.rnactCoordinator
478     ->select(a | a.rnctCoordinator.login.value.eq('steve'))
479     ->any2(true)
480     //and AdtCrisisID.value= '1'
481     //and AetCrisisStatus = solved
482   }
483   test message{
484     out:TheActor sends to system actCoordinator.outactCoordinator.oeSetCrisisStatus(AdtCrisisID,
485     AetCrisisStatus)
486   }
486   oracle{

```

```

487     variables{
488         AMesssage:ptString
489     }
490     constraints{
491         AMesssage = 'The crisis status has been updated !'
492         TheActor.inactAuthenticated.ieMessage(AMesssage)
493     }
494 }
495 }
496 //-----
497 test step ts18oeReportOnCrisis order 18{
498     variables{
499         TheActor : actCoordinator
500         AdtCrisisID : dtCrisisID
501         AdtComment : dtComment
502     }
503     constraints{
504         TheActor=TheSystem.rnactCoordinator
505         ->select(a | a.rnctCoordinator.login.value.eq('steve'))
506         ->any2(true)
507         //and AdtCrisisID.value= '1'
508         //and AdtComment.value = '3 victims sent to hospital, 2 cars evacuated and 4 rescue unit
mobilized'
509     }
510     test message{
511         out:TheActor sends to system actCoordinator.outactCoordinator.oeReportOnCrisis(AdtCrisisID,
AdtComment)
512     }
513     oracle{
514         variables{
515             AMesssage:ptString
516         }
517         constraints{
518             AMesssage = 'The crisis comment has been updated !'
519             TheActor.inactAuthenticated.ieMessage(AMesssage)
520         }
521     }
522 }
523 //-----
524 test step ts19oeCloseCrisis order 19{
525     variables{
526         TheActor : actCoordinator
527         AdtCrisisID : dtCrisisID
528     }
529     constraints{
530         TheActor=TheSystem.rnactCoordinator
531         ->select(a | a.rnctCoordinator.login.value.eq('steve'))
532         ->any2(true)
533         //and AdtCrisisID.value= '1'
534     }
535     test message{
536         out:TheActor sends to system actCoordinator.outactCoordinator.oeCloseCrisis(AdtCrisisID)
537     }
538     oracle{
539         variables {
540             AMesssage:ptString
541         }
542         constraints{
543             AMesssage = 'The crisis is now closed !'
544             TheActor.inactAuthenticated.ieMessage(AMesssage)
545         }
546     }
547 }
548 }
549 }
550 }

```

Listing C.53: Messir Spec. file tc-testcase01.msr.

C.54 File ./src-gen/messir-spec/test/tci-testcase01-instance01.msr

```

1 package lu.uni.lassy.excalibur.examples.icrash.tests.testcase01.instance01 {
2
3 import lu.uni.lassy.messir.libraries.string
4 import lu.uni.lassy.messir.libraries.primitives
5 import lu.uni.lassy.messir.libraries.math
6 import lu.uni.lassy.messir.libraries.calendar
7
8 import icrash.concepts.primarytypes.associations
9 import icrash.concepts.primarytypes.classes
10 import icrash.concepts.primarytypes.datatypes
11 import lu.uni.lassy.excalibur.examples.icrash.tests.testcase01
12 import icrash.environment
13
14 Test Model {
15 test case instance instance01:testcase01{
16 /**
17 test step instance tsi01: testcase01.ts01oeCreateSystemAndEnvironment{
18 variables {
19 theCreator: testcase01.ts01oeCreateSystemAndEnvironment.Creator = "theCreator"
20 AqtyComCompanies : testcase01.ts01oeCreateSystemAndEnvironment.AqtyComCompanies="4"
21 }
22 oracle {
23 satisfaction = "true"
24 }
25 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
26 }
27 /**
28 test step instance tsi02: testcase01.ts02oeSetClock{
29 variables {
30 theClock: testcase01.ts02oeSetClock.TheActor = "theClock"
31 ACurrentClock : testcase01.ts02oeSetClock.ACurrentClock= "2017:11:24 - 03:20:00"
32 }
33 oracle {
34 satisfaction = "true"
35 }
36 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
37 }
38 /**
39 test step instance tsi03: testcase01.ts03oeLogin{
40 variables {
41 bill: testcase01.ts03oeLogin.TheActor="bill"
42 AdtLogin : testcase01.ts03oeLogin.AdtLogin= "icrashadmin"
43 AdtPassword : testcase01.ts03oeLogin.AdtPassword= "7WXC1359"
44 }
45 oracle {
46 satisfaction = "true"
47 received message {
48 AMessage : testcase01.ts03oeLogin.AMessage= 'You are logged ! Welcome ...'
49 tsi03.bill received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
50 }
51 }
52 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
53 }
54 /**
55 test step instance tsi04: testcase01.ts04oeAddCoordinator{
56 variables {
57 reuse tsi03.bill as testcase01.ts04oeAddCoordinator.TheActor
58 AdtCoordinatorID : testcase01.ts04oeAddCoordinator.AdtCoordinatorID = "1"
59 AdtLogin : testcase01.ts04oeAddCoordinator.AdtLogin= "steve"
60 AdtPassword : testcase01.ts04oeAddCoordinator.AdtPassword = "pwdMessirExcalibur2017"
61 }
62 oracle {
63 satisfaction = "true"
64 received message {
65 tsi03.bill received from system actAdministrator.inactAdministrator.ieCoordinatorAdded()
66 }
67 }
68 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}

```

```

69     }
70 //-----
71 test step instance tsi05: testcase01.ts05oeLogout{
72   variables {
73     reuse tsi03.bill as testcase01.ts05oeLogout.TheActor
74   }
75   oracle {
76     satisfaction = "true"
77     received message {
78       AMessage : testcase01.ts05oeLogout.AMessage= 'You are logged out ! Good Bye ...'
79       tsi03.bill received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
80     }
81   }
82   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
83 }
84 //-----
85 test step instance tsi06: testcase01.ts06oeSetClock02{
86   variables {
87     reuse tsi02.theClock as testcase01.ts06oeSetClock02.TheActor
88     ACurrentClock : testcase01.ts06oeSetClock02.ACurrentClock= "2017:11:26 - 10:15:00"
89   }
90   oracle {
91     satisfaction = "true"
92   }
93   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
94 }
95 //-----
96 test step instance tsi07: testcase01.ts07oeAlert1{
97   variables {
98     tango:testcase01.ts07oeAlert1.TheActor ="tango"
99     AetHumanKind : testcase01.ts07oeAlert1.AetHumanKind = "witness"
100    AdtDate : testcase01.ts07oeAlert1.AdtDate = "2017:11:26"
101    AdtTime : testcase01.ts07oeAlert1.AdtTime = "10:10:16"
102    AdtPhoneNumber : testcase01.ts07oeAlert1.AdtPhoneNumber = "+3524666445252"
103    AdtGPSLocation : testcase01.ts07oeAlert1.AdtGPSLocation = "49.627675:6.159590"
104    AdtComment : testcase01.ts07oeAlert1.AdtComment = "3 cars involved in an accident."
105  }
106  oracle {
107    satisfaction = "true"
108    received message {
109      AdtSMS : testcase01.ts07oeAlert1.AdtSMS= 'Your alert has been registered. We will handle it and keep you informed'
110      tsi07.tango received from system actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
111    }
112  }
113 }
114   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
115 }
116
117 //-----
118 test step instance tsi08: testcase01.ts08oeSetClock03{
119   variables {
120     reuse tsi02.theClock as testcase01.ts08oeSetClock03.ACurrentClock
121     ACurrentClock : testcase01.ts08oeSetClock03.ACurrentClock = "2017:11:26 - 10:30:00"
122   }
123   oracle {
124     satisfaction = "true"
125   }
126   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
127 }
128 //-----
129 test step instance tsi09: testcase01.ts09oeSollicitateCrisisHandling{
130   variables {
131     reuse tsi02.theClock as testcase01.ts09oeSollicitateCrisisHandling.TheActor
132     reuse tsi03.bill as testcase01.ts09oeSollicitateCrisisHandling.TheAdministrator
133   }
134   oracle {
135     satisfaction = "true"
136     received message {
137       steve:testcase01.ts09oeSollicitateCrisisHandling.TheCoordinator ="steve"

```

```

138     AMessageForCrisisHandlers : testcase01.ts09oeSollicitateCrisisHandling.
139     AMessageForCrisisHandlers= 'There are alerts pending since more than the defined delay. Please
140     REACT !'
141
142     tsi03.bill received from system actAuthenticated.inactAuthenticated.ieMessage(
143     AMessageForCrisisHandlers)
144     tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(
145     AMessageForCrisisHandlers)
146     }
147 }
148 test step instance tsi10: testcase01.ts10oeLogin02{
149   variables {
150     reuse tsi09.steve as testcase01.ts10oeLogin02.TheActor
151     AdtLogin : testcase01.ts10oeLogin02.AdtLogin = "steve"
152     AdtPassword : testcase01.ts10oeLogin02.AdtPassword= "pwdMessirExcalibur2017"
153   }
154   oracle {
155     satisfaction = "true"
156     received message {
157       AMessage : testcase01.ts10oeLogin02.AMessage= 'You are logged ! Welcome ...'
158       tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
159     }
160   }
161 }
162 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
163 }
164 -----
165 test step instance ts11: testcase01.ts11oeGetCrisisSet{
166   variables {
167     reuse tsi09.steve as testcase01.ts11oeGetCrisisSet.TheActor
168     AetCrisisStatus : testcase01.ts11oeGetCrisisSet.AetCrisisStatus = "pending"
169   }
170   oracle {
171     satisfaction = "true"
172     received message {
173       ActCrisis : testcase01.ts11oeGetCrisisSet.ActCrisis= "crisis with ID 1 details"
174       tsi09.steve received from system actCoordinator.inactCoordinator.ieSendACrisis(ActCrisis)
175     }
176   }
177   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
178 }
179 -----
180 test step instance ts12: testcase01.ts12oeSetCrisisHandler{
181   variables {
182     reuse tsi09.steve as testcase01.ts12oeSetCrisisHandler.TheActor
183     AdtCrisisID : testcase01.ts12oeSetCrisisHandler.AdtCrisisID = "1"
184
185     reuse tsi07.tango as testcase01.ts12oeSetCrisisHandler.TheComCompany
186
187   }
188   oracle {
189     satisfaction = "true"
190     received message {
191       AMessage : testcase01.ts12oeSetCrisisHandler.AMessage= 'You are now considered as handling the
192       crisis !'
193       AdtSMS : testcase01.ts12oeSetCrisisHandler.AdtSMS= 'The handling of your alert by our services
194       is in progress !'
195       AdtPhoneNumber : testcase01.ts12oeSetCrisisHandler.AdtPhoneNumber= "+3524666445252"
196
197       tsi07.tango received from system actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
198       tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
199     }
200   }
201   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
202 }
```

```

202 //-----
203 test step instance tsi13: testcase01.ts13oeSetClock04{
204   variables {
205     reuse tsi02.theClock as testcase01.ts13oeSetClock04.TheActor
206     ACurrentClock : testcase01.ts13oeSetClock04.ACurrentClock = "2017:11:26 - 10:45:00"
207   }
208   oracle {
209     satisfaction = "true"
210   }
211   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
212 }
213 //-----
214 test step instance tsi14: testcase01.ts14oeValidateAlert{
215   variables {
216     reuse tsi09.steve as testcase01.ts14oeValidateAlert.TheActor
217     AdtAlertID : testcase01.ts14oeValidateAlert.AdtAlertID = "1"
218   }
219   oracle {
220     satisfaction = "true"
221     received message {
222       AMesssage : testcase01.ts14oeValidateAlert.AMessage= 'The Alert is now declared as valid !'
223       tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMesssage)
224     }
225   }
226 }
227 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
228 }
229 //-----
230 test step instance tsi15: testcase01.ts15oeAlert2{
231   variables {
232     reuse tsi07.tango as testcase01.ts15oeAlert2.TheActor
233     AetHumanKind : testcase01.ts15oeAlert2.AetHumanKind ="witness"
234     AdtDate : testcase01.ts15oeAlert2.AdtDate= "2017:11:26"
235     AdtTime : testcase01.ts15oeAlert2.AdtTime= "10:20:00"
236     AdtPhoneNumber : testcase01.ts15oeAlert2.AdtPhoneNumber= "+3524666445000"
237     AdtGPSLocation : testcase01.ts15oeAlert2.AdtGPSLocation= "49.627095:6.160251"
238     AdtComment : testcase01.ts15oeAlert2.AdtComment= "A car crash just happened."
239   }
240   message {
241     tsi07.tango sent to system testcase01.ts15oeAlert2.out : actComCompany.outactComCompany.oeAlert(
242       AetHumanKind,AdtDate,AdtTime,AdtPhoneNumber,AdtGPSLocation,AdtComment)
243   }
244   oracle {
245     satisfaction = "true"
246     received message {
247       AdtSMS : testcase01.ts15oeAlert2.AdtSMS= 'Your alert has been registered. We will handle it and
248         keep you informed'
249       tsi07.tango received from system actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
250     }
251   }
252   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
253 }
254 //-----
255 test step instance tsi16: testcase01.ts16oeSetClock05{
256   variables {
257     reuse tsi02.theClock as testcase01.ts16oeSetClock05.TheActor
258     ACurrentClock : testcase01.ts16oeSetClock05.ACurrentClock = "2017:11:26 - 12:45:00"
259   }
260   oracle {
261     satisfaction = "true"
262     received message {
263
264   }
265   }
266   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
267 }
268 //-----
269 test step instance tsi17: testcase01.ts17oeSetCrisisStatus{

```

```

270  variables {
271    reuse tsi09.steve as testcase01.ts17oeSetCrisisStatus.TheActor
272    AdtCrisisID : testcase01.ts17oeSetCrisisStatus.AdtCrisisID = "1"
273    AetCrisisStatus : testcase01.ts17oeSetCrisisStatus.AetCrisisStatus= "solved"
274  }
275  oracle {
276    satisfaction = "true"
277    received message {
278      AMesssage : testcase01.ts17oeSetCrisisStatus.AMessage= "The crisis status has been updated !"
279      tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
280    }
281  }
282  test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
283  }
284 /**
285  test step instance tsi18: testcase01.ts18oeReportOnCrisis{
286  variables {
287    reuse tsi09.steve as testcase01.ts18oeReportOnCrisis.TheActor
288    AdtCrisisID : testcase01.ts18oeReportOnCrisis.AdtCrisisID = "1"
289    AdtComment : testcase01.ts18oeReportOnCrisis.AdtComment= "3 victims sent to hospital, 2 cars
290    evacuated and 4 rescue unit mobilized"
291  }
292  oracle {
293    satisfaction = "true"
294    received message {
295      AMesssage : testcase01.ts18oeReportOnCrisis.AMessage= 'The crisis comment has been updated !'
296      tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
297    }
298  }
299  test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
300  }
301 /**
302  test step instance tsi19: testcase01.ts19oeCloseCrisis{
303  variables {
304    reuse tsi09.steve as testcase01.ts19oeCloseCrisis.TheActor
305    AdtCrisisID : testcase01.ts19oeCloseCrisis.AdtCrisisID = "1"
306  }
307  oracle {
308    satisfaction = "true"
309    received message {
310      AMesssage : testcase01.ts19oeCloseCrisis.AMessage= 'The crisis is now closed !'
311
312      tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
313    }
314  }
315  test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
316  }
317  }
318  }
319  }
320 /**
321 /**
322 /**
323 test case instance instance01Part01:testcase01{
324 /**
325  test step instance tsi01:testcase01.ts01oeCreateSystemAndEnvironment{
326  variables {
327    theCreator:testcase01.ts01oeCreateSystemAndEnvironment.Creator = "theCreator"
328    AqtyComCompanies : testcase01.ts01oeCreateSystemAndEnvironment.AqtyComCompanies="4"
329  }
330  oracle {
331    satisfaction = "true"
332  }
333  test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
334  }
335 /**
336  test step instance tsi02: testcase01.ts02oeSetClock{
337  variables {
338    theClock:testcase01.ts02oeSetClock.TheActor = "theClock"

```

```

339     ACurrentClock : testcase01.ts02oeSetClock.ACurrentClock= "2017:11:24 - 03:20:00"
340   }
341   oracle {
342     satisfaction = "true"
343   }
344   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
345 }
346 //-----
347 test step instance tsi03: testcase01.ts03oeLogin{
348   variables {
349     bill:testcase01.ts03oeLogin.TheActor="bill"
350     AdtLogin : testcase01.ts03oeLogin.AdtLogin= "icrashadmin"
351     AdtPassword : testcase01.ts03oeLogin.AdtPassword= "7WXC1359"
352   }
353   oracle {
354     satisfaction = "true"
355     received message {
356       AMessage : testcase01.ts03oeLogin.AMessage= 'You are logged ! Welcome ...'
357       tsi03.bill received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
358     }
359   }
360   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
361 }
362 //-----
363 test step instance tsi04: testcase01.ts04oeAddCoordinator{
364   variables {
365     reuse tsi03.bill as testcase01.ts04oeAddCoordinator.TheActor
366     AdtCoordinatorID : testcase01.ts04oeAddCoordinator.AdtCoordinatorID = "1"
367     AdtLogin : testcase01.ts04oeAddCoordinator.AdtLogin= "steve"
368     AdtPassword : testcase01.ts04oeAddCoordinator.AdtPassword = "pwdMessirExcalibur2017"
369   }
370   oracle {
371     satisfaction = "true"
372     received message {
373       tsi03.bill received from system actAdministrator.inactAdministrator.ieCoordinatorAdded()
374     }
375   }
376   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
377 }
378 //-----
379 test step instance tsi05: testcase01.ts05oeLogout{
380   variables {
381     reuse tsi03.bill as testcase01.ts05oeLogout.TheActor
382   }
383   oracle {
384     satisfaction = "true"
385     received message {
386       AMassage : testcase01.ts05oeLogout.AMassage= 'You are logged out ! Good Bye ...'
387       tsi03.bill received from system actAuthenticated.inactAuthenticated.ieMessage(AMassage)
388     }
389   }
390   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
391 }
392 //-----
393 test step instance tsi06: testcase01.ts06oeSetClock02{
394   variables {
395     reuse tsi02.theClock as testcase01.ts06oeSetClock02.TheActor
396     ACurrentClock : testcase01.ts06oeSetClock02.ACurrentClock= "2017:11:26 - 10:15:00"
397   }
398   oracle {
399     satisfaction = "true"
400   }
401   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
402 }
403 //-----
404 test step instance tsi07: testcase01.ts07oeAlert1{
405   variables {
406     tango:testcase01.ts07oeAlert1.TheActor ="tango"
407     AetHumanKind : testcase01.ts07oeAlert1.AetHumanKind = "witness"
408     AdtDate : testcase01.ts07oeAlert1.AdtDate = "2017:11:26"

```

```

409 AdtTime : testcase01.ts07oeAlert1.AdtTime = "10:10:16"
410 AdtPhoneNumber : testcase01.ts07oeAlert1.AdtPhoneNumber = "+3524666445252"
411 AdtGPSLocation : testcase01.ts07oeAlert1.AdtGPSLocation = "49.627675:6.159590"
412 AdtComment : testcase01.ts07oeAlert1.AdtComment = "3 cars involved in an accident."
413 }
414 oracle {
415   satisfaction = "true"
416   received message {
417     AdtSMS : testcase01.ts07oeAlert1.AdtSMS= 'Your alert has been registered. We will handle it and
418       keep you informed'
419     tsi07.tango received from system actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
420   }
421 }
422 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
423 }
424
425 //-----
426 test step instance tsi08: testcase01.ts08oeSetClock03{
427   variables {
428     reuse tsi02.theClock as testcase01.ts08oeSetClock03.ACurrrentClock
429     ACurrentClock : testcase01.ts08oeSetClock03.ACurrrentClock = "2017:11:26 - 10:30:00"
430   }
431   oracle {
432     satisfaction = "true"
433   }
434   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
435 }
436 //-----
437 test step instance tsi09: testcase01.ts09oeSollicitateCrisisHandling{
438   variables {
439     reuse tsi02.theClock as testcase01.ts09oeSollicitateCrisisHandling.TheActor
440     reuse tsi03.bill as testcase01.ts09oeSollicitateCrisisHandling.TheAdministrator
441   }
442   oracle {
443     satisfaction = "true"
444     received message {
445       steve:testcase01.ts09oeSollicitateCrisisHandling.TheCoordinator ="steve"
446       AMesssageForCrisisHandlers : testcase01.ts09oeSollicitateCrisisHandling.
447       AMesssageForCrisisHandlers= 'There are alerts pending since more than the defined delay. Please
448       REACT !'
449       tsi03.bill received from system actAuthenticated.inactAuthenticated.ieMessage(
450         AMesssageForCrisisHandlers)
451       tsi09.steve received from system actAuthenticated.inactAuthenticated.ieMessage(
452         AMesssageForCrisisHandlers)
453     }
454   }
455
456 //-----
457 //-----
458 //-
459 test case instance instance01Part02:testcase01{
460
461 test step instance tsi10: testcase01.ts10oeLogin02{
462   variables {
463     steve : testcase01.ts10oeLogin02.TheActor
464     AdtLogin : testcase01.ts10oeLogin02.AdtLogin = "steve"
465     AdtPassword : testcase01.ts10oeLogin02.AdtPassword= "pwdMessirExcalibur2017"
466   }
467   oracle {
468     satisfaction = "true"
469     received message {
470       AMesssage : testcase01.ts10oeLogin02.AMesssage= 'You are logged ! Welcome ...'
471       steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMesssage)
472     }
473   }

```

```

474     }
475     test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
476   }
477 //-
478   test step instance ts11: testcase01.ts11oeGetCrisisSet{
479     variables {
480       reuse ts10.steve as testcase01.ts11oeGetCrisisSet.TheActor
481       AdtCrisisStatus : testcase01.ts11oeGetCrisisSet.AdtCrisisStatus = "pending"
482     }
483     oracle {
484       satisfaction = "true"
485       received message {
486         ActCrisis : testcase01.ts11oeGetCrisisSet.ActCrisis= "crisis with ID 1 details"
487         ts10.steve received from system actCoordinator.inactCoordinator.ieSendACrisis(ActCrisis)
488       }
489     }
490     test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
491   }
492 //-
493   test step instance ts12: testcase01.ts12oeSetCrisisHandler{
494     variables {
495       reuse ts10.steve as testcase01.ts12oeSetCrisisHandler.TheActor
496       AdtCrisisID : testcase01.ts12oeSetCrisisHandler.AdtCrisisID = "1"
497     }
498     oracle {
499       satisfaction = "true"
500       received message {
501         tango : testcase01.ts12oeSetCrisisHandler.TheComCompany
502         AMessage : testcase01.ts12oeSetCrisisHandler.AMessage= 'You are now considered as handling the
crisis !'
503         AdtSMS : testcase01.ts12oeSetCrisisHandler.AdtSMS= 'The handling of your alert by our services
is in progress !'
504         AdtPhoneNumber : testcase01.ts12oeSetCrisisHandler.AdtPhoneNumber= "+3524666445252"
505
506         tango received from system actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
507         ts10.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
508       }
509     }
510   }
511   test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
512 }
513 //-
514   test step instance ts13: testcase01.ts13oeSetClock04{
515     variables {
516       theClock : testcase01.ts13oeSetClock04.TheActor
517       ACurrentClock : testcase01.ts13oeSetClock04.ACurrentClock = "2017:11:26 - 10:45:00"
518     }
519     oracle {
520       satisfaction = "true"
521     }
522     test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
523   }
524 //-
525   test step instance ts14: testcase01.ts14oeValidateAlert{
526     variables {
527       reuse ts10.steve as testcase01.ts14oeValidateAlert.TheActor
528       AdtAlertID : testcase01.ts14oeValidateAlert.AdtAlertID = "1"
529     }
530     oracle {
531       satisfaction = "true"
532       received message {
533         AMessage : testcase01.ts14oeValidateAlert.AMessage= 'The Alert is now declared as valid !'
534         ts10.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
535
536       }
537     }
538     test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
539   }
540 //-
541   test step instance ts15: testcase01.ts15oeAlert2{

```

```

542 variables {
543   reuse tsil2.tango as testcase01.ts15oeAlert2.TheActor
544   AetHumanKind : testcase01.ts15oeAlert2.AetHumanKind ="witness"
545   AdtDate : testcase01.ts15oeAlert2.AdtDate= "2017:11:26"
546   AdtTime : testcase01.ts15oeAlert2.AdtTime= "10:20:00"
547   AdtPhoneNumber : testcase01.ts15oeAlert2.AdtPhoneNumber= "+3524666445000"
548   AdtGPSLocation : testcase01.ts15oeAlert2.AdtGPSLocation= "49.627095:6.160251"
549   AdtComment : testcase01.ts15oeAlert2.AdtComment= "A car crash just happened."
550 }
551 message {
552   tsil2.tango sent to system testcase01.ts15oeAlert2.out : actComCompany.outactComCompany.oeAlert(
553     AetHumanKind,AdtDate,AdtTime,AdtPhoneNumber,AdtGPSLocation,AdtComment)
554 }
555 oracle {
556   satisfaction = "true"
557   received message {
558     AdtSMS : testcase01.ts15oeAlert2.AdtSMS= 'Your alert has been registered. We will handle it and
559       keep you informed'
560     tsil2.tango received from system actComCompany.inactComCompany.ieSmsSend(AdtPhoneNumber,AdtSMS)
561   }
562 }
563 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
564 }
565 //-----
566 test step instance tsil6: testcase01.ts16oeSetClock05{
567 variables {
568   reuse tsil3.theClock as testcase01.ts16oeSetClock05.TheActor
569   ACurrentClock : testcase01.ts16oeSetClock05.ACurrentClock = "2017:11:26 - 12:45:00"
570 }
571 oracle {
572   satisfaction = "true"
573   received message {
574   }
575 }
576 }
577 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
578 }
579 //-----
580 test step instance tsil7: testcase01.ts17oeSetCrisisStatus{
581 variables {
582   reuse tsil0.steve as testcase01.ts17oeSetCrisisStatus.TheActor
583   AdtCrisisID : testcase01.ts17oeSetCrisisStatus.AdtCrisisID = "1"
584   AetCrisisStatus : testcase01.ts17oeSetCrisisStatus.AetCrisisStatus= "solved"
585 }
586 oracle {
587   satisfaction = "true"
588   received message {
589     AMesssage : testcase01.ts17oeSetCrisisStatus.AMessage= "The crisis status has been updated !"
590     tsil0.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
591   }
592 }
593 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
594 }
595 //-----
596 test step instance tsil8: testcase01.ts18oeReportOnCrisis{
597 variables {
598   reuse tsil0.steve as testcase01.ts18oeReportOnCrisis.TheActor
599   AdtCrisisID : testcase01.ts18oeReportOnCrisis.AdtCrisisID = "1"
600   AdtComment : testcase01.ts18oeReportOnCrisis.AdtComment= "3 victims sent to hospital, 2 cars
601     evacuated and 4 rescue unit mobilized"
602 }
603 oracle {
604   satisfaction = "true"
605   received message {
606     AMesssage : testcase01.ts18oeReportOnCrisis.AMessage= 'The crisis comment has been updated !'
607     tsil0.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
608   }

```

```

609     }
610     test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
611   }
612 //-
613 test step instance tsi19: testcase01.ts19oeCloseCrisis{
614   variables {
615     reuse tsi10.steve as testcase01.ts19oeCloseCrisis.TheActor
616     AdtCrisisID : testcase01.ts19oeCloseCrisis.AdtCrisisID = "1"
617   }
618   oracle {
619     satisfaction = "true"
620     received message {
621       AMessage : testcase01.ts19oeCloseCrisis.AMessage= 'The crisis is now closed !'
622     }
623     tsi10.steve received from system actAuthenticated.inactAuthenticated.ieMessage(AMessage)
624   }
625 }
626 }
627 test results {pre-protocol = "true" pre-functional = "true" post-functional = "true"}
628 }
629
630 }
631 }
632
633 }

```

Listing C.54: Messir Spec. file tci-testcase01-instance01.msr.

C.55 File

./src-gen/messir-spec/usecases/usecase-suDeployAndRun.msr

```

1 package icrash.usecases.suDeployAndRun {
2   import icrash.concepts.primarytypes.datatypes
3   import icrash.environment
4   import icrash.usecases.suGlobalCrisisHandling
5   import icrash.usecases.ugAdministrateTheSystem
6   import icrash.usecases.subfunctions
7
8   Use Case Model {
9     use case system summary suDeployAndRun() {
10       actor actAdministrator[primary,active]
11       actor actMsrCreator[secondary,active]
12       actor actCoordinator[secondary,active,multiple]
13       actor actActivator[secondary,proactive]
14       actor actComCompany[secondary,active]
15
16       reuse oeCreateSystemAndEnvironment[1..1]
17       reuse ugAdministrateTheSystem[1..*]
18       reuse suGlobalCrisisHandling[1..*]
19       reuse oeSetClock[1..*]
20       reuse oeSollicitateCrisisHandling[0..*]
21       reuse oeAlert[1..*]
22
23       step a: actMsrCreator executes oeCreateSystemAndEnvironment
24       step b: actAdministrator executes ugAdministrateTheSystem
25       step c: actComCompany executes oeAlert
26       step d: actActivator executes oeSetClock
27       step ^e: actActivator executes oeSollicitateCrisisHandling
28       step f: actCoordinator executes suGlobalCrisisHandling
29
30       ordering constraint
31         "step (a) must be always the first step."
32       ordering constraint
33         "step (f) can be executed by different actCoordinator actors."
34       ordering constraint
35         "if (e) then previously (d)."
36     }
37 //-

```

```

38 // -----
39 // -----
40 use case instance uciSimpleAndComplete : suDeployAndRun {
41   actors {
42     theCreator : actMsrCreator
43     theClock : actActivator
44     bill : actAdministrator
45     tango : actComCompany
46     steve : actCoordinator
47   }
48   use case steps {
49 // -----
50   theCreator
51   executed instanceof subfunction
52     oeCreateSystemAndEnvironment("4") {}
53 // -----
54   theClock
55   executed instanceof subfunction
56     oeSetClock("2017:11:24 - 03:20:00") {}
57 // -----
58   bill
59   executed instanceof subfunction
60     oeLogin("icrashadmin","7WXC1359"){
61       ieMessage('You are logged ! Welcome ...') returned to bill
62     }
63 // -----
64   bill
65   executed instanceof subfunction
66     oeAddCoordinator("1","steve","pwdMessirExcalibur2017") {
67       ieCoordinatorAddedreturned returned to bill
68     }
69 // -----
70   bill
71   executed instanceof subfunction
72     oeLogout{
73       ieMessage('You are logged out ! Good Bye ...') returned to bill
74     }
75 // -----
76   theClock
77   executed instanceof subfunction
78     oeSetClock("2017:11:26 - 10:15:00") {}
79 // -----
80   tango
81   executed instanceof subfunction
82     oeAlert("Twitness","2017:11:26","10:10:16","+3524666445252",
83       "49.627675:6.159590","3 cars involved in an accident."){
84       ieSmsSend("+3524666445252","Your alert has been registered. We will handle it and keep you
informed") returned to tango
85     }
86 // -----
87   theClock
88   executed instanceof subfunction
89     oeSetClock("2017:11:26 - 10:30:00") {}
90 // -----
91   theClock
92   executed instanceof subfunction
93     oeSollicitateCrisisHandling{
94       ieMessage("There are alerts pending since more than the defined delay. Please REACT !")
95       returned to bill
96       ieMessage("There are alerts pending since more than the defined delay. Please REACT !")
97       returned to steve
98     }
99 // -----
100  steve
101  executed instanceof subfunction
102    oeLogin("steve","pwdMessirExcalibur2017") {
103      ieMessage('You are logged ! Welcome ...') returned to steve
104    }
105 // -----
106  steve

```

```

107  executed instanceof subfunction
108      oeGetCrisisSet("pending"){
109          ieSendACrisis("crisis with ID 1 details") returned to steve
110      }
111 //-----
112  steve
113  executed instanceof subfunction
114      oeSetCrisisHandler("1"){
115          ieSmsSend("+3524666445252","The handling of your alert by our services is in progress !")
116          returned to tango
117          ieMessage("You are now considered as handling the crisis !")
118          returned to steve
119      }
120 //-----
121  theClock
122  executed instanceof subfunction
123      oeSetClock("2017:11:26 - 10:45:00"){}
124 //-----
125  steve
126  executed instanceof subfunction
127      oeValidateAlert("1"){
128          ieMessage('The Alert is now declared as valid !')
129          returned to steve
130      }
131 //-----
132  tango
133  executed instanceof subfunction
134      oeAlert("witness","2017:11:26","10:20:00","+3524666445000",
135          "49.627095:6.160251","A car crash just happened.")
136      ieSmsSend("+3524666445000","Your alert has been registered. We will handle it and keep you
informed") returned to tango
137  }
138 //-----
139  theClock
140  executed instanceof subfunction
141      oeSetClock("2017:11:26 - 12:45:00"){}
142 //-----
143  steve
144  executed instanceof subfunction
145      oeSetCrisisStatus("1","solved"){
146          ieMessage('The crisis status has been updated !')
147          returned to steve
148      }
149 //-----
150  steve
151  executed instanceof subfunction
152      oeReportOnCrisis("1","3 victims sent to hospital, 2 cars evacuated and 4 rescue unit
mobilized"){
153          ieMessage('The crisis comment has been updated !')
154          returned to steve
155      }
156 //-----
157  steve
158  executed instanceof subfunction
159      oeCloseCrisis("1"){
160          ieMessage('The crisis is now closed !')
161          returned to steve
162      }
163  }
164  }
165  }
166 //-----
167 //-----
168 //-----
169  use case instance uciSimpleAndCompletePart01 : suDeployAndRun{
170
171  actors {
172      theCreator : actMsrCreator
173      theClock : actActivator
174      bill : actAdministrator

```

```

175     tango : actComCompany
176     steve : actCoordinator
177   }
178   use case steps {
179   /
180     theCreator
181     executed instanceof subfunction
182       oeCreateSystemAndEnvironment("4") {}
183   /
184     theClock
185     executed instanceof subfunction
186       oeSetClock("2017:11:24 - 03:20:00") {}
187   /
188     bill
189     executed instanceof subfunction
190       oeLogin("micrashadmin","7WXC1359"){
191         ieMessage('You are logged ! Welcome ...') returned to bill
192       }
193   /
194     bill
195     executed instanceof subfunction
196       oeAddCoordinator("1","steve","pwdMessirExcalibur2017") {
197         ieCoordinatorAddedreturned returned to bill
198       }
199   /
200     bill
201     executed instanceof subfunction
202       oeLogout{
203         ieMessage('You are logged out ! Good Bye ...') returned to bill
204       }
205   /
206     theClock
207     executed instanceof subfunction
208       oeSetClock("2017:11:26 - 10:15:00") {}
209   /
210     tango
211     executed instanceof subfunction
212       oeAlert("witness","2017:11:26","10:10:16","+3524666445252",
213         "49.627675:6.159590","3 cars involved in an accident."){
214         ieSmsSend("+3524666445252","Your alert has been registered. We will handle it and keep you
informed") returned to tango
215       }
216   /
217     theClock
218     executed instanceof subfunction
219       oeSetClock("2017:11:26 - 10:30:00") {}
220   /
221     theClock
222     executed instanceof subfunction
223       oeSollicitateCrisisHandling(
224         ieMessage("There are alerts pending since more than the defined delay. Please REACT !")
225         returned to bill
226         ieMessage("There are alerts pending since more than the defined delay. Please REACT !")
227         returned to steve
228       )
229     }
230   }
231   /
232   /
233   /
234   use case instance uciSimpleAndCompletePart02 : suDeployAndRun{
235     actors {
236       theCreator : actMsrCreator
237       theClock : actActivator
238       bill : actAdministrator
239       tango : actComCompany
240       steve : actCoordinator
241     }
242     use case steps {
243

```

```

244 //-----
245     steve
246     executed instanceof subfunction
247         oeLogin("steve", "pwdMessirExcalibur2017") {
248             ieMessage('You are logged ! Welcome ...') returned to steve
249         }
250 //-----
251     steve
252     executed instanceof subfunction
253         oeGetCrisisSet("pending"){
254             ieSendACrisis("crisis with ID 1 details") returned to steve
255         }
256 //-----
257     steve
258     executed instanceof subfunction
259         oeSetCrisisHandler("1"){
260             ieSmsSend("+3524666445252", "The handling of your alert by our services is in progress !")
261             returned to tango
262             ieMessage("You are now considered as handling the crisis !")
263             returned to steve
264         }
265 //-----
266     theClock
267     executed instanceof subfunction
268         oeSetClock("2017:11:26 - 10:45:00") {}
269 //-----
270     steve
271     executed instanceof subfunction
272         oeValidateAlert("1"){
273             ieMessage('The Alert is now declared as valid !')
274             returned to steve
275         }
276 //-----
277     tango
278     executed instanceof subfunction
279         oeAlert("witness", "2017:11:26", "10:20:00", "+3524666445000",
280             "49.627095:6.160251", "A car crash just happened.")
281         ieSmsSend("+3524666445000", "Your alert has been registered. We will handle it and keep you
informed") returned to tango
282     }
283 //-----
284     theClock
285     executed instanceof subfunction
286         oeSetClock("2017:11:26 - 12:45:00") {}
287 //-----
288     steve
289     executed instanceof subfunction
290         oeSetCrisisStatus("1", "solved"){
291             ieMessage('The crisis status has been updated !')
292             returned to steve
293         }
294 //-----
295     steve
296     executed instanceof subfunction
297         oeReportOnCrisis("1", "3 victims sent to hospital, 2 cars evacuated and 4 rescue unit
mobilized")
298         ieMessage('The crisis comment has been updated !')
299         returned to steve
300     }
301 //-----
302     steve
303     executed instanceof subfunction
304         oeCloseCrisis("1"){
305             ieMessage('The crisis is now closed !')
306             returned to steve
307         }
308     }
309   }
310 }
311 }
```

312 }

Listing C.55: Messir Spec. file usecase-suDeployAndRun.msr.

C.56 File ./src-gen/messir-spec/usecases/usecase-suGlobalCrisisHandling.msr

```

1 package icrash.usecases.suGlobalCrisisHandling {
2   import lu.uni.lassy.messir.libraries.primitives
3   import icrash.environment
4   import icrash.usecases.subfunctions
5   import icrash.usecases.ugSecurelyUseSystem
6   import icrash.usecases.ugManageCrisis
7   import icrash.usecases.ugMonitor
8
9   Use Case Model {
10     use case system summary
11     suGlobalCrisisHandling() {
12       actor actCoordinator[primary,active]
13
14       reuse ugSecurelyUseSystem[1...*]
15       reuse ugMonitor[1...*]
16       reuse ugManageCrisis[1...*]
17
18       step a: actCoordinator
19         executes ugSecurelyUseSystem
20       step b: actCoordinator
21         executes ugMonitor
22       step c: actCoordinator
23         executes ugManageCrisis
24
25       ordering constraint
26         "steps (a) (b) and (c) executions are interleaved
27         (steps (b) and (c) have their protocol constrained by steps of (a))."
28       ordering constraint
29         "steps (a) (b) and (c) can be executed multiple times."
30     }
31   }

```

Listing C.56: Messir Spec. file usecase-suGlobalCrisisHandling.msr.

C.57 File ./src-gen/messir-spec/usecases/usecase-ugAdministrateTheSystem.msr

```

1 package icrash.usecases.ugAdministrateTheSystem {
2
3   import icrash.environment
4   import icrash.usecases.ugSecurelyUseSystem
5   import icrash.usecases.subfunctions
6
7   Use Case Model {
8
9     use case system usergoal
10    ugAdministrateTheSystem() {
11      actor actAdministrator[primary,active]
12
13      reuse ugSecurelyUseSystem[1...*]
14      reuse oeAddCoordinator[1...*]
15      reuse oeDeleteCoordinator[0...*]
16
17      step a: actAdministrator
18        executes ugSecurelyUseSystem
19      step b: actAdministrator
20        executes oeAddCoordinator
21      step c: actAdministrator
22        executes oeDeleteCoordinator

```

```

23
24 ordering constraint
25   "steps (a) (b) and (c) executions are interleaved
26   (steps (b) and (c) have their protocol constrained
27   by steps of (a))."
28 ordering constraint
29   "steps (a) (b) and (c) can be executed multiple times."
30 }
31 }
32 }
```

Listing C.57: Messir Spec. file usecase-ugAdministrateTheSystem.msr.

C.58 File [./src-gen/messir-spec/usecases/usecase-ugAverageTypeofCrisis.msr](#)

```

1 /*
2 * @author michm
3 * @date Mon Mar 27 11:54:54 CEST 2017
4 */
5
6 package icrash.usecases.ugAverageTypeofCrisis {
7
8 import lu.uni.lassy.messir.libraries.primitives
9 import icrash.usecases.subfunctions
10 import icrash.environment
11
12 import icrash.usecases.ugAdministrateTheSystem
13
14 Use Case Model {
15   use case system usergoal ugAverageTypeofCrisis() {
16     actor actAdministrator[primary, active]
17     actor actDatabase [primary, proactive]
18     actor actSystem[secondary, active]
19
20     reuse oeStatistic[1...*]
21     reuse ugSercurelyUserSystem[0...*]
22     reuse oeTimeOfTypeOfCrisis[0...*]
23     reuse ugAdministrateTheSystem[1...*]
24
25     step a: actSystem
26     executes ugSercurelyUserSystem()
27
28     step b: actSystem
29     executes oeStatistic()
30
31     step c : actAdministrator
32     executes oeTimeOfTypeOfCrisis()
33
34     step d : actAdministrator
35     executes ugAdministrateTheSystem()
36
37     step e : actDatabase
38     executes oeTimeOfTypeOfCrisis()
39
40     ordering constraint "at least a"
41     ordering constraint "if b then previously a"
42     ordering constraint "if c then previously b"
43     ordering constraint "if d then previously c"
44
45   }
46 }
47
48 }
```

Listing C.58: Messir Spec. file usecase-ugAverageTypeofCrisis.msr.

C.59 File ./src-gen/messir-spec/usecases/usecase-ugCrisisInTime.msr

```

1 /*
2 * @author michm
3 * @date Mon Mar 27 11:53:28 CEST 2017
4 */
5
6 package icrash.usecases.ugCrisisInTime {
7
8 import lu.uni.lassy.messir.libraries.primitives
9 import icrash.usecases.subfunctions
10 import icrash.environment
11
12 import icrash.usecases.ugAdministreTheSystem
13
14 Use Case Model {
15 use case system usergoal ugCrisisInTime() {
16 actor actAdministrator[primary, active]
17 actor actDatabase [primary, proactive]
18 actor actSystem[secondary, active]
19
20 reuse oeStatistic[1...*]
21 reuse ugSecurelyUserSystem[0...*]
22 reuse oeNumberOfCrisis[0...*]
23 reuse ugAdministreTheSystem[1...*]
24
25 step a: actSystem
26 executes ugSecurelyUserSystem()
27
28 step b: actSystem
29 executes oeStatistic()
30
31 step c : actAdministrator
32 executes oeNumberOfCrisis()
33
34 step d : actAdministrator
35 executes ugAdministreTheSystem()
36
37 step e : actDatabase
38 executes oeNumberOfCrisis()
39
40 ordering constraint "at least a"
41 ordering constraint "if b then previously a"
42 ordering constraint "if c then previously b"
43 ordering constraint "if d then previously c"
44 }
45 }
46
47 }

```

Listing C.59: Messir Spec. file usecase-ugCrisisInTime.msr.

C.60 File ./src-gen/messir-spec/usecases/usecase-ugLogin.msr

```

1 /*
2 * @author michm
3 * @date Mon Mar 27 11:29:20 CEST 2017
4 */
5
6 package icrash.usecases.ugLogin {
7
8 import lu.uni.lassy.messir.libraries.primitives
9 import icrash.usecases.subfunctions
10 import icrash.environment
11 import icrash.environment.authentication
12
13 Use Case Model {

```

```

14  use case system usergoal ugLogin() {
15    actor actAuthenticated[primary, active]
16    actor actCaptchaService[secondary, active]
17    actor actMailingService[secondary, active]
18
19    reuse oeLogin[1..1]
20    reuse oeSendCaptcha[1..1]
21    reuse oeSubmitCaptcha[1..1]
22    reuse oeCaptchaInvalid[1..1]
23    reuse oeCaptchaValid[1..1]
24
25    step a: actAuthenticated
26    executes oeLogin
27
28    step b: actCaptchaService
29    executes oeSendCaptcha
30
31    step c: actAuthenticated
32    executes oeSubmitCaptcha
33
34    step d: actCaptchaService
35    executes oeCaptchaInvalid
36
37    step e: actCaptchaService
38    executes oeCaptchaValid
39
40    ordering constraint "at least a"
41    ordering constraint "if b then previously a"
42    ordering constraint "if c then previously b"
43    ordering constraint "if d then previously c"
44    ordering constraint "if e then previously c"
45  }
46 }
47
48 }

```

Listing C.60: Messir Spec. file usecase-ugLogin.msr.

C.61 File ugManageCrisis.msr

./src-gen/messir-spec/usecases/usecase-

```

1 package icrash.usecases.ugManageCrisis {
2
3   import icrash.environment
4   import icrash.usecases.subfunctions
5
6   Use Case Model {
7
8     use case system usergoal ugManageCrisis() {
9       actor actCoordinator[primary, active]
10
11      reuse oeValidateAlert[0...*]
12      reuse oeSetCrisisStatus[0...*]
13      reuse oeSetCrisisHandler[0...*]
14      reuse oeReportOnCrisis[0...*]
15      reuse oeCloseCrisis[0...*]
16      reuse oeInvalidateAlert[0...*]
17
18      step a: actCoordinator executes oeValidateAlert
19      step b: actCoordinator executes oeSetCrisisStatus
20      step c: actCoordinator executes oeSetCrisisHandler
21      step d: actCoordinator executes oeReportOnCrisis
22      step f: actCoordinator executes oeCloseCrisis
23      step g: actCoordinator executes oeInvalidateAlert
24
25      ordering constraint "managing a crisis is doing one of the indicated use cases."
26
27    }

```

```

28
29 }
30 }
```

Listing C.61: Messir Spec. file usecase-ugManageCrisis.msr.

C.62 File ./src-gen/messir-spec/usecases/usecase-ugMonitor.msr

```

1 package icrash.usecases.ugMonitor {
2
3 import icrash.environment
4 import icrash.usecases.subfunctions
5
6 Use Case Model {
7 use case system usergoal ugMonitor() {
8 actor icrash.environment.actCoordinator[primary,active]
9
10 reuse oeGetCrisisSet[0...*]
11 reuse oeGetAlertsSet[0...*]
12
13 step a: icrash.environment.actCoordinator executes oeGetAlertsSet
14 step b: icrash.environment.actCoordinator executes oeGetCrisisSet
15 }
16 }
17 }
```

Listing C.62: Messir Spec. file usecase-ugMonitor.msr.

C.63 File ./src-gen/messir-spec/usecases/usecase-ugSecurelyUseSystem.msr

```

1 package icrash.usecases.ugSecurelyUseSystem {
2
3 import icrash.environment
4 import icrash.usecases.subfunctions
5
6 Use Case Model {
7
8 use case system usergoal
9 ugSecurelyUseSystem() {
10
11 actor actAuthenticated[primary,active]
12
13 reuse oeLogin[1..1]
14 reuse oeLogout[1..1]
15
16 step a: actAuthenticated
17   executes oeLogin
18 step b: actAuthenticated
19   executes oeLogout
20
21 ordering constraint
22 "step (a) must always precede step (b)."
23 }
24 }
25 }
```

Listing C.63: Messir Spec. file usecase-ugSecurelyUseSystem.msr.

C.64 File ./src-gen/messir-spec/usecases/usecase-ugUserActivity.msr

```

1 /*
2 * @author michm
3 * @date Mon Mar 27 11:31:30 CEST 2017
```

```

4 /*
5
6 package icrash.usecases.ugUserActivity {
7
8 import lu.uni.lassy.messir.libraries.primitives
9 import icrash.usecases.subfunctions
10 import icrash.environment
11
12 import icrash.usecases.ugAdministateTheSystem
13
14 Use Case Model {
15   use case system usergoal ugUserActivity() {
16     actor actAdministrator[primary, active]
17     actor actDatabase [primary, proactive]
18     actor actSystem[secondary, active]
19
20     reuse oeStatistic[1...*]
21     reuse ugSercurelyUserSystem[0...*]
22     reuse oeUserActivityStatistic[0...*]
23     reuse ugAdministateTheSystem[1...*]
24
25     step a: actSystem
26     executes ugSercurelyUserSystem()
27
28     step b: actSystem
29     executes oeStatistic()
30
31     step c : actAdministrator
32     executes oeUserActivityStatistic()
33
34     step d : actAdministrator
35     executes ugAdministateTheSystem()
36
37     step e : actDatabase
38     executes oeUserActivityStatistic()
39
40     ordering constraint "at least a"
41     ordering constraint "if b then previously a"
42     ordering constraint "if c then previously b"
43     ordering constraint "if d then previously c"
44
45   }
46
47 }
48
49 }

```

Listing C.64: Messir Spec. file usecase-ugUserActivity.msr.

C.65 File [./src-gen/messir-spec/usecases/usecase-ugVictimSendFamilyNotification.msr](#)

```

1 /*
2 * @author michm
3 * @date Mon Mar 27 11:36:07 CEST 2017
4 */
5
6 package icrash.usecases.ugVictimSendFamilyNotification {
7
8 import lu.uni.lassy.messir.libraries.primitives
9 import icrash.usecases.subfunctions
10 import icrash.environment
11
12 Use Case Model {
13   use case system usergoal ugVictimSendFamilyNotification() {
14     actor actSystem[primary, active]
15     actor actAuthenticated[secondary, active]
16     actor actCoordinator[secondary, proactive]

```

```

17
18 reuse oeCreateAlert[1..*]
19 reuse oeCreateCrisis[1..1]
20 reuse oeUpdateCrisis[0..*]
21
22 step a: actAuthenticated
23 executes oeCreateAlert()
24
25 step b: actCoordinator
26 executes oeCreateAlert()
27
28 step c: actCoordinator
29 executes oeCreateCrisis()
30
31 step d: actSystem
32 executes oeChooseInformation()
33
34 step e: actCoordinator
35 executes oeUpdateCrisis()
36
37 ordering constraint "if c then previously a or b"
38 ordering constraint "if d then previously a or b"
39 ordering constraint "if e then previously a or b"
40 }
41 }
42
43 }

```

Listing C.65: Messir Spec. file usecase-ugVictimSendFamilyNotification.msr.

C.66 File ./src-gen/messir-spec/usecases/usecase-ugWitnessSendFamilyNotification.msr

```

1 /*
2 * @author michm
3 * @date Mon Mar 27 11:35:08 CEST 2017
4 */
5
6 package icrash.usecases.ugWitnessSendFamilyNotification {
7
8 import lu.uni.lassy.messir.libraries.primitives
9 import icrash.usecases.subfunctions
10 import icrash.environment
11
12 Use Case Model {
13 use case system usergoal ugWitnessSendFamilyNotification() {
14 actor actSystem[primary, active]
15 actor actAuthenticated[secondary, active]
16 actor actCoordinator[secondary, proactive]
17
18 reuse oeCreateAlert[1..*]
19 reuse oeCreateCrisis[1..1]
20 reuse oeUpdateCrisis[0..*]
21
22 step a: actAuthenticated
23 executes oeCreateAlert()
24
25 step b: actCoordinator
26 executes oeCreateAlert()
27
28 step c: actCoordinator
29 executes oeCreateCrisis()
30
31 step d: actSystem
32 executes oeChooseInformation()
33
34 step e: actCoordinator
35 executes oeUpdateCrisis()

```

```

36
37 ordering constraint "if c then previously a or b"
38 ordering constraint "if d then previously a or b"
39 ordering constraint "if e then previously a or b"
40 }
41 }
42
43 }

```

Listing C.66: Messir Spec. file usecase-ugWitnessSendFamilyNotification.msr.

C.67 File ./src-gen/messir-spec/usecases/usecaseinstance-uciugLogin.msr

```

1 /*
2 * @author michm
3 * @date Mon Mar 27 13:56:35 CEST 2017
4 */
5
6 package usecases.uciugLogin {
7
8 import lu.uni.lassy.messir.libraries.primitives
9 import icrash.environment
10 import icrash.usecases.subfunctions
11 import icrash.usecases.ugLogin
12 import icrash.environment.authentication
13
14 Use Case Model {
15   use case instance uciugLoginSuccess : ugLogin{
16     actors {
17       MKremer : actAuthenticated
18     }
19     use case steps {
20       MKremer executed instanceof subfunction oeLogin("mkremer003", "Raichu124"){
21         ieMessage("You are now logged in!") returned to MKremer
22       }
23     }
24   }
25 }
26 use case instance uciugLoginFailure : ugLogin{
27   actors {
28     MKremer : actAuthenticated
29   }
30   use case steps {
31     MKremer executed instanceof subfunction oeLogin("mkremer003", "Raichu124"){
32       ieMessage("Wrong user name or password. Try again.") returned to MKremer
33     }
34   }
35 }
36 }
37 use case instance uciugLoginCaptchaSuccess : ugLogin{
38   actors {
39     MKremer : actAuthenticated
40     CaptchaService : actCaptchaService
41   }
42   use case steps {
43     MKremer executed instanceof subfunction oeLogin("mkremer003", "Raichu124") {
44       ieGenerateCaptcha() returned to CaptchaService
45     }
46     CaptchaService executed instanceof subfunction oeSendCaptcha("Captcha test", "Captcha answer") {
47       ieConfirmCaptcha("Captcha test") returned to MKremer
48     }
49     MKremer executed instanceof subfunction oeSubmitCaptcha("Captcha user response") {
50       ieVerifyCaptcha("Captcha user response") returned to CaptchaService
51     }
52     CaptchaService executed instanceof subfunction oeCaptchaValid("Captcha id"){
53       ieMessage("You are now logged in!") returned to MKremer
54     }

```

```

55     }
56   }
57 use case instance uciugLoginCaptchaFailure : ugLogin{
58   actors {
59     MKremer : actAuthenticated
60     CaptchaService : actCaptchaService
61   }
62 use case steps {
63   MKremer executed instanceof subfunction oeLogin("mkremer003", "Raichu124") {
64     ieGenerateCaptcha() returned to CaptchaService
65   }
66   CaptchaService executed instanceof subfunction oeSendCaptcha("Captcha test", "Captcha answer") {
67     ieConfirmCaptcha("Captcha test") returned to MKremer
68   }
69   MKremer executed instanceof subfunction oeSubmitCaptcha("Captcha user response") {
70     ieVerifyCaptcha("Captcha user response") returned to CaptchaService
71   }
72   CaptchaService executed instanceof subfunction oeCaptchaInvalid("Captcha id"){
73     ieMessage("Your submitted captcha response is invalid. Try again.") returned to MKremer
74   }
75 }
76 }
77 }
78 use case instance uciugLoginCaptchaToleranceExceeded : ugLogin{
79   actors {
80     MKremer : actAuthenticated
81     CaptchaService : actCaptchaService
82     GMail : actMailingService
83   }
84 use case steps {
85   MKremer executed instanceof subfunction oeLogin("mkremer003", "Raichu124") {
86     ieGenerateCaptcha() returned to CaptchaService
87   }
88   CaptchaService executed instanceof subfunction oeSendCaptcha("Captcha test", "Captcha answer") {
89     ieConfirmCaptcha("Captcha test") returned to MKremer
90   }
91   MKremer executed instanceof subfunction oeSubmitCaptcha("Captcha user response") {
92     ieVerifyCaptcha("Captcha user response") returned to CaptchaService
93   }
94   CaptchaService executed instanceof subfunction oeCaptchaInvalid("Captcha id"){
95     ieSendMail("michel.kremer.003@student.uni.lu", "Your account has been locked", "Notification
96       and unblocking instructions (a bit too long to write here...)") returned to GMail
97     ieMessage("Your user name will be blocked for logging in. Please contact an administrator.")
98   }
99 }
100 }
101 use case instance uciugLoginRejected : ugLogin{
102   actors {
103     MKremer : actAuthenticated
104   }
105 use case steps {
106   MKremer executed instanceof subfunction oeLogin("mkremer003", "Raichu124"){
107     ieMessage("The requested user is blocked from logging in") returned to MKremer
108   }
109 }
110 }
111 }
112 }
113 }
114 }

```

Listing C.67: Messir Spec. file usecaseinstance-uciugLogin.msr.

C.68 File ./src-gen/messir-spec/usecases/usecaseinstance-ugAverageTypeofCrisis-uciugStatisticAvergeTypeofCrisis.msr

```

1 package usecases.uciugAverageTypeofCrisis {

```

```

2 import icrash.usecases.ugAverageTypeofCrisis
3 import icrash.environment
4 import icrash.usecases.subfunctions
5
6 Use Case Model {
7
8 use case instance uciugStatisticAverageTypeofCrisis : ugAverageTypeofCrisis{
9   actors {
10     User : actAdministrator
11     Database : actDatabase
12   }
13   use case steps {
14     User executed instanceof subfunction oeStatistic{
15       ieCallTypeWithTimeAverage() returned to Database
16     }
17     Database executed instanceof subfunction oeSendStatistic("For the average time for the different
18       type of crises"){
19       ieShowStatisticTimeAverage() returned to User
20     }
21   }
22 }
23 }
24 }
```

Listing C.68: Messir Spec. file usecaseinstance-ugAverageTypeofCrisis-uciugStatisticAvergeTypeofCrisis.msr.

C.69 File [./src-gen/messir-spec/usecases/usecaseinstance-ugCrisisInTime-uciugStatisticCrisisInTime.msr](#)

```

1 package usecases.uciugCrisisInTime {
2   import icrash.usecases.ugCrisisInTime
3   import icrash.environment
4   import icrash.usecases.subfunctions
5
6 Use Case Model {
7
8 use case instance uciugStatisticCrisisInTime : ugCrisisInTime{
9   actors {
10     User : actAdministrator
11     Database : actDatabase
12   }
13   use case steps {
14     User executed instanceof subfunction oeStatistic{
15       ieCallTimeAndCrisisNumber() returned to Database
16     }
17     Database executed instanceof subfunction oeSendStatistic("For the number of cisises in time for
18       the different type of crisis"){
19       ieShowStatisticCrisis() returned to User
20     }
21   }
22 }
23 }
24 }
```

Listing C.69: Messir Spec. file usecaseinstance-ugCrisisInTime-uciugStatisticCrisisInTime.msr.

C.70 File [./src-gen/messir-spec/usecases/usecaseinstance-ugSecurelyUseSystem-uciugSecurelyUseSystem.msr](#)

```

1 package usecases.uciugSecurelyUseSystem {
2   import icrash.usecases.ugSecurelyUseSystem
3   import icrash.usecases.ugSecurelyUseSystem
4   import icrash.concepts.primarytypes.datatypes
```

```

5 import icrash.environment
6 import icrash.usecases.suGlobalCrisisHandling
7 import icrash.usecases.ugAdministrateTheSystem
8 import icrash.usecases.subfunctions
9
10 Use Case Model {
11
12 //-----
13 use case instance uciugSecurelyUseSystem : ugSecurelyUseSystem {
14   actors {
15     bill:actAuthenticated
16   }
17   use case steps {
18   /**
19    * bill
20    * executed instanceof subfunction
21    * oeLogin("icrashadmin","7WXC1359"){
22    *   ieMessage('You are logged ! Welcome ...') returned to bill
23    * }
24   /**
25    * bill
26    * executed instanceof subfunction
27    * oeLogout{
28    *   ieMessage('You are logged out ! Good Bye ...') returned to bill
29    * }
30  }
31 }
32 }
33 }

```

Listing C.70: Messir Spec. file usecaseinstance-ugSecurelyUseSystem-uciugSecurelyUseSystem.msr.

C.71 File ./src-gen/messir-spec/usecases/usecaseinstance-ugUserActivity-uciugUserActivity.msr

```

1 package usecases.uciugUserActivity {
2   import icrash.usecases.ugUserActivity
3   import icrash.environment
4   import icrash.usecases.subfunctions
5
6   Use Case Model {
7
8     use case instance uciugUserActivity : ugUserActivity{
9       actors {
10         User : actAdministrator
11         Database : actDatabase
12
13       }
14       use case steps {
15         User executed instanceof subfunction oeStatistic{
16           ieCallUserActivity() returned to Database
17         }
18         Database executed instanceof subfunction oeSendStatistic("Statistic for the user activity"){
19           ieShowStatisticUser() returned to User
20         }
21       }
22     }
23   }
24 }

```

Listing C.71: Messir Spec. file usecaseinstance-ugUserActivity-uciugUserActivity.msr.

C.72 File ./src-gen/messir-spec/usecases/usecaseinstance-ugVictimSendFamilyNotification-uciugVictimSendFamilyNotification.msr

```

1 package usecases.uciugVictimSendFamilyNotification {

```

```

2 import icrash.usecases.ugVictimSendFamilyNotification
3 import icrash.environment
4 import icrash.usecases.subfunctions
5
6 Use Case Model {
7
8 use case instance uciugVictimSendFamilyNotification : ugVictimSendFamilyNotification{
9   actors {
10     User : actAuthenticated
11     Coordinator : actCoordinator
12     System : actSystem
13   }
14   use case steps {
15     User executed instanceof subfunction oeCreateAlert("Chose if an alert will be sent to the family
16       ")
17   }
18   Coordinator executed instanceof subfunction oeCreateAlert() {
19
20   }
21   Coordinator executed instanceof subfunction oeCreateCrisis() {
22
23   }
24   Coordinator executed instanceof subfunction oeUpdateCrisis() {
25
26   }
27   System executed instanceof subfunction oeSendNotification() {
28
29   }
30 }
31 }
32 }
33 }
```

Listing C.72: Messir Spec. file
usecaseinstance-ugVictimSendFamilyNotification-uciugVictimSendFamilyNotification.msr.

C.73 File [./src-gen/messir-spec/usecases/usecaseinstance-ugWitnessSendFamilyNotification-uciugWitnessSendFamilyNotification](#)

```

1 package usecases.uciugWitnessSendFamilyNotification {
2   import icrash.usecases.ugWitnessSendFamilyNotification
3   import icrash.environment
4   import icrash.usecases.subfunctions
5
6   Use Case Model {
7
8     use case instance uciugWitnessSendFamilyNotification : ugWitnessSendFamilyNotification{
9       actors {
10         User : actAuthenticated
11         Coordinator : actCoordinator
12         System : actSystem
13       }
14     }
15     use case steps {
16       User executed instanceof subfunction oeCreateAlert("Add name and surname of the victim")
17     }
18     Coordinator executed instanceof subfunction oeCreateAlert() {
19
20     }
21     Coordinator executed instanceof subfunction oeCreateCrisis() {
22
23     }
24     Coordinator executed instanceof subfunction oeUpdateCrisis() {
25
26     }
27     System executed instanceof subfunction oeSendNotification() {
```

```
29
30      }
31      }
32      }
33      }
34 }
```

Listing C.73: Messir Spec. file
usecaseinstance-ugWitnessSendFamilyNotification-uciugWitnessSendFamilyNotification.msr.

Appendix D

Listing of the Prolog Files Referenced in the Operation Model Specification

D.1

File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactActivatorSetClock.pl

```
1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactActivator,
7    oeSetClock,
8    [preProtocol,Self,
9     AcurrentClock
10    ],
11    []):-!
12/* Pre Protocol:*/
13/* PreP01 */
14 msrVar(ctState,TheSystem),
15 msrVar(ptBoolean,AvpStarted),
16
17 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
18
19 msrNav([Self],[rnActor,rnSystem,vpStarted],[AvpStarted]),
20 AvpStarted = [ptBoolean,true],
21
22 msrNav([TheSystem],
23     [clock,lt,[AcurrentClock]],
24     [[ptBoolean,true]]))
25 .
26
27msrop(outactActivator,
28    oeSetClock,
29    [preFunctional,Self,
30     AcurrentClock
31    ],
32    []):-!
33/* Pre Functional:*/
34/* PreF01 */
35true.
36
37msrop(outactActivator,
38    oeSetClock,
39    [post,Self,
40     AcurrentClock
41    ],
42    []):-!
43
```

```

44 msrVar(ctState,TheSystem),
45
46 /* Post Functional:*/
47
48 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
49
50 /* PostF01 */
51 msrNav([TheSystem],
52     [msmAtPost,clock],
53     [AcurrentClock]),
54
55 /* Post Protocol:*/
56 /* PostP01 */
57 true
58 .

```

Listing D.1: Prolog file outactActivator-oeSetClock.pl.

D.2 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactActivator-oeSollicitateCrisisHandling.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6
7msrop(outactActivator,
8    oeSollicitateCrisisHandling,
9    [preProtocol,Self
10   ],
11   []):-!
12/* Pre Protocol:*/
13 msrVar(ctState,TheSystem),
14 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
15
16 msrVarCol(ctCrisis,_,ColctCrisisToHandle),
17
18/* PreP01 */
19 msrNav([TheSystem],
20     [vpStarted],
21     [[ptBoolean,true]]),
22
23/* PreP02 */
24 msrNav([TheSystem],
25     [rnctCrisis,msrSelect,
26      handlingDelayPassed,[]]
27   ],
28   ColctCrisisToHandle),
29
30 msrNav(ColctCrisisToHandle,
31     [msrSize,geq,[[ptInteger,1]]],
32     [[ptBoolean,true]]),
33.
34
35msrop(outactActivator,
36    oeSollicitateCrisisHandling,
37    [preFunctional,Self
38   ],
39   []):-!
40/* Pre Functional:*/
41/* PreF01 */
42true.
43
44msrop(outactActivator,
45    oeSollicitateCrisisHandling,
46    [post,Self
47   ],

```

```

48      []):-  

49  

50 msrVar(ctState,TheSystem),  

51 msrVar(dtComment,AMessageForCrisisHandlers),  

52 msrVar(dtDateAndTime, TheClock),  

53 msrVarCol(ctCrisis,_,ColctCrisisToAllocateIfPossible),  

54  

55 /* Post Functional:*/  

56 msrNav([Self],[rnActor,rnSystem],[TheSystem]),  

57  

58 /* PostF01 */  

59 msrNav([TheSystem],  

60     [rnctCrisis,msrSelect,  

61      maxHandlingDelayPassed, []  

62    ],  

63    ColctCrisisToAllocateIfPossible),  

64  

65msrNav(ColctCrisisToAllocateIfPossible,  

66     [msrForAll,isAllocatedIfPossible,[],  

67     [[ptBoolean,true]]],  

68  

69 /* PostF02 */  

70 msrNav([TheSystem],  

71     [rnctCrisis,msrSelect,  

72      handlingDelayPassed, []  

73    ],  

74    ColctCrisisToHandle),  

75  

76 msrNav(ColctCrisisToHandle,  

77     [msrColSubtract,[ColctCrisisToAllocateIfPossible]  

78   ],  

79    ColctCrisisToRemind),  

80  

81 (msrNav(ColctCrisisToRemind,  

82     [msrSize,geq,[[ptInteger,1]]],  

83     [[ptBoolean,true]])  

84 -> (msrNav([AMessageForCrisisHandlers],  

85     [value],  

86     [[ptString,'There are alerts pending since more than the defined delay. Please REACT !']] ),  

87  

88 msrNav([TheSystem],  

89     [rnactAdministrator,rnInterfaceIN,  

90      ieMessage, [AMessageForCrisisHandlers]  

91    ],  

92    [[ptBoolean,true]]),  

93  

94 msrNav([TheSystem],  

95     [rnactCoordinator,msrForAll,rnInterfaceIN,  

96      ieMessage, [AMessageForCrisisHandlers]  

97    ],  

98    [[ptBoolean,true]]))  

99 )  

100 ; true  

101 ),  

102  

103/* Post Protocol:*/  

104/* PostP01 */  

105 msrNav([TheSystem],  

106     [clock],  

107     [TheClock]),  

108  

109 msrNav([TheSystem],  

110     [msmAtPost,vpLastReminder],  

111     [TheClock])  

112 .

```

Listing D.2: Prolog file outactActivator-oeSollicitateCrisisHandling.pl.

D.3 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactAdm oeAddCoordinator.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5%-----%
6msrop(outactAdministrator,
7    oeAddCoordinator,
8    [preProtocol,Self,
9     AdtCoordinatorID,
10    AdtLogin,
11    AdtPassword
12    ],
13    []):-!
14/* Pre Protocol:*/
15 msrVar(ctState,TheSystem),
16 msrVar(actAdministrator,TheActor),
17 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
18 msrNav([Self],[rnActor],[TheActor]),
19 .
20/* PreP01 */
21 msrNav([TheSystem],
22     [vpStarted],
23     [[ptBoolean,true]]),
24 .
25/* PreP02 */
26 msrNav([TheActor],
27     [rnctAuthenticated,vpIsLogged],
28     [[ptBoolean,true]]),
29 .
30 .
31 .
32msrop(outactAdministrator,
33    oeAddCoordinator,
34    [preFunctional,Self,
35     AdtCoordinatorID,
36     AdtLogin,
37     AdtPassword
38    ],
39    []):-!
40/* Pre Functional:*/
41 msrVar(ctState,TheSystem),
42 msrVar(actAdministrator,TheActor),
43 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
44 msrNav([Self],[rnActor],[TheActor]),
45/* PreF01 */
46 msrNav([TheSystem],
47     [rnctCoordinator,
48      msrSelect,id,eq,[AdtCoordinatorID]],
49     ColctCoordinators),
50 msrNav(ColctCoordinators,
51     [msrIsEmpty],
52     [[ptBoolean,true]]),
53 .
54 .
55msrop(outactAdministrator,
56    oeAddCoordinator,
57    [post,Self,
58     AdtCoordinatorID,
59     AdtLogin,
60     AdtPassword
61    ],
62    []):-!
63 .
64/* Post Functional:*/
65 msrVar(ctState,TheSystem),
66 msrVar(actAdministrator,TheActor),

```

```

67 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
68 msrNav([Self],[rnActor],[TheActor]),
69
70 msrVar(actCoordinator,TheactCoordinator),
71 msrVar(ctCoordinator,ThectCoordinator),
72
73 /* PostF01 */
74 msrNav([TheactCoordinator],
75     [init,[]],
76     [[ptBoolean,true]]),
77
78 /* PostF02 */
79 msrNav([ThectCoordinator],
80     [init,[AdtCoordinatorID,AdtLogin,AdtPassword]],
81     [[ptBoolean,true]]),
82
83 /* PostF03 */
84 msrNav([TheactCoordinator],
85     [msmAtPost,rnctCoordinator],
86     [ThectCoordinator]),
87
88 /* PostF04 */
89 msrNav([ThectCoordinator],
90     [msmAtPost,rnactAuthenticated],
91     [TheactCoordinator]),
92
93 /* PostF05 */
94 msrNav([TheActor],
95     [rnInterfaceIN,
96     ieCoordinatorAdded,[]],
97     [[ptBoolean,true]]),
98
99 /* Post Protocol:*/
100 /* PostP01 */
101 true
102 .

```

Listing D.3: Prolog file outactAdministrator-oeAddCoordinator.pl.

D.4 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactAdministrator-oeDeleteCoordinator.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactAdministrator,
7    oeDeleteCoordinator,
8    [preProtocol,Self,
9     AdtCoordinatorID
10    ],
11    []):-
12/* Pre Protocol:*/
13 msrVar(ctState,TheSystem),
14 msrVar(actAdministrator,TheActor),
15 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
16 msrNav([Self],[rnActor],[TheActor]),
17
18/* PreP01 */
19 msrNav([TheSystem],
20     [vpStarted],
21     [[ptBoolean,true]]),
22
23 msrNav([TheActor],
24     [rnctAuthenticated,vpIsLogged],
25     [[ptBoolean,true]]))
26.

```

```

27
28msrop(outactAdministrator,
29    oeDeleteCoordinator,
30    [preFunctional,Self,
31     AdtCoordinatorID
32    ],
33    []):-!
34/* Pre Functional:*/
35 msrVar(ctState,TheSystem),
36 msrVar(actAdministrator,TheActor),
37 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
38 msrNav([Self],[rnActor],[TheActor]),
39
40/* PreF01 */
41 msrNav([TheSystem],
42     [rnctCoordinator,
43      msrSelect,id,eq,[AdtCoordinatorID]],
44     ColctCoordinators),
45
46 msrNav(ColctCoordinators,
47     [msrSize,eq,[[ptInteger,1]]],
48     [[ptBoolean,true]]).
49
50msrop(outactAdministrator,
51    oeDeleteCoordinator,
52    [post,Self,
53     AdtCoordinatorID
54    ],
55    []):-!
56
57/* Post Functional:*/
58 msrVar(ctState,TheSystem),
59 msrVar(actAdministrator,TheActor),
60 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
61 msrNav([Self],[rnActor],[TheActor]),
62
63/* PostF01 */
64 msrNav([TheSystem],
65     [rnctCoordinator,
66      msrSelect,id,eq,[AdtCoordinatorID]],
67     [ThectCoordinator]),
68
69 msrNav([ThectCoordinator],
70     [rnactCoordinator,msrForAll,msrIsKilled],
71     [[ptBoolean,true]]),
72
73 msrNav([ThectCoordinator],
74     [msrIsKilled],
75     [[ptBoolean,true]]),
76
77 /* PostF02 */
78 msrNav([TheActor],
79     [rnInterfaceIN,
80      ieCoordinatorDeleted,[]]
81    ],
82    [[ptBoolean,true]]),
83
84 /* Post Protocol:*/
85/* PostP01 */
86 true
87 .

```

Listing D.4: Prolog file outactAdministrator-oeDeleteCoordinator.pl.

D.5 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactAdministrator-oeLogin.pl

%%%%%%%%%%%%%

```

2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5%-----%
6msrop(outactAuthenticated,
7    oeLogin,
8    [preProtocol,Self,
9     AdtLogin,
10    AdtPassword
11    ],
12    []):-.
13/* Pre Protocol:*/
14 msrVar(ctState,TheSystem),
15 msrVar(actAuthenticated,TheactAuthenticated),
16 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
17 msrNav([Self],[rnActor],[TheactAuthenticated]),
18 .
19 /* PreP01 */
20 msrNav([TheSystem],
21     [vpStarted],
22     [[ptBoolean,true]]),
23 .
24 msrNav([TheactAuthenticated],
25     [rnctAuthenticated,vpisLogged],
26     [[ptBoolean,false]])
27 .
28
29msrop(outactAuthenticated,
30    oeLogin,
31    [preFunctional,Self,
32     AdtLogin,
33     AdtPassword
34     ],
35    []):-.
36/* Pre Functional:*/
37/* PreF01 */
38true
39.
40
41msrop(outactAuthenticated,
42    oeLogin,
43    [post,Self,
44     AdtLogin,
45     AdtPassword
46     ],
47    []):-.
48
49 msrVar(ctState,TheSystem),
50 msrVar(actAuthenticated,TheactAuthenticated),
51 .
52 msrVar(ptString,AptStringMessageForTheactAuthenticated),
53 msrVar(ptString,AptStringMessageForTheactAdministrator),
54 .
55/* Post Functional:*/
56
57 msrNav([Self],[rnActor],[TheactAuthenticated]),
58 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
59 .
60/* PostF01 */
61
62 ( (msrNav([TheactAuthenticated],
63            [rnctAuthenticated,pwd],
64            [AdtPassword]),
65   msrNav([TheactAuthenticated],
66            [rnctAuthenticated,login],
67            [AdtLogin])
68 )
69 -> ( msrNav([AptStringMessageForTheactAuthenticated],
70              [eq,[[ptString,'You are logged ! Welcome ...']]],
71              [[ptBoolean,true]]),

```

```

72     msrNav([TheactAuthenticated],
73         [rnInterfaceIN,
74          ieMessage, [AptStringMessageForTheactAuthenticated]],
75          [[ptBoolean,true]])
76    )
77 ; ( msrNav([AptStringMessageForTheactAuthenticated],
78         [eq,[[ptString,'Wrong identification information ! Please try again ...']]],,
79         [[ptBoolean,true]]),
80     msrNav([TheactAuthenticated],
81         [rnInterfaceIN,
82          ieMessage, [AptStringMessageForTheactAuthenticated]],
83          [[ptBoolean,true]]),
84
85     msrNav([AptStringMessageForTheactAdministrator],
86         [eq,[[ptString,'Intrusion tentative !']]],,
87         [[ptBoolean,true]]),
88     msrNav([TheSystem],
89         [rnactAdministrator,rnInterfaceIN,
90          ieMessage, [AptStringMessageForTheactAdministrator]],
91          [[ptBoolean,true]])
92    )
93 ),
94
95 /* Post Protocol:*/
96/* PostP01 */
97 ( (msrNav([TheactAuthenticated],
98     [rnctAuthenticated,pwd],
99     [AdtPassword]),
100 msrNav([TheactAuthenticated],
101     [rnctAuthenticated,login],
102     [AdtLogin])
103 )
104 -> (msrNav([TheactAuthenticated],
105     [rnctAuthenticated,msmAtPost,vpIsLogged],
106     [[ptBoolean,true]])
107   )
108 ; true
109 )
110 .

```

Listing D.5: Prolog file outactAuthenticated-oeLogin.pl.

D.6 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactAuthenticated-oeLogout.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactAuthenticated,
7    oeLogout,
8    [preProtocol,Self
9     ],
10    []):- 
11/* Pre Protocol:*/
12 msrVar(ctState,TheSystem),
13 msrVar(actAuthenticated,TheActor),
14 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
15 msrNav([Self],[rnActor],[TheActor]),
16
17/* PreP01 */
18 msrNav([TheSystem],
19     [vpStarted],
20     [[ptBoolean,true]]),
21
22 msrNav([TheActor],
23     [rnctAuthenticated,vpIsLogged],

```

```

24     [[ptBoolean,true]]) )
25 .
26
27msrop(outactAuthenticated,
28     oeLogout,
29     [preFunctional,Self
30     ],
31     []):- 
32/* Pre Functional:*/
33/* PreF01 */
34true
35.
36
37msrop(outactAuthenticated,
38     oeLogout,
39     [post,Self
40     ],
41     []):- 
42
43 msrVar(ctState,TheSystem),
44 msrVar(actAuthenticated,TheactAuthenticated),
45
46 msrVar(ptString,AptStringMessageForTheactAuthenticated),
47
48/* Post Functional:*/
49 msrNav([Self],[rnActor],[TheactAuthenticated]),
50 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
51
52/* PostF01 */
53 msrNav([AptStringMessageForTheactAuthenticated],
54     [eq,[[ptString,'You are logged out ! Good Bye ...']]], 
55     [[ptBoolean,true]]),
56 msrNav([TheactAuthenticated],
57     [rnInterfaceIN,
58      ieMessage,[AptStringMessageForTheactAuthenticated]],
59     [[ptBoolean,true]]),
60
61 /* Post Protocol:*/
62/* PostP01 */
63msrNav([TheactAuthenticated],
64     [rnctAuthenticated,msmAtPost,vpIsLogged],
65     [[ptBoolean,false]])
66.

```

Listing D.6: Prolog file outactAuthenticated-oeLogout.pl.

D.7 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactComCoeAlert.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6nico(A):-
7 trace,
8 write('here'),
9 write('\n').
10
11msrop(outactComCompany,
12     oeAlert,
13     [preProtocol,Self,
14      AetHumanKind,
15      AdtDate,
16      AdtTime,
17      AdtPhoneNumber,
18      AdtGPSLocation,
19      AdtComment

```

```

20      ],
21      []):-  

22 /* Pre Protocol:-/  

23 msrVar(ctState,TheSystem),  

24 msrNav([Self],[rnActor,rnSystem],[TheSystem]),  

25 /* PreP01 */  

26 msrNav([TheSystem],  

27     [vpStarted],  

28     [[ptBoolean,true]]))  

29 .  

30  

31 msrop(outactComCompany,  

32     oeAlert,  

33     [preFunctional,Self,  

34     AetHumanKind,  

35     AdtDate,  

36     AdtTime,  

37     AdtPhoneNumber,  

38     AdtGPSLocation,  

39     AdtComment  

40     ],  

41     []):-  

42 /* Pre Functional:-/  

43 /* PreF01 */  

44 msrVar(ctState,TheSystem),  

45 msrNav([Self],  

46     [msmAtPre,rnActor,rnSystem],  

47     [TheSystem]),  

48  

49 ( msrNav([TheSystem],[clock,date,gt,[AdtDate]],[[ptBoolean,true]]))  

50 ; (msrNav([TheSystem],[clock,date,eq,[AdtDate]],[[ptBoolean,true]]))  

51 , msrNav([TheSystem],[clock,time,gt,[AdtTime]],[[ptBoolean,true]]))  

52 )  

53 )  

54 .  

55  

56 msrop(outactComCompany,  

57     oeAlert,  

58     [post,Self,  

59     AetHumanKind,  

60     AdtDate,  

61     AdtTime,  

62     AdtPhoneNumber,  

63     AdtGPSLocation,  

64     AdtComment  

65     ],  

66     []):-  

67  

68 msrVar(ctState,TheSystem),  

69 msrVar(ctHuman,ActHuman),  

70 msrVar(actComCompany,TheactComCompany),  

71 msrVar(ctAlert,ActAlert),  

72 msrVar(dtDateAndTime,AAlertInstant),  

73 msrVar(etAlertStatus,AetAlertStatus),  

74% msrVar(ctAlert,ActAlertNearBy),  

75 msrVar(ctCrisis,ActCrisis),  

76 msrVar(dtCrisisID,AdtCrisisID),  

77% msrVar(etCrisisType,AetCrisisType),  

78 msrVar(etCrisisStatus,AetCrisisStatus),  

79 msrVar(dtDateAndTime,ACrisisInstant),  

80 msrVar(dtComment,ACrisisdtComment),  

81% msrVar(ptString,AptStringMessage),  

82 msrVar(dtSMS,AdtSMS),  

83 msrVar(dtAlertID,AdtAlertID),  

84  

85% msrVar(ptInteger,TheNextptIntegerValue),  

86% msrVar(ptInteger,UpdatedNextptIntegerValue),  

87% msrVar(inactComCompany,TheComCompanyIN),  

88% msrVar(dtComment,TheCommentStored),  

89% msrVar(dtString,TheCommentStoreddtString),

```

```

90
91/* Post Functional:*/
92
93 msrNav([Self], [rnActor], [TheactComCompany]),
94 msrNav([Self], [rnActor, rnSystem], [TheSystem]),
95
96/* PostF01 */
97 msrNav([TheSystem],
98     [nextValueForAlertID],
99     [PrenextValueForAlertID]),
100 msrNav([PrenextValueForAlertID],
101     [add, [[dtInteger, [[value, [ptInteger, 1]]], []]], [PostnextValueForAlertID]),
102     [PostnextValueForAlertID]),
103 msrNav([TheSystem],
104     [msmAtPost, nextValueForAlertID],
105     [PostnextValueForAlertID]),
106
107 /* PostF02 */
108 msrNav([AAlerInstant], [date], [AdtDate]),
109 msrNav([AAlerInstant], [time], [AdtTime]),
110
111 msrNav([AetAlertStatus],
112     [],  
     [[etAlertStatus,pending]]),
113
114 msrNav([TheSystem],
115     [nextValueForAlertID,
116     todTimeString, [], eq, [AdtAlertID]],
117     [[ptBoolean,true]])  
,
118
119 msrNav([ActAlert],
120     [init, [AdtAlertID,
121         AetAlertStatus,
122         AdtGPSLocation,
123         AAlerInstant,
124         AdtComment]],  
     [[ptBoolean,true]])  
,
125
126 /* PostF03 */
127
128 msrNav([TheSystem],
129     [rnctAlert,  
      msrSelect,location,isNearTo,[AdtGPSLocation]],
130     ColctAlertsNearBy),
131
132 ( (msrNav(ColctAlertsNearBy,  
133     [msrIsEmpty],  
134     [[ptBoolean,true]])  
135     )
136 -> (
137     msrNav([TheSystem],
138         [nextValueForCrisisID],
139         [PrenextValueForCrisisID]),
140         msrNav([PrenextValueForCrisisID],
141             [add, [[dtInteger, [[value, [ptInteger, 1]]], []]], [PostnextValueForCrisisID]),
142             [PostnextValueForCrisisID]),
143             msrNav([TheSystem],
144                 [msmAtPost, nextValueForCrisisID],
145                 [PostnextValueForCrisisID]),
146
147 msrNav([TheSystem],
148     [nextValueForCrisisID,
149     todTimeString, [], eq, [AdtCrisisID]],
150     [[ptBoolean,true]])  
,
151
152 msrNav([AdtCrisisType],[],[[etCrisisType,small]]),
153 msrNav([AetCrisisStatus],[],[[etCrisisStatus,pending]]),
154 msrNav([ACrisisInstant],[],[AAlerInstant]),
155 msrNav([ACrisisdtComment],
156     [value],
157     [[ptString, 'no reporting yet defined']])),
158
159

```

```

160   msrNav([ActCrisis],[init,[AdtCrisisID,
161             AdtCrisisType,
162             AetCrisisStatus,
163             AdtGPSLocation,
164             ACrisisInstant,
165             ACrisisdtComment]],,
166             [[ptBoolean,true]]),
167
168   )
169 ; (
170   msrNav(ColctAlertsNearBy,
171             [rnTheCrisis,msrAny,msrTrue],
172             [ActCrisis])
173   ),
174 ),
175
176 /* PostF04 */
177
178 msrNav([ActAlert],
179         [msmAtPost,rnTheCrisis],
180         [ActCrisis]),
181
182 /* PostF05 */
183
184 msrNav([TheSystem],
185         [rnctHuman,
186           msrSelect,id,eq,[AdtPhoneNumber]],
187         HumanColl),
188
189 msrNav(HumanColl,
190         [msrSelect,kind,etEq,[AetHumanKind]],
191         HumanCol2),
192
193 (msrNav(HumanCol2,[msrIsEmpty],[[ptBoolean,true]]))
194 -> (msrNav([ActHuman],
195             [init,[AdtPhoneNumber,AetHumanKind]],
196             [[ptBoolean,true]]),
197   msrNav([ActHuman],
198             [msmAtPost,rnactComCompany],
199             [TheactComCompany])
200   )
201 ; msrNav(HumanCol2,
202             [msrAny],
203             [ActHuman])
204 ),
205
206msrNav([ActHuman],
207         [rnSignaled,msrIncluding,[ActAlert]],
208         ColAlerts),
209
210msrNav([ActHuman],
211         [msmAtPost,rnSignaled],
212         ColAlerts),
213
214/* PostF06 */
215msrNav([AdtSMS],
216         [value],
217         [[ptString,'Your alert has been registered. We will handle it and keep you informed']])),
218msrNav([TheactComCompany],
219         [rnInterfaceIN,
220           ieSmsSend,[AdtPhoneNumber,
221                     AdtSMS]],[[ptBoolean,true]]),
222
223/*
224
225 */
226
227 /* Post Protocol:*/
228 /* PostP01 */
229 true

```

230 .

Listing D.7: Prolog file outactComCompany-oeAlert.pl.

D.8 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoord oeCloseCrisis.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactCoordinator,
7    oeCloseCrisis,
8    [preProtocol,Self,
9     AdtCrisisID
10    ],
11   []):-!
12/* Pre Protocol:*/
13 msrVar(ctState,TheSystem),
14 msrVar(actCoordinator,TheActor),
15 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
16 msrNav([Self],[rnActor],[TheActor]),
17 .
18/* PreP01 */
19 msrNav([TheSystem],
20        [vpStarted],
21        [[ptBoolean,true]]),
22 .
23/* PreP02 */
24 msrNav([TheActor],
25        [rnctAuthenticated,vpIsLogged],
26        [[ptBoolean,true]]),
27 .
28
29msrop(outactCoordinator,
30    oeCloseCrisis,
31    [preFunctional,Self,
32     AdtCrisisID
33    ],
34   []):-!
35/* Pre Functional:*/
36 msrVar(ctState,TheSystem),
37 msrVar(actCoordinator,TheActor),
38 .
39 msrVar(dtCrisisID,AdtCrisisID),
40 .
41 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
42 msrNav([Self],[rnActor],[TheActor]),
43 .
44/* PreF01 */
45 msrNav([TheSystem],
46        [rnctCrisis,
47         msrSelect,
48         id,eq,[AdtCrisisID]
49       ],
50       ColCrisis),
51 .
52 msrNav(ColCrisis,
53        [msrSize,eq,[[ptInteger,1]]],
54        [[ptBoolean,true]]),
55 .
56
57msrop(outactCoordinator,
58    oeCloseCrisis,
59    [post,Self,
60     AdtCrisisID
61    ],

```

```

62      []):-  

63  

64 /* Post Functional: */  

65 msrVar(ctState,TheSystem),  

66 msrVar(actCoordinator,TheActor),  

67  

68 msrVar(ctCrisis,TheCrisis),  

69 msrVar(dtCrisisID,AdtCrisisID),  

70  

71 msrNav([Self],[rnActor,rnSystem],[TheSystem]),  

72 msrNav([Self],[rnActor],[TheActor]),  

73  

74 /* PostF01 */  

75 msrNav([TheSystem],  

76     [rnctCrisis,  

77      msrSelect,  

78      id,eq,[AdtCrisisID]],  

79     [TheCrisis]),  

80  

81 msrNav([TheCrisis],  

82     [msmAtPost,status],  

83     [[etCrisisStatus,closed]]),  

84  

85 /* PostF02 */  

86 msrNav([TheCrisis],  

87     [msmAtPost,rnHandler],  

88     []),  

89  

90 /* PostF03 */  

91 msrNav([TheCrisis],  

92     [rnAlerts,msrForAll,msrIsKilled],  

93     [[ptBoolean,true]]),  

94  

95 /* PostF04 */  

96 msrNav([TheActor],  

97     [rnInterfaceIN,  

98      ieMessage,[[ptString,'The crisis is now closed !']]  

99    ],  

100   [[ptBoolean,true]]),  

101  

102 /* Post Protocol: */  

103 /* PostP01 */  

104 true  

105 .

```

Listing D.8: Prolog file outactCoordinator-oeCloseCrisis.pl.

D.9 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeGetAlertsSet.pl

```

1%%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */  

3:- multifile msrop/4.  

4%%%%%%%%%%%%%%%
5-----  

6msrop(outactCoordinator,  

7 oeGetAlertsSet,  

8 [preProtocol,Self,  

9 AetAlertStatus  

10 ],  

11 []):-  

12 /* Pre Protocol: */  

13 msrVar(ctState,TheSystem),  

14 msrVar(actCoordinator,TheActor),  

15 msrNav([Self],[rnActor,rnSystem],[TheSystem]),  

16 msrNav([Self],[rnActor],[TheActor]),  

17  

18 /* PreP01 */

```

```

19 msrNav([TheSystem],
20   [vpStarted],
21   [[ptBoolean,true]]),
22 .
23 msrNav([TheActor],
24   [rnctAuthenticated,vpIsLogged],
25   [[ptBoolean,true]])
26 .
27
28 msrop(outactCoordinator,
29   oeGetAlertsSet,
30   [preFunctional,Self,
31   AetAlertStatus
32   ],
33   []):-!
34 /* Pre Functional:*/
35 /* PreF01 */
36 true
37 .
38
39 msrop(outactCoordinator,
40   oeGetAlertsSet,
41   [post,Self,
42   AetAlertStatus
43   ],
44   []):-!
45
46 /* Post Functional:*/
47 msrVar(ctState,TheSystem),
48 msrVar(actCoordinator,TheActor),
49 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
50 msrNav([Self],[rnActor],[TheActor]),
51
52 /* PostF01 */
53 msrNav([TheSystem],
54   [rnctAlert,
55   msrSelect,
56   status,etEq,[AetAlertStatus]],
57   ColAlertSet),
58
59 msrNav(ColAlertSet,
60   [msrForAll,isSentToCoordinator,[TheActor]],
61   [[ptBoolean,true]]),
62
63 /* Post Protocol:*/
64 /* PostP01 */
65 true
66 .

```

Listing D.9: Prolog file outactCoordinator-oeGetAlertsSet.pl.

D.10 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeGetCrisisSet.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactCoordinator,
7   oeGetCrisisSet,
8   [preProtocol,Self,
9   AetCrisisStatus
10  ],
11  []):-!
12/* Pre Protocol:*/
13 msrVar(ctState,TheSystem),
14 msrVar(actCoordinator,TheActor),

```

```

15 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
16 msrNav([Self],[rnActor],[TheActor]),
17
18/* PreP01 */
19 msrNav([TheSystem],
20     [vpStarted],
21     [[ptBoolean,true]]),
22
23 msrNav([TheActor],
24     [rnctAuthenticated,vpIsLogged],
25     [[ptBoolean,true]])
26.
27
28msrop(outactCoordinator,
29 oeGetCrisisSet,
30 [preFunctional,Self,
31 AetCrisisStatus
32 ],
33 []):-!
34/* Pre Functional:*/
35/* PreF01 */
36true
37.
38
39msrop(outactCoordinator,
40 oeGetCrisisSet,
41 [post,Self,
42 AetCrisisStatus
43 ],
44 []):-!
45
46/* Post Functional:*/
47 msrVar(ctState,TheSystem),
48 msrVar(actCoordinator,TheActor),
49 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
50 msrNav([Self],[rnActor],[TheActor]),
51
52/* PostF01 */
53 msrNav([TheSystem],
54     [rnctCrisis,
55      msrSelect,
56      status,etEq,[AetCrisisStatus]],
57     ColCrisisSet),
58
59 msrNav(ColCrisisSet,
60     [msrForAll,isSentToCoordinator,[TheActor]],
61     [[ptBoolean,true]]),
62
63 /* Post Protocol:*/
64/* PostP01 */
65 true
66 .

```

Listing D.10: Prolog file outactCoordinator-oeGetCrisisSet.pl.

D.11 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeInvalidateAlert.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactCoordinator,
7    oeInvalidateAlert,
8    [preProtocol,Self,
9     AdtAlertID
10    ],

```

```

11  []):-  

12 /* Pre Protocol:*/  

13 msrVar(ctState,TheSystem),  

14 msrVar(actCoordinator,TheActor),  

15 msrNav([Self],[rnActor,rnSystem],[TheSystem]),  

16 msrNav([Self],[rnActor],[TheActor]),  

17  

18 /* PreP01 */  

19 msrNav([TheSystem],  

20     [vpStarted],  

21     [[ptBoolean,true]]),  

22  

23 /* PreP02 */  

24 msrNav([TheActor],  

25     [rnctAuthenticated,vpIsLogged],  

26     [[ptBoolean,true]]))  

27.  

28  

29 msrop(outactCoordinator,  

30     oeInvalidateAlert,  

31     [preFunctional,Self,  

32      AdtAlertID  

33      ],  

34      []):-  

35 /* Pre Functional:*/  

36 msrVar(ctState,TheSystem),  

37 msrVar(actCoordinator,TheActor),  

38  

39 msrVar(dtAlertID,AdtAlertID),  

40  

41 msrNav([Self],[rnActor,rnSystem],[TheSystem]),  

42 msrNav([Self],[rnActor],[TheActor]),  

43  

44 /* PreF01 */  

45 msrNav([TheSystem],  

46     [rnctAlert,  

47      msrSelect,  

48      id,eq,[AdtAlertID]  

49      ],  

50      ColAlert),  

51  

52 msrNav(ColAlert,  

53     [msrSize,eq,[[ptInteger,1]]],  

54     [[ptBoolean,true]]))  

55 .  

56  

57 msrop(outactCoordinator,  

58     oeInvalidateAlert,  

59     [post,Self,  

60      AdtAlertID  

61      ],  

62      []):-  

63  

64 /* Post Functional:*/  

65 msrVar(ctState,TheSystem),  

66 msrVar(actCoordinator,TheActor),  

67  

68 msrVar(ctAlert,TheAlert),  

69 msrVar(dtAlertID,AdtAlertID),  

70  

71 msrNav([Self],[rnActor,rnSystem],[TheSystem]),  

72 msrNav([Self],[rnActor],[TheActor]),  

73  

74 /* PostF01 */  

75 msrNav([TheSystem],  

76     [rnctAlert,  

77      msrSelect,  

78      id,eq,[AdtAlertID]],  

79      [TheAlert]),  

80

```

```

81 msrNav([TheAlert],
82     [msmAtPost,status],
83     [[etAlertStatus,invalid]]),
84
85 /* PostF02 */
86 msrNav([TheActor],
87     [rnInterfaceIN,
88     ieMessage,[[ptString,'The alert is now declared as invalid !']],
89     ],
90     [[ptBoolean,true]]),
91
92 /* Post Protocol:*/
93 /* PostP01 */
94 true
95 .

```

Listing D.11: Prolog file outactCoordinator-oeInvalidateAlert.pl.

D.12 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeReportOnCrisis.pl

```

1%-----%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%-----%
5-----%
6msrop(outactCoordinator,
7    oeReportOnCrisis,
8    [preProtocol,Self,
9     AdtCrisisID,
10    AdtComment
11    ],
12    []):-!
13/* Pre Protocol:*/
14 msrVar(ctState,TheSystem),
15 msrVar(actCoordinator,TheActor),
16 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
17 msrNav([Self],[rnActor],[TheActor]),
18
19/* PreP01 */
20 msrNav([TheSystem],
21     [vpStarted],
22     [[ptBoolean,true]]),
23
24 msrNav([TheActor],
25     [rnctAuthenticated,vpIsLogged],
26     [[ptBoolean,true]]),
27.
28
29msrop(outactCoordinator,
30    oeReportOnCrisis,
31    [preFunctional,Self,
32     AdtCrisisID,
33     AdtComment
34     ],
35    []):-!
36/* Pre Functional:*/
37 msrVar(ctState,TheSystem),
38 msrVar(actCoordinator,TheActor),
39
40 msrVar(dtCrisisID,AdtCrisisID),
41
42 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
43 msrNav([Self],[rnActor],[TheActor]),
44
45/* PreF01 */
46 msrNav([TheSystem],
47     [rnctCrisis,

```

```

48     msrSelect,
49     id,eq,[AdtCrisisID]
50   ],
51   ColCrisis),
52
53 msrNav(ColCrisis,
54   [msrSize,eq,[[ptInteger,1]]],
55   [[ptBoolean,true]])
56 .
57
58msrop(outactCoordinator,
59   oeReportOnCrisis,
60   [post,Self,
61   AdtCrisisID,
62   AdtComment
63   ],
64   []):-!
65
66/* Post Functional:*/
67 msrVar(ctState,TheSystem),
68 msrVar(actCoordinator,TheActor),
69
70 msrVar(ctCrisis,TheCrisis),
71 msrVar(dtCrisisID,AdtCrisisID),
72 msrVar(dtComment,AdtComment),
73
74 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
75 msrNav([Self],[rnActor],[TheActor]),
76
77/* PostF01 */
78 msrNav([TheSystem],
79   [rnctCrisis,
80    msrSelect,
81    id,eq,[AdtCrisisID]],
82   [TheCrisis]),
83
84 msrNav([TheCrisis],
85   [msmAtPost,comment],
86   [AdtComment]),
87
88 msrNav([TheActor],
89   [rnInterfaceIN,
90   ieMessage,[[ptString,'The crisis comment has been updated !']]
91   ],
92   [[ptBoolean,true]]),
93
94/* Post Protocol:*/
95/* PostP01 */
96 true
97 .

```

Listing D.12: Prolog file outactCoordinator-oeReportOnCrisis.pl.

D.13 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeSetCrisisHandler.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactCoordinator,
7   oeSetCrisisHandler,
8   [preProtocol,Self,
9   AdtCrisisID
10  ],
11  []):-!
12/* Pre Protocol:*/

```

```

13 msrVar(ctState,TheSystem),
14 msrVar(actCoordinator,TheActor),
15 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
16 msrNav([Self],[rnActor],[TheActor]),
17
18 /* PreP01 */
19 msrNav([TheSystem],
20     [vpStarted],
21     [[ptBoolean,true]]),
22
23 msrNav([TheActor],
24     [rnctAuthenticated,vpIsLogged],
25     [[ptBoolean,true]]))
26.
27
28msrop(outactCoordinator,
29 oeSetCrisisHandler,
30 [preFunctional,Self,
31 AdtCrisisID
32 ],
33 []):-!
34 /* Pre Functional:*/
35 msrVar(ctState,TheSystem),
36 msrVar(actCoordinator,TheActor),
37
38 msrVar(dtCrisisID,AdtCrisisID),
39
40 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
41 msrNav([Self],[rnActor],[TheActor]),
42
43 /* PreF01 */
44 msrNav([TheSystem],
45     [rnctCrisis,
46      msrSelect,
47      id,eq,[AdtCrisisID]
48 ],
49     ColCrisis),
50
51 msrNav(ColCrisis,
52     [msrSize,eq,[[ptInteger,1]]],
53     [[ptBoolean,true]]))
54 .
55
56msrop(outactCoordinator,
57 oeSetCrisisHandler,
58 [post,Self,
59 AdtCrisisID
60 ],
61 []):-!
62
63 /* Post Functional:*/
64 msrVar(ctState,TheSystem),
65 msrVar(actCoordinator,TheActor),
66 msrVar(ctCoordinator,TheCoordinator),
67 msrVar(ctCoordinator,TheCurrentHandler),
68
69 msrVar(ctCrisis,TheCrisis),
70 msrVar(dtCrisisID,AdtCrisisID),
71
72 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
73 msrNav([Self],[rnActor],[TheActor]),
74
75 /* PostF01 */
76 msrNav([TheSystem],
77     [rnctCrisis,
78      msrSelect,
79      id,eq,[AdtCrisisID]],
80     [TheCrisis]),
81
82 msrNav([TheCrisis],

```

```

83     [msmAtPost,status],
84     [[etCrisisStatus,handled]]),
85
86 msrNav([TheActor],
87     [rnctCoordinator],
88     [TheCoordinator]),
89 msrNav([TheCrisis],
90     [msmAtPost,rnHandler],
91     [TheCoordinator]),
92
93 msrNav([TheActor],
94     [rnInterfaceIN,
95      ieMessage,[[ptString,'You are now considered as handling the crisis !']],
96      ],
97      [[ptBoolean,true]]),
98
99 /* PostF02 */
100 msrNav([TheCrisis],
101     [rnAlerts,msrForAll,isSentToCoordinator,[TheActor]],
102     [[ptBoolean,true]]),
103
104 /* PostF03 */
105 ( msrNav([TheCrisis],
106     [rnHandler,msrSize,eq,[[ptInteger,1]]],
107     [[ptBoolean,true]]))
108 -> (msrNav([TheCrisis],
109     [rnHandler],
110     [TheCurrentHandler]),
111     msrNav([TheCurrentHandler],
112     [rnactCoordinator,rnInterfaceIN,
113      ieMessage,[[ptString,'One of the crisis you were handling is now handled by one of your
114      colleagues!']]],
115      [[ptBoolean,true]]))
116 )
117 ; true
118 ),
119
120 /* PostF04 */
121 msrNav([TheCrisis],
122     [rnAlerts,rnSignaler,msrForAll,isAcknowledged,[],,
123     [[ptBoolean,true]]),
124
125 /* Post Protocol:*/
126/* PostP01 */
127 true
128 .

```

Listing D.13: Prolog file outactCoordinator-oeSetCrisisHandler.pl.

D.14 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeSetCrisisStatus.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactCoordinator,
7    oeSetCrisisStatus,
8    [preProtocol,Self,
9     AdtCrisisID,
10    AetCrisisStatus
11    ],
12    []):-!
13/* Pre Protocol:*/
14 msrVar(ctState,TheSystem),
15 msrVar(actCoordinator,TheActor),

```

```

16 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
17 msrNav([Self],[rnActor],[TheActor]),
18
19/* PreP01 */
20 msrNav([TheSystem],
21     [vpStarted],
22     [[ptBoolean,true]]),
23
24 msrNav([TheActor],
25     [rnctAuthenticated,vpIsLogged],
26     [[ptBoolean,true]])
27.
28
29msrop(outactCoordinator,
30 oeSetCrisisStatus,
31 [preFunctional,Self,
32 AdtCrisisID,
33 AetCrisisStatus
34 ],
35 []):-!
36/* Pre Functional:*/
37 msrVar(ctState,TheSystem),
38 msrVar(actCoordinator,TheActor),
39
40 msrVar(dtCrisisID,AdtCrisisID),
41
42 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
43 msrNav([Self],[rnActor],[TheActor]),
44
45/* PreF01 */
46 msrNav([TheSystem],
47     [rnctCrisis,
48      msrSelect,
49      id,eq,[AdtCrisisID]
50 ],
51 ColCrisis),
52
53 msrNav(ColCrisis,
54     [msrSize,eq,[[ptInteger,1]]],
55     [[ptBoolean,true]]))
56 .
57
58msrop(outactCoordinator,
59 oeSetCrisisStatus,
60 [post,Self,
61 AdtCrisisID,
62 AetCrisisStatus
63 ],
64 []):-!
65
66/* Post Functional:*/
67 msrVar(ctState,TheSystem),
68 msrVar(actCoordinator,TheActor),
69
70 msrVar(ctCrisis,TheCrisis),
71 msrVar(dtCrisisID,AdtCrisisID),
72 msrVar(etCrisisStatus,AetCrisisStatus),
73
74 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
75 msrNav([Self],[rnActor],[TheActor]),
76
77/* PostF01 */
78 msrNav([TheSystem],
79     [rnctCrisis,
80      msrSelect,
81      id,eq,[AdtCrisisID]],
82     [TheCrisis]),
83
84 msrNav([TheCrisis],
85     [msmAtPost,status],

```

```

86     [AetCrisisStatus]),
87
88 msrNav([TheActor],
89     [rnInterfaceIN,
90      ieMessage,[[ptString,'The crisis status has been updated !']],
91     ],
92     [[ptBoolean,true]]),
93
94 /* Post Protocol:*/
95 /* PostP01 */
96 true
97 .

```

Listing D.14: Prolog file outactCoordinator-oeSetCrisisStatus.pl.

D.15 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeSetCrisisType.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactCoordinator,
7    oeSetCrisisType,
8    [preProtocol,Self,
9     AdtCrisisID,
10    AetCrisisType
11    ],
12    []):-!
13/* Pre Protocol:*/
14 msrVar(ctState,TheSystem),
15 msrVar(actCoordinator,TheActor),
16 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
17 msrNav([Self],[rnActor],[TheActor]),
18
19/* PreP01 */
20 msrNav([TheSystem],
21     [vpStarted],
22     [[ptBoolean,true]]),
23
24 msrNav([TheActor],
25     [rnctAuthenticated,vpiIsLogged],
26     [[ptBoolean,true]]))
27.
28
29msrop(outactCoordinator,
30    oeSetCrisisType,
31    [preFunctional,Self,
32     AdtCrisisID,
33     AetCrisisType
34     ],
35    []):-!
36/* Pre Functional:*/
37 msrVar(ctState,TheSystem),
38 msrVar(actCoordinator,TheActor),
39
40 msrVar(dtCrisisID,AdtCrisisID),
41
42 msrNav([Self],[rnActor,rnSystem],[TheSystem]),
43 msrNav([Self],[rnActor],[TheActor]),
44
45/* PreF01 */
46 msrNav([TheSystem],
47     [rnctCrisis,
48      msrSelect,
49      id,eq,[AdtCrisisID]
50     ],

```

```

51     ColCrisis),
52
53 msrNav(ColCrisis,
54     [msrSize, eq, [[ptInteger, 1]]], 
55     [[ptBoolean, true]])
56 .
57
58 msrop(outactCoordinator,
59     oeSetCrisisType,
60     [post, Self,
61      AdtCrisisID,
62      AetCrisisType
63     ],
64     []):-!
65
66 /* Post Functional:*/
67 msrVar(ctState, TheSystem),
68 msrVar(actCoordinator, TheActor),
69
70 msrVar(ctCrisis, TheCrisis),
71 msrVar(dtCrisisID, AdtCrisisID),
72 msrVar(etCrisisType, AetCrisisType),
73
74 msrNav([Self], [rnActor, rnSystem], [TheSystem]),
75 msrNav([Self], [rnActor], [TheActor]),
76
77 /* PostF01 */
78 msrNav([TheSystem],
79     [rnctCrisis,
80      msrSelect,
81      id, eq, [AdtCrisisID]],
82     [TheCrisis]),
83
84 msrNav([TheCrisis],
85     [msmAtPost, type],
86     [AetCrisisType]),
87
88 msrNav([TheActor],
89     [rnInterfaceIN,
90      ieMessage, [[ptString, 'The crisis type has been updated !']]
91     ],
92     [[ptBoolean, true]]),
93
94 /* Post Protocol:*/
95 /* PostP01 */
96 true
97 .

```

Listing D.15: Prolog file outactCoordinator-oeSetCrisisType.pl.

D.16 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactCoordinator-oeValidateAlert.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5-----
6msrop(outactCoordinator,
7    oeValidateAlert,
8    [preProtocol, Self,
9     AdtAlertID
10    ],
11    []):-!
12/* Pre Protocol:*/
13 msrVar(ctState, TheSystem),
14 msrVar(actCoordinator, TheActor),
15 msrNav([Self], [rnActor, rnSystem], [TheSystem]),

```

```

16 msrNav([Self], [rnActor], [TheActor]),
17
18/* PreP01 */
19 msrNav([TheSystem],
20     [vpStarted],
21     [[ptBoolean,true]]),
22
23 msrNav([TheActor],
24     [rnctAuthenticated,vpiIsLogged],
25     [[ptBoolean,true]])
26.
27
28msrop(outactCoordinator,
29    oeValidateAlert,
30    [prefunctional,Self,
31     AdtAlertID
32     ],
33     []):-!
34/* Pre Functional:*/
35 msrVar(ctState,TheSystem),
36 msrVar(actCoordinator,TheActor),
37
38 msrVar(dtAlertID,AdtAlertID),
39
40 msrNav([Self], [rnActor,rnSystem],[TheSystem]),
41 msrNav([Self], [rnActor], [TheActor]),
42
43/* PreF01 */
44 msrNav([TheSystem],
45     [rnctAlert,
46      msrSelect,
47      id,eq,[AdtAlertID]
48      ],
49     ColAlerts),
50
51 msrNav(ColAlerts,
52     [msrSize,eq,[[ptInteger,1]]],
53     [[ptBoolean,true]]))
54 .
55
56msrop(outactCoordinator,
57    oeValidateAlert,
58    [post,Self,
59     AdtAlertID
60     ],
61     []):-!
62
63/* Post Functional:*/
64 msrVar(ctState,TheSystem),
65 msrVar(actCoordinator,TheActor),
66
67 msrVar(ctAlert,TheAlert),
68 msrVar(dtAlertID,AdtAlertID),
69
70 msrNav([Self], [rnActor,rnSystem],[TheSystem]),
71 msrNav([Self], [rnActor], [TheActor]),
72
73/* PostF01 */
74 msrNav([TheSystem],
75     [rnctAlert,
76      msrSelect,
77      id,eq,[AdtAlertID]],
78     [TheAlert]),
79
80 msrNav([TheAlert],
81     [msmAtPost,status],
82     [[etAlertStatus,valid]]),
83
84 msrNav([TheActor],
85     [rnInterfaceIN,

```

```

86     ieMessage, [[ptString, 'The Alert is now declared as valid !']])
87     ],
88     [[ptBoolean,true])),
89
90 /* Post Protocol:*/
91/* PostP01 */
92true
93 .

```

Listing D.16: Prolog file outactCoordinator-oeValidateAlert.pl.

D.17 File ./src-gen/prolog-ref-spec/Operations/Environment/OUT/outactMsrCreator-oeCreateSystemAndEnvironment.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5/*
6*****
7MSRCreatorActor
8*****
9
10/** createSystemAndEnvironment ***/
11
12msrop(outactMsrCreator,
13    oeCreateSystemAndEnvironment,
14    [preFunctional,_Self,_AqtyComCompanies],
15    []):-!
16true.
17
18msrop(outactMsrCreator,
19    oeCreateSystemAndEnvironment,
20    [preProtocol,_Self,_AqtyComCompanies],
21    []):-!
22true.
23
24msrop(outactMsrCreator,
25    oeCreateSystemAndEnvironment,
26    [post,_Self,AqtyComCompanies],
27    []):-!
28
29 msrVar(ctState,TheSystem),
30 msrVar(actMsrCreator,AactMsrCreator),
31 msrVar(actAdministrator,AactAdministrator),
32
33 msrVar(dtInteger, AnextValueForAlertID),
34 msrVar(dtInteger, AnextValueForCrisisID),
35 msrVar(dtDateAndTime, Aclock),
36 msrVar(dtSecond, AcrisisReminderPeriod),
37 msrVar(dtSecond, AmaxCrisisReminderPeriod),
38 msrVar(ptBoolean, AvpStarted),
39
40 /* PostF01 -- MUST ALWAYS BE MADE FIRST -- */
41 msrNav([AnextValueForAlertID],
42     [value,eq,[[ptInteger,1]]],
43     [[ptBoolean,true])),
44
45 msrNav([AnextValueForCrisisID],
46     [value,eq,[[ptInteger,1]]],
47     [[ptBoolean,true])),
48
49msrNav([Aclock],
50     [date,year,value],
51     [[ptInteger,1970]]),
52msrNav([Aclock],
53     [date,month,value],
54     [[ptInteger,01]]),

```

```

55msrNav ([Aclock],
56    [date,day,value],
57    [[ptInteger,01]]),
58
59msrNav ([Aclock],
60    [time,hour,value],
61    [[ptInteger,00]]),
62msrNav ([Aclock],
63    [time,minute,value],
64    [[ptInteger,00]]),
65msrNav ([Aclock],
66    [time,second,value],
67    [[ptInteger,00]]),
68
69 msrNav ([AcrisisReminderPeriod],
70    [value,eq,[[ptInteger,300]]],
71    [[ptBoolean,true]]),
72
73 msrNav ([AmaxCrisisReminderPeriod],
74    [value,eq,[[ptInteger,1200]]],
75    [[ptBoolean,true]]),
76
77 msrNav ([AvpStarted],
78    [],
79    [[ptBoolean,true]]),
80
81 msrNav ([TheSystem],
82    [init, [AnextValueForAlertID,
83        AnextValueForCrisisID,
84        Aclock,
85        AcrisisReminderPeriod,
86        AmaxCrisisReminderPeriod,
87        Aclock,
88        AvpStarted]
89    ],
90    [[ptBoolean,true]]),
91
92/* PostF02*/
93 msrNav ([AactMsrCreator],
94    [init, []],
95    [[ptBoolean,true]]),
96
97 /* PostF03 */
98 msrVarCol(actComCompany,AqtyComCompanies,AactComCompanyCol),
99
100 msrNav (AactComCompanyCol,
101    [msrForAll,init,[]],
102    [[ptBoolean,true]]),
103
104 /* PostF04*/
105 msrNav ([AactAdministrator],
106    [init, []],
107    [[ptBoolean,true]]),
108
109 /* PostF05*/
110 msrVar(actActivator,AactActivator),
111 msrNav ([AactActivator],
112    [init, []],
113    [[ptBoolean,true]]),
114
115/* PostF06 */
116 msrVar(ctAdministrator,ActAdministrator),
117 msrVar(dtLogin,AdtLogin),
118 msrVar(dtPassword,AdtPassword),
119
120 msrNav ([AdtLogin],
121    [value,eq,[[ptString,'icrashadmin']]],
122    [[ptBoolean,true]]),
123
124 msrNav ([AdtPassword],

```

```

125      [value,eq,[[ptString,'7WXC1359']]],  

126      [[ptBoolean,true]]),  

127  

128 msrNav([ActAdministrator],  

129     [init,[AdtLogin,AdtPassword]],  

130     [[ptBoolean,true]]),  

131  

132 /* PostF07 */  

133 msrNav([ActAdministrator],  

134     [msmAtPost,rnactAuthenticated],  

135     [AactAdministrator]),  

136  

137 /* Post Protocol:*/  

138 /* PostP01 */  

139 true  

140 .

```

Listing D.17: Prolog file outactMsrCreator-oeCreateSystemAndEnvironment.pl.

D.18 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClass-ctAdministrator-init.pl

```

1%%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */  

3:- multifile msrop/4.  

4%%%%%%%%%%%%%%%
5  

6msrop(ctAdministrator,init,[Self,  

7          Alogin,  

8          Apwd],  

9          Result):-  

10 (  

11msrVar(ctAdministrator,Self),  

12  

13/* Post F01 */  

14msrNav([Self],[login],[Alogin]),  

15msrNav([Self],[pwd],[Apwd]),  

16msrNav([Self],[vpIsLogged],[[ptBoolean,false]]),  

17  

18/* Post F02 */  

19 msrNav([Self],[msrIsNew],[Self])  

20)  

21-> Result = [ptBoolean,true]  

22; Result = [ptBoolean,false]  

23.

```

Listing D.18: Prolog file PrimaryTypesClasses-ctAdministrator-init.pl.

D.19 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClass-ctAlert-init.pl

```

1%%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */  

3:- multifile msrop/4.  

4%%%%%%%%%%%%%%%
5  

6msrop(ctAlert,init,[Self,  

7          Aid,  

8          Astatus,  

9          Alocation,  

10         Ainstant,  

11         Acomment],  

12         Result):-  

13  

14/* Post F01 */  

15 (

```

```

16msrVar(ctAlert,Self) ,
17
18msrNav([Self],[id],[Aid]),
19msrNav([Self],[status],[Astatus]),
20msrNav([Self],[location],[Alocation]),
21msrNav([Self],[instant],[Ainstant]),
22msrNav([Self],[comment],[Acomment]),
23
24/* Post F02 */
25 msrNav([Self],[msrIsNew], [Self])
26)
27-> Result = [ptBoolean,true]
28; Result = [ptBoolean,false]
29.

```

Listing D.19: Prolog file PrimaryTypesClasses-ctAlert-init.pl.

D.20 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctAlert-isSentToCoordinator.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctAlert,isSentToCoordinator,[Self,AactCoordinator],
7      Result):-
8
9/* Post F01 */
10(
11 msrNav([AactCoordinator],
12        [rnInterfaceIN,ieSendAnAlert,[Self] ],
13        [[ptBoolean,true]])
14)
15-> Result = [ptBoolean,true]
16; Result = [ptBoolean,false]
17.

```

Listing D.20: Prolog file PrimaryTypesClasses-ctAlert-isSentToCoordinator.pl.

D.21 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctAuthenticated-init.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctAuthenticated,init,[Self,
7          Alogin,
8          Apwd],
9      Result):-
10
11/* Post F01 */
12(
13msrVar(ctAuthenticated,Self),
14
15msrNav([Self],[login],[Alogin]),
16msrNav([Self],[pwd],[Apwd]),
17msrNav([Self],[vpIsLogged],[[ptBoolean,false]]),
18
19/* Post F02 */
20 msrNav([Self],[msrIsNew], [Self])
21)
22-> Result = [ptBoolean,true]
23; Result = [ptBoolean,false]

```

24.

Listing D.21: Prolog file PrimaryTypesClasses-ctAuthenticated-init.pl.

D.22 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctCoordinator-init.pl

```

1%%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%%%
5
6msrop(ctCoordinator,init,[Self,
7      Aid,
8      Alogin,
9      Apwd],
10     Result):-
11
12/* Post F01 */
13(
14msrVar(ctCoordinator,Self),
15
16msrNav([Self],[id],[Aid]),
17msrNav([Self],[login],[Alogin]),
18msrNav([Self],[pwd],[Apwd]),
19msrNav([Self],[vpIsLogged],[[ptBoolean,false]]),
20
21/* Post F02 */
22 msrNav([Self],[msrIsNew],[Self])
23)
24-> Result = [ptBoolean,true]
25; Result = [ptBoolean,false]
26.

```

Listing D.22: Prolog file PrimaryTypesClasses-ctCoordinator-init.pl.

D.23 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctCrisis-handlingDelayPassed.pl

```

1%%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%%%
5
6msrop(ctCrisis,handlingDelayPassed,[Self],
7     Result):-
8
9/* Post F01 */
10(
11 msrVar(ctState,TheSystem),
12 msrVar(dtInteger,CurrentClockSecondsQty),
13 msrVar(dtInteger,LastReminderSecondsQty),
14 msrVar(dtSecond,CrisisReminderPeriod),
15
16 msrNav([Self],[rnSystem],[TheSystem]),
17
18 msrNav([Self],
19      [status],
20      [[etCrisisStatus,pending]]),
21
22 msrNav([TheSystem],
23      [clock,toSecondsQty,[],],
24      [CurrentClockSecondsQty]),
25
26 msrNav([TheSystem],
27      [vpLastReminder,toSecondsQty,[]],

```

```

28     [LastReminderSecondsQty]),
29
30 msrNav([TheSystem],
31     [crisisReminderPeriod],
32     [CrisisReminderPeriod]),
33
34 msrNav([CurrentClockSecondsQty],
35     [sub, [LastReminderSecondsQty],
36         gt, [CrisisReminderPeriod]
37     ],
38     [[ptBoolean,true]])
39
40)
41-> Result = [ptBoolean,true]
42; Result = [ptBoolean,false]
43.

```

Listing D.23: Prolog file PrimaryTypesClasses-ctCrisis-handlingDelayPassed.pl.

D.24 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctCrisis-init.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctCrisis,init,[Self,
7    Aid,
8    Atype,
9    Astatus,
10   Alocation,
11   Ainstant,
12   Acomment],
13   Result):-!
14
15/* Post F01 */
16(
17msrVar(ctCrisis,Self),
18
19msrNav([Self], [id], [Aid]),
20msrNav([Self], [type], [Atype]),
21msrNav([Self], [status], [Astatus]),
22msrNav([Self], [location], [Alocation]),
23msrNav([Self], [instant], [Ainstant]),
24msrNav([Self], [comment], [Acomment]),
25
26/* Post F02 */
27 msrNav([Self], [msrIsNew], [Self])
28)
29-> Result = [ptBoolean,true]
30; Result = [ptBoolean,false]
31.

```

Listing D.24: Prolog file PrimaryTypesClasses-ctCrisis-init.pl.

D.25 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctCrisis-isAllocatedIfPossible.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctCrisis,isAllocatedIfPossible,[Self],
7   Result):-

```

```

8(
9 msrVar(ctState,TheSystem),
10 msrNav([Self],[rnSystem],[TheSystem]),
11
12 msrVar(actCoordinator,TheCoordinatorActor),
13 msrVar(ctCoordinator,TheCoordinator),
14 msrVar(ptString,TheMessage),
15 msrVar(ptString,TheCrisisIDptString),
16
17 (
18 /* Post F01 */
19 msrNav([Self],
20 [maxHandlingDelayPassed,[]],
21 [[ptBoolean,true]]),
22
23 ( msrNav([TheSystem],
24 [rnactCoordinator,msrIsEmpty],
25 [[ptBoolean,false]])
26 -> (
27 /* Post F02 */
28 msrNav([TheSystem],
29 [rnactCoordinator,msrAny,msrTrue],
30 [TheCoordinatorActor]),
31
32 msrNav([TheCoordinatorActor],
33 [rnctCoordinator],
34 [TheCoordinator]),
35
36 msrNav([Self],
37 [msmAtPost,rnHandler],
38 [TheCoordinator]),
39
40 msrNav([Self],
41 [msmAtPost,status],
42 [[etCrisisStatus,handled]]),
43
44 msrNav([Self],
45 [id,value],
46 [TheCrisisIDptString]),
47
48 msrNav([[ptString,'You are now considered as handling the crisis having ID: ']],
49 [ptStringConcat,[TheCrisisIDptString]],
50 [TheMessage]),
51
52 msrNav([TheCoordinatorActor],
53 [rnInterfaceIN,
54 ieMessage,[TheMessage]
55 ],
56 [[ptBoolean,true]])
57 )
58 ; /* Post F03 */
59 msrNav([TheSystem],
60 [rnactAdministrator,msrForAll,rnInterfaceIN,
61 ieMessage,[[ptString,'Please add new coordinators to handle pending crisis !']]],
62 [[ptBoolean,true]])
63 )
64 )
65 )
66)
67-> Result = [ptBoolean,true]
68; Result = [ptBoolean,false]
69.

```

Listing D.25: Prolog file PrimaryTypesClasses-ctCrisis-isAllocatedIfPossible.pl.

D.26 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClass-ctCrisis-isSentToCoordinator.pl

%%%%%%%%%%%%%

```

2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctCrisis,isSentToCoordinator,[Self,AactCoordinator],
7      Result):-_
8
9/* Post F01 */
10(
11 msrNav([AactCoordinator],
12         [rnInterfaceIN,ieSendACrisis,[Self]],[[ptBoolean,true]])
13)
14)
15-> Result = [ptBoolean,true]
16; Result = [ptBoolean,false]
17.

```

Listing D.26: Prolog file PrimaryTypesClasses-ctCrisis-isSentToCoordinator.pl.

D.27 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctCrisis-maxHandlingDelayPassed.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctCrisis,maxHandlingDelayPassed,[Self],
7      Result):-_
8
9/* Post F01 */
10(
11 msrVar(ctState,TheSystem),
12 msrVar(dtInteger,CurrentClockSecondsQty),
13 msrVar(dtInteger,CrisisInstantSecondsQty),
14 msrVar(dtSecond,MaxCrisisReminderPeriod),
15
16 msrNav([Self], [rnSystem], [TheSystem]),
17
18 msrNav([Self],
19         [status],
20         [[etCrisisStatus,pending]]),
21
22 msrNav([TheSystem],
23         [clock,toSecondsQty,[]],
24         [CurrentClockSecondsQty]),
25
26 msrNav([Self],
27         [instant,toSecondsQty,[]],
28         [CrisisInstantSecondsQty]),
29
30 msrNav([TheSystem],
31         [maxCrisisReminderPeriod],
32         [MaxCrisisReminderPeriod]),
33
34 msrNav([CurrentClockSecondsQty],
35         [sub,[CrisisInstantSecondsQty],
36          gt, [MaxCrisisReminderPeriod]
37          ],
38         [[ptBoolean,true]]))
39
40)
41-> Result = [ptBoolean,true]
42; Result = [ptBoolean,false]
43.

```

Listing D.27: Prolog file PrimaryTypesClasses-ctCrisis-maxHandlingDelayPassed.pl.

D.28 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctHuman-init.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctHuman,init,[Self,
7          Aid,
8          Akind],
9      Result):-!
10
11/* Post F01 */
12(
13msrVar(ctHuman,Self),
14
15msrNav([Self],[id],[Aid]),
16msrNav([Self],[kind],[Akind]),
17
18/* Post F02 */
19 msrNav([Self],[msrIsNew],[Self])
20)
21-> Result = [ptBoolean,true]
22; Result = [ptBoolean,false]
23.
```

Listing D.28: Prolog file PrimaryTypesClasses-ctHuman-init.pl.

D.29 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctHuman-isAcknowledged.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(ctHuman,isAcknowledged,[Self],Result):-
7
8/* Post F01 */
9(msrVar(dtPhoneNumber,AdtPhoneNumber),
10 msrVar(dtSMS,AdtSMS),
11
12 msrNav([Self],
13         [id,eq,[AdtPhoneNumber]],
14         [[ptBoolean,true]]),
15 msrNav([AdtSMS],
16         [value,eq,[[ptString,'The handling of your alert by our services is in progress !']]],
17         [[ptBoolean,true]]),
18 msrNav([Self],
19         [rnactComCompany,rnInterfaceIN,ieSmsSend,[AdtPhoneNumber,AdtSMS]],
20         [[ptBoolean,true]]),
21)
22-> Result = [ptBoolean,true]
23; Result = [ptBoolean,false]
24.
```

Listing D.29: Prolog file PrimaryTypesClasses-ctHuman-isAcknowledged.pl.

D.30 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses-ctState-init.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
```

```

4%%%%%%%%%%%%%%%
5
6msrop(ctState,init,[Self,
7      AnextValueForAlertID,
8      AnextValueForCrisisID,
9      Aclock,
10     AcrisisReminderPeriod,
11     AmaxCrisisReminderPeriod,
12     AvpLastReminder,
13     AvpStarted],
14   Result):-
15
16 /* Post F01 */
17(
18 msrVar(ctState,Self),
19
20 msrNav([Self],[nextValueForAlertID],[AnextValueForAlertID]),
21 msrNav([Self],[nextValueForCrisisID],[AnextValueForCrisisID]),
22 msrNav([Self],[clock],[Aclock]),
23 msrNav([Self],[crisisReminderPeriod],[AcrisisReminderPeriod]),
24 msrNav([Self],[maxCrisisReminderPeriod],[AmaxCrisisReminderPeriod]),
25 msrNav([Self],[vpLastReminder],[AvpLastReminder]),
26 msrNav([Self],[vpStarted],[AvpStarted]),
27
28 msrNav([Self],[msrIsNew],[Self])
29)
30-> Result = [ptBoolean,true]
31; Result = [ptBoolean,false]
32.

```

Listing D.30: Prolog file PrimaryTypesClasses-ctState-init.pl.

D.31 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDataty... dtAlertID-is.pl

```

1%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%%
5
6msrop(dtAlertID,is,[AdtValue],Result):-
7% msd01
8msrVar(ptBoolean,TheResult),
9(
10 ( msrNav([AdtValue],
11   [value,length,[],gt,[[ptInteger,0]]],
12   [[ptBoolean,true]]),
13   msrNav([AdtValue],
14   [value,length,[],leq,[[ptInteger,20]]],
15   [[ptBoolean,true]])
16 )
17 -> (TheResult = [ptBoolean,true])
18 ; (TheResult = [ptBoolean,false])
19),
20TheResult = Result
21.
22
23/*
24| ?- X = [dtAlertID,[],[[dtString,[[value,[ptString,'0123456789']]]],[]]],,
25msrNav([X],[is,[],[Result]).
26
27X = [dtAlertID,[],[[dtString,[[value,[ptString,'0123456789']]]],[]]],,
28Result = [ptBoolean,true] ?
29
30yes
31
32| ?- X = [dtAlertID,[],[[dtString,[[value,[ptString,'012345678901234567890123456789']]]],[]]],,
33msrNav([X],[is,[],[Result]).
```

```

34
35X = [dtAlertID, [], [[dtString, [[value, [ptString, '012345678901234567890123456789']]]], []]],,
36Result = [ptBoolean, false] ?
37
38yes
39*/

```

Listing D.31: Prolog file PrimaryTypesDatatypes-dtAlertID-is.pl.

D.32 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtComment-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5%% dtComment
6
7msd01
8msrop(dtComment,is,[AdtValue],Result):-
9 msrVar(ptBoolean,TheResult),
10 msrVar(ptInteger,MaxLength),
11 (
12   (
13     (
14       MaxLength = [ptInteger,160],
15       msrNav([AdtValue],
16               [value,length,[],leg,[MaxLength]],
17               [[ptBoolean,true]])
18     )
19     -> TheResult = [ptBoolean,true]
20     ; TheResult = [ptBoolean,false]
21   )
22),
23 Result = TheResult
24.
25
26/*
27| ?- X = [dtComment,[],[[dtString,[[value,[ptString,'I broke my leg ! Please help ...']]],[[]]]],[],[Result]].
28msrNav([X],[is,[],[Result]]).
29X = [dtComment,[],[[dtString,[[value,[ptString,'I broke my leg ! Please help ...']]],[[]]]],[],[Result] = [ptBoolean,true] ?
30Result = [ptBoolean,true] ?
31yes
32
33| ?- X = [dtComment,[],[[dtString,[[value,[ptString,'I broke my leg when I was running with my dog
34      to go to the skate park because my friends called me on my mobile phone and told me that a skate
35      star was doing triple back flips.']]],[[]]]],[],[Result]].
36msrNav([X],[is,[],[Result]]).
37X = [dtComment,[],[[dtString,[[value,[ptString,'I broke my leg when I was running with my dog to go
38      to the skate park because my friends called me on my mobile phone and told me that a skate star
      was doing triple back flips.']]],[[]]]],[],[Result] = [ptBoolean,false] ?
39yes
40*/

```

Listing D.32: Prolog file PrimaryTypesDatatypes-dtComment-is.pl.

D.33 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtCoordinatorID-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(dtCoordinatorID,is,[AdtValue],Result):-

```

```

7% msd01
8 msrVar(ptBoolean,TheResult),
9(
10 ( msrNav([AdtValue],
11   [value,length,[],gt,[[ptInteger,0]]]),
12   [[ptBoolean,true]]),
13 msrNav([AdtValue],
14   [value,length,[],leq,[[ptInteger,5]]],
15   [[ptBoolean,true]])
16 )
17 -> (TheResult = [ptBoolean,true])
18 ; (TheResult = [ptBoolean,false])
19),
20 TheResult = Result
21.

```

Listing D.33: Prolog file PrimaryTypesDatatypes-dtCoordinatorID-is.pl.

D.34 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtCrisisID-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6msrop(dtCrisisID,is,[AdtValue],Result):-
7% msd01
8 msrVar(ptBoolean,TheResult),
9(
10 ( msrNav([AdtValue],
11   [value,length,[],gt,[[ptInteger,0]]]),
12   [[ptBoolean,true]]),
13 msrNav([AdtValue],
14   [value,length,[],leq,[[ptInteger,10]]],
15   [[ptBoolean,true]])
16 )
17 -> (TheResult = [ptBoolean,true])
18 ; (TheResult = [ptBoolean,false])
19),
20 TheResult = Result
21.
22/*
23| ?- X = [dtCrisisID,[],[[dtString,[[value,[ptString,'0123456789']]]],[]]],,
24msrNav([X],[is,[],[Result]]).
25X = [dtCrisisID,[],[[dtString,[[value,[ptString,'0123456789']]]],[]]],,
26Result = [ptBoolean,true] ?
27yes
28
29| ?- X = [dtCrisisID,[],[[dtString,[[value,[ptString,'0123456789a']]]],[]]],,
30msrNav([X],[is,[],[Result]]).
31X = [dtCrisisID,[],[[dtString,[[value,[ptString,'0123456789a']]]],[]]],,
32Result = [ptBoolean,false] ?
33yes
34*/

```

Listing D.34: Prolog file PrimaryTypesDatatypes-dtCrisisID-is.pl.

D.35 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtGPSLocation-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5

```

```

6%% dtPhoneNumber
7
8% msd01
9msrop(dtGPSLocation, is, [AdtValue], Result) :-
10msrVar(ptBoolean, TheResult),
11(
12(
13    msrNav([AdtValue],
14        [latitude, is, []],
15        [[ptBoolean, true]]),
16    msrNav([AdtValue],
17        [longitude, is, []],
18        [[ptBoolean, true]])
19)
20 -> TheResult = [ptBoolean, true]
21 ; TheResult = [ptBoolean, false]
22),
23
24 Result = TheResult
25.

```

Listing D.35: Prolog file PrimaryTypesDatatypes-dtGPSLocation-is.pl.

D.36 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtGPSLocation-isNearTo.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6%% dtGPSLocation
7
8msrop(dtGPSLocation, isNearTo, [Self, AdtValue], Result) :-
9msrVar(ptBoolean, TheResult),
10msrVar(dtReal, EarthRadius),
11msrVar(dtReal, MaxDistance),
12
13msrVar(dtLatitude, ComparedLatitude),
14msrVar(dtLongitude, ComparedLongitude),
15
16msrVar(dtReal, R1), msrVar(dtReal, R1a),
17msrVar(dtReal, R2), msrVar(dtReal, R2a),
18
19(
20(
21(
22    % msd01
23    msrNav([EarthRadius], [value], [[ptReal, 6371]]),
24    msrNav([MaxDistance], [value], [[ptReal, 100]]),
25
26    msrNav([AdtValue], [latitude], [ComparedLatitude]),
27    msrNav([AdtValue], [longitude], [ComparedLongitude]),
28
29    msrNav([Self], [latitude, sin, [], [R1a]]),
30    msrNav([AdtValue], [latitude, sin, [], mul, [R1a]], [R1]),
31
32    msrNav([Self], [latitude, cos, [], [R2a]]),
33    msrNav([AdtValue], [latitude, cos, [], mul, [R2a]], [R2]),
34
35    msrNav([AdtValue], [longitude], [ComparedLongitude]),
36    msrNav([Self], [longitude, sub, [ComparedLongitude], cos, [], mul, [R2],
37        add, [R1],
38        acos, [],
39        mul, [EarthRadius],
40        sub, [MaxDistance],
41        value, leq, [[ptReal, 0]]],
42        [[ptBoolean, true]])

```

```

43      )
44      -> TheResult = [ptBoolean,true]
45      ; TheResult = [ptBoolean,false]
46  )
47),
48 Result = TheResult
49.

```

Listing D.36: Prolog file PrimaryTypesDatatypes-dtGPSLocation-isNearTo.pl.

D.37 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtLatitude-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6% msd01
7msrop(dtLatitude,is,[AdtValue],Result):-%
8msrVar(ptBoolean,TheResult),
9(
10 ( msrNav([AdtValue],
11   [value,geq,[[ptReal,-90.0]]],
12   [[ptBoolean,true]]),
13  msrNav([AdtValue],
14   [value,leq,[[ptReal,+90.0]]],
15   [[ptBoolean,true]])
16 )
17 -> (TheResult = [ptBoolean,true])
18 ; (TheResult = [ptBoolean,false])
19),
20Result = TheResult
21.

```

Listing D.37: Prolog file PrimaryTypesDatatypes-dtLatitude-is.pl.

D.38 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtLogin-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5% dtComment
6
7%msd01
8msrop(dtLogin,is,[AdtValue],Result):-%
9 msrVar(ptBoolean,TheResult),
10 msrVar(ptInteger,MaxLength),
11 (
12  (
13    (
14      MaxLength = [ptInteger,20],
15      msrNav([AdtValue],
16        [value,length,[],leq,[MaxLength]],
17        [[ptBoolean,true]]))
18  )
19  -> TheResult = [ptBoolean,true]
20  ; TheResult = [ptBoolean,false]
21 )
22),
23 Result = TheResult
24.
25/*
26| ?- X = [dtLogin,[],[[dtString,[value,[ptString,'01234567']]],[[]]]],
```

```

27msrNav([X],[is,[],[Result]).
28X = [dtLogin,[],[[dtString,[[value,[ptString,'01234567']]]],[],[],[],],
29Result = [ptBoolean,true] ?
30yes
31
32| ?- X = [dtLogin,[],[[dtString,[[value,[ptString,'01234567a']]]],[],[],[],],
33msrNav([X],[is,[],[Result]).
34X = [dtLogin,[],[[dtString,[[value,[ptString,'01234567a']]]],[],[],[],],
35Result = [ptBoolean,false] ?
36yes
37*/

```

Listing D.38: Prolog file PrimaryTypesDatatypes-dtLogin-is.pl.

D.39 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtLongitude-is.pl

```

1%%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%%%
5
6%% dtPhoneNumber
7
8% msd01
9msrop(dtLongitude,is,[AdtValue],Result):-
10msrVar(ptBoolean,TheResult),
11(
12 ( msrNav([AdtValue],
13   [value,geq,[[ptReal,-180.0]]],
14   [[ptBoolean,true]]),
15 msrNav([AdtValue],
16   [value,leq,[[ptReal,+180.0]]],
17   [[ptBoolean,true]]))
18 )
19 -> (TheResult = [ptBoolean,true])
20 ; (TheResult = [ptBoolean,false])
21),
22
23 Result = TheResult
24.

```

Listing D.39: Prolog file PrimaryTypesDatatypes-dtLongitude-is.pl.

D.40 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtPassword-is.pl

```

1%%%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%%%
5%% dtComment
6
7%msd01
8msrop(dtPassword,is,[AdtValue],Result):-
9 msrVar(ptBoolean,TheResult),
10 msrVar(ptInteger,MinLength),
11 (
12 (
13   (
14     MinLength = [ptInteger,6],
15     msrNav([AdtValue],
16       [value,length,[],geq,[MinLength]],
17       [[ptBoolean,true]]))
18   )
19   -> TheResult = [ptBoolean,true]

```

```

20      ; TheResult = [ptBoolean, false]
21  )
22),
23 Result = TheResult
24.
25/*
26| ?- X = [dtPassword, [], [[dtString, [[value, [ptString, '012345']]]], []]], 
27msrNav([X], [is, []], [Result]).
28X = [dtPassword, [], [[dtString, [[value, [ptString, '012345']]]], []]], 
29Result = [ptBoolean, true] ?
30yes
31
32| ?- X = [dtPassword, [], [[dtString, [[value, [ptString, '01234']]]], []]], 
33msrNav([X], [is, []], [Result]).
34X = [dtPassword, [], [[dtString, [[value, [ptString, '01234']]]], []]], 
35Result = [ptBoolean, false] ?
36yes
37*/

```

Listing D.40: Prolog file PrimaryTypesDatatypes-dtPassword-is.pl.

D.41 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesDatatypes-dtPhoneNumber-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6%% dtPhoneNumber
7
8% msd01
9msrop(dtPhoneNumber,is,[AdtValue],Result):-
10msrVar(ptBoolean,TheResult),
11(
12  ( msrNav([AdtValue],
13    [value,length,[],gt,[[ptInteger,4]]],
14    [[ptBoolean,true]]),
15  msrNav([AdtValue],
16    [value,length,[],leq,[[ptInteger,30]]],
17    [[ptBoolean,true]])
18 )
19
20 -> TheResult = [ptBoolean,true]
21 ; TheResult = [ptBoolean,false]
22),
23 Result = TheResult
24.
25/*
26| ?- X = [dtPhoneNumber, [], [[dtString, [[value, [ptString, '(+352) 46 66 44 60 00']]]], []]], 
27msrNav([X], [is, []], [Result]).
28X = [dtPhoneNumber, [], [[dtString, [[value, [ptString, '(+352) 46 66 44 60 00']]]], []]], 
29Result = [ptBoolean,true] ?
30
31yes
32
33yes
34*/

```

Listing D.41: Prolog file PrimaryTypesDatatypes-dtPhoneNumber-is.pl.

D.42 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClassesAndAlertStatus-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */

```

```

3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6% etAlertStatus
7
8% msd01
9msrop(etAlertStatus,is,[AdtValue],Result) :-
10msrVar(ptBoolean,TheResult),
11(
12 (
13 member(AdtValue,[pending, valid, invalid])
14 )
15 -> TheResult = [ptBoolean,true]
16 ; TheResult = [ptBoolean,false]
17),
18 Result = TheResult
19.
```

Listing D.42: Prolog file PrimaryTypesDatatypes-etAlertStatus-is.pl.

D.43 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClassifications/etCrisisStatus-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6% etCrisisStatus
7
8% msd01
9msrop(etCrisisStatus,is,[AdtValue],Result) :-
10msrVar(ptBoolean,TheResult),
11(
12 (
13 member(AdtValue,[pending, handled, solved, closed])
14 )
15 -> TheResult = [ptBoolean,true]
16 ; TheResult = [ptBoolean,false]
17),
18 Result = TheResult
19.
```

Listing D.43: Prolog file PrimaryTypesDatatypes-etCrisisStatus-is.pl.

D.44 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClassifications/etCrisisType-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6% etCrisisType
7
8% msd01
9msrop(etCrisisType,is,[AdtValue],Result) :-
10msrVar(ptBoolean,TheResult),
11(
12 (
13 member(AdtValue,[small, medium, huge]))
14 )
15 -> TheResult = [ptBoolean,true]
16 ; TheResult = [ptBoolean,false]
17),
18 Result = TheResult
```

19.

Listing D.44: Prolog file PrimaryTypesDatatypes-etCrisisType-is.pl.

D.45 File ./src-gen/prolog-ref-spec/Operations/Concepts/PrimaryTypesClasses etHumanKind-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5
6%% etHumanKind
7
8% msd01
9msrop(etHumanKind,is,[AdtValue],Result) :-
10msrVar(ptBoolean,TheResult),
11(
12(
13    member(AdtValue,[witness,victim,anonymous])
14)
15 -> TheResult = [ptBoolean,true]
16 ; TheResult = [ptBoolean,false]
17),
18 Result = TheResult
19.

```

Listing D.45: Prolog file PrimaryTypesDatatypes-etHumanKind-is.pl.

D.46 File ./src-gen/prolog-ref-spec/Operations/Concepts/SecondaryTypesDatatypesdtSMS-is.pl

```

1%%%%%%%%%%%%%
2/* DISCONTIGUOUS PREDICATES */
3:- multifile msrop/4.
4%%%%%%%%%%%%%
5%% dtComment
6
7%msd01
8msrop(dtSMS,is,[AdtValue],Result) :-
9 msrVar(ptBoolean,TheResult),
10 msrVar(ptInteger,MaxLength),
11(
12(
13(
14    MaxLength = [ptInteger,160],
15    msrNav([AdtValue],
16        [value,length,[],leq,[MaxLength]],
17        [[ptBoolean,true]]))
18)
19 -> TheResult = [ptBoolean,true]
20 ; TheResult = [ptBoolean,false]
21)
22),
23 Result = TheResult
24.

```

Listing D.46: Prolog file SecondaryTypesDatatypes-dtSMS-is.pl.

Glossary

<i>abstract actor</i> an actor that is not	22
<i>actor</i> An actor is a person, organization, or external system that plays a role in one or more interactions with the system	18
<i>direct actor</i> an actor that interacts directly with the system. It thus belongs to the environment.	22
<i>indirect actor</i> an actor that interacts indirectly with the system through a direct actor. It thus belongs the domain but not to the environment.	22
<i>system operation</i> a functionality of the system that can be triggered by a message sent by an actor belonging to the environment.	18

