HuGaDB GitHub v1 — two on-disk corpora in this repository

This project uses the **official HuGaDB v1** release (GitHub-style filenames `HuGaDB_v1_<activity>_*.txt`, ≈635 trials, 12 activity classes). There is **no** internal dataset versioning called "v2", "v3", or "v4"; training and loaders read GitHub v1 `.txt` files from one of two folder layouts below (see `LoadHuGaDB.m` for the full fallback chain).

`v1_raw/` — original GitHub v1 tree

Path: `data/HuGaDB/v1_raw/`
Unmodified download layout; optional nested folders such as `HuGaDB_v1_github_raw/` or `HuGaDB_source_github_v1/`.

At load time, corrupted gyros are handled per the official CSV matrix (`readmatrix` may see numeric values until cleanup is applied).

same GitHub v1 content, different on-disk roles →

`v1_cleanup_github/` — canonical flat corpus

Path: `data/HuGaDB/v1_cleanup_github/`
Flat `HuGaDB_v1_*.txt` files; corrupted gyro channels written as `na` in place using the official matrix (optional in-place build: `RunBuildHuGaDBv1Cleanup.m`).

This is the preferred tree when present; `LoadHuGaDB` falls back to `v1_raw/` and other legacy paths if needed.

Folder	Role	Notes
`v1_raw/`	Original GitHub v1 layout	Not a separate `v1_raw_github/` directory name in this repo.
`v1_cleanup_github/`	Canonical training corpus	Flat files; `na` gyros where the README matrix marks corruption.

Implementation: `src/acquisition/LoadHuGaDB.m`.