

# Package ‘FuzzyNumbers’

August 29, 2013

**Title** Tools to deal with fuzzy numbers

**Type** Package

**Description** The FuzzyNumbers package provides S4 classes and methods to deal with Fuzzy Numbers: computations of arithmetic operations, approximation by trapezoidal and piecewise linear FNs, visualization, etc.

**Version** 0.3-1

**Date** 2013-06-23

**URL** <http://www.rexamine.com/resources/fuzzynumbers/>

**BugReports** <https://github.com/Rexamine/FuzzyNumbers/issues>

**License** LGPL ( $\geq 3$ )

**ByteCompile** TRUE

**Depends** R ( $\geq 2.12.0$ ), base, methods, grDevices, graphics, stats

**Suggests** testthat

**Collate** 'FuzzyNumbers-package.R' 'class-FuzzyNumber.R' 'class-DiscontinuousFuzzyNumber.R' 'class-TrapezoidalFuzzyNumber.R' 'class-PiecewiseLinearFuzzyNumber.R' 'class-PowerFuzzyNumber.R' 'methods-core.R' 'methods-supply.R' 'methods-value.R' 'methods-expectedValue.R' 'methods-weightedExpectedValue.R' 'methods-width.R' 'methods-ambiguity.R' 'methods-plot.R' 'methods-as.character.R' 'methods-show.R' 'methods-fapply.R' 'methods-alphacut.R' 'methods-evaluate.R' 'auxiliary-convert.R' 'auxiliary-invert.R' 'methods-piecewiseLinearApproximation.R' 'methods-trapezoidalApproximation.R' 'methods-Arithmetic.R' 'methods-alphaInterval.R' 'methods-expectedInterval.R' 'methods-distance.R' 'methods-integrate.R' 'methods-Extract.R' 'methods-as.PiecewiseLinearFuzzyNumber.R' 'methods-as.FuzzyNumber.R' 'methods-as.TrapezoidalFuzzyNumber.R' 'methods-as.PowerFuzzyNumber.R'

**Author** Marek Gagolewski [aut, cre], Jan Caha [ctb]

**Maintainer** Marek Gagolewski <gagolews@rexamine.com>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2013-06-23 16:16:39

## R topics documented:

FuzzyNumbers-package . . . . .	3
alphacut . . . . .	5
alphaInterval . . . . .	6
ambiguity . . . . .	7
approxInvert . . . . .	8
Arithmetic . . . . .	8
as.character . . . . .	11
as.FuzzyNumber . . . . .	12
as.PiecewiseLinearFuzzyNumber . . . . .	13
as.PowerFuzzyNumber . . . . .	14
as.TrapezoidalFuzzyNumber . . . . .	15
convertAlpha . . . . .	16
convertSide . . . . .	17
core . . . . .	18
DiscontinuousFuzzyNumber . . . . .	18
DiscontinuousFuzzyNumber-class . . . . .	20
distance . . . . .	21
evaluate . . . . .	22
expectedInterval . . . . .	23
expectedValue . . . . .	24
Extract . . . . .	25
fapply . . . . .	26
FuzzyNumber . . . . .	27
FuzzyNumber-class . . . . .	28
integrateAlpha . . . . .	29
integrate_discont_val . . . . .	30
piecewiseLinearApproximation . . . . .	31
PiecewiseLinearFuzzyNumber . . . . .	32
PiecewiseLinearFuzzyNumber-class . . . . .	33
plot . . . . .	34
PowerFuzzyNumber . . . . .	36
PowerFuzzyNumber-class . . . . .	37
show . . . . .	38
supp . . . . .	38
trapezoidalApproximation . . . . .	39
TrapezoidalFuzzyNumber . . . . .	41
TrapezoidalFuzzyNumber-class . . . . .	41
TriangularFuzzyNumber . . . . .	42
value . . . . .	43
weightedExpectedValue . . . . .	44
width . . . . .	45

## Description

**FuzzyNumbers** is an open source (LGPL 3) package for R. It provides S4 classes and methods to deal with Fuzzy Numbers. The package may be used by the practitioners as well as by the researchers in fuzzy numbers theory (e.g. for testing new algorithms, generating numerical examples, preparing figures).

## Details

Fuzzy set theory lets us quite intuitively represent imprecise or vague information. Fuzzy numbers, which form a particular subclass of fuzzy sets of the real line, play a significant role in many important theoretical and/or practical considerations. This is because we often describe our knowledge about objects through numbers, e.g. "I'm about 180 cm tall" or "The rocket was launched between 2 and 3 p.m."

For the formal definition of a fuzzy number please refer to the [FuzzyNumber](#) man page. Note that this package also deals with particular types of fuzzy numbers like trapezoidal, piecewise linear, or "parametric" FNs (see [TrapezoidalFuzzyNumber](#), [PiecewiseLinearFuzzyNumber](#), [PowerFuzzyNumber](#), and [\\*EXPERIMENTAL\\* DiscontinuousFuzzyNumber](#))

The package aims to provide the following functionality:

1. Representation of arbitrary fuzzy numbers (including FNs with discontinuous side functions and/or alpha-cuts), as well as their particular types, e.g. trapezoidal and piecewise linear fuzzy numbers,
2. Defuzzification and approximation by triangular and piecewise linear FNs (see e.g. [expectedValue](#), [value](#), [trapezoidalApproximation](#), [piecewiseLinearApproximation](#)),
3. Visualization of FNs (see [plot](#), [as.character](#)),
4. Basic operations on FNs (see e.g. [fapply](#)),
5. Aggregation of FNs **\*\*TO DO\*\***,
6. Ranking of FNs **\*\*TO DO\*\***,
7. Random FN generation **\*\*TO DO\*\***,
8. ...

Please feel free to send any comments and feature requests to the author (see his homepage at <http://staff.rexamine.com/gagolews/>).

For a complete list of classes and methods call `help(package="FuzzyNumbers")`. Moreover, you will surely be interested in a step-by-step guide to the package usage and features which is available by calling `vignette('FuzzyNumbers-Tutorial', 'FuzzyNumbers')` or at <http://github.com/Rexamine/FuzzyNumbers/raw/master/inst/doc/FuzzyNumbers-Tutorial.pdf>.

**Keywords:** Fuzzy Numbers, Fuzzy Sets, Shadowed Sets, Trapezoidal Approximation, Piecewise Linear Approximation, Approximate Reasoning, Imprecision, Vagueness, Randomness.

**Acknowledgments:** Many thanks to Jan Caha, Przemyslaw Grzegorzewski, Lucian Coroianu, and Pablo Villacorta Iglesias for stimulating discussion.

The development of the package in March-June 2013 was partially supported by the European Union from resources of the European Social Fund, Project PO KL “Information technologies: Research and their interdisciplinary applications”, agreement UDA-POKL.04.01.01-00-051/10-00.

### Author(s)

Marek Gagolewski <gagolews@rexamine.com>,  
with contributions from Jan Caha

### References

- FuzzyNumbers** Homepage, <http://www.rexamine.com/resources/fuzzynumbers/>.
- Ban A.I. (2008), Approximation of fuzzy numbers by trapezoidal fuzzy numbers preserving the expected interval, *Fuzzy Sets and Systems* 159, pp. 1327-1344.
- Ban A.I. (2009), On the nearest parametric approximation of a fuzzy number - Revisited, *Fuzzy Sets and Systems* 160, pp. 3027-3047.
- Chanas S. (2001), On the interval approximation of a fuzzy number, *Fuzzy Sets and Systems* 122, pp. 353-356.
- Coroianu L., Gagolewski M., Grzegorzewski P. (2013), Nearest Piecewise Linear Approximation of Fuzzy Numbers, *Fuzzy Sets and Systems*, 2013, doi:10.1016/j.fss.2013.02.005.
- Delgado M., Vila M.A., Voxman W. (1998), On a canonical representation of a fuzzy number, *Fuzzy Sets and Systems* 93, pp. 125-135.
- Dubois D., Prade H. (1978), Operations on fuzzy numbers, *Int. J. Syst. Sci.* 9, pp. 613-626.
- Dubois D., Prade H. (1987), The mean value of a fuzzy number, *Fuzzy Sets and Systems* 24, pp. 279-300.
- Gagolewski M. (2013), A Guide to the **FuzzyNumbers** Package for R, <http://github.com/Rexamine/FuzzyNumbers/raw/master/inst/doc/FuzzyNumbers-Tutorial.pdf>.
- Grzegorzewski P. (2010), Algorithms for trapezoidal approximations of fuzzy numbers preserving the expected interval, In: Bouchon-Meunier B. et al (Eds.), *Foundations of Reasoning Under Uncertainty*, Springer, pp. 85-98.
- Grzegorzewski P. (1998), Metrics and orders in space of fuzzy numbers, *Fuzzy Sets and Systems* 97, pp. 83-94.
- Grzegorzewski P., Pasternak-Winiarska K. (2011), Trapezoidal approximations of fuzzy numbers with restrictions on the support and core, *Proc. EUSFLAT/LFA 2011*, Atlantic Press, pp. 749-756.
- Klir G.J., Yuan B. (1995), *Fuzzy sets and fuzzy logic. Theory and applications*, Prentice Hall, New Jersey.
- Stefanini L., Sorini L. (2009), Fuzzy arithmetic with parametric LR fuzzy numbers, In: *Proc. IFSA/EUSFLAT 2009*, pp. 600-605.
- Yeh C.-T. (2008), Trapezoidal and triangular approximations preserving the expected interval, *Fuzzy Sets and Systems* 159, pp. 1345-1353.

---

alphacut	<i>Calculate Alpha-Cuts</i>
----------	-----------------------------

---

## Description

If  $A$  is a fuzzy numbers, then its  $\alpha$ -cuts are always in form of intervals. Moreover, the  $\alpha$ -cuts form a nonincreasing chain w.r.t.  $\alpha$ .

## Usage

```
## S4 method for signature 'FuzzyNumber,numeric'
alphacut(object, alpha)
```

## Arguments

object	a fuzzy numbers
alpha	numeric vector with elements in $[0,1]$

## Value

a matrix with two columns (left and right alpha cut bounds). if some elements in alpha are not in  $[0,1]$ , then NA is set.

## See Also

Other alpha\_cuts: [core](#), [supp](#)

Other FuzzyNumber-method: [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

## Examples

```
A <- TrapezoidalFuzzyNumber(1, 2, 3, 4)
alphacut(A, c(-1, 0.4, 0.2))
```

---

alphaInterval	<i>Calculate the Alpha-Interval of a Fuzzy Number</i>
---------------	---

---

### Description

We have  $\alpha - Int(A) := [\int_0^1 \alpha A_L(\alpha) d\alpha, \int_0^1 \alpha A_U(\alpha) d\alpha]$ .

### Usage

```
## S4 method for signature 'FuzzyNumber'
alphaInterval(object, ...)

## S4 method for signature 'TrapezoidalFuzzyNumber'
alphaInterval(object)

## S4 method for signature 'PiecewiseLinearFuzzyNumber'
alphaInterval(object)

## S4 method for signature 'PowerFuzzyNumber'
alphaInterval(object)
```

### Arguments

object	a fuzzy number
...	for FuzzyNumber and DiscontinuousFuzzyNumber - additional arguments passed to <a href="#">integrateAlpha</a>

### Details

Note that if an instance of the FuzzyNumber or DiscontinuousFuzzyNumber class is given, the calculation is performed via numerical integration. Otherwise, the computation is exact.

### Value

numeric vector of length 2

### See Also

Other FuzzyNumber-method: [alphacut](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Other PiecewiseLinearFuzzyNumber-method: [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#), [plot](#)

Other PowerFuzzyNumber-method: [as.character](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [PowerFuzzyNumber](#), [PowerFuzzyNumber-class](#)

Other TrapezoidalFuzzyNumber-method: [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [plot](#), [TrapezoidalFuzzyNumber](#), [TrapezoidalFuzzyNumber-class](#), [TriangularFuzzyNumber](#)

---

ambiguity

---

*Calculate the Ambiguity of a Fuzzy Number*


---

## Description

The ambiguity (Delgado et al, 1998) is a measure of nonspecificity of a fuzzy number.

## Usage

```
## S4 method for signature 'FuzzyNumber'
ambiguity(object, ...)
```

## Arguments

object	a fuzzy number
...	additional arguments passed to <a href="#">alphaInterval</a>

## Details

The ambiguity is defined as  $amb(A) := \int_0^1 \alpha (A_U(\alpha) - A_L(\alpha)) d\alpha$ .

## Value

a single numeric value

## References

Delgado M., Vila M.A., Voxman W. (1998), On a canonical representation of a fuzzy number, Fuzzy Sets and Systems 93, pp. 125-135.

## See Also

Other characteristics: [expectedValue](#), [value](#), [weightedExpectedValue](#), [width](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

---

approxInvert

*Approximate the Inverse of a Given Function*


---

### Description

The function may be used to create side generating functions from alpha-cut generators and inversely.

### Usage

```
approxInvert(f,
  method = c("monoH.FC", "linear", "hyman"), n = 500)
```

### Arguments

f	a monotonic, continuous function $f: [0,1] \rightarrow [0,1]$
method	interpolation method: "monoH.FC", "hyman" or "linear"
n	number of interpolation points

### Details

The function is a wrapper to [splinefun](#) and [approxfun](#). Thus, interpolation is used.

### Value

a new function, the approximate inverse of the input

### See Also

[FuzzyNumber](#)

Other auxiliary: [convertAlpha](#), [convertSide](#)

---

Arithmetic

*Arithmetic Operations on Fuzzy Numbers*


---

### Description

Applies arithmetic operations using the extension principle and interval-based calculations.



**Usage**

```

    ## S4 method for signature 'numeric,FuzzyNumber'
    e1 + e2 # e2 + e1

    ## S4 method for signature 'TrapezoidalFuzzyNumber,TrapezoidalFuzzyNumber'
    e1 +
      e2

    ## S4 method for signature 'PiecewiseLinearFuzzyNumber,PiecewiseLinearFuzzyNumber'
    e1 +
      e2

    ## S4 method for signature 'PiecewiseLinearFuzzyNumber,numeric'
    e1 + e2

    ## S4 method for signature 'PiecewiseLinearFuzzyNumber,FuzzyNumber'
    e1 +
      e2 # calls as.PiecewiseLinearFuzzyNumber()

    ## S4 method for signature 'numeric,FuzzyNumber'
    e1 - e2 # e2*(-1) + e1

    ## S4 method for signature 'TrapezoidalFuzzyNumber,TrapezoidalFuzzyNumber'
    e1 -
      e2

    ## S4 method for signature 'PiecewiseLinearFuzzyNumber,PiecewiseLinearFuzzyNumber'
    e1 -
      e2

    ## S4 method for signature 'PiecewiseLinearFuzzyNumber,numeric'
    e1 - e2

    ## S4 method for signature 'PiecewiseLinearFuzzyNumber,FuzzyNumber'
    e1 -
      e2 # calls as.PiecewiseLinearFuzzyNumber()

    ## S4 method for signature 'FuzzyNumber,ANY'
    e1 - e2 # -e1

    ## S4 method for signature 'numeric,FuzzyNumber'
    e1 * e2 # e2 * e1

    ## S4 method for signature 'TrapezoidalFuzzyNumber,numeric'
    e1 * e2

    ## S4 method for signature 'PiecewiseLinearFuzzyNumber,PiecewiseLinearFuzzyNumber'
    e1 *

```

```

e2

## S4 method for signature 'PiecewiseLinearFuzzyNumber,FuzzyNumber'
e1 *
  e2 # calls as.PiecewiseLinearFuzzyNumber()

## S4 method for signature 'PiecewiseLinearFuzzyNumber,numeric'
e1 * e2

## S4 method for signature 'PiecewiseLinearFuzzyNumber,numeric'
e1 / e2

## S4 method for signature 'PiecewiseLinearFuzzyNumber,PiecewiseLinearFuzzyNumber'
e1 /
  e2

## S4 method for signature 'PiecewiseLinearFuzzyNumber,FuzzyNumber'
e1 /
  e2 # calls as.PiecewiseLinearFuzzyNumber()

```

### Arguments

e1	a fuzzy number or single numeric value
e2	a fuzzy number or single numeric value

### Details

Implemented operators: +, -, \*, / for piecewise linear fuzzy numbers. Also some versions may be applied on numeric values and trapezoidal fuzzy numbers.

Note that according to the theory the class of PLFNs is not closed under the operations \* and /. However, if you operate on a large number of knots, the results should be satisfactory.

### Value

a fuzzy number of the class [PiecewiseLinearFuzzyNumber](#) of a [TrapezoidalFuzzyNumber](#)  
a fuzzy number

### See Also

Other extension\_principle: [fapply](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [as.character](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#), [plot](#)

Other TrapezoidalFuzzyNumber-method: [alphaInterval](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [plot](#), [TrapezoidalFuzzyNumber](#), [TrapezoidalFuzzyNumber-class](#), [TriangularFuzzyNumber](#)

as.character

*Get Basic Information on a Fuzzy Number in a String*

## Description

This method is especially useful if you would like to generate LaTeX equations defining a fuzzy numbers.

## Usage

```
## S4 method for signature 'FuzzyNumber'
as.character(x, toLaTeX=FALSE,
             varnameLaTeX="A")

## S4 method for signature 'TrapezoidalFuzzyNumber'
as.character(x,
             toLaTeX=FALSE, varnameLaTeX="A")

## S4 method for signature 'PiecewiseLinearFuzzyNumber'
as.character(x,
             toLaTeX=FALSE, varnameLaTeX="A")

## S4 method for signature 'PowerFuzzyNumber'
as.character(x,
             toLaTeX=FALSE, varnameLaTeX="A")
```

## Arguments

x	a fuzzy number
toLaTeX	logical; should LaTeX code be output?
varnameLaTeX	character; variable name to be included in equations

## Details

Consider calling the [cat](#) function on the resulting string.

Thanks to Jan Caha for suggesting the toLaTeX arg.

## Value

character vector

**See Also**

Other conversion: [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#), [plot](#)

Other PowerFuzzyNumber-method: [alphaInterval](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [PowerFuzzyNumber](#), [PowerFuzzyNumber-class](#)

---

as.FuzzyNumber

*Converts an Object to a Fuzzy Number*


---

**Description**

Please note that applying this function on a [FuzzyNumber](#) child class causes information loss, as it drops all additional slots defined in the child classes. [FuzzyNumber](#) is the base class for all FNs. Note that some functions for TFNs or PLFNs work much faster and are more precise. This function shouldn't be used in normal computations.

**Usage**

```
## S4 method for signature 'numeric'
as.FuzzyNumber(object)

## S4 method for signature 'FuzzyNumber'
as.FuzzyNumber(object)
```

**Arguments**

object            a fuzzy number or a single numeric value (crisp number) or vector of length two (interval)

**Value**

Object of class [FuzzyNumber](#)

**See Also**

Other conversion: [as.character](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

---

as.PiecewiseLinearFuzzyNumber

*Converts an Object to a Piecewise Linear Fuzzy Number*

---

**Description**

This method is only for exact conversion. For other cases (e.g. general FNs), use [piecewiseLinearApproximation](#).

**Usage**

```
## S4 method for signature 'TrapezoidalFuzzyNumber'
as.PiecewiseLinearFuzzyNumber(object,
  knot.n=0, knot.alpha=seq(0, 1,
    length.out=knot.n+2)[-c(1,knot.n+2)])

## S4 method for signature 'numeric'
as.PiecewiseLinearFuzzyNumber(object,
  knot.n=0, knot.alpha=seq(0, 1,
    length.out=knot.n+2)[-c(1,knot.n+2)])

## S4 method for signature 'FuzzyNumber'
as.PiecewiseLinearFuzzyNumber(object,
  knot.n=0, knot.alpha=seq(0, 1,
    length.out=knot.n+2)[-c(1,knot.n+2)])

## S4 method for signature 'PiecewiseLinearFuzzyNumber'
as.PiecewiseLinearFuzzyNumber(object,
  knot.n=0, knot.alpha=seq(0, 1,
    length.out=knot.n+2)[-c(1,knot.n+2)])
```

**Arguments**

object	a fuzzy number or a single numeric value (crisp number) or vector of length two (interval)
knot.n	the number of knots
knot.alpha	knot.n alpha-cut values at knots, defaults to uniformly distributed knots

**Value**

Object of class [PiecewiseLinearFuzzyNumber](#)

**See Also**

Other conversion: [as.character](#), [as.FuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#), [plot](#)

Other TrapezoidalFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [plot](#), [TrapezoidalFuzzyNumber](#), [TrapezoidalFuzzyNumber-class](#), [TriangularFuzzyNumber](#)

---

as.PowerFuzzyNumber	<i>Converts an Object to a Power Fuzzy Number</i>
---------------------	---

---

**Description**

This method is only for exact conversion.

**Usage**

```
## S4 method for signature 'numeric'
as.PowerFuzzyNumber(object)

## S4 method for signature 'FuzzyNumber'
as.PowerFuzzyNumber(object)

## S4 method for signature 'PowerFuzzyNumber'
as.PowerFuzzyNumber(object)

## S4 method for signature 'PiecewiseLinearFuzzyNumber'
as.PowerFuzzyNumber(object)

## S4 method for signature 'TrapezoidalFuzzyNumber'
as.PowerFuzzyNumber(object)
```

**Arguments**

object	a fuzzy number or a single numeric value (crisp number) or vector of length two (interval)
--------	--

**Value**

Object of class [PowerFuzzyNumber](#)

**See Also**

Other conversion: [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#), [plot](#)

Other PowerFuzzyNumber-method: [alphaInterval](#), [as.character](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [PowerFuzzyNumber](#), [PowerFuzzyNumber-class](#)

Other TrapezoidalFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [plot](#), [TrapezoidalFuzzyNumber](#), [TrapezoidalFuzzyNumber-class](#), [TriangularFuzzyNumber](#)

---

as.TrapezoidalFuzzyNumber

*Converts an Object to a Trapezoidal Fuzzy Number*

---

**Description**

This method is only for exact conversion. For other cases (e.g. general FNs), use [trapezoidalApproximation](#).

**Usage**

```
## S4 method for signature 'numeric'
as.TrapezoidalFuzzyNumber(object)
```

```
## S4 method for signature 'FuzzyNumber'
as.TrapezoidalFuzzyNumber(object)
```

```
## S4 method for signature 'PowerFuzzyNumber'
as.TrapezoidalFuzzyNumber(object)
```

```
## S4 method for signature 'PiecewiseLinearFuzzyNumber'
as.TrapezoidalFuzzyNumber(object)
```

```
## S4 method for signature 'TrapezoidalFuzzyNumber'
as.TrapezoidalFuzzyNumber(object)
```

Arguments

object                    a fuzzy number or a single numeric value (crisp number) or vector of length two (interval)

Value

Object of class `TrapezoidalFuzzyNumber`

See Also

Other conversion: `as.character`, `as.FuzzyNumber`, `as.PiecewiseLinearFuzzyNumber`, `as.PowerFuzzyNumber`

Other `FuzzyNumber`-method: `alphacut`, `alphaInterval`, `ambiguity`, `Arithmetic`, `as.character`, `as.FuzzyNumber`, `as.PiecewiseLinearFuzzyNumber`, `as.PowerFuzzyNumber`, `core`, `distance`, `evaluate`, `expectedInterval`, `expectedValue`, `FuzzyNumber`, `FuzzyNumber-class`, `integrateAlpha`, `piecewiseLinearApproximation`, `plot`, `show`, `supp`, `trapezoidalApproximation`, `value`, `weightedExpectedValue`, `width`

Other `PiecewiseLinearFuzzyNumber`-method: `alphaInterval`, `Arithmetic`, `as.character`, `as.PiecewiseLinearFuzzyN`, `as.PowerFuzzyNumber`, `expectedInterval`, `fapply`, `PiecewiseLinearFuzzyNumber`, `PiecewiseLinearFuzzyNumber-cl`, `plot`

Other `PowerFuzzyNumber`-method: `alphaInterval`, `as.character`, `as.PowerFuzzyNumber`, `expectedInterval`, `PowerFuzzyNumber`, `PowerFuzzyNumber-class`

Other `TrapezoidalFuzzyNumber`-method: `alphaInterval`, `Arithmetic`, `as.PiecewiseLinearFuzzyNumber`, `as.PowerFuzzyNumber`, `expectedInterval`, `plot`, `TrapezoidalFuzzyNumber`, `TrapezoidalFuzzyNumber-class`, `TriangularFuzzyNumber`

---

convertAlpha	<i>Convert a Given Upper/Lower Alpha-Cut Function to an Alpha-Cut Generating Function</i>
--------------	---

---

Description

The resulting function calls the original function and then linearly scales its output.

Usage

```
convertAlpha(f, y1, y2)
```

Arguments

f                    a function into [y1,y2]  
y1                   numeric vector of length 1  
y2                   numeric vector of length 1

Value

a new function defined on [0,1] (scaled input)



**See Also**[FuzzyNumber](#)Other auxiliary: [approxInvert](#), [convertSide](#)

---

convertSide*Convert a Given Side Function to Side Generating Function*

---

**Description**

The resulting function linearly scales the input and passes it to the original function.

**Usage**

```
convertSide(f, x1, x2)
```

**Arguments**

f	a function defined on [x1,x2]
x1	numeric vector of length 1; if longer, only the first element is used
x2	numeric vector of length 1; if longer, only the first element is used

**Details**

The function works for  $x1 < x2$  and  $x1 > x2$ .

**Value**

a new function defined on [0,1] (scaled input)

**See Also**[FuzzyNumber](#)Other auxiliary: [approxInvert](#), [convertAlpha](#)

---

core	<i>Calculate the Core of a Fuzzy Number</i>
------	---

---

**Description**

We have  $\text{core}(A) := [a_2, a_3]$ . This gives the values that a fuzzy number necessarily represents.

**Usage**

```
## S4 method for signature 'FuzzyNumber'
core(object)
```

**Arguments**

object            a fuzzy number

**Value**

numeric vector of length 2

**See Also**

Other alpha\_cuts: [alphacut](#), [supp](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

---

DiscontinuousFuzzyNumber

*Creates a Fuzzy Number with Possibly Discontinuous Side Functions  
or Alpha-Cut Bounds*

---

**Description**

For convenience, objects of class [DiscontinuousFuzzyNumber](#) may be created with this function.

**Usage**

```
DiscontinuousFuzzyNumber(a1, a2, a3, a4,
  lower = function(a) rep(NA_real_, length(a)),
  upper = function(a) rep(NA_real_, length(a)),
  left = function(x) rep(NA_real_, length(x)),
  right = function(x) rep(NA_real_, length(x)),
  discontinuities.left = numeric(0),
  discontinuities.right = numeric(0),
  discontinuities.lower = numeric(0),
  discontinuities.upper = numeric(0))
```

**Arguments**

a1	a number specifying left bound of the support
a2	a number specifying left bound of the core
a3	a number specifying right bound of the core
a4	a number specifying right bound of the support
lower	lower alpha-cut bound generator; a nondecreasing function $[0,1] \rightarrow [0,1]$ or returning NA_real_
upper	upper alpha-cut bound generator; a nonincreasing function $[0,1] \rightarrow [1,0]$ or returning NA_real_
left	lower side function generator; a nondecreasing function $[0,1] \rightarrow [0,1]$ or returning NA_real_
right	upper side function generator; a nonincreasing function $[0,1] \rightarrow [1,0]$ or returning NA_real_
discontinuities.left	nondecreasingly sorted numeric vector with elements in $(0,1)$ , possibly of length 0
discontinuities.right	nondecreasingly sorted numeric vector with elements in $(0,1)$ , possibly of length 0
discontinuities.lower	nondecreasingly sorted numeric vector with elements in $(0,1)$ , possibly of length 0
discontinuities.upper	nondecreasingly sorted numeric vector with elements in $(0,1)$ , possibly of length 0

**Value**

Object of class [DiscontinuousFuzzyNumber](#)

**See Also**

Other DiscontinuousFuzzyNumber-method: [DiscontinuousFuzzyNumber-class](#), [distance](#), [integrateAlpha](#), [plot](#)

---

DiscontinuousFuzzyNumber-class

***\*\*EXPERIMENTAL\*\*** S4 Class Representing a Fuzzy Number with Discontinuous Side Functions or Alpha-Cut Bounds*

---

## Description

Discontinuity information increase the precision of some numerical integration-based algorithms, e.g. of [piecewiseLinearApproximation](#). It also allows for making more valid fuzzy number plots.

## Slots

`a1, a2, a3, a4, lower, upper, left, right`: Inherited from the [FuzzyNumber](#) class.

`discontinuities.left`: nondecreasingly sorted numeric vector with elements in (0,1); discontinuity points for the left side generating function

`discontinuities.right`: nondecreasingly sorted numeric vector with elements in (0,1); discontinuity points for the right side generating function

`discontinuities.lower`: nondecreasingly sorted numeric vector with elements in (0,1); discontinuity points for the lower alpha-cut bound generator

`discontinuities.upper`: nondecreasingly sorted numeric vector with elements in (0,1); discontinuity points for the upper alpha-cut bound generator

## Extends

Class [FuzzyNumber](#), directly.

## See Also

[DiscontinuousFuzzyNumber](#) for a convenient constructor

Other DiscontinuousFuzzyNumber-method: [DiscontinuousFuzzyNumber](#), [distance](#), [integrateAlpha](#), [plot](#)

## Examples

```
showClass("DiscontinuousFuzzyNumber")
showMethods(classes="DiscontinuousFuzzyNumber")
```

distance

*Calculate the Distance Between Two Fuzzy Numbers***Description**

Currently, only Euclidean distance may be calculated. We have  $d_E^2(A, B) := \int_0^1 (A_L(\alpha) - B_L(\alpha))^2 d\alpha, \int_0^1 (A_U(\alpha) - B_U(\alpha))^2 d\alpha$ , see (Grzegorzewski, 1988).

**Usage**

```
## S4 method for signature 'FuzzyNumber,FuzzyNumber'
distance(e1, e2,
         type=c("Euclidean", "EuclideanSquared"), ...)

## S4 method for signature 'FuzzyNumber,DiscontinuousFuzzyNumber'
distance(e1,
         e2, type=c("Euclidean", "EuclideanSquared"), ...)

## S4 method for signature 'DiscontinuousFuzzyNumber,FuzzyNumber'
distance(e1,
         e2, type=c("Euclidean", "EuclideanSquared"), ...)

## S4 method for signature 'DiscontinuousFuzzyNumber,DiscontinuousFuzzyNumber'
distance(e1,
         e2, type=c("Euclidean", "EuclideanSquared"), ...)
```

**Arguments**

e1	a fuzzy number
e2	a fuzzy number
type	one of "Euclidean", "EuclideanSquared"
...	additional arguments passed to <a href="#">integrate</a>

**Details**

The calculation are done using numerical integration,

**Value**

the calculated distance, single numeric value

**References**

Grzegorzewski P., Metrics and orders in space of fuzzy numbers, Fuzzy Sets and Systems 97, 1998, pp. 83-94.

See Also

Other DiscontinuousFuzzyNumber-method: [DiscontinuousFuzzyNumber](#), [DiscontinuousFuzzyNumber-class](#), [integrateAlpha](#), [plot](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

---

evaluate	<i>Evaluate the Membership Function</i>
----------	---

---

Description

This function returns the value(s) of the membership function of a fuzzy number at given point(s).

Usage

```
## S4 method for signature 'FuzzyNumber,numeric'
evaluate(object, x)
```

Arguments

object	a fuzzy numbers
x	numeric vector

Value

a numeric vector

See Also

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Examples

```
T <- TrapezoidalFuzzyNumber(1,2,3,4)
evaluate(T, seq(0, 5, by=0.5))
```

---

expectedInterval	<i>Calculate the Expected Interval of a Fuzzy Number</i>
------------------	--

---

### Description

We have  $EI(A) := [\int_0^1 A_L(\alpha) d\alpha, \int_0^1 A_U(\alpha) d\alpha]$ , see (Duboid, Prade, 1987).

### Usage

```
## S4 method for signature 'FuzzyNumber'
expectedInterval(object, ...)

## S4 method for signature 'TrapezoidalFuzzyNumber'
expectedInterval(object)

## S4 method for signature 'PiecewiseLinearFuzzyNumber'
expectedInterval(object)

## S4 method for signature 'PowerFuzzyNumber'
expectedInterval(object)
```

### Arguments

object	a fuzzy number
...	for FuzzyNumber and DiscontinuousFuzzyNumber - additional arguments passed to <a href="#">integrateAlpha</a>

### Details

Note that if an instance of the FuzzyNumber or DiscontinuousFuzzyNumber class is given, the calculation is performed via numerical integration. Otherwise, the computation is exact.

### Value

numeric vector of length 2

### References

Dubois D., Prade H. (1987), The mean value of a fuzzy number, Fuzzy Sets and Systems 24, pp. 279-300.

### See Also

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#),

[piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Other [PiecewiseLinearFuzzyNumber](#)-method: [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyN](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#), [plot](#)

Other [PowerFuzzyNumber](#)-method: [alphaInterval](#), [as.character](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNum](#), [PowerFuzzyNumber](#), [PowerFuzzyNumber-class](#)

Other [TrapezoidalFuzzyNumber](#)-method: [alphaInterval](#), [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [plot](#), [TrapezoidalFuzzyNumber](#), [TrapezoidalFuzzyNumber-cla](#), [TriangularFuzzyNumber](#)

---

<code>expectedValue</code>	<i>Calculate the Expected Value of a Fuzzy Number</i>
----------------------------	---

---

**Description**

The calculation of the so-called expected value is one of possible methods to defuzzify a fuzzy number.

**Usage**

```
## S4 method for signature 'FuzzyNumber'
expectedValue(object, ...)
```

**Arguments**

<code>object</code>	a fuzzy number
<code>...</code>	additional arguments passed to <a href="#">expectedInterval</a>

**Details**

The expected value of  $A$  is defined as  $EV(A) := (EI_U(A) + EI_L(A))/2$ , where  $EI$  is the [expectedInterval](#).

**Value**

a single numeric value

**See Also**

Other characteristics: [ambiguity](#), [value](#), [weightedExpectedValue](#), [width](#)

Other defuzzification: [value](#), [weightedExpectedValue](#)

Other [FuzzyNumber](#)-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)



---

Extract

*FuzzyNumber Slot Accessors*

---

## Description

For possible slot names see man pages for the [FuzzyNumber](#) class and its derivatives

## Usage

```
## S4 method for signature 'FuzzyNumber,character'
x[i]

## S4 method for signature 'PiecewiseLinearFuzzyNumber,character'
x[i]

## S4 method for signature 'PowerFuzzyNumber,character'
x[i]

## S4 method for signature 'DiscontinuousFuzzyNumber,character'
x[i]
```

## Arguments

x	a fuzzy number
i	character; slot name

## Details

All slot accessors are read-only.

## Value

slot value

## Examples

```
A <- FuzzyNumber(1,2,3,4)
A["a1"]
A["right"]
```

fapply

*Apply a Function on a Fuzzy Number***Description**

Applies a given monotonic function using the extension principle (i.e. the function is applied on alpha-cuts).

**Usage**

```
## S4 method for signature 'PiecewiseLinearFuzzyNumber,function'
fapply(object,
       fun, ...)
```

**Arguments**

object	a fuzzy number
fun	a monotonic, vectorized R function
...	additional arguments passed to fun

**Details**

Currently only a method for the [PiecewiseLinearFuzzyNumber](#) class has been defined. The computations are exact (up to a numeric error) at knots. So, make sure you have a sufficient number of knots if you want good approximation.

For other types of fuzzy numbers, consider using [piecewiseLinearApproximation](#).

**Value**

a [PiecewiseLinearFuzzyNumber](#)

**See Also**

Other extension\_principle: [Arithmetic](#)

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyN](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#), [plot](#)

---

FuzzyNumber	<i>Creates a Fuzzy Number</i>
-------------	-------------------------------

---

## Description

For convenience, objects of class [FuzzyNumber](#) may be created with this function.

## Usage

```
FuzzyNumber(a1, a2, a3, a4,
  lower = function(a) rep(NA_real_, length(a)),
  upper = function(a) rep(NA_real_, length(a)),
  left = function(x) rep(NA_real_, length(x)),
  right = function(x) rep(NA_real_, length(x)))
```

## Arguments

a1	a number specyfing left bound of the support
a2	a number specyfing left bound of the core
a3	a number specyfing right bound of the core
a4	a number specyfing right bound of the support
lower	lower alpha-cut bound generator; a nondecreasing function $[0,1] \rightarrow [0,1]$ or returning NA_real_
upper	upper alpha-cut bound generator; a nonincreasing function $[0,1] \rightarrow [1,0]$ or returning NA_real_
left	lower side function generator; a nondecreasing function $[0,1] \rightarrow [0,1]$ or returning NA_real_
right	upper side function generator; a nonincreasing function $[0,1] \rightarrow [1,0]$ or returning NA_real_

## Value

Object of class [FuzzyNumber](#)

## See Also

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

### Description

Formally, a fuzzy number  $A$  (Dubois, Prade, 1978) is a fuzzy subset of the real line  $R$  with membership function  $\mu$  given by:

$$\mu(x) = \begin{cases} 0 & \text{if } x < a1, \\ \text{left}((x - a1)/(a2 - a1)) & \text{if } a1 \leq x < a2, \\ 1 & \text{if } a2 \leq x \leq a3, \\ \text{right}((x - a3)/(a4 - a3)) & \text{if } a3 < x \leq a4, \\ 0 & \text{if } a4 < x, \end{cases}$$

where  $a1, a2, a3, a4 \in R$ ,  $a1 \leq a2 \leq a3 \leq a4$ ,  $\text{left} : [0, 1] \rightarrow [0, 1]$  is a nondecreasing function called the *left side generator of A*, and  $\text{right} : [0, 1] \rightarrow [0, 1]$  is a nonincreasing function called the *right side generator of A*.

Alternatively, it may be shown that each fuzzy number  $A$  may be uniquely determined by specifying its  $\alpha$ -cuts,  $A(\alpha)$ . We have  $A(0) = [a1, a4]$  and

$$A(\alpha) = [a1 + (a2 - a1) * \text{lower}(\alpha), a3 + (a4 - a3) * \text{upper}(\alpha)]$$

for  $0 < \alpha \leq 1$ , where  $\text{lower} : [0, 1] \rightarrow [0, 1]$  and  $\text{upper} : [0, 1] \rightarrow [0, 1]$  are, respectively, strictly increasing and decreasing functions satisfying  $\text{lower}(\alpha) = \inf\{x : \mu(x) \geq \alpha\}$  and  $\text{upper}(\alpha) = \sup\{x : \mu(x) \geq \alpha\}$ .

### Details

Please note that many algorithms that deal with fuzzy numbers often use  $\alpha$ -cuts rather than side functions.

Note that the **FuzzyNumbers** package also deals with particular types of fuzzy numbers like trapezoidal, piecewise linear, or “parametric” FNs.

### Slots

**a1:** Single numeric value specifying the left bound for the support.

**a2:** Single numeric value specifying the left bound for the core.

**a3:** Single numeric value specifying the right bound for the core.

**a4:** Single numeric value specifying the right bound for the support.

**lower:** A nondecreasing function  $[0,1] \rightarrow [0,1]$  that gives the lower alpha-cut bound.

**upper:** A nonincreasing function  $[0,1] \rightarrow [0,1]$  that gives the upper alpha-cut bound.

**left:** A nondecreasing function  $[0,1] \rightarrow [0,1]$  that gives the left side function.

**right:** A nonincreasing function  $[0,1] \rightarrow [0,1]$  that gives the right side function.

Child/sub classes

[TrapezoidalFuzzyNumber](#), [PiecewiseLinearFuzzyNumber](#), [PowerFuzzyNumber](#), and [DiscontinuousFuzzyNumber](#)

See Also

[FuzzyNumber](#) for a convenient constructor, and [as.FuzzyNumber](#) for conversion of objects to this class. Also, see [convertSide](#) for creating side functions generators, [convertAlpha](#) for creating alpha-cut bounds generators, [approxInvert](#) for inverting side functions/alpha-cuts numerically.

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Examples

```
showClass("FuzzyNumber")
showMethods(classes="FuzzyNumber")
```

---

integrateAlpha	<i>Numerically Integrate Alpha-Cut Bounds</i>
----------------	---

---

Description

Integrates numerically a transformed or weighted lower or upper alpha-cut bound of a fuzzy number.

Usage

```
## S4 method for signature 'FuzzyNumber,character,numeric,numeric'
integrateAlpha(object,
  which=c("lower", "upper"), from=0, to=1, weight=NULL,
  transform=NULL, ...)

## S4 method for signature 'DiscontinuousFuzzyNumber,character,numeric,numeric'
integrateAlpha(object,
  which=c("lower", "upper"), from=0, to=1, weight=NULL,
  transform=NULL, ...)
```

Arguments

object	a fuzzy number
which	one of "lower", "upper"
from	numeric
to	numeric
weight	a function or NULL
transform	a function or NULL
...	additional arguments passed to <a href="#">integrate</a> or <a href="#">integrate_discont_val</a>

**Value**

a single numeric value

**See Also**

Other DiscontinuousFuzzyNumber-method: [DiscontinuousFuzzyNumber](#), [DiscontinuousFuzzyNumber-class](#), [distance](#), [plot](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

---

`integrate_discont_val` *Integrate a Function with at Most Finite Number of Discontinuities*  
*\*EXPERIMENTAL\**

---

**Description**

The function uses multiple calls to [integrate](#).

**Usage**

```
integrate_discont_val(f, from, to,
  discontinuities = numeric(0), ...)
```

**Arguments**

<code>f</code>	an R function taking a numeric vector of length 1 as its first argument and returning a numeric vector of length 1
<code>from</code>	the lower limit of integration
<code>to</code>	the upper limit of integration
<code>discontinuities</code>	nondecreasingly sorted numeric vector which indicates the points at which <code>f</code> is discontinuous
<code>...</code>	further arguments to be passed to the <a href="#">integrate</a> function.

**Value**

the estimate of the integral

---

piecewiseLinearApproximation

*Piecewise Linear Approximation of a Fuzzy Number*

---

## Description

This method finds a piecewise linear approximation  $P(A)$  of a given fuzzy number  $A$  by using the algorithm specified by the method parameter.

## Usage

```
## S4 method for signature 'FuzzyNumber'
piecewiseLinearApproximation(object,
  method=c("NearestEuclidean", "Naive",
    "ApproximateNearestEuclidean [DEPRECATED]"), knot.n=1,
  knot.alpha=seq(0, 1,
    length.out=knot.n+2)[-c(1,knot.n+2)], ...,
  verbose=FALSE)
```

## Arguments

object	a fuzzy number
method	character; one of: "NearestEuclidean" (default), or "Naive"
knot.n	desired number of knots (if missing, then calculated from given knot.alpha)
knot.alpha	alpha-cuts at which knots will be positioned (defaults to equally distributed knots)
verbose	logical; should some technical details on the computations being performed be printed? [only "NearestEuclidean"]
...	further arguments passed to <a href="#">integrateAlpha</a> [only "NearestEuclidean"]

## Details

‘method’ may be one of:

1. NearestEuclidean: see (Coroianu, Gagolewski, Grzegorzewski, 2013a) for the description of the knot.n==1 case; uses numerical integration, see [integrateAlpha](#). Slow for large knot.n.
2. Naive: We have  $\text{core}(A) == \text{core}(T(A))$  and  $\text{supp}(A) == \text{supp}(T(A))$  and the knots are taken directly from the specified alpha cuts (linear interpolation).

## References

Coroianu L., Gagolewski M., Grzegorzewski P. (2013a), Nearest Piecewise Linear Approximation of Fuzzy Numbers, Fuzzy Sets and Systems, doi:10.1016/j.fss.2013.02.005.  
 Coroianu L., Gagolewski M., Grzegorzewski P. (2013b), Nearest Piecewise Linear Approximation of Fuzzy Numbers - general case, in preparation.

**See Also**

Other approximation: [trapezoidalApproximation](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

**Examples**

```
(A <- FuzzyNumber(-1,0,1,3,lower=function(x) sqrt(x),upper=function(x) 1-sqrt(x)))
(PA <- piecewiseLinearApproximation(A, "NearestEuclidean", knot.n=1, knot.alpha=0.2))
```

---

PiecewiseLinearFuzzyNumber

*Creates a Piecewise Linear Fuzzy Number*

---

**Description**

For convenience, objects of class [PiecewiseLinearFuzzyNumber](#) may be created with this function.

**Usage**

```
PiecewiseLinearFuzzyNumber(a1, a2, a3, a4, knot.n = 0,
  knot.alpha = numeric(0), knot.left = numeric(0),
  knot.right = numeric(0))
```

**Arguments**

a1	a number specifying left bound of the support
a2	a number specifying left bound of the core
a3	a number specifying right bound of the core
a4	a number specifying right bound of the support
knot.n	the number of knots
knot.alpha	knot.n alpha-cut values at knots
knot.left	knot.n knots on the left side; a nondecreasingly sorted vector with elements in [a1,a2]
knot.right	knot.n knots on the right side; a nondecreasingly sorted vector with elements in [a3,a4]

**Details**

If a1, a2, a3, and a4 are missing, then knot.left and knot.right may be of length knot.n+2.

If knot.n is not given, then it guessed from length(knot.left). If knot.alpha is missing, then the knots will be equally distributed on the interval [0,1].



## Value

An object of class [PiecewiseLinearFuzzyNumber](#).

## See Also

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyN](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber-cla](#), [plot](#)

---

PiecewiseLinearFuzzyNumber-class

*S4 Class Representing a Piecewise Linear Fuzzy Number*

---

## Description

A piecewise linear fuzzy number (PLFN) has side functions and alpha-cut bounds that linearly interpolate a given set of points (at fixed alpha-cuts).

## Details

If `knot.n` is equal to 0 or all left and right knots lie on common lines, then a Piecewise Linear Fuzzy Number reduces to a [TrapezoidalFuzzyNumber](#). Note that, however, the [TrapezoidalFuzzyNumber](#) does not inherit from [PiecewiseLinearFuzzyNumber](#) for efficiency reasons. To convert the former to the latter, call [as.PiecewiseLinearFuzzyNumber](#).

## Slots

`a1`, `a2`, `a3`, `a4`, `lower`, `upper`, `left`, `right`: Inherited from the [FuzzyNumber](#) class.  
`knot.n`: number of knots, a single integer value, 0 for a trapezoidal fuzzy number  
`knot.alpha`: alpha-cuts, increasingly sorted vector of length `knot.n` with elements in  $[0,1]$   
`knot.left`: nondecreasingly sorted vector of length `knot.n`; defines left alpha-cut bounds at knots  
`knot.right`: nondecreasingly sorted vector of length `knot.n`; defines right alpha-cut bounds at knots

## Extends

Class [FuzzyNumber](#), directly.

## See Also

[PiecewiseLinearFuzzyNumber](#) for a convenient constructor, [as.PiecewiseLinearFuzzyNumber](#) for conversion of objects to this class, and [piecewiseLinearApproximation](#) for approximation routines.

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyN](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [plot](#)

## Examples

```
showClass("PiecewiseLinearFuzzyNumber")
showMethods(classes="PiecewiseLinearFuzzyNumber")
```

---

plot

*Plot a Fuzzy Number*

---

## Description

The function aims to provide a similar look-and-feel to the built-in `plot.default` and `curve` function.

## Usage

```
## S4 method for signature 'FuzzyNumber,missing'
plot(x, y, from=NULL,
      to=NULL, n=101, at.alpha=NULL,
      draw.membership.function=TRUE,
      draw.alphacuts=!draw.membership.function, xlab=NULL,
      ylab=NULL, xlim=NULL, ylim=NULL, type="l", col=1,
      lty=1, pch=1, lwd=1, shadowdensity=15, shadowangle=45,
      shadowcol=col, shadowborder=NULL, add=FALSE, ...)

## S4 method for signature 'TrapezoidalFuzzyNumber,missing'
plot(x, y,
      from=NULL, to=NULL, draw.membership.function=TRUE,
      draw.alphacuts=!draw.membership.function, xlab=NULL,
      ylab=NULL, xlim=NULL, ylim=NULL, type="l", col=1,
      lty=1, pch=1, lwd=1, add=FALSE, ...)

## S4 method for signature 'PiecewiseLinearFuzzyNumber,missing'
plot(x, y,
      from=NULL, to=NULL, draw.membership.function=TRUE,
      draw.alphacuts=!draw.membership.function, xlab=NULL,
      ylab=NULL, xlim=NULL, ylim=NULL, type="l", col=1,
      lty=1, pch=1, lwd=1, add=FALSE, ...)

## S4 method for signature 'DiscontinuousFuzzyNumber,missing'
plot(x, y,
      from=NULL, to=NULL, n=101,
      draw.membership.function=TRUE,
      draw.alphacuts=!draw.membership.function, xlab=NULL,
      ylab=NULL, xlim=NULL, ylim=NULL, type="l", col=1,
      lty=1, pch=1, lwd=1, add=FALSE, ...)
```

**Arguments**

x	a fuzzy number
y	not used
from	numeric;
to	numeric;
n	numeric; number of points to probe
at.alpha	numeric vector; give exact alpha-cuts at which linear interpolation should be done
draw.membership.function	logical; you want membership function (TRUE) or alpha-cuts plot (FALSE)?
draw.alphacuts	logical; defaults !draw.membership.function
xlab	character; x-axis label
ylab	character; y-axis label
xlim	numeric;
ylim	numeric;
type	character; defaults "l"; plot type, e.g. "l" for lines, "p" for points, or "b" for both
col	see <a href="#">plot.default</a>
lty	see <a href="#">plot.default</a>
pch	see <a href="#">plot.default</a>
lwd	see <a href="#">plot.default</a>
shadowdensity	numeric; for shadowed sets;
shadowangle	numeric; for shadowed sets;
shadowcol	color specification, see <a href="#">plot.default</a> ; for shadowed sets;
shadowborder	numeric; for shadowed sets;
add	logical; add another FuzzyNumber to existing plot?
...	further arguments passed to <a href="#">plot.default</a>

**Details**

Note that if `from > a1` then it is set to `a1`.

**Value**

nothing really interesting

See Also

Other DiscontinuousFuzzyNumber-method: [DiscontinuousFuzzyNumber](#), [DiscontinuousFuzzyNumber-class](#), [distance](#), [integrateAlpha](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

Other PiecewiseLinearFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.character](#), [as.PiecewiseLinearFuzzyN](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [fapply](#), [PiecewiseLinearFuzzyNumber](#), [PiecewiseLinearFuzzyNumber-class](#)

Other TrapezoidalFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [TrapezoidalFuzzyNumber](#), [TrapezoidalFuzzyNumber-class](#), [TriangularFuzzyNumber](#)

Examples

```
plot(FuzzyNumber(0,1,2,3), col="gray")
plot(FuzzyNumber(0,1,2,3, left=function(x) x^2, right=function(x) 1-x^3), add=TRUE)
plot(FuzzyNumber(0,1,2,3, lower=function(x) x, upper=function(x) 1-x), add=TRUE, col=2)
```

---

PowerFuzzyNumber	<i>Creates a Fuzzy Number with Sides Given by Power Functions</i>
------------------	---

---

Description

For convenience, objects of class [PowerFuzzyNumber](#) may be created with this function.

Usage

```
PowerFuzzyNumber(a1, a2, a3, a4, p.left = 1, p.right = 1)
```

Arguments

- a1                    a number specyfing left bound of the support
- a2                    a number specyfing left bound of the core
- a3                    a number specyfing right bound of the core
- a4                    a number specyfing right bound of the support
- p.left                a positive number specyfing the exponent for the left side
- p.right               a positive number specyfing the exponent for the right side

Value

Object of class [PowerFuzzyNumber](#)

**See Also**

Other PowerFuzzyNumber-method: [alphaInterval](#), [as.character](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [PowerFuzzyNumber-class](#)

---

PowerFuzzyNumber-class

*S4 class Representing a Fuzzy Number with Sides Given by Power Functions*

---

**Description**

Fuzzy numbers which sides are given by power functions are defined using four coefficients  $a_1 \leq a_2 \leq a_3 \leq a_4$ , and parameters  $p.\text{left}$ ,  $p.\text{right} > 0$ , which determine exponents for the side functions.

**Details**

We have  $\text{left}(x) = x^{p.\text{left}}$ , and  $\text{right}(x) = (1 - x)^{p.\text{right}}$ .

This class is a natural generalization of trapezoidal FNs. For other see [PiecewiseLinearFuzzyNumber](#).

**Slots**

$a_1$ ,  $a_2$ ,  $a_3$ ,  $a_4$ , lower, upper, left, right: Inherited from the [FuzzyNumber](#) class.

$p.\text{left}$ : single numeric value; 1.0 for a trapezoidal FN.

$p.\text{right}$ : single numeric value; 1.0 for a trapezoidal FN.

**Extends**

Class [FuzzyNumber](#), directly.

**See Also**

[PowerFuzzyNumber](#) for a convenient constructor, [as.PowerFuzzyNumber](#) for conversion of objects to this class.

[PowerFuzzyNumber](#) for a convenient constructor

Other PowerFuzzyNumber-method: [alphaInterval](#), [as.character](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [PowerFuzzyNumber](#)

**Examples**

```
showClass("PowerFuzzyNumber")
showMethods(classes="PowerFuzzyNumber")
```

---

show	<i>Print Basic Information on a Fuzzy Number</i>
------	--

---

**Description**

See [as.character](#) for more details.

**Usage**

```
## S4 method for signature 'FuzzyNumber'
show(object)
```

**Arguments**

object                    a fuzzy number

**Details**

The method [as.character](#) is called on given fuzzy number object with default arguments. The results are printed on stdout.

**Value**

nothing interesting

**See Also**

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

---

supp	<i>Calculate the Support of a Fuzzy Number</i>
------	--

---

**Description**

We have  $\text{supp}(A) := [a1, a4]$ . This gives the values that a fuzzy number possibly may represent.

**Usage**

```
## S4 method for signature 'FuzzyNumber'
supp(object)
```

**Arguments**

object            a fuzzy number

**Value**

numeric vector of length 2

**See Also**

Other alpha\_cuts: [alphacut](#), [core](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#), [width](#)

---

trapezoidalApproximation

*Trapezoidal Approximation of a Fuzzy Number*

---

**Description**

This method finds a trapezoidal approximation  $T(A)$  of a given fuzzy number  $A$  by using the algorithm specified by the method parameter.

**Usage**

```
## S4 method for signature 'FuzzyNumber'
trapezoidalApproximation(object,
  method=c("NearestEuclidean",
    "ExpectedIntervalPreserving", "SupportCoreRestricted",
    "Naive"), ..., verbose=FALSE)
```

**Arguments**

object            a fuzzy number

method            character; one of: "NearestEuclidean" (default), "ExpectedIntervalPreserving", "SupportCoreRestricted", "Naive"

verbose           logical; should some technical details on the computations being performed be printed?

...                further arguments passed to [integrateAlpha](#)

## Details

method may be one of:

1. NearestEuclidean: see (Ban, 2009); uses numerical integration, see [integrateAlpha](#)
2. Naive: We have  $\text{core}(A) == \text{core}(T(A))$  and  $\text{supp}(A) == \text{supp}(T(A))$
3. ExpectedIntervalPreserving: L2-nearest trapezoidal approximation preserving the expected interval given in (Grzegorzewski, 2010; Ban, 2008; Yeh, 2008) Unfortunately, for highly skewed membership functions this approximation operator may have quite unfavourable behavior. E.g. if  $\text{Val}(A) < \text{EV}_{1/3}(A)$  or  $\text{Val}(A) > \text{EV}_{2/3}(A)$ , then it may happen that the core of the output and the core of the original fuzzy number A are disjoint (cf. Grzegorzewski, Pasternak-Winiarska, 2011)
4. SupportCoreRestricted: This method was proposed in (Grzegorzewski, Pasternak-Winiarska, 2011). L2-nearest trapezoidal approximation with constraints  $\text{core}(A) \subseteq \text{core}(T(A))$  and  $\text{supp}(T(A)) \subseteq \text{supp}(A)$ , i.e. for which each point that surely belongs to A also belongs to T(A), and each point that surely does not belong to A also does not belong to T(A).

## References

- Ban A.I. (2008), Approximation of fuzzy numbers by trapezoidal fuzzy numbers preserving the expected interval, Fuzzy Sets and Systems 159, pp. 1327-1344.
- Ban A.I. (2009), On the nearest parametric approximation of a fuzzy number - Revisited, Fuzzy Sets and Systems 160, pp. 3027-3047.
- Grzegorzewski P. (2010), Algorithms for trapezoidal approximations of fuzzy numbers preserving the expected interval, In: Bouchon-Meunier B. et al (Eds.), Foundations of Reasoning Under Uncertainty, Springer, pp. 85-98.
- Grzegorzewski P, Pasternak-Winiarska K. (2011), Trapezoidal approximations of fuzzy numbers with restrictions on the support and core, Proc. EUSFLAT/LFA 2011, Atlantic Press, pp. 749-756.
- Yeh C.-T. (2008), Trapezoidal and triangular approximations preserving the expected interval, Fuzzy Sets and Systems 159, pp. 1345-1353.

## See Also

Other approximation: [piecewiseLinearApproximation](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [value](#), [weightedExpectedValue](#), [width](#)

## Examples

```
(A <- FuzzyNumber(-1,0,1,40,lower=function(x) sqrt(x),upper=function(x) 1-sqrt(x)))
(TA <- trapezoidalApproximation(A, "ExpectedIntervalPreserving")) # Note that cores are disjoint!
expectedInterval(A)
expectedInterval(TA)
```



---

TrapezoidalFuzzyNumber

*Creates a Trapezoidal Fuzzy Number*


---

### Description

For convenience, objects of class [TrapezoidalFuzzyNumber](#) may be created with this function.

### Usage

```
TrapezoidalFuzzyNumber(a1, a2, a3, a4)
```

### Arguments

a1	a number specifying left bound of the support
a2	a number specifying left bound of the core
a3	a number specifying right bound of the core
a4	a number specifying right bound of the support

### Value

Object of class [TrapezoidalFuzzyNumber](#)

### See Also

Other TrapezoidalFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [plot](#), [TrapezoidalFuzzyNumber-class](#), [TriangularFuzzyNumber](#)

---

TrapezoidalFuzzyNumber-class

*S4 class Representing a Trapezoidal Fuzzy Number*


---

### Description

Trapezoidal Fuzzy Numbers have linear side functions and alpha-cut bounds.

### Details

Trapezoidal fuzzy numbers are among the simplest FNs. Despite their simplicity, however, they include triangular FNs, “crisp” real intervals, and “crisp” reals. Please note that currently no separate classes for these particular TFNs types are implemented in the package.

**Slots**

a1, a2, a3, a4, lower, upper, left, right: Inherited from the [FuzzyNumber](#) class.

**Extends**

Class [FuzzyNumber](#), directly.

**See Also**

[TrapezoidalFuzzyNumber](#) for a convenient constructor, [as.TrapezoidalFuzzyNumber](#) for conversion of objects to this class, and [trapezoidalApproximation](#) for approximation routines.

Other TrapezoidalFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [plot](#), [TrapezoidalFuzzyNumber](#), [TriangularFuzzyNumber](#)

**Examples**

```
showClass("TrapezoidalFuzzyNumber")
showMethods(classes="TrapezoidalFuzzyNumber")
```

---

`TriangularFuzzyNumber` *Creates a Triangular Fuzzy Number*

---

**Description**

For convenience, objects of class [TrapezoidalFuzzyNumber](#) may be created with this function.

**Usage**

```
TriangularFuzzyNumber(a1, amid, a4)
```

**Arguments**

a1	a number specyfing left bound of the support
amid	a number specyfing the core
a4	a number specyfing right bound of the support

**Details**

Currently there is no separate class of a Triangular Fuzzy Number.

**Value**

Object of class [TrapezoidalFuzzyNumber](#)

**See Also**

Other TrapezoidalFuzzyNumber-method: [alphaInterval](#), [Arithmetic](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [expectedInterval](#), [plot](#), [TrapezoidalFuzzyNumber](#), [TrapezoidalFuzzyNumber-class](#)

value

*Calculate the Value of a Fuzzy Number***Description**

The calculation of the so-called value is one of possible methods to defuzzify a fuzzy number.

**Usage**

```
## S4 method for signature 'FuzzyNumber'
value(object, ...)
```

**Arguments**

`object`            a fuzzy number  
`...`              additional arguments passed to [alphaInterval](#)

**Details**

The value of  $A$  (Delgado et al, 1998) is defined as  $val(A) := \int_0^1 \alpha (A_L(\alpha) + A_U(\alpha)) d\alpha$ .

**Value**

a single numeric value

**References**

Delgado M., Vila M.A., Voxman W. (1998), On a canonical representation of a fuzzy number, Fuzzy Sets and Systems 93, pp. 125-135.

**See Also**

Other characteristics: [ambiguity](#), [expectedValue](#), [weightedExpectedValue](#), [width](#)

Other defuzzification: [expectedValue](#), [weightedExpectedValue](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [weightedExpectedValue](#), [width](#)

---

weightedExpectedValue *Calculate the Weighted Expected Value of a Fuzzy Number*

---

### Description

The calculation of the so-called weighted expected value is one of possible methods to defuzzify a fuzzy number.

For  $w = 0.5$  we get the ordinary [expectedValue](#).

### Usage

```
## S4 method for signature 'FuzzyNumber'
weightedExpectedValue(object,
  w=0.5, ...)
```

### Arguments

object	a fuzzy number
w	a single numeric value in [0,1]
...	additional arguments passed to <a href="#">expectedInterval</a>

### Details

The weighted expected value of  $A$  is defined as  $EV_w(A) := (1 - w)EI_L(A) + wEI_U(A)$ , where  $EI$  is the [expectedInterval](#).

### Value

a single numeric value

### See Also

Other characteristics: [ambiguity](#), [expectedValue](#), [value](#), [width](#)

Other defuzzification: [expectedValue](#), [value](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [width](#)

---

width	<i>Calculate the Width of a Fuzzy Number</i>
-------	--

---

### Description

The width (Chanas, 2001) is a measure of nonspecificity of a fuzzy number.

### Usage

```
## S4 method for signature 'FuzzyNumber'
width(object, ...)
```

### Arguments

object	a fuzzy number
...	additional arguments passed to <a href="#">expectedInterval</a>

### Details

The width of  $A$  is defined as  $width(A) := EI_U(A) - EI_L(A)$ , where  $EI$  is the [expectedInterval](#).

### Value

a single numeric value

### References

Chanas S. (2001), On the interval approximation of a fuzzy number, Fuzzy Sets and Systems 122, pp. 353-356.

### See Also

Other characteristics: [ambiguity](#), [expectedValue](#), [value](#), [weightedExpectedValue](#)

Other FuzzyNumber-method: [alphacut](#), [alphaInterval](#), [ambiguity](#), [Arithmetic](#), [as.character](#), [as.FuzzyNumber](#), [as.PiecewiseLinearFuzzyNumber](#), [as.PowerFuzzyNumber](#), [as.TrapezoidalFuzzyNumber](#), [core](#), [distance](#), [evaluate](#), [expectedInterval](#), [expectedValue](#), [FuzzyNumber](#), [FuzzyNumber-class](#), [integrateAlpha](#), [piecewiseLinearApproximation](#), [plot](#), [show](#), [supp](#), [trapezoidalApproximation](#), [value](#), [weightedExpectedValue](#)

# Index

<code>*</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>FuzzyNumber-method</code> (Arithmetic), 8	<code>as.character</code> , <code>FuzzyNumber-method</code> (Extract), 25
<code>*</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>PiecewiseLinearFuzzyNumber-method</code> (Arithmetic), 8	<code>as.character</code> , <code>PiecewiseLinearFuzzyNumber-method</code> (Extract), 25
<code>*</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>numeric-method</code> (Arithmetic), 8	<code>as.character</code> , <code>PowerFuzzyNumber-method</code> (Extract), 25
<code>*</code> , <code>TrapezoidalFuzzyNumber</code> , <code>numeric-method</code> (Arithmetic), 8	<code>alphacut</code> , 5, 6, 7, 10, 12–16, 18, 22–24, 27, 29, 30, 32, 36, 38–40, 43–45
<code>*</code> , <code>numeric</code> , <code>FuzzyNumber-method</code> (Arithmetic), 8	<code>alphacut</code> , <code>FuzzyNumber-method</code> (alphacut), 5
<code>+</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>FuzzyNumber-method</code> (Arithmetic), 8	<code>alphaInterval</code> , 5, 6, 7, 10–16, 18, 22–24, 26, 27, 29, 30, 32, 33, 36–45
<code>+</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>PiecewiseLinearFuzzyNumber-method</code> (Arithmetic), 8	<code>alphaInterval</code> , <code>FuzzyNumber-method</code> (alphaInterval), 6
<code>+</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>numeric-method</code> (Arithmetic), 8	<code>alphaInterval</code> , <code>PiecewiseLinearFuzzyNumber-method</code> (alphaInterval), 6
<code>+</code> , <code>TrapezoidalFuzzyNumber</code> , <code>TrapezoidalFuzzyNumber-method</code> (Arithmetic), 8	<code>alphaInterval</code> , <code>PowerFuzzyNumber-method</code> (alphaInterval), 6
<code>+</code> , <code>numeric</code> , <code>FuzzyNumber-method</code> (Arithmetic), 8	<code>alphaInterval</code> , <code>TrapezoidalFuzzyNumber-method</code> (alphaInterval), 6
<code>-</code> , <code>FuzzyNumber</code> , <code>ANY-method</code> (Arithmetic), 8	<code>ambiguity</code> , 5, 6, 7, 10, 12–16, 18, 22–24, 27, 29, 30, 32, 36, 38–40, 43–45
<code>-</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>FuzzyNumber-method</code> (Arithmetic), 8	<code>ambiguity</code> , <code>FuzzyNumber-method</code> (ambiguity), 7
<code>-</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>PiecewiseLinearFuzzyNumber-method</code> (Arithmetic), 8	<code>approxfun</code> , 8
<code>-</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>numeric-method</code> (Arithmetic), 8	<code>approxInvert</code> , 8, 17, 29
<code>-</code> , <code>TrapezoidalFuzzyNumber</code> , <code>TrapezoidalFuzzyNumber-method</code> (Arithmetic), 8	<code>Arithmetic</code> , 5–7, 8, 12–16, 18, 22–24, 26, 27, 29, 30, 32, 33, 36, 38–45
<code>-</code> , <code>numeric</code> , <code>FuzzyNumber-method</code> (Arithmetic), 8	<code>as.character</code> , 3, 5–7, 10, 11, 13–16, 18, 22–24, 26, 27, 29, 30, 32, 33, 36–40, 43–45
<code>/</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>FuzzyNumber-method</code> (Arithmetic), 8	<code>as.character</code> , <code>FuzzyNumber-method</code> (as.character), 11
<code>/</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>PiecewiseLinearFuzzyNumber-method</code> (Arithmetic), 8	<code>as.character</code> , <code>PiecewiseLinearFuzzyNumber-method</code> (as.character), 11
<code>/</code> , <code>PiecewiseLinearFuzzyNumber</code> , <code>numeric-method</code> (Arithmetic), 8	<code>as.character</code> , <code>PowerFuzzyNumber-method</code> (as.character), 11
<code>[</code> , <code>DiscontinuousFuzzyNumber</code> , <code>character-method</code> (Extract), 25	<code>as.character</code> , <code>TrapezoidalFuzzyNumber-method</code> (as.character), 11

- as.FuzzyNumber, [5–7](#), [10](#), [12](#), [12](#), [14–16](#), [18](#),  
[22–24](#), [27](#), [29](#), [30](#), [32](#), [36](#), [38–40](#),  
[43–45](#)
- as.FuzzyNumber, FuzzyNumber-method  
(as.FuzzyNumber), [12](#)
- as.FuzzyNumber, numeric-method  
(as.FuzzyNumber), [12](#)
- as.PiecewiseLinearFuzzyNumber, [5–7](#),  
[10–13](#), [13](#), [15](#), [16](#), [18](#), [22–24](#), [26](#), [27](#),  
[29](#), [30](#), [32](#), [33](#), [36](#), [38–45](#)
- as.PiecewiseLinearFuzzyNumber, FuzzyNumber-method  
(as.PiecewiseLinearFuzzyNumber),  
[13](#)
- as.PiecewiseLinearFuzzyNumber, numeric-method  
(as.PiecewiseLinearFuzzyNumber),  
[13](#)
- as.PiecewiseLinearFuzzyNumber, PiecewiseLinearFuzzyNumber-method  
(as.PiecewiseLinearFuzzyNumber),  
[13](#)
- as.PiecewiseLinearFuzzyNumber, TrapezoidalFuzzyNumber-method  
(as.PiecewiseLinearFuzzyNumber),  
[13](#)
- as.PowerFuzzyNumber, [5–7](#), [10–14](#), [14](#), [16](#),  
[18](#), [22–24](#), [26](#), [27](#), [29](#), [30](#), [32](#), [33](#),  
[36–45](#)
- as.PowerFuzzyNumber, FuzzyNumber-method  
(as.PowerFuzzyNumber), [14](#)
- as.PowerFuzzyNumber, numeric-method  
(as.PowerFuzzyNumber), [14](#)
- as.PowerFuzzyNumber, PiecewiseLinearFuzzyNumber-method  
(as.PowerFuzzyNumber), [14](#)
- as.PowerFuzzyNumber, PowerFuzzyNumber-method  
(as.PowerFuzzyNumber), [14](#)
- as.PowerFuzzyNumber, TrapezoidalFuzzyNumber-method  
(as.PowerFuzzyNumber), [14](#)
- as.TrapezoidalFuzzyNumber, [5–7](#), [10–15](#),  
[15](#), [18](#), [22–24](#), [26](#), [27](#), [29](#), [30](#), [32](#), [33](#),  
[36–45](#)
- as.TrapezoidalFuzzyNumber, FuzzyNumber-method  
(as.TrapezoidalFuzzyNumber), [15](#)
- as.TrapezoidalFuzzyNumber, numeric-method  
(as.TrapezoidalFuzzyNumber), [15](#)
- as.TrapezoidalFuzzyNumber, PiecewiseLinearFuzzyNumber-method  
(as.TrapezoidalFuzzyNumber), [15](#)
- as.TrapezoidalFuzzyNumber, PowerFuzzyNumber-method  
(as.TrapezoidalFuzzyNumber), [15](#)
- as.TrapezoidalFuzzyNumber, TrapezoidalFuzzyNumber-method  
(as.TrapezoidalFuzzyNumber), [15](#)
- cat, [11](#)
- convertAlpha, [8](#), [16](#), [17](#), [29](#)
- convertSide, [8](#), [17](#), [17](#), [29](#)
- core, [5–7](#), [10](#), [12–16](#), [18](#), [22–24](#), [27](#), [29](#), [30](#),  
[32](#), [36](#), [38–40](#), [43–45](#)
- core, FuzzyNumber-method (core), [18](#)
- curve, [34](#)
- DiscontinuousFuzzyNumber, [3](#), [18](#), [18](#), [19](#),  
[20](#), [22](#), [29](#), [30](#), [36](#)
- DiscontinuousFuzzyNumber-class, [20](#)
- distance, [5–7](#), [10](#), [12–16](#), [18–20](#), [21](#), [22–24](#),  
[27](#), [29](#), [30](#), [32](#), [36](#), [38–40](#), [43–45](#)
- distance, DiscontinuousFuzzyNumber, DiscontinuousFuzzyNumber  
(distance), [21](#)
- distance, DiscontinuousFuzzyNumber, FuzzyNumber-method  
(distance), [21](#)
- distance, FuzzyNumber, DiscontinuousFuzzyNumber-method  
(distance), [21](#)
- distance, FuzzyNumber, FuzzyNumber-method  
(distance), [21](#)
- evaluate, [5–7](#), [10](#), [12–16](#), [18](#), [22](#), [22](#), [23](#), [24](#),  
[27](#), [29](#), [30](#), [32](#), [36](#), [38–40](#), [43–45](#)
- evaluate, FuzzyNumber, numeric-method  
(evaluate), [22](#)
- expectedInterval, [5–7](#), [10–16](#), [18](#), [22](#), [23](#),  
[24](#), [26](#), [27](#), [29](#), [30](#), [32](#), [33](#), [36–45](#)
- expectedInterval, FuzzyNumber-method  
(expectedInterval), [23](#)
- expectedInterval, PiecewiseLinearFuzzyNumber-method  
(expectedInterval), [23](#)
- expectedInterval, PowerFuzzyNumber-method  
(expectedInterval), [23](#)
- expectedInterval, TrapezoidalFuzzyNumber-method  
(expectedInterval), [23](#)
- expectedValue, [3](#), [5–7](#), [10](#), [12–16](#), [18](#), [22](#), [23](#),  
[24](#), [27](#), [29](#), [30](#), [32](#), [36](#), [38–40](#), [43–45](#)
- expectedValue, FuzzyNumber-method  
(expectedValue), [24](#)
- Extract, [25](#)
- fapply, [3](#), [6](#), [10](#), [12](#), [14–16](#), [24](#), [26](#), [33](#), [36](#)
- fapply, PiecewiseLinearFuzzyNumber, function-method  
(fapply), [26](#)
- fuzzy, [3](#), [5–8](#), [10](#), [12–18](#), [20](#), [22–25](#),  
[27](#), [27](#), [29](#), [30](#), [32](#), [33](#), [36–40](#), [42–45](#)
- FuzzyNumber-class, [28](#)
- FuzzyNumbers-package, [3](#)

- integrate, [21, 29, 30](#)
- integrate\_discont\_val, [29, 30](#)
- integrateAlpha, [5–7, 10, 12–16, 18–20, 22–24, 27, 29, 29, 31, 32, 36, 38–40, 43–45](#)
- integrateAlpha, DiscontinuousFuzzyNumber, character, numeric, numeric-method, (integrateAlpha), [29](#)
- integrateAlpha, FuzzyNumber, character, numeric, numeric-method, (integrateAlpha), [29](#)
- piecewiseLinearApproximation, [3, 5–7, 10, 12–16, 18, 20, 22, 24, 26, 27, 29, 30, 31, 33, 36, 38–40, 43–45](#)
- piecewiseLinearApproximation, FuzzyNumber-method, (piecewiseLinearApproximation), [31](#)
- PiecewiseLinearFuzzyNumber, [3, 6, 10, 12, 14–16, 24, 26, 29, 32, 32, 33, 36, 37](#)
- PiecewiseLinearFuzzyNumber-class, [33](#)
- plot, [3, 5–7, 10–16, 18–20, 22, 24, 26, 27, 29, 30, 32, 33, 34, 38–45](#)
- plot, DiscontinuousFuzzyNumber, missing-method, (plot), [34](#)
- plot, FuzzyNumber, missing-method (plot), [34](#)
- plot, PiecewiseLinearFuzzyNumber, missing-method, (plot), [34](#)
- plot, TrapezoidalFuzzyNumber, missing-method, (plot), [34](#)
- plot.default, [34, 35](#)
- PowerFuzzyNumber, [3, 7, 12, 15, 16, 24, 29, 36, 36, 37](#)
- PowerFuzzyNumber-class, [37](#)
- show, [5–7, 10, 12–16, 18, 22, 24, 27, 29, 30, 32, 36, 38, 39, 40, 43–45](#)
- show, FuzzyNumber-method (show), [38](#)
- splinefun, [8](#)
- supp, [5–7, 10, 12–16, 18, 22, 24, 27, 29, 30, 32, 36, 38, 38, 40, 43–45](#)
- supp, FuzzyNumber-method (supp), [38](#)
- trapezoidalApproximation, [3, 5–7, 10, 12–16, 18, 22, 24, 27, 29, 30, 32, 36, 38, 39, 39, 42–45](#)
- trapezoidalApproximation, FuzzyNumber-method, (trapezoidalApproximation), [39](#)
- TrapezoidalFuzzyNumber, [3, 7, 10, 11, 14–16, 24, 29, 33, 36, 41, 41, 42, 43](#)
- TrapezoidalFuzzyNumber-class, [41](#)
- TriangularFuzzyNumber, [7, 11, 14–16, 24, 36, 41, 42, 42](#)
- value, [3, 5–7, 10, 12–16, 18, 22, 24, 27, 29, 30, 32, 36, 38–40, 43, 44, 45](#)
- value, FuzzyNumber-method (value), [43](#)
- weightedExpectedValue, [5–7, 10, 12–16, 18, 22, 24, 27, 29, 30, 32, 36, 38–40, 43, 44, 45](#)
- weightedExpectedValue, FuzzyNumber-method, (weightedExpectedValue), [44](#)
- width, [5–7, 10, 12–16, 18, 22, 24, 27, 29, 30, 32, 36, 38–40, 43, 44, 45](#)
- width, FuzzyNumber-method (width), [45](#)