

INCOMPLETE DOCUMENT

code and title for 11 to 24 accurate,
rest INCOMPLETE including the aim

Rexiel Scarlet

2-10-2024

Contents

1	Fibonacci Series	4
2	Operations On Complex Numbers	4
3	Package Implementation	4
4	Class Implementation	4
5	Abstract Class Implementation	4
6	Inheritance In Java	4
7	Abstract Class With Inheritance	4
8	Interface Implementation	4
9	Multithreading In Java	4
10	Exception Handling	4
11	Validation using Swing	5
11.1	Aim	5
11.2	Code	5
11.3	Output	6
12	Text Field in Swing	7
12.1	Aim	7
12.2	Code	7
12.3	Output	8
13	Traffic Light Simulation	9
13.1	Aim	9
13.2	Code	9
13.3	Output	10
14	Applet In Java	11
14.1	Aim	11
14.2	Code	11
14.3	Output	11
15	Savings Account	12
15.1	Aim	12
15.2	Code	12
15.3	Output	12
16	Integer Divisions	13
16.1	Aim	13
16.2	Code	13
16.3	Output	14
17	Simple Interest	15
17.1	Aim	15
17.2	Code	15
17.3	Output	15
18	Mouse Coordinates	16
18.1	Aim	16
18.2	Code	16
18.3	Output	16

19 Simple Banner	17
19.1 Aim	17
19.2 Code	17
19.3 Output	17
20 Grid Layout Manager	18
20.1 Aim	18
20.2 Code	18
20.3 Output	18
21 Priority Threads	19
21.1 Aim	19
21.2 Code	19
21.3 Output	19
22 Employee Details	20
22.1 Aim	20
22.2 Code	20
22.3 Output	20
23 Update In JDBC	21
23.1 Aim	21
23.2 Code	21
23.3 Output	22
24 Product Details	23
24.1 Aim	23
24.2 Code	23
24.3 Output	24

- 1 Fibonacci Series
- 2 Operations On Complex Numbers
- 3 Package Implementation
- 4 Class Implementation
- 5 Abstract Class Implementation
- 6 Inheritance In Java
- 7 Abstract Class With Inheritance
- 8 Interface Implementation
- 9 Multithreading In Java
- 10 Exception Handling

11 Validation using Swing

11.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

11.2 Code

```
package org.projects.prog11;
import java.awt.GridLayout;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;

import javax.swing.*;

//11. Write a swing program for validating the form having a numeric field,
//character field, phone number, and email ID.

public class Swing {
    public static void main(String[] args) {
        JFrame frame = new JFrame("Swing Example");
        frame.setLayout(new GridLayout(3, 2));
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        frame.setSize(300, 130);

        JTextField phoneNum = new JTextField();
        frame.add(new JLabel("Phone"));
        frame.add(phoneNum);

        JTextField email = new JTextField();
        frame.add(new JLabel("Email"));
        frame.add(email);

        JButton submit = new JButton("Submit");
        JLabel result = new JLabel();
        result.setHorizontalAlignment(JLabel.CENTER);

        submit.addActionListener( new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                String em = email.getText();
                String phone = phoneNum.getText();
                result.setText("invalid");

                if (em.isEmpty() || phone.isEmpty()) { return; }

                try {
                    Long.parseLong(phone);
                    if (phone.length() < 10) { return; }
                } catch (Exception error) { return; }

                if (!em.contains("@")) { return; }

                result.setText("Valid");
            }
        });
    }
}
```

```
    frame.add(submit);  
    frame.add(result);  
    frame.setVisible(true);  
}  
}
```

11.3 Output

12 Text Field in Swing

12.1 Aim

- Create a Swing program that accepts a number
- if the number is even add it to list1
- else add it to list 2

12.2 Code

```
package org.projects.prog12;
import java.awt.GridLayout;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;

import javax.swing.*;

public class Swing {
    public static void main(String[] args) {
        JFrame frame = new JFrame("Swing Example");
        frame.setLayout(new GridLayout(4, 2));
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        frame.setSize(300, 130);

        JTextField number = new JTextField();
        frame.add(new JLabel("Number: "));
        frame.add(number);

        JLabel list1 = new JLabel();
        list1.setHorizontalAlignment(JLabel.CENTER);
        frame.add(new JLabel("List 1"));
        frame.add(list1);

        JLabel list2 = new JLabel();
        list2.setHorizontalAlignment(JLabel.CENTER);
        frame.add(new JLabel("List 2"));
        frame.add(list2);

        JButton submit = new JButton("Submit");

        submit.addActionListener( new ActionListener() {
            public void actionPerformed(ActionEvent e) throws NumberFormatException {
                int num = Integer.parseInt(number.getText());
                number.setText("");
                if (num % 2 == 0) {
                    list1.setText(list1.getText() + " " + num);
                } else {
                    list2.setText(list2.getText() + " " + num);
                }
            }
        });

        frame.add(submit);
        frame.setVisible(true);
    }
}
```

}

12.3 Output

13 Traffic Light Simulation

13.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

13.2 Code

```
package org.projects.prog13;
import java.awt.Color;
import java.awt.GridLayout;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;

import javax.swing.*;

//13. Write a java program to simulate a traffic light. The program lets the user
//select one of the three lights: red, yellow, or green. On selecting a button,
//an appropriate message with "Stop", "Ready" or "Go" should appear above the
//buttons selected color.

public class Traffic {
    public static void main(String[] args) {
        JFrame frame = new JFrame("Traffic");
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        frame.setLayout(new GridLayout(2, 1));
        frame.setSize(300, 130);

        JLabel sign = new JLabel();
        sign.setHorizontalAlignment(JLabel.CENTER);
        frame.add(sign);

        JPanel panel = new JPanel();
        panel.setLayout(new GridLayout(1, 3));

        JButton red = new JButton("STOP");
        red.setBackground(Color.RED);
        panel.add(red);

        JButton yellow = new JButton("READY");
        yellow.setBackground(Color.YELLOW);
        panel.add(yellow);

        JButton green = new JButton("GO");
        green.setBackground(Color.GREEN);
        panel.add(green);

        ActionListener on_click = new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                sign.setText(((JButton) e.getSource()).getText());
            }
        };

        red.addActionListener(on_click);
        yellow.addActionListener(on_click);
        green.addActionListener(on_click);
    }
}
```

```
    frame.add(panel);  
    frame.setVisible(true);  
}  
}
```

13.3 Output

14 Applet In Java

14.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

14.2 Code

```
package org.projects.prog14;

import java.applet.*;
import java.awt.*;
import java.awt.event.*;

public class Tables extends Applet implements ActionListener {
    TextField t1;
    Button t2;
    String[] result;

    public void init() {
        t1 = new TextField(5);
        t2 = new Button("Submit");
        t2.addActionListener(this);

        result = new String[10];

        add(new Label("Enter a number"));
        add(t1);
        add(t2);
    }

    public void paint(Graphics g) {
        for (int i = 0; i < 10; i++) {
            g.drawString(result[i], 20, 40 + 20*i);
        }
    }

    public void actionPerformed(ActionEvent e) {
        int number = Integer.parseInt(t1.getText());
        for (int i = 1; i <= 10; i++) {
            result[i-1] = number + " x " + i + " = " + i * number;
        }
    }
}
```

14.3 Output

15 Savings Account

15.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

15.2 Code

```
package org.projects.prog15;

//15. Write a Java program to define Account class. Derive Saving_Account class
//from Account class. Define appropriate constructors for both classes. Define
//the following methods in the Saving_Account class:
// Display( ): To display account details including account number and balance in
// the account.
// Deposit( ): To deposit money in an account.

class Account {
    public String accName;
    public long accNumber;

    Account (String name, long number) {
        accName = name;
        accNumber = number;
    }
}

public class SavingsAccount extends Account {
    private int accBalance;

    SavingsAccount(String name, long number) {
        super(name, number);
        accBalance = 0;
    }

    public void display() {
        System.out.println("Account: " + accName);
        System.out.println("No: " + accNumber);
        System.out.println("Balance: " + accBalance);
    }

    public void deposit(int ammount) {
        accBalance += ammount;
    }

    public static void main(String args[]) {
        SavingsAccount account = new SavingsAccount("BiJo", 1239812398);
        account.deposit(1000);
        account.display();
    }
}
```

15.3 Output

16 Integer Divisions

16.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

16.2 Code

```
package org.projects.prog16;

import javax.swing.*;
import java.awt.*;
import java.awt.event.*;

public class Dialog {
    public static void main (String args[]) {
        JFrame frame = new JFrame("cool frame");
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        frame.setSize(300, 200);
        frame.setLayout(new GridLayout(2, 1));

        JPanel panel = new JPanel();
        panel.setLayout(new GridLayout(2, 2));

        panel.add(new JLabel("Num 1: "));
        JTextField num1 = new JTextField();
        panel.add(num1);

        panel.add(new JLabel("Num 2: "));
        JTextField num2 = new JTextField();
        panel.add(num2);

        frame.add(panel);

        JButton submit = new JButton("Submit");
        submit.addActionListener(new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                JDialog dialog = new JDialog();
                dialog.setSize(300, 50);

                JLabel prompt = new JLabel();
                prompt.setHorizontalAlignment(JLabel.CENTER);
                try {
                    int n1 = Integer.parseInt(num1.getText());
                    int n2 = Integer.parseInt(num2.getText());
                    int result = n1 / n2;

                    prompt.setText(n1 + "/" + n2 + " = " + result);
                } catch (NumberFormatException _e) {
                    prompt.setText("Invalid Number");
                } catch (ArithmeticException _e) {
                    prompt.setText("Division by Zero");
                }

                dialog.add(prompt);
                dialog.setVisible(true);
            }
        });
    }
}
```

```
    }  
  });  
  
  frame.add(submit);  
  frame.setVisible(true);  
}  
}
```

16.3 Output

17 Simple Interest

17.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

17.2 Code

```
package org.projects.prog17;

import java.applet.*;
import java.awt.*;
import java.awt.event.*;

public class Interest extends Applet implements ActionListener {
    TextField principle, rate, time;
    Label result;
    Button submit;

    public void init() {
        principle = new TextField("principle");
        rate = new TextField("rate%");
        time = new TextField("time");

        add(new Label("Fill the following"));
        add(principle);
        add(rate);
        add(time);

        submit = new Button("Submit");
        submit.addActionListener(this);
        add(submit);

        result = new Label();
        add(result);
    }

    public void actionPerformed(ActionEvent e) {
        int p = Integer.parseInt(principle.getText());
        int r = Integer.parseInt(rate.getText());
        int n = Integer.parseInt(time.getText());

        float si = (p * r * n)/100;
        result.setText("" + si);
    }
}
```

17.3 Output

18 Mouse Coordinates

18.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

18.2 Code

```
package org.projects.prog18;
import java.applet.*;
import java.awt.*;
import java.awt.event.*;

public class MouseProg extends Applet implements MouseMotionListener {
    int x, y;

    public void init() {
        x = 0;
        y = 0;

        addMouseMotionListener(this);
    }

    public void paint(Graphics g) {
        g.drawString("x = " + x + " y = " + y, 20, 20);
    }

    public void mouseMoved(MouseEvent e) {
        x = e.getX();
        y = e.getY();
        repaint();
    }
    public void mouseDragged(MouseEvent e) {}
}
```

18.3 Output

19 Simple Banner

19.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

19.2 Code

```
import java.applet.*;
import java.awt.*;
import java.awt.event.*;

public class Banner extends Applet implements Runnable {
    String bannerText;
    Thread scroll;

    public void init() {
        bannerText = "REALLY COOL BANNER ";
        scroll = new Thread(this);
    }

    public void start() {
        scroll.start();
    }

    public void paint(Graphics g) {
        g.drawString(bannerText, 100, 100);
    }

    public void run() {
        try {
            while (true) {
                Thread.sleep(500);
                bannerText = bannerText.substring(1) + bannerText.charAt(0);
                repaint();
            }
        } catch (Exception e) {}
    }
}
```

19.3 Output

20 Grid Layout Manager

20.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

20.2 Code

```
package org.projects.prog20;

import javax.swing.*;
import java.awt.*;
import java.awt.event.*;

public class GridLay {
    public static void main(String args[]) {
        JFrame frame = new JFrame("Simple Grid");
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        frame.setSize(300, 200);
        frame.setLayout(new GridLayout(3, 1));

        JPanel panel = new JPanel();
        panel.setLayout(new GridLayout(1, 2));
        panel.add(new JLabel("Enter Name"));

        JTextField name = new JTextField();
        panel.add(name);

        frame.add(panel);

        JButton submit = new JButton("Submit");
        JLabel hello = new JLabel();

        submit.addActionListener(new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                hello.setText("Hello " + name.getText() + "!!");
            }
        });
        frame.add(submit);

        frame.add(hello);

        frame.setVisible(true);
    }
}
```

20.3 Output

21 Priority Threads

21.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

21.2 Code

```
package org.projects.prog21;

public class Threading {
    public static Runnable simple_runnable = new Runnable() {
        public void run() {
            String name = Thread.currentThread().getName();
            for (int i = 0; i < 10; i++) {
                System.out.println(name + " " + i);
            }
        }
    };

    public static void main (String args[]) {
        Thread th0 = new Thread(simple_runnable), th1 = new Thread(simple_runnable);

        th0.setPriority(Thread.MIN_PRIORITY);
        th1.setPriority(Thread.MAX_PRIORITY);

        th0.start();
        th1.start();
    }
}
```

21.3 Output

22 Employee Details

22.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

22.2 Code

```
package org.projects.prog22;
import java.sql.*;

public class Employee {
    public static void main(String args[]) {
        try {
            Class.forName("com.mysql.cj.jdbc.Driver");
            String username = "root", password = "coolPass", dbname = "dbone";
            Connection cn = DriverManager.getConnection(
                //"jdbc:mysql://localhost:3306/dbone", "root", "coolPass"
                "jdbc:mysql://localhost:3306/" + dbname, username, password
            );

            Statement state = cn.createStatement();
            ResultSet rs = state.executeQuery("select * from employee");

            while (rs.next()) {
                System.out.println("Id: " + rs.getInt(1));
                System.out.println("Name: " + rs.getString(2));
                System.out.println("Designation: " + rs.getString(3));
                System.out.println();
            }

            cn.close();
        } catch (Exception e) {}
    }
}
```

22.3 Output

23 Update In JDBC

23.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

23.2 Code

```
package org.projects.prog23;
import java.sql.*;
import java.util.Scanner;

public class Student {
    public static Scanner sc = new Scanner(System.in);
    public static void main(String args[]) {
        try {
            Class.forName("com.mysql.cj.jdbc.Driver");
            String username = "root", password = "coolPass", dbname = "dbone";
            Connection cn = DriverManager.getConnection(
                //"jdbc:mysql://localhost:3306/dbone", "root", "coolPass"
                "jdbc:mysql://localhost:3306/" + dbname, username, password
            ); System.out.println("1 - add Student");
            System.out.println("2 - update Student");

            switch (sc.nextInt()) {
                case 1:
                    addStudent(cn);
                    break;
                case 2:
                    updateStudent(cn);
                    break;
                default:
                    System.out.println("Invalid Choice");
                    break;
            }

            displayStudents(cn);
            cn.close();
        } catch (Exception e) {}
    }

    public static void addStudent(Connection cn) {
        sc.nextLine(); // ignore garbage
        System.out.println("Enter name");
        String name = sc.nextLine();

        System.out.println("Enter roll number, age");
        int roll = sc.nextInt(), age = sc.nextInt();

        System.out.println("Enter Grade");
        char grade = sc.next().charAt(0);

        // to create the table use the following mysql code
        // create table students (
        //     roll int unique not null,
```

```

// name varchar(20) not null,
// age int not null,
// grade char(1) not null
// );

try {
    cn.createStatement().execute(String.format(
        "INSERT INTO students VALUES (%d, '%s', %d, '%c')",
        roll, name, age, grade
    ));
} catch (Exception e) {
    System.out.println(e.getMessage());
}
}

public static void updateStudent(Connection cn) {
    System.out.println("Enter rol number to update");
    int roll = sc.nextInt();

    System.out.println("Enter new age");
    int age = sc.nextInt();

    System.out.println("Enter new grade");
    char grade = sc.next().charAt(0);

    try {
        cn.createStatement().executeUpdate(String.format(
            "UPDATE students SET age = %d, grade = '%c' WHERE roll = %d",
            age, grade, roll
        ));
    } catch (Exception e) {
        System.out.println(e.getMessage());
    }
}

public static void displayStudents(Connection cn) {
    try {
        ResultSet set = cn.createStatement().executeQuery("select * from students");
        while (set.next()) {
            System.out.println(String.format(
                "roll: %d, name: %s, age: %d, grade: %s",
                set.getInt(1), set.getString(2), set.getInt(3), set.getString(4)
            ));
        }
    } catch (Exception e) {}
}
}

```

23.3 Output

24 Product Details

24.1 Aim

- Create a Swing form with fields phone number and email ID
- Validate the fields

24.2 Code

```
package org.projects.prog24;
import java.sql.*;
import java.util.Scanner;

public class Product {
    public static Scanner sc = new Scanner(System.in);
    public static void main(String args[]) {
        try {
            Class.forName("com.mysql.cj.jdbc.Driver");
            String username = "root", password = "coolPass", dbname = "dbone";
            Connection cn = DriverManager.getConnection(
                //"jdbc:mysql://localhost:3306/dbone", "root", "coolPass"
                "jdbc:mysql://localhost:3306/" + dbname, username, password
            );

            boolean done = false;
            while (!done) {
                System.out.println("1 - add Product");
                System.out.println("2 - delete Product");
                System.out.println("3 - display");

                switch (sc.nextInt()) {
                    case 1:
                        addProduct(cn);
                        break;
                    case 2:
                        deleteProduct(cn);
                        break;
                    case 3:
                        displayProducts(cn);
                        break;
                    default:
                        System.out.println("Invalid Choice");
                        done = true;
                        break;
                }
            }
            cn.close();
        } catch (Exception e) {}
    }

    public static void addProduct(Connection cn) {
        sc.nextLine(); // ignore garbage
        System.out.println("Enter Product name");
        String name = sc.nextLine();

        System.out.println("Enter product price");
        float price = sc.nextFloat();
    }
}
```

```

// to create the table use the following mysql code
// create table products (
//   id int unique AUTO_INCREMENT,
//   name varchar(20) not null,
//   price decimal(8, 2) not null,
// );

try {
    cn.createStatement().execute(String.format(
        "INSERT INTO products (name, price) VALUES ('%s', %f)",
        name, price
    ));
} catch (Exception e) {
    System.out.println(e.getMessage());
}

}

public static void deleteProduct(Connection cn) {
    System.out.println("Enter and id to delete");
    int id = sc.nextInt();

    try {
        cn.createStatement().execute(String.format(
            "DELETE FROM products WHERE id = %d",
            id
        ));
    } catch (Exception e) {
        System.out.println(e.getMessage());
    }

}

public static void displayProducts(Connection cn) {
    try {
        ResultSet set = cn.createStatement().executeQuery("select * from products");
        while (set.next()) {
            System.out.println(String.format(
                "id: %d, name: %s, cost: %f",
                set.getInt(1), set.getString(2), set.getFloat(3)
            ));
        }
    } catch (Exception e) {}

}

}

```

24.3 Output