

JWT attacks

Mario Alviano


Main References

Bug Bounty Bootcamp – Chapter 3 (something)

<https://portswigger.net/web-security/jwt>


OWASP Top Ten

A broad consensus about the most critical security risks to web applications



JSON Web Tokens (JWTs)

Standardized format for sending cryptographically **signed** JSON data. Often used for AuthN and AuthZ.



eyJraWQiOiI5MTM2ZGRiMy1jYjBhLTRhMTktYTA
3ZS1lYWVmNWE0NGM4YjUiLCJhbGciOiJSUzI1Ni
J9.eyJpc3MiOiJwb3J0c3dpZ2dlciIsImV4cCI6
MTY0ODAzNzE2NCwibmFtZSI6IkNhcmxvcyBNb25
0b3lhIiwic3ViIjojY2FybG9zIiwicm9sZSI6Im
Jsb2dfYXV0aG9yIiwiaW1haWwiOiJjYXJsb3NAY
2FybG9zLW1vbnRveWEubmV0IiwiaWF0IjoxNTE2
MjM5MDIyfQ.SYZBPIBg2CRjXAJ8vCER0LA_ENjI
I1JakvNQoP-
Hw6GG1zf14JyngsZReIfqRvIAEi5L4HV0q7_9qG
hQZvy9ZdxEJbwTxRs_6Lb-
fZTDpW6lKYNdMyjw45_a1SCZ1fypsMWz_2mTpQz
i1010tps5Ei_z7mM7M8gCwe_AGpI53JxduQ0aB5
HkT5gVrv9cKu9CsW5MS6ZbqYXpGy0G5ehoxqm8D
L5tFYaW31B50ELxi0KsuTKEbD0t5BC10aCR2MBJ
WAbN-
xeLwEenaqBiwPVvKixYleeDQiBEIylFdNNIMviK
RgXiYuAvMziVPbwSgkZVHeEdF5MQP10e2Spac-
6IfA

Header

HEADER: ALGORITHM & TOKEN TYPE

```
{  
  "kid": "9136ddb3-cb0a-4a19-a07e-eadf5a44c8b5",  
  "alg": "RS256"  
}
```

Key ID (optional, often used to inform clients on key changes)

Payload

PAYLOAD: DATA


```
{  
  "iss": "portswigger",  
  "exp": 1648037164,  
  "name": "Carlos Montoya",  
  "sub": "carlos",  
  "role": "blog_author",  
  "email": "carlos@carlos-montoya.net",  
  "iat": 1516239022  
}
```

Can be everything!

Signature

JWT signature

```
eyJraWQiOiI5MTM2ZGRiMy1jYjBhLTRhMTktYTA3ZS1lYWVmNWE0NGM4YjUiLCJhbGciOiJSUzI1NiJ9.eyJpc3MiOiJwb3J0c3dpZ2dlciIsImV4cCI6MTY0ODAzNzE2NCwibmFtZSI6IkNhcmxvcyBnb250b3lhIiwic3ViIjoiiY2FybG9zIiwicm9sZSI6ImJsb2dfYXV0aG9yIiwiaWZwIhaWwiOiJjYXJsb3NAY2FybG9zLW1vbnRveWEubmV0IiwiaWF0IjoxNTE2MjM5MDIyfQ.SYZBPIBg2CRjXAJ8vCER0LA_ENjI11JakvNQoP-Hw6GG1zf14JyngsZReIfqRvIAEi5L4HV0q7_9qGhQZvy9ZdxEJbwTxRs_6Lb-fZTDpW6lKYNdMyjw45_a1SCZ1fypsMWz_2mTpQz il0l0tps5Ei_z7mM7M8gCwe_AGpI53JxduQ0aB5HkT5gVrv9cKu9CsW5MS6ZbqYXpGyOG5ehoxqm8DL5tFYaW31B50ELxi0KsuTKEbD0t5BC10aCR2MBJWAbN-xeLwEenaqBiwPVvKixYleeDQiBEIy1FdNNIMviKRgXiYuAvMziVPbwSgkZVHeEdF5MQP10e2Spac-6IfA
```



JSON Web Signature


JSON Web Encryption

**Most of the time,
JWT actually refers to JWS.**

In JWS the header and payload are signed by HMAC (hash-based message authentication code).

Vulnerabilities

- Accepting tokens with no signature
- Accepting tokens with tampered algorithm
- Weak encryption keys
- Misunderstand symmetric and asymmetric encryption
- Using JWS and thinking data is not readable



Questions

