Exercise 2

Rhirhondzu Ngobeni
Data Science

Student number: 2805000621
SQL Fundamentals
(Aggregate function & grouping)

1. Select distinct count (ID) as Total_number_of_Employees
from employees;

	Department	Total_number_of_employees
1	Finance	591500

2. Select department, sum (salary) as Total_salary
from employees
where department = 'IT'
Group by department;

	Department	Total_salary
1	IT	220 000

3. Select department, avg (salary) as Average_salary
from employees
where department = 'HR'
Group by department;

	Department	Average_salary
1	HR	49500

4. Select ~~departm~~ max (salary) as Highest_salary,
Min (salary) as Lowest_salary
from employees;

	Highest_salary	Lowest_salary
1	62 000	48 000

5. Select department, sum (salary) as Total_salary
from employees
Group by department;

	Department	Total_salary
1	IT	220 000
2	HR	99 000
3	Finance	119 000
4	Marketing	105 000

6. Select city, count (ID) as Total_employees
from employees
Group by city;

	City	Total_employees
1	New york	2
2	Chicago	3
3	Los Angeles	2
4	San francisco	2
5	Houston	1

7. Select department, avg(salary) as Average_salary
from employees
Group by department
order by 'Average_salary' desc;

	Department	Average_salary
1	IT	55 000
2	HR	49500
3	Finance	59500
4	Marketing	52500

8. Select department, sum(salary) as Total_salary
from employees
Group by department
having Total_salary > 100000;

	Department	Total_salary
1	IT	220 000
2	Finance	119 000
3	Marketing	105 000

9. Select City, count(ID) as Total_employees
From employees
Group by city
Having Total_employees > 1
Order by Total_employees desc;

	City	Total_employees
1	Chicago	3
2	New York	2
3	Los Angeles	2
4	San Francisco	2

10. Select department, Avg(salary) as Highest_average
from employees

Group by department
Order by Highest_average desc
limit 1;

	Department	Highest_average
1	Finance	595 000