msg + hash code + encry → confidentiality

Hash function: (give confidentiality)

Symmetric key



$E(K, [M \| H(M)])$

→ Confidentiality is provided by cz of symetric key as this key is present only to authorised person.

→ Hash code is used for authentication.

(2)



No confidentiality

(3)



No confidentiality

(4)



confidentiality + authentication

msg + hash → Encrypt

↑ K

(Assymetric key)

→ Digital signature.



Authentication ✓

For confidenciality



So conclusion → Hash provides integrity by default

→ if ~~this~~ [Msg + Hash]

Encrypt, confidentiality + Authentication

Only Authentication

Not encrypt

Formulas:

RSA →

- $n = p * q$
- $\phi(n) = (p-1)(q-1)$
- choose e $\quad 1 < e < \phi(n) \quad \gcd(e, \phi(n)) = 1$
- calculate d

$$ed \equiv 1 \bmod \phi(n)$$

$$d = e^{-1} \bmod \phi(n).$$

- Public key $\{e, n\}$
- Private key $\{d, n\}$

- En : $C = M^e \bmod n$
- De : $M = C^d \bmod n.$

→ Deffie Hellmann

- Let prime q
- primitive root α. $\quad \alpha < q$
- Assume Private key X_A , Y_A

- Public key = $Y_A = \alpha^{X_A} \bmod q$

$$Y_B = \alpha^{X_B} \bmod q.$$

- key to be used = $Y_B^{X_A} \bmod q = Y_A^{X_B} \bmod q$

HMAC Hash Msg Auth code



Integrity + Authentic

ipad → (36 in hexa) 00110110

opad → (5C in hexa) 01011100



$$HMAC(K, m) = H[(K^{+} \oplus opad) \,||\, H[(K^{+} \oplus ipad) \,||\, m]]$$

Other topic → DAA (Data Authentication Algo)
→ CMAC [Cipher Based Msg Authentication Code]

These both are based on Block cipher

See ppt and video.

X.509 Certificate:

Purpose → The main purpose of digital certificates (SSL/TLS) is to identify people and resources over network such as Internet & also to provide secure, confidential communication b/w 2 parties using encryption.

See ppt for detailed view of certificate.

Version → Version of X.509

Serial Number → uniquely identifies certificate (not user)

Signature Algorithm ID → name of public key algo that CA has used to sign certificate (RSA)

Issuer (CA) X.500Name → identity of CA

Validity Period

Subject Public key Info | Algo Id | Public key Value

Subject X.500Name → owners identity within X.500 directory

Public key of owner and algo associated to it

Issuer Unique ID → Info that can be used to identify issue

Subject Unique ID → ident user

Extension → Additional Info CRL, CDP

CA dig. sig. → The actual digital signature of CA

Version Serial Numbe	
Algo used to sign certificate.	Websites have certificates issued by servers.
Identity of CA Validity Period	
Identity of owner	
Public key and algo used.	
Verify id of CA	
Verify ID of owner Other (Extension)	
signature	

→ Public key Infrastructure:

→ set of { hardware, software, policies, procedure, people } needed to { create, manage, store, distribute, revoke digital certificates }

→ Public key Infrastructure X.509 is called (PRIX)

→ PRIX Elements:

CRL (Certification Revocation List).

Full Ratta, read PPT.

* PRIX Elements:

→ End entity
→ Certification Authority (CA)
→ Registration Authority (RA)
→ CRL issuer
→ Repository.

* PRIX management functions

- Registration
- Initialization
- Certification
- Key Pair Recovery
- Revocation Request
- Cross Validation

* PKI management Protocols.

- CMP (certificate management Protocol) → request, revoke, suspend, reinst
- CMS (Cryptographic message syntax) → encrypt decrypt sign verify compress decompr

Kerberos: Kerberos is a network authentication protocol that works on basis of tickets to allow nodes communicating over non-secure network to prove their identity to one another in a secure manner.

3 heads: 3 step process:

- → Authentication.
- → Authorization
- → Accounting.

as per video →

(1) User
(2) KDC
(3) Services.

Requirement of kerberos

- Secure
- Reliable: one system able to back up another.
- Transparent.
- Scalable: modular distribute architecture

→ KDC → The service that offers Kerberos ticket

→ Ticket Granting server (TGS): A server that issues tickets for desired services which in turn are given to user to access the services. Runs on same host as KDC.

Kerberos is capable of both symmetric and asymmetric techniques.

Kerberos is more secure than other authentication methods because it doesn't send plain text password over network and instead uses encrypted tickets.

- Kerberos 4.

2 ways

(1) Using Authentication servers only

(2) Using AS + TGT (Ticket granting server).

(1) Using AS.



(1) C → AS

(2) AS → C : Ticket

Encrypted, Client can't decrypt

(3) C → V ID_C || Ticket

Server will match ID_C which means Identity of client is verified.

(1) C → AS : $ID_C \| P_C \| ID_V$

(2) AS → C : Ticket $E(K_V, [ID_C \| AD_C \| ID_V])$

(3) C → V : ID_C || Ticket.

V (server) will match them and then start communication on AD_C.

(⇒ Problem : (1) User would need ticket for every new service.

(2) password is transmitted without encryption.

Elgamal Algo:

global elements of Elgamal digital signature is based on prime number q and α, which is a primitive root of q.

→ Generate private key & public key.

→ X_A $\quad 1 < X_A < q-1$

eg $q = 19$, $\alpha = 10$

let $X_A = 16$

q, α → global elements

$$Y_A = \alpha^{X_A} \bmod q$$

$Y_A = 4$

A public key = $\{q, \alpha, Y_A\}$

~~So X_A & public key and~~ X_A → private key.

Y_A → public key.

let Sender wants to sign a hash value $m = 14$

→ Create digital signature

- Choose k $\quad 1 \le k \le q-1$ $\quad \gcd(k, q-1) = 1$

Let $k = 5$ $\quad \gcd(5, 18) = 1$

$S_1 = \alpha^k \bmod q = 3.$

$S_2 = k^{-1} (m - X_A S_1) \bmod (q-1)$

$= 5^{-1} (14 - (16)(3)) \% 18 = -374 \bmod 18 = 4$

Signature consists of $(S_1, S_2) = (3, 4)$

$5^{16} \bmod 18 \qquad 5^{17} \bmod 19$

$5^{18} \bmod 19 = a \times 5^{i}$

→ Signature verification:

$5^{17} \bmod$

$V_1 = \alpha^m \bmod q$

$= 10^{14} \bmod 19 = 16$

$V_2 = (Y_A)^{S1} (S_1)^{S_2} \bmod q$

$= 6^3 3^4 \% 19 = 16.$

$V_1 = V_2 = 16.$ both the values are same.

In a nutshell:

Assume q and α.

- Select X_A → private key
- Find $Y_A = \alpha^{X_A} \bmod q$

Public key $\{q, \alpha, Y_A\}$

- Given hash value m
- Chose k $(1 \le k \le q)$ · $\gcd(k, q-1) = 1$
- Find $S_1 = \alpha^k \bmod q$
- Find $S_2 = k^{-1} (m - X_A S_1) \bmod (q-1)$

Signature consists of (S_1, S_2)

$V_1 = \alpha^m \bmod q$

$V_2 = (Y_A)^{S1} (S_1)^{S_2} \bmod q$

$V_1 = V_2$.

p and e_1

d

public key $e_2 = e_1^d \% p$

(e_1, e_2, p)

m

r

$S_1 = e_1^r \bmod p$

$S_2 = r^{-1}(m - dS_1) \% p-1$

$V = e_1^m \% p$

$V_2 = e_2^{S_1} S_1^{S_2} \bmod p$

$a^* b = 1$

$(a^* b)$

5×5

5^{-1}

$5^{-1} \% 18.$

$a \times \% \bmod m = 1$

Security Association:

→ one way relationship b/w sender and reciever.
→ 3 parameter.
  → security Protocol Identifier (which Protocol AH / ESP?)
  → IP Destination Address
  → Security Parameter Index (unique identifies a particular security Association)
  → Sequence number counter (0 to $2^{32}-1$) (increment after every packet is sent)
→ has other Param:
  → EH, AH into, Key life time
  → Algo used.
  → IPsec Protocol mode.

→

Bas inka block diagram nahi aayega bhaiyo ar

JESUS LOVE ME

→

AL
↓
SSL
↓
TL

Secure socket layer (SSL)

→ lies b/w Application and Transport layer.
→ Ensures conf + auth + integrity

overview

→ 4 Protocols:
  → Handshake Protocol (Imp) (connection + authen)
  → SSL Record Protocol (Imp) (conf + integrity) (encrypt) (MAC)
  → Alert Protocol (Alert, error msgs)
  → change cipher spec Protocol. (1 msg of 1 byte of value 1 Pending state → running state)

bit flip.

Handshake	spec	Alert	HTTP
SSL Record Protocol			
TCP			
IP			

SSL Protocol Stack

FIREWALL:

External Network ↔ Firewall ↔ Internet Network

→ prevent unauthorise access
→ Monitors and controls incoming and outgoing traffic based on predifined rules
→ can be software, Network or mixture

Types of Firewall:



(1) Packet filtering (layer 4)
→ check IP header, TCP header
→ Works on Network and Transport layer
→ Can block IP address, full Network
→ can block a service (http, ftp)
→ Source IP, Source Port, Dest IP, Dest Port

~~(2) Application filtering~~

(2) Application-level Gateway (layer 5) (proxy server)
→ data is also verified., check data / Payload.
data may contain malacious data.
→ More secure
→ Eg checking email / password on login.
→ processing overhead (Disadvantage)



We think that hum directly external host se connect ho. external host thinks ki proxy se a rhi e but bhej hum rahe h

(3) Circuit level Gateaway

→ uses 2 TCP connection
  → b/w Internal host ↔ Gateaway
  → b/w external host ↔ gateaway

→ Security check is done before establish connection

Intrusion Detection system (IDS)

Intruder (someone with unauthorized access) → Outside Intruder (Masquerade)
→ Inside Intruder (Misfeasor)
(hard to identify)

↓

Intrusion (art of intruders)

↓

Intrusion Detection System (IDS)

IDS methods:

(1) Signature Based IDS:
→ pattern (Sig) among packets.
→ Database of attack pattern.
→ If signature matches, their is attack.
→ can't identify new attacks.

(2) Anomaly Based IDS:
- deviation
→ behaviour of people from their 'normal' behaviour

IDS Types!

(1) Network Based IDS
- → Analysis: Matches traffic to the library of known attack.
- → monitors, capture & Analyze network traffic
- → Detect malicious data present in to packets.
- → Difficult to do on busy network.

(2) Host Based IDS
- → installed on device or network
- → monitors packets from device only (to and fro packets)
- → Alert suspious activity (check with ideal system)
- → file deleted or modified.

What is NAT?

Network Address Translation allows a private network to use a set of private address and a set of global Internet address for external communication It uses translation table to route msgs b/w two networks and provides substantial security.

A computer virus is a kind of malicious comp program which when executed, replicates itself and modify or insert its own code.