



# Machine and deep learning approaches for alzheimer disease detection using magnetic resonance images: An updated review

M. Menagadevi<sup>a</sup>, Somasundaram Devaraj<sup>b</sup>, Nirmala Madian<sup>c,\*</sup>, D. Thiyagarajan<sup>d</sup>

<sup>a</sup> Department of Computer Science and Engineering, School of Engineering, Malla Reddy University, Hyderabad, India

<sup>b</sup> Department of Micro and Nanoelectronics, School of Electronics Engineering (SENSE), Vellore Institute of Technology, Vellore, India

<sup>c</sup> Department of Biomedical Engineering, Dr.N.G.P Institute of Technology, Coimbatore, India

<sup>d</sup> Department of Artificial Intelligence and Machine Learning, School of Engineering, Malla Reddy University, Hyderabad, India

## ARTICLE INFO

### Keywords:

Alzheimer Disease  
Machine learning  
Deep learning  
Image Preprocessing  
Magnetic Resonance Image

## ABSTRACT

The most frequent chronic illness affecting the elderly and one with a high incidence rate is Alzheimer's disease (AD). Deep Learning (DL) and Machine Learning (ML) techniques has significant success and gained popularity in medical imaging. It has emerged as the method of choice for examining medical images and has drawn considerable interest in identification of AD. The review paper mainly focus on image pre-processing which contributes on noise removal, illumination and intensity correction in Magnetic Resonance (MR) images, segmentation methods which helps in extracting the region of interest for AD detection, feature extraction which are considered as the inputs for classification and various machine and deep learning algorithms are analysed for detecting AD. The survey focus on papers related with academic year 2013 to 2023. The maximum number of paper considered for the review falls from 2019 with 13 papers, 2021 with 27, 2022 with 18 and 2023 with 22 papers and other papers are related with dataset reference and papers published before 2019. From the survey, deep learning techniques are more robust in detecting AD.

## 1. Introduction

Globally Neurological disorders affects hundred million peoples. 50 million peoples affected by epilepsy globally [1]. It is estimated as 47.5 million worldwide affected with dementia, and 7.7 million new patients are reported each year. AD is the most frequent cause of dementia and may be to blame for 60 to 70 % of cases. Over 10 % of people globally suffer from migraines. Two crucial illness indicators are morbidity and mortality. The term morbidity refers to the presence of a disease or its symptoms. Mortality is the total number of fatalities or injuries. The rates of morbidity and mortality for some of the most common neuropsychiatric and neurological conditions, including stroke, AD, epilepsy, Parkinson's disease, migraine and multiple sclerosis, are shown in [Figures 1 and 2](#). Stroke, AD, Parkinson's, epilepsy, migraine, and multiple sclerosis morbidity rates are 61 %, 12 %, 1 %, 7 %, 17 %, and 1 %, respectively. Similarly, the death rates for stroke, AD, epilepsy, migraine, Parkinson's and multiple sclerosis are, respectively, 74 %, 22 %, 1 %, 2 %, 0 %, and 0 % [2].

AD is a clinical illness that is characterized by a steady decline in mental and memory function. It accounts for 60 to 80 percent of all dementia subtypes, making it a rather common condition among the

elderly. The prevalence of AD is significant and currently no cure. Mild Cognitive Impairment (MCI) is the term used for patients who are in the starting stages of AD [60]. About 30–40 % of MCI patients will eventually get AD, but not all MCI patients will suffer AD. Before the patient's neurological deterioration starts the AD-related brain changes starts that includes early lateral ventricle expansion and noticeable hippocampal and amygdala atrophy. Some brain areas will started to shrink, according to studies on biomarkers linked to AD [67].

The development of numerous open-source Alzheimer's databases has boosted this area of study. The most popular databases are OASIS (<https://www.oasis-brains.org>), ADNI ([adni.loni.usc.edu](http://adni.loni.usc.edu)). The ADNI database, which contains information from long-term studies conducted in Japan, is a new clinical Alzheimer data source that is open to the public. Additionally, processing MR images is quite labor-intensive. Open-source programmes like Statistical Parametric Mapping (SPM) have been created at the Welcome Centre for Human Neuroimaging to make it easier for users to analyse MR images. Voxel-Based Morphometry (VBM) [76] of MRI data is carried out using SPM. Freesurfer is a very well-liked piece of open-source software that was created for volume-based morphometry and is employed by numerous researchers.

It is typically difficult to identify AD using artificial intelligence

\* Corresponding author.

<https://doi.org/10.1016/j.measurement.2023.114100>

Received 15 August 2023; Received in revised form 17 October 2023; Accepted 28 December 2023

Available online 4 January 2024

0263-2241/© 2023 Elsevier Ltd. All rights reserved.




Fig. 1. Morbidity and Mortality rate for various disorder.

because.

- Low quality of medical images, brain segmentation and pre-processing errors.
- Lack of a sizable dataset with a variety of people and biomarkers.
- Low interclass variability throughout AD stages.
- A lack of knowledge, particularly with regard to identifying brain Regions-Of-Interest (ROIs).
- Medical images are more complex than the typical other images.

Computer vision has become more important in the diagnosis of AD due to the quick development of artificial intelligence. The constraints of more conventional methods overcome by a significant subset of ML and DL approaches. Recently, the field of imaging has seen advancements in DL and ML technology, which have been applied for extracting information from images [63,64]. Since identifying medical images is a difficult task, computer-aided systems have a significant impact on clinical diagnosis. Positron Emission Tomography (PET), Structural Magnetic Resonance imaging (sMRI), and Computed Tomography (CT) are the most widely used techniques for diagnosing neurodegenerative diseases [61]. This paper reviews various datasets used for analysis, image preprocessing methods, segmentation, machine learning, deep learning approach and their parameters used for predicting the AD [65,74].

## 2. Dataset

Dataset of Alzheimer are Alzheimer's Disease Neuroimaging

Initiative (ADNI) [94]. The dataset are related to ADNI1, ADNI2, ADNI3 and ADNI GO. The dataset are classified as Alzheimer (AD), Normal control (NC), Early Mild Cognitive impairment (EMCI), Late Mild Cognitive impairment (LMCI), Mild Cognitive impairment (MCI). The MR images of ADNI are related to Structural MRI, FLAIR, T2 GRE, DTI, fMRI, ASL, Hippocampal T2. Open Access Series of Imaging Studies (OASIS) [95]. The dataset has OASIS1 belong to Cross-sectional MRI Data with 416 subjects and 434 MR session. OASIS2 belong to longitudinal MRI Data with 150 subjects and 373 MR session. OASIS3 belong to longitudinal multimodal neuroimaging with subjects 1379, MR session 2842, PET session 2157 and CT session 1472. OASIS4 belong to clinical cohort with subjects 663 and MR session 676. Kaggle dataset [96]. The MR images are resized for 128 x 128 and mainly classified into four groups. The dataset has 6400 MR images. The grouping of dataset is given as Mild Demented (MD) with 896 images, Moderate Demented (MoD) with 64 images, Non Demented (ND) with 3200 images and Very Mild Demented (VMD) with 2240 images. Other dataset are Minimal Interval Resonance Imaging in Alzheimer's Disease (MIRIAD) [97], ANSH Database [98].

The AD Detection can be performed by analysing biomarkers of MR images. The brain MRI helps in analysing brain shrinkage, damages in blood vessels, inflammation etc. Hippocampi region is initially affected first so this can be analysed effectively from MR images for AD detection. MR images can help in analysing the shape and size of brain region for detecting atrophied (brain shrinkage). Atrophied helps in diagnosing AD. Gray and white matter region is considered as biomarkers. When gray region shrinks it leads to decline in cognitive function. When white matter shrinks it leads to problem with memory loss, balance and mobility functions. The sample images that is normal and Alzheimer from Kaggle and ADNI dataset is shown Figure 3a and 3b. The image shows the shrinkage in white and gray matter region

## 3. Methods

Figure 4 shows the general block diagram of the survey paper which includes image preprocessing methods, image enhancement, image segmentation, image classification using ML and DL techniques [69].

Figure 5 shows the detailed survey of these steps like image preprocessing, image denoising and enhancement. Image enhancement is performed by Histogram equalization, Intensity Normalization, Skull Striping, Thersholding, Discrete wavelet transform, 2D Adaptive consensual filter, Laplacian, Hessian, Contrast Stretching and Curvelet filtering. For image segmentation to extract region of intrest for AD prediction are thersholding, Atlas-based registration, M-Net, Optimization-based segmentation techniques, Bayesian segmentation, Statistical Parametric Mapping, Patch-Based Classifiers, Particle Swarm Optimization, Convolutional Neural Network, SegNet, Autoencoder, K-




Fig. 2. Number of Cases of Alzheimer Disease.




Normal Image

Alzheimer Image

a: Kaggle Dataset Images

Fig. 3a. Kaggle Dataset Images.



Normal Image

Alzheimer Image

b: ADNI Dataset Images

Fig. 3b. ADNI Dataset Images.




Fig. 4. General block diagram of AD analysis.




Fig. 5. Algorithms and methods used in AD Analysis.

Means Clustering, Watershed Method, OTSU segmentation, U-Net architecture and MultiRes + U Net network. For image classification ML and DL methods such as CNN, ELM, H-FCN, DCNN, Mixed effect model Ensemble, Decision tree, SVM, Deep Multi-task multi-channel learning, Transfer Learning, RBF-SVM and Semi supervised ELM were used widely [78].

#### 4. Image preprocessing

The operating procedures used by medical staff may differ as image acquisition performed by devices made by various manufacturers. The patient's body position will surely change slightly because of the prolonged capturing period. Several preprocessing procedures must be carried out in order to obtain the clear image and the obtained image is used for feature extraction, and classification. Most studies require preprocessing before data analysis, particularly in machine learning. Some investigations might not require preprocessing with the aid of DL. Most of the articles in ML and DL used intensity normalization, skull stripping, registration, tissue segmentation and motion correction as preprocessing methods [79].

Images obtained from various modalities like CT, MRI, PET and Single Photon Emission Computed tomography(SPECT) mainly affected by different types of noises. The pre-processing improves the quality of the image by using denoising method and those images are used for image segmentation and image classification. Spatial and frequency domain filters are widely used for denoising the images [3].

Image normalization, a common procedure in image processing, which changes the pixel intensity values. An image in  $n$  dimensions that is grayscale is changed via normalization [70].

$$I: \{x \subseteq r^n\} \{min, ..., max\}$$

Values of intensity between (Min, Max)

For new image

$$I: \{x \subseteq r^n\} \{newmin, ..., newmax\}$$

Range of new intensity value is (new Min, new Max).

The N3 nonparametric non-uniform intensity normalization technique is the method most frequently used. Sharpening histogram peaks with the reliable and well-proven algorithm N3 will lessen any intensity non-uniformity [4,5,7].

Image scans are spatially aligned to a reference anatomical space by registration. It is crucial since human brains differ from one another and have complicated structural differences. Image registration helps to standardize neuroimaging techniques in relation to a single fixed-size template [6]. In MR images, measurement of tissue volume in each location is the purpose of tissue segmentation. Early stages of neurodegeneration, especially in the medial temporal lobe, have an impact on Grey Matter (GM). GM probability provide a measurable depiction of the location of this tissue in the brain, with the quantity of local GM indicated by the brightness of each voxel [8].

Skull Stripping is one of the risky preprocessing techniques that could aid in the precise detection of neurological disorder. This eliminates the skull's from images. This can be utilised independently or in conjunction with neck or cerebellar excision. Additionally, Skull Stripping lessens the possibility of incorrect classification of brain tissues during the division of incompatible tissues [75]. Correct brain extraction increases the possibility that many neurological illnesses, including dementia and schizophrenia, will be self-diagnosed. The primary concept behind Skull Stripping is that it solely affects the brain and destroys non-brain tissue-dura substances like the exterior blood vessels. The computational efficiency of many neuroimaging algorithms is improved by these non-brain tissues. Skull Stripping is divided into a number of groups, as manual, semi-automated and automated methods [3] and motion artifacts in the brain image are reduced [67].

In preprocessing noise removal play a major role. Various filters are used for removing noises in the images. Image filtering is the pre-processing steps that aids in the removal of noise and enhances the image quality. There are many imaging modalities including X-rays, CT, ultrasound, MRI [71]. Every modality is affected by the appropriate noises. One important non-invasive medical imaging technique is MRI.

MRI is affected by various types of noises such as Gaussian noise, salt and pepper noise, speckle noise and Rician noise. Rician noise is mostly reflected in the MR image [77]. Rician noise is a type of multiplicative noise, so MR images become challenging to analyses [72]. Denoising techniques are classified into a spatial and frequency domain filtering. In spatial domain mean filter, median filter, gaussian filter and wiener filters used widely. In frequency domain lee filter, cuan filter, frost filter, wavelet filter and curvelet filter are considered [73,76]. Tables 1 and 2 shows the different preprocessing methods and denosing techniques used for AD analysis.

## 5. Image segmentation

In brain MRI, the affected area is highlighted via image segmentation. In brain MRI, the hippocampus and overall brain volume are the areas that are diagnosed with the help of segmentation process. Alzheimer's disease patients, members of the healthy cohort, and people with mild cognitive impairment are identified using different segmentation methods. Depending upon the area of brain in MR images different methods of segmentation algorithm is used to segment the region of interest. Thersholding, region-based methods, clustering, atlas guide approaches, edge-based methods are widely used methods for image segmentation. Table 3 shows the different segmentation methods used for AD analysis.

## 6. Feature extraction

Feature extraction is an important step in image classification. The output of segmentation which give the region of interest is considered as input for feature extraction. In machine learning the necessary features are extracted. The deep learning methods extracted features from the layers developed. The tabulation of feature analysis is shown in Table 4.

## 7. Image classification

For the purpose of early disease prediction and classification, different automated techniques based on ML and DL have recently been developed. Table 5 shows the performance analysis of various ML techniques.

### 7.1. Machine learning approach for AD classification

In this survey different machine learning algorithm for classification of AD is discussed. Weimingling et al. (2018) developed a learning strategy based on CNN. It is intended to precisely predict the conversion of MCI to AD using MRI data. Features are extracted from the patch images and principal component analysis was used for feature reduction. These features are given to an ELM to predict the AD with accuracy of 81.4 %, specificity of 68 %, sensitivity 89.6 % and Area Under Curve (AUC) of 87.8 %. Samsuddin Ahmed et al. (2019) designed CNN network for patch-based classification, left and right hippocampus classification of AD and NC images. Ensemble classifiers achieves the classification accuracy of 90.0 % for the GRAD dataset and 85.55 % for the ADNI dataset. Chunfeng Lian et al. (2020) developed a hierarchical classification model by jointly learning and fusing multi-scale feature representations. This network reduces the parameter and increases the classification performance. Classification of AD vs NC achieves the accuracy of 90 %, the sensitivity of 82 %, specificity of 97 %, and AUC of 95 %, Progressive MCI vs MCI achieves 81 % accuracy, 53 % of sensitivity, and 85 % of specificity.

Abolbahr et al. (2021) proposed a CNN and Deep Neural Network (DNN) model for AD classification from structural MR image. From this method 94.82 % of average weighted classification accuracy and 94.02 % for volumetric feature accuracy for left and right hippocamp was achieved. Additional to this AUC of 92.54 % and 90.62 % for right and left hippocampi was achieved. Jie Zhang (2021) suggested a technique

**Table 1**  
Preprocessing methods for Quality Improvement.

Process	Remarks	Method	Author and year
Skull-stripping	Gray and white mater are separated from non brain,	FreeSurfer	Fan, Z [30], 2021
		–	Weimingling [8], 2018
		FMRIB's Brain Extraction Tool	Shaji [33], 2021
		–	Jain [19], 2019
		CAT12 with SPM12 software	Sun, H. [35], 2021
		–	Oktavian [24], 2022
		–	Liu M [26], 2019
		Brain Extraction Tool (FSL-BET)	Hongfei Wang [36], 2019
		–	Buvaneswari, P.R [44], 2021
		–	Weimingling [8], 2018
Intensity normalization and Intensity correction (contrast, Brightness)	(i) handle the illumination correction in image (ii) improve contrast and brightness (iii) normalize uneven light distribution where linear contrast stretching helps in enhancing the image quality (iv) affine alignment of brain images are performed to remove the linear global differences	Performed by histogram deformation	Samsuddin Ahmed [9], 2019
		–	Jie Zhang [13], 2021
		Non-parametric and non-uniform bias correction algorithm	AbdulAzeem, Y [15], 2021
		Adaptive thresholding	Vaithinathan K [18], 2019
		Statistical Parametric Mapping (SPM)	–
		–	Jain [19], 2019
		Edge-Preservation Coherence Improvement (EP-CI) algorithm	T.V.Ramana, [21], 2021
		Adaptive Histogram Adjustment (AHA) algorithm	V. Sathiyamoorthi [22], 2021
		Histogram Equalization	Ahmed s. Musallam [40], 2022
		VBM-DARTEL, and DPABI	Yu Wang [27], 2021
		CAT12 toolkit	N. Deepa [28], 2022
		FreeSurfer	Fan, Z [30], 2021
		FMRIB's Brain Extraction Tool	Shaji [33], 2021
		linear contrast stretching algorithm	Jayanthi Venkatraman [34], 2022
		CAT12 with SPM12 software	Sun, H. [35], 2021
Hippocampus localization	Left and right hippocampus regions are detected better and considered as Region of interest	Brain Extraction Tool (FSL-BET)	Hongfei Wang [36], 2019
		nnU-Net	K.R. Kruthika [49], 2019
		Octagon histogram equalization with black and white Stretching.	Menagadevi [45], 2023
		–	Samsuddin Ahmed [9], 2019
		–	–
sMRI image sampling	Improve spatial resolution	–	Chunfeng Lian [10], 2020



**Table 2**  
Preprocessing Methods for Image Denoising.

Filter	Noises and distortion	Author and year
Median Filter	Salt and pepper noise	Muhammad Assam [80], 2021
	Scalp and skull	Nayak, M.M [86], 2023
	–	Allada [92], 2023
	Rician noise	Saladi, S [93], 2023
2D-Adaptive Consensual Filter	–	Kaur [90], 2023
	Salt and pepper noise, Gaussian noise, Speckle and random noise	T.V.Ramana [21], 2021
Non-local mean algorithm (NLM)	–	Ahmed s. Musallam [40], 2022
3-D Log-Gabor Filters	–	Katia M. Poloni [81], 2021
Gaussian Filter	Geometric distortion and noise	Shaik Basheera [82], 2019
Adaptive Bilateral Filter	Speckle noise, Binary noise and random noise	V. Sathiyamoorthi [22], 2021
Rolling Guidance Filter	–	Vanitha, K [87], 2023
Spacial Domain Filters	–	Archana Gopinadhan [88], 2022
Wiener filter	Rician noise, Gaussian noise, and Rayleigh noise	Alabdali, R. N [89], 2023
Anisotropic diffusion filtering method	Interference noise and blurred edge	Bin Yan [83], 2022
3D median modified Wiener filter (MMWF)	Rician noise	Dohwa Lee [85], 2023
SGLSA algorithm	Static speckle noise	Ximeng Feng [91], 2023
Modified optimal curvelet	Rician noise	M.Menagadevi [45]
Transform-based multi-sensor denoising methods	–	Vishwakarma, A [66], 2022

that eliminated the white spaces from the brain image. 3D CNN method was developed with an accuracy of 97.35 %, sensitivity of 97.10 %, specificity of 97.95 %, AUC of 99.70 % to classify AD. AbdulAzeem, Y *et al.* (2021) proposed a CNN based end to end structure to classify AD from MR images. The framework achieved 97.5 % accuracy for ADNI dataset during multi-classification testing.

Amir Ebrahimi *et al.* (2021) proposed a 2D and 3D CNNs and Recurrent Neural Networks (RNN). 96.88 % accuracy, 100 % sensitivity, and 94.12 % specificity are achieved. Vaithinathan K (2019) proposed random forest, KNN and linear SVM for classification. The 812 images from ADNI database are used for validation. For AD/NC classification, the sensitivity of 89.58 % and specificity of 85.82 % was achieved. Jain *et al.* (2019) proposed a CNN architecture, for feature extractor VGG-16 was used and for the classification problem the mathematical model called PFSECTL which is based on transfer learning. V. Sathiyamoorthi *et al.* (2021) proposed a new methodology called the computer aided design process, which employs different algorithms to detect AD. The developed method is used to categorise the images and its symptoms based on a selection of parameters. 98 % accuracy is achieved to detect AD disease.

Oktavian *et al.* (2022) proposed a CNN approach using the Residual Network 18 Layer (ResNet-18) architecture. The model shows the accuracy of 88.3 %. Liu M *et al.* (2019) used both MR imaging data and demographic data. They proposed deep multi task and channel learning framework for simultaneous AD categorization and clinical score regression. The algorithm shows the accuracy of 93.7 %, specificity 93.2 %, sensitivity of 94.6 %, and area under curve of 98.6 % for AD vs CN images. C.Kavitha *et al.* (2022) proposed a ML model for the early detection of AD disease. They used OASIS and kaggle dataset of AD detection. The correlation coefficient, information gain, chi square feature is used for classification. The classification was achieved using decision tree, random forest, SVM, and XG boost voting with an

**Table 3**  
Segmentation methods for AD analysis.

Segmentation Techniques	Segmentation region	Author and year
Efficient Fuzzy C Means	Alzheimer region	T.V.Ramana [21], 2021
Adaptive Thresholding	Alzheimer region	V. Sathiyamoorthi [22], 2021
Adaptive Mean Shift		
Modified Expectation Maximization		
DBSegment	Small deep brain structures	K.R. Kruthika [49], 2019
DeepBrain library	Alzheimer region	Oktavian [24], 2022
Multiatlas label propagation and expectation maximization based refinement segmentation	138 anatomical morphometry image region	Saidjalol Toshkhujav [41], 2020
Thersholding	Hippocampus region	Balasundaram, A [47], 2023
SCF intensity probability distribution with bias regularization	Gray and white matter region	Raza, N. [48], 2023
Whale optimization algorithm and gray wolf optimization		Chitradevi [51], 2023
SPM with CAT12 toolbox	Brain tissue segmentation and White and gray region smoothing	Chitradevi Dhakhnamoorthy [53], 2023
SynthSeg	Alzheimer region, Not effected by changes in contrast and resolution.	Benjamin Billot [52], 2023
Seg Net	Detect Alzheimer region pertinent brain parts	Buveneswari, [44], 2021
Multi scale pooling	White matter extraction	Menagadevi [45], 2023
Residual autoencoder architecture		
K-Means Clustering and Watershed Method	Segmentation of hippocampus region	D Holilah [46], 2018
Modified Fuzzy C-means, pixel power segmentation	orchestrated location, white and gray region	Balaji, P [54], 2023
OTSU segmentation	Alzheimer region	Alhassan, A.M [56], 2019
U-Net architecture	Left and right hippocampus region	Helaly, H.A [57], 2022
MultiRes + UNet network	White and gray region	Li M [58], 2022

accuracy of 83 %.

## 7.2. Deep learning approach for AD classification

A batch normalisation layer and modified pre-trained AlexNet using brain images were proposed by Lu, Siyuan *et al.* in 2021. The chaotic bat method was employed to enhance the ELM's classification performance. The sensitivity, specificity and overall accuracy of the BN-AlexNet is better compared to other networks. Yu Wang *et al.* (2021) proposed a multimodal diagnosis approach for AD based on principal component analysis network and three-dimensional shufflenet. For AD versus NC, accuracy, sensitivity, specificity, precision, recall, f1 score and AUC is 85.2 %, 69 %, 96 %, 93.3 %, 69 %, 79 % and 86.9 %. For AD versus MCI accuracy, sensitivity, specificity, precision, recall, f1 score and AUC is 84 %, 84 %, 84 %, 84.9 %, 84 %, 84.1 % and 91.9 %. For MCI versus NC accuracy, sensitivity, specificity, precision, recall, f1 score and AUC 64.8 %, 43 %, 79.3 %, 60.2 %, 43 %, 48 % and 67.3 %.

N. Deepa *et al.* (2022) proposed the classification of AD, an improved VGG-16 network using the arithmetic optimization algorithm. An improved VGG-16 with arithmetic optimization algorithm successfully distinguishes between the several AD classes, including normal, early dementia and late dementia. Odusami *et al.* (2021) applies a modified version of ResNet18, which does binary classification of AD to detect different stages of AD. The 99.99 % of accuracy for EMCI vs. AD, 99.95 % for LMCI vs. AD and 99.95 % MCI vs. EMCI was obtained. Fan, Z *et al.* (2021) used the U-net model's characteristics for the purpose of diagnosing AD. Accuracy of  $95.71 \pm 1.36$  % for AD versus NC,  $90.14 \pm 3.66$

**Table 4**  
Feature Extraction for AD diagnosis.

Features	Method	Author and year
Deep (low and high level) features and multi-level features	Convolution Neural Network	Samsuddin Ahmed <a href="#">et.al</a> [9], 2019 Jie Zhang <a href="#">et.al</a> [13], 2021 Ahmed s. Musallam <a href="#">et.al</a> [40], 2022 N. Deepa <a href="#">et.al</a> [28], 2022 S. Murugan <a href="#">et.al</a> [16], 2021 Yu Wang <a href="#">et.al</a> [27], 2021
	Two dimensional ShuffleNet	Fan, Z <a href="#">et.al</a> [30], 2021
	U-net with skip connection	Zhonghao Fan <a href="#">et.al</a> [30], 2021
	Base model	Jain <a href="#">et.al</a> [19], 2019
	Deep Convolution Neural Network	Naz, S. <a href="#">et.al</a> [32], 2022
	Deep ResNet learning	Sun, H. <a href="#">et.al</a> [35], 2021
	DenseNet	Hongfei Wang <a href="#">et.al</a> [36], 2019
	SegNet	Buvaneswari, P.R <a href="#">et.al</a> [44], 2021
Patch, region, Structural and subject level feature	Hierarchical fully convolutional network	Chunfeng Lian <a href="#">et.al</a> [10], 2020
	FreeSurfer	Weimingling <a href="#">et.al</a> [8], 2018
	Fusion scheme with multiple grading maps	Hett K <a href="#">et.al</a> [23], 2018
	landmark-based feature extraction	Zhang J [60], 2017
Texture		Vaithinathan K <a href="#">et.al</a> [18], 2019
Gray Level Co-Occurrence Matrix		V. Sathiyamoorthi <a href="#">et.al</a> [22], 2021
Features of Ventricles and Hippocampi	Mixed effects models	Samaneh Abolpour Mofrad [12], 2021
	Convolution Neural Network	Samsuddin Ahmed <a href="#">et.al</a> [9], 2019
Cortical thickness and subcortical volumes	MALPEM toolbox	Saidjalol Toshkhujaev <a href="#">et.al</a> [41], 2020
Jacobian domain features	DLB framework	S. Qasim Abbas [55], 2023

% for EMCI versus LMCI  $90.05 \pm 2.63$  % for AD versus LMCI, and  $87.98 \pm 4.54$  % for NC versus EMCI, was obtained.

Heta Acharya *et al.* (2021) proposed VGG16, modified AlexNet and ResNet –50 to classify AD vs MCI, mild Alzheimer, moderate Alzheimer and severe impairment. Modified AlexNet shows improved result compared to other models. Naz, S. *et al.* (2022) developed the CNN architectures to classify binary and ternary data using freeze characteristics that were taken from the original data set ImageNet. It achieves an accuracy of 99.27 % for MCI/AD, 98.89 % for AD/CN, and 97.06 % for MCI/CN.

Jayanthi Venkatraman Shanmugam *et al.* (2022) proposed transfer learning to identify early signs of AD and different phases of cognitive impairment. The total success rates in identifying AD using GoogleNet, AlexNet, and ResNet-18 are 96.39 %, 94.08 %, and 97.51 %, respectively. Hongfei Wang (2019) developed an ensemble of 3D densely connected convolutional networks for the diagnosis of AD and MCI. Accuracy, recall and precision for classification of MCI/AD are 93.61 %, 92.45 % and 94.59 %. for MCI/NC 98.42 %, 98.34 % and 98.37 %, for AD/NC are 98.83, 98.70 and 98.70 %. Sunday Adeola Ajagbe *et al.* (2022) used magnetic resonance imaging to increase the classification of AD images using deep CNN, CNN, and transfer learning (VGG16 and VGG19). VGG 19 shows better accuracy. Buvaneswari, P.R *et al.* (2021) proposed deep learning-based segmenting strategy uses SegNet to identify brain regions relevant to AD from sMRI and ResNet-101 to reliably categorise AD and dementia conditions. Sensitivity of 96 % and

**Table 5**  
Performance Analysis of Various Machine Learning Techniques.

Author name/Year	Methodology	Dataset	Performance metrics
Weimingling <i>et al.</i> /2018 [18]	CNN, ELM	ADNI	Accuracy = 81.4 % Sensitivity = 89.6 % Specificity = 68 %
Samsuddin Ahmed <i>et al.</i> / 2019 [9]	ELM	GRAD ADNI	Accuracy ADNI dataset = 85.55 % GRAD dataset = 90.05 %
Chunfeng Lian <i>et al.</i> /2020 [10]	H-FCN	ADNI	AD vs NC Accuracy = 90.3 % Sensitivity = 82.4 % Specificity = 96.5 % Progressive MCI Vs MCI Accuracy = 80.9 % Sensitivity = 52.6 % Specificity = 85.4 %
A. Basher <i>et al.</i> /2021 [11]	DCNN	ADNI OASIS	Accuracy Left hippocampi = 94.82 % Right hippocampi = 94.02 % MCI Accuracy = 69 % Precision = 73 % Recall = 60 % AD Accuracy = 75 % Precision = 74 % Recall = 77 %
Samaneh Abolpour Mofrad <i>et al.</i> /2021 [12]	Mixed effect model	ADNI	Accuracy = 97.35 % Sensitivity = 97.10 % Specificity = 97.95 %
Salunkhe, S <i>et al.</i> /2021 [14]	Ensemble Decision tree, SVM		Accuracy Ensemble = 90.2 % Decision tree = 88.5 % SVM = 87.2 %
AbdulAzeem, Y <i>et al.</i> /2021 [15]	CNN	ADNI	Accuracy = 97.5 %
Amir Ebrahimi <i>et al.</i> /2021 [17]	CNN, RNN	ADNI	Accuracy = 96.88 % Sensitivity = 100 % Specificity = 94.12 %
Vaithinathan K <i>et al.</i> /2019 [18]	RROI-GM + WMkNN (Fisher)	ADNI	Sensitivity = 89.58 % Specificity = 85.82 %
Jain <i>et al.</i> /2019 [19]	P <sub>F</sub> S <sub>E</sub> C <sub>TL</sub> CNN	ADNI	AD Precision = 100 %

(continued on next page)

Table 5 (continued)

Author name/Year	Methodology	Dataset	Performance metrics
			Recall = 95 % F1 score = 91 % <u>CN</u> Precision = 99 % Recall = 98 % F1 score = 97 % <u>MCI</u> Precision = 90 % Recall = 94 % F1 score = 100 % Accuracy = 98 %
Shailendra Kumar Mishra and V. Hima Deepthi/2021 [20]	SVM	ADNI	
T.V.Ramana, S M Nandhagopal/2021 [21]	CNN	FLAIR	Accuracy = 98 %
V. Sathiyamoorthi et al./2021 [22]	CNN	ADNI, OASIS	Accuracy = 98 %
Oktavian et al./2022 [24]	CNN	ADNI	Accuracy = 90.1 % Precision = 93 % Accuracy = 99.32 % Sensitivity = 95 % Specificity = 98.33 % Precision = 97.26 % F1 score = 96.58 % <u>CN Vs AD</u> Accuracy = 94.6 % Sensitivity = 94.2 % Specificity = 86.86 % <u>CN Vs pMCI</u> Accuracy = 92 % Sensitivity = 92.5 % Specificity = 81.2 % <u>ADVs sMCI</u> Accuracy = 82.6 % Sensitivity = 77.6 % Specificity = 72.6 % <u>sMCI Vs pMCI</u> Accuracy = 76.1 % Sensitivity = 74.9 % Specificity = 70.2 %
Xu-Dong Li et al./2022 [25]	Probability distributions Biogeography-based Optimization (PDBO)	ADNI	
Hett K et al./2018 [23]	Texture-based grading method	ADNI	
Liu M et al./2019 [26]	Deep Multi-task multi-channel learning	ADNI MIRIAD	Accuracy = 93.7 % Sensitivity = 94.6 % Specificity = 93.2 %
W. Li, Y et al./2019 [38]	Transfer Learning	ADNI Tongji	Accuracy = 84.6 % Sensitivity = 92 %

Table 5 (continued)

Author name/Year	Methodology	Dataset	Performance metrics
Y. Lei et al./2019 [39]	Semi supervised ELM	G50C COIL20B USPST USPST (B)	Specificity = 79 % Accuracy = 0.87
SaidjalolToshkhujav et al./2020 [41]	RBF-SVM principal component analysis	ADNI ARWIBONACC	<u>Accuracy:</u> NACC = 94.74 ARWIBO = 94.87 ADNI = 87.50 <u>Sensitivity:</u> NACC = 92.56 ARWIBO = 88.89 ADNI = 77.78 <u>Specificity:</u> NACC = 100 ARWIBO = 92.75 ADNI = 100 Accuracy = 83 %
C. Kavitha et al./2022 [42]	Decision Tree Random Forest	OASIS Kaggle	

an accuracy of 95 % was achieved over 240 ADNI sMRI that were not used for training.

Zhonghao Fan et al. (2021) used 3D T1-weighted MRI, a U-net type model for AD diagnosis. The model was evaluated for classification of AD vs. NC vs. EMCI vs. LMCI in addition to these binary-classification tasks and it performs accuracy is 96 %. K.R. Kruthika (2019) presented a system for the early detection of Alzheimer's that uses 3D Capsule Network, 3D-CNN, and pre-trained 3D-autoencoder technology. The model could classify AD with up to 98.42 % accuracy. Suriya Murugan et al. (2021) proposed Dementia Network architecture to diagnose Alzheimer and dementia disorder. The model produced an accuracy of 95.23 %, 97 % of the area under curve and 93 % of cohens kappa value for ADNI and Kaggle dataset. Table 6 shows the performance metrics of various DL techniques. Figure 6 shows the accuracy of different DL techniques.

8. Limitation of learning techniques

There are various machine and deep learning techniques are mentioned and discussed. Both the techniques have their own limitations. The limitation of machine learning techniques includes limited number of dataset for validation [8,22,29,30,38], less accuracy [9], fixed input patches, complicated pruning strategy, nonlinear registration increased the computational complexity [10], less explainable model [12] computational time to train parameters [13,18], multi-classification not possible [15,24,33,35,37,39,44,59], not applicable for larger dataset [17,21,23], computational complexity [19,20,27,28,30–32,36,43], input images should be increased [25], performance degradation due to different dataset [26], redundant and irrelevant features are used [42], structure complexity [34].

The accuracy of various machine and deep learning techniques are shown in figure 6 and 7.

9. Conclusion

Major causes of death in developed nations after stroke is AD. Due to the difficulty of early AD detection in hospitals, the integration of computer-based methods with medical professionals has much to recommend it for early AD detection. ML and DL has established a lot of attention recently for this task. The study describes how the development of AD detection systems has been made possible by machine learning and deep learning. This paper is about image dataset available



**Table 6**

Performance analysis of Various DL Techniques.

Author name/Year	Methodology	Dataset	Performance metrics
Lu, Siyuan <i>et al.</i> /2021[37]	AlexNet ELM optimized by chaotic bat algorithm	ATLAS	Sensitivity = 97.14 % % Specificity = 95.71 % Accuracy = 96.43 % Precision = 96.17 % F1 score = 96.50 %
Yu Wang <i>et al.</i> /2021 [27]	PCA Net 3D ShuffleNet	ADNI	<u>AD versus NC</u> Accuracy = 85.2 %, Sensitivity = 69 %, Specificity = 96 %, Precision = 93.3 % F1 score = 69 %, Recall = 79 % <u>AD versus MCI</u> Accuracy = 84 %, Sensitivity = 84 %, Specificity = 84 %, Precision = 84 % F1 score = 84.9 %, Recall = 84.1 % <u>MCI versus NC</u> Accuracy = 85.2 %, Sensitivity = 69 %, Specificity = 96 %, Precision = 93.3 % F1 score = 69 %, Recall = 79 % Accuracy = 97 %
N. Deepa <i>et al.</i> /2022 [28]	VGG-16	ADNI OASIS	
Odusami <i>et al.</i> /2021 [29]	Modified version of ResNet18	ADNI	<u>Accuracy</u> EMCI vs. AD = 99.99 % LMCI vs.AD = 99.95 % MCI vs. EMCI = 99.95 % <u>Accuracy</u> AD versus NC = 95.71 ± 1.36 % EMCI versus LMCI = 90.14 ± 3.66 % AD versus LMCI = 90.05 ± 2.63 % NC versus EMCI = 87.98 ± 4.54 % <u>VGG16</u> Accuracy = 84 %, Precision = 84 % F1 score = 84.9 %, Recall = 84.1 % <u>ResNet-50</u> Accuracy = 75.25 %,Precision = 56.56 % F1 score = 79.41 %, Recall = 43.78 % <u>AlexNet</u> Accuracy = 95.70 %,Precision = 91.90 % F1 score = 94.70 %, Recall = 92.30 %
Fan, Z <i>et al.</i> / 2021 [30]	U-net model's	ADNI, AIBL	<u>Accuracy</u> AD versus NC = 95.71 ± 1.36 % EMCI versus LMCI = 90.14 ± 3.66 % AD versus LMCI = 90.05 ± 2.63 % NC versus EMCI = 87.98 ± 4.54 % <u>VGG16</u> Accuracy = 84 %, Precision = 84 % F1 score = 84.9 %, Recall = 84.1 % <u>ResNet-50</u> Accuracy = 75.25 %,Precision = 56.56 % F1 score = 79.41 %, Recall = 43.78 % <u>AlexNet</u> Accuracy = 95.70 %,Precision = 91.90 % F1 score = 94.70 %, Recall = 92.30 %
Heta Acharya <i>et al.</i> /2021[31]	VGG16, ResNet –50 and modified AlexNet	ADNI	<u>Accuracy</u> MCI/AD-99.27 %, AD/CN-98.89 % MCI/CN-97.06 % Precision = 69 %, Recall = 69 % <u>Accuracy</u> GoogleNet = 96.39 %,AlexNet = 94.08
Naz, S. <i>et al.</i> /2022 [32]	VGG	ADNI	<u>Accuracy</u> MCI/AD-99.27 %, AD/CN-98.89 % MCI/CN-97.06 % Precision = 69 %, Recall = 69 % <u>Accuracy</u> GoogleNet = 96.39 %,AlexNet = 94.08
Shaji <i>et al.</i> /2021[33]	Inception-Residual Network (ResNet)	ADNI	<u>Accuracy</u> GoogleNet = 96.39 %,AlexNet = 94.08
Jayanthi Venkatraman	Google Net, Alex Net, ResNet-18	ADNI	<u>Accuracy</u> GoogleNet = 96.39 %,AlexNet = 94.08

**Table 6 (continued)**

Author name/Year	Methodology	Dataset	Performance metrics
Shanmugam <i>et al.</i> /2022[34]			% ResNet-18 = 97.51 %
Sun, H. <i>et al.</i> /2021 [35]	ResNet	ADNI	Accuracy = 97.1 %, Precision = 95.5 % F1 score = 95.4 %, Recall = 95.3 %
Hongfei Wang <i>et al.</i> / 2019[36]	3D-DenseNets	ADNI	<u>MCI/AD</u> Accuracy = 93.61 %,Precision = 92.45 % Recall = 94.59 % <u>MCI/NC</u> Accuracy = 98.42 %,Precision = 98.34 % Recall = 98.37 % <u>AD/NC</u> Accuracy = 98.83 %,Precision = 98.70 % Recall = 98.70 %
Sunday Adeola Ajagbe <i>et al.</i> /2022 [43]	DL CNN VGG-16,19	Kaggle	<u>Accuracy</u> CNN = 0.7102 VGG-16 = 0.7704 VGG-19 = 0.7766 <u>Precision</u> CNN = 0.54 VGG-16 = 0.5708 VGG-19 = 0.5848 <u>F1 score</u> CNN = 0.52 VGG-16 = 0.4617 VGG-19 = 0.4505 <u>Recall</u> CNN = 0.5004 VGG-16 = 0.3878 VGG-19 = 0.3667
Buvaneswari, P.R <i>et al.</i> /2021 [44]	Segnet Resnet101	ADNI	Accuracy = 95 %, Sensitivity = 96 %
Zhonghao Fan <i>et al.</i> / 2021[30]	U-net	ADNI, AIBL	<u>Accuracy</u> AD vs NC = 95.71 %, EMCI vs LMCI = 90.14 % AD vs LMCI = 90.5 % NC vs EMCI = 87.98 % Accuracy = 98.42 %
K.R. Kruthika <i>et al.</i> /2019[49]	3D-Capsule Networks (CapsNets)	ADNI	Accuracy = 95.23 %
S. Murugan <i>et al.</i> /2021[16]	DEMNET	ADNI, Kaggle	Accuracy = 97.35 %
Mujahid, M <i>et.al</i> / 2023 [84]	Efficient ensemble approach of VGG16 and Efficient-Net-B2	ADNI	Accuracy = 98.50 %
Ibrahim, R <i>et.al</i> / 2023 [50]	Particle Swarm Optimization with CNNs	ADNI	Accuracy = 99.68 %
Marwa EL <i>et.al</i> / 2023 [59]	Shallow Convolutional Neural Network	OASIS	Accuracy = 97.31 %
Rana <i>et.al</i> / 2023 [68]	Hybrid Deep Learning Model	kaggle	Accuracy = 97.14 %
Rana <i>et.al</i> / 2023 [62]	Sub-grouping analysisby manifold learning	ADNI	

for AD analysis, image pre-processing techniques for image denoising and enhancement, image segmentation techniques to segment the region of interest and image classification using machine learning and deep learning techniques. Classification accuracy of AD is better in DL compare to ML models.




Fig. 6. Accuracy of different ML techniques.




Fig. 7. Accuracy of different DL techniques.

## Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

## Data availability

Review Paper

## References

- [1] Emma Nichols 'Estimation of the global prevalence of dementia in 2019 and forecasted prevalence in 2050: An analysis for the Global Burden of Disease Study 2019', 7 2 2022.
- [2] R. Gautam, M. Sharma, 'Prevalence and diagnosis of neurological disorders using different deep learning techniques: A meta-analysis, J. Med. Syst. 49 (2020), <https://doi.org/10.1007/s10916-019-1519-7>.
- [3] C. Narasimha, A.N. Rao, A comparative study: Spatial domain filter for medical image enhancement, Int. Conference on Signal Processing and Communication Eng. Sys. (2015) 291–295, <https://doi.org/10.1109/SPACES.2015.7058268>.
- [4] H.-I. Suk S.-W. Lee D. Shen and the Alzheimer's Disease Neuroimaging Initiative, 'Hierarchical feature representation and multimodal fusion with deep learning for AD/MCI diagnosis' Neuroimage. 101 2014 569 582.
- [5] Suryawanshi, Shweta Patil, Sanja, 'Preprocessing and Skull Stripping of Brain Tumor Extraction from Magnetic Resonance Imaging Images Using Image Processing' 2021 10.3233/APC210208.
- [6] Y. Zeng, B. Zhang, W. Zhao, S. Xiao, G. Zhang, H. Ren, Y. Ding, Magnetic resonance image denoising algorithm based on cartoon, texture, and residual parts, Comput. Math. Methods. Med. (2020) 1–10, <https://doi.org/10.1155/2020/1405647>.
- [7] D. Sreelakshmi, S. Inthiyaz, Fast and denoise feature extraction based ADMF-CNN with GBML framework for MRI brain image, Int J Speech Technol. 24 (2021) 529–544, <https://doi.org/10.1007/s10772-020-09793-w>.
- [8] L. Weiming, T. Tong, G. Qinqun, D.u. Guo Di, Y.Y. Xiaofeng, G. Gang, D.u. Xiao Min, M.Q. Xiaobo, The Alzheimer's disease neuroimaging initiative, 'convolutional neural networks-based mri image analysis for the Alzheimer's disease prediction from mild cognitive impairment', Front. Neurosci. 12 (2018) <https://doi.org/10.3389/fnins.2018.00777>, ISSN=1662-453X.
- [9] S. Ahmed, 'Ensembles of patch-based classifiers for diagnosis of Alzheimer diseases', IEEEAccess 7 (2019) 73373–73383, <https://doi.org/10.1109/ACCESS.2019.2920011>.
- [10] C. Lian, M. Liu, J. Zhang, D. Shen, Hierarchical fully convolutional network for joint atrophy localization and Alzheimer's disease diagnosis using structural MRI, IEEE Trans. Pattern Anal. Mach. Intell. 42 (4) (2020) 880–893, <https://doi.org/10.1109/TPAMI.2018.2889096>.
- [11] B.C. Basher, K.H. Kim, Lee, H.Y. Jung, 'Volumetric feature-based Alzheimer's disease diagnosis from sMRI data using a convolutional neural network and a deep neural network', IEEEAccess 9 (2021) 29870–29882, <https://doi.org/10.1109/ACCESS.2021.3059658>.
- [12] Samaneh Abolpour Mofrad, Arvid Lundervold, Alexander Selvikvåg Lundervold, 'A predictive framework based on brain volume trajectories enabling early detection of Alzheimer's disease', Comput. Med. Imaging Graph. 90 (2021).
- [13] J. Zhang, B. Zheng, A. Gao, X. Feng, D. Liang, X. Long, A 3D densely connected convolution neural network with connection-wise attention mechanism for Alzheimer's disease classification, Magn. Reson. Imaging 78 (2021) 119–126, <https://doi.org/10.1016/j.mri.2021.02.001>.
- [14] S. Salunkhe, M. Bachute, S. Gite, N. Vyas, S. Khanna, K. Modi, C. Katpatal, K. Kotecha, Classification of Alzheimer's disease patients using texture analysis and machine learning, Appl. Syst. Innov. (2021), <https://doi.org/10.3390/asi4030049>.
- [15] Y. AbdulAzeem, W.M. Bahgat, M. Badawy, A CNN based framework for classification of Alzheimer's disease, Neural. Comput. & Applic. 33 (2021) 10415–10428, <https://doi.org/10.1007/s00521-021-05799-9>.
- [16] S. Murugan, 'DEMNET: A Deep learning model for early diagnosis of Alzheimer diseases and dementia from MR images', IEEEAccess. 9 (2021) 90319–90329, <https://doi.org/10.1109/ACCESS.2021.3090474>.
- [17] A. Ebrahimi, Suhuai Luo, Alzheimer's Disease Neuroimaging Initiative 'Convolutional neural networks for Alzheimer's disease detection on MRI images', Journal of Medical Imaging 8 (2) (2021) <https://doi.org/10.1117/1.JMI.8.2.024503>.
- [18] K. Vaithinathan, L. Parthiban, Alzheimer's disease neuroimaging initiative, 'a novel texture extraction technique with T1 weighted MRI for the classification of Alzheimer's disease', J. Neurosci Methods. 318 (2019) 84–99, <https://doi.org/10.1016/j.jneumeth.2019.01.011>.
- [19] Jain Rachna, Jain Nikita, Aggarwal Akshay, Hemanth D. Jude, 'Convolutional neural network based alzheimer's disease classification from magnetic resonance brain images', Cogn. Syst. Res. (2019) <https://doi.org/10.1016/j.cogsys.2018.12.015>.
- [20] S.K. Mishra, V.H. Deepthi, RETRACTED ARTICLE: 'Brain image classification by the combination of different wavelet transforms and support vector machine classification', J. Ambient Intell. Hum. Comput. 12 (6) (2020) 6741–6749, <https://doi.org/10.1007/s12652-020-02299-y>.

- [21] T.V. Ramana, S.M. Nandhagopal, 'Alzheimer Disease Detection And classification on magnetic resonance imaging (Mri) brain images using improved expectation maximization (IEM) and convolutional neural network (CNN)', *Turkish Journal of Computer and Mathematics Education* 12 (11) (2021) 5998–6006.
- [22] V. Sathiyamoorthi, A.K. Ilavarasi, K. Murugeswari, S.T. Ahmed, B. Aruna Devi, M. Kalipindi, A deep convolutional neural network based computer aided diagnosis system for the prediction of Alzheimer's disease in MRI images, *Measurement* 171 (2021).
- [23] K. Hett, V.T. Ta, J.V. Manjón, P. Coupé, Alzheimer's disease neuroimaging initiative. 'adaptive fusion of texture-based grading for Alzheimer's disease classification', *Comput. Med. Imaging. Graph.* 70 (2018) 8–16, <https://doi.org/10.1016/j.compmedimag.2018.08.002>.
- [24] Oktavian, Muhammad Wildan, Novanto Yudistira, and Achmad Ridok. 'Classification of Alzheimer's Disease Using the Convolutional Neural Network (CNN) with Transfer Learning and Weighted Loss', *arXiv preprint arXiv: 2207.01584* (2022).
- [25] X.-D. Li, J.-S. Wang, W.-K. Hao, M. Wang, M. Zhang, Multi-layer perceptron classification method of medical data based on biogeography-based optimization algorithm with probability distributions, *Appl. Soft Comput.* 121 (2022).
- [26] M. Liu, J. Zhang, E. Adeli, D. Shen, Joint classification and regression via deep multi-task multi-channel learning for Alzheimer's disease diagnosis, *IEEE. Trans. Biomed. Eng.* 66 (5) (2019) 1195–1206, <https://doi.org/10.1109/TBME.2018.2869989>.
- [27] Yu Wang, Xi Liu, Chongchong Yu, 'Assisted Diagnosis of Alzheimer's disease based on deep learning and multimodal feature fusion', *Complexity* (2021) <https://doi.org/10.1155/2021/6626728>.
- [28] N. Deepa, S.P. Chokkalingam, Optimization of VGG16 utilizing the arithmetic optimization algorithm for early detection of Alzheimer's disease, *Biomed. Signal Process. Control.* 74 (2022).
- [29] M. Odusami, R. Maskeliūnas, R. Damaševičius, T. Krilavičius, Analysis of features of Alzheimer's disease: Detection of early stage from functional brain changes in magnetic resonance images using a finetuned ResNet18 network, *Diagnostics*. 11 (6) (2021), <https://doi.org/10.3390/diagnostics11061071>.
- [30] Z. Fan, J. Li, L. Zhang, U-net based analysis of MRI for Alzheimer's disease diagnosis, *Neural. Comput. & Applic.* 33 (2021) 13587–13599, <https://doi.org/10.1007/s00521-021-05983>.
- [31] H. Acharya, R. Mehta, D.K. Singh, Alzheimer Disease Classification Using Transfer Learning, in: 5th International Conference on Computing Methodologies and Communication (ICCMC), 2021, <https://doi.org/10.1109/iccmc51019.2021.9418294>.
- [32] S. Naz, A. Ashraf, A. Zaib, Transfer learning using freeze features for Alzheimer neurological disorder detection using ADNI dataset, *Multimedia. Syst.* 28 (2022) 85–94, <https://doi.org/10.1007/s00530-021-00797-3>.
- [33] S. Shaji, N. Ganapathy, R. Swaminathan, Classification of Alzheimer condition using MR brain images and inception-residual network model, *Current Directions in Biomedical. Engineering.* 7 (2) (2021) 763–766, <https://doi.org/10.1515/cdbme-2021-2195>.
- [34] Jayanthi Venkatraman Shanmugam, Baskar Duraisamy, Blessy Chittattukarakkaran Simon, Preethi Bhaskaran, 'Alzheimer's disease classification using pre-trained deep networks', *Biomed. Signal Process. Control* 71 (2022).
- [35] H. Sun, A. Wang, W. Wang, C. Liu, An improved deep residual network prediction model for the early diagnosis of Alzheimer's disease, *Sensors*. 21 (2021), <https://doi.org/10.3390/s21124182>.
- [36] H. Wang, Y. Shen, S. Wang, T. Xiao, L. Deng, X. Wang, X. Zhao, Ensemble of 3D densely connected convolutional network for diagnosis of mild cognitive impairment and Alzheimer's disease, *Neurocomputing* 333 (2019) 145–156.
- [37] S. Lu, S.H. Wang, Y.D. Zhang, Detection of abnormal brain in MRI via improved AlexNet and ELM optimized by chaotic bat algorithm, *Neural. Comput. & Applic.* 33 (2021) 10799–10811, <https://doi.org/10.1007/s00521-020-05082-4>.
- [38] W. Li, Y. Zhao, X. Chen, Y. Xiao, Y. Qin, Detecting Alzheimer's disease on small dataset: A knowledge transfer perspective, *IEEE J. Biomed. Health Inform.* 23 (3) (2019) 1234–1242, <https://doi.org/10.1109/JBHI.2018.2839771>.
- [39] Y. Lei, L. Cen, X. Chen, Y. Xie, A hybrid regularization semi-supervised extreme learning machine method and its application, *IEEE Access.* 7 (2019) 30102–30111, <https://doi.org/10.1109/ACCESS.2019.2900267>.
- [40] S. Musallam, A.S. Sherif, M.K. Hussein, A new convolutional neural network architecture for automatic detection of brain tumors in magnetic resonance imaging images, *IEEE. Access.* 10 (2022) 2775–2782, <https://doi.org/10.1109/ACCESS.2022.3140289>.
- [41] Hossa.in. Belayat, Toshkhujayev Saidjalol, 'Classification of alzheimer's disease and mild cognitive impairment based on cortical and subcortical features from MRI T1 brain images utilizing four different types of datasets', *Journal of Healthcare Engineering* (2020).
- [42] C. Kavitha, M. Vinodhini, S.R. Srividhya, K.O. Ibrahim, T.R.C. Andrés, 'Early-Stage Alzheimer's disease prediction using machine learning models', *Frontiers. Public. Health.* 10 (2022).
- [43] S.A. Ajagbe, K.A. Amuda, M.A. Oladipupo, F.A.F.E. Oluwaseyi, K.I. Okesola, Multi-classification of Alzheimer disease on magnetic resonance images (MRI) using deep convolutional neural network (DCNN) approaches, *International. J. Advanced. Computer. Research.* 11 (53) (2022), <https://doi.org/10.19101/IJACR.2021.1152001>.
- [44] P.R. Buvaeswari, R. Gayathri, deep learning-based segmentation in classification of Alzheimer's disease, *Arab. J. Sci. Eng.* 46 (2021) 5373–5383, <https://doi.org/10.1007/s13369-020-05193-z>.
- [45] M. Menagadevi, S. Mangai, Nirmala Madian, D. Thiyagarajan, 'Automated prediction system for Alzheimer detection based on deep residual autoencoder and support vector machine', *Optik* 272 (2023).
- [46] D. Holilah, A. Bustamam, D. Sarwinda, Detection of Alzheimer's disease with segmentation approach using K-Means clustering and watershed method of MRI image, *J. Phys.: Conf.* (2021).
- [47] A. Balasundaram, S. Srinivasan, A. Prasad, Hippocampus segmentation-based Alzheimer's disease diagnosis and classification of MRI images, *Arab. J. Sci. Eng.* (2023), <https://doi.org/10.1007/s13369-022-07538-2>.
- [48] N. Raza, A. Naseer, M. Tamoor, K. Zafar, Alzheimer disease classification through transfer learning approach, *Diagnostics*. 13 (2023), <https://doi.org/10.3390/diagnostics13040801>.
- [49] M. Baniyasadi, M.V. Petersen, J. Gonçalves, A. Horn, V. Vlasov, F. Hertel, A. Husch, DBSegment: Fast and robust segmentation of deep brain structures considering domain generalization, *Hum. Brain Mapp.* 44 (2) (2023) 762–778, <https://doi.org/10.1002/hbm.26097>.
- [50] R. Ibrahim, R. Ghnemat, Q. Abu Al-Hajja, Improving Alzheimer's Disease and brain tumor detection using deep learning with particle swarm optimization, *AI.* 4 (2023) 551–573, <https://doi.org/10.3390/ai4030030>.
- [51] C. Dhakshinamoorthy, Sathish Kumar Mani, Sandeep Kumar Mathivanan, Senthilkumar Mohan, Prabhu Jayagopal, Saurav Mallik, Hong Qin, 'Hybrid whale and gray wolf deep learning optimization algorithm for prediction of alzheimer's disease', *Mathematics*. 11 (5) (2023) 1136.
- [52] B. Billot, D.N. Greve, O. Puonti, A. Thielscher, K. Van Leemput, B. Fischl, A. V. Dalca, Juan Eugenio Iglesias, 'SynthSeg: Segmentation of brain MRI scans of any contrast and resolution without retraining', *Med. Image Anal.* 86 (2023).
- [53] A.J. Chang, R. Roth, E. Bougiouklis, MRI-based deep learning can discriminate between temporal lobe epilepsy, Alzheimer's disease, and healthy controls, *Commun Med* 3 (2023) 33, <https://doi.org/10.1038/s43856-023-00262-4>.
- [54] P. Balaji, M.A. Chaurasia, S.M. Bilfaqih, A. Muniasamy, L.E.G. Alsidi, Hybridized deep learning approach for detecting alzheimer's disease, *Biomedicine* 11 (2023).
- [55] S. Qasim Abbas, L. Chi, Y.-P. Chen, Transformed domain convolutional neural network for Alzheimer's disease diagnosis using structural MRI, *Pattern Recogn.* 133 (2023).
- [56] A.M. Alhassan, The Alzheimer's disease neuroimaging initiative, the australian imaging biomarkers and lifestyle flagship study of ageing. 'Enhanced Fuzzy elephant herding optimization-based OTSU segmentation and deep learning for alzheimer's disease diagnosis', *Mathematics* 10 (2022) <https://doi.org/10.3390/math10081259>.
- [57] H.A. Helaly, M. Badawy, A.Y. Haikal, Toward deep MRI segmentation for Alzheimer's disease detection, *Neural Comput & Applic* 34 (2020) 1047–1063, <https://doi.org/10.1007/s00521-021-06430-8>.
- [58] M. Li, C. Hu, Z. Liu, Y. Zhou, MRI segmentation of brain tissue and course classification in alzheimer's disease, *Electronics* 11 (2022), <https://doi.org/10.3390/electronics11081288>.
- [59] Marwa EL-Geneedy, Hossam El-Din Moustafa, Fahmi Khalifa, Hatem Khater, Eman Abdelhalim, An MRI-based deep learning approach for accurate detection of Alzheimer's disease', *Alex. Eng. J.* 63 (2023) 211–221.
- [60] J. Zhang, M. Liu, L. An, Y. Gao, D. Shen, Alzheimer's disease diagnosis using landmark-based features from longitudinal structural MR images, *IEEE J Biomed Health Inform* 21 (6) (2017) 1607–1616, <https://doi.org/10.1109/JBHI.2017.2704614>.
- [61] Y. Gupta, R. Lama, G.R. Kwon, Prediction and classification of alzheimer's disease based on combined features from apolipoprotein-E genotype, cerebrospinal fluid, MR, and FDG-PET imaging biomarkers, *Front. Comput. Neurosci.* (2019), <https://doi.org/10.3389/fncom.2019.00072>.
- [62] D. Van der Haar, A. Moustafa, S.L. Warren, et al., An Alzheimer's disease category progression sub-grouping analysis using manifold learning on ADNI, *Sci Rep* 13 (2023), <https://doi.org/10.1038/s41598-023-37569-0>.
- [63] X. Bi, S. Li, Y. Bin Xiao, G.W. Li, X. Ma, Computer aided Alzheimer's disease diagnosis by an unsupervised deep learning technology, *Neurocomputing* 392 (2020) 296–304.
- [64] X. Zhao, C.K.E. Ang, U. Rajendra Acharya, K.H. Cheong, 'Application of Artificial Intelligence techniques for the detection of Alzheimer's disease using structural MRI images', *Biocybernetics and Biomedical Engineering* 41 (2) (2021) 456–473.
- [65] W. Li, Y. Zhao, X. Chen, Y. Xiao, Y. Qin, Detecting alzheimer's disease on small dataset: A knowledge transfer perspective, *IEEE J. Biomed. Health Inform.* 23 (2019) 1234, <https://doi.org/10.1109/JBHI.2018.2839771>.
- [66] A. Vishwakarma, M.K. Bhuyan, A curvelet-based multi-sensor image denoising for KLT-based image fusion, *Multimed Tools Appl* 81 (2022) 4991–5016, <https://doi.org/10.1007/s11042-021-11570-z>.
- [67] A.B. Tufail, Y.-K. Ma, M.K.A. Kaabar, A.U. Rehman, R. Khan, O. Cheikhrouhou, 'Classification of initial stages of alzheimer's disease through PET neuroimaging modality and deep learning: quantifying the impact of image filtering approaches', *Mathematics* 9 (2021) <https://doi.org/10.3390/math9233101>.
- [68] M.M. Rana, M.M. Islam, M.A. Talukder, M.A. Uddin, S. Aryal, N. Alotaibi, S. A. Alyami, K.F. Hasan, M.A. Moni, A robust and clinically applicable deep learning model for early detection of Alzheimer's, *IET Image Process* (2023) 1–17, <https://doi.org/10.1049/ipr2.12910>.
- [69] T. Smith-Vikos, F.J. Slack, MicroRNAs circulate around Alzheimer's disease, *Genome Biol.* 14 (2013) 125, <https://doi.org/10.1186/gb-2013-14-7-125>.
- [70] T. Zhang, Z. Zhao, C. Zhang, J. Zhang, Z. Jin, L. Li, Classification of early and late mild cognitive impairment using functional brain network of resting-state fMRI, *Front. Psych.* 10 (2019) 572.
- [71] F. Susanto, A.P. Rahardian, H.S. Utami, L.D. Saputri, K.M. Wibowo, A.N. Mayani, Application of Denoising Weighted Bilateral Filter and Curvelet Transform on

- Brain MR Imaging of Non-cooperative Patients, in: Proceedings of the 2nd International Conference on Electronics, Biomedical Engineering, and Health Informatics. Lecture Notes in Electrical Engineering, 2022, p. 898, [https://doi.org/10.1007/978-981-19-1804-9\\_17](https://doi.org/10.1007/978-981-19-1804-9_17).
- [72] Silvia Basaia Federica Agosta Luca Wagner Elisa Canu Giuseppe Magnani Roberto Santangelo Massimo Filippi 'Automated classification of Alzheimer's disease and mild cognitive impairment using a single MRI and deep neural networks' *NeuroImage: Clinical* 21 2019 10.1016/j.nicl.2018.101645.
- [73] S. Savas, Detecting the stages of alzheimer's disease with pre-trained deep learning architectures, *Arab J Sci Eng* 47 (2022) 2201–2218, <https://doi.org/10.1007/s13369-021-06131-3>.
- [74] P. Sahu P.K. Sarangi S.K. Mohapatra B.K. Sahoo 'Detection and Classification of Encephalon Tumor Using Extreme Learning Machine Learning Algorithm Based on Deep Learning Method', In: Dehuri, S., Prasad Mishra, B.S., Mallick, P.K., Cho, SB. (eds), *Biologically Inspired Techniques in Many Criteria Decision Making, Smart Innovation, Systems and Technologies*, 271 2022 10.1007/978-981-16-8739-6\_26.
- [75] S. Tripathi, S.H. Nozadi, M. Shakeri, S. Kadoury, Sub- cortical shape morphology and voxel-based features for Alzheimer's disease classification. *Proceedings of IEEE 14th International Symposium on Biomedical Imaging*, 2017.
- [76] B. Richhariya M. Tanveer A. Rashid Initiative ADN et al., 'Diagnosis of Alzheimer's disease using universum support vector machine based recursive feature elimination (USVM-RFE)' *Biomed Signal Process Control* 59 2020 10. 1016/j.bspc.2020.101903.
- [77] R. Biswas, D. Purkayastha, S. Roy, Denoising of MRI images using curvelet transform, in: *In Proc. of ASCA*, 2018, pp. 575–583.
- [78] P. Singh, S.K. Mishra, Alzheimer's Detection and Categorization using a Deep-Learning Approach, in: *Third International Conference on Intelligent Computing Instrumentation and Control Technologies (ICICICT)*, 2022, pp. 727–734, <https://doi.org/10.1109/ICICICT54557.2022.9917774>.
- [79] T.A. Lakshmi, R. Vinupriyadharshini, Noise and skull removal of brain magnetic resonance image using curvelet transform and mathematical morphology, in: *International Conference on Electronics and Communication Systems (ICECS)*, 2014, pp. 1–4, <https://doi.org/10.1109/ECS.2014.6892801>.
- [80] M. Assam, H. Kanwal, U. Farooq, S.K. Shah, A. Mehmood, G.S. Choi, An efficient classification of MRI brain images, *IEEE Access* 9 (2021) 33313–33322, <https://doi.org/10.1109/ACCESS.2021.3061487>.
- [81] K.M. Poloni, A. Italo, D. de Oliveira, R. Tam, R.J. Ferrari, 'Brain MR image classification for Alzheimer's disease diagnosis using structural hippocampal asymmetrical attributes from directional 3-D log-Gabor filter responses, *Neurocomputing*' 419 (2021) 126–135, <https://doi.org/10.1016/j.neucom.2020.07.102>.
- [82] S. Basheera, M. Satya Sai Ram, 'Convolution neural network-based Alzheimer's disease classification using hybrid enhanced independent component analysis based segmented gray matter of T2 weighted magnetic resonance imaging with clinical valuation', *Alzheimer's & Dementia: Translational Research & Clinical Interventions* 5 (2019) 974–986, <https://doi.org/10.1016/j.trci.2019.10.001>.
- [83] B. Yan, Y. Li, L. Li, X. Yang, T.-Q. Li, G. Yang, M. Jiang, Quantifying the impact of Pyramid Squeeze Attention mechanism and filtering approaches on Alzheimer's disease classification, *Comput. Biol. Med.* 148 (2022).
- [84] M. Mujahid, A. Rehman, T. Alam, F.S. Alamri, S.M. Fati, T. Saba, An efficient ensemble approach for alzheimer's disease detection using an adaptive synthetic technique and deep learning, *Diagnostics* 13 (2023), <https://doi.org/10.3390/diagnostics13152489>.
- [85] D. Lee, C.-S. Yun, S.-H. Kang, M. Park, Y. Lee, 'Performance evaluation of 3D median modified Wiener filter in brain T1-weighted magnetic resonance imaging', *Nuclear instruments and methods in physics research section A: Accelerators, spectrometers, Detectors and Associated Equipment* 1047 (2023).
- [86] M.M. Nayak, S.D. Kengeri Anjanappa, An efficient hybrid classifier for MRI brain images classification using machine learning based naive bayes algorithm, *SN COMPUT. SCI.* 4 (223) (2023), <https://doi.org/10.1007/s42979-022-01614-y>.
- [87] K. Vanitha, D. Satyanarayana, M.N.G. Prasad, Medical image fusion for diagnosis of alzheimer using rolling guidance filter and parameter adaptive PCNN, *Lecture Notes in Electrical Engineering* 946 (2023), [https://doi.org/10.1007/978-981-19-5868-7\\_6](https://doi.org/10.1007/978-981-19-5868-7_6).
- [88] A. Gopinadhan, P.G. Angeline, S. Anbarasu, AD-EHS: Alzheimer's disease severity detection using efficient hybrid image segmentation, *Adv. Eng. Softw.* 173 (2022).
- [89] R.N. Alabdali, An intelligent hybrid optimization with deep learning model-based schizophrenia identification from structural MRI, *Information Sciences Letters* (2023).
- [90] Kaur Chamandeep Tuhina Panda Subhasis Panda Abdul Rahman Mohammed ALAnsari Ms M. Nivetha B. Kiran Bala 'Utilizing the Random Forest Algorithm to Enhance Alzheimer's disease Diagnosis' 2023.
- [91] X. Feng, M. Geng, X. Meng, D.a. Zou, Z.i. Jin, G. Liu, C. Zhou, Q. Ren, L.u. Yanye, SGLSA: Sphygmus gated laser speckle angiography for microcirculation hemodynamics imaging, *Comput. Med. Imaging Graph.* 103 (2023).
- [92] A. Allada, R. Bhavani, K. Chaduvula, R. Priya, 'Early diagnosis of alzheimer disease from mri using deep learning models', *Journal of Information Technol. Manag.* (2023) 52–71.
- [93] S. Saladi, Y. Karuna, S. Koppu, G.R. Reddy, S. Mohan, S. Mallik, H. Qin, 'Segmentation and analysis emphasizing neonatal MRI brain images using machine learning techniques', *Mathematics* 11 (2023) <https://doi.org/10.3390/math11020285>.
- [94] <https://adni.loni.usc.edu/about/>.
- [95] <https://www.oasis-brains.org/#access>.
- [96] <https://www.kaggle.com/datasets/sachinkumar413/alzheimer-mri-dataset/data>.
- [97] <https://www.ucl.ac.uk/drc/research/research-methods/minimal-interval-resonance-imaging-alzheimers-disease-miriad>.
- [98] <https://www.frontiersin.org/articles/10.3389/fninf.2020.571039/full>.