

CariSurg MedTech Pathways Research Project

Preliminary Proposal

Project Title: Assessing the Performance Gain of Stacked Ensemble Models Over Traditional Machine Learning Methods for Emergency Department Triage in a Caribbean Emergency Departments

Student Name: Rhys Brown

Statement of the Problem:

At Mercer ED, limited resuscitation bed capacity places pressure on timely and accurate patient triage. The department operates in a Caribbean hospital, sharing laboratory, radiology and pharmacy services with other departments. Previous studies demonstrate that AI-integrated triage systems can improve triage performance compared with conventional methods (1–3) and reduce the time required for patients to receive life-saving care (4). However, TriageIntelli (5) achieved a less than 2% absolute improvement in triage accuracy using stacked machine learning models compared with base models, raising questions about whether additional complexity is clinically justified.

Previous Work:

Traditional triage is under strain from overcrowding, resource constraints and significant variation in patient prioritization due to subjective clinical assessments. Using peer-reviewed articles from PubMed, Scopus, IEEE Xplore and Google Scholar, researchers conducted a narrative review of the strengths and limitations of AI for patient triage in emergency departments. Several studies suggested that AI-driven triage may improve patient prioritization, reduce wait times and optimize resource allocation. However, key challenges were found, including data quality limitations, algorithmic bias, low trust among clinicians and overall ethical concerns. That said, the review was narrative in nature and limited to English-language articles published between 2014-2024, potentially omitting relevant findings from studies that failed to meet said criteria. (1)

Despite positive outcomes in other aspects of healthcare, the capacity of AI to assist in triaging patients in the emergency department remains relatively underexplored. Researchers conducted a search for peer-reviewed, English-language studies in the EMBASE, Ovid MEDLINE and Web of Science databases using relevant medical subject headings (MeSH) terms. The review found that, compared with conventional triage, AI integration was associated with improved triage discrimination, disease identification and resource allocation. Despite these findings, the review included several studies which used retrospective datasets from only a single teaching hospital, possibly limiting the generalisability of the results. (2)

Overcrowding within hospital emergency departments has become a major challenge, risking negative health outcomes for patients. A narrative synthesis was conducted on ten studies that evaluated AI-assisted Emergency Severity Index (ESI) triage systems involving emergency nurses as well as reporting on triage performance and challenges. AI-assisted triage enhanced patient flow as well as reducing over-triage, under-triage and patient wait times. Despite these findings, the review relied on retrospective data and included studies with limited model validation, potentially restricting real-world applicability. (3)

Based on industry guidelines, patients with ST-segment elevation myocardial infarction (STEMI) require a door-to-balloon (D2B) time of less than 90 minutes, but delays often occur due failures to interpret the electrocardiography (ECG) efficiently. An AI-based model for STEMI detection using ECG data and ASAP scores was developed using 2907 twelve-lead ECGs, including 882 STEMI and 2025 non-STEMI. Mean D2B time was reduced from 64.5 minutes to 53.2 minutes with the proportion of patients treated within 90 minutes increasing from 87.2% to 98.5%. Limitations include the study relying on a cohort of less than 200 patients from a single center. Verification of generalisability would require a larger-scale diverse study. Moreover, the study also has a false positive rate of roughly 20%, which may contribute to unnecessary prioritization of non-STEMI patients. (4)

Limited resources, overcrowding and a rising number of complex cases are putting pressure on patient triage; AI integration was identified as a means to enhance process efficiency. Seven different AI-based models were used to evaluate patient triage levels in accordance with the Korean triage and acuity score (KTAS). The Support Vector Machines (SVM) and Gradient Boosting Machines (GBM) models performed best individually with accuracies of 79% and 78.7% respectively, but the stacking model had a marginal improvement of less than 2% compared with both. However, the study used only one dataset; therefore, the model generalisability may be limited as different regions have varying clinical conditions, demographics and seasonal patterns. Real-world testing in different medical contexts is required. (5)

Inconsistent triage decisions can reduce the quality of patient care, an especially severe problem in the high-pressure environment of an emergency department. The researchers used a large language model-based intake system to obtain patient data, analysed it using a machine learning model (CatBoost) to predict triage levels. After tuning, the model achieved 85% accuracy with an F1-score of 0.960 on the ESI-1 class. Although promising, the model needs to be validated in multilingual settings to ensure fairness and generalisability. (6)

Prolonged ED stays contribute to patient flow bottlenecks which are associated with worse clinical outcomes, making accurately assigning ED disposition an operational challenge. To manage this issue, three machine learning models were trained to differentiate between those who could be discharged or admitted. The models were trained on progressively enriched feature sets: immediately apparent triage stage information from patients triaged under the Manchester Triage System (MTS), a clinical model which combined the triage stage information with four binary health indicators and a comprehensive model which combined the clinical model data with laboratory tests and diagnosis-related variables. The comprehensive model performed the best, followed by the clinical and triage-stage models. However, all three models achieved moderate

predictive performance. The study was only a single-center retrospective study; furthermore, the performance of the models suffered when information could not be extracted as readily, such as in the case of another language being spoken by the patient. (7)

Emergency department personnel must rapidly determine whether patients need to be admitted on limited clinical data under rigid time and resource constraints. To address this challenge, several machine learning models were trained on triage data gathered within ten minutes of patient presentation. The models had good overall performance on hospital admission and 30-day mortality, particularly for mortality prediction. Comparatively, predictive performance on ICU admission was lower. However, the study's single-centre design may limit generalizability. (8)

Across studies employing different machine learning approaches, the integration of AI into the triage process was associated with improvements in clinically relevant patient outcomes (1–3,6). Reported clinical benefits include reduced time to receive life-saving intervention (4). Operational improvements such as reduced patient waiting times and improved hospital resource allocation have been recorded (1,2,4). Moreover, some models were capable of classifying patients requiring discharge or further treatment (2,7,8). These findings were not limited to a specific machine learning architecture and have been demonstrated across different algorithms (5–8). Similar findings have been documented across multiple triaging systems, including the Manchester Triage System, Korean Triage and Acuity Score and Emergency Severity Index (3,5–7).

However, several gaps in the literature are evident. Most studies relied on retrospective data from a single center to train the machine learning models (2,3,7). The use of this type of clinical data in model training may reduce model generalizability. Moreover, none of the reviewed models were trained on Caribbean datasets. This raises concerns regarding the applicability of these models to Caribbean populations, which may differ in comorbidity profiles and case-mix compared to the original training datasets. Ensemble models showed improved predictive accuracy compared to the base models; however, the improvement was marginal (5). Further research is needed to determine whether ensemble approaches provide meaningful and clinically significant performance gains over simpler baseline models. This is particularly relevant due to the increased computational complexity of ensemble models where performance gains must match the additional implementation and computational costs within the resource-constrained Caribbean healthcare settings.

Proposed Solution:

Over the course of a 12-week pilot, a stacked ensemble AI triage model will be developed and evaluated using Mercer ED data. The model performance will be compared to both the base machine learning/deep learning models and the baseline Mercer ED triage statistics. A stacked model will be considered successful if it exhibits an absolute improvement in accuracy of greater than or equal to 5% over the base models and the triage baseline. This threshold will be used to determine whether the increased complexity of a stacked ensemble model is justified for future clinical use.

References:

1. Da'Costa A, Teke J, Origbo JE, Osonuga A, Egbon E, Olawade DB. AI-driven triage in emergency departments: A review of benefits, challenges, and future directions. *Int J Med Inf.* 2025 May;197:105838. doi:10.1016/j.ijmedinf.2025.105838
2. Tyler S, Olis M, Aust N, Patel L, Simon L, Triantafyllidis C, et al. Use of Artificial Intelligence in Triage in Hospital Emergency Departments: A Scoping Review. *Cureus.* 2024 May 8;16(5). doi:10.7759/cureus.59906
3. Fatai A, Sattayarom C, Laochai W, Faksook E. Effectiveness of AI-assisted ESI triage on accuracy and selected outcomes in emergency nursing: A systematic review. *Int Emerg Nurs.* 2025 Dec;83:101680. doi:10.1016/j.ienj.2025.101680
4. Wang YC, Chen KW, Tsai BY, Wu MY, Hsieh PH, Wei JT, et al. Implementation of an All-Day Artificial Intelligence–Based Triage System to Accelerate Door-to-Balloon Times. *Mayo Clin Proc.* 2022 Dec;97(12):2291–303. doi:10.1016/j.mayocp.2022.05.014
5. Araouchi Z, Adda M. TriageIntelli: AI-Assisted Multimodal Triage System for Health Centers. *Procedia Comput Sci.* 2024;251:430–7. doi:10.1016/j.procs.2024.11.130
6. Saeed O, Yüksel ME. An Intelligent Triage System for Hospital Emergency Services Based on Large Language Models and Machine Learning. In: 2026 5th International Informatics and Software Engineering Conference (IISEC) [Internet]. Ankara, Turkey: IEEE; 2026 [cited 2026 Jun 15]. p. 267–71. Available from: <https://ieeexplore.ieee.org/document/11418412/> doi:10.1109/IISEC69317.2026.11418412
7. Yoshimura K, Moriguchi T. Machine learning-based model for triage-stage prediction of emergency department disposition. *BMC Emerg Med.* 2026 Mar 10;26:110. doi:10.1186/s12873-026-01523-w
8. Tschoellitsch T, Seidl P, Böck C, Maletzky A, Moser P, Thumfart S, et al. Using emergency department triage for machine learning-based admission and mortality prediction. *Eur J Emerg Med.* 2023 Dec;30(6):408–16. doi:10.1097/MEJ.0000000000001068