

# Building a Khmer Traffic Sign Dataset for Automated Detection and Classification

**Sophearith Chren      Second Author      Third Author      Fourth Author**

Department of Computer Science of Cambodia Academy of Digital Technology,

Phnom Penh Cambodia

corresponding\_author@cadt.edu.kh

## Abstract

Traffic Sign Detection and Classification have become a core feature of computer vision, contributing for intelligent transportation systems, traffic monitoring and driver assistance technologies. However, the availability of public datasets illustrating Khmer traffic signs remains limited, making it challenging to develop and evaluate reliable detection and classification models for Cambodia. To overcome the lack of the publicly available Khmer datasets, this research introduces a custom Khmer traffic sign datasets collected and annotated the capture image from various locations in Cambodia. The datasets contain an image captured under multiple real-world conditions including different lighting, different angles, distance, background and covers 42 classes commonly found in Cambodia. To evaluate the dataset, YOLOv8 and YOLOv10 models were trained and compared. YOLOv8 achieved the best performance with an accuracy of 93% on the primary dataset and was integrated into a bilingual web-based application supporting both Khmer and English languages for automated traffic sign detection and classification. This system demonstrates the practical application of deep learning-based Khmer traffic sign recognition and provides a foundation for future research and intelligent transportation applications in Cambodia.

**Keywords:** *Khmer Traffic Sign, Khmer Traffic Sign Detection and Classification (KTSDC), Computer Vision, Deep Learning*

## 1 Introduction

Traffic Signs play a significance role in modern transportation systems by providing an importance information, guiding driver behavior and enhancing road safety [1][2]. With the rapid of development of computer vision and deep learning techniques, automated traffic sign detection

and classification have become main research areas for intelligent transportation systems and driver assistance technologies.

Developing accurate and reliable traffic sign detection and classification models require a large-scale dataset. Existing datasets, including German Traffic Sign Recognition Benchmark (GTSRB) [3], Mapillary Traffic Sign Dataset (MTSD) [1], Tsinghua-Tencent 100K (TT100K) [4], provide comprehensive coverage for their regions. However, they are limited for specific countries and do not effectively represent the traffic sign used in Cambodia [1], [3], [4].

In Cambodia, the availability of publicly accessed Khmer traffic sign datasets remains limited [5]. Existing research on Cambodian traffic signs focuses only on seven classes [5], which do not fully represent the wide range of usually found in Cambodia roadways. Therefore, this limitation highlights a significant research gap in the development of a complete KTSDC system.

To address this research gap, this study proposes a KTSDC system based on a custom traffic sign dataset that was collected and annotated from various locations across Cambodia. The proposed collection consists of 42 classes of traffic sign types collected under various real-world conditions, including different lighting, different angles, distances, and backgrounds. Furthermore, YOLOv8 and YOLOv10 were trained and evaluated to find out the effectiveness for Khmer traffic sign detection and classification.

## 2 Dataset

In this section, we will describe the custom Khmer traffic sign dataset produced in this project. The dataset was manually collected and annotated for traffic sign detection and classification in Cambodia road environments.

## 2.1 Dataset Overview

This paper introduces custom Khmer traffic sign dataset designed for traffic sign detection and classification in Cambodia road conditions. The proposed dataset was collected and annotated by our team, which consisted of 42 classes that consisting several categories including regulation, warning, required, and informational signals. The collected images demonstrate various real-world environments with differences in lighting, angles, distances and backgrounds. Figure 1 demonstrates the complete set of traffic sign classes included in the proposed dataset. In the next section will detail the data collection, annotation and data statistics.



Figure 1. The 42 traffic sign classes included in the proposed dataset

## 2.2 Data Collection

The traffic sign images were manually collected by our team from several sites across Cambodia using a smartphone camera. Data collecting was conducted on a few different road types, which include urban streets and rural streets. Images were taken under different real-world conditions, such as different lighting conditions, viewing angles, object distances, and background environments, to boost dataset diversity. After data gathering, all the images were carefully reviewed to remove duplicate images, images without traffic signs, and images that contain poor visibility that prevented clear identification of the traffic signs. This process ensured that only the quality images were left for data annotation process.

## 2.3 Data Annotation

Following data collection, all the images were manually annotated using the CVAT annotation tool. Each traffic sign was allocated a rectangular bounding box and provided with a class label according to one of the 42 predefined traffic sign

classes. The annotations were exported in the YOLO format, containing the class identifier and normalized bounding box coordinates for each signs. To ensure annotations quality, all annotations have been manually validated by our team, and incorrect class labels or inaccurate bounding boxes were fixed before finish datasets.




Figure 2. Example of the traffic sign annotation process. Original image. Annotated image with bounding box and class label generated using CVAT

## 2.4 Data Statistics

The proposed dataset consisted of 31667 images illustrating 42 classes and 31734 for annotated traffic signs, while 123 images are the images contain backgrounds images without traffic signs annotation. The number of annotated images exceeds the number of images because some images contain multiple annotated traffic signs. The distribution of annotated across the 42 classes demonstrated in Figure 3, displaying the variance in each class represent within the dataset. To simplify model training, validation and testing. The dataset was divided into training, validation, and testing subsets using a [70:20:10] ratio. The training subset was used to enhance the model parameters, while validation was utilized to check model performance throughout training. The testing subset designed for the final evaluation of the train models. The number of propotion of images assigned to each subset are summarizezed in Table 1.

## 3 Methodology

The following section discusses the techniques utilized to develop and create the Khmer traffic sign detection and classification approach. The overall research process and experimental procedures are describe in the following section.

Table 1. Distribution of Images and Annotations in the Proposed Dataset

| Dataset Subset | Total | Training | Validation | Testing |
|----------------|-------|----------|------------|---------|
| Images         | 31667 | 22148    | 6318       | 3201    |
| Labels         | 31544 | 22064    | 6292       | 3188    |
| Bounding Box   | 31734 | 22195    | 6335       | 3204    |




Figure 3. Class distribution of images and annotated traffic signs across the 42 classes.

### 3.1 Methodology Workflow

The proposed methodology establishes a systematic workflow for Khmer traffic sign detection and classification. The process begins with data preparation and data preprocessing for the annotated traffic sign dataset, followed by the model development and training under experimental set up. After training, the models will be evaluated on the test dataset using standard object detection metrics. The obtained results are subsequently compared to identify the model that achieves performance for the Khmer dataset.

### 3.2 Data Preprocessing

This stage was conducted to ensure that the dataset was properly prepared and the images and annotations were accurate and suitable for model processing.

#### 3.2.1 Data Cleaning

The collected dataset was first reviewed to delete unnecessary or low quality images. Duplicates were detected and eliminated to prevent repeated samples from introducing bias into the training dataset. Furthermore, the images with severe blur were identified and removed when the traffic sign was not clearly recognizable.

The annotation files were also checked for duplicate or inconsistent labels. The image and label were reviewed to ensure that each image was associated with the correct annotation in-

formations. These cleaning methods were conducted before the annotation verification and model training stages.

#### 3.2.2 Annotation and Label Verification

Following data cleaning, the annotation and matching class labels were verified to ensure their validation and consistency. The bounding boxes were checked to confirm that they accurately involved the traffic sign without unnecessary background regions. The images containing several traffic signs were annotated with a separate bounding box for each sign. Images without traffic signs that were identified as background were kept. The class labels were checked against the class ID in each annotation to ensure both images and labels are consistent.

### 3.3 Model Development

Two YOLO-based object detection models, YOLOv8 and YOLOv10, were trained on the proposed Khmer traffic sign dataset to detect and classify 42 traffic sign classes. The development process involved configuring each model for the proposed detection task, training the models using the prepared dataset, and evaluating the model performance under consistent experimental conditions. The architecture of the two models is described in the following subsections.

#### 3.3.1 YOLOv8 Architecture

YOLOv8 is a one-stage, anchor-free object detection model applied for Khmer traffic sign detection and classification, with its overall architecture pipeline represented in Figure 4. The input images are resized to 832 x 832 before processing. The backbone uses convolutional layers, C2f modules, and Spatial Pyramid Pooling-Fast (SPPF), which extract features at different spatial resolutions. The extracted feature maps are passed to the neck, which uses an FPN-PAN structure to perform multi-scale feature fusion through upsampling, concatenation, and convolutional operations. Finally, the anchor-free, decoupled detection head generates predictions at

three feature levels, P3, P4, and P5, with strides of 8, 16, and 32, respectively, for bounding-box regression and classification [6], [7].




Figure 4. YOLOv8-based architecture for Khmer traffic sign detection and classification

### 3.3.2 YOLOv10 Architecture

The overall architecture of YOLOv10 designed for Khmer traffic sign recognition is presented in Figure 5. YOLOv10 is designed as an end-to-end object detector that avoids the Non-Maximum Suppression (NMS). In this study, the images are downsized to 832 x 832 before process by the network. The backbone utilizes efficient design including Compact Inverted Block (CIB) modules and Spatial-Channel Decoupled Downsampling (SCDown) to enhance the computing performance while maintain an important feature information. In advanced stages, the model integrates Partial Self-Attention (PSA) to enhance global feature representation with minimum computational cost. The neck performs multi-scale feature fusion using a PAN-based structure to merge semantic and Spatial Information from differnt features levels. Ultimately, YOLOv10 adopts a consistent dual-assignment method with one-to-many and one-to-one prediction head during training. One-to-many head provides the model more training information for each object, while the one-to-one head is preserved during inference to provide the final prediction without require NMS [8].

### 3.4 Model Training

The experiment were conducted using Google Colab with an NVIDIA Tesla T4 GPU (15GB




Figure 5. YOLOv10-based architecture for Khmer traffic sign detection and classification

VRAM) to train the YOLOv8 and YOLOv10 models. Both models were develop using the Ultralytics framework, established with their pre-trained weights, and fine-tuned on the prepared Khmer traffic sign dataset. The dataset for this experiment was split into 70% for training, 20% for validation and 10% for testing as shown in the Table 1.

Both model were trained with an input image size of 832 x 832 pixels, and a batch size of 6 for a maximum of 40 epochs. The AdamW optimizer was used for model optimization, with validation performance during training to monitor the model performance. The detailed training configuration and hyperparameter are summarized in Table 2.

Table 2. Training Configuration and Hyperparameters

| Hyperparameter | YOLOv8    | YOLOv10   |
|----------------|-----------|-----------|
| Image Size     | 832 × 832 | 832 × 832 |
| Batch Size     | 6         | 6         |
| Epochs         | 40        | 40        |
| Optimizer      | AdamW     | AdamW     |
| Learning Rate  | 0.001     | 0.001     |
| Weight Decay   | 0.0005    | 0.0005    |
| Workers        | 2         | 2         |
| Patience       | 20        | 20        |

### 3.5 Model Evaluation

Model Evaluation is the process of using the different evaluating method to analyze machine learning model performance. As shown it is a crucial step for machine learning process, as it determines the models ability to generalize

to unseen data and make accurate predictions. In this research, the models were evaluated on unseen data standard object detection metric to evaluate their ability for recognize Khmer traffic sign.

The evaluation metric used in this study include:

**Accuracy:** is the propotion of correct predictions among the total number of predictions made by the model.

$$\text{Accuracy} = \frac{TP + TN}{TP + FP + FN + TN} \quad (1)$$

**Precision:** is the propotion of correctly detected among all the traffic signs predicted by the model.

$$\text{Precision} = \frac{TP}{TP + FP} \quad (2)$$

**Recall:** is the ratio of correctly detected object among all actual objects in the dataset.

$$\text{Recall} = \frac{TP}{TP + FN} \quad (3)$$

**F1-Score:** is an evaluation metric that combines precision and recall to measure the overall performance of the model.

$$\text{F1-Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} \quad (4)$$

**Intersection over Union (IoU):** is measures the overlap between the predicted bounding box and the ground-truth bounding box.

$$\text{IoU} = \frac{\text{Area of Intersection}}{\text{Area of Union}} \quad (5)$$

**mean Average Precision (mAP):** is an evaluation metric used to measure the overall performance of an object detection model, often given as mAP@50 and mAP@95, by calculating the average precision (AP) overall traffic sign classes at different thresholds.

$$\text{mAP} = \frac{1}{N} \sum_{i=1}^N \text{AP}_i \quad (6)$$

In this research, True Positive (TP) represent a correctly detected traffic sign, True Negative (TN) represents a correctly identified non-traffic-sign region, False Positive (FP) represents an incorrect detection and False Negative (FN) represents a traffic sign that is missed by the model [9].

## 4 Result and Discussion

## 5 Conclusion

Although a conclusion may review the main points of the paper, do not replicate the abstract as the conclusion. A conclusion might elaborate on the importance of the work or suggest applications and extensions.

## Acknowledgment

Thanks to XXXXXXXXXXXX. This format is a modification of ONA 2018, SNLP 2013, KICSS2006 and IJCKS2007 style file.

## References

- [1] C. Ertler, J. Mislej, T. Ollmann, L. Porzi, G. Neuhold, and Y. Kuang, “The Mapillary Traffic Sign Dataset for detection and classification on a global scale,” *Lecture notes in computer science*, pp. 68–84, 1 2020. [Online]. Available: [https://doi.org/10.1007/978-3-030-58592-1\\_5](https://doi.org/10.1007/978-3-030-58592-1_5)
- [2] W. Farag, “Traffic signs classification by deep learning for advanced driving assistance systems,” *Intelligent Decision Technologies*, vol. 13, no. 3, pp. 305–314, 8 2019. [Online]. Available: <https://doi.org/10.3233/idt-180064>
- [3] J. Stallkamp, M. Schlipsing, J. Salmen, and C. Igel, “Man vs. computer: Benchmarking machine learning algorithms for traffic sign recognition,” *Neural Networks*, vol. 32, pp. 323–332, 2 2012. [Online]. Available: <https://doi.org/10.1016/j.neunet.2012.02.016>
- [4] Z. Zhu, D. Liang, S. Zhang, X. Huang, B. Li, and S. Hu, “Traffic-sign detection and classification in the wild,” in *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 2110–2118.
- [5] S. Ratitya and M. Tokunaga, “Traffic signs mapping in cambodia with deep learning and gnss,” in *Proc. 46th Asian Conference on Remote Sensing (ACRS)*, Oct 2025, accessed: 2025. [Online]. Available: <https://acrs-aars.org/proceedings2025/>
- [6] J. Terven, D.-M. Córdoba-Esparza, and J.-A. Romero-González, “A comprehensive review of YOLO architectures in computer vision: from YOLOV1 to YOLOV8 and YOLO-NAS,” *Machine Learning and Knowledge Extraction*, vol. 5, no. 4, pp.

1680–1716, 11 2023. [Online]. Available: <https://doi.org/10.3390/make5040083>

- [7] Ultralytics, “Explore Ultralytics YOLOV8,” 8 2026. [Online]. Available: <https://docs.ultralytics.com/models/yolov8>
- [8] A. Wang, H. Chen, L. Liu, K. Chen, Z. Lin, J. Han, and G. Ding, “YOLOV10: Real-Time End-to-End Object Detection,” *arXiv (Cornell University)*, 5 2024. [Online]. Available: <http://arxiv.org/abs/2405.14458>
- [9] “Classification: Accuracy, recall, precision, and related metrics.” [Online]. Available: <https://developers.google.com/machine-learning/crash-course/classification/accuracy-precision-recall>