

0. Imports and Setting up Anthropic API Client

```
from google.colab import drive
```

```
drive.mount('/content/drive')
```

Mounted at /content/drive

```
!pip install python-dotenv
```

```
import os
import dotenv
```

```
dotenv.load_dotenv('/content/drive/MyDrive/.env')
```

Collecting python-dotenv
 Downloading python_dotenv-1.0.1-py3-none-any.whl (19 kB)
 Installing collected packages: python-dotenv
 Successfully installed python-dotenv-1.0.1
 True

```
# Load Prompts and Problem Description
```

```
# Variables Prompt
```

```
prompt11_path = '/content/drive/MyDrive/Thesis/Prompts/Prompt11_MathematicalModel.txt'
```

```
# Objective Prompt
```

```
prompt12_path = '/content/drive/MyDrive/Thesis/Prompts/Prompt12_MathematicalModel.txt'
```

```
# Constraint Prompt
```

```
prompt13_path = '/content/drive/MyDrive/Thesis/Prompts/Prompt13_MathematicalModel.txt'
```

```
# Code Prompt
```

```
prompt2_path = '/content/drive/MyDrive/Thesis/Prompts/Prompt2_PyomoCode.txt'
```

```
problem_desc_path = '/content/drive/MyDrive/Thesis/ProblemDescriptions/IP/IP2.txt'
```

```
prompt11_file = open(prompt11_path, "r")
prompt12_file = open(prompt12_path, "r")
prompt13_file = open(prompt13_path, "r")
prompt2_file = open(prompt2_path, "r")
problem_desc_file = open(problem_desc_path, "r")
```

```
prompt11 = prompt11_file.read()
print("Prompt 1.1 (Variables):\n", prompt11)
```

```
prompt12 = prompt12_file.read()
print("Prompt 1.2 (Objective):\n", prompt12)
```

```
prompt13 = prompt13_file.read()
print("Prompt 1.3 (Constraints):\n", prompt13)
```

```
prompt2 = prompt2_file.read()
print("Prompt 2:\n", prompt2)
```

```
problem_desc = problem_desc_file.read()
print("Problem Description:\n", problem_desc)
```

Prompt 1.1 (Variables):
 Please formulate only the variables for this mathematical optimization problem.
 Prompt 1.2 (Objective):
 Please formulate only the objective function for this mathematical optimization problem.
 Prompt 1.3 (Constraints):
 Please formulate only the constraints for this mathematical optimization problem.
 Prompt 2:
 Please write a python pyomo code for this optimization problem.
 Use sample data where needed.
 Indicate where you use sample data.
 Problem Description:
 Your goal is to invest in several of 10 possible investment strategies in the most optimal way. The historic returns of

The costs for investing in a given investment is stored in a vector A, which has one value for each strategy in order.
 The values are: [80, 340, 410, 50, 180, 221, 15, 348, 191, 225]

You can only invest once into an investment.

Unfortunately due to other costs and inflation, your available budget at this time is uncertain. There are four possible
 The tolerable probability of exceeding the budget is 0.4.

Please formulate a mean-variance mathematical model for this optimization problem, considering the past performance of i

```
!pip install anthropic
```

 [Show hidden output](#)

```
# Importing Anthropic & Setting Headers
import anthropic
```


```
client = anthropic.Anthropic(
    # defaults to os.environ.get("ANTHROPIC_API_KEY")
    api_key=os.environ.get("ANTHROPIC_API_KEY"),
)
```

✓ 1. Prompt 1.1: Create Variables for Mathematical Model

```
message11 = client.messages.create(
    model="claude-3-opus-20240229",
    system=prompt11,
    max_tokens=4096,
    messages=[
        {"role": "user", "content": problem_desc}
    ]
)
```

```
response_p11 = message11.content[0].text
```

```
# Print response
print(response_p11)
```

 Let's define the variables for this mean-variance optimization problem:

Decision variables:

x_i : binary variable indicating whether to invest in strategy i ($x_i = 1$) or not ($x_i = 0$), for $i = 1, 2, \dots, 10$.

Parameters:

r_{ij} : historical return of strategy i in period j , for $i = 1, 2, \dots, 10$ and $j = 1, 2, \dots, n$, where n is the number of

A_i : cost of investing in strategy i , for $i = 1, 2, \dots, 10$.

B_k : available budget in scenario k , for $k = 1, 2, 3, 4$.

p_k : probability of scenario k occurring, for $k = 1, 2, 3, 4$.

α : tolerable probability of exceeding the budget ($\alpha = 0.4$).

r : risk parameter ($r = 2$).

Auxiliary variables:

μ_i : mean return of strategy i , calculated as $\mu_i = (1/n) * \sum_j r_{ij}$, for $i = 1, 2, \dots, 10$.

σ_{ij} : covariance between the returns of strategies i and j , calculated as $\sigma_{ij} = (1/(n-1)) * \sum_k (r_{ik} - \mu_i) * (r_{jk} - \mu_j)$

y_k : binary variable indicating whether the budget is exceeded in scenario k ($y_k = 1$) or not ($y_k = 0$), for $k = 1, 2, 3$


These are the variables needed to formulate the mean-variance optimization problem with uncertain budget constraints.

✓ 1. Prompt 1.2: Create Objective for Mathematical Model

```
message12 = client.messages.create(
    model="claude-3-opus-20240229",
    system=prompt12,
    max_tokens=4096,
    messages=[
        {"role": "user", "content": (problem_desc + response_p11)}
    ]
)
```

```
response_p12 = message12.content[0].text
```

```
# Print response
print(response_p12)
```

 Objective function:
Maximize: $\sum_i \mu_i * x_i - r * \sum_i \sum_j \sigma_{ij} * x_i * x_j$

Constraints:

1. Budget constraint for each scenario k :

$\sum_i A_i * x_i \leq B_k + M * y_k$, for $k = 1, 2, 3, 4$.

(M is a large constant, allowing the budget to be exceeded when $y_k = 1$)

2. Probability of exceeding the budget:

$\sum_k p_k * y_k \leq \alpha$

3. Binary constraints:
 $x_i \in \{0, 1\}$, for $i = 1, 2, \dots, 10$.
 $y_k \in \{0, 1\}$, for $k = 1, 2, 3, 4$.

The objective function maximizes the expected return ($\sum_i \mu_i * x_i$) while penalizing the risk, represented by the varia

The first set of constraints ensures that the total cost of the selected strategies does not exceed the available budget

The second constraint limits the probability of exceeding the budget to the tolerable level α .

Finally, the binary constraints ensure that the decision variables x_i and y_k can only take values of 0 or 1.

✓ 1. Prompt 1.3: Create Constraints for Mathematical Model

```
message13 = client.messages.create(
    model="claude-3-opus-20240229",
    system=prompt13,
    max_tokens=4096,
    messages=[
        {"role": "user", "content": (problem_desc + response_p11 + response_p12)}
    ]
)
```

```
response_p13 = message13.content[0].text
```

```
# Print response
print(response_p13)
```

🔄 Here are the constraints for the mean-variance optimization problem with uncertain budget:

- Budget constraint for each scenario k :
 $\sum_i A_{i,k} * x_i \leq B_k + M * y_k$, for $k = 1, 2, 3, 4$.
 M is a large constant, allowing the budget to be exceeded when $y_k = 1$.
- Probability of exceeding the budget:
 $0.55 * y_1 + 0.4 * y_2 + 0.04 * y_3 + 0.01 * y_4 \leq 0.4$
- Binary constraints:
 $x_i \in \{0, 1\}$, for $i = 1, 2, \dots, 10$.
 $y_k \in \{0, 1\}$, for $k = 1, 2, 3, 4$.
- Investment constraint:
 $\sum_i x_i \leq 1$, for $i = 1, 2, \dots, 10$.

The budget constraints ensure that the total cost of the selected strategies does not exceed the available budget in eac

The probability constraint limits the probability of exceeding the budget to the tolerable level of 0.4, considering the

The binary constraints ensure that the decision variables x_i and y_k can only take values of 0 or 1.

The investment constraint ensures that you can only invest once into an investment strategy.

✓ 2. Prompt 2: Write Code based on Mathematical Model

In case more than the component of each step was generated, use "last instance"/ "newest version" of the components.

Example: Prompt 1.1 (Variables): Model generates only variables Prompt 1.2 (Objective): Model generates objective and constraints Prompt 1.3

(Constraints): Model generates only constraints

Use Variables from step 1.1, use objective from 1.2 and use constraints from 1.3 (since constraints version 1.3 is more recent than constraints version 1.2).

This set up allows for potential self-correction of the model throughout the three prompts.

Correctness of each component is still generated in the respective step, so self-correction is independent of this.

```
# Extract objective related answer part from response two
response_p12_adjusted = ""
Objective function:
Maximize:  $\sum_i \mu_i * x_i - r * \sum_i \sum_j \sigma_{ij} * x_i * x_j$ 
```

The objective function maximizes the expected return ($\sum_i \mu_i * x_i$) while penalizing the risk, represented by the variance

```
message2 = client.messages.create(
    model="claude-3-opus-20240229",
    system=prompt2,
    max_tokens=4069,
    messages=[
        {"role": "user", "content": (response_p11 + response_p12_adjusted + response_p13)}
    ]
)

response_p2 = message2.content[0].text
```

```
# Print response
print(response_p2)
```

Here's a Python code using Pyomo to solve the mean-variance optimization problem with uncertain budget constraints:

```
```python
import pyomo.environ as pyo
import numpy as np

Sample data (replace with your actual data)
n = 10 # Number of historical periods
m = 10 # Number of strategies
scenarios = 4 # Number of budget scenarios

Generate sample returns (replace with your actual returns)
returns = np.random.rand(m, n)

Generate sample costs for each strategy (replace with your actual costs)
costs = np.random.randint(10, 50, m)

Sample budgets for each scenario (replace with your actual budgets)
budgets = [100, 120, 80, 90]

Sample probabilities for each scenario (replace with your actual probabilities)
probabilities = [0.55, 0.4, 0.04, 0.01]

Create the Pyomo model
model = pyo.ConcreteModel()

Define sets
model.strategies = pyo.RangeSet(1, m)
model.scenarios = pyo.RangeSet(1, scenarios)

Define decision variables
model.x = pyo.Var(model.strategies, domain=pyo.Binary)
model.y = pyo.Var(model.scenarios, domain=pyo.Binary)

Define parameters
model.returns = pyo.Param(model.strategies, initialize=lambda model, i: returns[i-1].mean())
model.costs = pyo.Param(model.strategies, initialize=lambda model, i: costs[i-1])
model.budgets = pyo.Param(model.scenarios, initialize=lambda model, k: budgets[k-1])
model.probabilities = pyo.Param(model.scenarios, initialize=lambda model, k: probabilities[k-1])

Calculate covariance matrix
covariance_matrix = np.cov(returns)

Define objective function
def objective_rule(model):
 return sum(model.returns[i] * model.x[i] for i in model.strategies) - \
 2 * sum(covariance_matrix[i-1, j-1] * model.x[i] * model.x[j] for i in model.strategies for j in model.st

model.objective = pyo.Objective(rule=objective_rule, sense=pyo.maximize)

Define budget constraints for each scenario
def budget_constraint_rule(model, k):
 return sum(model.costs[i] * model.x[i] for i in model.strategies) <= model.budgets[k] + 1e6 * model.y[k]

model.budget_constraint = pyo.Constraint(model.scenarios, rule=budget_constraint_rule)

Define probability of exceeding the budget constraint
```

## 4. Input Problem Data and Test Model Code

```
Installing pyomo nd solver
!pip install -q pyomo
!pip install pandas
!apt-get install -y -qq glpk-utils
!pip install glpk
```

 [Show hidden output](#)

```
import pyomo.environ as pyo
import numpy as np
import pandas as pd

Sample data (replace with your actual data)
scenarios = 4 # Number of budget scenarios

Generate sample returns (replace with your actual returns)
data = pd.read_csv("/content/drive/MyDrive/Thesis/ProblemData/IP/IP2/investments_data.csv", header=None, sep=';')
returns = data.to_numpy()
n, m = returns.shape

Generate sample costs for each strategy (replace with your actual costs)
costs = [80, 340, 410, 50, 180, 221, 15, 348, 191, 225]

Sample budgets for each scenario (replace with your actual budgets)
budgets = [100, 120, 80, 90]

Sample probabilities for each scenario (replace with your actual probabilities)
probabilities = [0.55, 0.4, 0.04, 0.01]

Create the Pyomo model
model = pyo.ConcreteModel()

Define sets
model.strategies = pyo.RangeSet(1, m)
model.scenarios = pyo.RangeSet(1, scenarios)

Define decision variables
model.x = pyo.Var(model.strategies, domain=pyo.Binary)
model.y = pyo.Var(model.scenarios, domain=pyo.Binary)

Define parameters
model.returns = pyo.Param(model.strategies, initialize=lambda model, i: returns[i-1].mean())
model.costs = pyo.Param(model.strategies, initialize=lambda model, i: costs[i-1])
model.budgets = pyo.Param(model.scenarios, initialize=lambda model, k: budgets[k-1])
model.probabilities = pyo.Param(model.scenarios, initialize=lambda model, k: probabilities[k-1])

Calculate covariance matrix
covariance_matrix = np.cov(returns)

Define objective function
def objective_rule(model):
 return sum(model.returns[i] * model.x[i] for i in model.strategies) - \
 2 * sum(covariance_matrix[i-1, j-1] * model.x[i] * model.x[j] for i in model.strategies for j in model.strategies)

model.objective = pyo.Objective(rule=objective_rule, sense=pyo.maximize)

Define budget constraints for each scenario
def budget_constraint_rule(model, k):
 return sum(model.costs[i] * model.x[i] for i in model.strategies) <= model.budgets[k] + 1e6 * model.y[k]

model.budget_constraint = pyo.Constraint(model.scenarios, rule=budget_constraint_rule)

Define probability of exceeding the budget constraint
def probability_constraint_rule(model):
 return sum(model.probabilities[k] * model.y[k] for k in model.scenarios) <= 0.4

model.probability_constraint = pyo.Constraint(rule=probability_constraint_rule)

Define investment constraint
def investment_constraint_rule(model):
 return sum(model.x[i] for i in model.strategies) <= 1

model.investment_constraint = pyo.Constraint(rule=investment_constraint_rule)

Solve the model
solver = pyo.SolverFactory('glpk')
results = solver.solve(model)

Print the results
print("Objective value:", pyo.value(model.objective))
print("Selected strategies:")
```

```
for i in model.strategies:
 if pyo.value(model.x[i]) > 0.5:
 print("Strategy", i)
```



```

ValueError Traceback (most recent call last)
<ipython-input-26-ed26b6c0b8b9> in <cell line: 69>()
 67 # Solve the model
 68 solver = pyo.SolverFactory('glpk')
--> 69 results = solver.solve(model)
 70
 71 # Print the results
```

9 frames

```
_____/usr/local/lib/python3.10/dist-packages/pyomo/repn/plugins/lp_writer.py in
write(self, model)
 376 repn = objective_visitor.walk_expression(obj.expr)
 377 if repn.nonlinear is not None:
--> 378 raise ValueError(
 379 f"Model objective ({obj.name}) contains nonlinear
terms that "
 380 "cannot be written to LP format"
```

**ValueError:** Model obiective (objective) contains nonlinear terms that cannot

## ✓ 5. Correct The Model Code to Test Mathematical Model (if applicable)

```
%%capture
import sys
import os

if 'google.colab' in sys.modules:
 !pip install idaes-pse --pre
 !idaes get-extensions --to ./bin
 os.environ['PATH'] += ':bin'

import pyomo.environ as pyo
import numpy as np
import pandas as pd

Sample data (replace with your actual data)
scenarios = 4 # Number of budget scenarios

Generate sample returns (replace with your actual returns)
data = pd.read_csv("/content/drive/MyDrive/Thesis/ProblemData/IP/IP2/investments_data.csv", header=None, sep=';')
returns = data.to_numpy()
n, m = returns.shape

Generate sample costs for each strategy (replace with your actual costs)
costs = [80, 340, 410, 50, 180, 221, 15, 348, 191, 225]

Sample budgets for each scenario (replace with your actual budgets)
budgets = [100, 120, 80, 90]

Sample probabilities for each scenario (replace with your actual probabilities)
probabilities = [0.55, 0.4, 0.04, 0.01]

Create the Pyomo model
model = pyo.ConcreteModel()

Define sets
model.strategies = pyo.RangeSet(1, m)
model.scenarios = pyo.RangeSet(1, scenarios)

Define decision variables
model.x = pyo.Var(model.strategies, domain=pyo.Binary)
model.y = pyo.Var(model.scenarios, domain=pyo.Binary)

Define parameters
model.returns = pyo.Param(model.strategies, initialize=lambda model, i: returns[i-1].mean())
model.costs = pyo.Param(model.strategies, initialize=lambda model, i: costs[i-1])
model.budgets = pyo.Param(model.scenarios, initialize=lambda model, k: budgets[k-1])
model.probabilities = pyo.Param(model.scenarios, initialize=lambda model, k: probabilities[k-1])

Calculate covariance matrix
covariance_matrix = np.cov(returns)

Define objective function
def objective_rule(model):
 return sum(model.returns[i] * model.x[i] for i in model.strategies) - \
 2 * sum(covariance_matrix[i-1, j-1] * model.x[i] * model.x[j] for i in model.strategies for j in model.strategies)
```

```

model.objective = pyo.Objective(rule=objective_rule, sense=pyo.maximize)

Define budget constraints for each scenario
def budget_constraint_rule(model, k):
 return sum(model.costs[i] * model.x[i] for i in model.strategies) <= model.budgets[k] + 1e6 * model.y[k]

model.budget_constraint = pyo.Constraint(model.scenarios, rule=budget_constraint_rule)

Define probability of exceeding the budget constraint
def probability_constraint_rule(model):
 return sum(model.probabilities[k] * model.y[k] for k in model.scenarios) <= 0.4

model.probability_constraint = pyo.Constraint(rule=probability_constraint_rule)


Define investment constraint
def investment_constraint_rule(model):
 return sum(model.x[i] for i in model.strategies) <= 1

model.investment_constraint = pyo.Constraint(rule=investment_constraint_rule)

Solve the model
solver = pyo.SolverFactory('couenne')
results = solver.solve(model)

Print the results
print("Objective value:", pyo.value(model.objective))
print("Selected strategies:")
for i in model.strategies:
 if pyo.value(model.x[i]) > 0.5:
 print("Strategy", i)

```

 Objective value: 0.0  
 Selected strategies: