

# Supplementary Material for: A Survey on Data Augmentation for Text Classification

MARKUS BAYER, MARC-ANDRÉ KAUFHOLD, and CHRISTIAN REUTER, PEASEC,  
Technical University of Darmstadt

## 3 TEXTUAL DATA AUGMENTATION METHODS

### 3.1 Data Space

#### 3.1.2 Word Level.

##### 3.1.2.2 Synonym Replacement.

Table 2. Overview of Different Approaches of the Synonym Replacement Method

	Synonym Database	Replacement Method	Synonym Selection	Model Base	Dataset	Improvements
[57]	WordNet	Headword replacement	Not stated	Logistic Regression	TempEval Reuters (12) Wikipedia (1)	-1 (F1) -0.6 -0.1
[61], [63]	mytheas (LibreOffice) WordNet-based	Randomly chosen number of words based on geometric distribution.	Randomly based on geometric distribution.	Character CNN	AG News DBP. Yelp P. Yelp F. Yahoo A. Amazon F. Amazon P.	[61]/[63] (Acc.) -0.38 / -0.57 +0.05 / +0.13 -0.03/ +0.36 +0.22/0.65 +0.1/0.1 -0.17/-0.17
[39]	WordNet	Substitutable words are nouns, verbs, adjectives, or adverbs that are not part of a named entity. Each word is replaced with a certain probability.	The remaining probability of substitution is shared among the synonyms based on a language model score.	CNN	MR CR Subj SST MR/CR CR/MR	+0.8 (Acc.) +1.2 +0.5 +0.1 0.9 0.3
[9]	WordNet	Only adverbs and adjectives, sometimes nouns, more rarely verbs.	Most similar companion information of the synonym with the context of the chosen word.	XGBoost MLP (2 hidden layer)	IMDB	+0.5 (Acc.) +4.92
[59]	WordNet	No pronouns, conjunctions, prepositions, and articles for replacement. Choosing uniform randomly.	Uniform random	CNN with word embedding	Toxic Comment Classification	-0.09/-0.21 (AUC)
[60]	HIT IR-Lab Tongyici Cilin (Extended) (Chinese)	No time words, prepositions, and mimetic words. Chi-square statistics method.	Chi-square statistics method	Character CNN-SVM	Hotel R. Laptop R. Book R.	~+1 (Acc.) ~+1 ~+0.25

(Continued)

Table 2. Continued

	Synonym Database	Replacement Method	Synonym Selection	Model Base	Dataset	Improvements
[62]	WordNet	Verbs, nouns, and their combination. Geometric distribution.	Geometric distribution	DNN	AG News Sentiment Hate Speech	~+0.4 (Acc.) ~+0 ~-0.8
[64]	WordNet & Thesaurus.com	For Minibatch: Augmentation with probability. Replacement of those words that belong to certain POS-tags. One replacement of a word per sentence that maximizes loss.	Synonym that maximizes the loss.	Kim CNN	TREC	+1.2 (Acc.)
[2]	WordNet	No stop words. Choosing n random words to be replaced (SR) or from which the synonyms are inserted at a random position (RI)	Uniform random	CNN	Classification tasks (500) (2000) (5000) (full)	SR / RI (Acc.) ~+1.9/~+2.0 ~+1.2/~+0.9 ~+0.7/~+0.6 ~+1.0/~+0.9
[1]	WordNet	Replacement of a word based on a certain probability.	Temperature hyperparameter learned while training.	CNN	SST-5 SST-2 Subj MPQA RT TREC	-0.6 (Acc.) +0.5 +0 +0.2 +0.1 -0.4
[40]	WordNet	Replacement of a word based on a certain probability.	Temperature hyperparameter learned while training.	TextRCNN	ICS NEWS	-0.26 (Macro F1) +1.63
[49]	Not stated	Filtering words according to their POS-tag. Selecting a fixed or variable number of words.	Specific or variable number of synonyms.	LSTM-CNN	Tan NLPCC	Results only in combination with other methods
[65]	WordNet	Not stated	Not stated	BERT	SST-5 (40) IMDB (40) TREC (40)	-0.87 (Acc.) -0.87 +0.01
[66]	WordNet	No stop words. 10% of documents randomly selected.	Not stated	M-BERT	CodiEsp-D CodiEsp-P	+0.6 (F1) -0.7 (F1)
[37]	WordNet	Keywords replaced are ordered by their RAKE score (e.g., the probability of being a keyword).	Randomly selected. Replacement only with same POS-tag.	No model (intrinsic evaluation with different metrics)	Yelp-LR (small subset of Yelp Reviews)	+0.015 (SBLEU) -0.018 (UTR) -0.02 (TTR) -0.016 (RWords) 0 (SLOR) -0.007 (BPRO) +0.001 (SStd) 0 (SDiff)
[46]	WordNet	No stop words. Uniform random replacement until 20% of the words in a sentence are changed.	Uniform random	CNN	Yelp P.	Only against other data augmentation methods

### 3.1.2.3 Embedding Replacement.

Table 3. Overview of Different Approaches of the Embedding Replacement Method

	Replacement Selection	Embedding Selection	Model Base	Dataset	Embedding Model	Improvements
[70]	Not stated	K-nearest-neighbor and cosine similarity	Logistic regression	Petpeeve dataset	UrbanDictionary W2V Twitter W2V GoogleNews W2V	+0.3 (F1) +1.7 +2.4
[62]	Random	Random with probability proportional to cosine similarity.	DNN	AG News Sentiment Hate Speech	Wikipedia W2V Wikipedia W2V GloVe Twitter	~0 (Acc.) ~+0.5 ~-0.3
[48]	Every word	Cosine similarity threshold + POS-tag matching	CNN+LSTM/GRU	HON RSN-1 RSN-2	Word2Vec Hate Speech FastText Wikipedia GoogleNews W2V GloVe Common Crawl GloVe Common Crawl GloVe Common Crawl	-22.7 (Macro F1) +1.0 -3.3 +0.3 -0.2 0
[49]	1. Method: Filtering words according to their POS-tag. Selecting a fixed or variable number of words. 2. Method: Replacing adverbial phrases (Chinese related).	Own similarity measure and specific or variable number of replacements	LSTM-CNN	Tan	W2V self-pretrained	Results only in combination with other word level augmentation methods
[39]	Substitutable words are nouns, verbs, adjectives, or adverbs that are not part of a named entity. Each word is replaced with a certain probability.	Embeddings are found with the counter-fitting method. Each candidate is replaced with a probability. The remaining probability of substitution is shared among the embeddings based on a language model score.	CNN	MR CR Subj SST MR/CR CR/MR	GoogleNews W2V	-0.6/-4.2 (Acc) +0.1/-3.7 +0.2/-1.4 -0.4/-4.2 +1.9/+0.4 +0.1/-3.0
[41]	Not stated	Cosine similarity	Random Forest, Naïve Bayes, SVM	Vietnamese comments	W2V Vietnamese	Results only in combination
[20]	Random sampling with probabilities proportional to the neighbors each word has within the counter-fitted embedding space + exclusion of common articles and prepositions.	1. K-nearest-neighbors with Euclidean distance + counter-fitting method. 2. Google LM to filter out words. 3. Selection of the word that will maximize the target label prediction probability.	LSTM	IMDB	GloVe	Adversarial training: No improvements but safer model
[71]	Only for multi-piece words. Random probability for replacement.	Random embedding of the k-nearest-neighbor	Small transformer model	Various GLUE tasks	GloVe	No augmentation baseline comparisons
[72]	No stop words or symbolic and numerical data	Cosine similarity threshold of 0.97	Manhattan LSTM model	Thai text similarity task	Thai2fit (Thai language)	+1.71

3.1.2.4 Replacement by Language Models.

Table 4. Evaluation Results of the State of the Art Language Substitution Method c-BERT

Publication	Method	Dataset	Improvements (Accuracy)
[74]	c-BERT	SST-5	+0.8 (CNN)/+1.3 (RNN)
		SST-2	+0.2 (CNN)/+0.5 (RNN)
		Subj	+0.5 (CNN)/+0.4 (RNN)
		MPQA	+0.5 (CNN)/+0.7 (RNN)
		RT	+0.8 (CNN)/+0.6 (RNN)
		TREC	+0.8 (CNN)/+0.2 (RNN)
[76]	c-BERT with consistency training	MLNI-m	+0.4 (RoBERTa-Base)
[42]	c-BERT	ATIS	-1.9 (BERT)/-0.8 (SVM)/-5.8 (LSTM)
		TREC	+1.1 (BERT)/+1.1 (SVM)/+6.5 (LSTM)
		WVA	+0.2 (BERT)/0.5 (SVM)/+2.4 (LSTM)
[65]	c-BERT integrated in reinforcement learning scheme	SST-5 (42)	+1.17 (BERT)/+2.19 (normal c-BERT)
		IMDB (45)	+1.97 (BERT)/+1.97 (normal c-BERT)
		TREC (45)	+0.73 (BERT)/+0.87 (normal c-BERT)
[71]	c-BERT and embedding substitution for multiple-pieces words	MNLI-m	+2.3 (TinyBERT)
		MNLI-mm	+1.9 (TinyBERT)
		MRPC	+3.4 (TinyBERT)
		CoLA	+21.0 (TinyBERT)

### 3.1.4 Document Level.

#### 3.1.4.1 Round-trip Translation.

Table 5. Overview of the Round-trip Translation Approaches

	Translation Model	Languages	Filtering	Model	Dataset	Improvements
[92]	Google's NMT [96]	en → fr → en	No filtering	Convolution and self-attention model	SQuAD	+1.5 (EM)/+1.1 (F1)
[9]	Google Translate API	Not stated	Excluding identical instances. Similarity threshold based on lengths.	XGBoost MLP 2 hidden layer	IMDB	+0 (Acc.) +5.8
[69]	Google Translate API	en → fr, es, de, hi → en	No filtering	NBSVM CNN LSTM BiLSTM CNN-LSTM LSTM-CNN CNN-BiLSTM BiLSTM-CNN	Aggression Detection	+0.19 (Macro F1) +5.31 +7.39 +5.6 +5.94 +19.45 +14.33 +6.87
[94]	Google Translate	Randomly selected	No filtering	Fusion CNN	TREC Incident Streams track	~-1.2 (F1)
[62]	Google Translate API & Amazon translate	en → fr, de → en	"We ensured that the [...] texts carry the same meaning as the source text"	DNN	AG News Hate Speech	~+0.33 (Acc.) ~-2.3
[50]	WMT'14 English-French translation model	en → fr → en	No filtering	Randomly initialized transformer	Yelp-5	+1.65 (Acc.)
[76]	WMT19 and released in FairSeq	en → de → en	No filtering	RoBERTa	MLNI-m	+0.9 (Acc.)
[97]**	Translation models from Britz et al. [98]	en → de, zh → en	No filtering	BERT	MNLI QNLI QQP RTE SST-2 MRPC CoLA STS-B	+0 (Acc.) +0.2 (Acc.) +0.4 (Acc.) +3.6 (Acc.) +0.7 (Acc.) +0 (F1) +2.3 (Mcc) +0.6 (Corr.)
[99]*	Not stated	Not stated	No filtering	Transformer base with consistency training	MNLI QNLI QQP RTE SST-2 MRPC CoLA STS-B	+0.9 (Acc.) +0.6 (Acc.) -0.2 (Acc.) +5.1 (Acc.) +0.7 (Acc.) +2.6 (F1) +1.4 (Mcc) +0.4 (Corr.)
[100]	MarianMT	en → fr, de, es → en Chained: en → es → fr → en	Word sense disambiguation: Retaining of those in which the target word occurs exactly once (in both original and augmented instance).	MT-DNN	SemEval-2013 + SemEval-2015 + Senseval-2 + Senseval-3	No baseline comparisons

\*Trained with consistency training.

\*\*Trained with contrastive learning.

### 3.1.4.2 Generative Methods.

Table 6. Overview of Text Generation Methods

Publication	Method	Model	Dataset	Improvements
[40]	VAE CVAE + prior sampling CVAE + posterior sampling	Ensemble of BiLSTM, TextCNN, TextRCNN, and FastText with XGBoost as top-level classifier	ICS (Zh)	+0.04 (F1)
			News Category Dataset (EN)	+2.02
			ICS (Zh)	-0.13
			News Category Dataset (EN)	+1.55
			ICS (Zh)	-0.06
[101]	VAE CVAE + prior sampling CVAE + posterior sampling	BiLSTM	News Category Dataset (EN)	+1.88
			Movie	+4.0 (Macro F1)
			Movie + Live Entertainment	-0.5
			Movie	+5.9
			Movie + Live Entertainment	+1.7
[117]	CVAE	BERT	Movie	+5.6
			Movie + Live Entertainment	+0.6
			SNIPS (few shot)	+8.00
			SNIPS	+0.06 (Acc.)
			FBDialog (few shot)	+7.42
[103]	Transformer-based sentence editor	CNN CNN CNN CNN LSTM LSTM	FBDialog	+0.0
			Subj (20%)	+1.71 (Acc.)
			Subj (100%)	+1.62
			SST-2 (20%)	+0.87
			SST-2 (100%)	-0.84
[48]	RNN LM with random start word priming	CNN+LSTM + GloVe++	Amazon Reviews (1%)	+1.12
			Amazon Reviews (4%)	+0.41
			HON	-1.8 (Micro-F1)
			RSN-1	+8.2
			RSN-2	-7.4
[66]	CNN-LSTM LM with 30% of a given sentence for priming	CNN-LSTM	CodiEsp-P	+3.1 (F1)
[49]	seqGAN	LSTM + pretrained embeddings CNN + pretrained embeddings LSCNN + pretrained embeddings	Tan's task	+1.06 (F1)
				+0.9
				+0.8
[105]	CS-GAN (GAN, RNN and reinforcement learning)	CNN	Amazon-5000	+1.6 (Acc.)
			Amazon-30000	-0.21
			Emotion-15000	+0.77
			NEWS-15000	+2.25
[106]	GPT-2 for rarer instances without filtering	Logistic regression/biLSTM/Bi-attentive classification + ELMo + GloVe	Alerting Information Feed Prioritization	No comparative results
[42]	CVAE	BERT	ATIS (5)	+7.3 (Acc.)
			TREC (5)	+0.8
			WVA (5)	-1.8
[42]	LAMBADA – GPT-2 generation and classifier filtering	BERT	ATIS (5)	+22.4 (Acc.)
			ATIS (20)	~0
			ATIS (50)	~+2.0
			ATIS (100)	~+0.5
			TREC (5)	+4.0
			WVA (5)	+1.4
[107]	PREDATOR – DistilGPT2 generation and classifier filtering	BERT CNN BERT	AG-NEWS	+0.61 (Acc.)
			CyberTrolls	+0.45
			SST-2	+1.63

(Continued)

Table 6. Continued

Publication	Method	Model	Dataset	Improvements
[44]	GPT-2 with conditional fine-tuning, special prompting, and document embedding filtering	ULMFit	SST-2 (100)	+15.53 (Acc.)
			SST-2 (700)	-0.19 (Acc.)
			Layoff	+4.84 (F1)
			Management Change	+3.42 (F1)
			Mergers & Acquisitions	+1.42 (F1)
			Flood	+0.25 (F1)
			Wildfire	+0.44 (F1)
			Boston Bombings	+2.44 (F1)
			Bohol Earthquake	+2.05 (F1)
			West Texas Explosions	+3.81 (F1)
			Dublin	-2.54 (F1)
			New York	+0.44 (F1)
[108]	GPT-2 with conditional fine-tuning, special prompting, and classifier filtering	RoBERTa	MediaEval	+0.55 (micro-F1)
		FlauBERT	CLS-FR	+0.57
[109]	GPT-2 with a reinforcement learning component for class conditional generation.	XLNet	Offense Detection (20%)	+1.3 (F1)
			Offense Detection (40%)	+4.3
			Sentiment Analysis (20%)	+1.2
			Sentiment Analysis (40%)	+1.4
			Irony Classification (20%)	+1.0
			Irony Classification (40%)	+2.3
[112]	GPT-3 with prompt-based generation and pseudo-labeling	BERT (base)	COLA (0.1%, 0.3%, 1.0%)	+7.9, 3.2, -2.4
		BERT (large)	TREC6 (0.1%, 0.3%, 1.0%)	+15.6, 17.1, -6.5
			CR (0.1%, 0.3%, 1.0%)	+11.0, 17.3, 8.9
			SUBJ (0.1%, 0.3%, 1.0%)	+1.3, -1.8, -1.2
			MPQA (0.1%, 0.3%, 1.0%)	+12.9, 13.4, 3.8
			RT20 (0.1%, 0.3%, 1.0%)	+6.2, 13.6, 17.5
			SST-2 (0.1%, 0.3%, 1%, full)	+20.9, 19.3, 5.7, 2.9
			SST-2 (0.1%, 0.3%, 1.0%)	+23.7, 14.6, 3.0

### 3.2 Feature Space

#### 3.2.2 Interpolation Methods.

##### 3.2.2.2 Mixup Interpolation.

Table 8. Overview of Different Approaches of the Replacement Method “Mixup Interpolation”

Method	Technique for textual application	Model	Datasets	Improvements
mixup by Marivate and Sefara [62]	Not stated	DNN	AG News Sentiment 140 Hate Speech	+0.2 (Acc.) +0.4 +0
[117]	Interpolation of the BERT CLS output	BERT-base-english-uncased	SNIPS (few shot) SNIPS FBDialog (few shot) FBDialog	+8.36 (Acc.) +0.0 +7.92 +0.08
[76]	Interpolation of the embedding matrices	RoBERTa-base	MNLI-m	+0.6 (Acc.)
wordMixup by Guo et al. [137]	Interpolation of zero-padded word embeddings	CNN	Trec SST-1 SST-2 Subj MR	+1.6 (Acc.) +1.9 +0.2 +0.3 +1.5
senMixup by Guo et al. [137]	Interpolation on the final hidden layer	CNN	Trec SST-1 SST-2 Subj MR	+1.2 (Acc.) +2.3 +0.3 +0.5 +0.8
Nonlinear Mixup by Guo [138]	Nonlinear interpolation of padded word embeddings	CNN	Trec SST-1 SST-2 Subj MR	+2.6 (Acc.) +3.0 +2.3 <b>-0.5</b> +3.6
Mixup-Transformer by Sun et al. [136]	Interpolation after last layer of the transformer	BERT-large	CoLA SST-2 MRPC STS-B QQP MNLI-mm QNLI RTE	+2.68 (Corr.) +0.81 (Acc.) +1.72 (Acc.) +0.89 (Corr.) +0.42 (Acc.) <b>-0.01</b> (Acc.) +0.13 (Acc.) +0.37(Acc.)
TMix by Chen et al. [95]	Interpolation of the m-th BERT layer (7, 9, and 12 randomly chosen per batch)	BERT-base-uncased + average pooling + two-layer MLP	AG News (10) AG News (2500) DBPedia (10) DBPedia (2500) Yahoo! (10) Yahoo! (2500) IMDB (10) IMDB (2500)	+4.6 (Acc.) +0.2 +1.6 +0.0 +2.4 +0.3 +1.8 +0.5
TMix evaluated by [112]	Interpolation of the m-th BERT layer (7, 9, and 12 randomly chosen per batch)	BERT-base	SST-2 (0.1, 0.3, 1.0%) COLA (0.1, 0.3, 1.0%) TREC6 (0.1, 0.3, 1.0%) CR (0.1, 0.3, 1.0%) SUBJ (0.1, 0.3, 1.0%) MPQA (0.1, 0.3, 1.0%) RT20 (0.1, 0.3, 1.0%)	<b>-0.2, -1.5, -2.1</b> +0.8, 2.4, <b>-0.7</b> <b>-0.2, -1.4</b> , +2.4 <b>-0.1, -0.5, -3.3</b> <b>-0.5, +0.4, -0.1</b> +0.2, 2.9, 0.0 +2.3, 0.6, <b>-1.9</b>

(Continued)



Table 8. Continued

Method	Technique for textual application	Model	Datasets	Improvements
Intra-LADA [140]	Interpolation of an instance with a randomly reordered version of itself	BERT-base-multilingual-cased + linear layer	CoNLL (5%)	+0.24 (F1)
			CoNLL (100%)	+0.03 (*)
			GermEval (5%)	+0.29
			GermEval (100%)	+0.04 (*)
Inter-LADA [140]	Interpolation of the nearest neighbors and sometimes randomly selected instances	BERT-base-multilingual-cased + linear layer	CoNLL (5%)	+1.32 (F1)
			CoNLL (100%)	+0.64
			GermEval (5%)	+0.49
			GermEval (100%)	+0.33
Intra-Inter-LADA [140]	Combination of Intra- and Inter-LADA	BERT-base-multilingual-cased + linear layer	CoNLL (5%)	+1.57 (F1)
			CoNLL (30%)	+0.59
			GermEval (5%)	+0.53
			GermEval (30%)	+0.78

\*Included in the pretraining.

### 3.3 Training Strategies

Table 9. Overview of the Contrastive Learning Works Using Data Augmentation

Publication	Method	Model	Dataset	Improvement
CERT [97]	Continued contrastive self-supervised learning (MLM) with round-trip translation.	Continued BERT training compared to BERT	MNLI	+0 (Acc.)
			QNLI	+0.2 (Acc.)
			QQP	+0.4 (Acc.)
			RTE	+3.6 (Acc.)
			SST-2	+0.7 (Acc.)
			MRPC	+0 (F1)
			CoLA	+2.3 (Mcc)
			STS-B	+0.6 (Corr.)
CODA [76]	Supervised contrastive learning with adversarial training and round-trip translation.	RoBERTa-base finetuning compared to RoBERTa-base	MNLI-m	+0.5 (Acc.)
			QNLI	+0.8
			SST-2	+0.5
			RTE	+3.3
			MRPC	+1.5
CLEAR [47]	Contrastive self-supervised learning (MLM) from scratch with word deletion, span deletion, random reordering, synonym substitution (also in combination). Span deletion + random reordering is shown here.	Transformer architecture by Vaswani et al. [160] trained from scratch compared to RoBERTa-base	MNLI	-0.5 (Acc.)
			QNLI	-0.3 (Acc.)
			QQP	+1.8 (Acc.)
			RTE	+6.5 (Acc.)
			SST-2	+0.1 (Acc.)
			MRPC	+2.8 (F1)
			CoLA	+8.2 (Mcc)
			STS-B	+0.4 (Corr.)
ConSERT [144]	Continued contrastive self-supervised learning (MLM) with adversarial training, token shuffling, cutoff, dropout.	Continued BERT-large training compared to SBERT-large-NLI	STS12	+0.99 (S. Corr.)
			STS13	+3.9
			STS14	+2.83
			STS15	+2.85
			STS16	+2.5
			STsb	+2.31
			SICK-R	+4.89
C <sup>2</sup> L [51]	Supervised contrastive learning with counterfactual augmentation.	BERT-base finetuning compared to BERT-base	CF-IMDb	+0.7 (Acc.)
			CF-IMDb Revised	+3.3
			CF-NLI	-1.2
			CF-NLI RP	+2.2
			CF-NLI RH	+1.3
			CF-NLI RP & RH	+1.8

## REFERENCES

- [1] S. Kobayashi. 2018. Contextual augmentation: Data augmentation bywords with paradigmatic relations. In *Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, vol. 2. 452–457. DOI : [10.18653/v1/n18-2072](https://doi.org/10.18653/v1/n18-2072)
- [2] J. Wei and K. Zou. 2020. EDA: Easy data augmentation techniques for boosting performance on text classification tasks. In *Conference on Empirical Methods in Natural Language Processing and 9th International Joint Conference on Natural Language Processing*. 6382–6388. DOI : [10.18653/v1/d19-1670](https://doi.org/10.18653/v1/d19-1670)
- [3] K. Kafle, M. Yousefhussien, and C. Kanan. 2017. Data augmentation for visual question answering. In *INLG'17*. 198–202. DOI : [10.18653/v1/w17-3529](https://doi.org/10.18653/v1/w17-3529)
- [4] S. Longpre, Y. Wang, and C. DuBois. 2020. How Effective is task-agnostic data augmentation for pretrained transformers? In *EMNLP'20*. 4401–4411. DOI : [10.18653/v1/2020.findings-emnlp.394](https://doi.org/10.18653/v1/2020.findings-emnlp.394)
- [5] C. Shorten and T. M. Khoshgoftaar. 2019. A survey on image data augmentation for deep learning. *J. Big Data* 6, 1, (2019). DOI : [10.1186/s40537-019-0197-0](https://doi.org/10.1186/s40537-019-0197-0)
- [6] Q. Wen et al. 2020. Time series data augmentation for deep learning: A survey. 2020. arXiv:2002.12478. Retrieved from <http://arxiv.org/abs/2002.12478>.
- [7] L. Taylor and G. Nitschke. 2019. Improving deep learning with generic data augmentation. In *SSCI'18*. 1542–1547. DOI : [10.1109/SSCI.2018.8628742](https://doi.org/10.1109/SSCI.2018.8628742)
- [8] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. 1998. Gradient-based learning applied to document recognition. *Proc. IEEE* 86, 11 (1998), 2278–2323. DOI : [10.1109/5.726791](https://doi.org/10.1109/5.726791)
- [9] C. Coulombe. 2018. Text data augmentation made simple by leveraging NLP cloud APIs. <http://arxiv.org/abs/1812.04718>.
- [10] R. Müller, S. Kornblith, and G. Hinton. 2019. When does label smoothing help? In *Advances in Neural Information Processing Systems* 32.
- [11] M. Banko and E. Brill. 2001. Scaling to very very large corpora for natural language disambiguation. In *ACL'01*. 26–33. DOI : [10.3115/1073012.1073017](https://doi.org/10.3115/1073012.1073017)
- [12] L. Palen and K. M. Anderson. 2016. Crisis informatics-new data for extraordinary times: Focus on behaviors, not on fetishizing social media tools. *Science* (80-) 353, 6296 (2016), 224–225. DOI : [10.1126/science.aag2579](https://doi.org/10.1126/science.aag2579)
- [13] M. Bayer, M.-A. Kaufhold, and C. Reuter. 2021. Information overload in crisis management: Bilingual evaluation of embedding models for clustering social media posts in emergencies. *ECIS'21*.
- [14] M. A. Kaufhold, M. Bayer, and C. Reuter. 2020. Rapid relevance classification of social media posts in disasters and emergencies: A system and evaluation featuring active, incremental and online learning. *Inf. Process. Manage.* 57, 1 (2020). DOI : [10.1016/j.ipm.2019.102132](https://doi.org/10.1016/j.ipm.2019.102132)
- [15] M.-A. Kaufhold, A. S. Basyurt, K. Eyilmez, M. Stöttinger, and C. Reuter. 2022. Cyber threat observatory: Design and evaluation of an interactive dashboard for computer emergency response teams. In *ECIS'22*. 6–18.
- [16] M.-A. Kaufhold et al. 2021. CYWARN: Strategy and technology development for cross-platform cyber situational awareness and actor-specific cyber threat communication. In *Workshop of Mensch und Computer '21*. 1–9.
- [17] S. Minaee, N. Kalchbrenner, E. Cambria, N. Nikzad, M. Chenaghlu, and J. Gao. 2021. Deep learning-based text classification. *ACM Comput. Surv.* 54, 3 (April 2021). DOI : [10.1145/3439726](https://doi.org/10.1145/3439726)
- [18] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov. 2014. Dropout: A simple way to prevent neural networks from overfitting. *J. Mach. Learn. Res.* 15 (2014), 1929–1958.
- [19] S. Geman, E. Bienenstock, and R. Doursat. 1992. Neural networks and the bias/variance dilemma. *Neural Comput.* 4, 1 (1992), 1–58. DOI : [10.1162/neco.1992.4.1.1](https://doi.org/10.1162/neco.1992.4.1.1)
- [20] A. Hernández-García and P. König. 2018. Data augmentation instead of explicit regularization. arXiv:1806.03852. Retrieved from <http://arxiv.org/abs/1806.03852>.
- [21] J. Ebrahimi, A. Rao, D. Lowd, and D. Dou. 2018. Hotflip: White-box adversarial examples for text classification. In *ACL'18* 2 (2018), 31–36. DOI : [10.18653/v1/p18-2006](https://doi.org/10.18653/v1/p18-2006)
- [22] M. Alzantot, Y. Sharma, A. Elgohary, B. J. Ho, M. B. Srivastava, and K. W. Chang. 2018. Generating natural language adversarial examples. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP'18)*. 2890–2896. DOI : [10.18653/v1/d18-1316](https://doi.org/10.18653/v1/d18-1316)
- [23] S. C. Wong, A. Gatt, V. Stamatescu, and M. D. McDonnell. 2016. Understanding data augmentation for classification: When to warp? In *DICTA'16*. DOI : [10.1109/DICTA.2016.7797091](https://doi.org/10.1109/DICTA.2016.7797091)
- [24] P. Y. Simard, D. Steinkraus, and J. C. Platt. 2003. Best practices for convolutional neural networks applied to visual document analysis. In *ICDAR'03*, 958–963. DOI : [10.1109/ICDAR.2003.1227801](https://doi.org/10.1109/ICDAR.2003.1227801)
- [25] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel. 2017. Domain randomization for transferring deep neural networks from simulation to the real world. In *IEEE IROS'17*. 23–30. DOI : [10.1109/IROS.2017.8202133](https://doi.org/10.1109/IROS.2017.8202133)
- [26] H. Inoue. 2018. Data augmentation by pairing samples for images classification. arXiv:1801.02323. Retrieved from <http://arxiv.org/abs/1801.02929>.

- [27] Z. Zhong, L. Zheng, G. Kang, S. Li, and Y. Yang. 2020. Random erasing data augmentation. *AAAI'20*. 13001–13008. DOI : [10.1609/aaai.v34i07.7000](https://doi.org/10.1609/aaai.v34i07.7000)
- [28] M. Frid-Adar, E. Klang, M. Amitai, J. Goldberger, and H. Greenspan. 2018. Synthetic data augmentation using GAN for improved liver lesion classification. In *Proceedings of the International Symposium on Biomedical Imaging*. 289–293.
- [29] X. Zhu, Y. Liu, J. Li, T. Wan, and Z. Qin. 2018. Emotion classification with data augmentation using generative adversarial networks. In *Lecture Notes in Computer Science*. 349–360. DOI : [10.1007/978-3-319-93040-4\\_28](https://doi.org/10.1007/978-3-319-93040-4_28)
- [30] N. Carlini et al. 2020. Extracting training data from large language models. arXiv:2012.07805. Retrieved from <http://arxiv.org/abs/2012.07805>.
- [31] X. Cui, V. Goel, and B. Kingsbury. 2014. Data augmentation for deep neural network acoustic modeling. In *ICASSP'14*. 5582–5586. DOI : [10.1109/ICASSP.2014.6854671](https://doi.org/10.1109/ICASSP.2014.6854671)
- [32] N. Jaitly and G. E. Hinton. 2013. Vocal tract length perturbation (VTLP) improves speech recognition. In *Proceedings of the 30th International Conference on Machine Learning* 90, 42–51.
- [33] A. Ragni, K. M. Knill, S. P. Rath, and M. J. F. Gales. 2014. Data augmentation for low resource languages. In *INTERSPEECH'14*. 810–814.
- [34] A. Hannun et al. 2014. Deep speech: Scaling up end-to-end speech recognition. arXiv:1412.5567. Retrieved from <http://arxiv.org/abs/1412.5567>.
- [35] Z. Xie et al. 2017. Data noising as smoothing in neural network language models. In *ICLR'17*.
- [36] T. Ko, V. Peddinti, D. Povey, and S. Khudanpur. 2015. Audio augmentation for speech recognition. In *INTERSPEECH'15*. 3586–3589.
- [37] S. Feng et al. 2021. A survey of data augmentation approaches for NLP. In *ACL'21*. 968–988. DOI : [10.18653/v1/2021.findings-acl.84](https://doi.org/10.18653/v1/2021.findings-acl.84)
- [38] Y. Belinkov and Y. Bisk. 2018. Synthetic and natural noise both break neural machine translation. In *ICLR'18*.
- [39] S. Y. Feng, V. Gangal, D. Kang, T. Mitamura, and E. Hovy. 2020. GenAug: data augmentation for finetuning text generators. In *Deep Learning Inside Out (DeeLIO): The First Workshop on Knowledge Extraction and Integration for Deep Learning Architectures*. 29–42. DOI : [10.18653/v1/2020.deelio-1.4](https://doi.org/10.18653/v1/2020.deelio-1.4)
- [40] T. Miyato, A. M. Dai, and I. Goodfellow. 2017. Adversarial training methods for semi-supervised text classification. In *ICLR'17*.
- [41] Y. Li, T. Cohn, and T. Baldwin. 2017. Robust training under linguistic adversity. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics*, vol. 2. 21–27. DOI : [10.18653/v1/e17-2004](https://doi.org/10.18653/v1/e17-2004)
- [42] S. Qiu et al. 2020. EasyAug: An automatic textual data augmentation platform for classification tasks. In *Companion of the World Wide Web Conference*. 249–252. DOI : [10.1145/3366424.3383552](https://doi.org/10.1145/3366424.3383552)
- [43] T. H. Huong and V. T. Hoang. 2020. A data augmentation technique based on text for Vietnamese sentiment analysis. In *ACM International Conference Proceeding Series*. 1–5. DOI : [10.1145/3406601.3406618](https://doi.org/10.1145/3406601.3406618)
- [44] A. A. Tavor et al. 2020. Do not have enough data? Deep learning to the rescue!. In *Proceedings of the 34th AAAI Conf. Artif. Intell.* 7383–7390. DOI : [10.1609/aaai.v34i05.6233](https://doi.org/10.1609/aaai.v34i05.6233)
- [45] V. Kumar, A. Choudhary, and E. Cho. 2020. Data augmentation using Pre-trained transformer models. arXiv:2003.02245. Retrieved from <http://arxiv.org/abs/2003.02245>.
- [46] M. Bayer, M.-A. Kaufhold, B. Buchhold, M. Keller, J. Dallmeyer, and C. Reuter. 2022. Data augmentation in natural language processing: A novel text generation approach for long and short text classifiers. *Int. J. Mach. Learn. Cybernet.* (2022). DOI : [10.1007/s13042-022-01553-3](https://doi.org/10.1007/s13042-022-01553-3)
- [47] S. T. Luu, K. Van Nguyen, and N. L.-T. Nguyen. 2020. Empirical study of text augmentation on social media text in vietnamese. arXiv:2009.12319. Retrieved from <http://arxiv.org/abs/2009.12319>.
- [48] O. Kashefi and R. Hwa. 2020. Quantifying the evaluation of heuristic methods for textual data augmentation. In *Proceedings of the Sixth Workshop on Noisy User-generated Text (W-NUT'20)*. 200–208. DOI : [10.18653/v1/2020.wnut-1.26](https://doi.org/10.18653/v1/2020.wnut-1.26)
- [49] Z. Wu, S. Wang, J. Gu, M. Khabsa, F. Sun, and H. Ma. 2020. CLEAR: Contrastive learning for sentence representation. <http://arxiv.org/abs/2012.15466>.
- [50] G. Rizos, K. Hemker, and B. Schuller. 2019. Augment to prevent: Short-text data augmentation in deep learning for hate-speech classification. In *Proceedings of the International Conference on Information and Knowledge Management*. 991–1000. DOI : [10.1145/3357384.3358040](https://doi.org/10.1145/3357384.3358040)
- [51] X. Sun and J. He. 2020. A novel approach to generate a large scale of supervised data for short text sentiment analysis. *Multimed. Tools Appl.* 79, 9–10 (2020), 5439–5459. DOI : [10.1007/s11042-018-5748-4](https://doi.org/10.1007/s11042-018-5748-4)
- [52] Q. Xie, Z. Dai, E. Hovy, M.-T. Luong, and Q. V. Le. 2019. Unsupervised data augmentation for consistency training. In *Advances in Neural Information Processing Systems*. <http://arxiv.org/abs/1904.12848>.
- [53] S. Choi, M. Jeong, H. Han, and S.-W. Hwang. 2022. C 2 L: Causally contrastive learning for robust text classification. [www.aaai.org](http://www.aaai.org).

- [54] Y. Cheng, L. Jiang, and W. Macherey. 2020. Robust neural machine translation with doubly adversarial inputs. In *ACL'19*. 4324–4333. DOI: [10.18653/v1/p19-1425](#)
- [55] X. Wang, H. Pham, Z. Dai, and G. Neubig. 2020. Switchout: An efficient data augmentation algorithm for neural machine translation. In *EMNLP'18*. 856–861. DOI: [10.18653/v1/d18-1100](#)
- [56] J. Andreas. 2020. Good-Enough compositional data augmentation. In *ACL'20*. 7556–7566. DOI: [10.18653/v1/2020.acl-main.676](#)
- [57] D. Guo, Y. Kim, and A. Rush. 2020. Sequence-Level mixed sample data augmentation. In *EMNLP'20*. 5547–5552. DOI: [10.18653/v1/2020.emnlp-main.447](#)
- [58] G. Kurata, B. Xiang, and B. Zhou. 2016. Labeled data generation with encoder-decoder LSTM for semantic slot filling. In *INTERSPEECH*. 725–729, 2016. DOI: [10.21437/Interspeech.2016-727](#)
- [59] O. Kolomiyets, S. Bethard, and M. F. Moens. 2011. Model-portability experiments for textual temporal analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, vol. 2. 271–276.
- [60] G. A. Miller, R. Beckwith, C. Fellbaum, D. Gross, and K. J. Miller. 1990. Introduction to wordnet: An on-line lexical database. *Int. J. Lexicogr.* 3, 4 (1990), 235–244. DOI: [10.1093/ijl/3.4.235](#)
- [61] A. V. Mosolova, V. V. Fomin, and I. Y. Bondarenko. 2018. Text augmentation for neural networks. In *CEUR Workshop Proceedings*, 104–109.
- [62] X. Wang, Y. Sheng, H. Deng, and Z. Zhao. 2019. Charcnn-svm for chinese text datasets sentiment classification with data augmentation. *Int. J. Innov. Comput. Inf. Control* 15, 1 (2019), 227–246. DOI: [10.24507/ijicic.15.01.227](#)
- [63] X. Zhang, J. Zhao, and Y. Lecun. 2015. Character-level convolutional networks for text classification. In *Advances in Neural Information Processing Systems*, vol. 2015-Janua. 649–657.
- [64] V. Marivate and T. Sefara. 2020. Improving short text classification through global augmentation methods. In *Lecture Notes in Computer Science* 12279, 385–399. DOI: [10.1007/978-3-030-57321-8\\_21](#)
- [65] X. Zhang and Y. LeCun. 2015. Text understanding from scratch. <http://arxiv.org/abs/1502.01710>.
- [66] M. Jungiewicz and A. Smywiński-Pohl. 2019. Towards textual data augmentation for neural networks: Synonyms and maximum loss. *Comput. Sci.* 20, 1 (2019), 57–84. DOI: [10.7494/csci.2019.20.1.3023](#)
- [67] Z. Hu, B. Tan, R. Salakhutdinov, T. Mitchell, and E. P. Xing. 2019. Learning data manipulation for augmentation and weighting. In *Advances in Neural Information Processing Systems*, Vol. 32. 15764–15775.
- [68] A. Ollagnier and H. Williams. 2020. Text augmentation techniques for clinical case classification. In *Workshop Proceedings (CLEF'20)*, vol. 2996. 22–25. <https://temu.bsc.es/codisp/index.php/2019/09/19/resources/>.
- [69] Z. S. Harris. 1954. Distributional structure. *WORD* 10, 2–3 (1954), 146–162. DOI: [10.1080/00437956.1954.11659520](#)
- [70] J. Firth. 1962. A synopsis of linguistic theory. In *Studies in Linguistic Analysis*. 1–32.
- [71] S. T. Aroyehun and A. Gelbukh. 2018. Aggression detection in social media: Using deep neural networks, data augmentation, and pseudo labeling. In *Trolling, Aggress. Cyberbullying (TRAC'18)*. 90–97.
- [72] W. Y. Wang and D. Yang. 2015. That's so annoying!!!: A lexical and frame-semantic embedding based data augmentation approach to automatic categorization of annoying behaviors using #petpeeve tweets. In *Conference on Empirical Methods in Natural Language Processing*. 2557–2563. DOI: [10.18653/v1/d15-1306](#)
- [73] T. Phreeraphattanakarn and B. Kijsirikul. 2021. Text data-augmentation using text similarity with manhattan siamese long short-term memory for thai language. *J. Phys. Conf. Ser.* 1780, 1 (2021), 12018. DOI: [10.1088/1742-6596/1780/1/012018](#)
- [74] N. Mrkšić et al. 2016. Counter-fitting word vectors to linguistic constraints. In *NAACL HLT'16*. 142–148. DOI: [10.18653/v1/n16-1018](#)
- [75] X. Wu, S. Lv, L. Zang, J. Han, and S. Hu. 2019. Conditional BERT contextual augmentation. In *Lecture Notes in Computer Science* 11539, 84–95. DOI: [10.1007/978-3-030-22747-0\\_7](#)
- [76] J. Devlin, M. W. Chang, K. Lee, and K. Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *NAACL HLT'19*. 4171–4186.
- [77] Y. Qu, D. Shen, Y. Shen, S. Sajeev, J. Han, and W. Chen. 2020. CoDA: Contrast-enhanced and diversity-promoting data augmentation for natural language understanding. *arXiv* 5 (2020), 1–14. <http://arxiv.org/abs/2010.08670>.
- [78] X. Jiao et al. 2020. TinyBERT: Distilling BERT for natural language understanding. In *Findings of the Association for Computational Linguistics Findings of ACL (EMNLP'20)*. 4163–4174. DOI: [10.18653/v1/2020.findings-emnlp.372](#)
- [79] J. Pennington, R. Socher, and C. D. Manning. 2014. GloVe: Global vectors for word representation. In *EMNLP'14*. 1532–1543. DOI: [10.3115/v1/d14-1162](#)
- [80] F. Gao et al. 2020. Soft contextual data augmentation for neural machine translation. In *ACL'20*. 5539–5544. DOI: [10.18653/v1/p19-1555](#)
- [81] A. J. Ratner, H. R. Ehrenberg, Z. Hussain, J. Dunnmon, and C. Ré. 2017. Learning to compose domain-specific transformations for data augmentation. In *NeurIPS'17*. 3237–3247.

- [82] M. Fadaee, A. Bisazza, and C. Monz. 2017. Data augmentation for low-Resource neural machine translation. In *ACL'17*. 2 (2017), 567–573. DOI : [10.18653/v1/P17-2090](https://doi.org/10.18653/v1/P17-2090)
- [83] G. G. Şahin and M. Steedman. 2018. Data augmentation via dependency tree morphing for low-resource languages. In *EMNLP'18*. 5004–5009. DOI : [10.18653/v1/d18-1545](https://doi.org/10.18653/v1/d18-1545)
- [84] C. Vania, Y. Kementchedjheva, A. Søgaaard, and A. Lopez. 2020. A systematic comparison of methods for low-resource dependency parsing on genuinely low-resource languages. In *EMNLP-IJCNLP'19*. 1105–1116. DOI : [10.18653/v1/d19-1102](https://doi.org/10.18653/v1/d19-1102)
- [85] S. Y. Feng, A. W. Li, and J. Hoey. 2020. Keep calm and switch on! Preserving sentiment and fluency in semantic text exchange. In *EMNLP-IJCNLP'19*. 2701–2711. DOI : [10.18653/v1/d19-1272](https://doi.org/10.18653/v1/d19-1272)
- [86] J. Min, R. T. McCoy, D. Das, E. Pitler, and T. Linzen. 2020. Syntactic data augmentation increases robustness to inference heuristics. In *ACL'20*. 2339–2352. DOI : [10.18653/v1/2020.acl-main.212](https://doi.org/10.18653/v1/2020.acl-main.212)
- [87] R. Thomas McCoy, E. Pavlick, and T. Linzen. 2020. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *ACL'19*. 3428–3448. DOI : [10.18653/v1/p19-1334](https://doi.org/10.18653/v1/p19-1334)
- [88] Y. Goldberg. 2019. Assessing BERT's syntactic abilities. arXiv:1901.05287. Retrieved from <http://arxiv.org/abs/1901.05287>.
- [89] I. Tenney et al. 2019. What do you learn from context? Probing for sentence structure in contextualized word representations. In *ICLR'19*.
- [90] J. F. Steffensen, Interpolation. Courier Corporation, 2006.
- [91] H. Shi, K. Livescu, and K. Gimpel. 2021. Substructure Substitution: Structured data augmentation for NLP. arXiv:2101.00411. Retrieved from <http://arxiv.org/abs/2101.00411>.
- [92] H. Kim, D. Woo, S. J. Oh, J.-W. Cha, and Y.-S. Han. 2021. ALP: Data augmentation using lexicalized PCFGs for few-shot text classification. arXiv:2112.11916. Retrieved from <http://arxiv.org/abs/2112.11916>.
- [93] M. Aiken and M. Park. 2010. The efficacy of round-trip translation for MT evaluation. *Transl. J.* 14, 1 (2010).
- [94] A. W. Yu et al. 2018. QaNet: Combining local convolution with global self-attention for reading comprehension. In *Proceeding of the 6th International Conference on Learning Representations*.
- [95] E. Rabinovich, S. Mirkin, R. N. Patel, L. Specia, and S. Wintner. 2017. Personalized machine translation: Preserving original author traits. In *EACL'17*, 1, 1074–1084. DOI : [10.18653/v1/e17-1101](https://doi.org/10.18653/v1/e17-1101)
- [96] A. Kruspe, J. Kersten, M. Wiegmann, B. Stein, and F. Klan. 2018. Classification of Incident-related Tweets: Tackling imbalanced training data using hybrid CNNs and translation-based data augmentation. In *TREC'18*.
- [97] J. Chen, Z. Yang, and D. Yang. 2020. MixText: Linguistically-informed interpolation of hidden space for semi-supervised text classification. In *Proc. 58th Annu. Meet. Assoc. Comput. Linguist.* 2147–2157. DOI : [10.18653/v1/2020.acl-main.194](https://doi.org/10.18653/v1/2020.acl-main.194)
- [98] Y. Wu et al. 2016. Google's neural machine translation system: Bridging the gap between human and machine translation. arXiv (2016), 1–23. <http://arxiv.org/abs/1609.08144>.
- [99] H. Fang, S. Wang, M. Zhou, J. Ding, and P. Xie. 2020. CERT: Contrastive self-supervised learning for language understanding. Retrieved from 2022 <https://github.com/UCSD-AI4H/>.
- [100] D. Britz, A. Goldie, M. T. Luong, and Q. V Le. 2017. Massive exploration of neural machine translation architectures. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*. 1442–1451. DOI : [10.18653/v1/d17-1151](https://doi.org/10.18653/v1/d17-1151)
- [101] D. Shen, M. Zheng, Y. Shen, Y. Qu, and W. Chen. 2020. A simple but tough-to-beat data augmentation approach for natural language understanding and generation. <http://arxiv.org/abs/2009.13818>.
- [102] N. Malandrakis, M. Shen, A. Goyal, S. Gao, A. Sethi, and A. Metallinou. 2019. Controlled text generation for data augmentation in intelligent artificial agents. In *Proceedings of the 3rd Workshop on Neural Generation and Translation*. 90–98. DOI : [10.18653/v1/d19-5609](https://doi.org/10.18653/v1/d19-5609)
- [103] K. Guu, T. B. Hashimoto, Y. Oren, and P. Liang. 2018. Generating sentences by editing prototypes. In *ACL'18* 6, 437–450. DOI : [10.1162/tac1\\_a\\_00030](https://doi.org/10.1162/tac1_a_00030)
- [104] G. Raille, S. Djambazovska, and C. Musat. 2020. Fast cross-domain data augmentation through neural sentence editing. <http://arxiv.org/abs/2003.10254>.
- [105] L. Yu, W. Zhang, J. Wang, and Y. Yu. 2017. SeqGAN: Sequence generative adversarial nets with policy gradient. In *AAAI'17*. 2852–2858.
- [106] Y. Li, Q. Pan, S. Wang, T. Yang, and E. Cambria. 2018. A generative model for category text generation. *Inf. Sci. (N. Y.)* 450, C (2018), 301–315. DOI : [10.1016/j.ins.2018.03.050](https://doi.org/10.1016/j.ins.2018.03.050)
- [107] C. Wang and D. Lillis. 2020. Classification for crisis-related tweets leveraging word embeddings and data augmentation. In *TREC'19*, 8. <https://trec.nist.gov/>.
- [108] H. Queiroz Abonizio and S. Barbon Junior. 2020. Pre-trained data augmentation for text classification. In *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, vol. 12319, 551–565. DOI : [10.1007/978-3-030-61377-8\\_38](https://doi.org/10.1007/978-3-030-61377-8_38)





- [135] R. Shwartz-Ziv and N. Tishby. 2017. Opening the black box of deep neural networks via information. arXiv:1703.00810. Retrieved from <http://arxiv.org/abs/1703.00810>.
- [136] H. Zhang, M. Cisse, Y. N. Dauphin, and D. Lopez-Paz. 2018. MixUp: Beyond empirical risk minimization. In *ICLR'18*.
- [137] L. Sun, C. Xia, W. Yin, T. Liang, P. Yu, and L. He. 2021. Mixup-Transformer: Dynamic data augmentation for NLP tasks. In *COLING*. 3436–3440. DOI: [10.18653/v1/2020.coling-main.305](https://doi.org/10.18653/v1/2020.coling-main.305)
- [138] H. Guo, Y. Mao, and R. Zhang. 2019. Augmenting data with mixup for sentence classification: An empirical study. <http://arxiv.org/abs/1905.08941>.
- [139] H. Guo. 2020. Nonlinear mixup: Out-of-manifold data augmentation for text classification. *AAAI Conf. Artif. Intell.* 34, 04 (2020), 4044–4051. DOI: [10.1609/aaai.v34i04.5822](https://doi.org/10.1609/aaai.v34i04.5822)
- [140] G. Jawahar, B. Sagot, and D. Seddah. 2020. What does BERT learn about the structure of language? In *ACL'19*. 3651–3657. DOI: [10.18653/v1/p19-1356](https://doi.org/10.18653/v1/p19-1356)
- [141] J. Chen, Z. Wang, R. Tian, Z. Yang, and D. Yang. 2020. Local additivity based data augmentation for semi-supervised NER. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*. 1241–1251. DOI: [10.18653/v1/2020.emnlp-main.95](https://doi.org/10.18653/v1/2020.emnlp-main.95)
- [142] N. Reimers and I. Gurevych. 2019. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *EMNLP-IJCNLP'19*. 3982–3992. DOI: [10.18653/v1/d19-1410](https://doi.org/10.18653/v1/d19-1410)
- [143] D. Hendrycks, N. Mu, E. D. Cubuk, B. Zoph, J. Gilmer, and B. Lakshminarayanan. 2019. AugMix: A simple data processing method to improve robustness and uncertainty. arXiv:1912.02781. Retrieved from <http://arxiv.org/abs/1912.02781>.
- [144] S. Bonthu, A. Dayal, M. S. Lakshmi, and S. Rama Sree. 2022. *Effective Text Augmentation Strategy for NLP Models*. Springer, Singapore, 521–531.
- [145] Y. Yan, R. Li, S. Wang, F. Zhang, W. Wu, and W. Xu. 2021. ConSERT: A contrastive framework for self-supervised sentence representation transfer. In *59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing*. 5065–5075. DOI: [10.18653/v1/2021.acl-long.393](https://doi.org/10.18653/v1/2021.acl-long.393)
- [146] Y. Yang et al. 2020. Generative data augmentation for commonsense reasoning. In *EMNLP'20*. 1008–1025. DOI: [10.18653/v1/2020.findings-emnlp.90](https://doi.org/10.18653/v1/2020.findings-emnlp.90)
- [147] A. P. Parikh, O. Täckström, D. Das, and J. Uszkoreit. 2016. A decomposable attention model for natural language inference. In *EMNLP'16*. 2249–2255. DOI: [10.18653/v1/d16-1244](https://doi.org/10.18653/v1/d16-1244)
- [148] A. Robinson, R. D. Cook, and S. Weisberg. 1984. Residuals and influence in regression. *J. R. Stat. Soc. Ser. A* 147, 1 (1984), 108. DOI: [10.2307/2981746](https://doi.org/10.2307/2981746)
- [149] P. W. Koh and P. Liang. 2017. Understanding black-box predictions via influence functions. In *ICML'17*, 4, 2976–2987.
- [150] I. Chaturvedi, Y.-S. Ong, I. W. Tsang, R. E. Welsch, and E. Cambria. 2016. Learning word dependencies in text by means of a deep recurrent belief network. *Knowl.-Based Syst.* 108 (2016), 144–154. DOI: [10.1016/j.knosys.2016.07.019](https://doi.org/10.1016/j.knosys.2016.07.019)
- [151] W. Zhao, H. Peng, S. Eger, E. Cambria, and M. Yang. 2020. Towards scalable and reliable capsule networks for challenging NLP applications. In *ACL'19*. 1549–1559. DOI: [10.18653/v1/p19-1150](https://doi.org/10.18653/v1/p19-1150)
- [152] Y. Ma, H. Peng, T. Khan, E. Cambria, and A. Hussain. 2018. Sentic LSTM: A hybrid network for targeted aspect-based sentiment analysis. *Cognit. Comput.* 10, 4 (2018). DOI: [10.1007/s12559-018-9549-x](https://doi.org/10.1007/s12559-018-9549-x)
- [153] P. K. Jain, W. Quamer, V. Saravanan, and R. Pamula. 2022. Employing BERT-DCNN with sentic knowledge base for social media sentiment analysis. *J. Amb. Intell. Humaniz. Comput.* 1 (2022), 3. DOI: [10.1007/s12652-022-03698-z](https://doi.org/10.1007/s12652-022-03698-z)
- [154] M.-A. Kaufhold. 2021. *Information Refinement Technologies for Crisis Informatics: User Expectations and Design Principles for Social Media and Mobile Apps*. Springer Fachmedien Wiesbaden.
- [155] J. Bragg, A. Cohan, K. Lo, and I. Beltagy. 2021. FLEX: Unifying evaluation for few-shot NLP. arXiv:2107.07170. Retrieved from <http://arxiv.org/abs/2107.07170>.
- [156] S. Gehrmann et al. 2021. The GEM Benchmark: Natural language generation, its evaluation and metrics. In *GEM'21*. 96–120. DOI: [10.18653/v1/2021.gem-1.10](https://doi.org/10.18653/v1/2021.gem-1.10)
- [157] K. D. Dhole et al. 2021. NL-Augmenter: A framework for task-sensitive natural language augmentation. arXiv:2112.0272v1. Retrieved from <https://arxiv.org/abs/2112.02721v1>.
- [158] Z. Papakipos and J. Bitton. 2022. AugLy: Data augmentations for robustness. arXiv:2201.06494. Retrieved from <http://arxiv.org/abs/2201.06494>.
- [159] I. Solaiman et al. 2019. Release strategies and the social impacts of language models. arXiv:1908.09203. Retrieved from <http://arxiv.org/abs/1908.09203>.
- [160] A. Vaswani et al. 2017. Attention is all you need. *Adv. Neural Inf. Process. Syst.* 2017-Decem (2017), 5999–6009.