

Creating Web Pages Using Facelets



Jesper de Jong
SOFTWARE ARCHITECT

@jesperdj

www.jesperdj.com



Overview



Creating Web Pages Using Facelets

- Standard Tag Libraries
- Templating System

Managing Resource Files

- Resource Libraries
- Resource Library Contracts

Demo Application

- Web Shop for Musical Instruments



Creating Web Pages Using Facelets



The Hello World Example


```
workspace - Java EE - ps-jsf-helloworld/src/main/webapp/index.xhtml - Eclipse
File Edit Source Navigate Search Project Run Window Help

ps-jsf-helloworld/pom.xml | web.xml | faces-config.xml | index.xhtml

1 <?xml version="1.0" encoding="UTF-8"?>
2 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
3     "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
4 <html xmlns="http://www.w3.org/1999/xhtml"
5     xmlns:h="http://xmlns.jcp.org/jsf/html">
6 <h:head>
7     <title>Example</title>
8 </h:head>
9 <h:body>
10     <h:outputText value="Hello, World"/>
11 </h:body>
12 </html>
13
```



The Hello World Example



```
1 <?xml version="1.0" encoding="UTF-8"?>
2 <!DOCTYPE html>
3 <html xmlns="http://www.w3.org/1999/xhtml"><head id="j_idt2">
4   <title>Example</title></head><body>Hello, World</body>
5 </html>
```

```
1 <?xml version="1.0" encoding="UTF-8"?>
2 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
3   "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
4 <html xmlns="http://www.w3.org/1999/xhtml"
5   xmlns:h="http://xmlns.jcp.org/jsf/html">
6 <h:head>
7   <title>Example</title>
8 </h:head>
9 <h:body>
10   <h:outputText value="Hello, World"/>
11 </h:body>
12 </html>
13
```



JSF Tag Libraries

- JSP taglib directive

```
<%@ taglib prefix="c" uri="http://xmlns.jcp.org/jsp/jstl/core" %>
```

- JSF XML namespace declaration

```
<html xmlns="http://www.w3.org/1999/xhtml"  
      xmlns:c="http://xmlns.jcp.org/jsp/jstl/core">
```



JSF Standard Tag Libraries

- **HTML**
 - Standard HTML UI components
 - `xmlns:h="http://xmlns.jcp.org/jsf/html"`
- **Facelets**
 - Templating
 - `xmlns:ui="http://xmlns.jcp.org/jsf/facelets"`
- **Core**
 - Listeners, converters, validators, AJAX and more
 - `xmlns:f="http://xmlns.jcp.org/jsf/core"`
- **Composite Components**
 - Creating composite components
 - `xmlns:cc="http://xmlns.jcp.org/jsf/composite"`




JSF Standard Tag Libraries

- **Passthrough Attributes**
 - Support for HTML5
 - `xmlns:p="http://xmlns.jcp.org/jsf/passthrough"`
- **Passthrough Elements**
 - Support for HTML5
 - `xmlns:jsf="http://xmlns.jcp.org/jsf"`
- **JSTL Core**
 - JSP Standard Tag Library Core
 - `xmlns:c="http://xmlns.jcp.org/jsp/jstl/core"`
- **JSTL Functions**
 - JSP Standard Tag Library Functions
 - `xmlns:fn="http://xmlns.jcp.org/jsp/jstl/functions"`



Beware of Old Versions



- **This course is about JSF 2.2**
 - Part of Java EE 7
- **Standard Tag Library Namespace Prefix**
 - Since JSF 2.2: <http://xmlns.jcp.org>
 - Before JSF 2.2: <http://java.sun.com>

The Facelets Templating System

Facelets
Templating
Tags

ui:include

ui:composition

ui:insert


ui:define

ui:params

ui:decorate




Including Content




Using Templates

index.xhtml




product-details.xhtml




Using Templates

index.xhtml



page-template.xhtml




Using Templates



Content

+



Template


=



Final Page



The Facelets Templating Tags



Demo



Using the Facelets Templating System

- Create the first pages of the demo application
- Deploy and run it



Applying a Template to Part of a Page

The `ui:decorate` Tag

The decorate tag is identical to the composition tag, except that `ui:decorate`, unlike `ui:composition`, does not disregard all content outside of the tag.



Facelets Templating Summary

- **ui:include**
 - Inserts the content of another Facelets XHTML file
- **ui:composition**
 - Defines a page that uses a template
- **ui:insert**
 - Defines the point inside a template where content is to be inserted
- **ui:define**
 - Defines content to be inserted into the template
- **ui:param**
 - Passes a parameter to an included file or template
- **ui:decorate**
 - Applies a template to part of a page



Managing Resource Files



Packaging Resources Separately

musicshop.war

```
resources
  musicshop
    css
      default.css
    images
      microphone-120x120.jpg
      microphone-400x400.jpg
      ...
```

```
WEB-INF
  faces-config.xml
  web.xml
```


```
index.xhtml
...
```



resources.jar

```
META-INF
  resources
    musicshop
      css
        default.css
      images
        microphone-120x120.jpg
        microphone-400x400.jpg
        ...
```

Packaging Resources Separately



Resource Library Contracts



Summary



JSF Standard Tag Libraries

Facelets Templating System

- Reusing Content and Layout

Managing Resources

- Resource Libraries
- Resource Library Contracts

Coming Up

- Managed Beans
- Expression Language