
# An Extensive Review of Research in Swarm Robotics



# An Extensive Review of Research in Swarm Robotics

Yogeswaran Mohan School of Engineering, Monash University, Sunway campus, 46150 Petaling Jaya, Selangor, Malaysia yogeswaran.mohan@eng.monash.edu.my

S. G. Ponnambalam School of Engineering, Monash University, Sunway campus, 46150 Petaling Jaya, Selangor, Malaysia sgponnambalam@eng.monash.edu.my

Abstract— Swarm robotics is a new approach to the coordination of multi-robot systems which consist of large numbers of relatively simple robots which takes its inspiration from social insects. The most remarkable characteristic of swarm robots are the ability to work cooperatively to achieve a common goal. In this paper, classification of existing researches, problems and algorithms aroused in the study of swarm robotics are presented. The existing studies are classified into major areas and relevant sub-categories in the major areas.

Keywords-swarm robotics, review, state-of-art, multi-robot

#### I. Introduction

The term "Swarm Intelligence" refers to sophisticated collective behavior that can emerge from the combination of many simple individuals, each operating autonomously [1]. According to Cao et al. [2], swarm intelligence is "a property of systems of non-intelligent robots exhibiting collectively intelligent behavior". Nonetheless, based on the definitions, we can see that the essential characteristics of swarm intelligence consist of a biologically inspired emphasis on decentralized local control and local communication, and on the emergence of global behavior as the result of self-organization [3]. The application of swarm intelligence principles to collective robotics can be termed "Swarm Robotics" [1].

Swarm robotics is a new approach to the coordination of large numbers of relatively simple robots [4], that are autonomous, not controlled centrally, capable of local communication and operates based on some sense of biological inspiration [1]. Swarm robotic systems have become a major research area since 1980's [5], as new solution approaches are being developed and validated, it is often possible to realize the advantages of swarm robotic systems [2, 6, 7].

The early work on classification of research areas of swarm robotic systems was done by Dudek et al. [8] in 1993. The paper classified the areas into five areas which are swarm size, communication range, communication topology, communication bandwidth, swarm reconfigurability and swarm unit processing ability. Cao et al. [2] presented the survey of cooperative robotics in a hierarchical way. They split the publications into five main axes: group architecture, resource conflicts, origins of cooperation, learning and geometric problems. Luca Iocchi et al. [9] presented an analysis of multi robot systems by looking at their

cooperative aspects. They have also proposed taxonomy of multi robot systems and a characterization of reactive and social deliberative behaviors of the multi robot system as a whole. Rather than summarizing the research area of swarm robots into a taxonomy of cooperating systems [2, 8, 9], Lynne [10] have organized the areas by the principal topics that have generated significant levels of research. Open research issues within each topic area have also been identified and discussed clearly in this paper. Section II of this paper will use the classification reported in [10] as the main research axes and further classify the sub-categories in these areas.

### II. RESEARCH DOMAINS

### A. Biological Inspiration

Swarm robotics and the related concept of swarm intelligence, is inspired by an understanding of the decentralized mechanisms that underlie the organization of natural swarms such as ants, bees, birds, fish, wolfs and even humans. Social insects provide one of the best-known examples of biological self organized behavior. By means of local and limited communication, they are able to accomplish impressive behavioral feats: maintaining the health of the colony, caring for their young, responding to invasion and so on [11]. Thomas et al. [12] has analyzed the behavior of a group of robots involved in an object retrieval task where the robots' control system is inspired by a model of ants' foraging behaviors. The sub-tasks assigned to the robots are extracted from simple behavior of ant swarms such as search, retrieve, deposit, return and rest. Ideas inspired from such collective behaviors have led to the use of pheromone [13], a chemical substance deposited by ants and similar social insects in order to mark the environment with information to assist other ants at a later time.

Similarly David et al. [14] and Cazangi et al. [15] used pheromones to achieve inter-robot communication mechanism in their research. A higher level of research in this area, leaded to the studies of cooperation and interaction abilities in mammals.. Bill Tomlinson et al. [16] created an interactive virtual multi-agent system based on the behavior of packs of gray wolves (Canis lupus). Their virtual wolves are able to form social relationships with each other thru the mechanism of social relationship formation involves emotion, perception, and learning. In [17], Terrence Fong et al. have reviewed on socially interactive robots. They have modeled their robots to adopt humans' social interactions. As

research progresses in this area, more sophisticated teamwork architectures are being explored into to cater the increase in problem complexity. Such sophisticated teamwork architectures was demonstrated in [18].

### B. Communication

When a task requires cooperation, there is a need for some form of communication between the participating agents. There has been much debate about the level of communication that should be allowed between such systems. Most of the open literatures have made distinctions between implicit/indirect and explicit/direct communications. Implicit communication (sometimes also called stigmergy [19, 20, 21]) is a method of communicating through the environment.

Pheromone communication is a type of implicit communication. There a many papers that have explored the use of pheromone signal to convey messages within the robots in the swarm [22]. A higher level of pheromone called "virtual pheromone" was introduced in [23-25] to employ simple communication and coordination to achieve large scale results in the areas of surveillance, reconnaissance, hazard detection, and path finding.

Explicit communication is the type of communication in which the robots directly pass messages to each other and/or to the human operator [26]. McPartland et al. [27] has made comparison between implicit and explicit communications theory by applying it to two different swarms of robot which is assigned to explore a given environment in the shortest period of time. Paul et al. [28] introduced and explored simple communication strategies which implemented implicit and explicit communication. Hayes et al. [29] described a distributed algorithm for solving the full odor localization task, and shown that group performance can exceed that of a single robot using explicit communication.

Communication between robots can multiply their capabilities and increase the efficiency. Even though there is no clear conclusion on what type of communication is better for robot swarms, but most of the current research is aiming towards implicit communication for its robust characteristics.

### C. Control Approach

Iocchi et al. [9] has clearly distinguished between distributed and centralized control as:

- Centralized: the organization of a system having a robotic agent (a leader) that is in charge of organizing the work of the other robots; the leader is involved in the decisional process for the whole team, while the other members act according to the directions of the leader.
- Distributed: the organization of a system composed by robotic agents which are completely autonomous in the decisional process with respect to each other; in this class of systems a leader does not exist.

Lynne [30] experimented on the advantages and the disadvantages of the control approaches and reported that deciding the proper balance between centralized and distributed control is the key to achieve the desired emergent group behavior in a swarm of robots. Steele et al. [31]

introduced "Directed Stigmergy-Based Control" which incorporates the advantages of distributed control and centralized control. However, both distributed and centralized control approaches have contributed individually to the study of swarm robotics and have generated interesting experimental results.

### D. Mapping and Localization

Mapping is a representation of the physical environments through the mobile robots sensory data into spatial models [32]. Localization is defined as finding the absolute or rational location of robot in the spatial models generated [33]. Since the development of research in mapping and localization progressed, the problems that addresses mapping and localization has been referred to as simultaneous localization and mapping (SLAM) or concurrent mapping and localization (CML). SLAM or CML is the problem of acquiring a map of an unknown environment with a moving robot, while simultaneously localizing the robot relative to this map [32]. The SLAM problem addresses situations where the robot lacks a global positioning sensor. Instead, it has to rely on a of incremental egomotion for robot position estimation (e.g., odometry). To solve the problem of odometry in SLAM, many approaches have been made thru the application of various filters introduced in [34-35].

There are two distinct mapping approaches available namely topological mapping and geometric mapping. A topological map is an abstract encoding of the structural characteristics of an environment. Often, topological maps [35-36] represent the environment as a set of distinctive places using points (e.g., rooms), connected by sequences of robot behaviors using lines (e.g., wall-following). A geometric map, on the other hand, is a representation of the precise geometric characteristics of the environment, much like a floor plan.

## E. Object Transportation and Manipulation

Researches in this area of swarm robotics have drafted three types object manipulation method which are namely grasping, pushing and caging. Grasping [37-38] incorporates form closure and force closure techniques. Force closure is a condition that implies that the grasp can resist any external force applied to the object.

Pushing [39-40] on the other hand doesn't guarantee form closure or force closure, but requires external forces to be applied to the object such as gravity and friction. Pushing behaviors gives an advantage where any objects that can't be grasped to be moved and as well as to perform pushing to multiple objects.

Caging [41-42] introduces a bounded movable area for the object. Then, the contact between object and robotics mechanism need not be maintained by robot's control. This makes motion planning and control of each robotic mechanism to be simple and robust. This condition is called object closure.

### F. Reconfigurable Robotics

Self-reconfiguring robots are able to deliberately change their own shape by rearranging the connectivity of their parts, in order to adapt to new circumstances, perform new tasks, or recover from damage [43].

Modular self-reconfigurable robotic systems can be generally classified into several architectural groups by the geometric arrangement of their units [44]. Lattice architectures [45-46] have units that are arranged and connected in some regular, three-dimensional pattern, such as a simple cubic or hexagonal grid. Lattice architectures usually offer simpler reconfiguration, as modules move to a discrete set of neighboring locations in which motions can be made open-loop.

Chain architectures [47-48] have units that are connected together in a string or tree topology. This chain or tree can fold up to become space filling, but the underlying architecture is serial. Through articulation, chain architectures can potentially reach any point or orientation in space, and are therefore more versatile but computationally more difficult to represent and analyze and more difficult to control.

Mobile architectures [49-50] have units that use the environment to maneuver around and can either hook up to form complex chains or lattices or form a number of smaller robots that execute coordinated movements and together form a larger "virtual" network.Self-reconfigurable robots have an advantage over fixed-shape robots in these environments because of their special abilities which include versatility, robustness, adaptability, scale extensibility and even self-repair.

### G. Motion Coordination

Exploring into this domain, path-planning in swarm robotics has attracted a lot of attention in the past two decades. The problem of mobile robots path-planning is defined as follows: "for a given robot and an environment description, plan a route between two specific locations, which must be clear of obstacles and attend all the optimizations criteria" [51]. Studies in path-planning can be divided to local path-planning and global path-planning. In local path-planning, the planning is based on the information given by sensors installed on the robot, which provide details about the unknown environment [52]. In the global planning case, the environment's model is precisely defined [53-55], and the navigation is performed with the information known in priori.

The basic path-planning problem deals with static environments [53-54], in which the workspaces solely containing stationary obstacles of which the geometry is known. A natural extension to the basic path planning problem is planning in dynamic environments [56-57], in which besides stationary obstacles, also moving obstacles are present.

Various algorithms has been introduced to tackle the problems in path-planning for example fuzzy-logics [52], particle-swarm optimization (PSO) [58], ant-colony optimization (ACO) [53], D\*[56] and K-Bug [51]. Most of the algorithms aim to solve the shortest path [53-54] problem in path-planning. Nearly all the previous work has been aimed at 2D environment; only some papers considered 3D

environments such as the work presented by Yoshifumi et al [59] and Atsushi et al. [60].

The formation generation problem is defined as the coordination of a group of robots to get into and maintain a formation with a certain shape, such as circle [61], line [62-63] or even arbitrary shapes [64]. Erkin et al. [65] has divided formation generation into two groups. The first group includes studies where the coordination is done by a centralized [66] unit that can oversee the whole group and command the individual robots accordingly. The second group contains distributed [62] strategies for achieving the coordination. Various control strategies in formation generation such as behavior-based approach [63], potential field approach [67] and leader-follower approach [68] can be adopted to achieve coordination.

### H. Learning

At present most learning algorithms can be classified as supervised and unsupervised learning. Supervised learning requires the use of an external supervisor. With supervised learning the robot knows what the best output is in a certain situation as the supervisor provides the corrective information to the learner. Unsupervised learning is a method of learning with minor or without any external corrective feedback from the environment [69]. This method is useful for allowing robots to adapt to situations where the task/environment is unknown beforehand or is constantly changing [70].

Inductive learning is one of the supervised learning paradigms which is a method that generalize from observed training examples by identifying features that empirically distinguish positive from negative training examples [71]. Decision tree learning [72], neural network learning [73] and inductive logic programming [74] are all examples of inductive methods that operate in this fashion. Another well studied paradigm would be explanation-based learning (EBL) [75-76] where prior knowledge is used to analyze, or explain, how each observed training examples satisfies the target concept. This explanation is then used to distinguish the relevant features of the training example from the irrelevant, so that examples can be generalized based on logical reasoning [71]. Other common paradigms that have been applied to robot learning are case-based learning (CBL) and memory-based learning (MBL) which are reported in [77].

Similarly, in unsupervised learning, paradigms such as evolutionary learning and reinforcement learning (RL) received major attention from the researchers recently. Genetic algorithms [78-79] and genetic programming [80-81] are the most prominent computational techniques for evolutionary learning. Reinforcement leaning (RL) is defined as learning what to do, how to map situations to actions so as to maximize a numerical reward signal. The learner is not told which actions to take, as in most forms of machine learning, but instead must discover which actions yield the most reward by trying them. Actions may affect not only the immediate reward but also the next situation and, through that, all subsequent rewards [82]. Examples of

implementation of reinforcement learning can be viewed in [83-84].

### I. Task Allocation

Task allocation means assigning tasks among the robots in swarm in a productive and efficient manner. Task allocation must ensure that not only the global mission is achieved, but also the tasks are well distributed among the robots. An effective task allocation approach considers the available resources, the entities to optimize (time energy, quality and etc.), the capabilities of the deployable robots and appropriately allocates the tasks accordingly [85]. Tasks can be discrete or continuous and also can vary in a number of other ways, including time scale, complexity and specificity [86].

Often in task allocation problems, the comparison between heterogeneous system and homogeneous systems are made. Such comparison results can be found in papers presented by Goldberg and Mataric [87-88].

The problem of multi-robot task allocation (MRTA) has been investigated using different techniques such as physical modeling [89], distributed planning [90], market-based techniques [91], auction based techniques [92] and ALLIANCE [93-94]. One of the first algorithms for market based solutions for the MRTA problem was described in the MURDOCH system developed by Gerkey et al. [95, 96].

### III. CONCLUSION

Most of the research conducted was based on the biological inspirations adopted from the behaviors of ants, bees and birds. Implicit communication seems to give more robustness in the communication architecture of swarm robotics. Distributed control architecture was preferred compared to centralized architecture to prevent single point failures. As far as mapping and localization is concerned, work is still being carried out to fine tune the problems faced in this domain. In object transportation and manipulation, caging is preferred over the available methods as the constraints in the domain can be reduced and kept simple. In last two decades, research in reconfigurable robotics has taken a good progress. Even so, this domain is still at its infant stage. Path-planning and formation generation is one of the main domains that received a lot of attention from the authors. A lot of new heuristics and algorithms were introduced to solve the problems in this domain. In the learning domain, reinforcement learning (RL) was given much interest by the researchers. In task allocation domain, heterogeneous and homogenous systems are widely discussed. This domain has contributed in development of various techniques as listed in the paper.

#### REFERENCES

- Amanda J. C. Sharkey, "The Application of Swarm Intelligence to Collective Robots" in Advances in Applied Artificial Intelligence, John Fulcher, Idea Group Publishing, 2006, pp. 157 - 185.
- [2] Y. Uny Cao, Alex S. Fukunaga and Andrew B. Kahng, "Cooperative Mobile Robotics: Antecedents and Directions", Autonomous Robots, vol. 4, 1997, pp. 1-23.
- [3] Amanda J. C. Sharkey, "Swarm Robotics and Minimalism", Connection Science, vol. 19, no. 3, September 2007, pp. 245-260.

- [4] Levent Bayindir and Erol Sahin, "A Review of Studies in Swarm Robotics", The Turkish Journal of Electrical Engineering & Computer Sciences, vol. 15, no. 2, 2007, pp. 115-147.
- [5] Lynne E. Parker, "Distributed Intelligence: Overview of the Field and its Application in Multi-Robot Systems", Journal of Physical Agents, vol.2, no. 1, March 2008, pp. 5-14.
- [6] Altshuler Y., Yanovsky V., Wagner I. A. and Bruckstein A. M., "Swarm Intelligence – Searchers, Cleaners and Hunters" in Swarm Intelligent Systems, Nadia Nedjah and Luiza de Macedo Mourelle, Springer, 2006, pp. 93-132.
- [7] Bernardine Dias M. and Anthony (Tony) Stenz, "A Market Approach to Multirobot Coordination", The Robotics Institute, Carnegie Mellon University, Pittsburgh, Pennsylvania 15213, August 2001.
- [8] Dudek G., Jenkin M., Millios E. and Wilkes D., "A Taxonomy for Swarm Robots" in Proceedings of the 1993 IEEE/RSJ International Conference on Intelligent Robots and Systems, Yokohama Japan, July 26-30,1993, pp. 441-447.
- [9] Luca Iocchi, Daniel Nardi and Massimiliano Salerno, "Reactivity and Deliberation: A Survey on Multi-Robot Systems", Balancing Reactivity and Social Deliberation in Multi-Agent Systems, From RoboCup to Real-World Applications (selected papers from the ECAI 2000 Workshop and additional contributions), Springer-Verlag, London, UK, 2001, pp. 9-34.
- [10] Lynne E. Parker, "Current research in Multirobot Systems", Artificial Life Robotics, 2003, pp. 1-5.
- [11] Amanda J. C. Sharkey, "Robots, Insects and Swarm Intelligence", Artificial Intelligence Review, vol. 26, 2006, pp. 255-268.
- [12] Thomas H. Labella, Marco Dorigo and Jean-Louis Deneubourg, "Division of Labor in a Group of Robots Inspired by Ants' Foraging Behavior", ACM Transactions on Autonomous and Adaptive Systems, vol. 1, no. 1, September 2006, pp. 4-25.
- [13] Liviu Panait and Sean Luke, "A Pheromone-Based Utility Model for Collaborative Foraging", in AAMAS'04, New York, USA. : ACM, July 19-23, 2004, pp. 36-43.
- [14] David Payton, Regina Estkowski and Mike Howard, "Compound Behaviors in Pheromone Robotics", Robotics and Autonomous Systems, vol.44, 2003, pp. 229–240.
- [15] Renato Reder Cazangi, Fernando J. Von Zuben and Maurício F. Figueiredo, "Autonomous Navigation System Applied to Collective Robotics with Ant-Inspired Communication", GECCO'05, Washington, DC, USA.: ACM, June 25-29, 2005, pp. 121-128.
- [16] Bill Tomlinson and Bruce Blumberg, "Using Emotional Memories to Form Synthetic Social Relationships", Proceedings of AAMAS 02, Bologna, Italy, July 15, 2002.
- [17] Terrence Fong, Illah Nourbakhsh and Kerstin Dautenhahn, "A Survey of Socially Interactive Robots", Robotics and Autonomous Systems, vol. 42, 2003, pp. 143-166.
- [18] Kitano H., Asada M., Noda I. and Matsubara H., "Robocup: Robot World Cup" in Robotics & Automation Magazine, IEEE, vol. 5, issue. 3, Sept. 1998, pp. 30-36.
- [19] Vito Trianni, Thomas H. Labella, and Marco Dorigo, "Evolution of Direct Communication for a Swarm-bot Performing Hole Avoidance", in ANTS 2004, 2004, pp. 130-141.
- [20] I.Mir and B.P.Amavasai, "A Fully Decentralized Approach for Incremental Perception", Proceedings of the 1st International Conference on Robot Communication and Coordination, Athens, Greece, 2007.
- [21] Robin Kramer, "Stigmergic Communication: Achieving so much without saying a word", 2005.
- [22] Anies Hannawati Purnamadjaja, Johan Iskandar and R. Andrew Russell, "Pheromone Communication Simulation for Mobile Robots Using Java 3D", ICIS 2007
- [23] David Payton, Mike Daily, Bruce Hoff, Mike Howard and Craig Lee, "Pheromone Robotics", Autonomous Robots, vol. 11, no. 3, pp. 319–324, 2001.

- [24] David Payton, Regina Estkowski and Mike Howard, "Compound behaviors in pheromone robotics", Robotics and Autonomous Systems, vol. 44, 2003, pp. 229-240.
- [25] Yan Meng, Olorundamilola Kazeem and Juan C. Muller, "A Hybrid ACO/PSO Control Algorithm for Distributed Swarm Robots", Proceedings of the 2007 IEEE Swarm Intelligence Symposium, 1-5 April 2007, pp. 273-280.
- [26] Omer Cayirpunar, Bulent Tavli and Veysel Gazi, "Dynamic Robot Networks for Search and Rescue Operations", http://www.robot.uji.es/documents/rise08/reports/Cayirpunar.pdf, August 2008, 10.00am.
- [27] Michelle McPartland, Stefano Nolfi and Hussein A. Abbass, "Emergence of Communication in Competitive Multi-Agent Systems: A Pareto Multi-Objective Approach", GECCO'05, Washington, DC, USA. June 25-29, 2005, pp. 51-58.
- [28] Paul E. Rybski, Amy Larson, Harini Veeraraghavan, Monica LaPoint, and Maria Gini, "Communication strategies in Multi-Robot Search and Retrieval: Experiences with MinDART", Distributed Autonomous Robotic Systems 6, Springer Japan, 2007.
- [29] Adam T. Hayes, Alcherio Martinoli and Rodney M. Goodman, "Swarm Robotic Odor Localization: Off-Line Optimization and Validation with Real Robots", Robotica, vol. 21, 2003, pp. 427-441.
- [30] Lynne E. Parker, "Designing Control Laws for Cooperative Agent Teams", Proceedings of the IEEE International Conference on Robotics and Automation, vol. 3, 2-6 May1993, pp. 582 - 587.
- [31] Fitzgerald Steele Jr. and Geb Thomas, "Directed Stigmergy-Based Control for Multi-Robot Systems", HRI'07, March 8-11, 2007, Arlington, Virginia, USA, pp. 223-230.
- [32] Sebastion Thrun, "Robotic Mapping: A Survey", Exploring Artificial Intelligence in the New Millennium, Morgan Kaufmann, 2002.
- [33] http://www.cas.mcmaster.ca/~safyalh/presentations/autonomousRobo tMapGeneration.pdf, August 29 2008, 9am.
- [34] Stephen Se, David Lowe and Jim Little, "Mobile Robot Localization and Mapping with Uncertainty using Scale-Invariant Visual Landmarks", The International Journal of Robotics Research, vol. 21, 2002, pp. 735-759.
- [35] Howie Choset and Keiji Nagatani, "Topological Simultaneous Localization and Mapping (SLAM): Toward Exact Localization without Explicit Localization", IEEE Transactions on Robotics and Automation, vol. 17, no. 2, April 2001, pp. 125-137.
- [36] Benjamin Kuipers and Yung-Tai Byun, "A Robot Exploration and Mapping Strategy Based on a Semantic Hierarchy of Spatial Representations", Robotics and Autonomous Systems, vol. 8, 1981, pp. 47-63.
- [37] Roderich Gross, Francesco Mondada and Marco Dorigo, "Transport of an Object by Six Pre-attached Robots Interacting via Physical Links", Proceedings 2006 IEEE International Conference on Robotics and Automation, 15-19 May 2006, pp. 1317 – 1323.
- [38] ZhiDong Wang, Eiji Nakano and Takuji Matsukawa, "Realizing Cooperative Object Manipulation using Multiple Behavior- based Robots", Proceedings of the 1996 IEEE/RSJ International Conference on Intelligent Robots and Systems '96, vol. 1, 4-8 Nov 1996, pp. 310-317.
- [39] Miyata N., Ota J., Aiyama, Y., Sasaki J. and Arai T., "Cooperative Transport System with Regrasping Car-like Mobile Robots", Proceedings of the 1997 IEEE/RSJ International Conference on Intelligent Robots and Systems, vol. 3, 7-11 Sept. 1997, pp.1754 – 1761.
- [40] Seiji Yamada and Jun'ya Saito, "Adaptive Action Selection Without Explicit Communication for Multirobot Box-Pushing", IEEE Transactions On Systems, Man, And Cybernetics-Part C: Applications And Reviews, vol. 31, no. 3, August 2001, pp. 398-404.
- [41] ZhiDong Wang and Vijay Kumar, "Object Closure and Manipulation by Multiple Cooperating Mobile Robots", Proceedings of the 2002 IEEE International Conference on Robotics & Automation Washington, DC May 2002, pp. 394-399.

- [42] ZhiDong Wang, Yasuhisa Hirata, and Kazuhiro Kosuge, "Control a Rigid Caging Formation for Cooperative Object Transportation by Multiple Mobile Robots", Proceedings of the 2004 IEEE International Conference on Robotics & Automation, New Orleans, LA April, 2004, pp. 1580-1585.
- [43] http://en.wikipedia.org/wiki/Self-Reconfiguring\_Modular\_Robotics, September 01, 2008, 10.10AM.
- [44] Elio Tuci, Roderich Gross, Vito Trianni, Francesco Mondada, Michael Bonani and Marco Dorigo, "" Cooperation Through Self-Assembly in Multi-Robot Systems", ACM Transactions on Autonomous and Adaptive Systems, vol. 1, no. 2, December 2006, pp. 115-150.
- [45] S. Murata, E. Yoshida, A. Kamimura, H. Kurokawa, K. Tomita, and S.Kokaji, "M-TRAN: Self-reconfigurable modular robotic system," IEEE/ASME Trans. Mech., vol. 7, no. 4, 2002, pp. 431-441.
- [46] Kotay, K.D. and Rus, D.L., "Motion synthesis for the self-reconfiguring molecule", Intelligent Proceedings 1998 IEEE/RSJ International Conference on Robots and Systems, 13-17 Oct, vol.2, 1998, pp.843-851.
- [47] M. Yim, "A Reconfigurable Modular Robot with Many Modes of Locomotion," Proc. of JSM International Conf. on Advanced Mechatronics, 1993, pp.283-288.
- [48] Gregory J. Hamlin and Arthur C. Sanderson, "Tetrobot, Modular Robotics: Prototype and Experiments", Proceedings of the 1996 IEEE International Conference on Intelligent Robots and Systems, 1996, pp. 390-395.
- [49] Fukuda, T.; Nakagawa, S.; Kawauchi, Y.; Buss, M., "Self Organizing Robots Based on Cell Structures – CEBOT", IEEE International Workshop on Intelligent Robots, 1988, Oct. 31 -Nov. 2, 1988, pp. 145-150.
- [50] Roderich Gross, Michael Bonani, Francesco Mondada and Marco Dorigo, "Autonomous Self-Assembly in Swarm-Bots", IEEE Transactions on Robotics, vol. 22, no. 6, Dec. 2006, pp. 1115-1130.
- [51] Ricardo A. Langer, Leandro S. Coelho and Gustavo H. C. Oliveira, "K-Bug, A New Bug Approach for Mobile Robot's Path Planning", 16th IEEE International Conference on Control Applications Part of IEEE Multi-conference on Systems and Control Singapore, 1-3 October 2007, pp. 403-408.
- [52] Bin Lei and Wenfeng Li, "A Fuzzy Behaviours Fusion Algorithm for Mobile Robot Real-time Path Planning in Unknown Environment", Proceedings of the 2007 IEEE International Conference on Integration Technology Shenzhen, China, March 20 - 24, 2007, pp. 173-178
- [53] Beatriz A. Garro, Humberto Sossa and Roberto A. Vazquez, "Evolving Ant Colony System for Optimizing Path Planning in Mobile Robots", Fourth Congress of Electronics, Robotics and Automotive Mechanics, 2007.
- [54] Caihong Li, Yibin Li, Fengyu Zhou and Chen Fan, "Multi-objective Path Planning for the Mobile Robot", Conference on Automation and Logistics, Jinan, China, August 18 - 21, 2007, pp. 2248-2252.
- [55] Jung Won Kang, Si Jong Kim, Myung Jin Chung, Hyun Myung, Jun Ho Park and Seok Won Bang, "Path Planning for Complete and Efficient Coverage Operation of Mobile Robots", Proceedings of the 2007 IEEE International Conference Mechatronics and Automation, Harbin, China, August 5 - 8, 2007, pp. 2126-2131.
- [56] Jur van den Berg, Dave Ferguson and James Kuffner, "Anytime Path Planning and Replanning in Dynamic Environments", Proceedings of the 2006 IEEE International Conference on Robotics and Automation, Orlando, Florida, May 2006, pp. 2366-2371.
- [57] Jingwen Tian, Meijuan Gao and Erhong Lu, "Dynamic Collision Avoidance Path Planning for Mobile Robot Based on Multi-sensor Data Fusion by Support Vector Machine", Proceedings of the 2007 IEEE International Conference on Mechatronics and Automation, Harbin, China, August 5- 8, 2007, pp. 2779-2783.
- [58] Gerasimos G. Rigatos, "Distributed Gradient and Particle Swarm Optimization for Multi-Robot Motion Planning", Robotica vol.26, 2008, pp. 357-370.

- [59] Yoshifumi K., Takaaki T., Fumio K., and Masahiko Y., "3-D Path Planning in a Dynamic Environment Using an Octree and an Artificial Potential Field", Proceedings. IEEE/RSJ Intelligent Robots and Systems 95, vol.2, 5-9 Aug 1995, pp.474 – 481.
- [60] Atsushi Y., Masaki F., Jun O., Tamio A. and Hajime A., "Motion Planning for Cooperative Transportation of a Large Object by Multiple Mobile Robots in a 3D Environment", Proceedings of the IEEE International Conference on Robotics and Automation, San Francisco, 2000, pp 3144-3151.
- [61] Xavier Defago and Akihiko Konagaya, "Circle Formation for Oblivious Anonymous Mobile Robots with No Common Sense of Orientation", POMC'02, October 30-31, 2002, Toulouse, France.
- [62] Kazuo Sugihara and Ichiro Suzuki, "Distributed Motion Coordination of Multiple Mobile Robots", Proceedings., 5th IEEE International Symposium on Intelligent Control, vol. 1, 5-7 Sep 1990, pp. 138-143.
- [63] Tucker Balch, and Ronald C. Arkin, "Behavior-based Formation Control for Multi-robot Teams", IEEE Transactions on Robotics and Automation, vol. 14, Dec 1998, pp. 926-939.
- [64] Erol Sahin, Thomas H. Labella, Vito Trianni, Jean-Louis Deneubourg, Philip Rasse, Dario Flreano, Luca Gambardella, Francesco Mondada, Stefano Nolfi and Marco Dorigo, "Swarm-Bot: Pattern Formation in a Swarm of Self-Assembling Mobile Robots", Proceedings of the IEEE International Conference on Systems, Man and Cybernetics, Hammamet, 2002.
- [65] Erkin Bahceci, Onur Soysal, and Erol Sahin, "A Review: Pattern Formation and Adaptation in Multi-Robot Systems," tech. report CMU-RI-TR-03-43, Robotics Institute, Carnegie Mellon University, October, 2003.
- [66] Belta C. and Kumar V, "Trajectory Design for Formations of Robots by Kinetic Energy Shaping", Proceedings ICRA '02. IEEE International Conference on Robotics and Automation, 2002.
- [67] David J. Bruemmer, Donald D. Dudenhoeffer, Mark D. McKay and Matthew O. Anderson, "A Robotic Swarm for Spill Finding and Perimeter Formation", Proceedings of the 2004 IEEE International Conference on Robotics & Automation, New Orleans, LA, April 2004.
- [68] J. Desai, J. Ostrowski, and V. Kumar, "Modeling and Control of Formations of Nonholonomic Mobile Robots", IEEE Transactions on Robotics and Automation, vol. 17, no. 6, December 2001, pp. 905-908
- [69] Ethem Alpaydin, Introduction to Machine Learning. London, England: The MIT Press, 2004.
- [70] Jim Pugh and Alcherio Martinoli, "Multi-robot Learning with Particle Swarm Optimization", AAMAS, Hakodate, Hokkaido, Japan, May 8-12, 2006, pp. 441-448.
- [71] Tom M. Mitchell, Machine Learning. Boston, Massachusetts: WCB/McGraw-Hill,1997.
- [72] Quinlan, J. R., "Induction of Decision Trees," Machine Learning, Boston: Kluwer Academic Publishers, 1986, vol. 1, pp. 81-106.
- [73] D. Pomerleau, Neural Network Based Autonomous Navigation. In C. Thorpe, Vision and Navigation: The CMU Navlab. Kluwer Academic Publishers, 1990.
- [74] Tolga Konik and John E. Laird, "Hierarchical Procedural Knowledge Learning Through Observation using Inductive Logic Programming, an Extended Abstract", http://www.site.uottawa.ca/~stan/ilp2002/wippprs/konik\_ilp2002.pdf, August 2008, 10.00am.
- [75] G. Dejong and R. Mooney, "Explanation-Based Learning: An Alternative View", Machine Learning, vol. 1, no. 2, 1986, pp. 145-176.
- [76] T. Mitchell, R. Keller and S. Kedar-Cabelli, "Explanation-Based Generalization: A Unifying View", Machine Learning, vol. 1, no.1, 1986.

- [77] Siang Kok Sim, Kai Wei Ong and Gerald Seet, "A Foundation for Robot Learning", The Fourth International Conference on Control and Automation, 10-12 June 2003, Montreal, Canada, pp. 649-653.
- [78] Holland. J, "Adaptation in Natural and Artificial Systems", Ann Arbor: The University of Michigan Press, 1975 (Second edition printed in 1992 by MIT Press, Cambridge, MA.).
- [79] Goldberg D., Genetic Algorithms. Addison-Wesley, 1989.
- [80] Koza, J., Genetic Programming: On the Programming of Computers by Means of Natural Selection, Cambridge, MA: MIT Press, 1992.
- [81] Koza, J., Genetic Programming II: Automatic Discovery of Reusable Programs, Cambridge, MA: MIT Press, 1994.
- [82] Richard S. Sutton and Andrew G. Barto. Reinforcement Learning: An Introduction. London, England: The MIT Press, 1998.
- [83] R. Sun and T. Peterson, "Multi-Agent Reinforcement Learning: Weighting and Partitioning", Neural Networks, vol. 12, 1999, pp. 727-753.
- [84] K. Samejima and T. Omori, "Adaptive Internal State Space Construction Method for Reinforcement Learning of a Real-World Agent", Neural Networks, vol. 12, 1999, pp. 1143-1155.
- [85] Khashayar R. Baghaei and Arvin Agah, "Task Allocation Methodologies for Multi-Robot Systems", Technical Report Information and Telecommunication Technology Center, The University of Kansas, Lawrence, Kansas 66045, November 2002.
- [86] Brian P. Gerkey and Maja J Mataric, "A Formal Analysis and Taxonomy of Task Allocation in Multi-Robot Systems", The International Journal of Robotics Research, vol. 23, 2004, pp. 939-954.
- [87] D. Goldberg and M.J. Mataric. (2000). Robust behavior-based control for distributed multi-robot collection tasks. In T. Balch and L.E. Parker (Eds.) Robot Teams: From Diversity to Polymorphism.
- [88] D. Goldberg and M.J. Mataric. (2000). Design and evaluation of robust behavior-based controllers for distributed multi-robot collection tasks. USC Institute for Robotics and Intelligent Systems Technical Report IRIS-00-387.
- [89] L. Parker, "Distributed Algorithms for Multi-Robot Observation of Multiple Moving Targets", Autonomous Robots, vol. 12, no. 3, 2002, pp. 231-255.
- [90] C. Oritz, R. Vincent and B. Morriset, "Task Inference and Distributed Task Management in the Centibots Robotic System," Proceedings of the 4th Joint International Conference on Autonomous Agents and Multi-AgentSystems, Utrecht, The Netherlands, 2005, pp. 870-877.
- [91] M.B. Dias, R.M. Zlot, N. Kalra, and A. Stentz, "Market-Based Multirobot Coordination: A Survey and Analysis," Tech. report CMU-RI-TR-05-13, Robotics Institute, Carnegie Mellon University, 2005.
- [92] D.P. Bertsekas., "Auction Algorithms for Network Flow Problems: A Tutorial Introduction", Computational Optimization and Applications, 1992, pp. 7-66.
- [93] L.E. Parker, "ALLIANCE: An Architecture for Fault Tolerant Multi-Robot Cooperation", IEEE Transactions on Robotics and Automation, vol. 14, no. 2, 1998, pp. 220-240.
- [94] L.E. Parker, "On the Design of Behavior-Based Multi-Robot Teams", Journal of Advanced Robotics, vol. 10, no. 6, 1996.
- [95] B.P. Gerkey and M.J. Mataric., "Pusher-Watcher: An Approach to Fault-Tolerant Tightly-Coupled Robot Coordination", Proceedings of IEEE/RSJ IROS, 2001, in press.
- [96] B.P. Gerkey and M.J. Mataric., "Sold!: Market Methods for Multi-Robot Control", IEEE Transactions on Robotics and Automation, Special Issue on Multi Robot Systems, 2001, in press.