

Gramatica (LL1):

program : line*

line : expression NEWLINE

| NEWLINE

expression : '(' inner_expression ')'

| NUMERO

inner_expression : MEM

| expression MEM

| expression RES

| expression expression OPERADOR

| IF expression expression else_part?

| FOR expression expression expression

| expression

else_part : ELSE expression.

First:

program	{ '(', NUMERO, NEWLINE, ϵ }
line	{ '(', NUMERO, NEWLINE }
expression	{ '(', NUMERO }
inner_expression	{ MEM, IF, FOR, '(', NUMERO }
else_part	else_part

Follow:

program	{ \$ } (fim de arquivo)
line	{ '(', NUMERO, NEWLINE, \$ }
expression	{ MEM, RES, OPERADOR, IF, FOR, ELSE, ')', NEWLINE }
inner_expression	{ ')' }
else_part	{ ')' }

Tabela analítica:

Não Terminal	'('	NUMERO	') '	MEM	RES	OPERADOR	IF	FOR	ELSE	NEWLINE	\$
program	→ line	→ line								→ ε	→ ε
line	→ expr r	→ expr								→ \n	
expression	→ (ie)	→ NUMERO									
inner_expression	→ ie_tail	→ ie_tail		→ MEM			→ IF	→ FOR			
ie_tail	→ expr op	→ expr op	→ ε	→ e M	→ e R						
else_part									→ ELSE		