Multi-agentic implementation of a 2D topology optimization framework for compliance and linearized buckling via weighted sum method

Gabriele Ricatto

September 27, 2026

Abstract

This paper presents a framework for multi-objective topology optimization, focusing on the trade-off between structural compliance and linear buckling stability. A custom Finite Element Method solver, based on $\mathcal{Q}_4$ bilinear isoparametric elements, is implemented. The material distribution is parameterized utilizing the Solid Isotropic Material with Penalization (SIMP) approach. To explore the trade-off spectrum between global stiffness and the fundamental Buckling Load Factor (BLF), a weighted and dynamically normalized sensitivity scheme is implemented. The proposed framework provides an effective tool for generating preliminary components, illustrating transitions across the design space when stiffness is penalized in favor of structural stability and vice versa. Furthermore, a comparison between the results obtained and those derived from commercial software is presented.

The low-level debugging and code writing were primarily conducted using a multi-agentic human-in-the-loop workflow, leveraging commercially available large language models through Google's Antigravity.

1 FEM implementation

For the implementation of the FEM solver, we rely on bilinear isoparametric elements ($\mathcal{Q}_4$) applied to a fully structured mesh. The rectangular elements are aligned with the global reference system, with the origin of the natural coordinates centered in the centroid of each element. The general formulation for variable-size elements has been omitted, as unnecessarily complicated for the purpose of this project. In accordance with the semplifications introduced, the mapping between physical and natural coordinates assumes the following form:

$$x = x_1 + \frac{dx}{2}\xi, \quad y = y_1 + \frac{dy}{2}\eta \tag{1}$$

with $\eta \in [-1; 1]$ and $\xi \in [-1; 1]$. We can now derive the Jacobian as:

$$[J] = \begin{bmatrix} \frac{\partial x}{\partial \xi} & \frac{\partial y}{\partial \xi} \\ \frac{\partial x}{\partial \eta} & \frac{\partial y}{\partial \eta} \end{bmatrix} = \begin{bmatrix} dx/2 & 0 \\ 0 & dy/2 \end{bmatrix} \implies \det(J) = \frac{1}{4} dxdy \tag{2}$$

and its inverse:

$$[J]^{-1} = \begin{bmatrix} \frac{2}{dx} & 0 \\ 0 & \frac{2}{dy} \end{bmatrix} \tag{3}$$

The shape functions are:

$$N_1 = \frac{1}{4}(1-\xi)(1-\eta) \tag{4}$$

$$N_2 = \frac{1}{4}(1+\xi)(1-\eta) \tag{5}$$

$$N_3 = \frac{1}{4}(1+\xi)(1+\eta) \tag{6}$$

$$N_4 = \frac{1}{4}(1-\xi)(1+\eta) \tag{7}$$

The writing and calculation of the elementary stiffness matrix K_e^0 are quite simple and are done only once at the beginning of the calculation. After that, in accordance with the SIMP model, at each iteration the following calculation is foreseen:

$$[K] = \sum_{e=1}^{m} E_K(\hat{p}_e) \cdot K_e^0 = \sum_{e=1}^{m} [E_{min} + (E_0 - E_{min})\hat{p}_e^{p_K}][K_e^0] \tag{8}$$

We have already introduced the parameters p_K and p_G, but we have not yet assigned a value to it. In accordance with numerical evidence and those found in literature, we opt to assign both a value equal to 3, so $p_K = p_G = p = 3$ [1]. As for the elementary matrix K_e^0:

$$[K_e^0] = \int_V [B]^T [C][B] dV \tag{9}$$

The element is two-dimensional; thus, assuming a unit thickness, the elemental stiffness matrix is defined as:

$$[K_e^0] = \int_\Omega [B]^T [C][B]\, dxdy \tag{10}$$

where the matrix $[B]$ contains the spatial derivatives of the shape functions. By transitioning to natural coordinates to resolve the integral, the formulation becomes:

$$[K_e^0] = \int_{-1}^{1}\int_{-1}^{1} \left(\frac{1}{4}\right)^2 [B(\xi,\eta)]^T [C][B(\xi,\eta)] \det(J)\, d\eta d\xi \tag{11}$$

The elemental geometric stiffness matrix, G_e^0, is derived from the linearization of the Principle of Virtual Work:

$$[G_e^0] = \int_{\Omega_0} B_1^T T[\sigma_e] B_1 d\Omega_0 \tag{12}$$

where for a Q4 element the matrix B_1 is composed of the gradients of the shape functions, and furthermore we have the stress matrix:

$$T[\sigma_e] = \begin{bmatrix} \sigma_x & \tau_{xy} & 0 & 0 \\ \tau_{xy} & \sigma_y & 0 & 0 \\ 0 & 0 & \sigma_x & \tau_{xy} \\ 0 & 0 & \tau_{xy} & \sigma_y \end{bmatrix} \tag{13}$$

Where for simplicity, before optimization, the constant elements are pre-calculated by collecting the individual stresses in binary matrices:

$$T[\sigma_e] = \sigma_x \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} + \sigma_y \cdots + \tau_{xy} \ldots \tag{14}$$

The objective of the decomposition proposed is to separate the state-dependent variables (local stresses) from the geometric constant terms. By substituting the decomposed stress matrix back into the integral, the scalar stress components can be extracted from the integral as follows:

$$[G_e^0] = \sigma_x \int_{\Omega_0} B_1^T T_x B_1, d\Omega_0 + \sigma_y \int_{\Omega_0} B_1^T T_y B_1, d\Omega_0 + \tau_{xy} \int_{\Omega_0} B_1^T T_{xy} B_1, d\Omega_0 \tag{15}$$

where T_x, T_y, and T_{xy} denote the constant basis matrices presented in (14). This mathematical arrangement yields a significant computational advantage since the three integral terms now depend exclusively on the element geometry and the shape functions, which remain invariant throughout the optimization process on a fixed mesh. Consequently, these matrices can be evaluated exactly

once during the pre-processing phase: by doing so, within the optimization loop they will simply be scaled by the updated stress values at each iteration.

To to give a better insight of the FEM workflow, in the following one can find the steps persecuted by the solver:

1. For each element in the mesh, K_e^0 is evaluated. This computation is performed only once during the pre-processing phase. With the results obtained, the global stiffness matrix $[K]$ is assembled by penalizing the elemental matrices according to the SIMP interpolation scheme, $K_e = E(x_e)K_e^0$.
2. Boundary conditions (loads and constraints) are applied and the system $KU = F$ is solved.
3. Having retrieved the global displacement vector U, the overall structural compliance is evaluated as $C = U^T KU$.
4. The assembly of the geometric stiffness matrix G requires the local stress state of each element. Extracting the local nodal displacements u_e from the global vector U, the elemental strains and stresses are computed using $\epsilon_e = Bu_e$ and $\sigma_e = D\epsilon_e$.
5. The linear buckling eigenvalue problem $[K + \lambda_i G]\{\phi_i\} = \{0\}$ is solved to extract the fundamental buckling load factors λ and their corresponding eigenmodes ϕ. These results will then be used by the optimizer.

2 Optimization problem setup

In accordance with [7], the spatial domain is discretized in m equal elements for a total of n *Degrees of Freedom* (DOFs). We also define the pseudo-density field as $\hat{x} = \{\hat{x}_e\}_{e=1}^m$, that are partitioned between 3 sets:

1. $\Omega_{p_0} \rightarrow$ passive regions where $\hat{x}_e = 0$ (forced void)
2. $\Omega_{p_1} \rightarrow$ passive regions where $\hat{x}_e = 1$ (forced solid)
3. $\Omega_A \rightarrow$ actual domain with active design space variables.

In the design space, density $\hat{x}_e$ is obtained through a smoothed heaviside projection [8]:

$$\hat{x}_e = \frac{\tanh(\beta\eta) + \tanh(\beta(\tilde{x}_e - \eta))}{\tanh(\beta\eta) + \tanh(\beta(1 - \eta))} \tag{16}$$

with $\eta \in [0, 1]$ and $\beta \in [1, \infty)$. This equation, using the hyperbolic tangent, forces the intermediate values towards 0 and 1, in order to decrease the shades and define sharper boundaries.
The intermediate variable $\tilde{x}_e$ represents the filtered density, calculated via:

$$\tilde{x}_e = \frac{\sum_{i=1}^m h_{ei} x_i}{\sum_{i=1}^m h_{ei}} \tag{17}$$

with $h_{ei} = \max(0, r_{min} - dist(\Omega_i, \Omega_e))$. In this expression, r_{min} specifies the filter radius, and $\text{dist}(\Omega_i, \Omega_e)$ represents the center-to-center distance between elements i and e. The introduction of the previous formulation is needed in order to exclude elements further than r_{min} from an element e, thus increasing the weight of elements close to e. Ultimately, these measures prevent the generation of mesh-dependent solutions and checkerboarding patterns.

Let the Young's modulus be parametrized by the SIMP interpolations with penalizations $p_K, p_G > 1$

$$E_K(\hat{x}_e) = E_{min} + (E_0 - E_{min})\hat{x}_e^{p_K} \tag{18}$$

$$E_G(\hat{x}_e) = E_0\hat{x}_e^{p_G} \tag{19}$$

where E_0 represents the elastic modulus of the solid base material, and $E_{min} \ll E_0$ is a positive lower bound (in this case, set to 10^{-9}).

The volume fraction is defined as $f(\hat{x}) = \frac{1}{m}\sum_{e=1}^{m}\hat{x}_e$. Alongside this we introduce the compliance $C(\hat{x}) = F^T U(\hat{x})$, which represents the external work done by the loads: minimizing this compliance is equivalent to maximizing the global stiffness of the design.

To predict structural instability while maintaining computational efficiency, a linearized buckling analysis is adopted. This requires solving the following generalized eigenvalue problem:

$$(K + \lambda_i G)\phi_i = 0 \tag{20}$$

Specifically, the fundamental Buckling Load Factor (BLF), denoted as λ_1, is retrieved through the minimization of:

$$\lambda_1(\hat{x}, U) = \min_{v \in \mathbb{R}^n, v \neq 0} \frac{v^T K(\hat{x}) v}{-v^T G(U) v} \tag{21}$$

where v represents a non-zero virtual displacement field. Only positive BLFs, which indicate structural instability under the specific applied load direction, are considered. In computational practice, to prevent numerical singularities, the solver calculates the reciprocal eigenvalue $\mu_i = 1/\lambda_i$. Consequently, the problem can be formulated as:

$$(G(U) + \mu_i K(\hat{x}))\phi_i = 0 \tag{22}$$

As demonstrated by Ferrari and Sigmund [1, 7], the lowest buckling eigenvalues often coalesce and switch order during optimization. To avoid non-differentiable mode switching, the first n_{Eig} reciprocal buckling eigenvalues are aggregated using the smooth Kreisselmeier-Steinhauser (KS) function [7]. To explore the conflicting criteria between structural compliance and linear buckling resistance, the aggregated stability measure and compliance are combined

via a weighted sum method:

$$\tilde{f}(\hat{x}) = \sum_{i=1}^{M} w_i f_i(\hat{x}) \tag{23}$$

where $w_i \in [0, 1]$ represents the individual weighting parameter assigned to the i-th objective. In this framework, the trade-off between the two competing objectives is governed by an exploration parameter $\alpha \in [0, 1]$:

$$F(\vec{x}) = \alpha \mu_{KS} + (1 - \alpha) C \tag{24}$$

Combining those two directly into a single scalar function is problematic, as their respective raw sensitivities often differ by several orders of magnitude. A direct weighted sum would cause the objective with the steepest local gradients to completely dominate the density update process, overshadowing the secondary objective.

To ensure a balanced trade-off search, an adaptive dynamic sensitivity scaling is implemented at each iteration (i). Rather than using the arithmetic mean (which is sensitive to localized stress concentrations near concentrated point loads), both gradient fields are normalized by their 95-th percentile absolute value (P_{95}):

$$S_C^{(i)} = P_{95}\left(\left|\frac{\partial C^{(i)}}{\partial \hat{x}}\right|\right), \quad S_\mu^{(i)} = P_{95}\left(\left|\frac{\partial \mu_{KS}^{(i)}}{\partial \hat{x}}\right|\right) \tag{25}$$

By dividing the raw gradients by these dynamically updated factors, the sensitivities are mapped to a comparable magnitude at every optimization step. The final aggregated sensitivity, which constitutes the search direction passed to the optimizer, is then computed as a linear combination governed by the effective parameter $\alpha_{eff}^{(i)}$:

$$\frac{\partial F^{(i)}}{\partial \hat{x}_e} = (1 - \alpha_{eff}^{(i)}) \frac{1}{S_C^{(i)}} \frac{\partial C^{(i)}}{\partial \hat{x}_e} + \alpha_{eff}^{(i)} \frac{1}{S_\mu^{(i)}} \bar{g}_{\mu,e}^{(i)} \tag{26}$$

where $\bar{g}_{\mu,e}^{(i)}$ denotes the clamped buckling gradient defined in Section 6.

Classical scalarization theory (e.g. Geoffrion [?]) establishes that minimizing a convex linear combination with strictly positive, constant weights guarantees Pareto-optimality. However, in the present framework, the normalization factors $S_C^{(i)}$ and $S_\mu^{(i)}$ are dynamically re-evaluated at every iteration, the effective weight α_{eff} is ramped, positive buckling sensitivities are clamped ($\bar{g}_{\mu,e}$), and Heaviside continuation is applied. Consequently, this iterative procedure represents a practical engineering trade-off scan across design alternatives rather than a mathematically guaranteed convex Pareto front, accounting for the potential emergence of dominated points when exploring complex multi-modal topologies.

Furthermore, the exploration parameter α does not correspond to an unconstrained physical weight: to preserve global load-bearing integrity and prevent

tensile chord disconnection, α is mapped to an effective upper bound $\alpha_{eff} \leq 0.65$ (see Section 6). Thus, setting $\alpha = 1$ does not yield a purely buckling-driven structure, but rather an optimal compromise that retains a baseline 35% compliance weighting. Inside the code interface, a dashboard allows the user to sweep between $\alpha = 0$ and $\alpha = 1$ with discrete steps of 0.1 to inspect the structural morphology as buckling resistance is progressively emphasized.

3 Sensitivity Analysis

To evaluate the minimum of λ, and therefore the max of μ, we calculate the following derivative[4]

$$\frac{\partial \mu_i}{\partial \hat{x}_e} = -\left[\phi_i^T \frac{\partial G}{\partial \hat{x}_e}\phi_i + \mu_i \phi_i^T \frac{\partial K}{\partial \hat{x}_e}\phi_i - w_i^T \frac{\partial K}{\partial \hat{x}_e} U\right] \tag{27}$$

where:

- ϕ_i: eigenvector / buckling mode shape.
- μ_i: inverse of the critical load factor.
- U: displacement vector.
- w_i: adjoint vector. It is a vector of virtual displacements, obtained by solving $w_i = K^{-1}[\phi_i^T(\nabla_U G)\phi_i]$, where ∇_U represents the gradient with respect to the displacements U.

As for the elemental matrices derivatives, we can write:

$$\frac{\partial K^e}{\partial \hat{x}_e} = \frac{\partial E_K(\hat{x}_e)}{\partial \hat{x}_e} K_0^e, \quad \frac{\partial G^e}{\partial \hat{x}_e} = \frac{\partial E_G(\hat{x}_e)}{\partial \hat{x}_e} G_0^e \tag{28}$$

while the compliance derivative is evaluated as [7]:

$$\frac{\partial C}{\partial \hat{x}_e} = -U_e^T K_0^e U_e \frac{\partial E_K(\hat{x}_e)}{\partial \hat{x}_e} \tag{29}$$

4 Updating process

For the material update at each iteration i, an Optimality Criteria (OC) scheme is employed [2]. In the presence of Heaviside projection and density filtering, the sensitivities with respect to the design variables x_e are evaluated via the discrete chain rule detailed in Section 5.

For the update rule:

$$x_e^{new} = \begin{cases} \max(x_{min}, x_e - \zeta) & \text{if } x_e B_e^\eta \leq \max(x_{min}, x_e - \zeta) \\ x_e B_e^\eta & \text{if } \max(x_{min}, x_e - \zeta) < x_e B_e^\eta < \min(1, x_e + \zeta) \\ \min(1, x_e + \zeta) & \text{if } \min(1, x_e + \zeta) \leq x_e B_e^\eta \end{cases} \tag{30}$$

with initial move limit $\zeta = 0.2$ and initial damping exponent $\eta = 1/2$ (both adaptively tightened as continuation proceeds, see Section 5). x_{min} is fixed at 0.001 to avoid numerical singularities. Finally, B_e is defined as follows:

$$B_e = \frac{-\frac{\partial \tilde{F}}{\partial x_e}}{\lambda_L \frac{\partial \tilde{V}}{\partial x_e}} \tag{31}$$

where $\frac{\partial \tilde{F}}{\partial x_e}$ and $\frac{\partial \tilde{V}}{\partial x_e}$ denote the filtered sensitivities of the aggregated objective and projected volume fraction, respectively, and λ_L is the Lagrangian multiplier.

The Lagrangian multiplier λ_L is determined through the bisection method, so that the limit on the volume is satisfied:

$$\lambda_L = 0.5(l_2 + l_1); \quad l_2^{(0)} = 10^9, \quad l_1^{(0)} = 0 \tag{32}$$

The algorithm stops when $(l_2 - l_1)/(l_2 + l_1) < 10^{-4}$, and the update follows the classic bisection procedure.

5 Projection chain rule and continuation scheme

When the smoothed Heaviside projection (16) and the spatial density filter (17) are active, the sensitivities evaluated with respect to the physical densities $\hat{x}_e$ must be mapped back to the design variables x_i via the chain rule. Differentiating (16) with respect to the intermediate filtered density $\tilde{x}_e$ yields:

$$\frac{\partial \hat{x}_e}{\partial \tilde{x}_e} = \frac{\beta \left(1 - \tanh^2(\beta(\tilde{x}_e - \eta))\right)}{\tanh(\beta\eta) + \tanh(\beta(1-\eta))} \tag{33}$$

Applying the discrete adjoint of the spatial filter (17), the filtered sensitivities of the objective and of the volume fraction with respect to x_i become:

$$\frac{\partial \tilde{F}}{\partial x_i} = \sum_{e=1}^{m} \frac{h_{ei}}{\sum_{k=1}^{m} h_{ek}} \frac{\partial \hat{x}_e}{\partial \tilde{x}_e} \frac{\partial F}{\partial \hat{x}_e}, \quad \frac{\partial \tilde{f}}{\partial x_i} = \sum_{e=1}^{m} \frac{h_{ei}}{\sum_{k=1}^{m} h_{ek}} \frac{\partial \hat{x}_e}{\partial \tilde{x}_e} \tag{34}$$

To avoid premature convergence to local minima, a step-wise continuation scheme is adopted for the projection parameter β. Starting from $\beta = 1$, its value is doubled every 20 iterations up to $\beta_{max} = 8$, and is held constant for at least the final 15 iterations before i_{max} so that the optimizer can equilibrate at a fixed projection sharpness.

At high values of β, the steep slope of the hyperbolic tangent amplifies small gradient variations by a factor proportional to β, which can trigger period-2 zig-zag oscillations in the OC update. To damp these limit cycles, the filtered sensitivity is averaged across consecutive iterations whenever β remains constant:

$$\left(\frac{\partial \tilde{F}}{\partial x_e}\right)^{(i)}_{stab} = \gamma \left(\frac{\partial \tilde{F}}{\partial x_e}\right)^{(i)} + (1-\gamma) \left(\frac{\partial \tilde{F}}{\partial x_e}\right)^{(i-1)} \tag{35}$$

with $\gamma = 0.30$ (resetting the history whenever β steps up). Simultaneously, the OC damping exponent η and the move limit ζ in (32) are progressively tightened as β increases ($\eta = 0.5$ for $\beta < 2$, $\eta = 0.3$ for $2 \leq \beta < 8$, $\eta = 0.25$ for $\beta = 8$; $\zeta = 0.20, 0.10, 0.05, 0.02$ for $\beta = 1, 2, 4, 8$, respectively).

Furthermore, because a small fraction of grey boundary elements can continue to fluctuate at high β even when the global objective has stabilized, an objective-based stopping criterion is evaluated once $\beta = \beta_{max}$ for at least $W = 10$ consecutive iterations:

$$\frac{\max_{k\in[i-W,i]} C^{(k)} - \min_{k\in[i-W,i]} C^{(k)}}{C^{(i)}} < \epsilon_C \tag{36}$$

$$\frac{\max_{k\in[i-W,i]} \lambda_1^{(k)} - \min_{k\in[i-W,i]} \lambda_1^{(k)}}{\lambda_1^{(i)}} < \epsilon_\lambda \tag{37}$$

with $\epsilon_C = 10^{-3}$ and $\epsilon_\lambda = 5 \cdot 10^{-3}$. Measuring the full window excursion ($\max - \min$) rather than a single two-point difference prevents false convergence triggers on even/odd oscillation troughs.

6 Buckling and trade-off sweep stabilization

In accordance with (18) and (19), setting $p_K = p_G = 3$ with $E_{min} = 10^{-9}E_0$ implies that in low-density elements ($\hat{x}_e \sim 10^{-2}$, where $\hat{x}_e^3 \gg 10^{-9}$) the stiffness-to-stress ratio $E_G(\hat{x}_e)/E_K(\hat{x}_e)$ remains close to unity. Under these conditions, the eigenvalue solver can capture localized pseudo-buckling modes confined within the void regions. To suppress spurious void modes without altering the cubic penalization in solid bars ($\hat{x}_e \to 1$), a smooth rational cutoff function $\psi(\hat{x}_e)$ is introduced in the geometric stiffness interpolation:

$$\psi(\hat{x}_e) = \frac{\hat{x}_e^3}{\hat{x}_e^3 + x_0^3}, \quad E_G(\hat{x}_e) = E_0 \hat{x}_e^3 \psi(\hat{x}_e) \tag{38}$$

where $x_0 = 0.10$ is the void cutoff threshold. For $\hat{x}_e \ll x_0$, $E_G(\hat{x}_e) \propto \hat{x}_e^6$, decoupling low-density elements from the stability spectrum. The exact analytical derivative used in (28) becomes:

$$\frac{\partial E_G(\hat{x}_e)}{\partial \hat{x}_e} = 3E_0 \hat{x}_e^2 \psi(\hat{x}_e)\,(2 - \psi(\hat{x}_e)) \tag{39}$$

Moreover, as buckling-reinforced members evolve, the first n_{Eig} eigenvalues frequently coalesce, causing abrupt mode switching if only μ_1 is differentiated. In the implemented solver, the first $n_{Eig} = 6$ modes $\mu_m = 1/\lambda_m$ (normalized such that $\phi_m^T K \phi_m = 1$) are computed by passing the sparse LU factorization of $[K]$ as a linear inverse operator to ARPACK, scaled by $E_0 t$ to ensure exact scale invariance with respect to Young's modulus and thickness. The modal gradients (27) are then combined via Kreisselmeier-Steinhauser (KS) weights:

$$w_m^{KS} = \frac{\exp\left(\rho_{KS}(\mu_m - \mu_1)\right)}{\sum_{k=1}^{n_{Eig}} \exp\left(\rho_{KS}(\mu_k - \mu_1)\right)}, \quad \frac{\partial \mu_{KS}}{\partial \hat{x}_e} = \sum_{m=1}^{n_{Eig}} w_m^{KS} \frac{\partial \mu_m}{\partial \hat{x}_e} \tag{40}$$

with aggregation parameter $\rho_{KS} = 20$.

In tensile members and near the loaded node, $\frac{\partial \mu_{KS}}{\partial \hat{x}_e}$ can assume positive values. When $\alpha \to 1$, an unclamped positive buckling gradient makes the aggregated search direction non-negative in critical structural regions, driving $B_e \to 0$ in (31) and eroding the primary tension chord. To preserve the tensile load path, positive buckling sensitivities are clamped to zero prior to aggregation:

$$\bar{g}_{\mu,e}^{(i)} = \min\left(0, \frac{\partial \mu_{KS}^{(i)}}{\partial \hat{x}_e}\right) \tag{41}$$

As introduced in Section 2, evaluating the normalization factors $S_C^{(i)}$ and $S_\mu^{(i)}$ via the 95-th percentile (P_{95}) avoids gradient distortion from localized stress concentrations, while the user weight $\alpha \in [0, 1]$ is mapped to the effective weight $\alpha_{eff}^{(i)}$ ramped over the first $N_{ramp} = 15$ iterations:

$$\alpha_{eff}^{(i)} = 0.65\,\alpha \min\left(1, \frac{i}{N_{ramp}}\right) \tag{42}$$

retaining a minimum 35% compliance contribution so that global stiffness connectivity is never lost at the upper end of the trade-off sweep.

7 Stress recovery and post-processing

Once the optimization has converged, the local plane-stress tensor is reconstructed at the centroid of each element from the final nodal displacement vector u_e:

$$\sigma_e = \begin{bmatrix} \sigma_x \\ \sigma_y \\ \tau_{xy} \end{bmatrix} = E_0[C_0][B_0]u_e \tag{43}$$

From the Cartesian components, the in-plane principal stresses $\sigma_{I,II}$ and the signed dominant principal stress σ_{signed} are evaluated as:

$$\sigma_{I,II} = \frac{\sigma_x + \sigma_y}{2} \pm \sqrt{\left(\frac{\sigma_x - \sigma_y}{2}\right)^2 + \tau_{xy}^2}, \quad \sigma_{signed} = \begin{cases} \sigma_I & \text{if } |\sigma_I| > |\sigma_{II}| \\ \sigma_{II} & \text{otherwise} \end{cases} \tag{44}$$

In the post-processing interface, elements below the solid density threshold ($\hat{x}_e < 0.40$) are masked out, allowing a direct visual identification of tensile chords ($\sigma_{signed} > 0$) and compressed struts ($\sigma_{signed} < 0$) across the Pareto frontier.

References

[1] Ferrari, F., & Sigmund, O. (2020). *Revisiting topology optimization with buckling constraints.* Structural and Multidisciplinary Optimization, 61(4), 1401-1415.

[2] Sigmund, O. (2001). *A 99 line topology optimization code written in Matlab.* Structural and multidisciplinary optimization, 21(2), 120-127.

[3] Marler, R. T., & Arora, J. S. (2004). *Survey of multi-objective optimization methods for engineering.* Structural and multidisciplinary optimization, 26(6), 369-395.

[4] Sigmund, O. (1997). *On the design of compliant mechanisms using topology optimization.* Mechanics of structures and machines, 25(4), 493-524.

[5] Neves, M. M., Rodrigues, H., & Guedes, J. M. (1995). *Generalized topology design of structures with a buckling load criterion.* Structural Optimization, 10(2), 71-78.

[6] Bendsøe, M. P., & Sigmund, O. (2003). *Topology optimization: theory, methods, and applications.* Springer Science & Business Media.

[7] F. Ferrari, O. Sigmund, and J. K. Guest, "Topology optimization with linearized buckling criteria in 250 lines of Matlab," *Structural and Multidisciplinary Optimization*, vol. 63, pp. 3045–3066, 2021. DOI: 10.1007/s00158-021-02854-x.

[8] F. Wang, B. Lazarov, and O. Sigmund, "On projection methods, convergence and robust formulations in topology optimization," *Structural and Multidisciplinary Optimization*, vol. 43, no. 6, pp. 767–784, 2011.

[9] I. Das and J. E. Dennis, "A closer look at drawbacks of minimizing weighted sums of objectives for Pareto set generation in multicriteria optimization problems," *Structural Optimization*, vol. 14, no. 1, pp. 63–69, 1997.

[10] A. Messac, A. Ismail-Yahaya, and C. A. Mattson, "The normalized normal constraint method for generating the Pareto frontier," *Structural and Multidisciplinary Optimization*, vol. 25, no. 2, pp. 86–98, 2003.