

# **PROGETTO BASI DI DATI**

## **NEGOZIO ELETTRONICO DI VIDEOGIOCHI**

- Spolaor Riccardo (864877) -

## DESCRIZIONE

### NEGOZIO ELETTRONICO DI VIDEOGIOCHI:


Base di dati contenente:

- Videogiochi (titolo, console, prezzo, quantità disponibile in magazzino);
- Utenti (nome e cognome, indirizzo, telefono, login e password);
- Ordini (utente, titoli ordinati, data, tipo di pagamento);


Sito sviluppato in PhpStorm che permette di fare:

- Accesso senza login:
  - Accesso al catalogo dei videogiochi;
  - Ricerca dei videogiochi dal catalogo;
  - Registrazione di un nuovo utente;
  - Login di un utente o amministratore;
  - Aggiunta prodotti al carrello che rimane salvato in sessione anche dopo il login utente.
- Accesso con login utente:
  - Aggiunta prodotti al carrello;
  - Ordine dei prodotti inseriti nel carrello;
  - Visualizzazione dei propri ordini;
  - Cancellazione dei propri ordini.
- Accesso con login di amministratore:
  - Amministrazione utenti (ricerca utenti; modifica dei dati; cancellazione; registrazione nuovi utenti, amministrazione ordini di un utente specifico);
  - Amministrazione admin (ricerca admin; modifica dei dati; promozione utente ad admin; rimozione poteri di amministratore ad un admin);
  - Amministrazione prodotti: (ricerca prodotti; modifica dei dati; cancellazione prodotto; registrazione nuovo prodotto);
  - Amministrazione ordini: (ricerca ordini; modifica quantità o rimozione di prodotti dell'ordine; eliminazione ordini).

## SCHEMA AD OGGETTI



## SCHEMA RELAZIONALE



## CODICE CREAZIONE DATABASE (gamestore)

```
CREATE TABLE user_table (  
    login TEXT PRIMARY KEY NOT NULL,  
    password TEXT NOT NULL,  
    name TEXT NOT NULL,  
    surname TEXT NOT NULL,  
    adress TEXT NOT NULL,  
    phone TEXT,  
    admin BOOLEAN DEFAULT false  
);
```

```
CREATE TABLE videogame (  
    id INTEGER PRIMARY KEY NOT NULL,  
    title TEXT NOT NULL,  
    price FLOAT CHECK (price >=0),  
    console TEXT NOT NULL,  
    amount INTEGER CHECK (amount >= 0)  
);
```

```
CREATE TABLE order_table (  
    id INTEGER PRIMARY KEY NOT NULL,  
    date DATE NOT NULL,  
    payment TEXT NOT NULL,  
    userid TEXT REFERENCES user_table (login) ON UPDATE CASCADE ON DELETE CASCADE NOT NULL  
);
```


```
CREATE TABLE game_order (  
    gameid INTEGER REFERENCES videogame (id) NOT NULL,  
    orderid INTEGER REFERENCES order_table (id) ON DELETE CASCADE NOT NULL,  
    copies INTEGER NOT NULL CHECK (copies >= 1),  
    PRIMARY KEY (gameid, orderid)  
);
```

```
INSERT INTO user_table (login, password, name, surname, adress, phone, admin) VALUES (  
    'riccardo_admin',  
    'riccardo_admin',  
    'Riccardo',  
    'Spolaor',  
    'Via F. Petrarca 2, Spinea (VE)',  
    '3391007760',  
    true  
);
```

```
INSERT INTO user_table (login, password, name, surname, adress) VALUES (  
    'super_mario',  
    'mustache',  
    'Mario',  
    'Mario',  
    'Via dei Funghi 10, Regno dei Funghi'  
);
```

```
INSERT INTO videogame (id, title, price, console, amount) VALUES (  
    1,  
    'God of War',  
    74.98,  
    'PS4',  
    30  
);
```

## DIAGRAMMA DEL SITO (gamestore)



## CODICE

index.php

```
<?php
include_once "..\config\configurations.php";

if (isset($_SESSION['user'])&&$_SESSION['user'] == 'admin') {
    header ('Location: ..\admin\admin_panel.php');
}
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <?php
        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }
        $query = "
        SELECT *
        FROM videogame
        WHERE console = 'Xbox One'
        GROUP BY id
        ORDER BY id DESC
        LIMIT 4
        ";
        $statement = $database_handler->prepare($query);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $xboxone_result = $statement->fetchAll(PDO::FETCH_ASSOC);

        $query = "
        SELECT *
        FROM videogame
        WHERE console = 'PS4'
        GROUP BY id
        ORDER BY id DESC
        LIMIT 4
        ";
        $statement = $database_handler->prepare($query);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $ps4_result = $statement->fetchAll(PDO::FETCH_ASSOC);

        $query = "
        SELECT *
```

```

FROM videogame
WHERE console = 'Switch'
GROUP BY id
ORDER BY id DESC
LIMIT 4
";
$stmt = $db_handler->prepare($query);
$db_handler->beginTransaction();
$stmt->execute();
$db_handler->commit();
$switch_result = $stmt->fetchAll(PDO::FETCH_ASSOC);

$query = "
SELECT *
FROM videogame
WHERE console = 'PC'
GROUP BY id
ORDER BY id DESC
LIMIT 4
";
$stmt = $db_handler->prepare($query);
$db_handler->beginTransaction();
$stmt->execute();
$db_handler->commit();
$pc_result = $stmt->fetchAll(PDO::FETCH_ASSOC);

$db_handler = null;
?>

<section class="main_content">
    <br>
    <br>
    <br>

    <table class = 'games_table' align="center" style="text-align:
center">

        <caption id = 'ps_caption'>
            ULTIME USCITE PS4
            
        </caption>

        <tr>
            <?php

                $result = $ps4_result;

                if ($result != null):
                    foreach ($result as $row): ?>
                        <td>
                            "
                            >

                            <br>
                            <br>

                            <?php echo $row['title'] . ' - ' . $row['console']; ?>

```



```

        <br>

        <?php echo '€ ' . $row['price'] . ' - ' . $row['amount'] > 0 ? print 'Disponibile' : print 'Non
Disponibile' ?>

        <br>
        <br>

        <?php if ($row['amount'] > 0) : ?>
        <a href="../../cart/cart_action.php?id=<?php echo
$row['id'] ?>&action=add&amount=1">
            <button class="cart_add_button">
                ACQUISTA ORA!
            </button>
        </a>

        <?php else: ?>
        <b style="color: darkred;">
            AL MOMENTO NON DISPONIBILE
        </b>
        <?php endif: ?>

    </td>
    <?php endforeach;
endif;?>
</tr>
</table>

<br>
<br>

<table class="games_table" align="center" style="text-align:
center">
    <caption id="xbox_caption">
        ULTIME USCITE Xbox One
        
    </caption>

    <tr>
    <?php
$result = $xboxone_result;

    if ($result != null):
        foreach ($result as $row): ?>
            <td>
                "
                >

                <br>
                <br>

                <?php echo $row['title'] . ' - ' . $row['console']; ?>

                <br>

                <?php echo '€ ' . $row['price'] . ' - ' . $row['amount'] > 0 ? print 'Disponibile' : print 'Non

```

```

Disponibile' ?>

        <br>
        <br>

        <?php if ($row['amount']>0) : ?>

            <a href="../../../cart/cart_action.php?id=<?php echo
$row['id']?>&price=<?php echo $row['price']?>&action=add&amount=1">

                <button class="cart_add_button">
                    ACQUISTA ORA!
                </button>
            </a>

            <?php else: ?>
            <b style="color: darkred;">
                AL MOMENTO NON DISPONIBILE
            </b>
            <?php endif; ?>

        </td>

        <?php endforeach;
    endif;?>

</tr>
</table>

<br>
<br>

<table class='games_table' align="center" style="text-align:
center">

    <caption id = 'nintendo_caption'>
        ULTIME USCITE Switch
        
    </caption>

    <tr>
        <?php
        $result = $switch_result;
        if ($result != null):
            foreach ($result as $row): ?>
                <td>
                    "
                    >

                    <br>
                    <br>

                    <?php echo $row['title'].' - '.$row['console']; ?>

                    <br>

                    <?php echo '€ '.$row['price'].' - ';
                    $row['amount']>0 ? print 'Disponibile' : print 'Non

```

```

Disponibile' ?>

        <br>
        <br>

        <?php if ($row['amount']>0) : ?>
        <a href="../cart/cart_action.php?id=?php echo
$row['id']?>&price=?php echo $row['price']?>&action=add&amount=1">
            <button class="cart_add_button">
                ACQUISTA ORA!
            </button>
        </a>

        <?php else: ?>
        <b style="color: darkred;">
            AL MOMENTO NON DISPONIBILE
        </b>
        <?php endif; ?>

    </td>

    <?php endforeach;
endif;?>

</tr>
</table>

<br>
<br>

<table class="games_table" align="center" style="text-align:
center">

    <caption id="pc_caption">
        ULTIME USCITE PC
        
    </caption>

    <tr>
    <?php
$result = $pc_result;
if ($result != null):
    foreach ($result as $row): ?>
        <td>
            <img height="200"
                src=?php file_exists("../web/images/" .
$row['id'] . ".jpg") ? print "../web/images/" . $row['id'] . ".jpg" :
                print '../web/images/NA.jpg'; ?>
            >

            <br>
            <br>

            <?php echo $row['title'].' - '.$row['console']; ?>

            <br>

            <?php echo '€ '.$row['price'].' - ' ;

            $row['amount']>0 ? print 'Disponibile' : print 'Non
Disponibile' ?>

```

```

        <br>
        <br>

        <?php if ($row['amount']>0) : ?>
        <a href=" ../cart/cart_action.php?id=<?php echo
$row['id']?>&price=<?php echo $row['price']?>&action=add&amount=1">
            <button class="cart_add_button">
                ACQUISTA ORA!
            </button>
        </a>

        <?php else: ?>
        <b style="color: darkred;">
            AL MOMENTO NON DISPONIBILE
        </b>
        <?php endif; ?>

    </td>
    <?php endforeach;
endif;?>
</tr>

</table>

<br>
<br>
<br>
<br>
<br>

</section>

<?php
include_once '..\templates\footer.php';
?>

</body>

</html>

```

## configurations.php

```
<?php

if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
    die("Non autorizzato");
}

include_once '..\lib\cart.php';

ob_start();
session_start();

$dns =
'pgsql:host=localhost;port=5432;dbname=gamestore;user=postgres;password=Alpha94'
;

?>

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML//EN">

<html>

    <head>

        <meta http-equiv="content-type" content="text/html" charset="UTF-8">

        <title> Negozio Giochi Online </title>

        <link rel="stylesheet" type = "text/css" href="../../web/css/style.css" />

        <script type="text/javascript">
            window.onload = function cartItems() {
                var cart_items = null;
                cart_items = <?php
                    $cart= new Cart();
                    if (isset ($_SESSION['cart']))
                        $cart = $_SESSION['cart'];
                    if ($cart->getTotalItems() != 0) {
                        echo $cart -> getTotalItems();
                    }
                ?>;
                if (cart_items != null) {
                    document.getElementById('cart_items').innerHTML =
cart_items;
                }
            }
        </script>

    </head>

</html>
```

## cart.php

```
<?php

if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
    die("Non autorizzato");
}

class Cart {
    protected $cart_content = array();
    protected $cart_total = array();

    public function __construct()
    {
        $this->cart_content = array ();
        $this->cart_total = array('total_price' => 0, 'total_items' => 0);
    }

    public function getCartContent()
    {
        return $this->cart_content;
    }

    public function getTotalItems () {
        return $this -> cart_total['total_items'];
    }

    public function getTotalPrice () {
        return $this->cart_total['total_price'];
    }

    public function addItem ($item, $amount) {
        if (isset($this->cart_content[$item['id']])) {
            $this->cart_content[$item['id']]['quantity'] += $amount;
        }
        else
            $this->cart_content[$item['id']] = array (
                'title' => $item['title'],
                'price' => floatval ($item['price']),
                'console' => $item['console'],
                'quantity' => $amount
            );
        $this->cart_total['total_items'] += $amount;
        $this->cart_total['total_price'] += $item['price'] * $amount;
    }

    public function removeItem ($id, $amount) {
        if (isset($this->cart_content[$id])) {
            if ($amount == $this->cart_content[$id]['quantity']) {
                $this->cart_total['total_price'] -= ($this->
                cart_content[$id]['price'] * $amount);
                unset($this->cart_content[$id]);
            }
            elseif ($amount < $this->cart_content[$id]['quantity']) {
                $this->cart_total['total_price'] -= ($this->
```

```

>cart_content[$id]['price'] * $amount);
    $this->cart_content[$id]['quantity'] -= $amount;
    }
    else {
        return;
    }
    $this->cart_total['total_items'] -= $amount;

    }
}

    public function destroy () {
        $this->cart_content = $this->cart_content = array('total_price' => 0,
'total_items' => 0);
    }
}

```

## cart\_action.php

```
<?php
include_once "..\config\configurations.php";

if (isset($_SESSION['user']) && $_SESSION['user'] == 'admin') {
    header ('Location: ..\admin\admin_panel.php');
}

try {
    $database_handler = new PDO ($dns);
    $database_handler->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
} catch (PDOException $e) {
    echo $e->getMessage();
    die();
}

if (!isset($_SESSION['cart']))
    $_SESSION['cart'] = new Cart();

$temp_cart = $_SESSION['cart'];

if (isset($_GET['id']) && isset($_GET['action']) && isset($_GET['amount'])) {
    switch ($_GET['action']) {
        case ('add'): {
            $query = "
                SELECT *
                FROM videogame
                WHERE id = :id
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':id', $_GET['id']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $result = $statement->fetchAll(PDO::FETCH_ASSOC);
            $database_handler = null;
            $item = array();
            foreach ($result as $row) {
                $item = array('id' => $row['id'], 'title' => $row['title'],
'price' => $row['price'], 'console' => $row['console']);
            }
            $temp_cart->addItem($item, $_GET['amount']);
            break;
        }

        case ('remove'): {
            $temp_cart->removeItem($_GET['id'], $_GET['amount']);
            if ($temp_cart->getTotalItems() == 0) {
                $temp_cart = null;
            }
            break;
        }
    }
}
```



```

        default: {break;}
    }
}

$_SESSION['cart'] = $temp_cart;

header('Location: cart_view.php');

```

## cart\_view.php

```

<?php
include_once "..\config\configurations.php";

if (isset($_SESSION['user']) && $_SESSION['user'] == 'admin') {
    header('Location: ../admin/admin_panel.php');
}

if (!isset($_SESSION['cart']))
    header('Location: ../index/index.php')
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <section class="main_content">
            <br>
            <br>
            <br>

            <div align="center">

                <section class="panel" align="center" style="text-align:
center">

                    <?php if ($cart->getCartContent() != null): ?>

                    <div class = 'panel_title' id = 'users_title'>
                        IL MIO CARRELLO <br>
                        <?php echo 'Prodotti: ' . $cart -> getTotalItems();?>
                        <br>
                        <?php echo 'Totale: €' . $cart -> getTotalPrice();?>
                    </div>

                    <br>
                    <br>

                    <table align="center" class = 'box' width="100%" id =
'users_table'>

                        <tr>
                            <th></th>
                            <th>Prodotto</th>
                            <th>Quantità</th>
                            <th>Elimina</th>

```

```

        </tr>

        <?php foreach ($cart->getCartContent() as $item=>$row)
:??>
        <tr>
            <td class="image_cell">
                "
                >
            </td>
            <td>
                <?php echo $row['title']; ?> <br>
                <?php echo $row['console'] ?>
                € <?php echo
floatval($row['price'])*intval($row['quantity']); ?>
            </td>
            <td>
                <form action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST">
                    <br>
                    <label>
                        <input hidden name="current_amount"
value="<?php echo $row['quantity']; ?>" />
                        <input type="number" min = '0'
name="new_amount" value="<?php echo $row['quantity'];?>" />
                    </label>
                    <button type="submit" class =
'<?php echo $row['console'];?>' name="edit_amount" value="<?php echo $item;?>">
                        
                    </button>
                </form>
            </td>
            <td>
                <form action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST">
                    <input hidden name="amount" value="<?php
echo $row['quantity']; ?>" />
                    <button type="submit" class =
'<?php echo $row['console'];?>' name="remove_game" value="<?php echo $item;?>">
                        <br>
                        
                    </button>
                </form>
            </td>
        </tr>
        <?php endforeach; ?>

        <caption align="bottom" style="margin-top: 20px; text-
align: right; padding-right: 10px">

            <form action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST" style="display: inline">
                <button type="submit" name="clear">
                    
                </button>
            </form>
            Svuota

```

```

        </button>
    </form>

    <a href="../../../orders/add_order.php">
        <button type="button">
            
            Ordina
        </button>
    </a>
</caption>

</table>

<?php endif; ?>

<br>
<br>

<?php

    if (isset($_POST['edit_amount'])) {
        if ((($_POST['new_amount'] - $_POST['current_amount']) >=
0) {
            header('Location: cart_action.php?id=' .
$_POST['edit_amount'] .
                '&action=add&amount=' . ($_POST['new_amount'] -
$_POST['current_amount']));
        }
        else {
            header('Location: cart_action.php?id=' .
$_POST['edit_amount'] .
                '&action=remove&amount=' . ($_POST['current_amount'] - $_POST['new_amount']));
        }
    }

    if (isset($_POST['remove_game'])) {
        header('Location: cart_action.php?id=' .
$_POST['remove_game'] .
                '&action=remove&amount=' . ($_POST['amount']));
    }

    if (isset($_POST['clear'])) {
        unset($_SESSION ['cart']);
        header('Refresh: 0');
    }

    ?>
</section>

</div>

</section>

<?php
include_once '../../../templates/footer.php';
?>

</body>
</html>

```

## footer.php

```
<?php
if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
    die("Non autorizzato");
}
?>

<html>

    <body>

        <button onclick="topFunction()" id = 'top_button' style="display: none">
            TOP
        </button>

        <script type="text/javascript">
            window.onload = function () {
                if (document.body.scrollTop > 20) {
                    document.getElementById('top_button').style.display =
'block';
                }

                else {
                    document.getElementById('top_button').style.display =
'none';
                }
            }

            function topFunction() {
                document.body.scrollTop = 0;
            }
        </script>

        <footer>
            <p align="center" >
                © 2018 Riccardo Spolaor. <br>
                PlayStation © Sony Corporation , Xbox © Microsoft, Nintendo
                Switch © Nintendo. <br>
                All icons © their respective owners.
            </p>
        </footer>

    </body>

</html>
```

## header.php

```
<?php
if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
    die("Non autorizzato");
}
?>

<html>

    <body>

        <header class="main_header">

            <div class = "text">
                <?php if (isset ($_SESSION['username'])) : ?>

                    <?php if ($_SESSION['user'] == 'user'): ?>

                        
                        <b>Benvenuto <?php echo $_SESSION['username']; ?></b>

                        <a class = 'util_link' href="../../orders/orders.php">
                            
                            I Miei Ordini
                        </a>

                    <?php else: ?>

                        
                        <b>Benvenuto <?php echo $_SESSION['username']; ?></b>

                    <?php endif; ?>

                    <a class = 'util_link' href="../../utils/logout.php">
                        
                        Log Out
                    </a>

                    <?php else : ?>
                        <a class = 'util_link' href="../../utils/login.php">
                            
                            Login
                        </a>
                        <a class = 'util_link' href="../../utils/sign_up.php">
```

```

                
                Registrati
            </a>
        <?php endif; ?>

        <?php if ((isset($_SESSION['user'])&&
$_SESSION['user']!= 'admin') || !isset($_SESSION['user'])) :

            if (isset($_SESSION['cart'])) : ?>
                <a class = 'util_link' href="../../cart/cart_view.php" >
                    
                    <div id="cart_items"></div>
                </a>

                <?php else: ?>
                <a id = 'inactive_cart'>
                    
                </a>
                <?php endif; ?>

            <?php endif; ?>
        </div>
    </header>

    <?php if ((isset($_SESSION['user'])&& $_SESSION['user']!= 'admin') ||
!isset($_SESSION['user'])) : ?>
        <header class="second_header">
            <form action="<?php echo htmlentities($_SERVER['PHP_SELF']); ?>"
method="POST">
                <table>
                    <tr>
                        <td>
                            <a href="../../index/index.php"></a>
                        </td>

                        <td>
                            <label>
                                <input name='inputSearch' type="text"/>
                            </label>
                        </td>

                        <td>
                            <button type="submit" name='q'>Cerca</button>
                        </td>

                        <td width="100%" align="right">
                            <a class = 'console_link'
href="../../videogames/videogames.php?q=PS4">
                                <table class = 'console_table'>
                                    <tr>
                                        <td>
                                            &nbsp;
                                        </td>
                                        <td>
                                            &nbsp;   PS4 &nbsp;   &nbsp;   

```



```

        ?>

    </body>

</html>

```

## login.php

```

<?php
include_once "..\config\configurations.php";

if (isset($_SESSION['username'])) {
    if ($_SESSION['user'] == 'user') {
        header("Location: ..\index\index.php");
    }
    else {
        header("Location: ..\admin\admin_panel.php");
    }
}
?>

<html>

    <body>
        <?php
            include_once '../templates/header.php';
            ?>

            <section class= "main_content">

                <div class="container">

                    <form action = "<?php echo htmlentities ($_SERVER['PHP_SELF']);
?>" method = "POST">

                        <label for="username">
                            Username:
                        </label>
                        <br>

                        <input id = 'username' required maxlength="20" type="text"
name = "username" />
                        <br>
                        <br>

                        <label for="password">
                            Password:
                        </label>
                        <br>

                        <input id = 'password' required maxlength="20"
type="password" name = "password" />
                        <br>

```



```

        <br>

        <button type="submit" name = "submit">
            Login
        </button>

        <span class = "info">
            Non possiedi un account?<a href="sign_up.php">
Registrati!</a>
        </span>

    </form>

    <div class="error_messages">
    <?php

        if (!empty ($_POST['username']) && !empty ($_POST['password']))
        && isset ($_POST['submit'])) {

            try {
                $database_handler = new PDO ($dns);
                $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
            } catch (PDOException $e) {
                echo $e->getMessage();
                die();
            }

            $query = "
                SELECT *
                FROM user_table
                WHERE login = :username AND password = :password
            ";

            $statement = $database_handler->prepare($query);
            $statement -> bindParam (":username", $_POST['username']);
            $statement -> bindParam (":password", $_POST['password']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $result = $statement->fetch(PDO::FETCH_OBJ);
            if ($result) {
                $_SESSION['username'] = $_POST['username'];
                if ($result->admin == 'true') {
                    $_SESSION['user'] = 'admin';
                    if (isset($_SESSION['cart']))
                        unset ($_SESSION['cart']);
                    header("Location: ../admin/admin_panel.php");
                }
                else {
                    $_SESSION['user'] = 'user';
                    header("Location: ../index/index.php");
                }
            }
            else {
                echo "Login o password errati.";
            }
            $database_handler = null;
        }
    ?>
    </div>

```

```
        </div>

        <br>
        <br>

    </section>

    <?php
    include_once '..\templates\footer.php';
    ?>
</body>
</html>
```

### logout.php

```
<?php

session_start();

unset($_SESSION['username']);
unset($_SESSION['user']);
unset($_SESSION['cart']);

session_gc();
session_destroy();

header('Location: ..\Utils\login.php');
```

## sign\_up.php

```
<?php
include_once "..\config\configurations.php";

if (isset($_SESSION['username'])) {
    if ($_SESSION['user'] == 'user') {
        header('Location: ..\index\index.php');
    }
    else {
        header('Location: ..\admin\admin_panel.php');
    }
}
?>

<html>

    <body>

        <?php
        include_once '../templates/header.php';
        ?>

        <section class= "main_content">

            <div class="container">
                <form action = "<?php echo htmlentities ($_SERVER['PHP_SELF']);
?>" method = "POST">
                    <table>
                        <tr>
                            <td>
                                <label for="name">
                                    Nome: <b style="color: darkred">*</b>
                                </label>
                            </td>
                            <td>
                                <label for="surname">
                                    Cognome: <b style="color: darkred">*</b>
                                </label>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                <input id = 'name' required maxlength="20"
```

```

type="text" name = "name" />
        <br>
        <br>
    </td>
    <td>
        <input id = 'surname' required maxlength="20"
type="text" name = "surname" />
        <br>
        <br>
    </td>
</tr>

<tr>
    <td>
        <label for="adress">
            Indirizzo: <b style="color: darkred">*</b>
        </label>
    </td>
    <td>
        <label for="phone">
            Telefono:
        </label>
    </td>
</tr>
<tr>
    <td>
        <input id = 'adress' required maxlength="100"
type="text" name = "adress" />
        <br>
        <br>
    </td>
    <td>
        <input id = 'phone' maxlength="10" type="tel"
name = "phone" />
        <br>
        <br>
    </td>
</tr>

<tr>
    <td>
        <label for="username">
            Username: <b style="color: darkred">*</b>
        </label>
    </td>
    <td>
        <label for="repeatUsername">
            Ripeti Username: <b style="color:
darkred">*</b>
        </label>
    </td>
</tr>
<tr>
    <td>
        <input id = 'username' required maxlength="20"
type="text" name = "username" />
        <br>
        <br>
    </td>
    <td>
        <input id = 'repeatUsername' required
maxlength="20" type="text" name = "repeatUsername" />

```

```

        <br>
        <br>
    </td>
</tr>
<tr>
    <td>
        <label for="password">
            Password: <b style="color: darkred">*</b>
        </label>
    </td>
    <td>
        <label for="repeatPassword">
            Ripeti Password: <b style="color:
darkred">*</b>
        </label>
    </td>
</tr>
<tr>
    <td>
        <input id = 'password' required maxlength="20"
type="password" name = "password" />
        <br>
        <br>
    </td>
    <td>
        <input id = 'repeatPassword' required
maxlength="20" type="password" name = "repeatPassword" />
        <br>
        <br>
    </td>
</tr>
<tr>
    <td>
        <button class = "confirmButton" type="submit" name =
"submit">Registrati</button>
    </td>
    <td>
        <span class = "info">
            Hai già un account?<a href="login.php">
Login!</a>
        </span>
    </td>
</tr>
</table>
</form>

<div class="error_messages">
    * Campi Obbligatori.
</div>

<div class="error_messages">
<?php
if (!empty($_POST['name']) && !empty($_POST['surname']) &&
    !empty($_POST['adress']) && !empty($_POST['username']) &&
    !empty($_POST['repeatUsername']) &&
!empty($_POST['password']) &&
    !empty($_POST['repeatPassword']) && isset
($_POST['submit'])) {

    if ($_POST['username'] == $_POST['repeatUsername'] &&
$_POST['password'] == $_POST['repeatPassword']) {

```

```

        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }
        try {
            $query = "
INSERT INTO user_table (name, surname, adress,
phone, login, password, admin)
VALUES (:name, :surname, :adress, :phone,
:username, :password, false)
";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':name', $_POST['name']);
            $statement->bindParam(':surname',
$_POST['surname']);
            $statement->bindParam(':adress', $_POST['adress']);
            $statement->bindParam(':phone', $_POST['phone']);
            $statement->bindParam(':username',
$_POST['username']);
            $statement->bindParam(':password',
$_POST['password']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $result = $statement->fetch();
            $_SESSION['username'] = $_POST['username'];
            $_SESSION['user'] = 'user';
            header("Refresh: 4; url = ../index/index.php");
            echo 'Registrazione effettuata';
            $database_handler = null;
        } catch (PDOException $e) {
            echo "index non disponibile";
            $database_handler = null;
        }
    }

    else
        if ($_POST['username'] != $_POST['repeatUsername'] &&
$_POST['password'] != $_POST['repeatPassword']) {
            echo 'Inserire stesso Username e stessa Password';
        }

        else {
            if ($_POST['username'] != $_POST['repeatUsername'])
            {
                echo 'Inserire stesso Username';
            }
            else {
                echo 'Inserire stessa Password';
            }
        }
    }

    ?>
</div>

</div>

```

```

        <br>
        <br>

    </section>

    <?php
    include_once '..\templates\footer.php';
    ?>

</body>

</html>

```

### videogames.php

```

<?php
include_once "..\config\configurations.php";

if (isset($_SESSION['user']) && $_SESSION['user'] == 'admin') {
    header('Location: ../admin/admin_panel.php');
}

?>

<html>

    <body>

        <?php
        include_once "../templates/header.php";
        ?>

        <?php
        $id = null;
        if (!empty($_GET['q']))
            $id = strtoupper($_GET['q']);
        ?>

        <?php
        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }

        if ($id) {
            $query = "
                                SELECT *
                                FROM videogame
                                WHERE upper(title) LIKE :input OR upper(console) LIKE
:input
                                GROUP BY id
                                ORDER BY id DESC

```

```

        ";
        $statement = $database_handler->prepare($query);
        $statement->bindValue(":input", "%$id%", PDO::PARAM_STR);
    }
    else {
        $query = "
            SELECT *
            FROM videogame
            GROUP BY id
            ORDER BY id DESC
        ";
        $statement = $database_handler->prepare($query);
    }

    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetchAll(PDO::FETCH_ASSOC);
    $database_handler = null;
    ?>

<section class="main_content">

    <br>
    <br>
    <br>

    <div align="center">

        <section class="panel" align="center" style="text-align:
center">

            <div class = 'panel_title' id = 'users_title'>
                <?php if ($id): ?>
                    <?php echo count($result); ?> risultati per: '<?php echo
$id?>'

                <?php else: ?>
                    Catalogo Videogiochi
                <?php endif; ?>
            </div>

            <?php if ($result != null): ?>
                <table align="center" class = 'box' width="100%" id =
'users_table'>

                    <?php foreach ($result as $row):?>
                        <tr>
                            <td class="image_cell">
                                "
                                >
                            </td>

                            <td>
                                <?php echo $row['title']; ?>
                                <br>
                                <br>
                                <?php echo $row['console']; ?>
                                <br>
                                <?php echo $row['amount']>0 ? 'Disponibili

```



```

ancora: '.$row['amount'] : 'Prodotto non disponibile'; ?>
        </td>

        <td style= "text-align: center">

            <?php if ($row['amount']>0) : ?>
                <a href=" ../cart/cart_action.php?id=<?php echo
$row['id'];?>&price=<?php echo $row['price'];?>&action=add&amount=1">
                    <button class="cart_add_button">
                        ACQUISTA A € <?php echo $row['price'];
?>

                    </button>
                </a>

                <?php else: ?>
                <b style="color: darkred">
                    PRODOTTO NON DISPONIBILE
                </b>
                <?php endif; ?>

            </td>
        </tr>
        <?php endforeach; ?>
    </table>

    <?php else: ?>
        <div class="error_messages">La ricerca di '<?php echo $id?>'
non ha prodotto alcun risultato.</div>
        <?php endif; ?>

    </section>

</div>

</section>

<?php
include_once ' ../templates/footer.php';
?>
</body>

</html>

```

orders.php

```
<?php

include_once "..\config\configurations.php";

if (isset($_SESSION['username'])) {
    if ($_SESSION['user'] == 'admin') {
        header ('Location: ..\admin\admin_panel.php');
    }
}
else
    header ('Location: ..\utils\login.php')
?>

<html>

    <body>
        <?php
            include_once '../templates/header.php';
            ?>

            <?php
            try {
                $database_handler = new PDO ($dns);
                $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
            } catch (PDOException $e) {
                echo $e->getMessage();
                die();
            }

            $idOrders = array();

            $query = "
            SELECT *
            FROM order_table
            WHERE  userid = :username
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':username', $_SESSION['username']);
```

```

        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->fetchAll(PDO::FETCH_ASSOC);

        foreach ($result as $row) {
            $idOrders[$row['id']] = array ('date' => $row['date'], 'payment' =>
$row['payment'], 'games' => array());
            $query = "
            SELECT v.*, g_o.copies
            FROM game_order g_o JOIN videogame v on g_o.gameid = v.id
            WHERE g_o.orderid = :id
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':id', $row['id']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $result = $statement->fetchAll(PDO::FETCH_ASSOC);
            foreach ($result as $res) {
                $idOrders[$row['id']]['games'][$res['id']] = array (
                    'title' => $res['title'],
                    'console' => $res['console'],
                    'amount' => $res['copies'],
                    'price' => floatval($res['price']*intval($res['copies']))
                );
            }
        }
    }
    ?>

<section class="main_content">

    <br>
    <br>
    <br>

    <div align="center">

        <section class="panel" align="center" style="text-align:
center">

            <br>

            <div class = 'panel_title' id = 'users_title'>
                I MIEI ORDINI
            </div>

            <br>
            <br>

            <?php if ($idOrders != null): ?>

            <?php foreach ($idOrders as $order=>$value) :?>

            <div class = 'panel_title' id = 'users_title' style="border-
radius: 20px">

                ORDINE NUMERO <?php echo $order; ?>
                <br>
                <?php
                $total_price = 0;
                $total_products = 0;
                foreach ($value['games'] as $attribute) {

```

```

        $total_price += $attribute['price'];
        $total_products += $attribute['amount'];
    }
    echo "Prodotti: " . $total_products . " Totale: €" .
$total_price;
    ?>

</div>

<br>

<table align="center" class = 'box' width="100%" id =
'users_table'>

    <tr>
        <th></th>
        <th>Titolo</th>
        <th>Quantità</th>
        <th>Prezzo</th>
    </tr>

    <?php foreach ($value['games'] as $game => $attribute):
?>
        <tr>
            <td style="text-align: center">
                "
                >
            </td>
            <td><?php echo $attribute['title']; ?></td>
            <td><?php echo $attribute['amount'] ?></td>
            <td><?php echo '€'. $attribute['price']; ?></td>
        </tr>
    <?php endforeach; ?>

</table>

<br>

<div class = 'panel_title' id = 'users_title' style="border-
radius: 20px">
    Data: <?php echo date('d/m/Y - H:m',
strtotime($value['date'])) ?> &nbsp;
    Pagamento: <?php echo $value['payment']; ?>
</div>

<br>
<br>

    <form action = "<?php echo htmlentities
($_SERVER['PHP_SELF']); ?>" method = "POST">
        <button type="submit" name = "delete" value="<?php echo
$order; ?>">
            
            Elimina Ordine
        </button>
    </form>

```

```

<br>

<hr style="border: dashed 1px; width: 90%">

<br>
<br>
<br>

<?php endforeach;?>

<?php else: ?>
<div class="error_messages">Nessun ordine effettuato.</div>
<?php endif;?>

<div class="error_messages">
<?php
if (isset($_POST['delete'])) {
    try {
        $database_handler = new PDO ($dns);
        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
    } catch (PDOException $e) {
        echo $e->getMessage();
        die();
    }

    $gamesId = array();

    $query = "
        SELECT gameid, copies
        FROM game_order
        WHERE orderid = :id
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $_POST['delete']);
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetchAll(PDO::FETCH_ASSOC);

    foreach ($result as $row) {
        $gamesId[$row['gameid']] = $row['copies'];
    }

    foreach ($gamesId as $game=>$amount) {
        $query = "
            UPDATE videogame
            SET amount = amount + :amount
            WHERE id = :id
        ";
        $statement = $database_handler->prepare($query);
        $statement->bindParam(':id', $game);
        $statement->bindParam(':amount', intval($amount));
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
    }

    $query = "
        DELETE FROM order_table
        WHERE id = :id
    ";

```

```

        $statement = $database_handler->prepare($query);
        $statement->bindParam(':id', $_POST['delete']);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->fetchAll(PDO::FETCH_OBJ);
        $database_handler = null;
        if ($result) {
            echo "Eliminazione effettuata.";
        }
        else {
            echo "Eliminazione non riuscita.";
        }
        header('Refresh:5');
    }
    ?>
</div>

</section>

</div>

<br>
<br>

</section>

<?php
include_once '..\templates\footer.php';
?>

</body>

</html>

```

add\_order.php

```
<?php
include_once "..\config\configurations.php";

if (isset($_SESSION['username'])) {
    if ($_SESSION['user'] == 'admin') {
        header ('Location: ..\admin\admin_panel.php');
    }
}
else
    header ('Location: ..\utils\login.php')
?>

<html>

    <body>

        <?php
        include_once '../templates/header.php';
        ?>

        <section class="main_content">

            <br>
            <br>
            <br>

            <div align="center">

                <section class="panel" align="center" style="text-align:
center">

                    <?php if ($cart->getCartContent() != null): ?>

                        <div class = 'panel_title' id = 'users_title'>
                            DETTAGLI ORDINE <br>
```

```

        <?php echo 'Prodotti: ' . $cart -> getTotalItems();?>
&nbsp;
        <?php echo 'Totale: €' . $cart -> getTotalPrice();?>
    </div>

    <br>
    <br>

    <table align="center" class = 'box' width="100%" id =
'users_table'>

        <tr>
            <th></th>
            <th>Prodotto</th>
            <th>Quantità</th>
        </tr>

        <?php foreach ($cart->getCartContent() as $item=>$row)
:??>

            <tr>
                <td style="text-align: center">
                    "
                    >
                </td>
                <td>
                    <?php echo $row['title']; ?> <br>
                    <?php echo $row['console'] ?>
                    € <?php echo
floatval($row['price'])*intval($row['quantity']); ?>
                </td>
                <td>
                    <?php echo $row['quantity']; ?>
                </td>
            </tr>
        <?php endforeach; ?>

    </table>

    <br>
    <br>

    <form action = "<?php echo htmlentities
($_SERVER['PHP_SELF']); ?>" method = "POST">

        Pagamento:

        <input id='master_card' type = 'radio' name = 'payment'
value = 'Master Card' checked required>

        <label for="master_card">
            
        </label>

        <input id='visa' type = 'radio' name = 'payment' value =
'Visa' required>

```



```

        <label for="visa">
            
        </label>

        <input id='paypal' type = 'radio' name = 'payment' value
= 'Paypal' required>

        <label for="paypal">
            
        </label>

        <input id='bitcoin' type = 'radio' name = 'payment'
value = 'Bitcoin' required>

        <label for="bitcoin">
            
        </label>

        <br>

        <button type="submit" name = 'add_order'>
            
            Procedi All'Ordine
        </button>

        <br>
        <br>

        <div class="error_messages" style="width: auto">
            <?php
            if (isset ($_POST['add_order'])) {
                try {
                    $database_handler = new PDO ($dns);
                    $database_handler->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
                } catch (PDOException $e) {
                    echo $e->getMessage();
                    die();
                }

                $query = "
                    SELECT MAX(id) as idMax
                    FROM order_table
                ";
                $statement = $database_handler->prepare($query);
                $database_handler->beginTransaction();
                $statement->execute();
                $database_handler->commit();
                $result = $statement->fetchColumn();

                $idOrder = null;
                if ($result) {
                    $idOrder = $result + 1;
                }
                else
                    $idOrder = 1;

                $flag = true;
            }
        </div>
    </div>

```

```

        foreach ($cart->getCartContent() as $item => $array)
        {
            $query = "
                SELECT amount
                FROM videogame
                WHERE id = :id
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':id',$item);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $available = $statement->fetch();
            if
            (intval($available['amount'])<$array['quantity']) {
                echo 'Sono disponibili solo
                '.$available['amount'].' prodotti del tipo "'.$array['title'].'" per
                '.$array['console'].' <br>';
                $flag = false;
            }
        }
        if ($flag == false) {
            $database_handler = null;
            echo 'Apportare le necessarie modifiche al
            carrello';
            header ('Refresh:4; url =
            ../cart/cart_view.php');
        }
        else {
            $query = "
                INSERT INTO order_table (id, date, payment,
            userid)
                VALUES (:id, now(), :payment, :userid)
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':id',$idOrder);
            $statement->
            >bindParam(':payment',$_POST['payment']);
            $statement->
            >bindParam(':userid',$_SESSION['username']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();

            foreach ($cart->getCartContent() as $item =>
            $array) {

                $query = "
                    INSERT INTO game_order (gameid, orderid,
            copies)
                    VALUES (:game, :userorder, :amount)
                ";
                $statement = $database_handler->
            >prepare($query);
                $statement->bindParam(':game',$item);
                $statement->
            >bindParam(':userorder',$idOrder);
                $statement->
            >bindParam(':amount',$array['quantity']);
                $database_handler->beginTransaction();
                $statement->execute();
            }
        }
    }
}

```

```

        $database_handler->commit();
        $query = "
            UPDATE videogame
            SET amount = amount - :amount
            WHERE id = :id
        ";
        $statement = $database_handler->
>prepare($query);
        $statement->
>bindParam(':amount',$array['quantity']);
        $statement->bindParam(':id',$item);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
    }
    $database_handler = null;
    unset($_SESSION['cart']);
    header ('Location: orders.php');
}
}
?>
</div>

</form>

<?php else: ?>
    <div class="error_messages">Il tuo carrello è
vuoto.</div>
<?php endif; ?>

</section>

</div>

<br>
<br>

</section>

<?php
include_once '..\templates\footer.php';
?>

</body>

</html>

```

## add\_admin

```
<?php
include_once "..\config\configurations.php";

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">

            <br>
            <br>
            <div class = 'admin_layout' align="center">

                <section class="panel">

                    <?php include_once 'admin_buttons.php'; ?>

                    <br>
                    <br>

                    <div class = 'panel_title' id = 'admins_title'>
```

```

        AGGIUNTA NUOVO ADMIN
    </div>

    <br>

    <form align="center" action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST">
        <label>
            <input name = 'inputSearch' type="text"/>
        </label>
        <label>
            <select class="option" name="method">
                <option value="all">Tutto</option>
                <option value="username">Username</option>
                <option value="name">Nome e Cognome</option>
            </select>
        </label>
        <input hidden name = 'admins_button' />
        <button type="submit" name =
'search_admin'>Cerca</button>
    </form>

    <?php

    try {
        $database_handler = new PDO ($dns);
        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
    } catch (PDOException $e) {
        echo $e->getMessage();
        die();
    }

    $query = '';

    if (isset ($_POST['search_admin']) &&
!empty($_POST['inputSearch'])) {

        if (isset($_POST['method'])) {

            $input = strtoupper($_POST['inputSearch']);

            switch ($_POST['method']) {

                case ('all'): {
                    $query = "
                        SELECT *
                        FROM user_table
                        WHERE admin is false AND (upper(login)
LIKE :input OR upper(name) LIKE :input OR upper(surname) LIKE :input)
                        GROUP BY login
                        ORDER BY login ASC
                    ";
                    $statement = $database_handler-
>prepare($query);
                    $statement -> bindValue (":input",
"%$input%", PDO::PARAM_STR);
                    break;
                }

                case ('username'): {

```

```

        $query = "
            SELECT *
            FROM user_table
            WHERE upper(login) LIKE :input AND admin
is false
            ORDER BY login ASC
        ";
        $statement = $database_handler-
>prepare($query);
        $statement -> bindValue (":input",
"%$input%", PDO::PARAM_STR);
        break;
    }

    case ('name'): {
        $query = "
            SELECT *
            FROM user_table
            WHERE (upper(name) LIKE :input or
upper(surname) LIKE :input) AND admin is false
            GROUP BY login
            ORDER BY login ASC
        ";
        $statement = $database_handler-
>prepare($query);
        $statement -> bindValue (":input",
"%$input%", PDO::PARAM_STR);
        break;
    }

    default: {
        $query = "
            SELECT *
            FROM user_table
            WHERE admin is false
            GROUP BY login
            ORDER BY login ASC
        ";
        $statement = $database_handler-
>prepare($query);
        break;
    }
}
}
}

else {
    $query = "
        SELECT *
        FROM user_table
        WHERE admin is false
        GROUP BY login
        ORDER BY login ASC
    ";
    $statement = $database_handler->prepare($query);
}

$database_handler->beginTransaction();
$statement->execute();
$database_handler->commit();
$result = $statement->fetchAll(PDO::FETCH_ASSOC);

```

```

        $database_handler = null;

        ?>

        <?php if ($result != null): ?>

        <table class = 'box' id = 'admins_table' align="center"
width="100%">

            <tr>
                <th>User</th>
                <th>Nome</th>
                <th>Cognome</th>
                <th>Indirizzo</th>
                <th>Telefono</th>
                <th>Promuovi Utente</th>
            </tr>

            <?php foreach ($result as $row): ?>
            <tr>
                <td><?php echo $row['login']; ?></td>
                <td><?php echo $row['name']; ?></td>
                <td><?php echo $row['surname']; ?></td>
                <td><?php echo $row['adress']; ?></td>
                <td><?php $row['phone'] == null ? print "-" : print
$row['phone']; ?></td>

                <td>
                    <form action = "<?php echo htmlentities
($_SERVER['PHP_SELF']); ?>" method = "POST">
                        <br>
                        <button type="submit" class =
'button' name="add_admin" value="<?php echo $row['login']; ?>"
                        
                        </button>
                    </form>
                </td>
            </tr>
            <?php endforeach; ?>

        </table>

        <?php else:

            echo "<div class=error_messages>Nessun risultato
corrisponde alla ricerca.</div>";

        endif;?>

        <br>
        <br>

        <div align="right">
            <a href="add_admin.php">
                <button type= 'submit' name = 'users_button' class =
'button'>
                    
                    Mostra Tutto
                </button>
            </a>
        </div>

```

```

        <div class="error_messages">
        <?php

            if (isset($_POST['add_admin'])) {

                try {
                    $database_handler = new PDO ($dns);
                    $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
                } catch (PDOException $e) {
                    echo $e->getMessage();
                    die();
                }

                try {
                    $query = "
                    UPDATE user_table
                    SET admin = true
                    WHERE login = :login
                    ";
                    $statement = $database_handler->prepare($query);
                    $statement->bindParam(':login',
$_POST['add_admin']);

                    $database_handler->beginTransaction();
                    $statement->execute();
                    $database_handler->commit();
                    $result = $statement->fetch();
                    header("Refresh: 4; url = admin_panel.php");
                    echo 'Promozione nuovo admin effettuata.';
                } catch (PDOException $e) {
                    echo 'Promozione nuovo admin non riuscita.';
                }

                $database_handler = null;
            }

        ?>

        </div>
    </section>
</div>
</section>

<?php
include_once '..\templates\footer.php';
?>

</body>

</html>

```



## add\_order\_product

```
<?php
include_once "..\config\configurations.php";

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}

if (!isset($_GET['id'])) {
    header ('Location: admin_panel.php');
}
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">

            <br>
            <br>
```

```

<div class="admin_layout" align="center">

    <section class = 'panel' align="center">

        <?php include_once 'admin_buttons.php'; ?>

        <br>
        <br>

        <div class = 'panel_title' id = 'orders_title'>
            AGGIUNTA PRODOTTO ALL'ORDINE <?php echo $_GET['id'];?>
        </div>

        <br>

        <form align="center" action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="GET">

            <label>
                <input hidden name = 'id' value="<?php print
$_GET['id']; ?>"/>

                <input name = 'gameSearch' type="text"/>
            </label>

            <label>
                <select class="option" name="method">
                    <option value="id">ID</option>
                    <option value="title">Titolo</option>
                </select>
            </label>

            <input hidden name = 'products_button' />
            <button type="submit">Cerca</button>

        </form>

        <?php
        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }
        $errors = false;

        if (isset($_GET['gameSearch'])) {

            switch ($_GET['method']) {

                case ('id'): {
                    if (filter_var($_GET['gameSearch'],
FILTER_VALIDATE_INT)) {

                        $query = "
                        SELECT *
                        FROM videogame
                        WHERE id = :input
                        ";
                        $statement = $database_handler-
>prepare($query);

                        $statement->bindParam(":input",

```

```

intval($_GET['gameSearch']));
    }
    else {
        echo "<div class=\"error_messages\">Inserire
valore numerico intero per l'ID. </div>";
        $errors = true;
    }
    break;
}

case ('title'): {
    $gameTitle = strtoupper($_GET['gameSearch']);
    $query = "
SELECT *
FROM videogame
WHERE upper(title) LIKE :input OR upper(console)
LIKE :input

ORDER BY id DESC
";
    $statement = $database_handler->prepare($query);
    $statement -> bindValue (":input",
"%$gameTitle%", PDO::PARAM_STR);
    break;
}

default: {
    $query = "
SELECT *
FROM videogame
ORDER BY title ASC
";
    $statement = $database_handler->prepare($query);
    break;
}
}

else {
    $query = "
SELECT *
FROM videogame
ORDER BY id DESC
";
    $statement = $database_handler->prepare($query);
}

if (!$errors) {
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetchAll(PDO::FETCH_ASSOC);
}

else {
    $result=null;
}

$database_handler = null;
?>

<?php if ($result != null): ?>

```

```

        <table class = 'box' id = 'orders_table' align="center"
width="100%" action="<?php echo htmlentities($_SERVER["PHP_SELF"]);?>"
method="POST">

        <tr>

        <th>Title</th>
        <th>Console</th>
        <th>Price</th>
        <th>Disponibili</th>
        <th>Aggiungi</th>

        </tr>

        <?php foreach ($result as $row): ?>

        <tr>

        <td><?php echo $row['title']; ?></td>
        <td><?php echo $row['console']; ?></td>
        <td><?php echo $row['price']; ?></td>
        <td><?php echo $row['amount'] == 0 ? "N/D" :
$row['amount']; ?></td>

        <td>
                <?php if ($row['amount']>0) : ?>
                <form action="<?php echo
htmlentities($_SERVER["PHP_SELF"].'?id='.$_GET['id']);?>" method="POST">
                <input hidden name='gameId' value="<?php echo
$row['id'];?>" />
                <input hidden name ='orderId' value ='<?php echo
$_GET['id'];?>' />
                <label>
                        <br>
                        <input name='numberToAdd' type="number"
min="1" />
                </label>
                <button type="submit" class = 'action_button'
name="add_games" style="vertical-align: middle">
                        
                </button>
                </form>
                <?php else : ?>
                <form style="color: darkslategray">
                <label>
                        <br>
                        <input type="number" disabled
placeholder="N/D" />
                </label>
                <button type="submit" class = 'action_button'
name="add_games" style="vertical-align: middle" disabled>
                        
                </button>
                </form>
                <?php endif; ?>
        </td>

        </tr>

        <?php endforeach; ?>
</table>

```

```

        <?php

        else : {
            if (!$errors) {
                echo "<div class='error_messages'> Nessun prodotto
corrisponde alla ricerca. </div>";
            }
        }
        endif;

    ?>

    <form align="right" action="<?php echo
htmlentities($_SERVER["PHP_SELF"].'?id='.$_GET['id']); ?>" method="POST">
        <button type= 'submit' name = 'products_button' class =
'button'>
            
            Mostra Tutto
        </button>
    </form>

    <?php
    if (isset($_POST['add_games']) &&
intval($_POST['numberToAdd']) > 0) {
        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }

        $query = "
            SELECT amount
            FROM videogame
            WHERE id = :id;
        ";

        $statement = $database_handler->prepare($query);
        $statement->bindParam(':id', intval($_POST['gameId']));
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->fetch(PDO::FETCH_ASSOC);

        $available = $result['amount'] - $_POST['numberToAdd']
>= 0;

        if ($available) {
            $query = "
                UPDATE videogame
                SET amount = amount - :amount
                WHERE id = :id
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':id',
intval($_POST['gameId']));
            $statement->bindValue(':amount',

```

```

$_POST['numberToAdd'], PDO::PARAM_INT);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();

        $query = "
            SELECT *
            FROM game_order
            WHERE orderid = :orderId and gameid =
:gameId
            ";
        $statement = $database_handler->prepare($query);
        $statement->bindParam(":gameId",
intval($_POST['gameId']));
        $statement->bindParam(":orderId",
intval($_POST['orderId']));
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->fetchColumn();

        if (!$result) {
            $query = "
                INSERT INTO game_order (gameid, orderid,
copies)
                values (:gameId, :orderId, :amount)
                ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(":gameId",
$_POST['gameId']);
            $statement->bindParam(":orderId",
$_POST['orderId']);
            $statement->bindParam(":amount",
$_POST['numberToAdd']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $database_handler = null;
        } else {
            $query = "
                UPDATE game_order
                SET copies = :amount + copies
                WHERE gameid = :gameId and orderid =
:orderId
                ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(":gameId",
intval($_POST['gameId']));
            $statement->bindParam(":orderId",
intval($_POST['orderId']));
            $statement->bindParam(":amount",
$_POST['numberToAdd']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $database_handler = null;
        }
        header('Location: edit_order.php?id=' .
$_POST['orderId']);
    }

    else {

```

```

                                echo "<div class= 'error_messages'>Prodotti
Insufficienti!</div>";
                                }
                                }
                                ?>

                                <br>
                                <br>
                                <br>
                                <br>
                                <br>

                                </section>
                                </div>
                                </section>

                                <?php
                                include_once '..\templates\footer.php';
                                ?>

                                </body>

                                </html>

```

#### add\_product.php

```

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}
?>

<html>

    <body>
        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">

            <br>
            <br>

            <div class = 'admin_layout' align="center">
                <section class = 'panel'>

                    <?php include_once 'admin_buttons.php'; ?>

```

```

        <br>
        <br>

        <div class = 'panel_title' id = 'products_title'
align="center">
            AGGIUNTA NUOVO PRODOTTO
        </div>

    </section>
</div>

    <div class="container">
        <form action = "<?php echo htmlentities ($_SERVER['PHP_SELF']);
?>" method = "POST" enctype="multipart/form-data">

            <label for="title">
                Titolo: <b style="color: darkred">*</b> <br>
            </label>
            <input id = 'title' required maxlength="50" type="text" name
= "title" />

            <br>
            <br>

            <label for="price">
                Prezzo: <b style="color: darkred">*</b> <br>
            </label>
            € &nbsp;
            <input id = 'price' type="number" name = 'price_round'
min="0"/> .
            <input id = 'price' type="number" name = 'price_cents'
min="0" max="99" value="0" style="display: inline">

            <br>
            <br>

            <label for="console">
                Console: <b style="color: darkred">*</b> <br>
            </label>
            <ul class='fieldset' style="padding-left: 0">
                <li style="margin-left: 0">
                    <label>
                        <input type = 'radio' value = 'PS4' name="console"
checked required />
                        
                        &nbsp; PS4
                    </label>
                </li>
                <li style="margin-left: 0">
                    <label>
                        <input type = 'radio' value = 'Xbox One'
name="console" required/>
                        
                        &nbsp; Xbox One
                    </label>
                </li>
                <li style="margin-left: 0">
                    <label>
                        <input type = 'radio' value = 'Switch' name="console"
required/>

```



```

        
        &nbsp; Switch
        </label>
    </li>
    <li style="margin-left: 0">
        <label>
            <input type='radio' value = 'PC' name="console"
required/>
            
            &nbsp; PC
        </label>
    </li>
</ul>

<br>

<label for = 'numberToAdd'>
    Quantità: <b style="color: darkred">*</b> <br>
</label>
<input id = 'numberToAdd' name="numberToAdd" type="number"
min="0"/>

<br>
<br>

<label for = 'file'>
    Copertina: <br>
</label>
<input type="file" name = 'file'>

<br>
<br>

<button class = "action_button" type="submit" name =
"submit">
    
    Aggiungi Gioco
</button>
</form>

<div class="error_messages">
    * Campi Obbligatori.
</div>

<div class="error_messages">

<?php
if (!empty ($_POST['title']) && !empty ($_POST['price_round'])
&&
        isset($_POST['console']) && !empty($_POST['numberToAdd']) &&
isset ($_POST['submit'])) {

        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();

```

```

        die();
    }

    $alright = true;
    $upload = false;
    $fileName = null;
    $fileTmp = null;
    $fileError = null;
    $fileSize = null;
    $fileExt = null;

    if (is_uploaded_file($_FILES['file']['tmp_name'])) {

        $file = $_FILES['file'];

        $fileName = $_FILES['file']['name'];
        $fileTmp = $_FILES['file']['tmp_name'];
        $fileError = $_FILES['file']['error'];
        $fileSize = $_FILES['file']['size'];

        $fileExt = explode('.', $fileName);
        $fileExt = strtolower(end($fileExt));

        $allowed = 'jpg';

        if ($fileExt == $allowed) {
            if ($fileError == 0) {
                if ($fileSize < 1000000) {
                    $upload = true;
                } else {
                    echo 'File troppo grande';
                    $alright = false;
                }
            } else {
                echo "Errore nell'Upload";
                $alright = false;
            }
        } else {
            echo 'Estensione non utilizzabile';
            $alright = false;
        }
    }

    if ($alright) {

        $query = "
            SELECT MAX(id) as idMax
            FROM videogame
        ";
        $statement = $database_handler->prepare($query);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->fetchColumn();

        $idGame = null;
        if ($result) {
            $idGame = $result + 1;
        } else {
            $idGame = 1;
        }
        $query = "
            INSERT INTO videogame (id, title, price, console,

```

```

amount)
        VALUES (:id, :title, :price, :console, :amount)
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $idGame);
    $statement->bindParam(':title', $_POST['title']);
    $price = intval($_POST['price_round']);
    $price_cents = isset($_POST['price_cents'])?
intval($_POST['price_cents']):0;
    $price += ($price_cents * 0.01);
    $statement->bindParam(':price', $price);
    $statement->bindParam(':console', $_POST['console']);
    $statement->bindParam(':amount', $_POST['numberToAdd']);
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetch();
    $database_handler = null;
}
if ($upload) {
    $fileDestination =
"..\\web\\images\\".$idGame.'.'.$fileExt;
    move_uploaded_file($fileTmp, $fileDestination);
}

if ($alright) {
    header('Location: admin_panel.php');
}

else {
    echo 'Inserire dati.';
}

?>
</div>
</div>

<br>
<br>
<br>
<br>
<br>

</section>

<?php
include_once '..\\templates\\footer.php';
?>

</body>

</html>

```

add\_user.php

```
<?php
include_once "..\config\configurations.php";

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}
?>

<html>

    <body>
        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">
```

```

        <br>
        <br>

        <div class = 'admin_layout' align="center">
            <section class = 'panel'>

                <?php include_once 'admin_buttons.php'; ?>

                <br>
                <br>
                <div class = 'panel_title' id = 'users_title'
align="center">
                    AGGIUNTA NUOVO UTENTE
                </div>
            </section>
        </div>

        <div class="container">
            <form class = 'login' action = "<?php echo htmlentities
($_SERVER['PHP_SELF']); ?>" method = "POST">

                <label for="name">
                    Name: <b style="color: darkred">*</b>
                    <br>
                </label>
                <input id = 'name' required maxlength="20" type="text" name
= "name" />

                <br>
                <br>

                <label for="surname">
                    Surname: <b style="color: darkred">*</b>
                    <br>
                </label>
                <input id = 'surname' required maxlength="20" type="text"
name = "surname" />

                <br>
                <br>

                <label for="adress">
                    Indirizzo: <b style="color: darkred">*</b>
                    <br>
                </label>
                <input id = 'adress' required maxlength="100" type="text"
name = "adress" />

                <br>
                <br>

                <label for="phone">
                    Telefono:
                    <br>
                </label>
                <input id = 'phone' maxlength="10" type="tel" name =
"phone" />

                <br>
                <br>

                <label for="username">

```

```

        Username: <b style="color: darkred">*</b>
        <br>
    </label>
    <input id = 'username' required maxlength="20" type="text"
name = "username" />

    <br>
    <br>

    <label for="repeatUsername">
        Ripeti Username: <b style="color: darkred">*</b>
        <br>
    </label>
    <input id = 'repeatUsername' required maxlength="20"
type="text" name = "repeatUsername" />

    <br>
    <br>

    <label for="password">
        Password: <b style="color: darkred">*</b>
        <br>
    </label>
    <input id = 'password' required maxlength="20"
type="password" name = "password" />

    <br>
    <br>

    <label for="repeatPassword">
        Ripeti Password: <b style="color: darkred">*</b>
        <br>
    </label>
    <input id = 'repeatPassword' required maxlength="20"
type="password" name = "repeatPassword" />

    <br>
    <br>

    <button class = 'action_button' type="submit" name="submit">
        
        Registra Nuovo Utente
    </button>

</form>

<div class="error_messages">
    * Campi Obbligatori.
</div>

<div class="error_messages">
<?php
if (!empty($_POST['name']) && !empty($_POST['surname']) &&
    !empty($_POST['adress']) && !empty($_POST['username']) &&
    !empty($_POST['repeatUsername']) &&
!empty($_POST['password']) &&
    !empty($_POST['repeatPassword']) && isset
($_POST['submit'])) {

        if ($_POST['username']==$_POST['repeatUsername'] &&
$_POST['password']==$_POST['repeatPassword']) {

```

```

        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }
        try {
            $query = "
phone, login, password)
            INSERT INTO user_table (name, surname, adress,
:username, :password)
            VALUES (:name, :surname, :adress, :phone,
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':name', $_POST['name']);
            $statement->bindParam(':surname',
$_POST['surname']);
            $statement->bindParam(':adress', $_POST['adress']);
            $statement->bindParam(':phone', $_POST['phone']);
            $statement->bindParam(':username',
$_POST['username']);
            $statement->bindParam(':password',
$_POST['password']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $result = $statement->fetch();
            header("Refresh: 4; url = admin_panel.php");
            echo 'Registrazione nuovo utente effettuata';
            $database_handler = null;
        } catch (PDOException $e) {
            echo "Username non disponibile";
            $database_handler = null;
        }
    }

    else
        echo 'Inserire stesso username e Password';
}
?>

</div>
<br>
<br>
<br>
<br>
<br>

</div>

</section>

<?php
include_once '..\templates\footer.php';
?>

</body>
</html>

```

admin\_admin.php

```
<?php
if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
    die("Non autorizzato");
}
?>

<html>

    <body>

        <section class = 'panel' align="center">

            <?php include_once 'admin_buttons.php'; ?>

            <br>
```



```

<br>

<div class = 'panel_title' id = 'admins_title'>
    AMMINISTRAZIONE ADMIN
</div>

<br>

<form align="center" action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST">
    <label>
        <input name = 'inputSearch' type="text"/>
    </label>
    <label>
        <select class="option" name="method">
            <option value="all">Tutto</option>
            <option value="username">Username</option>
            <option value="name">Nome e Cognome</option>
        </select>
    </label>

    <input hidden name = 'admins_button' />

    <button type="submit" name = 'searchAdmin'>Cerca</button>
</form>

<?php
try {
    $database_handler = new PDO ($dns);
    $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
} catch (PDOException $e) {
    echo $e->getMessage();
    die();
}

$query = '';

if (isset ($_POST['searchAdmin']) && !empty($_POST['inputSearch']))
{

    if (isset($_POST['method'])) {
        $input = strtoupper($_POST['inputSearch']);

        switch ($_POST['method']) {

            case ('all'): {
                $query = "
                SELECT *
                FROM user_table
                WHERE admin is true AND (upper(login) LIKE
:input OR upper(name) LIKE :input OR upper(surname) LIKE :input)
                GROUP BY login
                ORDER BY login ASC
                ";
                $statement = $database_handler->prepare($query);
                $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

                break;
            }

```

```

        case ('username'): {
            $query = "
                SELECT *
                FROM user_table
                WHERE upper(login) LIKE :input AND admin is true
                ORDER BY login ASC
            ";
            $statement = $database_handler->prepare($query);
            $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

            break;
        }

        case ('name'): {
            $query = "
                SELECT *
                FROM user_table
                WHERE (upper(name) LIKE :input or upper(surname)
LIKE :input) AND admin is true
                GROUP BY login
                ORDER BY login ASC
            ";
            $statement = $database_handler->prepare($query);
            $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

            break;
        }

        default: {
            $query = "
                SELECT *
                FROM user_table
                WHERE admin is true
                GROUP BY login
                ORDER BY login ASC
            ";
            $statement = $database_handler->prepare($query);
            break;
        }
    }
}

else {
    $query = "
        SELECT *
        FROM user_table
        WHERE admin is true
        GROUP BY login
        ORDER BY login ASC
    ";
    $statement = $database_handler->prepare($query);
}

$database_handler->beginTransaction();
$statement->execute();
$database_handler->commit();
$result = $statement->fetchAll(PDO::FETCH_ASSOC);
$database_handler = null;
?>

```

```

        <?php if ($result != null): ?>

        <table class = 'box' id = 'admins_table' align="center"
width="100%">

            <tr>
                <th>User</th>
                <th>Nome</th>
                <th>Cognome</th>
                <th>Indirizzo</th>
                <th>Telefono</th>
                <th>Modifica </th>
            </tr>

            <?php foreach ($result as $row): ?>

                <tr <?php if ($row['login'] == $_SESSION['username']) echo
'style="font-weight: bold"'; ?>>
                    <td><?php echo $row['login']; ?></td>
                    <td><?php echo $row['name']; ?></td>
                    <td><?php echo $row['surname']; ?></td>
                    <td><?php echo $row['adress']; ?></td>
                    <td><?php $row['phone'] == null ? print "-" : print
$row['phone']; ?></td>
                    <td>
                        <form>
                            <br>
                            <a href="edit_admin.php?login=<?php echo
$row['login']; ?>">
                                <button type="button" class = 'action_button'>
                                    
                                </button>
                            </a>
                        </form>
                    </td>
                </tr>

            <?php endforeach; ?>

        </table>

        <?php
        else:
            echo "<div class=error_messages>Nessun risultato corrisponde
alla ricerca.</div>";
        endif;
        ?>

        <br>
        <br>

        <div align="right">

            <form action="<?php echo htmlentities($_SERVER["PHP_SELF"]); ?>"
method="POST" style="display: inline-block">
                <button type= 'submit' name = 'admins_button' class =
'actions_button'>
                    
                    Mostra Tutto
                </button>
            </div>

```

```

        </form>

        <form action="<?php echo htmlentities("add_admin.php");?>"
style="display: inline-block">
            <button class = 'action_button'>
                
                Aggiungi Admin
            </button>
        </form>

    </div>

</section>

</body>

</html>

```

#### admin\_buttons.php

```

<?php
if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
    die("Non autorizzato");
}
?>

<html>
    <body>

        <?php
        if (!isset($id)) {

```



```

<?php
include_once '..\templates\header.php';
?>

<?php
if ($_SESSION['user'] != 'admin') {
    header ('Location: ../utils/logout.php');
}
?>

<section class = 'panel' align="center">

    <?php include_once 'admin_buttons.php'; ?>

    <br>
    <br>
    <div class = 'panel_title' id = 'orders_title'>
        AMMINISTRAZIONE ORDINI
    </div>

    <br>

    <form align="center" action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST">
        <label>
            <input name = 'inputSearch' type="text"/>
        </label>
        <label>
            <select class="option" name="method">
                <option value="username">Per Utente</option>
                <option value="id">Per Numero</option>
                <option value="game">Per Videogioco</option>
            </select>
        </label>
        <input hidden name = 'orders_button'>
        <button type="submit" name = 'searchOrder'>Cerca</button>
    </form>

    <?php

    try {
        $database_handler = new PDO ($dns);
        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
    } catch (PDOException $e) {
        echo $e->getMessage();
        die();
    }

    $errors = false;
    $query = '';

    if (isset ($_POST['searchOrder']) && !empty($_POST['inputSearch']))
    {

        if (isset($_POST['method'])) {

            $input = strtoupper($_POST['inputSearch']);

            switch ($_POST['method']) {

```

```

        case ('username'): {
            $query = "
                SELECT *
                FROM order_table
                WHERE upper(userid) LIKE :input
                GROUP BY id
                ORDER BY id ASC
            ";
            $statement = $database_handler->prepare($query);
            $statement -> bindValue (":input", "$input%",
PDO::PARAM_STR);

            break;
        }

        case ('id'): {
            if (filter_var($input, FILTER_VALIDATE_INT)) {
                $query = "
                    SELECT *
                    FROM order_table
                    WHERE id = :input
                ";
                $statement = $database_handler->prepare($query);
                $statement->bindParam(":input", $input);
            }
            else {
                echo "<div class= error_messages>Inserire valore
numerico intero per l'ID.</div>";
                $errors = true;
            }
            break;
        }

        case ('game'): {
            $query = "
                SELECT DISTINCT o.*
                FROM order_table o, game_order g_o, videogame v
                WHERE upper(v.title) LIKE :input AND o.id =
g_o.orderid AND v.id = g_o.gameid
                GROUP BY o.id
                ORDER BY o.id ASC
            ";
            $statement = $database_handler->prepare($query);
            $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

            break;
        }

        default: {
            $query = "
                SELECT *
                FROM order_table
                GROUP BY id
                ORDER BY id ASC
            ";
            $statement = $database_handler->prepare($query);
            break;
        }
    }
}

else {

```

```

        if (isset($_POST['user_to_check'])) {
            $input = $_POST['user_to_check'];
            $query = "
                SELECT *
                FROM order_table
                WHERE userid = :input
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(":input", $input);
        }
        else {
            $query = "
                SELECT *
                FROM order_table
            ";
            $statement = $database_handler->prepare($query);
        }
    }

    $result = null;

    if (!$errors) {
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->fetchAll(PDO::FETCH_ASSOC);
    }
    $database_handler = null;

    ?>

<?php
if ($result != null): ?>

    <table class = 'box' id = 'orders_table' width="100%" align="center"
width="60%" action="<?php echo htmlentities($_SERVER["PHP_SELF"]);?>"
method="POST">

        <tr>
            <th>Ordine</th>
            <th>Utente</th>
            <th>Data</th>
            <th>Pagamento</th>
            <th>Modifica</th>
        </tr>

        <?php foreach ($result as $row): ?>
            <tr>
                <td><?php echo $row['id']; ?></td>
                <td><?php echo $row['userid']; ?></td>
                <td><?php echo date('d/m/Y - H:m', strtotime($row['date']));
?></td>

                <td><?php echo $row['payment']; ?></td>
                <td>
                    <form>
                        <a href="edit_order.php?id=<?php echo $row['id'];
?>">

                            <button type="button" class = 'action_button'>
                                <br>
                                
                            </button>

```



```

        </a>
    </form>
</td>
</tr>
<?php endforeach; ?>

</table>

<?php elseif (!$errors) :
    echo "<div class= 'error_messages'>Nessun risultato corrisponde
alla ricerca</div>";
    endif;?>

<br>

<form action="<?php echo htmlentities($_SERVER["PHP_SELF"]);?>"
align="right" method="POST">
    <button type= 'submit' name = 'orders_button' class =
'button'>
        
        Mostra Tutto
    </button>
</form>

</section>

</body>

</html>

```

#### admin\_panel.php

```

<?php
include_once "..\config\configurations.php";

if ($_SESSION['user'] != 'admin') {
    header ('Location: ..\Utils\logout.php');
}
?>

```

```

<html>

    <body>

        <?php
            include_once "../templates/header.php";
        ?>

        <?php

            $id = null;

            if (isset($_POST['products_button']))
                $id = 'products';

            elseif (isset($_POST['admins_button']))
                $id = 'admins';

            elseif (isset($_POST['users_button']))
                $id = 'users';

            elseif (isset($_POST['orders_button']))
                $id = 'orders';

            else
                $id = 'users';

        ?>

        <section class="main_content">

            <br>
            <br>

            <div class = 'admin_layout' align="center">
                <?php

                    switch ($id) {
                        case ('products'): {
                            include_once 'admin_product.php';
                            break;
                        }
                        case ('users'): {
                            include_once 'admin_user.php';
                            break;
                        }
                        case ('orders'): {
                            include_once 'admin_order.php';
                            break;
                        }
                        case ('admins'): {
                            include_once 'admin_admin.php';
                            break;
                        }
                        default: {
                            include_once 'admin_user.php';
                            break;
                        }
                    }

                }
            </div>
        </section>
    </body>
</html>

```

```
        ?>
    </div>
</section>

<?php
include_once '..\templates\footer.php';
?>

</body>
</html>
```

admin\_product.php

```
<?php
if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
    die("Non autorizzato");
}
?>
```

```

<html>

    <body>

        <section class = 'panel' align="center">

            <?php include_once 'admin_buttons.php'; ?>

            <br>
            <br>

            <div class = 'panel_title' id = 'products_title'>
                AMMINISTRAZIONE PRODOTTI
            </div>

            <br>

            <form align="center" action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST">
                <label>
                    <input name = 'inputSearch' type="text"/>
                </label>
                <label>
                    <select class="option" name="method">
                        <option value="id">ID</option>
                        <option value="title">Titolo</option>
                    </select>
                </label>
                <input hidden name = 'products_button' />
                <button type="submit" name = 'searchGame'>Cerca</button>
            </form>

            <?php

            try {
                $database_handler = new PDO ($dns);
                $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
            } catch (PDOException $e) {
                echo $e->getMessage();
                die();
            }

            $query = '';
            $errors = false;

            if (isset ($_POST['searchGame']) && !empty($_POST['inputSearch'])) {
                if (isset($_POST['method'])) {
                    $input = strtoupper($_POST['inputSearch']);
                    switch ($_POST['method']) {
                        case ('id'): {
                            if (filter_var($input, FILTER_VALIDATE_INT)) {
                                $query = "
                                SELECT *
                                FROM videogame
                                WHERE id = :input
                                ";
                                $statement = $database_handler->prepare($query);
                                $statement->bindParam(":input", $input);
                            }
                        }
                        else {
                            echo "<div class = 'error_messages'>Inserire

```

```

valore numerico intero per l'ID.</div>";
        $errors = true;
    }
    break;
}

case ('title'): {
    $query = "
    SELECT *
    FROM videogame
    WHERE upper(title) LIKE :input
    ORDER BY title ASC
    ";
    $statement = $database_handler->prepare($query);
    $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

    break;
}

default: {
    $query = "
    SELECT *
    FROM videogame
    ORDER BY title ASC
    ";
    $statement = $database_handler->prepare($query);
    break;
}
}
}

else {
    $query = "
    SELECT *
    FROM videogame
    ORDER BY title ASC
    ";
    $statement = $database_handler->prepare($query);
}

$result = null;

if (!$errors) {
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetchAll(PDO::FETCH_ASSOC);
}

$database_handler = null;

?>

<?php if ($result != null): ?>

    <table class = 'box' id = 'products_table' align="center"
width="100%" action="<?php echo htmlentities($_SERVER["PHP_SELF"]);?>"
method="POST">

        <tr>
            <th>Title</th>

```



```
</html>
```

admin\_user.php

```
<?php
if (basename($_SERVER['PHP_SELF']) == basename(__FILE__)) {
```

```

        die("Non autorizzato");
    }
    ?>

<html>

    <body>
        <section class = 'panel' align="center">

            <?php include_once 'admin_buttons.php'; ?>

            <br>
            <br>

            <div class = 'panel_title' id = 'users_title'>
                AMMINISTRAZIONE UTENTI
            </div>

            <br>

            <form align="center" action="<?php echo
htmlentities($_SERVER["PHP_SELF"]);?>" method="POST">
                <label>
                    <input name = 'inputSearch' type="text"/>
                </label>
                <label>
                    <select class="option" name="method">
                        <option value="all">Tutto</option>
                        <option value="username">Username</option>
                        <option value="name">Nome e Cognome</option>
                    </select>
                </label>
                <input hidden name = 'users_button' />
                <button type="submit" name = 'searchUser'>Cerca</button>
            </form>

            <?php

            try {
                $database_handler = new PDO ($dns);
                $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
            } catch (PDOException $e) {
                echo $e->getMessage();
                die();
            }

            $query = '';

            if (isset ($_POST['searchUser']) && !empty($_POST['inputSearch'])) {

                if (isset($_POST['method'])) {
                    $input = strtoupper($_POST['inputSearch']);

                    switch ($_POST['method']) {

                        case ('all'): {
                            $query = "
                            SELECT *
                            FROM user_table
                            WHERE admin is false AND (upper(login) LIKE :input
OR upper(name) LIKE :input OR upper(surname) LIKE :input)

```



```

        GROUP BY login
        ORDER BY login ASC
        ";
        $statement = $database_handler->prepare($query);
        $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

        break;
    }

    case ('username'): {
        $query = "
        SELECT *
        FROM user_table
        WHERE upper(login) LIKE :input AND admin is false
        ORDER BY login ASC
        ";
        $statement = $database_handler->prepare($query);
        $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

        break;
    }

    case ('name'): {
        $query = "
        SELECT *
        FROM user_table
        WHERE (upper(name) LIKE :input or upper(surname)
LIKE :input) AND admin is false
        GROUP BY login
        ORDER BY login ASC
        ";
        $statement = $database_handler->prepare($query);
        $statement -> bindValue (":input", "%$input%",
PDO::PARAM_STR);

        break;
    }

    default: {
        $query = "
        SELECT *
        FROM user_table
        WHERE admin is false
        GROUP BY login
        ORDER BY login ASC
        ";
        $statement = $database_handler->prepare($query);
        break;
    }
}
}
}

else {
    $query = "
    SELECT *
    FROM user_table
    WHERE admin is false
    GROUP BY login
    ORDER BY login ASC
    ";
    $statement = $database_handler->prepare($query);
}

```

```

$database_handler->beginTransaction();
$statement->execute();
$database_handler->commit();
$result = $statement->fetchAll(PDO::FETCH_ASSOC);
$database_handler = null;
?>

<?php if ($result != null): ?>

<table class = 'box' id = 'users_table' align="center" width="100%">
    <tr>
        <th>User</th>
        <th>Nome</th>
        <th>Cognome</th>
        <th>Indirizzo</th>
        <th>Telefono</th>
        <th>Ordini</th>
        <th>Modifica </th>
    </tr>

    <?php foreach ($result as $row): ?>
    <tr>
        <td><?php echo $row['login']; ?></td>
        <td><?php echo $row['name']; ?></td>
        <td><?php echo $row['surname']; ?></td>
        <td><?php echo $row['adress']; ?></td>
        <td><?php $row['phone'] == null ? print "-" : print
$row['phone']; ?></td>
        <td>
            <form action="<?php echo
htmlentities($_SERVER['PHP_SELF']);?>" method="POST">

                <button type="submit" class = 'action_button'
name="orders_button">

                    <br>
                    
                </button>
                <input hidden name = "user_to_check" value="<?php
echo $row['login']; ?>"/>
            </form>
        </td>
        <td>
            <a href="edit_user.php?login=<?php echo
$row['login'];?>">

                <button type="button" class = 'action_button'>
                    
                </button>
            </a>
        </td>
    </tr>
    <?php endforeach; ?>

</table>

<?php
else:
    echo "<div class=error_messages>Nessun risultato corrisponde
alla ricerca.</div>";

```

```

endif;
?>

<br>
<br>

<div align="right">
    <form action="<?php echo htmlentities($_SERVER["PHP_SELF"]);?>"
method="POST" style="display: inline-block">
        <button type= 'submit' name = 'users_button' class =
'button'>
            
            Mostra Tutto
        </button>
    </form>

    <form style="display: inline-block">
        <a href="add_user.php">
            <button type="button" class = 'button'>
                
                Aggiungi Utente
            </button>
        </a>
    </form>
</div>

</section>

</body>

</html>

```

## edit\_admin

```
<?php
include_once "..\config\configurations.php";

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}

if (!isset($_GET['login']))
    header ('Location: admin_panel.php');
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">

            <br>
            <br>

            <div class = 'admin_layout' align="center">

                <section class = 'panel' align="center">

                    <?php include_once 'admin_buttons.php'; ?>

                    <br>
                    <br>

                    <?php

                    try {
                        $database_handler = new PDO ($dns);
                        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
                    } catch (PDOException $e) {
                        echo $e->getMessage();
                        die();
                    }

                    $query = "
                    SELECT *
                    FROM user_table
                    WHERE login = :login AND admin is true
                    ";
                    $statement = $database_handler->prepare($query);
                    $statement->bindParam(':login', $_GET['login']);
                    $database_handler->beginTransaction();
                    $statement->execute();
                    $database_handler->commit();
                    $result = $statement->fetch(PDO::FETCH_ASSOC);
                    $database_handler = null;

                    if (!$result) {
```



```

                                Nuovo Username: <br> <br>
                                <input id = 'login' maxlength="20"
type="text" name = "login" />
                                <button type="submit" name="submit">
                                    
                                Modifica
                                </button>
                                </label>
                                </div>

                                <div class="menu_header" id = 'menu2'
onclick="show(2)" style="position: relative">
                                    <b>
                                        PASSWORD (attuale = <?php echo
$result['password'];?>)
                                    </b>

                                    <div style="position: absolute; right:6px; top:
5px; display: inline">
                                        <div id = 'show2' style="display: inline;
font-size: 80%">
                                            - Show
                                        </div>
                                        
                                        </div>
                                    </div>

                                    <div class= 'menu_content' id = 'content2' hidden>
                                        <label>
                                            Nuova Password: <br> <br>
                                            <input id = 'password' maxlength="20"
type="password" name = "password" />
                                            <button type="submit" name="submit">
                                                
                                            Modifica
                                            </button>
                                            </label>
                                        </div>

                                <div class="menu_header" id = 'menu3'
onclick="show(3)" style="position: relative">
                                    <b>
                                        NOME (attuale = <?php echo
$result['name'];?>)
                                    </b>

                                    <div style="position: absolute; right:6px; top:
5px; display: inline">
                                        <div id = 'show3' style="display: inline;
font-size: 80%">
                                            - Show
                                        </div>
                                        
                                        </div>

```

```

        </div>

        <div class= 'menu_content' id = 'content3' hidden>
            <label>
                Nuovo Nome: <br> <br>
                <input id = 'name' maxlength="20"
type="text" name = "name" />
                <button type="submit" name="submit">
                    
                    Modifica
                </button>
            </label>
        </div>

        <div class="menu_header" id = 'menu4'
onclick="show(4)" style="position: relative">
            <b>
                COGNOME (attuale = <?php echo
$result['surname'];?>)
            </b>

            <div style="position: absolute; right:6px; top:
5px; display: inline">
                <div id = 'show4' style="display: inline;
font-size: 80%">
                    - Show
                </div>
                
            </div>
        </div>

        <div class= 'menu_content' id = 'content4' hidden>
            <label>
                Nuovo Cognome: <br> <br>
                <input id = 'surname' maxlength="20"
type="text" name = "surname" />
                <button type="submit" name="submit">
                    
                    Modifica
                </button>
            </label>
        </div>

        <div class="menu_header" id = 'menu5'
onclick="show(5)" style="position: relative">
            <b>
                INDIRIZZO (attuale = <?php echo
$result['adress'];?>)
            </b>

            <div style="position: absolute; right:6px; top:
5px; display: inline">
                <div id = 'show5' style="display: inline;
font-size: 80%">
                    - Show

```

```

        </div>
        
    </div>
</div>

    <div class= 'menu_content' id = 'content5' hidden>
        <label>
            Nuovo Indirizzo: <br> <br>
            <input id = 'adress' maxlength="100"
type="text" name = "adress" />
            <button type="submit" name="submit">
                
                Modifica
            </button>
        </label>
    </div>

    <div class="menu_header" id = 'menu6'
onclick="show(6)" style="position: relative">
        <b>
            TELEFONO (attuale = <?php echo
$result['phone'] == null ? 'N/D' : $result['phone']; ?>)
        </b>

        <div style="position: absolute; right: 6px; top:
5px; display: inline">
            <div id = 'show6' style="display: inline;
font-size: 80%">
                - Show
            </div>
            
        </div>

    <div class= 'menu_content' id = 'content6' hidden>
        <label>
            Nuovo Telefono: <br> <br>
            <input id = 'phone' maxlength="10"
type="tel" name = "phone" />
            <button type="submit" name="submit">
                
                Modifica
            </button>
        </label>
    </div>

    <br>

    <div align="right">
        <button class="action_button" type="submit"
name="submit">
            
            Modifica Admin
        </button>

```



```

        <?php if
($_GET['login']!= $_SESSION['username']): ?>

        <button class="action_button" type="submit"
name="delete">

                
                Rimuovi Poteri Amministratore
        </button>

        <?php endif; ?>
</div>
</form>

<div class="error_messages">

<?php

        if (isset($_POST['delete'])) {
            try {
                $database_handler = new PDO ($dns);
                $database_handler->
>setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
            } catch (PDOException $e) {
                echo $e->getMessage();
                die();
            }
            $query = "
                UPDATE user_table
                SET admin = false
                WHERE login = :login
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':login', $_GET['login']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $result = $statement->fetchAll(PDO::FETCH_OBJ);
            $database_handler = null;
            if ($result) {
                echo "Rimozione Admin riuscita.";
            }
            else {
                echo 'Rimozione Admin non riuscita.';
            }
            $database_handler = null;
            header('Refresh:4; url = admin_panel.php');
        }

        if (isset ($_POST['submit'])) {

            if (!empty($_POST['login']) ||
!empty($_POST['password']) || !empty($_POST['adress']) ||
!empty($_POST['phone']) || !empty($_POST['name'])
|| !empty($_POST['surname'])) {

                try {
                    $database_handler = new PDO ($dns);
                    $database_handler->
>setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
                } catch (PDOException $e) {
                    echo $e->getMessage();

```

```

        die();
    }

    $success = true;

    if (!empty($_POST['login'])) {
        try {
            $query = "
                UPDATE user_table
                SET login = :newlogin
                WHERE login = :login
            ";
            $statement = $database_handler-
>prepare($query);
            $statement->bindParam(':login',
$_GET['login']);
            $statement->bindParam(':newlogin',
$_POST['login']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $_GET['login']=$_POST['login'];
        } catch (PDOException $error) {
            $success = false;
            echo 'Login non disponibile';
        }
    }

    if (!empty($_POST['password'])) {
        $query = "
            UPDATE user_table
            SET password = :password
            WHERE login = :login
        ";
        $statement = $database_handler-
>prepare($query);
        $statement->bindParam(':login',
$_GET['login']);
        $statement->bindParam(':password',
$_POST['password']);

        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
    }

    if (!empty($_POST['name'])) {
        $query = "
            UPDATE user_table
            SET name = :name
            WHERE login = :login
        ";
        $statement = $database_handler-
>prepare($query);
        $statement->bindParam(':login',
$_GET['login']);
        $statement->bindParam(':name',
$_POST['name']);

        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
    }
}

```

```

        if (!empty($_POST['surname'])) {
            $query = "
            UPDATE user_table
            SET surname = :surname
            WHERE login = :login
            ";
            $statement = $database_handler-
>prepare($query);
            $statement->bindParam(':login',
$_GET['login']);
            $statement->bindParam(':surname',
$_POST['surname']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
        }

        if (!empty($_POST['address'])) {
            $query = "
            UPDATE user_table
            SET address = :address
            WHERE login = :login
            ";
            $statement = $database_handler-
>prepare($query);
            $statement->bindParam(':login',
$_GET['login']);
            $statement->bindParam(':address',
$_POST['address']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
        }

        if (!empty($_POST['phone'])) {
            $query = "
            UPDATE user_table
            SET phone = :phone
            WHERE login = :login
            ";
            $statement = $database_handler-
>prepare($query);
            $statement->bindParam(':login',
$_GET['login']);
            $statement->bindParam(':phone',
$_POST['phone']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
        }

        $database_handler = null;

        if ($success) {
            header ('Location:
edit_admin.php?login='.$_GET['login']);
        }
    }

    else {
        echo 'Inserire almeno un nuovo dato';
    }
}

```

```
    }  
    ?>  
    </div>  
    </div>  
    </section>  
    </div>  
    </section>  
    <?php  
    include_once '..\templates\footer.php';  
    ?>  
    </body>  
</html>
```

## edit\_order.php

```
<?php
include_once "..\config\configurations.php";

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}

if (!isset($_GET['id']))
    header ('Location: admin_panel.php');
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">

            <br>
            <br>

            <div class="admin_layout" align="center">

                <section class = 'panel' align="center">

                    <?php include_once 'admin_buttons.php'; ?>

                    <br>
                    <br>

                    <?php

                    try {
                        $database_handler = new PDO ($dns);
                        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
                    } catch (PDOException $e) {
                        echo $e->getMessage();
                        die();
                    }

                    try {
                        $database_handler = new PDO ($dns);
                        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
                    } catch (PDOException $e) {
```

```

        echo $e->getMessage();
        die();
    }

    $order = array();

    $query = "
    SELECT *
    FROM order_table
    WHERE id = :id
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $_GET['id']);
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetch(PDO::FETCH_OBJ);

    $order = array ('id' => $result->id, 'date' => $result->date, 'payment' => $result->payment, 'games' => array());
    $query = "
    SELECT v.*, g_o.copies
    FROM game_order g_o JOIN videogame v on g_o.gameid = v.id
    WHERE g_o.orderid = :id
    GROUP BY v.id, g_o.copies
    ORDER BY v.id ASC
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $order['id']);
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetchAll(PDO::FETCH_ASSOC);
    $database_handler = null;
    if (!$result) {
        header('Location: admin_panel.php');
    }
    foreach ($result as $res) {
        $order['games'][$res['id']] = array (
            'id' => $res['id'],
            'title' => $res['title'],
            'console' => $res['console'],
            'amount' => $res['copies'],
            'price' =>
floatval($res['price']*intval($res['copies']))
        );
    }
    ?>

    <div class = 'panel_title' id = 'orders_title'>

        MODIFICA ORDINE &nbsp; <?php echo $order['id']; ?>

    </div>

    <br>

    <table class = 'box' id = 'orders_table' align="center"
width="100%" action="<?php echo htmlentities($_SERVER["PHP_SELF"]); ?>"
method="POST">

        <tr>

            <th>Title</th>

```

```

        <th>Console</th>
        <th>Price</th>
        <th>Quantità</th>
        <th>Elimina</th>
    </tr>

    <?php foreach ($order['games'] as $game): ?>
    <tr>
        <td><?php echo $game['title']; ?></td>
        <td><?php echo $game['console']; ?></td>
        <td><?php echo $game['price']; ?></td>
        <td>
            <form action="<?php echo
htmlentities($_SERVER["PHP_SELF"].'?id='.$order['id']);?>" method="POST">
                <br>
                <input hidden name = 'amount' value="<?php
echo $game['amount'];?>">
                <input type="number" min = '0'
name="new_amount" value="<?php echo $game['amount']; ?>">
                <button type="submit" class =
'button' name="edit_amount" value="<?php echo $game['id']; ?>">
                    
                </button>
            </form>
        </td>
        <td>
            <form action="<?php echo
htmlentities($_SERVER["PHP_SELF"].'?id='.$order['id']);?>" method="POST">
                <button type="submit" class =
'button' name="delete_game" value="<?php echo $game['id']; ?>">
                    <br>
                    
                </button>
            </form>
        </td>
    </tr>
    <?php endforeach; ?>

</table>

<br>
<br>

<table align="right" style="text-align: right">
    <tr>
        <td>
            DATA: <?php echo date('d/m/Y - H:m',
strtotime($order['date']));?>
        </td>
        <td>
            &nbsp;   PAGAMENTO: <?php echo
$order['payment'];?>
        </td>
    </tr>

    <tr>
        <td>
            <form>
                <a href="add_order_product.php?id=<?php echo
$order['id']; ?>">

```

```

                                <button class="action_button"
type="button">
                                
                                Aggiungi Prodotto
                                </button>
                                </a>
                                </form>
                                </td>
                                <td>
                                <form action="<?php echo
htmlentities($_SERVER['PHP_SELF']).'?id='.$order['id'];?>" method="POST">
                                <button type="submit" class =
'<?php echo $order['id']; ?>' name="delete_order" value="<?php echo $order['id']; ?>"
                                
                                Elimina Ordine
                                </button>
                                </form>
                                </td>
                                </tr>
                                </table>

                                <br>
                                <br>
                                <br>

                                <div class="error_messages">
                                <?php

                                if (isset ($_POST['edit_amount'])) {
                                    try {
                                        $database_handler = new PDO ($dns);
                                        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
                                    } catch (PDOException $e) {
                                        echo $e->getMessage();
                                        die();
                                    }
                                }

                                $gamesId = array();

                                $query = "
                                SELECT copies
                                FROM game_order
                                WHERE orderid = :id AND gameid = :game
                                ";
                                $statement = $database_handler->prepare($query);
                                $statement->bindParam(':id', $_GET['id']);
                                $statement->bindParam(':game', $_POST['edit_amount']);
                                $database_handler->beginTransaction();
                                $statement->execute();
                                $database_handler->commit();
                                $result = $statement->fetch(PDO::FETCH_ASSOC);

                                if ($result) {
                                    if ($_POST['new_amount']>$result['copies']) {
                                        $query = "
                                        UPDATE videogame
                                        SET amount = amount - :amount
                                        WHERE id = :id
                                        ";

```



```

        $statement = $database_handler->prepare($query);
        $statement->bindParam(':id',
$_POST['edit_amount']);
        $new_amount = intval($_POST['new_amount']) -
intval($result['copies']);
    }
    else {
        $query = "
        UPDATE videogame
        SET amount = amount + :amount
        WHERE id = :id
        ";
        $statement = $database_handler->prepare($query);
        $statement->bindParam(':id',
$_POST['edit_amount']);
        $new_amount = intval($result['copies']) -
intval($_POST['new_amount']) ;
    }

    try {
        $statement->bindParam(':amount', $new_amount);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();

        if (intval($_POST['new_amount']) > 0) {
            $query = "
            UPDATE game_order
            SET copies = :amount
            WHERE orderid = :id AND gameid = :game
            ";
            $statement = $database_handler-
>prepare($query);

            $statement->bindParam(':id', $_GET['id']);
            $statement->bindParam(':amount',
intval($_POST['new_amount']));
            $statement->bindParam(':game',
$_POST['edit_amount']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
        } else {
            $query = "
            DELETE FROM game_order
            WHERE orderid = :id AND gameid = :game
            ";
            $statement = $database_handler-
>prepare($query);

            $statement->bindParam(':id', $_GET['id']);
            $statement->bindParam(':game',
$_POST['edit_amount']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();

            $query = "
            SELECT FROM game_order
            WHERE orderid = :id;
            ";
            $statement = $database_handler-
>prepare($query);

```

```

        $statement->bindParam(':id', $_GET['id']);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->rowCount();
        if (!$result) {
            $query = "
                DELETE FROM order_table
                WHERE id = :id;
            ";
            $statement = $database_handler->
>prepare($query);
            $statement->bindParam(':id',
$_GET['id']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
        }
    }
    $database_handler = null;
    header('Refresh: 0');
}
catch (PDOException $e){
    echo "Quantità di prodotti Insufficiente per la
richiesta.";
}
}
}

elseif (isset($_POST['delete_order'])) {
    try {
        $database_handler = new PDO ($dns);
        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
    } catch (PDOException $e) {
        echo $e->getMessage();
        die();
    }

    $gamesId = array();

    $query = "
        SELECT gameid, copies
        FROM game_order
        WHERE orderid = :id
        GROUP BY gameid, copies
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $_POST['delete_order']);
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetchAll(PDO::FETCH_ASSOC);

    foreach ($result as $row) {
        $gamesId[$row['gameid']] = $row['copies'];
    }

    foreach ($gamesId as $game=>$amount) {
        $query = "
            UPDATE videogame
            SET amount = amount + :amount

```

```

        WHERE id = :id
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $game);
    $statement->bindParam(':amount', intval($amount));
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
}

$query = "
DELETE FROM order_table
WHERE id = :id
";
$statement = $database_handler->prepare($query);
$statement->bindParam(':id',
intval($_POST['delete_order']));
$database_handler->beginTransaction();
$statement->execute();
$database_handler->commit();
$database_handler = null;
header('admin_panel.php');
}

elseif (isset($_POST['delete_game'])) {
    try {
        $database_handler = new PDO ($dns);
        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
    } catch (PDOException $e) {
        echo $e->getMessage();
        die();
    }

    $gamesId = array();

    $query = "
        SELECT copies
        FROM game_order
        WHERE orderid = :id AND gameid = :game
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $_GET['id']);
    $statement->bindParam(':game', $_POST['delete_game']);
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetch(PDO::FETCH_ASSOC);

    if ($result) {
        $query = "
            UPDATE videogame
            SET amount = amount + :amount
            WHERE id = :id
        ";
        $statement = $database_handler->prepare($query);
        $statement->bindParam(':id', $_POST['delete_game']);
        $statement->bindParam(':amount',
intval($result['copies']));
        $database_handler->beginTransaction();
        $statement->execute();
    }
}

```

```

        $database_handler->commit();

        $query = "
            DELETE FROM game_order
            WHERE orderid = :id AND gameid = :game
        ";
        $statement = $database_handler->prepare($query);
        $statement->bindParam(':id', $_GET['id']);
        $statement->bindParam(':game',
$_POST['delete_game']);

        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $database_handler = null;
        header('Location: admin_panel.php');
    }
}
?>
</div>

</section>

</div>

</section>

<?php
include_once '..\templates\footer.php';
?>

</body>

</html>

```

## edit\_product.php

```
<?php
include_once "..\config\configurations.php";

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}

if (!isset($_GET['id']))
    header ('Location: admin_panel.php');
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">

            <br>
            <br>

            <div class = 'admin_layout' align="center">

                <section class = 'panel' align="center">

                    <?php include_once 'admin_buttons.php'; ?>

                    <br>
                    <br>

                    <?php

                    try {
                        $database_handler = new PDO ($dns);
                        $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
                    } catch (PDOException $e) {
                        echo $e->getMessage();
                        die();
                    }
                }
            }
        }
    }

```

```

    }

    $query = "
    SELECT *
    FROM videogame
    WHERE id = :id
    ";
    $statement = $database_handler->prepare($query);
    $statement->bindParam(':id', $_GET['id']);
    $database_handler->beginTransaction();
    $statement->execute();
    $database_handler->commit();
    $result = $statement->fetch(PDO::FETCH_ASSOC);
    $database_handler = null;
    if (!$result) {
        header('Location: admin_panel.php');
    }
    ?>

    <div class = 'panel_title' id = 'products_title'>

        MODIFICA PRODOTTO &nbsp; <?php echo $result['id']; ?>

    </div>

    <br>

    <script type="text/javascript">
        function show (num) {
            if (document.getElementById('content' + num).hidden
=== true) {
                document.getElementById('content' + num).hidden
= false;
                document.getElementById('show' + num).innerHTML
= '- Hide';
                document.getElementById('x' +
num).src="../../web/icons/hidden.png";
            }
            else {
                document.getElementById('content' + num).hidden
= true;
                document.getElementById('show' + num).innerHTML
= '- Show';
                document.getElementById('x' +
num).src="../../web/icons/shown.png";
            }
        }
    </script>

    <div class = 'edit_panel' id="edit_product_panel"
align="center">

        <form action = "<?php echo htmlentities
($_SERVER['PHP_SELF'] . '?id=' . $result['id']); ?>" method = "POST"
enctype="multipart/form-data">

            <div class="menu_header" id = 'menu1'
onclick="show(1)" style="position: relative">
                <b>
                    TITOLO (attuale = <?php echo
$result['title']; ?>)
                </b>

```

```

        <div style="position: absolute; right:6px; top:
5px; display: inline">
            <div id = 'show1' style="display: inline;
font-size: 80%">
                - Show
            </div>
            
            </div>
        </div>

        <div class= 'menu_content' id = 'content1' hidden>
            <label>
                Nuovo Titolo: <br> <br>
                <input id = 'title' maxlength="50"
type="text" name = "title" />
                <button type="submit" name="submit">
                    
                    Modifica
                </button>
            </label>
        </div>

        <div class="menu_header" id = 'menu2'
onclick="show(2)" style="position: relative">
            <b>
                CONSOLE (attuale = <?php echo
$result['console'];?>)
            </b>

            <div style="position: absolute; right:6px; top:
5px; display: inline">
                <div id = 'show2' style="display: inline;
font-size: 80%">
                    - Show
                </div>
                
                </div>
            </div>

            <div class= 'menu_content' id = 'content2' hidden>
                Nuova Console: <br> <br>
                <ul class='fieldset'>
                    <li>
                        <label>
                            <input type = 'radio' value = 'PS4'
name="console" />
                            
                            &nbsp; PS4
                        </label>
                    </li>
                    <li>
                        <label>
                            <input type = 'radio' value = 'Xbox
One' name="console" />

```

```

        
        &nbsp; Xbox One
        </label>
    </li>
    <li>
        <label>
            <input type='radio' value =
'Switch' name="console" />
            
            &nbsp; Switch
        </label>
    </li>
    <li>
        <label>
            <input type='radio' value = 'PC'
name="console" />
            
            &nbsp; PC
        </label>
    </li>
</ul>
<br>
<button type="submit" name="submit">
    
    Modifica
</button>
</div>

    <div class="menu_header" id = 'menu3'
onclick="show(3)" style="position: relative">
        <b>
            PREZZO (attuale = €<?php echo
$result['price'];?>)
        </b>

        <div style="position: absolute; right:6px; top:
5px; display: inline">
            <div id = 'show3' style="display: inline;
font-size: 80%">
                - Show
            </div>
            
        </div>
    </div>

    <div class= 'menu_content' id = 'content3' hidden>
        <label>
            Nuovo Prezzo: <br> <br>
            € &nbsp;
            <input id = 'price' type="number" name =
'price_round' min="0"/> .
            <input id = 'price' type="number" name =
'price_cents' min="0" max="99" value="0" style="display: inline">
            <button type="submit" name="submit">

```



```

        
        Modifica
    </button>
</label>
</div>

<div class="menu_header" id = 'menu4'
onclick="show(4)" style="position: relative">
    <b>
        DISPONIBILI (attuale = <?php echo
$result['amount'];?>)
    </b>

    <div style="position: absolute; right:6px; top:
5px; display: inline">
        <div id = 'show4' style="display: inline;
font-size: 80%">
            - Show
        </div>
        
    </div>
</div>

<div class= 'menu_content' id = 'content4' hidden>
    <label>
        Nuova Disponibilit : <br> <br>
        <input id = 'amount' name="amount"
type="number" min="0" value="<?php echo $result['amount']; ?>"/>
        <button type="submit" name="submit">
            
            Modifica
        </button>
    </label>
</div>

<div class="menu_header" id = 'menu5'
onclick="show(5)" style="position: relative">
    <b>
        COPERTINA
    </b>

    <div style="position: absolute; right:6px; top:
5px; display: inline">
        <div id = 'show5' style="display: inline;
font-size: 80%">
            - Show
        </div>
        
    </div>
</div>

<div class= 'menu_content' id = 'content5' hidden>

```

```

center">
        <table align="center" style="text-align:
center">
            <tr>
                <td>
                    Attuale:
                </td>
                <td>
                    Nuova Copertina:
                </td>
            </tr>
            <tr>
                <td>
                    <br>
                    "
                    >
                </td>
                <td>
                    <label>
                        <input type= "file" name
='file'>
                        <br>
                        <br>
                        <button type="submit"
name="submit">
                            
                            Modifica
                        </button>
                    </label>
                </td>
            </tr>
        </table>
    </div>

    <br>

    <div align="right">
        <button class="action_button" type="submit"
name="submit">
            
            Modifica Gioco
        </button>

        <input hidden name="id" value= '<?php echo
$result['id'];?>' />
        <button class="action_button" type="submit"
name="delete">
            
            Elimina Gioco
        </button>
    </div>
</form>

<br>
<br>

```

```

<div class="error_messages">
<?php

    if (isset($_POST['delete'])) {
        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }
        try {
            $query = "
                DELETE FROM videogame
                WHERE id = :id
            ";
            $statement = $database_handler->prepare($query);
            $statement->bindParam(':id', $_POST['id']);
            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
            $result = $statement->fetchAll(PDO::FETCH_OBJ);
            if ($result) {
                echo "eliminazione riuscita";
                header('Refresh:4; url = admin_panel.php');
            } else {
                echo 'eliminazione non riuscita';
            }
        }
        catch (PDOException $error) {
            echo "Sono presenti ordini con questo
videogioco, impossibile eliminare!";
        }
        $database_handler = null;
    }

    if (isset ($_POST['submit'])) {

        try {
            $database_handler = new PDO ($dns);
            $database_handler->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }

        $alright = true;
        $upload = false;
        $fileName = null;
        $fileTmp = null;
        $fileError = null;
        $fileSize = null;
        $fileExt = null;

        if (is_uploaded_file($_FILES['file']['tmp_name'])) {

            $file = $_FILES['file'];

```

```

$fileName = $_FILES['file']['name'];
$fileTmp = $_FILES['file']['tmp_name'];
$fileError = $_FILES['file']['error'];
$fileSize = $_FILES['file']['size'];

$fileExt = explode('.', $fileName);
$fileExt = strtolower(end($fileExt));

$allowed = 'jpg';

if ($fileExt == $allowed) {
    if ($fileError === 0) {
        if ($fileSize < 1000000) {
            $upload = true;
        } else {
            echo 'File troppo grande';
            $alright = false;
        }
    } else {
        echo "Errore nell'Upload";
        $alright = false;
    }
} else {
    echo 'Estensione non utilizzabile';
    $alright = false;
}

if ($alright) {

    if
(!empty($_POST['title']) || !empty($_POST['price_round']) || !empty($_POST['console'
]) || !empty($_POST['amount'])) {

        if (!empty($_POST['title'])) {
            $query = "
                UPDATE videogame
                SET title = :title
                WHERE id = :id
            ";
            $statement = $database_handler-
>prepare($query);
            $statement->bindParam(':id',
$_GET['id']);
            $statement->bindParam(':title',
$_POST['title']);

            $database_handler->beginTransaction();
            $statement->execute();
            $database_handler->commit();
        }

        if (!empty($_POST['price_round'])) {
            $query = "
                UPDATE videogame
                SET price = :price
                WHERE id = :id
            ";
            $statement = $database_handler-
>prepare($query);

            $price = intval($_POST['price_round']);
            $price_cents =
isset($_POST['price_cents'])? intval($_POST['price_cents']):0;
            $price += ($price_cents * 0.01);

```

```

$statement->bindParam(':id',
$_GET['id']);
$statement->bindParam(':price', $price);
$database_handler->beginTransaction();
$statement->execute();
$database_handler->commit();
}

if (!empty($_POST['console'])) {
    $query = "
        UPDATE videogame
        SET console = :console
        WHERE id = :id
    ";
    $statement = $database_handler->
>prepare($query);
$statement->bindParam(':id',
$_GET['id']);
$statement->bindParam(':console',
$_POST['console']);
$database_handler->beginTransaction();
$statement->execute();
$database_handler->commit();
}

if (isset($_POST['amount'])) {
    $query = "
        UPDATE videogame
        SET amount = :amount
        WHERE id = :id
    ";
    $statement = $database_handler->
>prepare($query);
$statement->bindParam(':id',
$_GET['id']);
$statement->bindParam(':amount',
intval($_POST['amount']));
$database_handler->beginTransaction();
$statement->execute();
$database_handler->commit();
}
}

else {
    if (!$upload)
        $alright = false;
}

$database_handler = null;
}

if ($upload) {
    $fileDestination =
"..\\web\\images\\".$_GET['id'].'.'.$fileExt;
    move_uploaded_file($fileTmp, $fileDestination);
}

if ($alright) {
    header('Location:
edit_product.php?id='.$_GET['id']);
}
else {

```

```

                                echo 'INSERIRE DATI';
                                }
                                }
                                ?>
                            </div>
                        </div>
                    </section>
                </div>

                <br>
                <br>
                <br>
                <br>
                <br>

            </section>

            <?php
            include_once '..\templates\footer.php';
            ?>

        </body>
    </html>

```

#### edit\_user.php

```

<?php
include_once "..\config\configurations.php";

if (!isset($_SESSION['user']) || (isset($_SESSION['user']) && $_SESSION['user']
!= 'admin')) {
    header ('Location: ..\utils\logout.php');
}

if (!isset($_GET['login']))
    header ('Location: admin_panel.php');
?>

<html>

    <body>

        <?php
        include_once '..\templates\header.php';
        ?>

        <section class= "main_content">

            <br>
            <br>

            <div class = 'admin_layout' align="center">

                <section class = 'panel' align="center">

                    <?php include_once 'admin_buttons.php'; ?>

                    <br>
                    <br>

```

```

<?php

try {
    $database_handler = new PDO ($dns);
    $database_handler->setAttribute(PDO::ATTR_ERRMODE,
PDO::ERRMODE_EXCEPTION);
} catch (PDOException $e) {
    echo $e->getMessage();
    die();
}

$query = "
SELECT *
FROM user_table
WHERE login = :login AND admin is false
";
$stmt = $database_handler->prepare($query);
$stmt->bindParam(':login', $_GET['login']);
$database_handler->beginTransaction();
$stmt->execute();
$database_handler->commit();
$result = $stmt->fetch(PDO::FETCH_ASSOC);
$database_handler = null;
if (!$result) {
    header('Location: admin_panel.php');
}

?>

<div class = 'panel_title' id = 'users_title'>

    MODIFICA UTENTE &nbsp; <?php echo $result['login']; ?>

</div>

<br>

<script type="text/javascript">
    function show (num) {
        if (document.getElementById('content' + num).hidden
=== true) {
            document.getElementById('content' + num).hidden
= false;
            document.getElementById('show' + num).innerHTML
= '- Hide';
            document.getElementById('x' +
num).src="../../web/icons/hidden.png";
        }
        else {
            document.getElementById('content' + num).hidden
= true;
            document.getElementById('show' + num).innerHTML
= '- Show';
            document.getElementById('x' +
num).src="../../web/icons/shown.png";
        }
    }
</script>

<div class = 'edit_panel' id="edit_user_panel"
align="center">

```

```

        <form action = "<?php echo htmlentities
($_SERVER['PHP_SELF'] . '?login=' . $result['login']); ?>" method = "POST">

            <div class="menu_header" id = 'menu1'
onclick="show(1)" style="position: relative">
                <b>
                    USERNAME (attuale = <?php echo
$result['login'];?>)
                </b>

                <div style="position: absolute; right:6px; top:
5px; display: inline">
                    <div id = 'show1' style="display: inline;
font-size: 80%">
                        - Show
                    </div>
                    
                    </div>
                </div>

                <div class= 'menu_content' id = 'content1' hidden>
                    <label>
                        Nuovo Username: <br> <br>
                        <input id = 'login' maxlength="20"
type="text" name = "login" />
                        <button type="submit" name="submit">
                            
                            Modifica
                        </button>
                    </label>
                </div>

            <div class="menu_header" id = 'menu2'
onclick="show(2)" style="position: relative">
                <b>
                    PASSWORD (attuale = <?php echo
$result['password'];?>)
                </b>

                <div style="position: absolute; right:6px; top:
5px; display: inline">
                    <div id = 'show2' style="display: inline;
font-size: 80%">
                        - Show
                    </div>
                    
                    </div>
                </div>

                <div class= 'menu_content' id = 'content2' hidden>
                    <label>
                        Nuova Password: <br> <br>
                        <input id = 'password' maxlength="20"
type="password" name = "password" />
                        <button type="submit" name="submit">
                            <img src="../../web/icons/edit.png" height=

```



```

'20' style="vertical-align: middle"/>
        Modifica
        </button>
    </label>
</div>

    <div class="menu_header" id = 'menu3'
onclick="show(3)" style="position: relative">
        <b>
            NOME (attuale = <?php echo
$result['name'];?>)
        </b>

        <div style="position: absolute; right:6px; top:
5px; display: inline">
            <div id = 'show3' style="display: inline;
font-size: 80%">
                - Show
            </div>
            
        </div>
    </div>
    <div class= 'menu_content' id ='content3' hidden>
        <label>
            Nuovo Nome: <br> <br>
            <input id = 'name' maxlength="20"
type="text" name = "name" />
            <button type="submit" name="submit">
                
                Modifica
            </button>
        </label>
    </div>

    <div class="menu_header" id = 'menu4'
onclick="show(4)" style="position: relative">
        <b>
            COGNOME (attuale = <?php echo
$result['surname'];?>)
        </b>

        <div style="position: absolute; right:6px; top:
5px; display: inline">
            <div id = 'show4' style="display: inline;
font-size: 80%">
                - Show
            </div>
            
        </div>
    </div>

    <div class= 'menu_content' id ='content4' hidden>
        <label>
            Nuovo Cognome: <br> <br>

```

```

                                <input id = 'surname'  maxlength="20"
type="text" name = "surname" />
                                <button type="submit" name="submit">
                                    
                                    Modifica
                                </button>
                                </label>
                            </div>
                        </div>

                                <div class="menu_header" id = 'menu5'
onclick="show(5)" style="position: relative">
                                    <b>
                                        INDIRIZZO (attuale = <?php echo
$result['adress'];?>)
                                    </b>

                                    <div style="position: absolute; right:6px; top:
5px; display: inline">
                                        <div id = 'show5' style="display: inline;
font-size: 80%">
                                            - Show
                                        </div>
                                        
                                        </div>
                                    </div>

                                    <div class= 'menu_content' id = 'content5' hidden>
                                        <label>
                                            Nuovo Indirizzo: <br> <br>
                                            <input id = 'adress' maxlength="100"
type="text" name = "adress" />
                                            <button type="submit" name="submit">
                                                
                                                Modifica
                                            </button>
                                        </label>
                                    </div>
                                </div>

                                <div class="menu_header" id = 'menu6'
onclick="show(6)" style="position: relative">
                                    <b>
                                        TELEFONO (attuale = <?php echo
$result['phone']==null?'N/D':$result['phone'];?>)
                                    </b>

                                    <div style="position: absolute; right:6px; top:
5px; display: inline">
                                        <div id = 'show6' style="display: inline;
font-size: 80%">
                                            - Show
                                        </div>
                                        

```

```

        </div>
    </div>

    <div class= 'menu_content' id = 'content6' hidden>
        <label>
            Nuovo Telefono: <br> <br>
            <input id = 'phone' maxlength="10"
type="tel" name = "phone" />
            <button type="submit" name="submit">
                
                Modifica
            </button>
        </label>
    </div>

    <br>

    <div align="right">
        <button class="action_button" type="submit"
name="submit">
            
            Modifica Utente
        </button>

        <button class="action_button" type="submit"
name="delete">
            
            Elimina Utente
        </button>
    </div>

</form>

<div class="error_messages">

<?php

    if (isset($_POST['delete'])) {
        try {
            $database_handler = new PDO ($dns);
            $database_handler-
>setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
        } catch (PDOException $e) {
            echo $e->getMessage();
            die();
        }
        $query = "
        DELETE FROM user_table
        WHERE login = :login
        ";
        $statement = $database_handler->prepare($query);
        $statement->bindParam(':login', $_GET['login']);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
        $result = $statement->fetchAll(PDO::FETCH_OBJ);
        $database_handler = null;
    }
}

```

```

        if ($result) {
            echo "eliminazione riuscita";
        }
        else {
            echo 'eliminazione non riuscita';
        }
        $database_handler = null;
        header('Refresh:4; url = admin_panel.php');
    }

    if (isset ($_POST['submit'])) {

        if (!empty($_POST['login']) ||
!empty($_POST['password']) || !empty($_POST['adress']) ||
!empty($_POST['phone']) || !empty($_POST['name'])
|| !empty($_POST['surname'])) {

            try {
                $database_handler = new PDO ($dns);
                $database_handler->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
            } catch (PDOException $e) {
                echo $e->getMessage();
                die();
            }

            $success = true;

            if (!empty($_POST['login'])) {
                try {
                    $query = "
                    UPDATE user_table
                    SET login = :newlogin
                    WHERE login = :login
                    ";
                    $statement = $database_handler->prepare($query);
                    $statement->bindParam(':login',
$_GET['login']);
                    $statement->bindParam(':newlogin',
$_POST['login']);
                    $database_handler->beginTransaction();
                    $statement->execute();
                    $database_handler->commit();
                    $_GET['login']=$_POST['login'];
                } catch (PDOException $error) {
                    $success = false;
                    echo 'Login non disponibile';
                }
            }

            if (!empty($_POST['password'])) {
                $query = "
                UPDATE user_table
                SET password = :password
                WHERE login = :login
                ";
                $statement = $database_handler->prepare($query);
                $statement->bindParam(':login',
$_GET['login']);
                $statement->bindParam(':password',

```

```

$_POST['password']);

                                $database_handler->beginTransaction();
                                $statement->execute();
                                $database_handler->commit();
                                }

                                if (!empty($_POST['name'])) {
                                    $query = "
                                        UPDATE user_table
                                        SET name = :name
                                        WHERE login = :login
                                        ";
                                    $statement = $database_handler-
>prepare($query);
                                    $statement->bindParam(':login',
$_GET['login']);
                                    $statement->bindParam(':name',
$_POST['name']);

                                    $database_handler->beginTransaction();
                                    $statement->execute();
                                    $database_handler->commit();
                                    }

                                if (!empty($_POST['surname'])) {
                                    $query = "
                                        UPDATE user_table
                                        SET surname = :surname
                                        WHERE login = :login
                                        ";
                                    $statement = $database_handler-
>prepare($query);
                                    $statement->bindParam(':login',
$_GET['login']);
                                    $statement->bindParam(':surname',
$_POST['surname']);

                                    $database_handler->beginTransaction();
                                    $statement->execute();
                                    $database_handler->commit();
                                    }

                                if (!empty($_POST['adress'])) {
                                    $query = "
                                        UPDATE user_table
                                        SET adress = :adress
                                        WHERE login = :login
                                        ";
                                    $statement = $database_handler-
>prepare($query);
                                    $statement->bindParam(':login',
$_GET['login']);
                                    $statement->bindParam(':adress',
$_POST['adress']);

                                    $database_handler->beginTransaction();
                                    $statement->execute();
                                    $database_handler->commit();
                                    }

                                if (!empty($_POST['phone'])) {
                                    $query = "
                                        UPDATE user_table
                                        SET phone = :phone
                                        WHERE login = :login

```

```

        ";
        $statement = $database_handler->prepare($query);
        $statement->bindParam(':login',
$_GET['login']);
        $statement->bindParam(':phone',
$_POST['phone']);
        $database_handler->beginTransaction();
        $statement->execute();
        $database_handler->commit();
    }

    $database_handler = null;

    if ($success) {
        header('Location:
edit_user.php?login='.$_GET['login']);
    }

    else {
        echo 'Inserire almeno un nuovo dato';
    }

?>
</div>

</div>

</section>

</div>

</section>

<?php
include_once '..\templates\footer.php';
?>

</body>
</html>

```

## style.css

```
/*
Main Header
*/

header.main_header {
  z-index: 99;
  height: 45px;
  font-family: "Trebuchet MS", serif;
  background-color: darkred;
  position: fixed;
  top: 0;
  width: 100%;
  display: flex;
}

div.text {
  display: block;
  text-align: right;
  margin: auto;
  width: calc(60% + 100px);
  color: white;
}

a.util_link {
  position: relative;
  padding-left: 10px;
```

```

    color: white;
    text-decoration: none;
    min-width: 500px;
    border-left: solid white 2px;
}

a#inactive_cart {
    position: relative;
    padding-left: 10px;
    color: white;
    text-decoration: none;
    min-width: 500px;
    border-left: solid white 2px;
}

a#inactive_cart img {
    -webkit-filter: invert(100%);
}

a.util_link:hover {
    color: darkgray;
    border-left: solid grey 2px;
}

a.util_link:active {
    color: black;
    border-left: solid black 2px;
}

a.util_link img {
    -webkit-filter: invert(100%);
}

a.util_link:hover img {
    -webkit-filter: invert(50%);
}

a.util_link:active img {
    -webkit-filter: invert(0%);
}

img#cart_balloon {
    position: absolute;
    right: -7px;
    top: -7px;
    -webkit-filter: invert(0%);
    height: 20px;
}

div#cart_items {
    max-width: 15px;
    position: absolute;
    top: -6px;
    border-radius: 18px;
    padding-left: 5px;
    padding-right: 5px;
    background-color: indianred;
    font-size: 12px;
    right: -6px;
}

```



```

/*
Second Header
*/

.second_header {
    padding: 5px 0 5px 0;
    margin: 45px auto 0 auto;
    width: calc(60% + 100px);
    background-color: white;
}

a.console_link {
    text-decoration: none;
    font-family: 'Trebuchet MS', serif;
}

table.console_table {
    border-left: 2px solid;
    display: inline-table;
}

table.console_table:hover{
    background-color: black;
    color: white;
}

table.console_table:hover img {
    -webkit-filter: invert(100%);
}

/*
GENERAL
*/

body {
    margin: 0;
    background: url("../images/backgrounds/Crash.jpg") no-repeat center center
fixed;
    background-size: cover;
}

div.container {
    margin-top: 100px;
    margin-left: 30%;
    font-family: "Trebuchet MS", serif;
    font-size: 20px;
}

input {
    width: 60%;
    min-width: 200px;
}

span.info {
    float: right;
    margin-right: 40%;
    font-family: sans-serif;
    font-weight: bold;
    font-size: 12px;
}

span.info > a {

```

```

    color: darkred;
}

div.error_messages {
    text-align: left;
    padding-top: 20px;
    font-weight: bold;
    color: darkred;
    font-family: sans-serif;
    font-size: 12px;
}

section.main_content {
    margin: 0 auto;
    min-height: 100%;
    width: calc(60% + 100px);
    background-color: white;
    overflow: auto;
}

button#top_button {
    display: none;
    position: fixed;
    font-family: "Trebuchet MS", serif;
    bottom: 20px;
    right: 30px;
    z-index: 99;
    border: none;
    background-color: darkred;
    color: white;
    padding: 15px;
    border-radius: 20px;
}

ul.fieldset {
    list-style: none;
    text-align: left;
}

ul.fieldset li {
    margin-left: calc( 52% - 100px );
}

input[type='radio'] {
    min-width: 20px;
    width: 50px;
    margin-left: auto;
}

input[type='number'] {
    width: 40px;
    min-width: 40px;
}

/*
    VIDEOGAMES
*/

button.cart_add_button {
    padding: 10px;
    background-color: white;

```

```

    color: red;
    border: 3px red solid;
    box-shadow: 0 0 0 1px inset white;
}

button.cart_add_button:hover {
    background-color: red;
    color: white;
    box-shadow: 0 0 0 1px inset grey;
}

table.games_table {
    border: dashed 1px;
    font-family: "Trebuchet MS", serif;
    width: 80%;
}

table.games_table td {
    padding-top: 20px;
    padding-bottom: 20px;
}

table.games_table caption {
    padding-top: 20px;
    padding-bottom: 20px;
    font-size: 120%;
    color: white;
}

caption#ps_caption {
    background-color: #003791;
}

caption#xbox_caption {
    background-color: #52b043;
}

caption#nintendo_caption {
    background-color: #e60012;
}

caption#pc_caption {
    background-color: #000000;
}

/*
ADMIN PANEL
*/

div.admin_layout {
    padding-top: 90px;
}

section.panel {
    width: calc(60% + 100px);
}

div.panel_title {
    font-family: "Trebuchet MS", serif;
    color: white;
    font-weight: bold;
}

```

```

    font-size: 150%;
    padding-top: 20px;
    padding-bottom: 20px;
}

div.panel_title#users_title {
    background-color: darkred;
}

div.panel_title#orders_title {
    background-color: #0283a0;
}

div.panel_title#admins_title {
    background-color: forestgreen;
}

div.panel_title#products_title {
    background-color: rebeccapurple;
}

table.box {
    border-collapse: collapse;
}

table.box td {
    text-align: center;
}

table.box th {
    color: white;
}

table.box#users_table th {
    background-color: darkred;
}

table.box#orders_table th {
    background-color: #0283a0;
}

table.box#admins_table th {
    background-color: forestgreen;
}

table.box#products_table th {
    background-color: rebeccapurple;
}

table.box#users_table tr:nth-child(even) {
    background-color: indianred;
}

table.box#orders_table tr:nth-child(even) {
    background-color: cadetblue;
}

table.box#admins_table tr:nth-child(even) {
    background-color: limegreen;
}

table.box#products_table tr:nth-child(even) {

```

```

    background-color: mediumpurple;
}

button.action_button {
    border: none;
    background: none;
}

button.panel_button {
    font-family: "Trebuchet MS", serif;
    font-size: 80%;
    padding: 10px;
    border: none;
    color: white;
}

button.panel_button img {
    height: 25px;
    -webkit-filter: invert(100%);
}

button.panel_button:disabled {
    color: black;
    font-weight: bold;
    font-size: 90%;
    box-shadow: inset -5px -3px rgba(0, 0, 0, 0.1);
}

button.panel_button:disabled img {
    height: 30px;
    -webkit-filter: invert(0%);
}

button#users_button {
    background-color: indianred;
}

button#users_button:disabled {
    background-color: firebrick;
}

button#admins_button {
    background-color: limegreen;
}

button#admins_button:disabled {
    background-color: forestgreen;
}

button#orders_button {
    background-color: cadetblue;
}

button#orders_button:disabled {
    background-color: #0283a0;
}

button#products_button {
    background-color: mediumpurple;
}

button#products_button:disabled {

```

```

    background-color: rebeccapurple;
}

div.edit_panel div.menu_header {
    font-family: "Trebuchet MS", serif;
    border-bottom: dashed 1px;
    color: white;
    padding-top: 10px;
    padding-bottom: 10px;
}

div.edit_panel#edit_user_panel div.menu_header {
    background-color: darkred;
}

div.edit_panel#edit_product_panel div.menu_header {
    background-color: rebeccapurple;
}

div.edit_panel#edit_admin_panel div.menu_header {
    background-color: forestgreen;
}

div.edit_panel div.menu_content {
    padding-top: 30px;
    padding-bottom: 30px;
}

div.edit_panel#edit_user_panel div.menu_content {
    background-color: indianred;
}

div.edit_panel#edit_product_panel div.menu_content {
    background-color: mediumpurple;
}

/*
    FOOTER
*/

footer {
    font-family: "Trebuchet MS", serif;
    padding: 15px 0 15px 0;
    background-color: black;
    color: white;
    margin-bottom: 0;
    margin-top: 0;
    width: 100%;
}

```