Drill Bit Sizes

Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)	Fract (in)	. Decimal	Wire No. /Letter	Metric (mm)		Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)
	0.0098		0.25		0.1065	36				0.3480	S	
	0.0118		0.30	7/64	0.1094					0.3543		9.00
	0.0135	80			0.1100	35				0.3580	Т	
	0.0138		0.35		0.1102		2.80	2	23/64	0.3594		
	0.0145	79			0.1110	34				0.3680	U	
1/64	0.0156				0.1130	33				0.3740		9.50
	0.0157		0.40		0.1142		2.90		3/8	0.3750		
	0.0160	78			0.1160	32				0.3770	V	
	0.0177		0.45		0.1181		3.00			0.3860	W	
	0.0180	77			0.1200	31		2	25/64	0.3906		
	0.0197		0.50	1/8	0.1250					0.3937		10.00
	0.0200	76			0.1285	30				0.3970	X	
	0.0210	75			0.1360	29				0.4040	Y	
	0.0217		0.55		0.1378		3.50		13/32	0.4063		
	0.0225	74			0.1405	28				0.4130	Z	
	0.0236		0.60	9/64	0.1406					0.4134		10.50
	0.0240	73			0.1440	27		2	27/64	0.4219		
	0.0250	72			0.1470	26				0.4331		11.00
	0.0256		0.65		0.1495	25			7/16	0.4375		
	0.0260	71			0.1520	24				0.4528		11.50
	0.0276		0.70		0.1540	23		2	29/64	0.4531		
	0.0280	70		5/32	0.1563				15/32	0.4688		
	0.0292	69			0.1570	22				0.4724		12.00
	0.0295		0.75		0.1575		4.00	(31/64	0.4844		
	0.0310	68			0.1590	21				0.4921		12.50
1/32	0.0313				0.1610	20			1/2	0.5000		
	0.0315		0.80		0.1660	19				0.5118		13.00
	0.0320	67			0.1695	18		;	33/64	0.5156		
	0.0330	66		11/64	0.1719				17/32	0.5313		
	0.0335		0.85		0.1730	17				0.5315		13.50
	0.0350	65			0.1770	16		;	35/64	0.5469		
	0.0354		0.90		0.1772		4.50			0.5512		14.00
	0.0360	64			0.1800	15			9/16	0.5625		
	0.0370	63			0.1820	14				0.5709		14.50
	0.0374		0.95		0.1850	13		;	37/64	0.5781		
	0.0380	62		3/16	0.1875					0.5905		15.00
	0.0390	61			0.1890	12			19/32	0.5938		
	0.0394		1.00		0.1910	11		(39/64	0.6094		
	0.0400	60			0.1935	10				0.6102		15.50
	0.0410	59			0.1960	9			5/8	0.6250		
	0.0420	58			0.1968		5.00			0.6299		16.00
	0.0430	57			0.1990	8			41/64	0.6406		

Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)		Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)	Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)
	0.0433		1.10			0.2010	7			0.6496		16.50
	0.0465	56			13/64	0.2031			21/32	0.6563		
3/64	0.0469			L		0.2040	6			0.6693		17.00
	0.0472		1.20			0.2055	5		43/64	0.6719		
	0.0512		1.30	L		0.2090	4		11/16	0.6875		
	0.0520	55				0.2130	3			0.6890		17.50
	0.0550	54				0.2165		5.50	45/64	0.7031		
	0.0551		1.40		7/32	0.2188				0.7087		18.00
	0.0591		1.50	L		0.2210	2		23/32	0.7188		
	0.0595	53				0.2280	1			0.7283		18.50
1/16	0.0625			L		0.2340	Α		47/64	0.7344		
	0.0630		1.60		15/64	0.2344				0.7480		19.00
	0.0635	52				0.2362		6.00	3/4	0.7500		
	0.0669		1.70			0.2380	В		49/64	0.7656		
	0.0670	51				0.2420	С			0.7677		19.50
	0.0700	50				0.2460	D		25/32	0.7813		
	0.0709		1.80		1/4	0.2500	E			0.7874		20.00
	0.0730	49				0.2559		6.50	51/64	0.7969		
	0.0748		1.90			0.2570	F			0.8071		20.50
	0.0760	48				0.2610	G		13/16	0.8125		
5/64	0.0781				17/64	0.2656				0.8268		21.00
	0.0785	47				0.2660	Н		53/64	0.8281		
	0.0787		2.00			0.2720	I		27/32	0.8438		
	0.0810	46				0.2756		7.00		0.8465		21.50
	0.0820	45				0.2770	J		55/64	0.8594		
	0.0827		2.10			0.2810	K			0.8661		22.00
	0.0860	44			9/32	0.2813			7/8	0.8750		
	0.0866		2.20			0.2900	L			0.8858		22.50
	0.0890	43				0.2950	М		57/64	0.8906		
	0.0906		2.30			0.2953		7.50		0.9055		23.00
	0.0935	42			19/64	0.2969			29/32	0.9063		
3/32	0.0938					0.3020	N		59/64	0.9219		
	0.0945		2.40		5/16	0.3125				0.9252		23.50
	0.0960	41				0.3150		8.00	15/16	0.9375		
	0.0980	40				0.3160	0			0.9449		24.00
	0.0984		2.50			0.3230	Р		61/64	0.9531		
	0.0995	39			21/64	0.3281				0.9646		24.50
	0.1015	38				0.3320	Q		31/32	0.9688		
	0.1024		2.60			0.3346		8.50		0.9842		25.00
	0.1040	37				0.3390	R		63/64	0.9844		
	0.1063		2.70		11/32	0.3438			1	1.0000		
Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)		Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)	Fract. (in)	Decimal	Wire No. /Letter	Metric (mm)