

10.5.6 Lab: Configure Network Security Appliance Access

Candidate: Richard Habib ()

Time Spent: 00:14

Score: 0%

Task Summary

Required Actions

- ✗ Change the password for the admin account to **P@ssw0rd**
- ✗ Create and configure a new pfSense user [Show Details](#)
- ✗ Set a 20-minute session timeout for pfSense
- ✗ Enable anti-lockout for HTTP

Explanation

Complete this lab as follows:

1. Access the pfSense management console.
 - a. From the taskbar, select **Google Chrome**.
 - b. Maximize the window for better viewing.
 - c. In the Google Chrome address bar, enter **198.28.56.22** and then press **Enter**.
 - d. Enter the pfSense sign-in information as follows:
 - Username: **admin**
 - Password: **pfsense**
 - e. Select **SIGN IN**.
2. Change the password for the default (admin) account.
 - a. From the pfSense menu bar, select **System > User Manager**.
 - b. For the admin account, under Actions, select the *Edit user* icon (*pencil*).
 - c. For Password, change to **P@ssw0rd** (0 = zero).
 - d. Enter **P@ssw0rd** in the Confirm Password field.
 - e. Scroll to the bottom and select **Save**.
3. Create and configure a new pfSense user.
 - a. Select **Add**.
 - b. Enter **lyoung** as the username.
 - c. Enter **C@nyouGuessIt** in the Password field.
 - d. Enter **C@nyouGuessIt** in the Confirm Password field.
 - e. Enter **Liam Young** in Full Name field.

- f. For Group membership, select **admins** and then select **Move to "Member of" list**.
 - g. Scroll to the bottom and select **Save**.
- 4. Set a session timeout for pfSense.
 - a. Under the *System* breadcrumb, select **Settings**.
 - b. For Session timeout, enter **20**.
 - c. Select **Save**.
- 5. Disable the webConfigurator anti-lockout rule for HTTP.
 - a. From the pfSense menu bar, select **System > Advanced**.
 - b. Under webConfigurator, for Protocol, select **HTTP**.
 - c. Scroll down and select **Anti-lockout** to disable the webConfigurator anti-lockout rule.
 - d. Scroll to the bottom and select **Save**.